

infra

- OpenAPI, on page 1
- Info, on page 1
- Servers, on page 1
- tags, on page 1
- Paths, on page 2
- Components, on page 4030

OpenAPI

OpenAPI Version: 3.0.1

Info

```
Title: tailf-mobile-infra
Description:
Version: 2026-05-19
```

Servers

```
- URL: /restconf
```

tags

```
- Name: root
  Description: root resources
- Name: operations
  Description: operations resources
- Name: data
  Description: data resources
```

```
- Name: get
  Description: get resources
- Name: head
  Description: head resources
- Name: post
  Description: post resources
- Name: patch
  Description: patch resources
- Name: put
  Description: put resources
- Name: options
  Description: options resources
- Name: delete
  Description: delete resources
```

Paths

/

```
get:

  Tags:
  - root
  - get
  Operation ID: root_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/root"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - root
  - head
  Operation ID: root_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/operations

```
get:

  Tags:
  - operations
  - get
  Operation ID: operations_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/operations"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
```

/yang-library-version

```
get:

  Tags:
  - yang-library-version
  - get
  Operation ID: yang_library_version_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/yang-library-version"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - yang-library-version
  - head
  Operation ID: yang_library_version_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data


```
get:

  Tags:
  - data
  - get
  Operation ID: data_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-post"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: data
head:

  Tags:
  - data
  - head
  Operation ID: data_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/tailf-mobile-infra:sessions

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_sessions"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_sessions_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_sessions"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container sessions created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_sessions_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_sessions-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container sessions created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_sessions_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_sessions_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_sessions_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_sessions_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_sessions"
    Required/Optional: true

  Responses:
    "204":
      Description: container sessions updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
```

/data/tailf-mobile-infra:sessions/commit-pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_commit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_sessions_commit_pending_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_get


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_head


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_podInstance_get
```

```
Parameters:
- Name: commit-pending-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: commit-pending-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_podInstance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_podInstance_head

Parameters:
- **Name**: commit-pending-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: commit-pending-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_grInstance_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: commit-pending-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_grInstance_head
```

```
Parameters:
- Name: commit-pending-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: commit-pending-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_count_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_count_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: commit-pending-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_pendingCommit_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_pendingCommit"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_pendingCommit_head


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_dbBinarySize_get


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_dbBinarySize"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_dbBinarySize_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
    - report-all
    - trim
    - explicit
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-podInstance},{c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_lastDbSyncTime_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_lastDbSyncTime"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_lastDbSyncTime_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_affinity_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_sessions_affinity"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_sessions_affinity_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_get

  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_head

  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}/podInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_podInstance_get

  Parameters:
  - Name: affinity-podInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_podInstance_head

    Parameters:
    - Name: affinity-podInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}/count

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_count_get


  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_count_head


  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_peers_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_peers"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_peers_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_peers"
    Required/Optional: true

  Responses:
    "201":
      Description: container peers created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_peers_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_peers-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container peers created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_peers_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_peers_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_peers_patch
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_peers"
    Required/Optional: true

  Responses:
    "204":
      Description: container peers updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
```

/data/tailf-mobile-infra:peers/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_peers_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_peers_all"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_get


  Parameters:
  - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_grInstance_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_grInstance_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_endpoint_get


    Parameters:
    - Name: all-grInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_endpoint"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_endpoint_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_localAddress_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-peerAddress
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_localAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_localAddress_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_peerAddress_get


    Parameters:
    - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_peerAddress"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_peerAddress_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_direction_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_direction"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_direction_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_podInstance_get


    Parameters:
    - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_podInstance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_podInstance_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_type_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_type_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_connectedTime_get


    Parameters:
    - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_connectedTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_connectedTime_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_rpc_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_rpc"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_rpc_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_additionalDetails_get


    Parameters:
    - Name: all-grInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_additionalDetails"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_additionalDetails_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_interfaceName_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_interfaceName"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_interfaceName_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{a

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_vrf_get


    Parameters:
    - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_vrf_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_peers_ipv4_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_peers_ipv4"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_ipv4_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_head

  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_grInstance_get

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_grInstance"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_grInstance_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_endpoint_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_endpoint_head

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_localAddress_get

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_localAddress"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_localAddress_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_peerAddress_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_peerAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_peerAddress_head

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
get:
```

```
  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_direction_get

  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_direction"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_direction_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_podInstance_get

  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_podInstance_head

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_type_get

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_type"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_type_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_connectedTime_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_connectedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_connectedTime_head

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
  get:
```

```
  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_rpc_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_rpc"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_rpc_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: ipv4-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_additionalDetails_get

  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_additionalDetails"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_additionalDetails_head

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAd

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_interfaceName_get

Parameters:
- **Name**: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_interfaceName"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_interfaceName_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_vrf_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-localAddress
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
Operation ID:
data_tailf_mobile_infra_peers_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_localAddress_ipv4_peerAddress_vrf_head

Parameters:
- Name: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_peers_ipv6_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_peers_ipv6"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_ipv6_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_grInstance_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_grInstance_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
    Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_endpoint_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_endpoint_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_localAddress_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_localAddress"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_localAddress_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_peerAddress_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_peerAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_peerAddress_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_direction_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_direction"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_direction_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
    Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_podInstance_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_podInstance_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_type_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_type_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_connectedTime_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_connectedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_connectedTime_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_rpc_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_rpc"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_rpc_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
    Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_additionalDetails_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_additionalDetails"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_additionalDetails_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAd

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_interfaceName_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_interfaceName"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_interfaceName_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-localAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_vrf_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_localAddress_ipv6_peerAddress_vrf_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_rpc_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_rpc"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_rpc_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_rpc"
    Required/Optional: true

  Responses:
    "201":
      Description: container rpc created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rpc
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_rpc_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_rpc-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container rpc created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rpc
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_rpc_delete

  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_rpc_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_rpc_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_rpc"
      Required/Optional: true

    Responses:
      "204":
        Description: container rpc updated
        Content: {}
      "400":
        Description: Bad Request
```

```
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: rpc
```

/data/tailf-mobile-infra:rpc/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_rpc_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_rpc_all"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_head

    Parameters:
    - Name: all-podInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/p

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_podInstance_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_podInstance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_podInstance_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/n

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

```
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_name_get

  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_name_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/rem

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteAddress_get


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteAddress"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteAddress_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/rem

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteHost_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteHost"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteHost_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/typ

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_type_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_type_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/set

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_setName_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_setName"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_setName_head

    Parameters:
    - Name: all-podInstance
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/sta

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_status_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_status"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_status_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/con

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_connectedTime_get
```

```
Parameters:
- Name: all-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_connectedTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_connectedTime_head


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/d

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_disconnectedTime_get


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_disconnectedTime"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_disconnectedTime_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/m

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_monitorRPCHost_get


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_monitorRPCHost"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_monitorRPCHost_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/p

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_processingInstanceInfo_get


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_processingInstanceInfo"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_processingInstanceInfo_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/v

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_version_get

  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_version"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_version_head
```

```
Parameters:
- Name: all-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all-remoteAddress}/v

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_vrf_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_vrf_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_tailf_mobile_infra_rpc_ipv4_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_rpc_ipv4"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_ipv4_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_get

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_head

  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_podInstance_get


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_podInstance_head


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_name_get

  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_name_head

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_remoteAddress_get


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_remoteAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_remoteAddress_head
```

```
Parameters:
- Name: ipv4-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_remoteHost_get


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_remoteHost"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_remoteHost_head


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_type_get

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_type"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_type_head

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_setName_get

  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_setName"

    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_setName_head


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_status_get

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_status"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_status_head

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_connectedTime_get


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_connectedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_connectedTime_head


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_disconnectedTime_get


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_disconnectedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_disconnectedTime_head

Parameters:
- **Name**: ipv4-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_monitorRPCHost_get


  Parameters:
```

```
- Name: ipv4-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_monitorRPCHost"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_monitorRPCHost_head


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_processingInstanceInfo_get


  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_processingInstanceInfo"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_processingInstanceInfo_head

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_version_get

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_version"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_version_head


    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-remoteAddress
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv4={ipv4-podInstance},{ipv4-name},{ipv4-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_vrf_get

  Parameters:
  - Name: ipv4-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv4_ipv4_podInstance_ipv4_name_ipv4_remoteAddress_vrf_head

    Parameters:
    - Name: ipv4-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_rpc_ipv6_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_rpc_ipv6"
  "204":
    Description: No Content
    Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_ipv6_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_get

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6_podInstance_ipv6-name_ipv6-remoteAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_head

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

```
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_podInstance_get

  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_podInstance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_podInstance_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_name_get

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_name"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_name_head

  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_remoteAddress_get


  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_remoteAddress"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_remoteAddress_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_remoteHost_get


  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_remoteHost"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_remoteHost_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_type_get

  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_type"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_type_head
```

```
Parameters:
- Name: ipv6-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_setName_get

  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_setName"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_setName_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
get:

  Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_status_get

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_status"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_status_head

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_connectedTime_get


  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_connectedTime"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_connectedTime_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_disconnectedTime_get


  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_disconnectedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_disconnectedTime_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_monitorRPCHost_get


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_monitorRPCHost"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_monitorRPCHost_head


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_processingInstanceInfo_get


    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_processingInstanceInfo"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_processingInstanceInfo_head

Parameters:
- **Name**: ipv6-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_version_get
```

```
Parameters:
- Name: ipv6-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_version"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_version_head


  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/ipv6={ipv6-podInstance},{ipv6-name},{ipv6-remoteAddr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_vrf_get

    Parameters:
    - Name: ipv6-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_ipv6_ipv6_podInstance_ipv6_name_ipv6_remoteAddress_vrf_head

  Parameters:
  - Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:resources

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_resources"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
```

```
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resources_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resources"
    Required/Optional: true

  Responses:
    "201":
      Description: container resources created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_resources_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resources-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container resources created
      Content: {}
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resources_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resources_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resources_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resources"
    Required/Optional: true

  Responses:
    "204":
      Description: container resources updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
```

/data/tailf-mobile-infra:resources/info

```
get:

  Tags:
```

```
- data
- get
Operation ID: data_tailf_mobile_infra_resources_info_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_resources_info"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/podInstance

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_podInstance_get


  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_podInstance"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_podInstance_head


    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/cpuUsage

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_cpuUsage_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_cpuUsage"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_cpuUsage_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/totalNodeMemoryInMB

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_totalNodeMemoryInMB_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_totalNodeMemoryInMB"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_totalNodeMemoryInMB_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/usedPodMemoryInMB

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_usedPodMemoryInMB_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_usedPodMemoryInMB"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_usedPodMemoryInMB_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/diskUsageInKbps

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_diskUsageInKbps_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_diskUsageInKbps"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_diskUsageInKbps_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/goRoutinesCount

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_goRoutinesCount_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_goRoutinesCount"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_goRoutinesCount_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/gcCount

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcCount_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_gcCount"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcCount_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/gcPauseInNS

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcPauseInNS_get


  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_gcPauseInNS"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcPauseInNS_head


  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/loadFactor

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_loadFactor_get


    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_loadFactor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_loadFactor_head


    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_running_status_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_running-status"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_running_status_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_running-status"
    Required/Optional: true

  Responses:
    "201":
      Description: container running-status created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: running-status
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_running_status_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_running-status-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container running-status created
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: running-status
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_running_status_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_running_status_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_running_status_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_running_status_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_running-status"
    Required/Optional: true

  Responses:
    "204":
      Description: container running-status updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: running-status
```

/data/tailf-mobile-infra:running-status/info

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_running_status_info_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_running-status_info"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_running_status_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_running_status_info_info_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_running_status_info_info_podInstance_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/podInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_podInstance_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/runningStatus

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_runningStatus_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_runningStatus"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_runningStatus_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/systemHealth

```
    get:

      Tags:
      - data
      - get
      Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_systemHealth_get

      Parameters:
      - Name: info-podInstance
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_systemHealth"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_systemHealth_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/startTime

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_startTime_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_startTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_startTime_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_diagnostics_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_diagnostics_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics"
    Required/Optional: true

  Responses:
    "201":
      Description: container diagnostics created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: diagnostics
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_diagnostics_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container diagnostics created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: diagnostics
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_diagnostics_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_diagnostics_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_diagnostics_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_diagnostics_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics"
    Required/Optional: true
```

```
Responses:
  "204":
    Description: container diagnostics updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: diagnostics
```

/data/tailf-mobile-infra:diagnostics/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_diagnostics_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics_info"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_diagnostics_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/podIns

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_podInstance_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_podInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_podInstance_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/diagno

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_diagnostic_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_diagnostic"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_diagnostic_head

      Parameters:
      - Name: info-podInstance
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: info-diagnostic
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: content
        In: query
        Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/compo

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_component_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_component"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_component_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/startTi

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_startTime_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_startTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_startTime_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/statu

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

```
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_status_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_status"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_status_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}/retri

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_retries_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_retries"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_retries_head

    Parameters:
```

```
- Name: info-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra"
  "204":
    Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra"
    Required/Optional: true

  Responses:
    "201":
      Description: container infra created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: infra
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container infra created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: infra
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra"
    Required/Optional: true

  Responses:
    "204":
      Description: container infra updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: infra
```

/data/tailf-mobile-infra:infra/metrics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_metrics_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics"
    Required/Optional: true

  Responses:
    "201":
      Description: container metrics created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_metrics_post
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container metrics created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_metrics_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_options

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_metrics_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics"
    Required/Optional: true

  Responses:
    "204":
      Description: container metrics updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
```

/data/tailf-mobile-infra:infra/metrics/experimental

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental"
      Required/Optional: true

    Responses:
      "201":
        Description: container experimental created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: experimental
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container experimental created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: experimental
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental"
        Required/Optional: true

      Responses:
        "204":
          Description: container experimental updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: experimental
```

/data/tailf-mobile-infra:infra/metrics/experimental/version

```
    get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf version created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: version
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf version updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: version
```

/data/tailf-mobile-infra:infra/metrics/verbose

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose"

      Required/Optional: true

    Responses:
      "201":
        Description: container verbose created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: verbose
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container verbose created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose"

    Required/Optional: true

  Responses:
    "204":
      Description: container verbose updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_options

  Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_put

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType"

      Required/Optional: true

    Responses:
      "201":
        Description: list verboseLevels created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: verboseLevels
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_delete

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_options

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_head

    Parameters:
```

```
- Name: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
  data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_patch

      Parameters:
      - Name: verboseLevels-podType
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: enumeration
          Default: protocol
          enum:
          - protocol
          - load-balancer
          - service
          - application
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
  "#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType"

        Required/Optional: true
```

```
  Responses:
    "204":
      Description: list verboseLevels updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verboseLevels
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
```

```
      - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf podType created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: podType
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf podType updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podType
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_put

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods"

      Required/Optional: true

    Responses:
      "201":
        Description: container pods created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pods
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_post


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
```

```
      - service
      - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container pods created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pods
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_head


  Parameters:
  - Name: verboseLevels-podType
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: container pods updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: pods
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_get


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name"

  "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_put


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
```

```
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list pod-names created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-names
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: list pod-names updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: pod-names
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_get


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf pod-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-name
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_delete

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_options

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_patch


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf pod-name updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-name
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_get


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_delete

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_options

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
```

```
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_head


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf level updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf level created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
```

```
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
```

```
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_get


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics"
```

```
      Required/Optional: true

    Responses:
      "201":
        Description: container metrics created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_post


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container metrics created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
```

```
        - application

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics"

      Required/Optional: true

    Responses:
      "204":
        Description: container metrics updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_get

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_put


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name"

      Required/Optional: true

    Responses:
      "201":
        Description: list metricsList created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metricsList
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_delete

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_options

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list metricsList updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metricsList
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
```

```
        enum:
        - protocol
        - load-balancer
        - service
        - application
      - Name: metricsList-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name"

        Required/Optional: true

      Responses:
        "201":
          Description: leaf name created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: name
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_delete
```

```
    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
```

```
      - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_patch


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podT

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podTyp

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_get

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: granular-labels-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf-list granular-labels created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: granular-labels
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_head


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_patch

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf-list granular-labels updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: granular-labels
```

/data/tailf-mobile-infra:infra/transaction

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction"
    Required/Optional: true

  Responses:
    "201":
      Description: container transaction created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_transaction_post
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container transaction created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_options

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_transaction_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction"
    Required/Optional: true

  Responses:
    "204":
      Description: container transaction updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:infra/transaction/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit"
      Required/Optional: true

    Responses:
      "201":
        Description: container limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container limit created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_infra_transaction_limit_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit"
        Required/Optional: true

      Responses:
        "204":
          Description: container limit updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:infra/transaction/limit/stage

```
    get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf stage created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stage
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf stage updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: stage
```

/data/tailf-mobile-infra:infra/transaction/limit/consecutive

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive"
     Required/Optional: true

   Responses:
     "201":
       Description: container consecutive created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: consecutive
 Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive-post"
     Required/Optional: true

   Responses:
     "201":
       Description: container consecutive created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive"
       Required/Optional: true

    Responses:
      "204":
        Description: container consecutive updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
```


/data/tailf-mobile-infra:infra/transaction/limit/consecutive/same


```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same"
      Required/Optional: true

    Responses:
      "201":
        Description: container same created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: same
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container same created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: same
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
   Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same"
      Required/Optional: true

    Responses:
      "204":
        Description: container same updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: same
```

/data/tailf-mobile-infra:infra/transaction/limit/consecutive/same/stage

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf stage created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stage
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf stage updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: stage
```


/data/tailf-mobile-infra:infra/transaction/loop


```
  get:

    Tags:
    - data
```

```
- get
Operation ID: data_tailf_mobile_infra_infra_transaction_loop_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop"

      Required/Optional: true

    Responses:
      "201":
        Description: container loop created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container loop created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop"

    Required/Optional: true

  Responses:
    "204":
      Description: container loop updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
```

/data/tailf-mobile-infra:infra/transaction/loop/detection

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf detection created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: detection
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf detection updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: detection
```

/data/tailf-mobile-infra:infra/transaction/loop/category

```
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_options

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_category_name_get


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_category_name_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: list category created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: category
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_head

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_patch
```

```
    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list category updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: category
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_get

    Parameters:
```

```
- Name: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_put

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_head

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_patch

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshol

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_get

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_put

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold"

      Required/Optional: true

    Responses:
      "201":
        Description: container threshold created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: threshold
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_post

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container threshold created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_head
```

```
Parameters:
- Name: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_patch

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold"

      Required/Optional: true

    Responses:
      "204":
        Description: container threshold updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshold/i

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_get


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_put


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf interval created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_delete


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_options


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_head


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshold/t

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshol

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_get


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
```

```
      - high
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list thresholds created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholds
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_delete


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_options


    Parameters:
    - Name: category-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_head


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
```

```
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name"

      Required/Optional: true

    Responses:
      "204":
```

```
      Description: list thresholds updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: thresholds
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshol

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_get

  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
```

```
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_delete
```

```
    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_head


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshol

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_get

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_delete


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_options


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_head

Parameters:
- Name: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/threshold/t

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_get


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_put


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf action created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: action
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_delete


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_head


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
```

```
      - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf action updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: action
```


/data/tailf-mobile-infra:infra/k8-validation


```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_infra_k8_validation_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_k8-validation"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_k8_validation_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_infra_k8-validation"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf k8-validation created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8-validation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_k8_validation_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_k8_validation_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_k8_validation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_k8_validation_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_infra_k8-validation"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf k8-validation updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8-validation
```

/data/tailf-mobile-infra:client

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client"
    Required/Optional: true

  Responses:
    "201":
      Description: container client created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: client
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container client created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: client
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_client_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: container client updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: client
```

/data/tailf-mobile-infra:client/http

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_http"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_http_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http"
    Required/Optional: true

  Responses:
    "201":
      Description: container http created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: http
Method: Post:
```

```
  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_http_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container http created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: http
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_http_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http"
    Required/Optional: true

  Responses:
    "204":
      Description: container http updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: http
```

/data/tailf-mobile-infra:client/http/header

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_header_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_header"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_header_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_header"

      Required/Optional: true

    Responses:
      "201":
        Description: container header created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: header
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_http_header_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container header created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: header
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_header_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_header_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_header_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_header_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_header"

      Required/Optional: true

    Responses:
      "204":
        Description: container header updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: header
```

/data/tailf-mobile-infra:client/http/header/user-agent

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent"
       Required/Optional: true

    Responses:
      "201":
        Description: leaf user-agent created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: user-agent
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf user-agent updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: user-agent
```

/data/tailf-mobile-infra:client/http/ping

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_ping_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_http_ping_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping"
    Required/Optional: true

  Responses:
    "201":
      Description: container ping created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_http_ping_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping-post"

    Required/Optional: true

  Responses:
    "201":
```

```
      Description: container ping created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_ping_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_ping_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_client_http_ping_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_http_ping_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping"
    Required/Optional: true

  Responses:
    "204":
      Description: container ping updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/http/ping/timeout

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf timeout created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: timeout
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_options

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf timeout updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/http/ping/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_ping_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_ping_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound"
    Required/Optional: true

  Responses:
    "201":
      Description: container outbound created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_outbound_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound-post"

    Required/Optional: true

  Responses:
```

```
    "201":
      Description: container outbound created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
- data
- head
Operation ID: data_tailf_mobile_infra_client_outbound_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound"
    Required/Optional: true

  Responses:
    "204":
      Description: container outbound updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
```

/data/tailf-mobile-infra:client/outbound/interface

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_interface_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_client_outbound_interface_interface_interface_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface"

      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_client_outbound_interface_interface_interface_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: list interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: list interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
 Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_post

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_options

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit"

      Required/Optional: true

    Responses:
      "204":
        Description: container limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/pending

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending"

      Required/Optional: true

    Responses:
      "201":
        Description: container pending created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post"

```
    Required/Optional: true

  Responses:
    "201":
      Description: container pending created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending"

      Required/Optional: true

    Responses:
      "204":
        Description: container pending updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/pendi

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_get

Parameters:
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_put
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf response created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_delete
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf response updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/consec

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive"

    Required/Optional: true

  Responses:
    "201":
      Description: container consecutive created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_post


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container consecutive created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive"

      Required/Optional: true

    Responses:
      "204":
        Description: container consecutive updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/conse

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure"

      Required/Optional: true

    Responses:
      "201":
        Description: container failure created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failure
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_post


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container failure created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failure
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure"

      Required/Optional: true

    Responses:
      "204":
        Description: container failure updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failure
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/conse

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf count updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/conse

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/limit/conse

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_get

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: codes-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf-list codes created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: codes
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: codes-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list codes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: codes
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host"

      Required/Optional: true

    Responses:
      "201":
        Description: container host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container host created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host"

      Required/Optional: true

    Responses:
      "204":
        Description: container host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping"

      Required/Optional: true

    Responses:
      "201":
        Description: container ping created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_post
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container ping created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_delete

    Parameters:
```

```
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_patch

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping"

    Required/Optional: true

  Responses:
    "204":
      Description: container ping updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/tim

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf timeout created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf timeout updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/int

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf interval created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/ba

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf backoff created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backoff
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_head


    Parameters:
```

```
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf backoff updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backoff
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/r

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf retry created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf retry updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retry
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/f

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf fast-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: fast-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_head


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf fast-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: fast-interval
```

/data/tailf-mobile-infra:client/outbound/interface={interface-interface}/host/ping/all

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_get

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf all-host-down-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: all-host-down-interval
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf all-host-down-interval updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all-host-down-interval
```

/data/tailf-mobile-infra:client/outbound/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_limit"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
Method: Post:

  Tags:
  - data
```

```
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container limit created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_limit"

    Required/Optional: true

  Responses:
    "204":
      Description: container limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/outbound/limit/pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending"
      Required/Optional: true

    Responses:
      "201":
        Description: container pending created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending-post"
      Required/Optional: true
```

```
  Responses:
    "201":
      Description: container pending created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending"
      Required/Optional: true

    Responses:
      "204":
        Description: container pending updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/outbound/limit/pending/response

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf response created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
   Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_options


    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf response updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive"
      Required/Optional: true

    Responses:
      "201":
        Description: container consecutive created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container consecutive created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive"
      Required/Optional: true

    Responses:
      "204":
        Description: container consecutive updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container failure created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
Method: Post:

  Tags:
  - data
  - post
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_post

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container failure created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure"
      Required/Optional: true

    Responses:
      "204":
        Description: container failure updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failure
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure/count

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf count created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf count updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure/codes

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure/codes={codes-id}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_get

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id"

      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_put

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf-list codes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: codes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_delete

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_options

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_head

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_patch

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list codes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: codes
```

/data/tailf-mobile-infra:client/outbound/host

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_host"

      Required/Optional: true

    Responses:
      "201":
        Description: container host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_host_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container host created
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_head

  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_host_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_host"

    Required/Optional: true

  Responses:
    "204":
      Description: container host updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```


/data/tailf-mobile-infra:client/outbound/host/ping


```
get:

  Tags:
```

```
- data
- get
Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping"
      Required/Optional: true

    Responses:
      "201":
        Description: container ping created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container ping created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping"
      Required/Optional: true

    Responses:
      "204":
        Description: container ping updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/outbound/host/ping/timeout

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf timeout created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf timeout updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/outbound/host/ping/interval

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound/host/ping/backoff

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf backoff created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backoff
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_head

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf backoff updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backoff
```

/data/tailf-mobile-infra:client/outbound/host/ping/retry

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf retry created or replaced
        Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retry
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf retry updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retry
```

/data/tailf-mobile-infra:client/outbound/host/ping/fast-interval

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval"
      Required/Optional: true

    Responses:
```

```
    "201":
      Description: leaf fast-interval created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fast-interval
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf fast-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: fast-interval
```

/data/tailf-mobile-infra:client/outbound/host/ping/all-host-down-interval

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_put
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf all-host-down-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: all-host-down-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_options
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf all-host-down-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all-host-down-interval
```

/data/tailf-mobile-infra:client/inbound

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound"
    Required/Optional: true

  Responses:
    "201":
      Description: container inbound created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: inbound
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_inbound_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound-post"

    Required/Optional: true
```

```
  Responses:
    "201":
      Description: container inbound created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: inbound
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_inbound_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound"
      Required/Optional: true

    Responses:
      "204":
        Description: container inbound updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: inbound
```

/data/tailf-mobile-infra:client/inbound/interface

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_interface_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface"

      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: list interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: list interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/limit

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_post

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_options

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit"

      Required/Optional: true

    Responses:
      "204":
        Description: container limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/limit/pendin

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending"

      Required/Optional: true

    Responses:
      "201":
        Description: container pending created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post"

```
      Required/Optional: true

    Responses:
      "201":
        Description: container pending created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
```

```
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending"

      Required/Optional: true

    Responses:
      "204":
        Description: container pending updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/limit/pending/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

```
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_put
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_delete


    Parameters:
```

```
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/limit/overlo

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload"

      Required/Optional: true

    Responses:
      "201":
        Description: container overload created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container overload created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: overload
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container overload updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: overload
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/limit/overload

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: leaf reject-code created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reject-code
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf reject-code updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reject-code
```

/data/tailf-mobile-infra:client/inbound/limit

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_tailf_mobile_infra_client_inbound_limit_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound_limit"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound_limit"

    Required/Optional: true

  Responses:
    "201":
      Description: container limit created or replaced
      Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container limit created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound_limit"

      Required/Optional: true

    Responses:
      "204":
        Description: container limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/inbound/limit/pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending"
    Required/Optional: true

  Responses:
    "201":
      Description: container pending created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container pending created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container pending updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/inbound/limit/pending/request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: request
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:client/inbound/limit/overload

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload"
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload"
    Required/Optional: true

  Responses:
    "201":
      Description: container overload created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container overload created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_delete

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload"
      Required/Optional: true

    Responses:
      "204":
        Description: container overload updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: overload
```

/data/tailf-mobile-infra:client/inbound/limit/overload/reject-code

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf reject-code created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reject-code
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
 Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_patch

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf reject-code updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reject-code
```

/data/tailf-mobile-infra:instance

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_instance_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instance"
  "204":
    Description: No Content
    Content: {}
  "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_instance_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instance"
    Required/Optional: true

  Responses:
    "201":
      Description: container instance created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: instance
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_instance_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instance-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container instance created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_instance_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instance"
    Required/Optional: true

  Responses:
    "204":
      Description: container instance updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:instance/instance-id

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_instance_id_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id"
      Required/Optional: true

    Responses:
      "201":
        Description: list instance-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
  delete:

    Tags:
    - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_patch

      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id"
        Required/Optional: true

      Responses:
        "204":
          Description: list instance-id updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/id

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
- head
Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_head

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint"

    Required/Optional: true

  Responses:
    "201":
      Description: container endpoint created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
Method: Post:

  Tags:
  - data
  - post
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container endpoint created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint"

      Required/Optional: true

    Responses:
      "204":
        Description: container endpoint updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "200":
        Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
```

```
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype"

      Required/Optional: true

    Responses:
      "201":
        Description: list ep created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ep
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_delete

    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype"

      Required/Optional: true

    Responses:
      "204":
        Description: list ep updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ep
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_get


    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf eptype created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: eptype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf eptype updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: eptype
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf replicas created or replaced
      Content: {}
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf replicas updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf nodes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nodes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf nodes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nodes
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_put
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf loopbackEth created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf loopbackEth updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackEth
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
  data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf loopbackPort created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf loopbackPort updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf instancetype created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf instancetype updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip"

  Required/Optional: true

Responses:
  "201":
    Description: list vip created or replaced
    Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip"

      Required/Optional: true

  Responses:
    "204":
      Description: list vip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip"

    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_put


    Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface"

    Required/Optional: true

Responses:
  "201":
    Description: leaf vip-interface created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_get

    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
```

```
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6"

    Required/Optional: true

  Responses:
    "201":
      Description: list vip6 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_options


    Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6"

      Required/Optional: true

    Responses:
      "204":
        Description: list vip6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ipv6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_head


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ipv6 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_patch

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vip-ipv6-port updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-interface updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf offline updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level"

      Required/Optional: true

    Responses:
      "201":
        Description: container system-health-level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-health-level
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container system-health-level created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-health-level
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level"

      Required/Optional: true

    Responses:
      "204":
        Description: container system-health-level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-health-level
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn"

      Required/Optional: true

    Responses:
      "201":
        Description: container warn created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: warn
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container warn created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: warn
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

head:

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn"

      Required/Optional: true

    Responses:
      "204":
        Description: container warn updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: warn
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_get

    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-percent created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf cpu-percent updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-percent
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf memory-in-mbs created or replaced
      Content: {}
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-in-mbs updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf num-of-goroutine created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: num-of-goroutine
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf num-of-goroutine updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_put
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical"

      Required/Optional: true

    Responses:
      "201":
        Description: container critical created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: critical
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container critical created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: critical
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical"

      Required/Optional: true

    Responses:
      "204":
        Description: container critical updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: critical
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: leaf cpu-percent created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: leaf cpu-percent updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-percent
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-in-mbs created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-in-mbs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf num-of-goroutine created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf num-of-goroutine updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash"

      Required/Optional: true

    Responses:
      "201":
        Description: container crash created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: crash
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post"
```

```
      Required/Optional: true

    Responses:
      "201":
        Description: container crash created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: crash
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_patch


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash"
      Required/Optional: true

    Responses:
      "204":
        Description: container crash updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: crash
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent"

        Required/Optional: true

      Responses:
        "201":
          Description: leaf cpu-percent created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: cpu-percent
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf cpu-percent updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-percent
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-in-mbs created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-in-mbs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: leaf num-of-goroutine created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: num-of-goroutine
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf num-of-goroutine updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor"

      Required/Optional: true

    Responses:
      "201":
        Description: container monitor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_post


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container monitor created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_patch


    Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor"

    Required/Optional: true

  Responses:
    "204":
      Description: container monitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf protocol created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: protocol
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf protocol updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf uri-scheme created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_delete

    Parameters:
    - Name: instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:

```
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_head


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf uri-scheme updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf mtls-enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mtls-enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf mtls-enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mtls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf certificate-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf certificate-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list service created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: service
delete:

  Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name"

        Required/Optional: true

      Responses:
        "204":
          Description: list service updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: service
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
    get:

      Tags:
      - data
      - get
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_get


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name"

    Required/Optional: true

Responses:
  "201":
    Description: leaf service-name created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: service-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf service-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: service-name
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp


```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_get

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type"

      Required/Optional: true

  Responses:
    "201":
      Description: list interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type"

  Required/Optional: true

Responses:
  "204":
    Description: list interface updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type-put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf interface-type created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type"

      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf interface-type updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf loopbackEth created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackEth
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf loopbackEth updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf loopbackPort created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf loopbackPort updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme_get

    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf uri-scheme created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf uri-scheme updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: uri-scheme
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf instancetype created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype_delete


    Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf instancetype updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: instancetype
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf tls-enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-enable
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_patch


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable"

  Required/Optional: true

Responses:
  "204":
    Description: leaf tls-enable updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable"

      Required/Optional: true

  Responses:
    "201":
      Description: leaf mtls-enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable"

      Required/Optional: true

    Responses:
      "204":
```

```
      Description: leaf mtls-enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_put

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name"

  Required/Optional: true

Responses:
  "201":
    Description: leaf certificate-name created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf certificate-name updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: certificate-name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
    get:

      Tags:
      - data
      - get
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_get

      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container sla created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container sla created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_head

```
  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla"

    Required/Optional: true

  Responses:
    "204":
      Description: container sla updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf response created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf response updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure"

  Required/Optional: true

Responses:
  "201":
    Description: leaf procedure created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf procedure updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: procedure
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip"

  Required/Optional: true

Responses:
  "201":
    Description: list vip created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip"

      Required/Optional: true

    Responses:
      "204":
        Description: list vip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-ip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_get

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

  Required/Optional: true

Responses:
  "201":
```

```
      Description: leaf vip-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

- data
- put

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_patch


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vip-interface updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_head


  Parameters:
  - Name: instance-id-id
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip_vip-ip_offline"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_options


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_get

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

    Required/Optional: true

  Responses:
    "201":
      Description: list sec-vip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

      Required/Optional: true

  Responses:
    "204":
      Description: list sec-vip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep_eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep_eptype_service_service-service-name_interface_interface_interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf sec-vip-ip created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

  Required/Optional: true

Responses:
  "204":
    Description: leaf sec-vip-ip updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

  Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf vip-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
      - Name: service-service-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: interface-interface-type
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      - Name: sec-vip-sec-vip-ip
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-port updated
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

Tags:
- data
- put

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:

```
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

  Required/Optional: true
```

```
Responses:
  "204":
    Description: leaf vip-interface updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf offline created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

patch:

Tags:
- data
- patch

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_patch

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf offline updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service_service-name_interface_interface_interface-type_sec-vip_sec-vip_sec-vip-ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

- data
- head

Operation ID:

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_head

Parameters:

- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-ip_vrf"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf vrf updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6"

      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6"

      Required/Optional: true

    Responses:
      "201":
        Description: list vip6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6"

    Required/Optional: true

  Responses:
    "204":
      Description: list vip6 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_get

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

  Required/Optional: true

Responses:
  "201":
```

```
      Description: leaf vip-ipv6 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-ipv6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_patch


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vip-ipv6-port updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_head

  Parameters:
  - Name: instance-id-id
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-interface updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_options


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf offline updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

      Required/Optional: true

  Responses:
    "201":
      Description: leaf vrf created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_delete


  Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_options

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  "200":
    Description: OK
    Content: {}
security:
- **basicAuth**: []

head:

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ip6_vrf"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vrf updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

    Required/Optional: true

  Responses:
    "201":
      Description: list sec-vip6 created or replaced
      Content: {}
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailfmobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

  Required/Optional: true

Responses:
  "204":
    Description: list sec-vip6 updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_endpoint_ep_eptype_service_service-name_interface_interface-interface-type_sec-vip6_sec-vip-ipv6_sec-vip-ipv6"

  Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf sec-vip-ipv6 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
      - Name: service-service-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: interface-interface-type
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      - Name: sec-vip6-sec-vip-ipv6
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf sec-vip-ipv6 updated
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

Tags:
- data
- put

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ipv6-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

  Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf vip-ipv6-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_eptype_service_service-name_interface_interface-type_sec-vip6_sec-vip-ipv6_vip-interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

patch:

Tags:
- data
- patch

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_patch

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

Tags:
- data
- options

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_options

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  "200":
    Description: OK
    Content: {}

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ip6_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf_get

    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vrf created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher"

      Required/Optional: true

    Responses:
      "201":
        Description: container dispatcher created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dispatcher
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service-name_interface_interface_interface_type_dispatcher_post


    Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
 Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-post"

    Required/Optional: true

 Responses:
    "201":
      Description: container dispatcher created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: container dispatcher updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
Tags:
- data
- put
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_put


Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count"

  Required/Optional: true

Responses:
  "201":
    Description: leaf count created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf count updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf capacity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf capacity updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf outbound created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf outbound updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

get:

Tags:
- data
- get

Operation ID:
data_tailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf rate-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf rate-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache"

  Required/Optional: true

Responses:
  "201":
    Description: leaf cache created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cache
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf cache updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cache
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_put


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold"

  Required/Optional: true

Responses:
  "201":
    Description: leaf threshold created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf threshold updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf expiry created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: expiry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf expiry updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: expiry
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf nonresponsive created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nonresponsive
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf nonresponsive updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nonresponsive
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_put


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      - Name: service-service-name
        In: path
        Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: list flowctrl-group created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_patch

    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

    Required/Optional: true

  Responses:
    "204":
      Description: list flowctrl-group updated
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_path

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:

"#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name"

  Required/Optional: true

```
Responses:
  "204":
    Description: leaf name updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_eptype_service_service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf capacity created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

patch:

Tags:
- data
- patch

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_patch

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_endpoint_ep_eptype_service_service-name_interface_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf capacity updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-name_interface_interface-type_dispatcher_flowctrl_group_flowctrl_group_name_rate-limit_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_eptype_service_service-name_interface_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf rate-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit_delete

    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_rate-limit"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf rate-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_outbound-capacity_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/data/cnf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ep-type}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctl-group={flowctl-group-name}/outbound-capacity"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_ctrl_group_flow_ctrl_group_name_outbound_capacity_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf outbound-capacity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-capacity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

Tags:
- data
- options

Operation ID:
data_tail_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_options

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  "200":
    Description: OK
    Content: {}

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_ailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_outbound-rate-limit"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf outbound-capacity updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_outbound-rate-limit_get

    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-mobile-infra-instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_dispatcher_flow-ctrl-group_flow-ctrl-group-name_outbound-rate-limit"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_ailf-mobile-infra-instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flow-ctrl-group_flow-ctrl-group-name_outbound-rate-limit_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf outbound-rate-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-rate-limit
  delete:
```

Tags:
- data
- delete

Operation ID:
data_ailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit_delete

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  "204":
    Description: No Content

```
      Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_ctrl_group_flow_ctrl_group_name_outbound_rate_limit_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_endpoint_ep_service_service-name_interface_interface-type_monitor_flowctrl-group_flowctrl-group-name_outbound-rate-limit"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf outbound-rate-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor"

      Required/Optional: true

    Responses:
      "201":
        Description: container monitor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container monitor created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor"

      Required/Optional: true

    Responses:
```

```
    "204":
      Description: container monitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf protocol created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf protocol updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
    get:

      Tags:
      - data
      - get
      Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_get

      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container internal created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container internal created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_head

```
    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal"

    Required/Optional: true

  Responses:
    "204":
      Description: container internal updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port"

    Required/Optional: true

  Responses:
    "201":
      Description: container base-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container base-port created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port"

      Required/Optional: true

    Responses:
      "204":
        Description: container base-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf start created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf start updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: start
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type"

      Required/Optional: true

    Responses:
      "201":
        Description: list interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type"

      Required/Optional: true

    Responses:
      "204":
        Description: list interface updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface-type created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: interface-type
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf interface-type updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf loopbackEth created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackEth
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_head


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf loopbackEth updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp


```
  get:

    Tags:
    - data
```

```
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort"

    Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf loopbackPort created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort"

  Required/Optional: true

Responses:
  "204":
    Description: leaf loopbackPort updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf uri-scheme created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf uri-scheme updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: uri-scheme
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf instancetype created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf instancetype updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_get


    Parameters:
    - Name: instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf tls-enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf tls-enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf mtls-enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable"

    Required/Optional: true

Responses:
  "204":
    Description: leaf mtls-enable updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf certificate-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf certificate-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla"

      Required/Optional: true

  Responses:
    "201":
      Description: container sla created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
Method: Post:

  Tags:
  - data
  - post
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_post

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container sla created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla"

    Required/Optional: true

  Responses:
    "204":
      Description: container sla updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf response created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_patch

    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf response updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf procedure created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf procedure updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip"

```
      Required/Optional: true

    Responses:
      "201":
        Description: list vip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_delete

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip"

      Required/Optional: true

    Responses:
      "204":
        Description: list vip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-interface updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_put


    Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf offline created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vrf updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_get

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
```

```
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: list sec-vip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_options


    Parameters:
    - Name: instance-id-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

    Required/Optional: true

  Responses:
    "204":
      Description: list sec-vip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf sec-vip-ip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_patch

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"
  Required/Optional: true

Responses:
  "204":
    Description: leaf sec-vip-ip updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

      Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf vip-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
Tags:
- data
- put
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_put

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

  Required/Optional: true

Responses:
  "201":
    Description: leaf vip-interface created or replaced
    Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-interface updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

```
      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline_delete

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vrf updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6"

    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6"

      Required/Optional: true

  Responses:
    "201":
      Description: list vip6 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: list vip6 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ipv6 created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ipv6 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ipv6-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface_get

  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vip-interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf offline created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_patch

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf offline updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vrf updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: list sec-vip6 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

      Required/Optional: true

    Responses:
      "204":
        Description: list sec-vip6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6-get

    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_put

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf sec-vip-ipv6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip-ipv6
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf sec-vip-ipv6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

  "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vip-ipv6-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port_delete


    Parameters:
    - Name: instance-id-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf vip-ipv6-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf vip-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_patch


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

  Required/Optional: true

Responses:
  "204":
    Description: leaf vip-interface updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_put


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf offline created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

    Required/Optional: true

  Responses:
    "204":
```

```
    Description: leaf offline updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

  Required/Optional: true

Responses:
  "201":
    Description: leaf vrf created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_patch
```

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container dispatcher created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container dispatcher created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dispatcher
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher"

    Required/Optional: true

  Responses:
    "204":
      Description: container dispatcher updated
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface_interface-type_dispatcher_capacity_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf capacity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf capacity updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf outbound created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound"

    Required/Optional: true

Responses:
  "204":
    Description: leaf outbound updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: outbound
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf rate-limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf rate-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf cache created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cache
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf cache updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cache
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold"

  Required/Optional: true

Responses:
  "201":
    Description: leaf threshold created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf threshold updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_get

    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf expiry created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: expiry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf expiry updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: expiry
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive"

    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf nonresponsive created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nonresponsive
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf nonresponsive updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nonresponsive
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: list flowctrl-group created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list flowctrl-group updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: flowctrl-group
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name-name"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
```

```
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf capacity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf capacity updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

      Required/Optional: true

  Responses:
    "201":
      Description: leaf rate-limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf rate-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_outbound-capacity"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_outbound-capacity_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_outbound-capacity"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf outbound-capacity created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf outbound-capacity updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-capacity
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowvctrl_group_flowvctrl_group_name_outbound_rate_limit_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_outbound-rate-limit"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowvctrl-group_flowvctrl-group-name_outbound-rate-limit_put


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit"

  Required/Optional: true

Responses:
  "201":
    Description: leaf outbound-rate-limit created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-rate-limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf outbound-rate-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-rate-limit
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_put


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor"

  Required/Optional: true

Responses:
  "201":
    Description: container monitor created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container monitor created
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor"

    Required/Optional: true

  Responses:
    "204":
      Description: container monitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol"

    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf protocol created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: protocol
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf protocol updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_put


    Parameters:
    - Name: instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal"

      Required/Optional: true

    Responses:
      "201":
        Description: container internal created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_post
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post"

  Required/Optional: true

Responses:
  "201":
    Description: container internal created
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal"

    Required/Optional: true

  Responses:
    "204":
      Description: container internal updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_get


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port"

    Required/Optional: true

  Responses:
    "201":
      Description: container base-port created or replaced
      Content: {}
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container base-port created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port"

      Required/Optional: true

    Responses:
      "204":
        Description: container base-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf start created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf start updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: start
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal"

      Required/Optional: true

    Responses:
      "201":
        Description: container internal created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_post
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container internal created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal"

    Required/Optional: true

  Responses:
    "204":
      Description: container internal updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port"

    Required/Optional: true

  Responses:
    "201":
      Description: container base-port created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post"

    Required/Optional: true

  Responses:
    "201":
```

```
      Description: container base-port created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container base-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf start created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

head:

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf start updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptyp

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_get

    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp"

      Required/Optional: true

    Responses:
      "201":
        Description: container dscp created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: dscp
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container dscp created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dscp
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp"

      Required/Optional: true

    Responses:
      "204":
        Description: container dscp updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dscp
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-ept

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value"

      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value"

    Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
```

```
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_dscp_value_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf value updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
```

/data/tailf-mobile-infra:endpoint

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_endpoint_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint"
    Required/Optional: true

  Responses:
    "201":
      Description: container endpoint created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: endpoint
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_endpoint_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container endpoint created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_endpoint_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_endpoint_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_endpoint_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint"
    Required/Optional: true

  Responses:
    "204":
      Description: container endpoint updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
```

/data/tailf-mobile-infra:endpoint/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint_all"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/g

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_grInstance_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_grInstance_head

Parameters:
- **Name**: all-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_endpoint_get

  Parameters:
  - Name: all-grInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_endpoint_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/a

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_address_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_address_head

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/type

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_type_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_type"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_type_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/stat

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_status_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_status"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_status_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/Inte

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_Interface_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_Interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_Interface_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/inte

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_internal_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_internal"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_internal_head
```

```
Parameters:
- Name: all-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/sta

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_startTime_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_startTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_startTime_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/sto

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_stoppedTime_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_stoppedTime"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_stoppedTime_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoint},{all-address}/v

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_vrf_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_vrf"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_vrf_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint_info"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-address

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_head

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-address

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_grInstance_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_grInstance"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_grInstance_head

Parameters:
- **Name**: info-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-address

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_endpoint_get


  Parameters:
```

```
- Name: info-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_endpoint_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_address_get


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_address"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_address_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_type_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_type_head

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_status_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_status"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_status_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_Interface_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_Interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_Interface_head
```

```
Parameters:
- Name: info-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_internal_get


    Parameters:
    - Name: info-grInstance
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_internal"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_internal_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-addre

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_startTime_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_startTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_startTime_head


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-address

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_stoppedTime_get


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_stoppedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_stoppedTime_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-endpoint},{info-address

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_vrf_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_vrf_head

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_endpoint_ipv4_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_ipv4_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_get

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_head

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_grInstance_get
```

```
Parameters:
- Name: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_grInstance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_grInstance_head


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
  data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_endpoint_get


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_endpoint"

      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_endpoint_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_address_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_address_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_type_get

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_type_head

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_status_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_status"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_status_head
```

```
Parameters:
- Name: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_Interface_get


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_Interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_Interface_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addres

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_internal_get


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_internal"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_internal_head


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_startTime_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_startTime"

"204":
Description: No Content
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
head:

Tags:
- data
- head
Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_startTime_head

Parameters:
- Name: ipv4-grInstance
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: ipv4-endpoint
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: ipv4-address
In: path
Required/Optional: true
Style: simple
Explode: false

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_stoppedTime_get


  Parameters:
  - Name: ipv4-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv4-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_stoppedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_stoppedTime_head


    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv4={ipv4-grInstance},{ipv4-endpoint},{ipv4-addr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_vrf_get

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv4-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_vrf"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv4_ipv4_grInstance_ipv4_endpoint_ipv4_address_vrf_head

    Parameters:
    - Name: ipv4-grInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_ipv6_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_endpoint_ipv6_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_get

    Parameters:
```

```
- Name: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_head

    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_grInstance_get

Parameters:
- **Name**: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_grInstance"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_grInstance_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_endpoint_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_endpoint_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-address
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_address_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_address"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_address_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_type_get

  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_type_head
```

```
Parameters:
- Name: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_status_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_status"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_status_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addr

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_Interface_get

Parameters:
- **Name**: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_Interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_Interface_head


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addres

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_internal_get


  Parameters:
  - Name: ipv6-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: ipv6-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_internal"

"204":
Description: No Content
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
head:

Tags:
- data
- head
Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_internal_head

Parameters:
- Name: ipv6-grInstance
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: ipv6-endpoint
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: ipv6-address
In: path
Required/Optional: true
Style: simple
Explode: false

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_startTime_get


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_startTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_startTime_head


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_stoppedTime_get


    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: ipv6-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_stoppedTime"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_stoppedTime_head


    Parameters:
    - Name: ipv6-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/ipv6={ipv6-grInstance},{ipv6-endpoint},{ipv6-addres

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_vrf_get

    Parameters:
    - Name: ipv6-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_endpoint_ipv6_ipv6_grInstance_ipv6_endpoint_ipv6_address_vrf_head

Parameters:
- **Name**: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:vrf

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf"
    Required/Optional: true

  Responses:
    "201":
      Description: container vrf created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_vrf_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container vrf created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_patch
```

```
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_vrf"
  Required/Optional: true

Responses:
  "204":
    Description: container vrf updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:vrf/vrflist

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_get

Parameters:
- Name: vrflist-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name"
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_put
```

```
    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name"
      Required/Optional: true

    Responses:
      "201":
        Description: list vrflist created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrflist
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name"
      Required/Optional: true

    Responses:
      "204":
        Description: list vrflist updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrflist
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_get

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_options

  Parameters:
  - Name: vrflist-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/gateway

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_get

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf gateway created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gateway
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_patch

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf gateway updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateway
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/gatewayIpv6

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_get
```

```
Parameters:
- Name: vrflist-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf gatewayIpv6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gatewayIpv6
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_delete

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf gatewayIpv6 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gatewayIpv6
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf device created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: device
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_delete
```

```
  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf device updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: device
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf linkDevice created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: linkDevice
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_head
```

```
Parameters:
- Name: vrflist-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_patch

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf linkDevice updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: linkDevice
```

/data/tailf-mobile-infra:vrf-info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_info_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info"
    Required/Optional: true

  Responses:
    "201":
      Description: container vrf-info created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf-info
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_vrf_info_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container vrf-info created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf-info
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_info_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_info_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_info_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info"
    Required/Optional: true

  Responses:
    "204":
      Description: container vrf-info updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf-info
```

/data/tailf-mobile-infra:vrf-info/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info_all"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_name_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_name_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/gateway

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gateway_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_gateway"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gateway_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/gatewayIpv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gatewayIpv6_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_gatewayIpv6"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gatewayIpv6_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_device_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_device"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_device_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_linkDevice_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_linkDevice"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_linkDevice_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/tableId

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_tableId_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_tableId"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_tableId_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/state

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_state_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_state"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_state_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/podName

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_podName_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_podName"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_podName_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4"
  "204":
    Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_head

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
    - trim
    - explicit
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_name_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_name_head

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/gateway

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_gateway_get

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_gateway"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_gateway_head

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/gatewayIpv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_gatewayIpv6_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_gatewayIpv6"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_gatewayIpv6_head

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_device_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_device"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_device_head

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_linkDevice_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_linkDevice"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_linkDevice_head

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/tableId

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_tableId_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_tableId"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_tableId_head

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/state

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_state_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_state"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_state_head

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv4={ipv4-name}/podName

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_podName_get

  Parameters:
  - Name: ipv4-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_podName"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv4_ipv4_name_podName_head

    Parameters:
    - Name: ipv4-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_head

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_name_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_name_head

    Parameters:
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/gateway

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_gateway_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_gateway"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_gateway_head

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/gatewayIpv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_gatewayIpv6_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_gatewayIpv6"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_gatewayIpv6_head

    Parameters:
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
    - report-all
    - trim
    - explicit
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_device_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_device"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_device_head

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_linkDevice_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_linkDevice"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_linkDevice_head

    Parameters:
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
    - trim
    - explicit
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/tableId

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_tableId_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_tableId"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_tableId_head

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/state

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_state_get

    Parameters:
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_state"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_state_head

    Parameters:
    - Name: ipv6-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/ipv6={ipv6-name}/podName

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_podName_get

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_podName"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_ipv6_ipv6_name_podName_head

  Parameters:
  - Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:logging

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging"
      Required/Optional: true

    Responses:
      "201":
        Description: container logging created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container logging created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging"
    Required/Optional: true

  Responses:
    "204":
      Description: container logging updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: logging
```

/data/tailf-mobile-infra:logging/transaction

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_transaction"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_logging_transaction"

    Required/Optional: true

  Responses:
    "201":
      Description: container transaction created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
Method: Post:

  Tags:
```

```
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_transaction_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container transaction created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: transaction
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_transaction_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_tailf_mobile_infra_logging_transaction_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_logging_transaction"

      Required/Optional: true

    Responses:
      "204":
        Description: container transaction updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/transaction/persist

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_persist_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf persist created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: persist
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_transaction_persist_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_persist_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf persist updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: persist
```

/data/tailf-mobile-infra:logging/transaction/max-file-size

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-file-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-file-size
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_delete

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-file-size updated
        Content: {}
      "400":
```

```
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: max-file-size
```

/data/tailf-mobile-infra:logging/transaction/max-rotation

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf max-rotation created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-rotation
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation"
    Required/Optional: true

  Responses:
```

```
    "204":
      Description: leaf max-rotation updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-rotation
```

/data/tailf-mobile-infra:logging/transaction/message

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_message"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_message_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_message"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf message created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: message
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_message_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_message"
     Required/Optional: true

  Responses:
    "204":
      Description: leaf message updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: message
```

/data/tailf-mobile-infra:logging/transaction/duplicate

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate"
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf duplicate created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: duplicate
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf duplicate updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: duplicate
```

/data/tailf-mobile-infra:logging/level

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level"
      Required/Optional: true

    Responses:
      "201":
        Description: container level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_level_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container level created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level"
      Required/Optional: true

    Responses:
      "204":
        Description: container level updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:logging/level/application

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_level_application_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_application"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_level_application_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_application"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf application created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: application
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_application_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_application_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_application_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_application_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_application"
      Required/Optional: true
```

```
Responses:
  "204":
    Description: leaf application updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/level/transaction

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_transaction"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_transaction_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_transaction"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf transaction created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_transaction"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf transaction updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/level/tracing

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_tracing"
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level_tracing"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf tracing created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_logging_level_tracing_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level_tracing"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf tracing updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/level/monitor-subscriber

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf monitor-subscriber created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf monitor-subscriber updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/json-logging

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_json_logging_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_json-logging"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_json_logging_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_logging_json-logging"

    Required/Optional: true

  Responses:
    "201":
      Description: container json-logging created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: json-logging
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_json_logging_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container json-logging created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: json-logging
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_json_logging_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_json_logging_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_json_logging_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_json_logging_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_json-logging"
```

```
  Required/Optional: true

Responses:
  "204":
    Description: container json-logging updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: json-logging
```

/data/tailf-mobile-infra:logging/json-logging/application

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_json_logging_application_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_application"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_json_logging_application_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_application"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf application created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: application
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_json_logging_application_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_json_logging_application_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_json_logging_application_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_json_logging_application_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_application"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf application updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/json-logging/transaction

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_transaction"
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_transaction"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf transaction created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID: data_tailf_mobile_infra_logging_json_logging_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_transaction"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf transaction updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/json-logging/monitor-subscriber

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_monitor-subscriber"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_monitor-subscriber"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf monitor-subscriber created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_json_logging_monitor_subscriber_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_monitor-subscriber"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf monitor-subscriber updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/logger

```
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_logging_logger_options

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:logging/logger={logger-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name"
      Required/Optional: true

    Responses:
      "201":
        Description: list logger created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logger
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_delete

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_options

  Parameters:
```

```
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_patch

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name"
      Required/Optional: true

    Responses:
      "204":
        Description: list logger updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logger
```

/data/tailf-mobile-infra:logging/logger={logger-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_get

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name"
       Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_get
```

```
Parameters:
- Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level"
      Required/Optional: true

    Responses:
      "201":
        Description: container level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_post

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level-post"
        Required/Optional: true

      Responses:
        "201":
          Description: container level created
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: level
    delete:

      Tags:
      - data
      - delete
      Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_delete

      Parameters:
      - Name: logger-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string

      Responses:
        "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_patch

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level"
    Required/Optional: true

  Responses:
    "204":
      Description: container level updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/application

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_get


Parameters:
- Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf application created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_delete
```

```
    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_options

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_head


    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf application updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/transaction

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_get


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_put


    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf transaction created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_delete

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_head


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf transaction updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/tracing

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf tracing created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_delete


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_options


  Parameters:
  - Name: logger-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_patch


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf tracing updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/monitor-subscriber

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_get

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf monitor-subscriber created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
 options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf monitor-subscriber updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/async

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container async created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container async created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_async_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async"
    Required/Optional: true

  Responses:
    "204":
      Description: container async updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
```

/data/tailf-mobile-infra:logging/async/application

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_application_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_application_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application"
      Required/Optional: true

    Responses:
      "201":
        Description: container application created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_application_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container application created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: application
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_application_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application"
      Required/Optional: true

    Responses:
      "204":
        Description: container application updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/async/application/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable"
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable"
    Required/Optional: true

  Responses:
    "201":
      Description: container enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container enable created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_delete

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable"
      Required/Optional: true

    Responses:
      "204":
        Description: container enable updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/application/enable/buffer-size

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf buffer-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf buffer-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/application/disable

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/transaction

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction"
      Required/Optional: true

    Responses:
      "201":
        Description: container transaction created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container transaction created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction"
      Required/Optional: true
```

```
Responses:
  "204":
    Description: container transaction updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/async/transaction/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable"
      Required/Optional: true

    Responses:
      "201":
        Description: container enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: enable
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container enable created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable"
      Required/Optional: true

    Responses:
      "204":
        Description: container enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/transaction/enable/buffer-size

```
get:

 Tags:
 - data
 - get
Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_get


 Parameters:
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: integer
     Format: uint16
 - Name: fields
   In: query
   Description: optionally identify specific data nodes in response
   Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf buffer-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_delete
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: leaf buffer-size updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/transaction/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf disable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/tracing

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing"
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async_tracing"

    Required/Optional: true

  Responses:
    "201":
      Description: container tracing created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container tracing created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_delete

  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async_tracing"

      Required/Optional: true

    Responses:
      "204":
        Description: container tracing updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/async/tracing/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable"
    Required/Optional: true

  Responses:
    "201":
      Description: container enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
Method: Post:

  Tags:
  - data
  - post
```

```
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container enable created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable"
      Required/Optional: true

    Responses:
      "204":
        Description: container enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/tracing/enable/buffer-size

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf buffer-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf buffer-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/tracing/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf disable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_delete

  Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitor-subscriber created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
Method: Post:

  Tags:
  - data
```

```
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container monitor-subscriber created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber"
      Required/Optional: true

    Responses:
      "204":
        Description: container monitor-subscriber updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable"
      Required/Optional: true

    Responses:
      "201":
        Description: container enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container enable created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable"
      Required/Optional: true

    Responses:
      "204":
        Description: container enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/enable/buffer-size

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf buffer-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf buffer-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf disable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_delete


  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/error

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_error_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_error_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error"
    Required/Optional: true

  Responses:
    "201":
      Description: container error created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error
Method: Post:

  Tags:
  - data
  - post
```

```
  Operation ID: data_tailf_mobile_infra_logging_error_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container error created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_error_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_error_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_error_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_error_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error"
    Required/Optional: true

  Responses:
    "204":
      Description: container error updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: error
```

/data/tailf-mobile-infra:logging/error/stack

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_error_stack_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error_stack"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_error_stack_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error_stack"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf stack created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stack
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_error_stack_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_error_stack_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_error_stack_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_error_stack_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error_stack"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf stack updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stack
```

/data/tailf-mobile-infra:nodemonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_nodemonitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor"
    Required/Optional: true

  Responses:
    "201":
      Description: container nodemonitor created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_nodemonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container nodemonitor created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_nodemonitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_nodemonitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor"
    Required/Optional: true

  Responses:
    "204":
      Description: container nodemonitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
```

/data/tailf-mobile-infra:nodemonitor/mode

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_nodemonitor_mode_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf mode created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mode
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_nodemonitor_mode_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_nodemonitor_mode_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf mode updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: mode
```

/data/tailf-mobile-infra:nodemonitor/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_nodemonitor_interval_put
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf interval created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf interval updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:monitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitor created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitor created
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor"
    Required/Optional: true

  Responses:
    "204":
      Description: container monitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:monitor/bfd

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_monitor_bfd_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_monitor_bfd_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd"
      Required/Optional: true

    Responses:
      "201":
        Description: container bfd created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_bfd_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container bfd created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_bfd_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_bfd_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_bfd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_bfd_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd"
      Required/Optional: true

    Responses:
      "204":
        Description: container bfd updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:monitor/bfd/node-status

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf node-status created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-status
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf node-status updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: node-status
```

/data/tailf-mobile-infra:monitor/protocol

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_monitor_protocol_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_protocol_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol"
    Required/Optional: true

  Responses:
    "201":
      Description: container protocol created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_protocol_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container protocol created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: protocol
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_protocol_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_protocol_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_protocol_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_protocol_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
      Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol"
    Required/Optional: true

  Responses:
    "204":
      Description: container protocol updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:monitor/protocol/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit"
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
```

/data/tailf-mobile-infra:monitor/nf

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_monitor_nf_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_monitor_nf_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf"
      Required/Optional: true

    Responses:
      "201":
        Description: container nf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nf
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_nf_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container nf created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nf
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_nf_delete

  Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_nf_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_nf_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_nf_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf"
      Required/Optional: true

    Responses:
      "204":
        Description: container nf updated
        Content: {}
      "400":
```

```
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: nf
```

/data/tailf-mobile-infra:monitor/internal-vip-ipc

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc"
    Required/Optional: true

  Responses:
    "201":
      Description: container internal-vip-ipc created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal-vip-ipc
Method: Post:

  Tags:
  - data
  - post
```

```
    Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc-post"
        Required/Optional: true

    Responses:
      "201":
        Description: container internal-vip-ipc created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal-vip-ipc
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc"
      Required/Optional: true

    Responses:
      "204":
        Description: container internal-vip-ipc updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal-vip-ipc
```

/data/tailf-mobile-infra:monitor/internal-vip-ipc/max-conn-downtime

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-conn-downtime created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-conn-downtime
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
     Operation ID: data_tailf_mobile_infra_monitor_internal_vip_ipc_max_conn_downtime_patch

      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf max-conn-downtime updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-conn-downtime
```

/data/tailf-mobile-infra:monitor/active-instance-traffic

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic"
    Required/Optional: true

  Responses:
    "201":
      Description: container active-instance-traffic created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: active-instance-traffic
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_post
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container active-instance-traffic created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: active-instance-traffic
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_options

    Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic"
        Required/Optional: true

      Responses:
        "204":
          Description: container active-instance-traffic updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: active-instance-traffic
```

/data/tailf-mobile-infra:monitor/active-instance-traffic/no-traffic-duration

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf no-traffic-duration created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: no-traffic-duration
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_no_traffic_duration_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf no-traffic-duration updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: no-traffic-duration
```

/data/tailf-mobile-infra:monitor/active-instance-traffic/session-threshold

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf session-threshold created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: session-threshold
delete:

  Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_monitor_active_instance_traffic_session_threshold_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf session-threshold updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: session-threshold
```


/data/tailf-mobile-infra:monitor/active-instance-traffic/action


```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_action"
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_action"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf action created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: action
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_monitor_active_instance_traffic_action_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_action"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf action updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: action
```

/data/tailf-mobile-infra:router

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_router_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router"
      Required/Optional: true

    Responses:
      "201":
        Description: container router created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_router-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container router created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_router"
    Required/Optional: true

  Responses:
    "204":
      Description: container router updated
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
```

/data/tailf-mobile-infra:router/bgplist

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: insert
```

```
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp"
    Required/Optional: true

  Responses:
    "201":
      Description: list bgplist created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: bgplist
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_head

Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp"
      Required/Optional: true

    Responses:
      "204":
        Description: list bgplist updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bgplist
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bgp

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf bgp created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bgp
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf bgp updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bgp
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/loopbackPort

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf loopbackPort created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_patch

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf loopbackPort updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/loopbackBFDPort

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf loopbackBFDPort created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackBFDPort
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf loopbackBFDPort updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackBFDPort
```


/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/learnDefaultRoute


```
get:

  Tags:
  - data
  - get
```

Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_get

Parameters:
- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_put
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf learnDefaultRoute created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: learnDefaultRoute
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_delete

    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf learnDefaultRoute updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: learnDefaultRoute
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/prepend

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend"
      Required/Optional: true

    Responses:
      "201":
        Description: container prepend created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: prepend
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_post

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container prepend created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: prepend
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_head

  Parameters:
  - Name: bgplist-bgp
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend"
      Required/Optional: true

    Responses:
      "204":
        Description: container prepend updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: prepend
```


/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/prepend/as-path


```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf as-path created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: as-path
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path"
      Required/Optional: true

    Responses:
      "204":
```

```
    Description: leaf as-path updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: as-path
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList

```
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-inte

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: list interfaceList created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interfaceList
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: list interfaceList updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interfaceList
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_get


    Parameters:
```

```
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_get
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
```

```
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface"

      Required/Optional: true

    Responses:
      "201":
        Description: list bondingInterfaces created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bondingInterfaces
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_delete
```

```
  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: list bondingInterfaces updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: bondingInterfaces
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-inte

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_put


    Parameters:
    - Name: bgplist-bgp
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface"

  Required/Optional: true

Responses:
  "201":
    Description: leaf bondingInterface created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bondingInterface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_options
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterface-bondingInterface_bondingInterface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf bondingInterface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bondingInterface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-inter

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_put
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-inte

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-inte

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor"

      Required/Optional: true

    Responses:
      "201":
        Description: list neighbors created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbors
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor"

      Required/Optional: true

    Responses:
      "204":
        Description: list neighbors updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbors
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf neighbor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: neighbor
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_options


    Parameters:
    - Name: bgplist-bgp
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf neighbor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbor
```


/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_put

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-as created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-as
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_head


    Parameters:
    - Name: bgplist-bgp
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf remote-as updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-as
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-in

```
get:

  Tags:
  - data
```

- get

Operation ID:

data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_get

Parameters:

- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over"

    Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf fail-over created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fail-over
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_patch
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over"

  Required/Optional: true

Responses:
  "204":
    Description: leaf fail-over updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fail-over
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_get

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list policies created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: policies
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_head

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list policies updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: policies
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf policy-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: policy-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_head


    Parameters:
```

```
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf policy-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: policy-name
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-nam

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf as-path-set created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: as-path-set
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_delete

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_options

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_patch


      Parameters:
      - Name: bgplist-bgp
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf as-path-set updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: as-path-set
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ip-prefix created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip-prefix
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_options


  Parameters:
  - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ip-prefix updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip-prefix
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix"

    "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf source-prefix created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: source-prefix
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf source-prefix updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: source-prefix
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-nam

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf mask-range created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mask-range
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_delete


    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: integer
      Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf mask-range updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mask-range
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_get
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf modifySourceIp created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: modifySourceIp
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp"

      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf modifySourceIp updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: modifySourceIp
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-nam

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf isStaticRoute created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: isStaticRoute
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf isStaticRoute updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: isStaticRoute
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_get


    Parameters:
    - Name: bgplist-bgp
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf gateWay created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateWay
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf gateWay updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: gateWay
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd"
      Required/Optional: true

    Responses:
      "201":
        Description: container bfd created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bfd
  Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_post

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container bfd created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bfd
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_delete
```

```
  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd"
      Required/Optional: true

    Responses:
      "204":
        Description: container bfd updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_head

Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/min_rx

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf min_rx created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min_rx
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf min_rx updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min_rx
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/multiplier

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf multiplier created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: multiplier
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf multiplier updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: multiplier
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/dscp-marking

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf dscp-marking created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dscp-marking
 delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf dscp-marking updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dscp-marking
```

/data/tailf-mobile-infra:router/bfd

```
  get:

    Tags:
    - data
```

```
- get
Operation ID: data_tailf_mobile_infra_router_bfd_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_router_bfd_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd"
    Required/Optional: true

  Responses:
    "201":
      Description: container bfd created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_bfd_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container bfd created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bfd_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bfd_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bfd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_tailf_mobile_infra_router_bfd_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd"
  Required/Optional: true

Responses:
  "204":
    Description: container bfd updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:router/bfd/instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd_instance"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd_instance"

    Required/Optional: true

  Responses:
    "201":
      Description: container instance created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container instance created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd_instance"

    Required/Optional: true
```

```
  Responses:
    "204":
      Description: container instance updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_instance_id_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_get

  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id"

    Required/Optional: true

  Responses:
    "201":
      Description: list instance-id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: list instance-id updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/id

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_patch
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: id
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-lis

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface"

  Required/Optional: true

Responses:
  "201":
    Description: list interface-list created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-list
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: list interface-list updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-list
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface"

      Required/Optional: true

    Responses:
      "204":
```

```
      Description: leaf interface updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-li

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf vrf created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
Tags:
- data
- head
Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_head

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf vrf updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-li

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list_interface_neighbors_neighbors_neighbor_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: list neighbors created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbors
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor"

  Required/Optional: true

Responses:
  "204":
    Description: list neighbors updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbors
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf neighbor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbor
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf neighbor updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbor
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf gateway-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateway-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf gateway-ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateway-ip
```

/data/tailf-mobile-infra:router/monitor-interface

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface"
      Required/Optional: true

    Responses:
      "201":
        Description: container monitor-interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-interface
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitor-interface created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: monitor-interface
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface"
     Required/Optional: true

  Responses:
    "204":
      Description: container monitor-interface updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list

```
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_monitor_interface_interface_list_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={interface-list-interfa

```
get:

  Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_get


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_put


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface"

      Required/Optional: true

    Responses:
      "201":
        Description: list interface-list created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-list
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_options


    Parameters:
    - Name: interface-list-interface
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_head


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_patch


      Parameters:
      - Name: interface-list-interface
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface"

      Required/Optional: true

    Responses:
      "204":
        Description: list interface-list updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-list
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={interface-list-inter

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_get


    Parameters:
    - Name: interface-list-interface
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_put


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf interface created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_options


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_head


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={interface-list-interfa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_get


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_put


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf linked-interface created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linked-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_options


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_head


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf linked-interface updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: linked-interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={interface-list-interfa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_get


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_put


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf interface-type created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-type
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_options

    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_head

    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf interface-type updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-type
```

/data/tailf-mobile-infra:deployment

```
  get:

    Tags:
    - data
```

```
- get
Operation ID: data_tailf_mobile_infra_deployment_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment"
    Required/Optional: true

  Responses:
    "201":
      Description: container deployment created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_deployment_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container deployment created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_tailf_mobile_infra_deployment_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_deployment"
  Required/Optional: true

Responses:
  "204":
    Description: container deployment updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: deployment
```

/data/tailf-mobile-infra:deployment/app-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_app_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_app-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_app_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_app-name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf app-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: app-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_app_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_app_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_app_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_deployment_app_name_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_app-name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf app-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: app-name
```

/data/tailf-mobile-infra:deployment/cluster-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_deployment_cluster_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cluster-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_cluster_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cluster-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cluster-name
```

/data/tailf-mobile-infra:deployment/dc-name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_deployment_dc_name_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_dc-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_dc-name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf dc-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dc-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_dc-name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf dc-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dc-name
```

/data/tailf-mobile-infra:deployment/model

```
get:

  Tags:
  - data
  - get
  Summary: Deployment Model default large
  Description: Deployment Model default large
```

```
Operation ID: data_tailf_mobile_infra_deployment_model_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Deployment Model default large
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_model"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_put
  Request Body:
    Description: Deployment Model default large
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_model"
    Required/Optional: true

  Responses:
```

```
    "201":
      Description: leaf model created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: model
delete:

  Tags:
  - data
  - delete
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_patch
  Request Body:
    Description: Deployment Model default large
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_model"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf model updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: model
```

/data/tailf-mobile-infra:deployment/resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_resource_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_resource"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_deployment_resource_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_resource"

      Required/Optional: true

    Responses:
      "201":
        Description: container resource created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_deployment_resource_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource-post"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container resource created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_resource_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_resource_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_deployment_resource_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_deployment_resource_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_resource"

    Required/Optional: true

  Responses:
    "204":
      Description: container resource updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/tailf-mobile-infra:deployment/resource/cpu

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_options

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu
```

/data/tailf-mobile-infra:deployment/logical-nf-instance-id

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf logical-nf-instance-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logical-nf-instance-id
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf logical-nf-instance-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: logical-nf-instance-id
```

/data/tailf-mobile-infra:k8

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_k8_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_k8_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8"
    Required/Optional: true

  Responses:
    "201":
      Description: container k8 created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_k8_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8-post"
    Required/Optional: true

  Responses:
    "201":
```

```
      Description: container k8 created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_k8_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_tailf_mobile_infra_k8_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_k8_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8"
    Required/Optional: true

  Responses:
    "204":
      Description: container k8 updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
```

/data/tailf-mobile-infra:k8/label

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_k8_label_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_k8_label_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container label created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_k8_label_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container label created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_k8_label_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_label_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_k8_label_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_k8_label_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label"
    Required/Optional: true

  Responses:
    "204":
      Description: container label updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

/data/tailf-mobile-infra:k8/label/pod-group-config

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_label_pod_group_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_get


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_put


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
```

```
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value"

  Required/Optional: true

Responses:
  "201":
```

```
      Description: list pod-group-config created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-group-config
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_delete


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_options


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_head


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_patch


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value"

      Required/Optional: true

    Responses:
      "204":
        Description: list pod-group-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-group-config
```

/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{po

```
  get:

    Tags:
    - data
    - get
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_get

    Parameters:
    - Name: pod-group-config-pod-group
```

```
  In: path
  Description: Group for the VMs
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: Group for the VMs
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Group for the VMs
  Description: Group for the VMs
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_put


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Group for the VMs
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf pod-group created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-group
  delete:

    Tags:
    - data
    - delete
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_delete


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
```

```
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_options


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_head


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_patch


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Group for the VMs
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf pod-group updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-group
```

/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{po

```
get:

  Tags:
  - data
  - get
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_get


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Key for the label
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_put


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf key created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_delete


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_options


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_head


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_patch


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{

```
  get:

    Tags:
    - data
    - get
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_get

    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Value for the label
  Description: Value for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_put


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
  delete:

    Tags:
    - data
    - delete
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_delete


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_options


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_head


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
```

```
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Value for the label
  Description: Value for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_patch


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
```

```
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Value for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value"

      Required/Optional: true

  Responses:
    "204":
      Description: leaf value updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: value
```

/data/tailf-mobile-infra:geo

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geo_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_geo"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_geo_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:show

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_show_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_show"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_show_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:clear

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_clear_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_clear"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_clear_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:dump

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_dump_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_dump"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_dump_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_dump"
    Required/Optional: true

  Responses:
    "201":
      Description: container dump created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dump
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_dump_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_dump-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container dump created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dump
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_dump_delete

  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_dump_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_dump_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_dump_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_dump"
      Required/Optional: true

    Responses:
      "204":
        Description: container dump updated
        Content: {}
      "400":
        Description: Bad Request
```

```
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: dump
```

/data/tailf-mobile-infra:config-error

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_config_error_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_config-error"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_config_error_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_config-error"
    Required/Optional: true

  Responses:
    "201":
      Description: container config-error created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_config_error_post
  Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_config-error-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container config-error created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_config_error_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_config_error_options

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_config_error_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_config_error_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_config-error"
    Required/Optional: true

  Responses:
    "204":
      Description: container config-error updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
```

/data/tailf-mobile-infra:config-error/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_config_error_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_config-error_info"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
- head
Operation ID: data_tailf_mobile_infra_config_error_info_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_config_error_info_info_errorComponent_get

  Parameters:
  - Name: info-errorComponent
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_config_error_info_info_errorComponent_head

  Parameters:
  - Name: info-errorComponent
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}/errorComponent

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorComponent_get

    Parameters:
```

```
- Name: info-errorComponent
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent_errorComponent"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorComponent_head

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}/errorDescription

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorDescription_get

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent_errorDescription"

    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorDescription_head

  Parameters:
  - Name: info-errorComponent
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_resource"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resource"
    Required/Optional: true

  Responses:
    "201":
      Description: container resource created or replaced
      Content: {}
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_resource_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resource-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container resource created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
  Operation ID: data_tailf_mobile_infra_resource_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_resource"
    Required/Optional: true

  Responses:
    "204":
      Description: container resource updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/tailf-mobile-infra:resource/pod

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_get

Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_put
```

```
Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype"
    Required/Optional: true

Responses:
  "201":
    Description: list pod created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype"
      Required/Optional: true

    Responses:
      "204":
        Description: list pod updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/podtype

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf podtype created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podtype
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_options

  Parameters:
```

```
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf podtype updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: podtype
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_get

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu"
      Required/Optional: true

    Responses:
      "201":
        Description: container cpu created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_post

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container cpu created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_patch

    Parameters:
```

```
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu"
      Required/Optional: true

    Responses:
      "204":
        Description: container cpu updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu/request

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_get

    Parameters:
    - Name: pod-podtype
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu/limit

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_get

Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_put
```

```
    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_delete

    Parameters:
    - Name: pod-podtype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory"
      Required/Optional: true

    Responses:
      "201":
        Description: container memory created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory
  Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_post

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container memory created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory
  delete:

    Tags:
    - data
    - delete
```

```
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory"
      Required/Optional: true

    Responses:
      "204":
        Description: container memory updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf request created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: request
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_delete


  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_options


  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
- head
Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_head

Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
```


/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/limit


```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit"
      Required/Optional: true
```

```
Responses:
  "204":
    Description: leaf limit updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/gomemlimit

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_get


  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_put


    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf gomemlimit created or replaced
        Content: {}
      "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomemlimit
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_delete


    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_options

    Parameters:
    - Name: pod-podtype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_head


  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gomemlimit_patch


    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf gomemlimit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomemlimit
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/gogc

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_get

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf gogc created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gogc
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_gogc_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf gogc updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gogc
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/gomaxproc

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_get
```

```
Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_put

    Parameters:
    - Name: pod-podtype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf gomaxproc created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomaxproc
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf gomaxproc updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomaxproc
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels"
      Required/Optional: true

    Responses:
      "201":
        Description: container labels created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: labels
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_post
```

```
    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container labels created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: labels
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_delete

    Parameters:
    - Name: pod-podtype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels"
      Required/Optional: true

    Responses:
      "204":
        Description: container labels updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: labels
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels/key

```
get:

  Tags:
  - data
  - get
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Key for the label
    Description: Key for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```


/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels/value


```
  get:

    Tags:
    - data
    - get
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_get

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
      "200":
        Description: Value for the label
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value"
      Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf value created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

/data/tailf-mobile-infra:geomonitor

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_geomonitor_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_geomonitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor"
    Required/Optional: true

  Responses:
    "201":
```

```
      Description: container geomonitor created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_geomonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container geomonitor created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor"
    Required/Optional: true

  Responses:
    "204":
      Description: container geomonitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
```

/data/tailf-mobile-infra:geomonitor/podmonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor"

      Required/Optional: true

    Responses:
      "201":
        Description: container podmonitor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container podmonitor created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor"

    Required/Optional: true
```

```
  Responses:
    "204":
      Description: container podmonitor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_get

  Parameters:
```

```
- Name: pods-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name"
      Required/Optional: true

    Responses:
      "201":
        Description: list pods created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pods
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_delete

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_options

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_head

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name"
      Required/Optional: true

    Responses:
      "204":
        Description: list pods updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pods
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_get

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name"
    "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_delete


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_options


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_head


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_patch


    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/retryCount

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_get

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf retryCount created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_delete

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf retryCount updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/retryInterval

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_get

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_put
```

```
    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf retryInterval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_delete

    Parameters:
```

```
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf retryInterval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryInterval
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/retryFailOverIn

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_get

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf retryFailOverInterval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryFailOverInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_delete

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval"

      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf retryFailOverInterval updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryFailOverInterval
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/failedReplicaP

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_get

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf failedReplicaPercent created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failedReplicaPercent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_delete

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_options

    Parameters:
```

```
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_patch

      Parameters:
      - Name: pods-name
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf failedReplicaPercent updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failedReplicaPercent
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor"
      Required/Optional: true

    Responses:
      "201":
        Description: container remoteclustermonitor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remoteclustermonitor
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container remoteclustermonitor created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: remoteclustermonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor"
      Required/Optional: true

    Responses:
      "204":
        Description: container remoteclustermonitor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remoteclustermonitor
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor/retryCount

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount"
       Required/Optional: true

    Responses:
      "201":
        Description: leaf retryCount created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryCount
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf retryCount updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor/retryInterval

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf retryInterval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf retryInterval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryInterval
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor"
     Required/Optional: true

   Responses:
     "201":
       Description: container trafficMonitor created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: trafficMonitor
 Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor-post"
     Required/Optional: true

   Responses:
     "201":
       Description: container trafficMonitor created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: trafficMonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor"
       Required/Optional: true

    Responses:
      "204":
        Description: container trafficMonitor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: trafficMonitor
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor/thresholdCount

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf thresholdCount created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: thresholdCount
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
     Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_patch

      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf thresholdCount updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: thresholdCount
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor/thresholdInterval

```
    get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_get


Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval"
      Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf thresholdInterval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholdInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf thresholdInterval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: thresholdInterval
```

/data/tailf-mobile-infra:instances

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instances_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_instances"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instances_put
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instances"
    Required/Optional: true

  Responses:
    "201":
      Description: container instances created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_instances_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instances-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container instances created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_instances_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instances_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instances_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_instances_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_instances"
    Required/Optional: true

  Responses:
    "204":
      Description: container instances updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
```

/data/tailf-mobile-infra:instances/instance

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instances_instance_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_get

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_put

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id"
    Required/Optional: true
```

```
  Responses:
    "201":
      Description: list instance created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_delete


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
 Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_options


 Parameters:
 - Name: instance-instance-id
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: integer
     Format: int32

 Responses:
   "200":
     Description: OK
     Content: {}
 security:
 - basicAuth: []
head:

 Tags:
 - data
 - head
 Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_head

 Parameters:
 - Name: instance-instance-id
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: integer
     Format: int32
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_patch
```

```
    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id"
      Required/Optional: true

    Responses:
      "204":
        Description: list instance updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/instance-id

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_get

    Parameters:
```

```
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf instance-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: int32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf instance-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/system-id

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_get

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf system-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: system-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf system-id updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/cluster-id

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_get

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_put

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf cluster-id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_delete

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_options

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: integer
        Format: int32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf cluster-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cluster-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/slice-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_get

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf slice-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf slice-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-name
```

/data/tailf-mobile-infra:local-instance

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_local_instance_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_local_instance_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance"
      Required/Optional: true

    Responses:
      "201":
        Description: container local-instance created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_local_instance_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container local-instance created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_local_instance_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_local_instance_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_local_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_local_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance"
    Required/Optional: true

  Responses:
    "204":
      Description: container local-instance updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
```

/data/tailf-mobile-infra:local-instance/instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_local_instance_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_local-instance_instance"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_local_instance_instance_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_local-instance_instance"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf instance created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_local_instance_instance_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_local_instance_instance_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_local_instance_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_local_instance_instance_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_local-instance_instance"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf instance updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:datastore

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_datastore_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_datastore"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore"
    Required/Optional: true

  Responses:
    "201":
      Description: container datastore created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_datastore_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container datastore created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_datastore_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: container datastore updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
```

/data/tailf-mobile-infra:datastore/session-db

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_session_db_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_session-db"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_session_db_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_session-db"

    Required/Optional: true

  Responses:
    "201":
      Description: container session-db created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: session-db
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_datastore_session_db_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container session-db created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: session-db
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_datastore_session_db_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_session_db_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_session_db_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_datastore_session_db_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_session-db"

    Required/Optional: true

  Responses:
    "204":
      Description: container session-db updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: session-db
```

/data/tailf-mobile-infra:datastore/session-db/endpoints

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpoints-host}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_get


  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_put


    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host"

      Required/Optional: true

    Responses:
      "201":
        Description: list endpoints created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: endpoints
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_delete

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_options

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_head

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host"

      Required/Optional: true

    Responses:
      "204":
        Description: list endpoints updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoints
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpoints-host}/host

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_get

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_put

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf host created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_delete

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_options

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_head

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpoints-host}/port

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_get

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_put

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_delete

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_options

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_head

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/tailf-mobile-infra:datastore/dbs

```
  options:
```

```
    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_datastore_dbs_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_get

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_put

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
        Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list dbs created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbs
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_delete

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_options

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_head

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list dbs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dbs
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_get
```

```
Parameters:
- Name: dbs-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_put

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_delete

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_options

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_head

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_options

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpoints-host}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_get

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_put

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host"

      Required/Optional: true

    Responses:
      "201":
        Description: list endpoints created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoints
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_delete

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_options

    Parameters:
    - Name: dbs-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_head

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host"

      Required/Optional: true

    Responses:
      "204":
        Description: list endpoints updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoints
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpoints-host}/hos

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_get

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host"

      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_put

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf host created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_delete

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_options

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_head

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpoints-host}/port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_get

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_put

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_delete

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_options

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_head

    Parameters:
    - Name: dbs-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/tailf-mobile-infra:datastore/notification-ep

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep"
      Required/Optional: true

    Responses:
      "201":
        Description: container notification-ep created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: notification-ep
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container notification-ep created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: notification-ep
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep"
      Required/Optional: true

    Responses:
      "204":
        Description: container notification-ep updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: notification-ep
```

/data/tailf-mobile-infra:datastore/notification-ep/host

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf host updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/notification-ep/port

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: port
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/tailf-mobile-infra:load

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_load_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load"
  "204":
    Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_load_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load"
    Required/Optional: true

  Responses:
    "201":
      Description: container load created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: load
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_load_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container load created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: load
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_load_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_load_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_load_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_load_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load"
    Required/Optional: true

  Responses:
    "204":
      Description: container load updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: load
```

/data/tailf-mobile-infra:load/factor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_load_factor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_load_factor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor"
    Required/Optional: true

  Responses:
    "201":
      Description: container factor created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: factor
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_load_factor_post
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container factor created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: factor
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_load_factor_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_load_factor_options

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_load_factor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_load_factor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor"
    Required/Optional: true

  Responses:
    "204":
      Description: container factor updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: factor
```

/data/tailf-mobile-infra:load/factor/calc-frequency

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_calc-frequency"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_calc-frequency"
       Required/Optional: true

    Responses:
      "201":
        Description: leaf calc-frequency created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: calc-frequency
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_tailf_mobile_infra_load_factor_calc_frequency_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_calc-frequency"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf calc-frequency updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: calc-frequency
```

/data/tailf-mobile-infra:load/factor/exclude-pods

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_load_factor_exclude_pods_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:load/factor/exclude-pods={exclude-pods-pod-type}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_get

  Parameters:
  - Name: exclude-pods-pod-type
    In: path
    Description: Default set to exclude all infra-pods
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_put

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type"

      Required/Optional: true

    Responses:
      "201":
        Description: list exclude-pods created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: exclude-pods
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_delete

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_options

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_head
```

```
Parameters:
- Name: exclude-pods-pod-type
  In: path
  Description: Default set to exclude all infra-pods
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_patch

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type"

      Required/Optional: true

    Responses:
      "204":
        Description: list exclude-pods updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: exclude-pods
```

/data/tailf-mobile-infra:load/factor/exclude-pods={exclude-pods-pod-type}/pod-ty

```
get:

  Tags:
  - data
  - get
  Summary: Default set to exclude all infra-pods
  Description: Default set to exclude all infra-pods
  Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_get

  Parameters:
  - Name: exclude-pods-pod-type
    In: path
    Description: Default set to exclude all infra-pods
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Default set to exclude all infra-pods
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Default set to exclude all infra-pods
    Description: Default set to exclude all infra-pods
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_put

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Default set to exclude all infra-pods
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf pod-type created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-type
delete:

  Tags:
  - data
  - delete
  Summary: Default set to exclude all infra-pods
  Description: Default set to exclude all infra-pods
  Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_delete

  Parameters:
  - Name: exclude-pods-pod-type
    In: path
    Description: Default set to exclude all infra-pods
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Summary: Default set to exclude all infra-pods
    Description: Default set to exclude all infra-pods
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_options

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Default set to exclude all infra-pods
    Description: Default set to exclude all infra-pods
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_head

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Default set to exclude all infra-pods
    Description: Default set to exclude all infra-pods
    Operation ID:
data_tailf_mobile_infra_load_factor_exclude_pods_exclude_pods_pod_type_pod_type_patch

    Parameters:
    - Name: exclude-pods-pod-type
      In: path
      Description: Default set to exclude all infra-pods
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Default set to exclude all infra-pods
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf pod-type updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-type
```

Components


```
components:
  schemas:
    data:
      Type: object
      Properties:
        ietf-restconf:data:
          Type: object
          Properties: {}
         Description: This resource represents the combined configuration and state data
resources that can be
           accessed by a client and cannot be created or deleted by the client. See RESTCONF
RFC 8040
            for further information.
          x-yang:
            Type: datastore
    data-post:
      Type: object
      Properties:
        tailf-mobile-infra:sessions:
          Reference: "#/components/schemas/datapost_tailfmobileinfrasessions"
        tailf-mobile-infra:peers:
          Reference: "#/components/schemas/datapost_tailfmobileinfrapeers"
        tailf-mobile-infra:rpc:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarpc"
        tailf-mobile-infra:resources:
          Reference: "#/components/schemas/datapost_tailfmobileinfraresources"
        tailf-mobile-infra:running-status:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus"
        tailf-mobile-infra:diagnostics:
          Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics"
        tailf-mobile-infra:infra:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra"
        tailf-mobile-infra:client:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient"
        tailf-mobile-infra:instance:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainstance"
        tailf-mobile-infra:endpoint:
          Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint"
        tailf-mobile-infra:vrf:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrf"
        tailf-mobile-infra:vrf-info:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo"
        tailf-mobile-infra:logging:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging"
        tailf-mobile-infra:nodemonitor:
          Reference: "#/components/schemas/datapost_tailfmobileinfranodemonitor"
        tailf-mobile-infra:monitor:
          Reference: "#/components/schemas/datapost_tailfmobileinframonitor"
```

```
      tailf-mobile-infra:router:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter"
      tailf-mobile-infra:deployment:
        Reference: "#/components/schemas/datapost_tailfmobileinfradeployment"
      tailf-mobile-infra:k8:
        Reference: "#/components/schemas/datapost_tailfmobileinfrak8"
      tailf-mobile-infra:geo:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:show:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:clear:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:dump:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:config-error:
        Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror"
      tailf-mobile-infra:resource:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresource"
      tailf-mobile-infra:geomonitor:
        Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor"
      tailf-mobile-infra:instances:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainstances"
      tailf-mobile-infra:local-instance:
        Reference: "#/components/schemas/datapost_tailfmobileinfralocalinstance"
      tailf-mobile-infra:datastore:
        Reference: "#/components/schemas/datapost_tailfmobileinfradatastore"
      tailf-mobile-infra:load:
        Reference: "#/components/schemas/datapost_tailfmobileinfraload"
  data-put-patch:
    Type: object
    Properties:
```

```
    ietf-restconf:data:
      Reference: "#/components/schemas/dataputpatch_ietfrestconfdata"
data_tailf-mobile-infra_clear:
  Type: object
  Properties:
    tailf-mobile-infra:clear:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_tailf-mobile-infra_client:
  Type: object
  Properties:
    tailf-mobile-infra:client:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient"
data_tailf-mobile-infra_client-post:
  Type: object
  Properties:
    tailf-mobile-infra:http:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http"
    tailf-mobile-infra:outbound:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound"
    tailf-mobile-infra:inbound:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound"
data_tailf-mobile-infra_client_http:
  Type: object
  Properties:
    tailf-mobile-infra:http:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http"
data_tailf-mobile-infra_client_http-post:
  Type: object
  Properties:
    tailf-mobile-infra:header:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_header"
    tailf-mobile-infra:ping:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_ping"
data_tailf-mobile-infra_client_http_header:
  Type: object
  Properties:
    tailf-mobile-infra:header:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_header"
data_tailf-mobile-infra_client_http_header-post:
  Type: object
  Properties:
    tailf-mobile-infra:user-agent:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: cluster-name
```

```
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_header_user-agent:
  Type: object
  Properties:
    tailf-mobile-infra:user-agent:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: cluster-name
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_ping:
  Type: object
  Properties:
    tailf-mobile-infra:ping:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_ping"
data_tailf-mobile-infra_client_http_ping-post:
  Type: object
  Properties:
    tailf-mobile-infra:timeout:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_ping_interval:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_ping_timeout:
  Type: object
  Properties:
    tailf-mobile-infra:timeout:
```

```
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_inbound:
      Type: object
      Properties:
        tailf-mobile-infra:inbound:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound"
    data_tailf-mobile-infra_client_inbound-post:
      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface"
          x-yang:
            Type: list
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit"

    data_tailf-mobile-infra_client_inbound_interface_interface-interface:
      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface"
          x-yang:
            Type: list

data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface:

      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit:

      Type: object
      Properties:
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit"
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending"
        tailf-mobile-infra:overload:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload"
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload:

```
      Type: object
      Properties:
        tailf-mobile-infra:overload:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload"
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:reject-code:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code:

```
      Type: object
      Properties:
        tailf-mobile-infra:reject-code:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending:

```
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending"
```

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post:

```
      Type: object
      Properties:
```

```
        tailf-mobile-infra:request:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request:

      Type: object
      Properties:
        tailf-mobile-infra:request:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_inbound_limit:
      Type: object
      Properties:
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit"

    data_tailf-mobile-infra_client_inbound_limit-post:
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending"
        tailf-mobile-infra:overload:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload"
    data_tailf-mobile-infra_client_inbound_limit_overload:
      Type: object
      Properties:
        tailf-mobile-infra:overload:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload"
    data_tailf-mobile-infra_client_inbound_limit_overload-post:
      Type: object
      Properties:
        tailf-mobile-infra:reject-code:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_inbound_limit_overload_reject-code:
      Type: object
      Properties:
        tailf-mobile-infra:reject-code:
          Type: integer
          Description: (leaf)
```

```
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_inbound_limit_pending:
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending"
    data_tailf-mobile-infra_client_inbound_limit_pending-post:
      Type: object
      Properties:
        tailf-mobile-infra:request:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_inbound_limit_pending_request:
      Type: object
      Properties:
        tailf-mobile-infra:request:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound:
      Type: object
      Properties:
        tailf-mobile-infra:outbound:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound"
    data_tailf-mobile-infra_client_outbound-post:
      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface"
          x-yang:
            Type: list
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit"

        tailf-mobile-infra:host:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_host"

    data_tailf-mobile-infra_client_outbound_host:
      Type: object
      Properties:
```

```
        tailf-mobile-infra:host:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_host"

    data_tailf-mobile-infra_client_outbound_host-post:
      Type: object
      Properties:
        tailf-mobile-infra:ping:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping"
    data_tailf-mobile-infra_client_outbound_host_ping:
      Type: object
      Properties:
        tailf-mobile-infra:ping:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping"
    data_tailf-mobile-infra_client_outbound_host_ping-post:
      Type: object
      Properties:
        tailf-mobile-infra:timeout:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:interval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:backoff:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:retry:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:fast-interval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:all-host-down-interval:
          Type: integer
          Description: (leaf)
          Format: int32
```

```
        x-yang:
          Type: leaf
data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval:
    Type: object
    Properties:
      tailf-mobile-infra:all-host-down-interval:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_host_ping_backoff:
    Type: object
    Properties:
      tailf-mobile-infra:backoff:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_host_ping_fast-interval:
    Type: object
    Properties:
      tailf-mobile-infra:fast-interval:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_host_ping_interval:
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_host_ping_retry:
    Type: object
    Properties:
      tailf-mobile-infra:retry:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_host_ping_timeout:
    Type: object
    Properties:
```

```
        tailf-mobile-infra:timeout:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound_interface_interface-interface:

      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface"
          x-yang:
            Type: list

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host:

      Type: object
      Properties:
        tailf-mobile-infra:host:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_host"


data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post:

      Type: object
      Properties:
        tailf-mobile-infra:ping:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping:

      Type: object
      Properties:
        tailf-mobile-infra:ping:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post:

      Type: object
      Properties:
        tailf-mobile-infra:timeout:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:interval:
```

```
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:backoff:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:retry:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:fast-interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:all-host-down-interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval:

```
Type: object
Properties:
  tailf-mobile-infra:all-host-down-interval:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff:

```
Type: object
Properties:
  tailf-mobile-infra:backoff:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval:

```
Type: object
Properties:
  tailf-mobile-infra:fast-interval:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval:

```
Type: object
Properties:
  tailf-mobile-infra:interval:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry:

```
Type: object
Properties:
  tailf-mobile-infra:retry:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout:

```
Type: object
Properties:
  tailf-mobile-infra:timeout:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface:

```
Type: object
Properties:
  tailf-mobile-infra:interface:
    Type: string
    Description: (leaf)
    Format: identityref
    x-yang:
```

```
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit:

      Type: object
      Properties:
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit"


data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post:

      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending"
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive:

      Type: object
      Properties:
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post:

      Type: object
      Properties:
        tailf-mobile-infra:failure:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure:

      Type: object
      Properties:
        tailf-mobile-infra:failure:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure"

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post:

      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

```
        tailf-mobile-infra:codes:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id:

```
      Type: object
      Properties:
        tailf-mobile-infra:codes:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count:

```
      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending:

```
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending"
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:response:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response:

```
      Type: object
      Properties:
        tailf-mobile-infra:response:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound_limit:
      Type: object
      Properties:
        tailf-mobile-infra:limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit"

    data_tailf-mobile-infra_client_outbound_limit-post:
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending"
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive"
    data_tailf-mobile-infra_client_outbound_limit_consecutive:
      Type: object
      Properties:
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive"
    data_tailf-mobile-infra_client_outbound_limit_consecutive-post:
      Type: object
      Properties:
        tailf-mobile-infra:failure:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure"
    data_tailf-mobile-infra_client_outbound_limit_consecutive_failure:
      Type: object
      Properties:
        tailf-mobile-infra:failure:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure"
   data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post:

      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:codes:
          Type: array
```

```
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list

data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id:

      Type: object
      Properties:
        tailf-mobile-infra:codes:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count:

      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
   data_tailf-mobile-infra_client_outbound_limit_pending:
      Type: object
      Properties:
        tailf-mobile-infra:pending:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending"
    data_tailf-mobile-infra_client_outbound_limit_pending-post:
      Type: object
      Properties:
        tailf-mobile-infra:response:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound_limit_pending_response:
      Type: object
      Properties:
        tailf-mobile-infra:response:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
```

```
        Type: leaf
    data_tailf-mobile-infra_config-error:
      Type: object
      Properties:
        tailf-mobile-infra:config-error:
          Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror"
    data_tailf-mobile-infra_config-error-post:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror_info"
          x-yang:
            Type: list
    data_tailf-mobile-infra_config-error_info:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror_info"
          x-yang:
            Type: list
    data_tailf-mobile-infra_config-error_info_info-errorComponent:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror_info"
          x-yang:
            Type: list

data_tailf-mobile-infra_config-error_info_info-errorComponent_errorComponent:

      Type: object
      Properties:
        tailf-mobile-infra:errorComponent:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_config-error_info_info-errorComponent_errorDescription:

      Type: object
      Properties:
```

```
        tailf-mobile-infra:errorDescription:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_datastore:
      Type: object
      Properties:
        tailf-mobile-infra:datastore:
          Reference: "#/components/schemas/datapost_tailfmobileinfradatastore"
    data_tailf-mobile-infra_datastore-post:
      Type: object
      Properties:
        tailf-mobile-infra:session-db:
          Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb"

        tailf-mobile-infra:dbs:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_dbs"
          x-yang:
            Type: list
        tailf-mobile-infra:notification-ep:
          Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_notificationep"
    data_tailf-mobile-infra_datastore_dbs_dbs-name:
      Type: object
      Properties:
        tailf-mobile-infra:dbs:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_dbs"
          x-yang:
            Type: list
   data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host:

      Type: object
      Properties:
        tailf-mobile-infra:endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints"
          x-yang:
            Type: list

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host:

      Type: object
```

```
      Properties:
        tailf-mobile-infra:host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port:

      Type: object
      Properties:
        tailf-mobile-infra:port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_datastore_dbs_dbs-name_name:
      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_datastore_notification-ep:
      Type: object
      Properties:
        tailf-mobile-infra:notification-ep:
          Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_notificationep"
    data_tailf-mobile-infra_datastore_notification-ep-post:
      Type: object
      Properties:
        tailf-mobile-infra:host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        tailf-mobile-infra:port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_datastore_notification-ep_host:
      Type: object
      Properties:
        tailf-mobile-infra:host:
```

```
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_datastore_notification-ep_port:
      Type: object
      Properties:
        tailf-mobile-infra:port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_datastore_session-db:
      Type: object
      Properties:
        tailf-mobile-infra:session-db:
          Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb"

    data_tailf-mobile-infra_datastore_session-db-post:
      Type: object
      Properties:
        tailf-mobile-infra:endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints"
          x-yang:
            Type: list
   data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host:

      Type: object
      Properties:
        tailf-mobile-infra:endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints"
          x-yang:
            Type: list

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host:

      Type: object
      Properties:
        tailf-mobile-infra:host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
```

```
          Type: leaf

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port:
      Type: object
      Properties:
        tailf-mobile-infra:port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_deployment:
      Type: object
      Properties:
        tailf-mobile-infra:deployment:
          Reference: "#/components/schemas/datapost_tailfmobileinfradeployment"
    data_tailf-mobile-infra_deployment-post:
      Type: object
      Properties:
        tailf-mobile-infra:app-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        tailf-mobile-infra:cluster-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        tailf-mobile-infra:dc-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        tailf-mobile-infra:model:
          Type: string
          Description: Deployment Model default large (leaf)
          Format: enumeration
          Default: small
          enum:
          - small
          x-yang:
            Type: leaf
        tailf-mobile-infra:resource:
          Reference: "#/components/schemas/datapost_tailfmobileinfradeployment_resource"

        tailf-mobile-infra:logical-nf-instance-id:
          Type: integer
```

```
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_app-name:
  Type: object
  Properties:
    tailf-mobile-infra:app-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_cluster-name:
  Type: object
  Properties:
    tailf-mobile-infra:cluster-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_dc-name:
  Type: object
  Properties:
    tailf-mobile-infra:dc-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_logical-nf-instance-id:
  Type: object
  Properties:
    tailf-mobile-infra:logical-nf-instance-id:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_model:
  Type: object
  Properties:
    tailf-mobile-infra:model:
      Type: string
      Description: Deployment Model default large (leaf)
      Format: enumeration
      Default: small
      enum:
      - small
      x-yang:
        Type: leaf
```

```
    data_tailf-mobile-infra_deployment_resource:
      Type: object
      Properties:
        tailf-mobile-infra:resource:
          Reference: "#/components/schemas/datapost_tailfmobileinfradeployment_resource"

    data_tailf-mobile-infra_deployment_resource-post:
      Type: object
      Properties:
        tailf-mobile-infra:cpu:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_deployment_resource_cpu:
      Type: object
      Properties:
        tailf-mobile-infra:cpu:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_diagnostics:
      Type: object
      Properties:
        tailf-mobile-infra:diagnostics:
          Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics"
    data_tailf-mobile-infra_diagnostics-post:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics_info"
          x-yang:
            Type: list
    data_tailf-mobile-infra_diagnostics_info:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics_info"
          x-yang:
            Type: list

  data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics_info"
          x-yang:
            Type: list

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_component:

      Type: object
      Properties:
        tailf-mobile-infra:component:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_diagnostic:

      Type: object
      Properties:
        tailf-mobile-infra:diagnostic:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_podInstance:

      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_retries:

      Type: object
      Properties:
        tailf-mobile-infra:retries:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_startTime:
      Type: object
      Properties:
        tailf-mobile-infra:startTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_status:
      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_dump:
      Type: object
      Properties:
        tailf-mobile-infra:dump:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_tailf-mobile-infra_dump-post:
      Type: object
    data_tailf-mobile-infra_endpoint:
      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint"
    data_tailf-mobile-infra_endpoint-post:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
```

```
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list
    data_tailf-mobile-infra_endpoint_all:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address:

      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_Interface:

      Type: object
      Properties:
        tailf-mobile-infra:Interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_address:

     Type: object
     Properties:
       tailf-mobile-infra:address:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_endpoint:

     Type: object
     Properties:
       tailf-mobile-infra:endpoint:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_grInstance:

     Type: object
     Properties:
       tailf-mobile-infra:grInstance:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_internal:

     Type: object
     Properties:
       tailf-mobile-infra:internal:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_startTime:

     Type: object
     Properties:
       tailf-mobile-infra:startTime:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
```

```
            Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_status:

      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_stoppedTime:

      Type: object
      Properties:
        tailf-mobile-infra:stoppedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_type:

      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_endpoint_info:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
```

```
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address:

    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_Interface:

    Type: object
    Properties:
      tailf-mobile-infra:Interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_address:

    Type: object
    Properties:
      tailf-mobile-infra:address:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_endpoint:

    Type: object
    Properties:
      tailf-mobile-infra:endpoint:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_grInstance:

    Type: object
    Properties:
      tailf-mobile-infra:grInstance:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_internal:

      Type: object
      Properties:
        tailf-mobile-infra:internal:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_startTime:

      Type: object
      Properties:
        tailf-mobile-infra:startTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_status:

      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_stoppedTime:

      Type: object
      Properties:
        tailf-mobile-infra:stoppedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_type:

      Type: object
```

```
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_endpoint_ipv4:
      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address:

      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_Interface:

      Type: object
      Properties:
        tailf-mobile-infra:Interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_address:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:address:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_endpoint:

      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_grInstance:

      Type: object
      Properties:
        tailf-mobile-infra:grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_internal:

      Type: object
      Properties:
        tailf-mobile-infra:internal:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_startTime:

      Type: object
      Properties:
        tailf-mobile-infra:startTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_status:

      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_stoppedTime:

      Type: object
      Properties:
        tailf-mobile-infra:stoppedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_type:

      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-address_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_endpoint_ipv6:
      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
```

```
          Type: list

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address:

      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_Interface:

      Type: object
      Properties:
        tailf-mobile-infra:Interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_address:

      Type: object
      Properties:
        tailf-mobile-infra:address:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_endpoint:

      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_grInstance:

      Type: object
      Properties:
        tailf-mobile-infra:grInstance:
          Type: string
```

```
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_internal:

      Type: object
      Properties:
        tailf-mobile-infra:internal:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_startTime:

      Type: object
      Properties:
        tailf-mobile-infra:startTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_status:

      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_stoppedTime:

      Type: object
      Properties:
        tailf-mobile-infra:stoppedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_type:

      Type: object
      Properties:
```

```
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_tailf-mobile-infra_endpoint_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-address_vrf:
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geo:
      Type: object
      Properties:
        tailf-mobile-infra:geo:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_tailf-mobile-infra_geomonitor:
      Type: object
      Properties:
        tailf-mobile-infra:geomonitor:
          Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor"
    data_tailf-mobile-infra_geomonitor-post:
      Type: object
      Properties:
        tailf-mobile-infra:podmonitor:
         Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor"

        tailf-mobile-infra:remoteclustermonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor"
        tailf-mobile-infra:trafficMonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor"
    data_tailf-mobile-infra_geomonitor_podmonitor:
      Type: object
      Properties:
        tailf-mobile-infra:podmonitor:
         Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor"

    data_tailf-mobile-infra_geomonitor_podmonitor-post:
      Type: object
      Properties:
```

```
        tailf-mobile-infra:pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods"
          x-yang:
            Type: list
    data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name:
      Type: object
      Properties:
        tailf-mobile-infra:pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods"
          x-yang:
            Type: list

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent:

      Type: object
      Properties:
        tailf-mobile-infra:failedReplicaPercent:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name:
      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
   data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount:

      Type: object
      Properties:
        tailf-mobile-infra:retryCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval:

      Type: object
```

```
      Properties:
        tailf-mobile-infra:retryFailOverInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval:

      Type: object
      Properties:
        tailf-mobile-infra:retryInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor:
      Type: object
      Properties:
        tailf-mobile-infra:remoteclustermonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor"
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post:
      Type: object
      Properties:
        tailf-mobile-infra:retryCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:retryInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount:
      Type: object
      Properties:
        tailf-mobile-infra:retryCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval:

      Type: object
      Properties:
```

```
        tailf-mobile-infra:retryInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_trafficMonitor:
      Type: object
      Properties:
        tailf-mobile-infra:trafficMonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor"
    data_tailf-mobile-infra_geomonitor_trafficMonitor-post:
      Type: object
      Properties:
        tailf-mobile-infra:thresholdCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:thresholdInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount:
      Type: object
      Properties:
        tailf-mobile-infra:thresholdCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval:
      Type: object
      Properties:
        tailf-mobile-infra:thresholdInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra:
      Type: object
      Properties:
        tailf-mobile-infra:infra:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra"
    data_tailf-mobile-infra_infra-post:
      Type: object
```

```
      Properties:
        tailf-mobile-infra:metrics:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics"
        tailf-mobile-infra:transaction:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction"
        tailf-mobile-infra:k8-validation:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
          - enable
          - disable
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_k8-validation:
      Type: object
      Properties:
        tailf-mobile-infra:k8-validation:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
          - enable
          - disable
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_metrics:
      Type: object
      Properties:
        tailf-mobile-infra:metrics:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics"
    data_tailf-mobile-infra_infra_metrics-post:
      Type: object
      Properties:
        tailf-mobile-infra:experimental:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental"
        tailf-mobile-infra:verbose:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose"

    data_tailf-mobile-infra_infra_metrics_experimental:
      Type: object
      Properties:
        tailf-mobile-infra:experimental:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental"
    data_tailf-mobile-infra_infra_metrics_experimental-post:
      Type: object
      Properties:
        tailf-mobile-infra:version:
          Type: integer
```

```
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_infra_metrics_experimental_version:
      Type: object
      Properties:
        tailf-mobile-infra:version:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_metrics_verbose:
      Type: object
      Properties:
        tailf-mobile-infra:verbose:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose"

    data_tailf-mobile-infra_infra_metrics_verbose-post:
      Type: object
      Properties:
        tailf-mobile-infra:verboseLevels:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels"
          x-yang:
            Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType:

      Type: object
      Properties:
        tailf-mobile-infra:verboseLevels:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels"
          x-yang:
            Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level:

      Type: object
      Properties:
        tailf-mobile-infra:level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: production
```

```
          enum:
          - production
          - debug
          - trace
          - off
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics:

```
      Type: object
      Properties:
        tailf-mobile-infra:metrics:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics"
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:metricsList:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:metricsList:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id:

```
      Type: object
      Properties:
        tailf-mobile-infra:granular-labels:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level:

```
Type: object
Properties:
  tailf-mobile-infra:level:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: production
    enum:
    - production
    - debug
    - trace
    - off
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name:

```
Type: object
Properties:
  tailf-mobile-infra:name:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType:

```
Type: object
Properties:
  tailf-mobile-infra:podType:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods:

```
Type: object
Properties:
  tailf-mobile-infra:pods:
    Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods"
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:pod-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:pod-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level:

```
      Type: object
      Properties:
        tailf-mobile-infra:level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: production
          enum:
          - production
          - debug
          - trace
          - off
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:pod-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_transaction:
      Type: object
```

```
      Properties:
        tailf-mobile-infra:transaction:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction"
    data_tailf-mobile-infra_infra_transaction-post:
      Type: object
      Properties:
        tailf-mobile-infra:limit:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit"

        tailf-mobile-infra:loop:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop"

    data_tailf-mobile-infra_infra_transaction_limit:
      Type: object
      Properties:
        tailf-mobile-infra:limit:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit"

    data_tailf-mobile-infra_infra_transaction_limit-post:
      Type: object
      Properties:
        tailf-mobile-infra:stage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive"
    data_tailf-mobile-infra_infra_transaction_limit_consecutive:
      Type: object
      Properties:
        tailf-mobile-infra:consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive"
    data_tailf-mobile-infra_infra_transaction_limit_consecutive-post:
      Type: object
      Properties:
        tailf-mobile-infra:same:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same"
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same:
      Type: object
      Properties:
        tailf-mobile-infra:same:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same"
   data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post:

      Type: object
      Properties:
        tailf-mobile-infra:stage:
```

```
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage:
      Type: object
      Properties:
        tailf-mobile-infra:stage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_transaction_limit_stage:
      Type: object
      Properties:
        tailf-mobile-infra:stage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_infra_transaction_loop:
      Type: object
      Properties:
        tailf-mobile-infra:loop:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop"
    data_tailf-mobile-infra_infra_transaction_loop-post:
      Type: object
      Properties:
        tailf-mobile-infra:detection:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
          - enable
          - disable
          x-yang:
            Type: leaf
        tailf-mobile-infra:category:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category"
          x-yang:
            Type: list
    data_tailf-mobile-infra_infra_transaction_loop_category_category-name:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:category:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category"
          x-yang:
            Type: list

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name:

      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold:

      Type: object
      Properties:
        tailf-mobile-infra:threshold:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold"

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post:

      Type: object
      Properties:
        tailf-mobile-infra:interval:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        tailf-mobile-infra:thresholds:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds"

          x-yang:
            Type: list

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval:

      Type: object
      Properties:
```

```
        tailf-mobile-infra:interval:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:thresholds:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action:

```
      Type: object
      Properties:
        tailf-mobile-infra:action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: noop
          enum:
          - noop
          - log-event
          - kill-session
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count:

```
      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name:

```
      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
```

```
      Description: (leaf)
      Format: enumeration
      Default: low
      enum:
      - low
      - high
      x-yang:
        Type: leaf
data_tailf-mobile-infra_infra_transaction_loop_detection:
  Type: object
  Properties:
    tailf-mobile-infra:detection:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_instance:
  Type: object
  Properties:
    tailf-mobile-infra:instance:
      Reference: "#/components/schemas/datapost_tailfmobileinfrainstance"
data_tailf-mobile-infra_instance-post:
  Type: object
  Properties:
    tailf-mobile-infra:instance-id:
      Type: array
      Description: (list)
      Items:
       Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_instanceid"

      x-yang:
        Type: list
data_tailf-mobile-infra_instance_instance-id_instance-id-id:
  Type: object
  Properties:
    tailf-mobile-infra:instance-id:
      Type: array
      Description: (list)
      Items:
       Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_instanceid"

      x-yang:
        Type: list
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint:
  Type: object
  Properties:
    tailf-mobile-infra:endpoint:
      Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post:

```
Type: object
Properties:
  tailf-mobile-infra:ep:
    Type: array
    Description: (list)
    Items:
    Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep"

    x-yang:
      Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype:

```
Type: object
Properties:
  tailf-mobile-infra:ep:
    Type: array
    Description: (list)
    Items:
    Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep"

    x-yang:
      Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name:

```
Type: object
Properties:
  tailf-mobile-infra:certificate-name:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp:

```
Type: object
Properties:
  tailf-mobile-infra:dscp:
   Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dscp"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp-post:

```
Type: object
Properties:
  tailf-mobile-infra:value:
    Type: string
    Description: (leaf)
    Format: union
```

```
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value:

```
    Type: object
    Properties:
      tailf-mobile-infra:value:
        Type: string
        Description: (leaf)
        Format: union
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype:

```
    Type: object
    Properties:
      tailf-mobile-infra:eptype:
        Type: string
        Description: (leaf)
        Format: identityref
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype:

```
    Type: object
    Properties:
      tailf-mobile-infra:instancetype:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type:

```
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface"
        x-yang:
          Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name:

```
Type: object
Properties:
  tailf-mobile-infra:certificate-name:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher:

```
Type: object
Properties:
  tailf-mobile-infra:dispatcher:
    Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post:

```
Type: object
Properties:
  tailf-mobile-infra:count:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:capacity:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:outbound:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  tailf-mobile-infra:rate-limit:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:cache:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  tailf-mobile-infra:threshold:
    Type: integer
```

```
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:expiry:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:nonresponsive:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:flowctrl-group:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache

```
    Type: object
    Properties:
      tailf-mobile-infra:cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity

```
    Type: object
    Properties:
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count

```
    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
```

```
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-type_interface_interface-interface-type_dispatcher_expiry:

      Type: object
      Properties:
        tailf-mobile-infra:expiry:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-type_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name:

      Type: object
      Properties:
        tailf-mobile-infra:flowctrl-group:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup"
          x-yang:
            Type: list

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-type_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity:

      Type: object
      Properties:
        tailf-mobile-infra:capacity:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-type_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name:

      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-type_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_flow-capacity:

      Type: object
      Properties:
```

```
      tailf-mobile-infra:outbound-capacity:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep-ep-type_interface_interface-interface-type_dispatcher_flow-id-group_flow-id-group-name_outbound-rate-limit:

    Type: object
    Properties:
      tailf-mobile-infra:outbound-rate-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep-ep-type_interface_interface-interface-type_dispatcher_flow-id-group_flow-id-group-name_rate-limit:

    Type: object
    Properties:
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep-ep-type_interface_interface-interface-type_dispatcher_nonresponsive:

    Type: object
    Properties:
      tailf-mobile-infra:nonresponsive:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep-ep-type_interface_interface-interface-type_dispatcher_outbound:

    Type: object
    Properties:
      tailf-mobile-infra:outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep-ep-type_interface_interface-interface-type_dispatcher_rate-limit:

    Type: object
```

```
      Properties:
        tailf-mobile-infra:rate-limit:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold:

```
      Type: object
      Properties:
        tailf-mobile-infra:threshold:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype:

```
      Type: object
      Properties:
        tailf-mobile-infra:instancetype:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: IPv4
          enum:
          - IPv4
          - IPv6
          - Dual
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type:

```
      Type: object
      Properties:
        tailf-mobile-infra:interface-type:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal:

```
      Type: object
      Properties:
        tailf-mobile-infra:internal:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port:

```
      Type: object
      Properties:
        tailf-mobile-infra:base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_post:

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start:

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackEth:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackPort:
```

```
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor:

```
      Type: object
      Properties:
        tailf-mobile-infra:monitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:protocol:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: on
          enum:
          - on
          - off
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol:

```
      Type: object
      Properties:
        tailf-mobile-infra:protocol:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: on
          enum:
          - on
          - off
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable:

```
      Type: object
      Properties:
        tailf-mobile-infra:mtls-enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-type_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6

```
      Type: object
      Properties:
        tailf-mobile-infra:sec-vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-type_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_offline

```
      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-type_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_sec-vip-ipv6

```
      Type: object
      Properties:
        tailf-mobile-infra:sec-vip-ipv6:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-type_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vip-interface

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-type_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vip-ipv6-port

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-ipv6-port:
          Type: integer
          Description: (leaf)
```

```
          Format: uint16
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instance-id_instance-id_endpoint_ep_ep_eptype_interface_interface_interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instance-id_instance-id_endpoint_ep_ep_eptype_interface_interface_interface-type_sec-vip_sec-vip_sec-vip-ip:

      Type: object
      Properties:
        tailf-mobile-infra:sec-vip:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip"
          x-yang:
            Type: list

data_tailfmobileinfrainstance_instance_instance-id_instance-id_endpoint_ep_ep_eptype_interface_interface_interface-type_sec-vip_sec-vip_sec-vip-ip_offline:

      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instance-id_instance-id_endpoint_ep_ep_eptype_interface_interface_interface-type_sec-vip_sec-vip_sec-vip-ip_sec-vip-ip:

      Type: object
      Properties:
        tailf-mobile-infra:sec-vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instance-id_instance-id_endpoint_ep_ep_eptype_interface_interface_interface-type_sec-vip_sec-vip_sec-vip-ip_vip-interface:

      Type: object
      Properties:
```

```
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip_vip-port:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip-port:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip_vrf:

```
    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        Format: leafref
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla:

```
    Type: object
    Properties:
      tailf-mobile-infra:sla:
       Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:procedure:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure:

```
Type: object
Properties:
  tailf-mobile-infra:procedure:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response:

```
Type: object
Properties:
  tailf-mobile-infra:response:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable:

```
Type: object
Properties:
  tailf-mobile-infra:tls-enable:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme:

```
Type: object
Properties:
  tailf-mobile-infra:uri-scheme:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: http
    enum:
    - http
    - https
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6:

```
Type: object
Properties:
  tailf-mobile-infra:vip6:
    Type: array
```

```
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6"
        x-yang:
          Type: list

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-e_type_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline:

    Type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-e_type_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface:

    Type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-e_type_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6:

    Type: object
    Properties:
      tailf-mobile-infra:vip-ipv6:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-e_type_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port:

    Type: object
    Properties:
      tailf-mobile-infra:vip-ipv6-port:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-e_type_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf:

    Type: object
```

```
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_interface_interface-interface-type_vip_vip-vip-ip

```
      Type: object
      Properties:
        tailf-mobile-infra:vip:
          Type: array
          Description: (list)
          Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip"

          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_interface_interface-interface-type_vip_vip-vip-ip_offline

```
      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port:

```
Type: object
Properties:
  tailf-mobile-infra:vip-port:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf:

```
Type: object
Properties:
  tailf-mobile-infra:vrf:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf:

```
Type: object
Properties:
  tailf-mobile-infra:vrf:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal:

```
Type: object
Properties:
  tailf-mobile-infra:internal:
    Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post:

```
Type: object
Properties:
  tailf-mobile-infra:base-port:
    Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port:

```
Type: object
Properties:
```

```
        tailf-mobile-infra:base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start:

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackEth:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackPort:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor:

```
      Type: object
      Properties:
        tailf-mobile-infra:monitor:
          Reference:
```

"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor"

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post:

```
Type: object
Properties:
  tailf-mobile-infra:protocol:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: on
    enum:
    - on
    - off
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol:

```
Type: object
Properties:
  tailf-mobile-infra:protocol:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: on
    enum:
    - on
    - off
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable:

```
Type: object
Properties:
  tailf-mobile-infra:mtls-enable:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes:

```
Type: object
Properties:
  tailf-mobile-infra:nodes:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas:

```
      Type: object
      Properties:
        tailf-mobile-infra:replicas:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:service:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_service"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type:

```
      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:certificate-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher:

```
      Type: object
      Properties:
        tailf-mobile-infra:dispatcher:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher"
```

data/tailf-mobile-infra:instance/instance-id/endpoint-type/service-type/service-name/interface-name/interface-type/dispatcher-ip:

```
Type: object
Properties:
  tailf-mobile-infra:count:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:capacity:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:outbound:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  tailf-mobile-infra:rate-limit:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:cache:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  tailf-mobile-infra:threshold:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:expiry:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:nonresponsive:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:flowctrl-group:
```

```
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep-type_ep-type_service_service-name_service-name_interface_interface-name_interface-type_dispatcher_cache

```
      Type: object
      Properties:
        tailf-mobile-infra:cache:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep-type_ep-type_service_service-name_service-name_interface_interface-name_interface-type_dispatcher_capacity

```
      Type: object
      Properties:
        tailf-mobile-infra:capacity:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep-type_ep-type_service_service-name_service-name_interface_interface-name_interface-type_dispatcher_count

```
      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep-type_ep-type_service_service-name_service-name_interface_interface-name_interface-type_dispatcher_expiry

```
      Type: object
      Properties:
        tailf-mobile-infra:expiry:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep-type_ep-type_service_service-name_service-name_interface_interface-name_interface-type_dispatcher_flowctrlgroup_flowctrlgroup-name

```
      Type: object
```

```
      Properties:
        tailf-mobile-infra:flowctrl-group:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup"
          x-yang:
            Type: list

datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup_capacity:

      Type: object
      Properties:
        tailf-mobile-infra:capacity:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup_name:

      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup_outbound_capacity:

      Type: object
      Properties:
        tailf-mobile-infra:outbound-capacity:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup_outbound_rate_limit:

      Type: object
      Properties:
        tailf-mobile-infra:outbound-rate-limit:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep-type/service/service-service-name/interface/interface-interface-type/dispatcher/fod-group/fod-group-name/rate-limit

```
Type: object
Properties:
  tailf-mobile-infra:rate-limit:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep-type/service/service-service-name/interface/interface-interface-type/dispatcher/nonresponsive

```
Type: object
Properties:
  tailf-mobile-infra:nonresponsive:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep-type/service/service-service-name/interface/interface-interface-type/dispatcher/outbound

```
Type: object
Properties:
  tailf-mobile-infra:outbound:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep-type/service/service-service-name/interface/interface-interface-type/dispatcher/rate-limit

```
Type: object
Properties:
  tailf-mobile-infra:rate-limit:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep-type/service/service-service-name/interface/interface-interface-type/dispatcher/threshold

```
Type: object
Properties:
  tailf-mobile-infra:threshold:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
```

```
          Type: leaf

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinstancetype:

      Type: object
      Properties:
        tailf-mobile-infra:instancetype:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: IPv4
          enum:
          - IPv4
          - IPv6
          - Dual
          x-yang:
            Type: leaf

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinterfacetype:

      Type: object
      Properties:
        tailf-mobile-infra:interface-type:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinternal:

      Type: object
      Properties:
        tailf-mobile-infra:internal:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal"

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinternalport:

      Type: object
      Properties:
        tailf-mobile-infra:base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinternalbaseport:

      Type: object
      Properties:
        tailf-mobile-infra:base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"

datatailfmobileinfrainstanceinstanceidinstanceidendpointpeertypeservicesservicenameinterfaceinterfacetypeinternalbaseportport:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailfmobileinfrainstance_instance-id_instance-id_endpoint_ep-ep-type_service_service-service-name_interface_interface-interface-type_internalBaseport_start:

```
      Type: object
      Properties:
        tailf-mobile-infra:start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailfmobileinfrainstance_instance-id_instance-id_endpoint_ep-ep-type_service_service-service-name_interface_interface-interface-type_loopbackEth:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackEth:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailfmobileinfrainstance_instance-id_instance-id_endpoint_ep-ep-type_service_service-service-name_interface_interface-interface-type_loopbackPort:

```
      Type: object
      Properties:
        tailf-mobile-infra:loopbackPort:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailfmobileinfrainstance_instance-id_instance-id_endpoint_ep-ep-type_service_service-service-name_interface_interface-interface-type_monitor:

```
      Type: object
      Properties:
        tailf-mobile-infra:monitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor"
```

data_tailfmobileinfrainstance_instance-id_instance-id_endpoint_ep-ep-type_service_service-service-name_interface_interface-interface-type_monitor_port:

```
      Type: object
      Properties:
```

```
        tailf-mobile-infra:protocol:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: on
          enum:
          - on
          - off
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instanceid_endpoint_epeptype_service_servicename_interface_interfacetype_protocol:

      Type: object
      Properties:
        tailf-mobile-infra:protocol:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: on
          enum:
          - on
          - off
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instanceid_endpoint_epeptype_service_servicename_interface_interfacetype_mtlsenable

      Type: object
      Properties:
        tailf-mobile-infra:mtls-enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_tailfmobileinfrainstance_instance_instanceid_endpoint_epeptype_service_servicename_interface_interfacetype_secvip6_secvip6ipv6

      Type: object
      Properties:
        tailf-mobile-infra:sec-vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6"
          x-yang:
            Type: list

data_tailfmobileinfrainstance_instance_instanceid_endpoint_epeptype_service_servicename_interface_interfacetype_secvip6_secvip6ipv6offline

      Type: object
      Properties:
        tailf-mobile-infra:offline:
```

```
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf

/data/tailf-mobile-infra:instance/instance-id/object-type/service/service-interface/interface-type/sec-vip-ipv6/sec-vip-ipv6

      Type: object
      Properties:
        tailf-mobile-infra:sec-vip-ipv6:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

/data/tailf-mobile-infra:instance/instance-id/object-type/service/service-interface/interface-type/sec-vip-ipv6/vip-interface

      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

/data/tailf-mobile-infra:instance/instance-id/object-type/service/service-interface/interface-type/sec-vip-ipv6/vip-ipv6-port

      Type: object
      Properties:
        tailf-mobile-infra:vip-ipv6-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

/data/tailf-mobile-infra:instance/instance-id/object-type/service/service-interface/interface-type/sec-vip-ipv6/vrf

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

/data/tailf-mobile-infra:instance/instance-id/object-type/service/service-interface/interface-type/sec-vip/sec-vip

      Type: object
```

```
      Properties:
        tailf-mobile-infra:sec-vip:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip"
          x-yang:
            Type: list

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_sec_vip_sec_vip_offline

      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_sec_vip_sec_vip_sec_vip_ip

      Type: object
      Properties:
        tailf-mobile-infra:sec-vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_sec_vip_sec_vip_vip_interface

      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_sec_vip_sec_vip_vip_port

      Type: object
      Properties:
        tailf-mobile-infra:vip-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_p_p-type_service_service-service-name_interface_interface-interface-type_service-ip_service-ip_service-ip_ipv_vrf

```
Type: object
Properties:
  tailf-mobile-infra:vrf:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_p_p-type_service_service-service-name_interface_interface-interface-type_sla

```
Type: object
Properties:
  tailf-mobile-infra:sla:
   Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla"
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_p_p-type_service_service-service-name_interface_interface-interface-type_sla_post

```
Type: object
Properties:
  tailf-mobile-infra:response:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
  tailf-mobile-infra:procedure:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_p_p-type_service_service-service-name_interface_interface-interface-type_sla_procedure

```
Type: object
Properties:
  tailf-mobile-infra:procedure:
    Type: integer
    Description: (leaf)
    Format: int32
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_p_p-type_service_service-service-name_interface_interface-interface-type_sla_response

```
Type: object
Properties:
  tailf-mobile-infra:response:
    Type: integer
```

```
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_type_type_service_service-service-name_interface_interface-interface-type_tls-enable

      Type: object
      Properties:
        tailf-mobile-infra:tls-enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_type_type_service_service-service-name_interface_interface-interface-type_uri-scheme

      Type: object
      Properties:
        tailf-mobile-infra:uri-scheme:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: http
          enum:
          - http
          - https
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_type_type_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6

      Type: object
      Properties:
        tailf-mobile-infra:vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6"
          x-yang:
            Type: list

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_type_type_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline

      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
```

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_vip_vip_vip_interface

```
Type: object
Properties:
  tailf-mobile-infra:vip-interface:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_vip_vip_vip_ipv6

```
Type: object
Properties:
  tailf-mobile-infra:vip-ipv6:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_vip_vip_vip_ipv6_port

```
Type: object
Properties:
  tailf-mobile-infra:vip-ipv6-port:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_vip_vip_vip_vrf

```
Type: object
Properties:
  tailf-mobile-infra:vrf:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

datapost_tailfmobileinfrainstance_instance_instance_id_endpoint_type_service_service_name_interface_interface_type_vip_vip_vip

```
Type: object
Properties:
  tailf-mobile-infra:vip:
    Type: array
    Description: (list)
    Items:
    Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip"
```

```
        x-yang:
          Type: list

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep/ep-type/service/service-service-name/interface/interface-interface-type/vip/vip-vip-ip/offline

      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep/ep-type/service/service-service-name/interface/interface-interface-type/vip/vip-vip-ip/vip-interface

      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep/ep-type/service/service-service-name/interface/interface-interface-type/vip/vip-vip-ip/vip-ip

      Type: object
      Properties:
        tailf-mobile-infra:vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep/ep-type/service/service-service-name/interface/interface-interface-type/vip/vip-vip-ip/vip-port

      Type: object
      Properties:
        tailf-mobile-infra:vip-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data/tailf-mobile-infra:instance/instance-id/instance-id/endpoint/ep-ep/ep-type/service/service-service-name/interface/interface-interface-type/vip/vip-vip-ip/vrf

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
```

```
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf:

```
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:service-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level:

```
      Type: object
      Properties:
        tailf-mobile-infra:system-health-level:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:warn:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
        tailf-mobile-infra:critical:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
        tailf-mobile-infra:crash:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash:

```
      Type: object
      Properties:
        tailf-mobile-infra:crash:
```

```
        Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs:

```
    Type: object
    Properties:
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine:

```
    Type: object
    Properties:
      tailf-mobile-infra:num-of-goroutine:
```

```
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical:

```
      Type: object
      Properties:
        tailf-mobile-infra:critical:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post:

```
      Type: object
      Properties:
        tailf-mobile-infra:cpu-percent:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:memory-in-mbs:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:num-of-goroutine:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent:

```
      Type: object
      Properties:
        tailf-mobile-infra:cpu-percent:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs:

```
      Type: object
      Properties:
        tailf-mobile-infra:memory-in-mbs:
```

```
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine:

```
    Type: object
    Properties:
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn:

```
    Type: object
    Properties:
      tailf-mobile-infra:warn:
        Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
```

```
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs:

```
      Type: object
      Properties:
        tailf-mobile-infra:memory-in-mbs:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine:

```
      Type: object
      Properties:
        tailf-mobile-infra:num-of-goroutine:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme:

```
      Type: object
      Properties:
        tailf-mobile-infra:uri-scheme:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: http
          enum:
          - http
          - https
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6"
          x-yang:
```

```
          Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline:

```
      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-ipv6:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-ipv6-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf:

```
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
```

```
          Format: leafref
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip:
          Type: array
          Description: (list)
          Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip"

          x-yang:
            Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline:

```
      Type: object
      Properties:
        tailf-mobile-infra:offline:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip:

```
      Type: object
      Properties:
        tailf-mobile-infra:vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port:

```
      Type: object
      Properties:
```

```
        tailf-mobile-infra:vip-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_instance_instance-id_instance-id-id_id:
      Type: object
      Properties:
        tailf-mobile-infra:id:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_instances:
      Type: object
      Properties:
        tailf-mobile-infra:instances:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainstances"
    data_tailf-mobile-infra_instances-post:
      Type: object
      Properties:
        tailf-mobile-infra:instance:
          Type: array
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrainstances_instance"

          x-yang:
            Type: list
    data_tailf-mobile-infra_instances_instance_instance-instance-id:
      Type: object
      Properties:
        tailf-mobile-infra:instance:
          Type: array
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrainstances_instance"

          x-yang:
```

```
          Type: list

data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id:

     Type: object
     Properties:
       tailf-mobile-infra:cluster-id:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id:

     Type: object
     Properties:
       tailf-mobile-infra:instance-id:
         Type: integer
         Description: (leaf)
         Format: int32
         x-yang:
           Type: leaf

data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name:

     Type: object
     Properties:
       tailf-mobile-infra:slice-name:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf

data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id:

     Type: object
     Properties:
       tailf-mobile-infra:system-id:
         Type: string
         Description: (leaf)
         Format: string
         x-yang:
           Type: leaf
   data_tailf-mobile-infra_k8:
     Type: object
     Properties:
       tailf-mobile-infra:k8:
         Reference: "#/components/schemas/datapost_tailfmobileinfrak8"
   data_tailf-mobile-infra_k8-post:
     Type: object
     Properties:
```

```
        tailf-mobile-infra:label:
          Reference: "#/components/schemas/datapost_tailfmobileinfrak8_label"
    data_tailf-mobile-infra_k8_label:
      Type: object
      Properties:
        tailf-mobile-infra:label:
          Reference: "#/components/schemas/datapost_tailfmobileinfrak8_label"
    data_tailf-mobile-infra_k8_label-post:
      Type: object
      Properties:
        tailf-mobile-infra:pod-group-config:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig"
          x-yang:
            Type: list

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value:

      Type: object
      Properties:
        tailf-mobile-infra:pod-group-config:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig"
          x-yang:
            Type: list

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key:

      Type: object
      Properties:
        tailf-mobile-infra:key:
          Type: string
          Description: Key for the label (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group:

      Type: object
      Properties:
        tailf-mobile-infra:pod-group:
          Type: string
          Description: Group for the VMs (leaf)
          Format: enumeration
          Default: protocol-layer
          enum:
```

```
          - protocol-layer
          - service-layer
          - cdl-layer
          - oam-layer
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config_pod-group_pod-group-config-key_pod-group-config-value_value:

```
      Type: object
      Properties:
        tailf-mobile-infra:value:
          Type: string
          Description: Value for the label (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_load:
      Type: object
      Properties:
        tailf-mobile-infra:load:
          Reference: "#/components/schemas/datapost_tailfmobileinfraload"
    data_tailf-mobile-infra_load-post:
      Type: object
      Properties:
        tailf-mobile-infra:factor:
          Reference: "#/components/schemas/datapost_tailfmobileinfraload_factor"
    data_tailf-mobile-infra_load_factor:
      Type: object
      Properties:
        tailf-mobile-infra:factor:
          Reference: "#/components/schemas/datapost_tailfmobileinfraload_factor"
    data_tailf-mobile-infra_load_factor-post:
      Type: object
      Properties:
        tailf-mobile-infra:calc-frequency:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:exclude-pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraload_factor_excludepods"
          x-yang:
            Type: list
    data_tailf-mobile-infra_load_factor_calc-frequency:
      Type: object
      Properties:
        tailf-mobile-infra:calc-frequency:
```

```
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type:

      Type: object
      Properties:
        tailf-mobile-infra:exclude-pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraload_factor_excludepods"
          x-yang:
            Type: list

  data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type:

      Type: object
      Properties:
        tailf-mobile-infra:pod-type:
          Type: string
          Description: Default set to exclude all infra-pods (leaf)
          Format: identityref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_local-instance:
      Type: object
      Properties:
        tailf-mobile-infra:local-instance:
          Reference: "#/components/schemas/datapost_tailfmobileinfralocalinstance"
    data_tailf-mobile-infra_local-instance-post:
      Type: object
      Properties:
        tailf-mobile-infra:instance:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_local-instance_instance:
      Type: object
      Properties:
        tailf-mobile-infra:instance:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:logging:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging"
    data_tailf-mobile-infra_logging-post:
      Type: object
      Properties:
        tailf-mobile-infra:transaction:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_transaction"

        tailf-mobile-infra:level:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_level"
        tailf-mobile-infra:json-logging:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_jsonlogging"

        tailf-mobile-infra:logger:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfralogging_logger"
          x-yang:
            Type: list
        tailf-mobile-infra:async:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_async"
        tailf-mobile-infra:error:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_error"
    data_tailf-mobile-infra_logging_async:
      Type: object
      Properties:
        tailf-mobile-infra:async:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_async"
    data_tailf-mobile-infra_logging_async-post:
      Type: object
      Properties:
        tailf-mobile-infra:application:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        tailf-mobile-infra:transaction:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        tailf-mobile-infra:tracing:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        tailf-mobile-infra:monitor-subscriber:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
    data_tailf-mobile-infra_logging_async_application:
      Type: object
      Properties:
        tailf-mobile-infra:application:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
    data_tailf-mobile-infra_logging_async_application-post:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_application_disable:
      Type: object
      Properties:
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_application_enable:
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
    data_tailf-mobile-infra_logging_async_application_enable-post:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_application_enable_buffer-size:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_monitor-subscriber:
      Type: object
      Properties:
        tailf-mobile-infra:monitor-subscriber:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
    data_tailf-mobile-infra_logging_async_monitor-subscriber-post:
      Type: object
```

```
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_monitor-subscriber_disable:
      Type: object
      Properties:
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_monitor-subscriber_enable:
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
    data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size:

      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_tracing:
      Type: object
      Properties:
        tailf-mobile-infra:tracing:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
    data_tailf-mobile-infra_logging_async_tracing-post:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_tracing_disable:
      Type: object
      Properties:
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_tracing_enable:
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
    data_tailf-mobile-infra_logging_async_tracing_enable-post:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_transaction:
      Type: object
      Properties:
        tailf-mobile-infra:transaction:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
    data_tailf-mobile-infra_logging_async_transaction-post:
      Type: object
```

```
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_transaction_disable:
      Type: object
      Properties:
        tailf-mobile-infra:disable:
          Type: string
          Description: (leaf)
          Format: [null]
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_transaction_enable:
      Type: object
      Properties:
        tailf-mobile-infra:enable:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
    data_tailf-mobile-infra_logging_async_transaction_enable-post:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size:
      Type: object
      Properties:
        tailf-mobile-infra:buffer-size:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_error:
      Type: object
      Properties:
        tailf-mobile-infra:error:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_error"
    data_tailf-mobile-infra_logging_error-post:
      Type: object
      Properties:
        tailf-mobile-infra:stack:
```

```
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_error_stack:
  Type: object
  Properties:
    tailf-mobile-infra:stack:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_json-logging:
  Type: object
  Properties:
    tailf-mobile-infra:json-logging:
      Reference: "#/components/schemas/datapost_tailfmobileinfralogging_jsonlogging"

data_tailf-mobile-infra_logging_json-logging-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_json-logging_application:
  Type: object
  Properties:
```

```
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_json-logging_monitor-subscriber:
  Type: object
  Properties:
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_json-logging_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level:
  Type: object
  Properties:
    tailf-mobile-infra:level:
      Reference: "#/components/schemas/datapost_tailfmobileinfralogging_level"
data_tailf-mobile-infra_logging_level-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
```

```
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_application:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_monitor-subscriber:
  Type: object
  Properties:
    tailf-mobile-infra:monitor-subscriber:
```

```
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_tracing:
  Type: object
  Properties:
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_logger_logger-name:
  Type: object
  Properties:
    tailf-mobile-infra:logger:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfralogging_logger"
```

```
      x-yang:
        Type: list
data_tailf-mobile-infra_logging_logger_logger-name_level:
  Type: object
  Properties:
    tailf-mobile-infra:level:
      Reference: "#/components/schemas/datapost_tailfmobileinfralogging_level"
data_tailf-mobile-infra_logging_logger_logger-name_level-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
```

```
        Format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - off
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_logging_logger_logger-name_level_application:
      Type: object
      Properties:
        tailf-mobile-infra:application:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: trace
          enum:
          - trace
          - debug
          - info
          - warn
          - error
          - off
          x-yang:
            Type: leaf

  data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber:

      Type: object
      Properties:
        tailf-mobile-infra:monitor-subscriber:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: trace
          enum:
          - trace
          - debug
          - info
          - warn
          - error
          - off
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_logging_logger_logger-name_level_tracing:
      Type: object
      Properties:
        tailf-mobile-infra:tracing:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: trace
```

```
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_logger_logger-name_level_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_logger_logger-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Reference: "#/components/schemas/datapost_tailfmobileinfralogging_transaction"

data_tailf-mobile-infra_logging_transaction-post:
  Type: object
  Properties:
    tailf-mobile-infra:persist:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
```

```
    tailf-mobile-infra:max-file-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:max-rotation:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:message:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    tailf-mobile-infra:duplicate:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_duplicate:
  Type: object
  Properties:
    tailf-mobile-infra:duplicate:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_max-file-size:
  Type: object
  Properties:
    tailf-mobile-infra:max-file-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
```

```
      Type: leaf
data_tailf-mobile-infra_logging_transaction_max-rotation:
  Type: object
  Properties:
    tailf-mobile-infra:max-rotation:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_message:
  Type: object
  Properties:
    tailf-mobile-infra:message:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_persist:
  Type: object
  Properties:
    tailf-mobile-infra:persist:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_monitor:
  Type: object
  Properties:
    tailf-mobile-infra:monitor:
      Reference: "#/components/schemas/datapost_tailfmobileinframonitor"
data_tailf-mobile-infra_monitor-post:
  Type: object
  Properties:
    tailf-mobile-infra:bfd:
      Reference: "#/components/schemas/datapost_tailfmobileinframonitor_bfd"
    tailf-mobile-infra:protocol:
      Reference: "#/components/schemas/datapost_tailfmobileinframonitor_protocol"
    tailf-mobile-infra:nf:
      Type: object
      Properties: {}
      Description: (non-presence)
```

```
          x-yang:
            Type: container
            is_presence: false
        tailf-mobile-infra:internal-vip-ipc:
        Reference: "#/components/schemas/datapost_tailfmobileinframonitor_internalvipipc"

        tailf-mobile-infra:active-instance-traffic:
          Reference:
"#/components/schemas/datapost_tailfmobileinframonitor_activeinstancetraffic"
    data_tailf-mobile-infra_monitor_active-instance-traffic:
      Type: object
      Properties:
        tailf-mobile-infra:active-instance-traffic:
          Reference:
"#/components/schemas/datapost_tailfmobileinframonitor_activeinstancetraffic"
    data_tailf-mobile-infra_monitor_active-instance-traffic-post:
      Type: object
      Properties:
        tailf-mobile-infra:no-traffic-duration:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:session-threshold:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: pod-restart
          enum:
          - pod-restart
          - trigger-switch-over
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_monitor_active-instance-traffic_action:
      Type: object
      Properties:
        tailf-mobile-infra:action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: pod-restart
          enum:
          - pod-restart
          - trigger-switch-over
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration:

Type: object
Properties:
tailf-mobile-infra:no-traffic-duration:
Type: integer
Description: (leaf)
Format: int32
x-yang:
Type: leaf

data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold:

Type: object
Properties:
tailf-mobile-infra:session-threshold:
Type: integer
Description: (leaf)
Format: int32
x-yang:
Type: leaf

data_tailf-mobile-infra_monitor_bfd:
Type: object
Properties:
tailf-mobile-infra:bfd:
Reference: "#/components/schemas/datapost_tailfmobileinframonitor_bfd"

data_tailf-mobile-infra_monitor_bfd-post:
Type: object
Properties:
tailf-mobile-infra:node-status:
Type: string
Description: (leaf)
Format: [null]
x-yang:
Type: leaf

data_tailf-mobile-infra_monitor_bfd_node-status:
Type: object
Properties:
tailf-mobile-infra:node-status:
Type: string
Description: (leaf)
Format: [null]
x-yang:
Type: leaf

data_tailf-mobile-infra_monitor_internal-vip-ipc:
Type: object
Properties:
tailf-mobile-infra:internal-vip-ipc:
Reference: "#/components/schemas/datapost_tailfmobileinframonitor_internalvipipc"

data_tailf-mobile-infra_monitor_internal-vip-ipc-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:max-conn-downtime:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime:
    Type: object
    Properties:
      tailf-mobile-infra:max-conn-downtime:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_monitor_nf:
    Type: object
    Properties:
      tailf-mobile-infra:nf:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
  data_tailf-mobile-infra_monitor_nf-post:
    Type: object
  data_tailf-mobile-infra_monitor_protocol:
    Type: object
    Properties:
      tailf-mobile-infra:protocol:
        Reference: "#/components/schemas/datapost_tailfmobileinframonitor_protocol"
  data_tailf-mobile-infra_monitor_protocol-post:
    Type: object
    Properties:
      tailf-mobile-infra:cpu-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_monitor_protocol_cpu-limit:
    Type: object
    Properties:
      tailf-mobile-infra:cpu-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
```

```
      Type: leaf
data_tailf-mobile-infra_nodemonitor:
  Type: object
  Properties:
    tailf-mobile-infra:nodemonitor:
      Reference: "#/components/schemas/datapost_tailfmobileinfranodemonitor"
data_tailf-mobile-infra_nodemonitor-post:
  Type: object
  Properties:
    tailf-mobile-infra:mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: 0
      enum:
      - 0
      - 1
      - 2
      - 3
      x-yang:
        Type: leaf
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_nodemonitor_interval:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_nodemonitor_mode:
  Type: object
  Properties:
    tailf-mobile-infra:mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: 0
      enum:
      - 0
      - 1
      - 2
      - 3
      x-yang:
        Type: leaf
data_tailf-mobile-infra_peers:
  Type: object
```

```
      Properties:
        tailf-mobile-infra:peers:
          Reference: "#/components/schemas/datapost_tailfmobileinfrapeers"
    data_tailf-mobile-infra_peers-post:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
    data_tailf-mobile-infra_peers_all:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress:

```
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_additionalDetails:

```
      Type: object
      Properties:
        tailf-mobile-infra:additionalDetails:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_connectedTime:

```
      Type: object
      Properties:
        tailf-mobile-infra:connectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_direction:

```
      Type: object
      Properties:
        tailf-mobile-infra:direction:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_endpoint:

```
      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_grInstance:

```
      Type: object
      Properties:
        tailf-mobile-infra:grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_interfaceName:

```
Type: object
Properties:
  tailf-mobile-infra:interfaceName:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_localAddress:

```
Type: object
Properties:
  tailf-mobile-infra:localAddress:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_peerAddress:

```
Type: object
Properties:
  tailf-mobile-infra:peerAddress:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_podInstance:

```
Type: object
Properties:
  tailf-mobile-infra:podInstance:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_rpc:

```
Type: object
Properties:
  tailf-mobile-infra:rpc:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
```

```
          Type: leaf

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_type:

      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_peers_ipv4:
      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress:

      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_additionalDetails:

      Type: object
      Properties:
        tailf-mobile-infra:additionalDetails:
          Type: string
          Description: (leaf)
```

```
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_connectedTime:

```
      Type: object
      Properties:
        tailf-mobile-infra:connectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_direction:

```
      Type: object
      Properties:
        tailf-mobile-infra:direction:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_endpoint:

```
      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_grInstance:

```
      Type: object
      Properties:
        tailf-mobile-infra:grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_interfaceName:

```
      Type: object
      Properties:
        tailf-mobile-infra:interfaceName:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_localAddress:

```
      Type: object
      Properties:
        tailf-mobile-infra:localAddress:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_peerAddress:

```
      Type: object
      Properties:
        tailf-mobile-infra:peerAddress:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_podInstance:

```
      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_rpc:

```
      Type: object
      Properties:
        tailf-mobile-infra:rpc:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_type:

```
      Type: object
```

```
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv4_ipv4-grInstance_ipv4-endpoint_ipv4-localAddress_ipv4-peerAddress_vrf:

```
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_peers_ipv6:
      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress:

```
      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_additionalDetails:

```
      Type: object
      Properties:
        tailf-mobile-infra:additionalDetails:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_connectedTime:

```
      Type: object
      Properties:
        tailf-mobile-infra:connectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_direction:

```
      Type: object
      Properties:
        tailf-mobile-infra:direction:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_endpoint:

```
      Type: object
      Properties:
        tailf-mobile-infra:endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_grInstance:

```
      Type: object
      Properties:
        tailf-mobile-infra:grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_interfaceName:

```
      Type: object
      Properties:
        tailf-mobile-infra:interfaceName:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_localAddress:

```
Type: object
Properties:
  tailf-mobile-infra:localAddress:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_peerAddress:

```
Type: object
Properties:
  tailf-mobile-infra:peerAddress:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_podInstance:

```
Type: object
Properties:
  tailf-mobile-infra:podInstance:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_rpc:

```
Type: object
Properties:
  tailf-mobile-infra:rpc:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_type:

```
Type: object
Properties:
  tailf-mobile-infra:type:
    Type: string
    Description: (leaf)
    Format: string
```

```
        x-yang:
          Type: leaf
data_tailf-mobile-infra_peers_ipv6_ipv6-grInstance_ipv6-endpoint_ipv6-localAddress_ipv6-peerAddress_vrf:
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_resource:
      Type: object
      Properties:
        tailf-mobile-infra:resource:
          Reference: "#/components/schemas/datapost_tailfmobileinfraresource"
    data_tailf-mobile-infra_resource-post:
      Type: object
      Properties:
        tailf-mobile-infra:pod:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraresource_pod"
          x-yang:
            Type: list
    data_tailf-mobile-infra_resource_pod_pod-podtype:
      Type: object
      Properties:
        tailf-mobile-infra:pod:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfraresource_pod"
          x-yang:
            Type: list
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu:
      Type: object
      Properties:
        tailf-mobile-infra:cpu:
          Reference: "#/components/schemas/datapost_tailfmobileinfraresource_cpu"
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post:
      Type: object
      Properties:
        tailf-mobile-infra:request:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
```

```
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit:
  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc:
  Type: object
  Properties:
    tailf-mobile-infra:gomaxproc:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels:
  Type: object
  Properties:
    tailf-mobile-infra:labels:
      Reference: "#/components/schemas/datapost_tailfmobileinfraresource_labels"
data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post:
  Type: object
  Properties:
    tailf-mobile-infra:key:
      Type: string
      Description: Key for the label (leaf)
      Format: string
      x-yang:
        Type: leaf
    tailf-mobile-infra:value:
      Type: string
      Description: Value for the label (leaf)
      Format: string
```

```
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key:
  Type: object
  Properties:
    tailf-mobile-infra:key:
      Type: string
      Description: Key for the label (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value:
  Type: object
  Properties:
    tailf-mobile-infra:value:
      Type: string
      Description: Value for the label (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory:
  Type: object
  Properties:
    tailf-mobile-infra:memory:
      Reference: "#/components/schemas/datapost_tailfmobileinfraresource_memory"
data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:gomemlimit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:gogc:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
```

```
      Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc:
  Type: object
  Properties:
    tailf-mobile-infra:gogc:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit:
  Type: object
  Properties:
    tailf-mobile-infra:gomemlimit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit:
  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_podtype:
  Type: object
  Properties:
    tailf-mobile-infra:podtype:
      Type: string
      Description: (leaf)
      Format: identityref
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resources:
  Type: object
  Properties:
    tailf-mobile-infra:resources:
      Reference: "#/components/schemas/datapost_tailfmobileinfraresources"
```

```
data_tailf-mobile-infra_resources-post:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresources_info"
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresources_info"
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info_info-podInstance:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresources_info"
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info_info-podInstance_cpuUsage:
  Type: object
  Properties:
    tailf-mobile-infra:cpuUsage:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resources_info_info-podInstance_diskUsageInKbps:
  Type: object
  Properties:
    tailf-mobile-infra:diskUsageInKbps:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resources_info_info-podInstance_gcCount:
  Type: object
  Properties:
```

```
      tailf-mobile-infra:gcCount:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_resources_info_info-podInstance_gcPauseInNS:
      Type: object
      Properties:
        tailf-mobile-infra:gcPauseInNS:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_goRoutinesCount:
      Type: object
      Properties:
        tailf-mobile-infra:goRoutinesCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_resources_info_info-podInstance_loadFactor:
      Type: object
      Properties:
        tailf-mobile-infra:loadFactor:
          Type: number
          Description: (leaf)
          Format: double
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_resources_info_info-podInstance_podInstance:
      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_totalNodeMemoryInMB:
      Type: object
      Properties:
        tailf-mobile-infra:totalNodeMemoryInMB:
          Type: integer
          Description: (leaf)
          Format: int32
```

```
        x-yang:
          Type: leaf
data_tailf-mobile-infra_resources_info_info-podInstance_usedPodMemoryInMB:
    Type: object
    Properties:
      tailf-mobile-infra:usedPodMemoryInMB:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router:
    Type: object
    Properties:
      tailf-mobile-infra:router:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter"
  data_tailf-mobile-infra_router-post:
    Type: object
    Properties:
      tailf-mobile-infra:bgplist:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bgplist"
        x-yang:
          Type: list
      tailf-mobile-infra:bfd:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1"
      tailf-mobile-infra:monitor-interface:
       Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface"

  data_tailf-mobile-infra_router_bfd:
    Type: object
    Properties:
      tailf-mobile-infra:bfd:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1"
  data_tailf-mobile-infra_router_bfd-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
       Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance"

  data_tailf-mobile-infra_router_bfd_instance:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
       Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance"

  data_tailf-mobile-infra_router_bfd_instance-post:
    Type: object
```

```
      Properties:
        tailf-mobile-infra:instance-id:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid"
          x-yang:
            Type: list
    data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id:

      Type: object
      Properties:
        tailf-mobile-infra:instance-id:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid"
          x-yang:
            Type: list

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id:

      Type: object
      Properties:
        tailf-mobile-infra:id:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface:

      Type: object
      Properties:
        tailf-mobile-infra:interface-list:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist"
          x-yang:
            Type: list

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip:

      Type: object
      Properties:
        tailf-mobile-infra:gateway-ip:
          Type: string
          Description: (leaf)
```

```
          Format: union
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface:

      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor:

      Type: object
      Properties:
        tailf-mobile-infra:neighbors:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors"
          x-yang:
            Type: list

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor:

      Type: object
      Properties:
        tailf-mobile-infra:neighbor:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp:
      Type: object
      Properties:
        tailf-mobile-infra:bgplist:
```

```
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bgplist"
      x-yang:
        Type: list
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd:
  Type: object
  Properties:
    tailf-mobile-infra:bfd:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd"
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:min_rx:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:multiplier:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:dscp-marking:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: none
      enum:
      - none
      - cs6
      x-yang:
        Type: leaf
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking:
  Type: object
  Properties:
    tailf-mobile-infra:dscp-marking:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: none
      enum:
      - none
```

```
        - cs6
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval:
      Type: object
      Properties:
        tailf-mobile-infra:interval:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx:
      Type: object
      Properties:
        tailf-mobile-infra:min_rx:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier:
      Type: object
      Properties:
        tailf-mobile-infra:multiplier:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp:
      Type: object
      Properties:
        tailf-mobile-infra:bgp:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface:

      Type: object
      Properties:
        tailf-mobile-infra:interfaceList:
          Type: array
          Description: (list)
          Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_interfaceList"

          x-yang:
            Type: list
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface:

```
Type: object
Properties:
  tailf-mobile-infra:bondingInterfaces:
    Type: array
    Description: (list)
    Items:
      Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bondingInterfaces"
    x-yang:
      Type: list
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterface_bondingInterface:

```
Type: object
Properties:
  tailf-mobile-infra:bondingInterface:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface:

```
Type: object
Properties:
  tailf-mobile-infra:interface:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor:

```
Type: object
Properties:
  tailf-mobile-infra:neighbors:
    Type: array
    Description: (list)
    Items:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_neighbors"
    x-yang:
      Type: list
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over:

```
Type: object
Properties:
  tailf-mobile-infra:fail-over:
    Type: string
```

```
        Description: (leaf)
        Format: enumeration
        Default: bfd
        enum:
        - bfd
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor:

```
      Type: object
      Properties:
        tailf-mobile-infra:neighbor:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as:

```
      Type: object
      Properties:
        tailf-mobile-infra:remote-as:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf:

```
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute:
      Type: object
      Properties:
        tailf-mobile-infra:learnDefaultRoute:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort:
      Type: object
      Properties:
        tailf-mobile-infra:loopbackBFDPort:
          Type: integer
```

```
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort:
      Type: object
      Properties:
        tailf-mobile-infra:loopbackPort:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name:

      Type: object
      Properties:
        tailf-mobile-infra:policies:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_policies"
          x-yang:
            Type: list

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set:

      Type: object
      Properties:
        tailf-mobile-infra:as-path-set:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay:

      Type: object
      Properties:
        tailf-mobile-infra:gateWay:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface:

      Type: object
      Properties:
        tailf-mobile-infra:interface:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix:

      Type: object
      Properties:
        tailf-mobile-infra:ip-prefix:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute:

      Type: object
      Properties:
        tailf-mobile-infra:isStaticRoute:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range:

      Type: object
      Properties:
        tailf-mobile-infra:mask-range:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp:

      Type: object
      Properties:
        tailf-mobile-infra:modifySourceIp:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name:

      Type: object
      Properties:
        tailf-mobile-infra:policy-name:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix:
      Type: object
      Properties:
        tailf-mobile-infra:source-prefix:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend:
      Type: object
      Properties:
        tailf-mobile-infra:prepend:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_prepend"
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post:
      Type: object
      Properties:
        tailf-mobile-infra:as-path:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path:
      Type: object
      Properties:
        tailf-mobile-infra:as-path:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_monitor-interface:
      Type: object
      Properties:
        tailf-mobile-infra:monitor-interface:
         Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface"
    data_tailf-mobile-infra_router_monitor-interface-post:
      Type: object
      Properties:
        tailf-mobile-infra:interface-list:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist"
```

```
        x-yang:
          Type: list

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface:

    Type: object
    Properties:
      tailf-mobile-infra:interface-list:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist"
        x-yang:
          Type: list

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface:

    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type:

    Type: object
    Properties:
      tailf-mobile-infra:interface-type:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface:

    Type: object
    Properties:
      tailf-mobile-infra:linked-interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_rpc:
    Type: object
    Properties:
      tailf-mobile-infra:rpc:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarpc"
```

```
    data_tailf-mobile-infra_rpc-post:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list
    data_tailf-mobile-infra_rpc_all:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress:

      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_connectedTime:

      Type: object
      Properties:
        tailf-mobile-infra:connectedTime:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_disconnectedTime:

      Type: object
      Properties:
        tailf-mobile-infra:disconnectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_monitorRPCHost:

      Type: object
      Properties:
        tailf-mobile-infra:monitorRPCHost:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_name:

      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_podInstance:

      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_processingInstanceInfo:

      Type: object
```

```
      Properties:
        tailf-mobile-infra:processingInstanceInfo:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteAddress:

      Type: object
      Properties:
        tailf-mobile-infra:remoteAddress:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteHost:

      Type: object
      Properties:
        tailf-mobile-infra:remoteHost:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_setName:

      Type: object
      Properties:
        tailf-mobile-infra:setName:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_status:

      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_type:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_version:

      Type: object
      Properties:
        tailf-mobile-infra:version:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_rpc_ipv4:
      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress:

      Type: object
      Properties:
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list
```

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_connectedTime:

```
Type: object
Properties:
  tailf-mobile-infra:connectedTime:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_disconnectedTime:

```
Type: object
Properties:
  tailf-mobile-infra:disconnectedTime:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_monitorRPCHost:

```
Type: object
Properties:
  tailf-mobile-infra:monitorRPCHost:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_name:

```
Type: object
Properties:
  tailf-mobile-infra:name:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_podInstance:

```
Type: object
Properties:
  tailf-mobile-infra:podInstance:
    Type: string
    Description: (leaf)
    Format: string
```

```
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_processingInstanceInfo:

    Type: object
    Properties:
      tailf-mobile-infra:processingInstanceInfo:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_remoteAddress:

    Type: object
    Properties:
      tailf-mobile-infra:remoteAddress:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_remoteHost:

    Type: object
    Properties:
      tailf-mobile-infra:remoteHost:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_setName:

    Type: object
    Properties:
      tailf-mobile-infra:setName:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_status:

    Type: object
    Properties:
      tailf-mobile-infra:status:
        Type: string
```

```
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_type:

      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_version:

      Type: object
      Properties:
        tailf-mobile-infra:version:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv4_ipv4-podInstance_ipv4-name_ipv4-remoteAddress_vrf:

      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_rpc_ipv6:
      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress:

      Type: object
      Properties:
        tailf-mobile-infra:ipv6:
```

```
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
          x-yang:
            Type: list

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_connectedTime:

      Type: object
      Properties:
        tailf-mobile-infra:connectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_disconnectedTime:

      Type: object
      Properties:
        tailf-mobile-infra:disconnectedTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_monitorRPCHost:

      Type: object
      Properties:
        tailf-mobile-infra:monitorRPCHost:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_name:

      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_podInstance:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_processingInstanceInfo:

      Type: object
      Properties:
        tailf-mobile-infra:processingInstanceInfo:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_remoteAddress:

      Type: object
      Properties:
        tailf-mobile-infra:remoteAddress:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_remoteHost:

      Type: object
      Properties:
        tailf-mobile-infra:remoteHost:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_setName:

      Type: object
      Properties:
        tailf-mobile-infra:setName:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_status:
      Type: object
      Properties:
        tailf-mobile-infra:status:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_type:
      Type: object
      Properties:
        tailf-mobile-infra:type:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_version:
      Type: object
      Properties:
        tailf-mobile-infra:version:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_tailf-mobile-infra_rpc_ipv6_ipv6-podInstance_ipv6-name_ipv6-remoteAddress_vrf:
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_running-status:
      Type: object
      Properties:
        tailf-mobile-infra:running-status:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus"
    data_tailf-mobile-infra_running-status-post:
      Type: object
      Properties:
        tailf-mobile-infra:info:
          Type: array
```

```
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus_info"

          x-yang:
            Type: list
      data_tailf-mobile-infra_running-status_info:
        Type: object
        Properties:
          tailf-mobile-infra:info:
            Type: array
            Description: (list)
            Items:
             Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus_info"

            x-yang:
              Type: list
      data_tailf-mobile-infra_running-status_info_info-podInstance:
        Type: object
        Properties:
          tailf-mobile-infra:info:
            Type: array
            Description: (list)
            Items:
             Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus_info"

            x-yang:
              Type: list

data_tailf-mobile-infra_running-status_info_info-podInstance_podInstance:

        Type: object
        Properties:
          tailf-mobile-infra:podInstance:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf

data_tailf-mobile-infra_running-status_info_info-podInstance_runningStatus:

        Type: object
        Properties:
          tailf-mobile-infra:runningStatus:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf
    data_tailf-mobile-infra_running-status_info_info-podInstance_startTime:

        Type: object
```

```
      Properties:
        tailf-mobile-infra:startTime:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_running-status_info_info-podInstance_systemHealth:

      Type: object
      Properties:
        tailf-mobile-infra:systemHealth:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_sessions:
      Type: object
      Properties:
        tailf-mobile-infra:sessions:
          Reference: "#/components/schemas/datapost_tailfmobileinfrasessions"
    data_tailf-mobile-infra_sessions-post:
      Type: object
      Properties:
        tailf-mobile-infra:commit-pending:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrasessions_commitpending"
          x-yang:
            Type: list
        tailf-mobile-infra:affinity:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrasessions_affinity"

          x-yang:
            Type: list
    data_tailf-mobile-infra_sessions_affinity:
      Type: object
      Properties:
        tailf-mobile-infra:affinity:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrasessions_affinity"

          x-yang:
```

```
          Type: list
    data_tailf-mobile-infra_sessions_affinity_affinity-podInstance:
      Type: object
      Properties:
        tailf-mobile-infra:affinity:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrasessions_affinity"

          x-yang:
            Type: list
    data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_count:
      Type: object
      Properties:
        tailf-mobile-infra:count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf

data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_podInstance:

      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_sessions_commit-pending:
      Type: object
      Properties:
        tailf-mobile-infra:commit-pending:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrasessions_commitpending"
          x-yang:
            Type: list

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance:

      Type: object
      Properties:
        tailf-mobile-infra:commit-pending:
          Type: array
          Description: (list)
          Items:
            Reference:
```

```
"#/components/schemas/datapost_tailfmobileinfrasessions_commitpending"
          x-yang:
            Type: list

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_count:

        Type: object
        Properties:
          tailf-mobile-infra:count:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_dbBinarySize:

        Type: object
        Properties:
          tailf-mobile-infra:dbBinarySize:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_grInstance:

        Type: object
        Properties:
          tailf-mobile-infra:grInstance:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_lastDbSyncTime:

        Type: object
        Properties:
          tailf-mobile-infra:lastDbSyncTime:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_pendingCommit:

        Type: object
        Properties:
          tailf-mobile-infra:pendingCommit:
            Type: integer
```

```
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_podInstance:

```
      Type: object
      Properties:
        tailf-mobile-infra:podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_show:
      Type: object
      Properties:
        tailf-mobile-infra:show:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_tailf-mobile-infra_vrf:
      Type: object
      Properties:
        tailf-mobile-infra:vrf:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrf"
    data_tailf-mobile-infra_vrf-info:
      Type: object
      Properties:
        tailf-mobile-infra:vrf-info:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo"
    data_tailf-mobile-infra_vrf-info-post:
      Type: object
      Properties:
        tailf-mobile-infra:all:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
          x-yang:
            Type: list
        tailf-mobile-infra:ipv4:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
          x-yang:
            Type: list
```

```
    tailf-mobile-infra:ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all_all-name:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all_all-name_device:
  Type: object
  Properties:
    tailf-mobile-infra:device:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_gateway:
  Type: object
  Properties:
    tailf-mobile-infra:gateway:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_gatewayIpv6:
  Type: object
  Properties:
    tailf-mobile-infra:gatewayIpv6:
      Type: string
      Description: (leaf)
```

```
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_linkDevice:
  Type: object
  Properties:
    tailf-mobile-infra:linkDevice:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_podName:
  Type: object
  Properties:
    tailf-mobile-infra:podName:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_state:
  Type: object
  Properties:
    tailf-mobile-infra:state:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_tableId:
  Type: object
  Properties:
    tailf-mobile-infra:tableId:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4:
  Type: object
  Properties:
    tailf-mobile-infra:ipv4:
```

```
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name:
  Type: object
  Properties:
    tailf-mobile-infra:ipv4:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_device:
  Type: object
  Properties:
    tailf-mobile-infra:device:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_gateway:
  Type: object
  Properties:
    tailf-mobile-infra:gateway:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_gatewayIpv6:
  Type: object
  Properties:
    tailf-mobile-infra:gatewayIpv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_linkDevice:
  Type: object
  Properties:
    tailf-mobile-infra:linkDevice:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
```

```
      Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_podName:
  Type: object
  Properties:
    tailf-mobile-infra:podName:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_state:
  Type: object
  Properties:
    tailf-mobile-infra:state:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv4_ipv4-name_tableId:
  Type: object
  Properties:
    tailf-mobile-infra:tableId:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6:
  Type: object
  Properties:
    tailf-mobile-infra:ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name:
  Type: object
  Properties:
    tailf-mobile-infra:ipv6:
      Type: array
```

```
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_device:
  Type: object
  Properties:
    tailf-mobile-infra:device:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_gateway:
  Type: object
  Properties:
    tailf-mobile-infra:gateway:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_gatewayIpv6:
  Type: object
  Properties:
    tailf-mobile-infra:gatewayIpv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_linkDevice:
  Type: object
  Properties:
    tailf-mobile-infra:linkDevice:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_podName:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:podName:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_state:
    Type: object
    Properties:
      tailf-mobile-infra:state:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_vrf-info_ipv6_ipv6-name_tableId:
    Type: object
    Properties:
      tailf-mobile-infra:tableId:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_vrf-post:
    Type: object
    Properties:
      tailf-mobile-infra:vrflist:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrf_vrflist"
        x-yang:
          Type: list
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name:
    Type: object
    Properties:
      tailf-mobile-infra:vrflist:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfravrf_vrflist"
        x-yang:
          Type: list
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device:
    Type: object
    Properties:
      tailf-mobile-infra:device:
        Type: string
        Description: (leaf)
```

```
        Format: string
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway:
      Type: object
      Properties:
        tailf-mobile-infra:gateway:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6:
      Type: object
      Properties:
        tailf-mobile-infra:gatewayIpv6:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice:
      Type: object
      Properties:
        tailf-mobile-infra:linkDevice:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name:
      Type: object
      Properties:
        tailf-mobile-infra:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    operations:
      Type: object
      Properties:
        ietf-restconf:operations:
          Type: object
          Properties: {}
          Description: This resource is a container that provides access to the
data-model-specific RPC
           operations supported by the server. See RESTCONF RFC 8040 for further information.

          x-yang:
            Type: operations
    root:
```

```
      Type: object
      Properties:
        ietf-restconf:restconf:
          Reference: "#/components/schemas/root_ietfrestconfrestconf"
    yang-library-version:
      Type: object
      Properties:
        ietf-restconf:yang-library-version:
          Type: object
          Properties: {}
          Description: This leaf identifies the revision date of the 'ietf-yang-library'
YANG module that is
            implemented by this server. See RESTCONF RFC 8040 for further information.
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrasessions_commitpending:
      Type: object
      Properties:
        podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        pendingCommit:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        dbBinarySize:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        lastDbSyncTime:
          Type: string
          Description: (leaf)
          Format: string
```

```
        x-yang:
          Type: leaf
    datapost_tailfmobileinfrasessions_affinity:
      Type: object
      Properties:
        podInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        count:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrasessions:
      Type: object
      Properties:
        commit-pending:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrasessions_commitpending"
          x-yang:
            Type: list
        affinity:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfrasessions_affinity"

          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrapeers_all:
      Type: object
      Properties:
        grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        endpoint:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
localAddress:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
peerAddress:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
direction:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
podInstance:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
Type:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
connectedTime:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
rpc:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
additionalDetails:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
interfaceName:
  Type: string
  Description: (leaf)
```

```
      Format: string
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrapeers:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
      x-yang:
        Type: list
    ipv4:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
      x-yang:
        Type: list
    ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrapeers_all"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrarpc_all:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    remoteAddress:
      Type: string
```

```
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
remoteHost:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
Type:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
setName:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
status:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
connectedTime:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
disconnectedTime:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
monitorRPCHost:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
processingInstanceInfo:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
```

```
        Type: leaf
    Version:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarpc:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
      x-yang:
        Type: list
    ipv4:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
      x-yang:
        Type: list
    ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarpc_all"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfraresources_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cpuUsage:
      Type: integer
      Description: (leaf)
      Format: int32
```

```
      x-yang:
        Type: leaf
    totalNodeMemoryInMB:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    usedPodMemoryInMB:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    diskUsageInKbps:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    goRoutinesCount:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    gcCount:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    gcPauseInNS:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    loadFactor:
      Type: number
      Description: (leaf)
      Format: double
      x-yang:
        Type: leaf
datapost_tailfmobileinfraresources:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
```

```
        Reference: "#/components/schemas/datapost_tailfmobileinfraresources_info"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrarunningstatus_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    runningStatus:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    systemHealth:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    startTime:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarunningstatus:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
       Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus_info"

      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfradiagnostics_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
```

```
    diagnostic:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    component:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    startTime:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    status:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    retries:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfradiagnostics:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics_info"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrainfra_metrics_experimental:
  Type: object
  Properties:
    Version:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
```

```
    datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames:
      Type: object
      Properties:
        pod-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: production
          enum:
          - production
          - debug
          - trace
          - off
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrainfra_metrics_verbose_pods:
      Type: object
      Properties:
        pod-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames"
          x-yang:
            Type: list
        Description: (non-presence)
    datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList:
      Type: object
      Properties:
        Name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: production
          enum:
          - production
          - debug
          - trace
          - off
          x-yang:
```

```
          Type: leaf
        granular-labels:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
    datapost_tailfmobileinfrainfra_metrics_verbose_metrics:
      Type: object
      Properties:
        metricsList:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels:
      Type: object
      Properties:
        podType:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: protocol
          enum:
          - protocol
          - load-balancer
          - service
          - application
          x-yang:
            Type: leaf
        pods:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods"
        level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: production
          enum:
          - production
          - debug
          - trace
          - off
          x-yang:
            Type: leaf
        metrics:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics"
```

```
    datapost_tailfmobileinfrainfra_metrics_verbose:
      Type: object
      Properties:
        verboseLevels:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels"
          x-yang:
            Type: list
        Description: (non-presence)
    datapost_tailfmobileinfrainfra_metrics:
      Type: object
      Properties:
        experimental:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental"
        verbose:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose"

      Description: (non-presence)
    datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same:
      Type: object
      Properties:
        stage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_transaction_limit_consecutive:
      Type: object
      Properties:
        same:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same"
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_transaction_limit:
      Type: object
      Properties:
        stage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        consecutive:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive"
      Description: (non-presence)
```

```
    datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds:
      Type: object
      Properties:
        Name:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: low
          enum:
          - low
          - high
          x-yang:
            Type: leaf
        count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: noop
          enum:
          - noop
          - log-event
          - kill-session
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrainfra_transaction_loop_threshold:
      Type: object
      Properties:
        interval:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        thresholds:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds"

          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_transaction_loop_category:
      Type: object
      Properties:
        Name:
```

```
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf
        threshold:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold"
    datapost_tailfmobileinfrainfra_transaction_loop:
      Type: object
      Properties:
        detection:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
          - enable
          - disable
          x-yang:
            Type: leaf
        category:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_transaction:
      Type: object
      Properties:
        limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit"

        loop:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop"

      Description: (non-presence)
    datapost_tailfmobileinfrainfra:
      Type: object
      Properties:
        metrics:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_metrics"
        transaction:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainfra_transaction"
        k8-validation:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
```

```
      - enable
      - disable
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_http_header:
  Type: object
  Properties:
    user-agent:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: cluster-name
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_http_ping:
  Type: object
  Properties:
    timeout:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_http:
  Type: object
  Properties:
    header:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_header"
    ping:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http_ping"
  Description: (non-presence)
datapost_tailfmobileinfraclient_outbound_limit_pending:
  Type: object
  Properties:
    response:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
```

```
            Type: leaf
        Description: (non-presence)
      datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure:
        Type: object
        Properties:
          count:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf
          codes:
            Type: array
            Items:
              Type: string
              Description: (leaf-list)
              Format: string
            x-yang:
              Type: leaf-list
        Description: (non-presence)
      datapost_tailfmobileinfraclient_outbound_limit_consecutive:
        Type: object
        Properties:
          failure:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure"
        Description: (non-presence)
      datapost_tailfmobileinfraclient_outbound_limit:
        Type: object
        Properties:
          pending:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending"
          consecutive:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive"
        Description: (non-presence)
      datapost_tailfmobileinfraclient_outbound_host_ping:
        Type: object
        Properties:
          timeout:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf
          interval:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf
```

```
        backoff:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        retry:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        fast-interval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        all-host-down-interval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfraclient_outbound_host:
      Type: object
      Properties:
        ping:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping"
      Description: (non-presence)
    datapost_tailfmobileinfraclient_outbound_interface:
      Type: object
      Properties:
        interface:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf
        limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit"

        host:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_host"

    datapost_tailfmobileinfraclient_outbound:
      Type: object
      Properties:
        interface:
          Type: array
```

```
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface"
        x-yang:
          Type: list
      limit:
       Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit"

      host:
       Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound_host"

    Description: (non-presence)
  datapost_tailfmobileinfraclient_inbound_limit_pending:
    Type: object
    Properties:
      request:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraclient_inbound_limit_overload:
    Type: object
    Properties:
      reject-code:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraclient_inbound_limit:
    Type: object
    Properties:
      pending:
        Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending"
      overload:
        Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload"
    Description: (non-presence)
  datapost_tailfmobileinfraclient_inbound_interface:
    Type: object
    Properties:
      interface:
        Type: string
        Description: (leaf)
        Format: identityref
        x-yang:
          Type: leaf
```

```
        limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit"

    datapost_tailfmobileinfraclient_inbound:
      Type: object
      Properties:
        interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface"
          x-yang:
            Type: list
        limit:
         Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit"

      Description: (non-presence)
    datapost_tailfmobileinfraclient:
      Type: object
      Properties:
        http:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient_http"
        outbound:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient_outbound"
        inbound:
          Reference: "#/components/schemas/datapost_tailfmobileinfraclient_inbound"
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_vip:
      Type: object
      Properties:
        vip-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        vip-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        vip-interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        offline:
          Type: string
          Description: (leaf)
```

```
      Format: [null]
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_vip6:
  Type: object
  Properties:
    vip-ipv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    vip-ipv6-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    vip-interface:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    offline:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn:
  Type: object
  Properties:
    cpu-percent:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
```

```
        memory-in-mbs:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        num-of-goroutine:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel:
      Type: object
      Properties:
        warn:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
        critical:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
        crash:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn"
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_monitor:
      Type: object
      Properties:
        protocol:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: on
          enum:
          - on
          - off
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_sla:
      Type: object
      Properties:
        response:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        procedure:
          Type: integer
          Description: (leaf)
```

```
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrainstance_endpoint_secvip:
  Type: object
  Properties:
    sec-vip-ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    vip-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    vip-interface:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    offline:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_secvip6:
  Type: object
  Properties:
    sec-vip-ipv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    vip-ipv6-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
```

```
        Type: leaf
      vip-interface:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      offline:
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf
      vrf:
        Type: string
        Description: (leaf)
        Format: leafref
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup:
    Type: object
    Properties:
      Name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      capacity:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      rate-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      outbound-capacity:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      outbound-rate-limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
```

```
      Type: leaf
datapost_tailfmobileinfrainstance_endpoint_dispatcher:
  Type: object
  Properties:
    count:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    capacity:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    outbound:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    rate-limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    cache:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    threshold:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    expiry:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    nonresponsive:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    flowctrl-group:
```

```
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_internal_baseport:
      Type: object
      Properties:
        start:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_internal:
      Type: object
      Properties:
        base-port:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport"
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_endpoint_interface:
      Type: object
      Properties:
        interface-type:
          Type: string
          Description: (leaf)
          Format: identityref
          x-yang:
            Type: leaf
        loopbackEth:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        loopbackPort:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        uri-scheme:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: http
          enum:
```

```
        - http
        - https
        x-yang:
          Type: leaf
      instancetype:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf
      tls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      certificate-name:
        Type: string
        Description: (leaf)
        Format: leafref
        x-yang:
          Type: leaf
      sla:
       Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla"

      vip:
        Type: array
        Description: (list)
        Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip"

        x-yang:
          Type: list
      sec-vip:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip"
        x-yang:
          Type: list
      vip6:
        Type: array
        Description: (list)
```

```
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6"
          x-yang:
            Type: list
        sec-vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6"
          x-yang:
            Type: list
        vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
        dispatcher:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher"
        monitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor"
        internal:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal"
    datapost_tailfmobileinfrainstance_endpoint_service:
      Type: object
      Properties:
        service-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface"
          x-yang:
            Type: list
    datapost_tailfmobileinfrainstance_endpoint_dscp:
      Type: object
      Properties:
        value:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
```

```
        Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_ep:
    Type: object
    Properties:
      eptype:
        Type: string
        Description: (leaf)
        Format: identityref
        x-yang:
          Type: leaf
      replicas:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      nodes:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      loopbackEth:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      loopbackPort:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      instancetype:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf
      vip:
        Type: array
        Description: (list)
        Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip"
```

```
          x-yang:
            Type: list
        vip6:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6"
          x-yang:
            Type: list
        system-health-level:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel"
        monitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor"
        uri-scheme:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: http
          enum:
          - http
          - https
          x-yang:
            Type: leaf
        mtls-enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        certificate-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
        service:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_service"
          x-yang:
            Type: list
        interface:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface"
          x-yang:
            Type: list
```

```
        internal:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal"
        dscp:
         Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dscp"

    datapost_tailfmobileinfrainstance_endpoint:
      Type: object
      Properties:
        ep:
          Type: array
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep"

          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainstance_instanceid:
      Type: object
      Properties:
        id:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
        endpoint:
          Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_endpoint"
    datapost_tailfmobileinfrainstance:
      Type: object
      Properties:
        instance-id:
          Type: array
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrainstance_instanceid"

          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfraendpoint_all:
      Type: object
      Properties:
        grInstance:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        endpoint:
          Type: string
```

```
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
address:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
Type:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
status:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
Interface:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
internal:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
startTime:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
stoppedTime:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
vrf:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
```

```
      Type: leaf
datapost_tailfmobileinfraendpoint:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
      x-yang:
        Type: list
    info:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
      x-yang:
        Type: list
    ipv4:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
      x-yang:
        Type: list
    ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint_all"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfravrf_vrflist:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    gateway:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    gatewayIpv6:
      Type: string
      Description: (leaf)
```

```
      Format: string
      x-yang:
        Type: leaf
    device:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    linkDevice:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfravrf:
  Type: object
  Properties:
    vrflist:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrf_vrflist"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfravrfinfo_all:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    gateway:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    gatewayIpv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    device:
      Type: string
      Description: (leaf)
      Format: string
```

```
      x-yang:
        Type: leaf
    linkDevice:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    tableId:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    state:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    podName:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfravrfinfo:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
    ipv4:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
    ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo_all"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfralogging_transaction:
```

```
    Type: object
    Properties:
      persist:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
      max-file-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      max-rotation:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      message:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
      duplicate:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_level:
    Type: object
    Properties:
      application:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: trace
```

```
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    transaction:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    tracing:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
    monitor-subscriber:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - off
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfralogging_jsonlogging:
  Type: object
  Properties:
    application:
```

```
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf
      transaction:
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf
      monitor-subscriber:
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_logger:
    Type: object
    Properties:
      Name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      level:
        Reference: "#/components/schemas/datapost_tailfmobileinfralogging_level"
  datapost_tailfmobileinfralogging_async_application_enable:
    Type: object
    Properties:
      buffer-size:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_async_application:
    Type: object
    Properties:
      enable:
        Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable"
      disable:
        Type: string
        Description: (leaf)
        Format: [null]
        x-yang:
          Type: leaf
    Description: (non-presence)
```

```
    datapost_tailfmobileinfralogging_async:
      Type: object
      Properties:
        application:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        transaction:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        tracing:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
        monitor-subscriber:
          Reference:
"#/components/schemas/datapost_tailfmobileinfralogging_async_application"
      Description: (non-presence)
    datapost_tailfmobileinfralogging_error:
      Type: object
      Properties:
        stack:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: enable
          enum:
          - enable
          - disable
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfralogging:
      Type: object
      Properties:
        transaction:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_transaction"

        level:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_level"
        json-logging:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_jsonlogging"

        logger:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfralogging_logger"
          x-yang:
            Type: list
        async:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_async"
        error:
          Reference: "#/components/schemas/datapost_tailfmobileinfralogging_error"
      Description: (non-presence)
```

```
datapost_tailfmobileinfranodemonitor:
  Type: object
  Properties:
    mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: 0
      enum:
      - 0
      - 1
      - 2
      - 3
      x-yang:
        Type: leaf
    interval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor_bfd:
  Type: object
  Properties:
    node-status:
      Type: string
      Description: (leaf)
      Format: [null]
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor_protocol:
  Type: object
  Properties:
    cpu-limit:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor_internalvipipc:
  Type: object
  Properties:
    max-conn-downtime:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
```

```
    datapost_tailfmobileinframonitor_activeinstancetraffic:
      Type: object
      Properties:
        no-traffic-duration:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        session-threshold:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: pod-restart
          enum:
          - pod-restart
          - trigger-switch-over
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinframonitor:
      Type: object
      Properties:
        bfd:
          Reference: "#/components/schemas/datapost_tailfmobileinframonitor_bfd"
        protocol:
          Reference: "#/components/schemas/datapost_tailfmobileinframonitor_protocol"
        nf:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
        internal-vip-ipc:
         Reference: "#/components/schemas/datapost_tailfmobileinframonitor_internalvipipc"

        active-instance-traffic:
          Reference:
"#/components/schemas/datapost_tailfmobileinframonitor_activeinstancetraffic"
        Description: (non-presence)
    datapost_tailfmobileinfrarouter_prepend:
      Type: object
      Properties:
        as-path:
          Type: boolean
```

```
        Description: (leaf)
        x-yang:
          Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfrarouter_bondingInterfaces:
      Type: object
      Properties:
        bondingInterface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrarouter_neighbors:
      Type: object
      Properties:
        neighbor:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf
        remote-as:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        fail-over:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: bfd
          enum:
          - bfd
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrarouter_interfaceList:
      Type: object
      Properties:
        interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        bondingInterfaces:
          Type: array
          Description: (list)
          Items:
            Reference:
  "#/components/schemas/datapost_tailfmobileinfrarouter_bondingInterfaces"
```

```
      x-yang:
        Type: list
    vrf:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
    neighbors:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_neighbors"
      x-yang:
        Type: list
datapost_tailfmobileinfrarouter_policies:
  Type: object
  Properties:
    policy-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    as-path-set:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    ip-prefix:
      Type: string
      Description: (leaf)
      Format: union
      x-yang:
        Type: leaf
    source-prefix:
      Type: string
      Description: (leaf)
      Format: union
      x-yang:
        Type: leaf
    mask-range:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    interface:
      Type: string
      Description: (leaf)
```

```
      Format: string
      x-yang:
        Type: leaf
    modifySourceIp:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    isStaticRoute:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    gateWay:
      Type: string
      Description: (leaf)
      Format: union
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarouter_bfd:
  Type: object
  Properties:
    interval:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    min_rx:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    multiplier:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    dscp-marking:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: none
      enum:
      - none
      - cs6
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrarouter_bgplist:
```

```
    Type: object
    Properties:
      bgp:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      loopbackPort:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      loopbackBFDPort:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      learnDefaultRoute:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      prepend:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_prepend"
      interfaceList:
        Type: array
        Description: (list)
        Items:
         Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_interfaceList"

        x-yang:
          Type: list
      policies:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_policies"
        x-yang:
          Type: list
      bfd:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd"
  datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors:
    Type: object
    Properties:
      neighbor:
        Type: string
        Description: (leaf)
        Format: union
        x-yang:
```

```
          Type: leaf
    datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist:
      Type: object
      Properties:
        interface:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        vrf:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
        neighbors:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors"
          x-yang:
            Type: list
        gateway-ip:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid:
      Type: object
      Properties:
        id:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
        interface-list:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist"
          x-yang:
            Type: list
    datapost_tailfmobileinfrarouter_bfd_1_instance:
      Type: object
      Properties:
        instance-id:
          Type: array
```

```
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid"
          x-yang:
            Type: list
        Description: (non-presence)
      datapost_tailfmobileinfrarouter_bfd_1:
        Type: object
        Properties:
          instance:
           Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance"

        Description: (non-presence)
      datapost_tailfmobileinfrarouter_monitorinterface_interfacelist:
        Type: object
        Properties:
          interface:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf
          linked-interface:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf
          interface-type:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf
      datapost_tailfmobileinfrarouter_monitorinterface:
        Type: object
        Properties:
          interface-list:
            Type: array
            Description: (list)
            Items:
              Reference:
"#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist"
            x-yang:
              Type: list
        Description: (non-presence)
      datapost_tailfmobileinfrarouter:
        Type: object
        Properties:
          bgplist:
            Type: array
```

```
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bgplist"
      x-yang:
        Type: list
    bfd:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1"
    monitor-interface:
     Reference: "#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface"

  Description: (non-presence)
datapost_tailfmobileinfradeployment_resource:
  Type: object
  Properties:
    cpu:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfradeployment:
  Type: object
  Properties:
    app-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cluster-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    dc-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    model:
      Type: string
      Description: Deployment Model default large (leaf)
      Format: enumeration
      Default: small
      enum:
      - small
      x-yang:
        Type: leaf
    resource:
```

```
        Reference: "#/components/schemas/datapost_tailfmobileinfradeployment_resource"

      logical-nf-instance-id:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrak8_label_podgroupconfig:
    Type: object
    Properties:
      pod-group:
        Type: string
        Description: Group for the VMs (leaf)
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
        x-yang:
          Type: leaf
      key:
        Type: string
        Description: Key for the label (leaf)
        Format: string
        x-yang:
          Type: leaf
      value:
        Type: string
        Description: Value for the label (leaf)
        Format: string
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrak8_label:
    Type: object
    Properties:
      pod-group-config:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig"
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrak8:
    Type: object
    Properties:
      label:
        Reference: "#/components/schemas/datapost_tailfmobileinfrak8_label"
```

```
    Description: (non-presence)
  datapost_tailfmobileinfraconfigerror_info:
    Type: object
    Properties:
      errorComponent:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      errorDescription:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  datapost_tailfmobileinfraconfigerror:
    Type: object
    Properties:
      info:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror_info"
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfraresource_cpu:
    Type: object
    Properties:
      request:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraresource_memory:
    Type: object
    Properties:
      request:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
```

```
        Type: leaf
      limit:
        Type: integer
        Description: (leaf)
        Format: int32
        x-yang:
          Type: leaf
      gomemlimit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      gogc:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
    Description: (non-presence)
datapost_tailfmobileinfraresource_labels:
    Type: object
    Properties:
      key:
        Type: string
        Description: Key for the label (leaf)
        Format: string
        x-yang:
          Type: leaf
      value:
        Type: string
        Description: Value for the label (leaf)
        Format: string
        x-yang:
          Type: leaf
    Description: (non-presence)
datapost_tailfmobileinfraresource_pod:
    Type: object
    Properties:
      podtype:
        Type: string
        Description: (leaf)
        Format: identityref
        x-yang:
          Type: leaf
      cpu:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresource_cpu"
      memory:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresource_memory"
      gomaxproc:
        Type: integer
```

```
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    labels:
      Reference: "#/components/schemas/datapost_tailfmobileinfraresource_labels"
datapost_tailfmobileinfraresource:
  Type: object
  Properties:
    pod:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresource_pod"
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrageomonitor_podmonitor_pods:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    retryCount:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    retryInterval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    retryFailOverInterval:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    failedReplicaPercent:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
datapost_tailfmobileinfrageomonitor_podmonitor:
```

```
      Type: object
      Properties:
        pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods"
          x-yang:
            Type: list
        Description: (non-presence)
    datapost_tailfmobileinfrageomonitor_remoteclustermonitor:
      Type: object
      Properties:
        retryCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        retryInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        Description: (non-presence)
    datapost_tailfmobileinfrageomonitor_trafficMonitor:
      Type: object
      Properties:
        thresholdCount:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        thresholdInterval:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        Description: (non-presence)
    datapost_tailfmobileinfrageomonitor:
      Type: object
      Properties:
        podmonitor:
         Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor"

        remoteclustermonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor"
```

```
        trafficMonitor:
          Reference:
"#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor"
      Description: (non-presence)
    datapost_tailfmobileinfrainstances_instance:
      Type: object
      Properties:
        instance-id:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        system-id:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cluster-id:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        slice-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    datapost_tailfmobileinfrainstances:
      Type: object
      Properties:
        instance:
          Type: array
          Description: (list)
          Items:
           Reference: "#/components/schemas/datapost_tailfmobileinfrainstances_instance"

          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfralocalinstance:
      Type: object
      Properties:
        instance:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

```
      Description: (non-presence)
    datapost_tailfmobileinfradatastore_sessiondb_endpoints:
      Type: object
      Properties:
        host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    datapost_tailfmobileinfradatastore_sessiondb:
      Type: object
      Properties:
        endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_tailfmobileinfradatastore_dbs:
      Type: object
      Properties:
        Name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints"
          x-yang:
            Type: list
    datapost_tailfmobileinfradatastore_notificationep:
      Type: object
      Properties:
        host:
          Type: string
          Description: (leaf)
          Format: string
```

```
          x-yang:
            Type: leaf
        port:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfradatastore:
      Type: object
      Properties:
        session-db:
          Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb"

        dbs:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_tailfmobileinfradatastore_dbs"
          x-yang:
            Type: list
        notification-ep:
          Reference:
"#/components/schemas/datapost_tailfmobileinfradatastore_notificationep"
      Description: (non-presence)
    datapost_tailfmobileinfraload_factor_excludepods:
      Type: object
      Properties:
        pod-type:
          Type: string
          Description: Default set to exclude all infra-pods (leaf)
          Format: identityref
          x-yang:
            Type: leaf
    datapost_tailfmobileinfraload_factor:
      Type: object
      Properties:
        calc-frequency:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        exclude-pods:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_tailfmobileinfraload_factor_excludepods"
          x-yang:
            Type: list
```

```
  Description: (non-presence)
datapost_tailfmobileinfraload:
  Type: object
  Properties:
    factor:
      Reference: "#/components/schemas/datapost_tailfmobileinfraload_factor"
  Description: (non-presence)
dataputpatch_ietfrestconfdata:
  Type: object
  Properties:
    tailf-mobile-infra:sessions:
      Reference: "#/components/schemas/datapost_tailfmobileinfrasessions"
    tailf-mobile-infra:peers:
      Reference: "#/components/schemas/datapost_tailfmobileinfrapeers"
    tailf-mobile-infra:rpc:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarpc"
    tailf-mobile-infra:resources:
      Reference: "#/components/schemas/datapost_tailfmobileinfraresources"
    tailf-mobile-infra:running-status:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarunningstatus"
    tailf-mobile-infra:diagnostics:
      Reference: "#/components/schemas/datapost_tailfmobileinfradiagnostics"
    tailf-mobile-infra:infra:
      Reference: "#/components/schemas/datapost_tailfmobileinfrainfra"
    tailf-mobile-infra:client:
      Reference: "#/components/schemas/datapost_tailfmobileinfraclient"
    tailf-mobile-infra:instance:
      Reference: "#/components/schemas/datapost_tailfmobileinfrainstance"
    tailf-mobile-infra:endpoint:
      Reference: "#/components/schemas/datapost_tailfmobileinfraendpoint"
    tailf-mobile-infra:vrf:
      Reference: "#/components/schemas/datapost_tailfmobileinfravrf"
    tailf-mobile-infra:vrf-info:
      Reference: "#/components/schemas/datapost_tailfmobileinfravrfinfo"
    tailf-mobile-infra:logging:
      Reference: "#/components/schemas/datapost_tailfmobileinfralogging"
    tailf-mobile-infra:nodemonitor:
      Reference: "#/components/schemas/datapost_tailfmobileinfranodemonitor"
    tailf-mobile-infra:monitor:
      Reference: "#/components/schemas/datapost_tailfmobileinframonitor"
    tailf-mobile-infra:router:
      Reference: "#/components/schemas/datapost_tailfmobileinfrarouter"
    tailf-mobile-infra:deployment:
      Reference: "#/components/schemas/datapost_tailfmobileinfradeployment"
    tailf-mobile-infra:k8:
      Reference: "#/components/schemas/datapost_tailfmobileinfrak8"
    tailf-mobile-infra:geo:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
```

```
        Type: container
        is_presence: false
      tailf-mobile-infra:show:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:clear:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:dump:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
      tailf-mobile-infra:config-error:
        Reference: "#/components/schemas/datapost_tailfmobileinfraconfigerror"
      tailf-mobile-infra:resource:
        Reference: "#/components/schemas/datapost_tailfmobileinfraresource"
      tailf-mobile-infra:geomonitor:
        Reference: "#/components/schemas/datapost_tailfmobileinfrageomonitor"
      tailf-mobile-infra:instances:
        Reference: "#/components/schemas/datapost_tailfmobileinfrainstances"
      tailf-mobile-infra:local-instance:
        Reference: "#/components/schemas/datapost_tailfmobileinfralocalinstance"
      tailf-mobile-infra:datastore:
        Reference: "#/components/schemas/datapost_tailfmobileinfradatastore"
      tailf-mobile-infra:load:
        Reference: "#/components/schemas/datapost_tailfmobileinfraload"
    Description:
  root_ietfrestconfrestconf:
    Type: object
    Properties:
      data:
        Type: object
        Properties: {}
      operations:
        Type: object
        Properties: {}
      yang-library-version:
        Type: string
    Description: This is the RESTCONF root resource for the RESTCONF datastore and
operation resources. See
      RESTCONF RFC 8040 for further information.
```

```
Responses:
  "200":
    Description: OK
    Content: {}
  "201":
    Description: Created
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
Parameters:
  Content:
    Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  depth:
    Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  fields:
```

```
  Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
filter:
  Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
with-defaults:
  Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
insert:
  Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
point:
  Name: point
```

```
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  affinity-podInstance:
    Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  all-address:
    Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  all-endpoint:
    Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  all-grInstance:
    Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  all-localAddress:
    Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
all-name:
  Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
all-peerAddress:
  Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
all-podInstance:
  Name: all-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
all-remoteAddress:
  Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
bgplist-bgp:
  Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
bondingInterfaces-bondingInterface:
  Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  category-name:
    Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  codes-id:
    Name: codes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  commit-pending-grInstance:
    Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  commit-pending-podInstance:
    Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  dbs-name:
    Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  endpoints-host:
```

```
  Name: endpoints-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ep-eptype:
  Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
exclude-pods-pod-type:
  Name: exclude-pods-pod-type
  In: path
  Description: Default set to exclude all infra-pods
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
flowctrl-group-name:
  Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
granular-labels-id:
  Name: granular-labels-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
info-address:
  Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
```

```
    Schema:
      Type: string
      Format: string
  info-diagnostic:
    Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  info-endpoint:
    Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  info-errorComponent:
    Name: info-errorComponent
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  info-grInstance:
    Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  info-podInstance:
    Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  instance-id-id:
    Name: instance-id-id
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  instance-instance-id:
    Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  interface-interface:
    Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  interface-interface-type:
    Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  interface-list-interface:
    Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  interfaceList-interface:
    Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
ipv4-address:
  Name: ipv4-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-endpoint:
  Name: ipv4-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-grInstance:
  Name: ipv4-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-localAddress:
  Name: ipv4-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-name:
  Name: ipv4-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-peerAddress:
  Name: ipv4-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
```

```
  Schema:
    Type: string
    Format: string
ipv4-podInstance:
  Name: ipv4-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv4-remoteAddress:
  Name: ipv4-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv6-address:
  Name: ipv6-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv6-endpoint:
  Name: ipv6-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv6-grInstance:
  Name: ipv6-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ipv6-localAddress:
  Name: ipv6-localAddress
  In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  ipv6-name:
    Name: ipv6-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  ipv6-peerAddress:
    Name: ipv6-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  ipv6-podInstance:
    Name: ipv6-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  ipv6-remoteAddress:
    Name: ipv6-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  logger-name:
    Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
metricsList-name:
  Name: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
neighbors-neighbor:
  Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
pod-group-config-key:
  Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
pod-group-config-pod-group:
  Name: pod-group-config-pod-group
  In: path
  Description: Group for the VMs
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
pod-group-config-value:
  Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
```

```
    Type: string
    Format: string
pod-names-pod-name:
  Name: pod-names-pod-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
pod-podtype:
  Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
pods-name:
  Name: pods-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
policies-policy-name:
  Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
sec-vip-sec-vip-ip:
  Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
sec-vip6-sec-vip-ipv6:
  Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  service-service-name:
    Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  thresholds-name:
    Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  verboseLevels-podType:
    Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  vip-vip-ip:
    Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  vip6-vip-ipv6:
    Name: vip6-vip-ipv6
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  vrflist-name:
    Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
requestBodies:
  data-post:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-post"
    Required/Optional: true
  data-put-patch:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true
  data_tailf-mobile-infra_client:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client"
    Required/Optional: true
  data_tailf-mobile-infra_client-post:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client-post"
    Required/Optional: true
  data_tailf-mobile-infra_client_http:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_client_http"
    Required/Optional: true
  data_tailf-mobile-infra_client_http-post:
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_http-post"
        Required/Optional: true
      data_tailf-mobile-infra_client_http_header:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_header"

        Required/Optional: true
      data_tailf-mobile-infra_client_http_header-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header-post"
        Required/Optional: true
      data_tailf-mobile-infra_client_http_header_user-agent:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent"
        Required/Optional: true
      data_tailf-mobile-infra_client_http_ping:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping"
        Required/Optional: true
      data_tailf-mobile-infra_client_http_ping-post:
        Content:
          application/yang-data+json:
            Schema:
             Reference: "#/components/schemas/data_tailf-mobile-infra_client_http_ping-post"

        Required/Optional: true
      data_tailf-mobile-infra_client_http_ping_interval:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval"
        Required/Optional: true
      data_tailf-mobile-infra_client_http_ping_timeout:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout"
        Required/Optional: true
      data_tailf-mobile-infra_client_inbound:
        Content:
          application/yang-data+json:
```

```
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound"
        Required/Optional: true
      data_tailf-mobile-infra_client_inbound-post:
        Content:
          application/yang-data+json:
            Schema:
             Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound-post"

        Required/Optional: true
      data_tailf-mobile-infra_client_inbound_interface_interface-interface:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface"

        Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface:

        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface"

        Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit:

        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit"

        Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post:

        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post"

        Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload:

        Content:
          application/yang-data+json:
            Schema:
              Reference:
```

"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload"

Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post"

Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code"

Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending"

Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post"

Required/Optional: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request"

Required/Optional: true
data_tailf-mobile-infra_client_inbound_limit:
Content:
application/yang-data+json:

```
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_client_inbound_limit"

      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_overload:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_overload-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_overload_reject-code:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_pending:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_pending-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_inbound_limit_pending_request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request"
      Required/Optional: true
```

```
    data_tailf-mobile-infra_client_outbound:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound-post"

      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_host"

      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping-post"
      Required/Optional: true

data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval"

      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping_backoff:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping_fast-interval:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping_interval:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping_retry:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_host_ping_timeout:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout"
      Required/Optional: true
  data_tailf-mobile-infra_client_outbound_interface_interface-interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval"
```

```
      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post:

      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id"

      Required/Optional: true
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count"

Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending"

Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post"

Required/Optional: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response"

Required/Optional: true
data_tailf-mobile-infra_client_outbound_limit:
Content:
application/yang-data+json:
Schema:
Reference: "#/components/schemas/data_tailf-mobile-infra_client_outbound_limit"

Required/Optional: true
data_tailf-mobile-infra_client_outbound_limit-post:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit-post"
Required/Optional: true
data_tailf-mobile-infra_client_outbound_limit_consecutive:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_limit_consecutive-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_limit_consecutive_failure:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure"
      Required/Optional: true
   data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post"

      Required/Optional: true

data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id"

      Required/Optional: true
   data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count"

      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_limit_pending:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_limit_pending-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending-post"
      Required/Optional: true
    data_tailf-mobile-infra_client_outbound_limit_pending_response:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response"
      Required/Optional: true
    data_tailf-mobile-infra_config-error:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_config-error"
      Required/Optional: true
    data_tailf-mobile-infra_config-error-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_config-error-post"
      Required/Optional: true
    data_tailf-mobile-infra_datastore:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_datastore"
      Required/Optional: true
    data_tailf-mobile-infra_datastore-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_datastore-post"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_dbs_dbs-name:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name"

      Required/Optional: true
   data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host"

      Required/Optional: true

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host"

      Required/Optional: true

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port"

      Required/Optional: true
    data_tailf-mobile-infra_datastore_dbs_dbs-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_notification-ep:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_notification-ep-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep-post"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_notification-ep_host:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_notification-ep_port:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_session-db:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_datastore_session-db"

      Required/Optional: true
    data_tailf-mobile-infra_datastore_session-db-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db-post"
      Required/Optional: true
    data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host"

      Required/Optional: true

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host"

      Required/Optional: true

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port"

      Required/Optional: true
    data_tailf-mobile-infra_deployment:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment"
      Required/Optional: true
    data_tailf-mobile-infra_deployment-post:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment-post"
      Required/Optional: true
    data_tailf-mobile-infra_deployment_app-name:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_app-name"

      Required/Optional: true
    data_tailf-mobile-infra_deployment_cluster-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name"
      Required/Optional: true
    data_tailf-mobile-infra_deployment_dc-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_dc-name"

      Required/Optional: true
    data_tailf-mobile-infra_deployment_logical-nf-instance-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id"
      Required/Optional: true
    data_tailf-mobile-infra_deployment_model:
      Description: Deployment Model default large
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_model"
      Required/Optional: true
    data_tailf-mobile-infra_deployment_resource:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_deployment_resource"

      Required/Optional: true
    data_tailf-mobile-infra_deployment_resource-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource-post"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_deployment_resource_cpu:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu"
      Required/Optional: true
    data_tailf-mobile-infra_diagnostics:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics"
      Required/Optional: true
    data_tailf-mobile-infra_diagnostics-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_diagnostics-post"
      Required/Optional: true
    data_tailf-mobile-infra_dump:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_dump"
      Required/Optional: true
    data_tailf-mobile-infra_dump-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_dump-post"
      Required/Optional: true
    data_tailf-mobile-infra_endpoint:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint"
      Required/Optional: true
    data_tailf-mobile-infra_endpoint-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_endpoint-post"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor-post:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor-post"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_podmonitor:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor"

      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_podmonitor-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor-post"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name"
      Required/Optional: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent"

      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name"
      Required/Optional: true
   data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount"

      Required/Optional: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval"

      Required/Optional: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval"

      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_remoteclustermonitor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount"
      Required/Optional: true
   data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval"

      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_trafficMonitor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor"
      Required/Optional: true
```

```
    data_tailf-mobile-infra_geomonitor_trafficMonitor-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor-post"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount"
      Required/Optional: true
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval"
      Required/Optional: true
    data_tailf-mobile-infra_infra:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra"
      Required/Optional: true
    data_tailf-mobile-infra_infra-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_k8-validation:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_infra_k8-validation"

      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics"
      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics-post"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics_experimental:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental"
      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics_experimental-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics_experimental_version:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version"
      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics_verbose:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose"

      Required/Optional: true
    data_tailf-mobile-infra_infra_metrics_verbose-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose-post"
      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level"
```

```
      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name:

      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name"

      Required/Optional: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level"

      Required/Optional: true
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name"

      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction-post"

      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_limit_stage:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_loop:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_loop-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop-post"
      Required/Optional: true
    data_tailf-mobile-infra_infra_transaction_loop_category_category-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name"
      Required/Optional: true
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action:

Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count"

Required/Optional: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name"

Required/Optional: true
data_tailf-mobile-infra_infra_transaction_loop_detection:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection"
Required/Optional: true
data_tailf-mobile-infra_instance:
Content:
application/yang-data+json:
Schema:
Reference: "#/components/schemas/data_tailf-mobile-infra_instance"
Required/Optional: true
data_tailf-mobile-infra_instance-post:
Content:
application/yang-data+json:
Schema:
Reference: "#/components/schemas/data_tailf-mobile-infra_instance-post"
Required/Optional: true
data_tailf-mobile-infra_instance_instance-id_instance-id-id:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id"
Required/Optional: true
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint:
Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_dscp_value"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher"
```

```
      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-etype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopback0h:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable"
```

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf

Content:
application/yang-data+json:

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6port:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"
```

```
      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name:

Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_post

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_capacity"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_count

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_count"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_expiry

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_expiry"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_capacity

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_capacity"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_name

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_endpoint_ep_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-name_name"
```

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-outbound-capacity

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-outbound-capacity"

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-outbound-rate-limit

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-outbound-rate-limit"

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-rate-limit

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-flow-ctrl-grp-flow-ctrl-grp-name-rate-limit"

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-responsive

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-responsive"

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-outbound

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-outbound"

Required/Optional: true

data-tailf-mobile-ifa-instance-instance-id-instance-id-id-endpoint-ep-ep-id-type-service-service-service-name-interface-interface-interface-type-dispatcher-rate-limit

Content:
application/yang-data+json:

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_threshold

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_threshold"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_instance-type

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_instance-type"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_interface-type

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_interface-type"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_internal

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_internal"

      Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_internal-post

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_internal-post"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port-post"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port_start:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_internal_base-port_start"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_loopbackEth:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_loopbackEth"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_loopbackPort:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_loopbackPort"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor:

Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor-post"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor_protocol:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_monitor_protocol"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_tls-enable

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_tls-enable"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_offline

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_offline"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_sc-vip-ipv6

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_sc-vip-ipv6"

      Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vip-interface

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vip-interface"

      Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vip-ipv6-port

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vip-ipv6-port"

      Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vrf

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6-sc-vip-ipv6_vrf"

      Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip"

      Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip_offline

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id-ide_epdr_ep-ep-type_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip_offline"
```

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-se-vip-se-vip-se-vip-ip-se-vip-ip

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa-instance_instance-id_instance-id-ie-endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_se-vip_se-vip-se-vip-ip_se-vip-ip"

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-se-vip-se-vip-se-vip-ip-vip-interface

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa-instance_instance-id_instance-id-ie-endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_se-vip_se-vip-se-vip-ip_vip-interface"

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-se-vip-se-vip-se-vip-ip-vip-port

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa-instance_instance-id_instance-id-ie-endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_se-vip_se-vip-se-vip-ip_vip-port"

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-se-vip-se-vip-se-vip-ip-vrf

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa-instance_instance-id_instance-id-ie-endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_se-vip_se-vip-se-vip-ip_vrf"

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-sla

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa-instance_instance-id_instance-id-ie-endpoint_ep-ep-ep-type_service_service-service-name_interface_interface-interface-type_sla"

Required/Optional: true

data_tailf-mobile-ifa-instance-instance-id-instance-id-ie-endpoint_ep-ep-ep-type-service-service-service-name-interface-interface-interface-type-sla-port

Content:
application/yang-data+json:

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_sla-post"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_sla_procedure

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_sla_procedure"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_sla_response

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_sla_response"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_tls-enable

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_tls-enable"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_uri-scheme

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_uri-scheme"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6"

      Required/Optional: true
```

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6port

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6port"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf"

Required/Optional: true

data_tailf-mobile-ifa_instance_instance-id_instance-id_endpoint_ep_ep-type_service_service-name_interface_interface-interface-type_vip_vip-vip-ip

Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-ide_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_vrf

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post"
```

```
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent"
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs"
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine"
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical"
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post"
      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent:

```
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline"

Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline"

Required/Optional: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port"

      Required/Optional: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf"

      Required/Optional: true
    data_tailf-mobile-infra_instance_instance-id_instance-id-id_id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id"
      Required/Optional: true
    data_tailf-mobile-infra_instances:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_instances"
      Required/Optional: true
    data_tailf-mobile-infra_instances-post:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_tailf-mobile-infra_instances-post"
      Required/Optional: true
    data_tailf-mobile-infra_instances_instance_instance-instance-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id"
      Required/Optional: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id"

      Required/Optional: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id"

      Required/Optional: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name"

      Required/Optional: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id"

      Required/Optional: true
    data_tailf-mobile-infra_k8:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_k8"
      Required/Optional: true
```

```
    data_tailf-mobile-infra_k8-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_k8-post"
      Required/Optional: true
    data_tailf-mobile-infra_k8_label:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label"
      Required/Optional: true
    data_tailf-mobile-infra_k8_label-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_k8_label-post"
      Required/Optional: true
```

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value"

      Required/Optional: true
```

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key:

```
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key"

      Required/Optional: true
```

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group:

```
      Description: Group for the VMs
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group"

      Required/Optional: true
```

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value:

```
      Description: Value for the label
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value"

      Required/Optional: true
    data_tailf-mobile-infra_load:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_load"
      Required/Optional: true
    data_tailf-mobile-infra_load-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_load-post"
      Required/Optional: true
    data_tailf-mobile-infra_load_factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor"
      Required/Optional: true
    data_tailf-mobile-infra_load_factor-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_load_factor-post"
      Required/Optional: true
    data_tailf-mobile-infra_load_factor_calc-frequency:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_calc-frequency"
      Required/Optional: true
   data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type"

      Required/Optional: true

data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type:

      Description: Default set to exclude all infra-pods
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_load_factor_exclude-pods_exclude-pods-pod-type_pod-type"

      Required/Optional: true
    data_tailf-mobile-infra_local-instance:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance"
      Required/Optional: true
    data_tailf-mobile-infra_local-instance-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_local-instance-post"

      Required/Optional: true
    data_tailf-mobile-infra_local-instance_instance:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_local-instance_instance"
      Required/Optional: true
    data_tailf-mobile-infra_logging:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging"
      Required/Optional: true
    data_tailf-mobile-infra_logging-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async-post"

      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application_enable-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_application_enable_buffer-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size"

      Required/Optional: true
    data_tailf-mobile-infra_logging_async_monitor-subscriber:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_monitor-subscriber-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_monitor-subscriber_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_monitor-subscriber_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post"

      Required/Optional: true

data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size"

      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_tailf-mobile-infra_logging_async_tracing"

      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing_enable-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction_enable-post:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size"

      Required/Optional: true
    data_tailf-mobile-infra_logging_error:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error"
      Required/Optional: true
    data_tailf-mobile-infra_logging_error-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error-post"

      Required/Optional: true
    data_tailf-mobile-infra_logging_error_stack:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_logging_error_stack"

      Required/Optional: true
    data_tailf-mobile-infra_logging_json-logging:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_logging_json-logging"

      Required/Optional: true
    data_tailf-mobile-infra_logging_json-logging-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_json-logging_application:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_application"
      Required/Optional: true
```

```
    data_tailf-mobile-infra_logging_json-logging_monitor-subscriber:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_monitor-subscriber"
      Required/Optional: true
    data_tailf-mobile-infra_logging_json-logging_transaction:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_json-logging_transaction"
      Required/Optional: true
    data_tailf-mobile-infra_logging_level:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level"
      Required/Optional: true
    data_tailf-mobile-infra_logging_level-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level-post"

      Required/Optional: true
    data_tailf-mobile-infra_logging_level_application:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_application"
      Required/Optional: true
    data_tailf-mobile-infra_logging_level_monitor-subscriber:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber"
      Required/Optional: true
    data_tailf-mobile-infra_logging_level_tracing:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_logging_level_tracing"

      Required/Optional: true
    data_tailf-mobile-infra_logging_level_transaction:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_logging_level_transaction"
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name"
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_level:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level"
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_level-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_level_application:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application"

      Required/Optional: true

data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber"

      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_level_tracing:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing"
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_level_transaction:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_logging_logger_logger-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_logging_transaction"

      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction-post"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction_duplicate:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction_max-file-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction_max-rotation:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction_message:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_message"
      Required/Optional: true
    data_tailf-mobile-infra_logging_transaction_persist:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist"
      Required/Optional: true
    data_tailf-mobile-infra_monitor:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor"
      Required/Optional: true
    data_tailf-mobile-infra_monitor-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor-post"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_active-instance-traffic:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_active-instance-traffic-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic-post"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_active-instance-traffic_action:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_action"
      Required/Optional: true

data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_no-traffic-duration"

      Required/Optional: true

data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_active-instance-traffic_session-threshold"

      Required/Optional: true
    data_tailf-mobile-infra_monitor_bfd:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_bfd-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_bfd-post"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_bfd_node-status:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_internal-vip-ipc:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_internal-vip-ipc-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc-post"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_internal-vip-ipc_max-conn-downtime"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_nf:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf"
      Required/Optional: true
    data_tailf-mobile-infra_monitor_nf-post:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_nf-post"
        Required/Optional: true
      data_tailf-mobile-infra_monitor_protocol:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol"
        Required/Optional: true
      data_tailf-mobile-infra_monitor_protocol-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_monitor_protocol-post"

        Required/Optional: true
      data_tailf-mobile-infra_monitor_protocol_cpu-limit:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit"
        Required/Optional: true
      data_tailf-mobile-infra_nodemonitor:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor"
        Required/Optional: true
      data_tailf-mobile-infra_nodemonitor-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor-post"
        Required/Optional: true
      data_tailf-mobile-infra_nodemonitor_interval:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval"

        Required/Optional: true
      data_tailf-mobile-infra_nodemonitor_mode:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode"
        Required/Optional: true
      data_tailf-mobile-infra_peers:
        Content:
          application/yang-data+json:
```

```
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_peers"
        Required/Optional: true
      data_tailf-mobile-infra_peers-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_peers-post"
        Required/Optional: true
      data_tailf-mobile-infra_resource:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_resource"
        Required/Optional: true
      data_tailf-mobile-infra_resource-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_tailf-mobile-infra_resource-post"
        Required/Optional: true
      data_tailf-mobile-infra_resource_pod_pod-podtype:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype"
        Required/Optional: true
      data_tailf-mobile-infra_resource_pod_pod-podtype_cpu:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu"
        Required/Optional: true
      data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post"
        Required/Optional: true
      data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit"
        Required/Optional: true
      data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request:
        Content:
          application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_labels:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key:
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gogc"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_gomemlimit"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request"
      Required/Optional: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_podtype:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype"
      Required/Optional: true
    data_tailf-mobile-infra_resources:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_resources"
      Required/Optional: true
    data_tailf-mobile-infra_resources-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_resources-post"
      Required/Optional: true
    data_tailf-mobile-infra_router:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_tailf-mobile-infra_router"
      Required/Optional: true
    data_tailf-mobile-infra_router-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router-post"
      Required/Optional: true
    data_tailf-mobile-infra_router_bfd:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd"
      Required/Optional: true
    data_tailf-mobile-infra_router_bfd-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd-post"
      Required/Optional: true
    data_tailf-mobile-infra_router_bfd_instance:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_router_bfd_instance"

      Required/Optional: true
    data_tailf-mobile-infra_router_bfd_instance-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance-post"
      Required/Optional: true
   data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id"

      Required/Optional: true

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id"

      Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface"

Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip"

Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface"

Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor"

Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor"

Required/Optional: true
```

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf:

```
Content:
  application/yang-data+json:
    Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier"
      Required/Optional: true
```

```
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp"
      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor"
```

```
      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf"

      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute"

      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort"
```

```
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort"
      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface"

      Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix"

Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute"

Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range"

Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp"

Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name"

Required/Optional: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix"

Required/Optional: true
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend:
Content:
application/yang-data+json:

```
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post"
      Required/Optional: true
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path"
      Required/Optional: true
    data_tailf-mobile-infra_router_monitor-interface:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface"
      Required/Optional: true
    data_tailf-mobile-infra_router_monitor-interface-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface-post"
      Required/Optional: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface"

      Required/Optional: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface"

      Required/Optional: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type"

      Required/Optional: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface"

      Required/Optional: true
    data_tailf-mobile-infra_rpc:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_rpc"
      Required/Optional: true
    data_tailf-mobile-infra_rpc-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_rpc-post"
      Required/Optional: true
    data_tailf-mobile-infra_running-status:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_running-status"
      Required/Optional: true
    data_tailf-mobile-infra_running-status-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_tailf-mobile-infra_running-status-post"

      Required/Optional: true
    data_tailf-mobile-infra_sessions:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_sessions"
      Required/Optional: true
    data_tailf-mobile-infra_sessions-post:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_tailf-mobile-infra_sessions-post"
      Required/Optional: true
    data_tailf-mobile-infra_vrf:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf"
      Required/Optional: true
    data_tailf-mobile-infra_vrf-info:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info"
      Required/Optional: true
    data_tailf-mobile-infra_vrf-info-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-info-post"
      Required/Optional: true
    data_tailf-mobile-infra_vrf-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_tailf-mobile-infra_vrf-post"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice"
      Required/Optional: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name"
      Required/Optional: true
  securitySchemes:
    basicAuth:
      Type: http
      scheme: basic
```