



Workorders API

This chapter describes the Workorders API:

- [Using the Workorders API, page 53](#)
- [Audit API Method Calls, page 53](#)

Using the Workorders API

These APIs talk with any cloud-based management services. It contains seven primary action calls sent using the SOAP envelope over HTTP(s):

`https://<server_address>:portnumber/nbapi/workorder`

Audit API Method Calls

- [RequestUserAuthentication, page 54](#)
- [RequestSignedAuthorization, page 56](#)
- [UploadServiceReport, page 60](#)

RequestUserAuthentication

This call requests user authentication with the cloud service. The utility field technician must sign in to IoT FND before they can use the field tool. The username and password is encrypted and cached in the device for remote connections. Below is the definition for this action based on the Cisco HSL language:

Struct UserAuthInfo

```
String appVersion      ## CG-NMS application version for version control
String scriptVersion   ## CG-NMS button script version for version control
```

Enum UserAuthResult

```
"AUTH_OK"              ## Authentication OK
"AUTH_OK_NO_PERMISSION" ## Authentication OK but no permission to access resources
"AUTH_OK_VER_MISMATCH" ## Authentication Fail - User/Pwd may be ok but the version is
                        ## not expected
"AUTH_FAIL"            ## NOTE: This may never appear in the SOAP response as some
                        ## web servers will return http status code 40x if auth fails.
                        ## Both the 40x status code and AUTH_FAIL in the SOAP response
                        ## are handled.
```

Struct UserAuthResponseInfo

```
UserAuthResult   userAuthResult      ## Authentication result
String           expectAppVer        ## [Optional] If the current app version
String           expectScriptVer     ## If the current script version needs to be
                                     ## upgraded
```

Struct UserAuthResponse

Input:

```
UserAuthInfo      userAuthInfo
```

Output:

```
UserAuthResponse  RequestUserAuthenticationResponse
```

Action RequestUserAuthentication

```
UserAuthResponseInfo userAuthResponse      ## Authentication result
```

SOAP XML Request Format

```
POST /nms/fieldtool HTTP/1.1
Host: sample.cisco.com:8080
Content-Length: nnn
Authorization: Basic bW2eFaHU5K+
SOAPAction: http://workorder.nbapi.cgms.cisco.com/RequestUserAuthentication
Connection: close
Content-type: text/xml; charset="UTF-8"
User-Agent: Cisco Device Management Application
```

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
  <SOAP-ENV:Body>
    <m:RequestUserAuthentication>
      <userAuthInfo>
        <appVersion>1.2.23.128</appVersion>
        <scriptVersion>2.3.4</scriptVersion>
```

Audit API Method Calls

```
        </userAuthInfo>
    </m:RequestUserAuthentication>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Response

```
HTTP/1.1 200 OK
Content-type: text/xml; charset="UTF-8"
Content-Length: nnn
```

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
  <SOAP-ENV:Body>
    <m:RequestUserAuthenticationResponse xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
      <userAuthResponse>
        <userAuthResult>AUTH_OK</userAuthResult>
        <expectAppVer>1.2.25.02</expectAppVer>
        <expectScriptVer>2.3.5</expectScriptVer>
      </userAuthResponse>
    </m:RequestUserAuthenticationResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

RequestSignedAuthorization

This call retrieves work authorizations from the cloud service. For security, the utility technician requests work authorizations from the management cloud service before they can complete the work order.

Enum UserRole

```
"ADMIN"    ## Unlimited commands
"TECH"     ## Most commands and interface configure
"VIEWER"   ## Read only commands
```

Struct DeviceInfo

```
String     deviceId          ## Device unique ID such as serial number
String     ssid              ## WiFi SSID for a specific FAR device
String     passphrase        ## WiFi Passphrase for a specific FAR device
String     firmwareVersion   ## [Optional] Firmware version for this device. If present,
                             ## CG-NMS needs to request it from NMS/Cloud
String     configurationId    ## [Optional] Unique configuration profile id for this
                             ## device. If present, Bahamas needs to request it from
                             ## NMS/Cloud
```

Attribute CanonicalizationTheMethod

```
String     Algorithm
```

Attribute SignatureTheMethod

```
String     Algorithm
```

Attribute TransformTheMethod

```
String     Algorithm
```

Attribute DigestTheMethod

```
String     Algorithm
```

Struct TransformsInfo

```
TransformTheMethod  TransformMethod
```

Struct SignatureReference

```
TransformsInfo      Transforms
DigestTheMethod     DigestMethod
String              DigestValue
```

Struct SignatureSignedInfo

```
CanonicalizationTheMethod CanonicalizationMethod
SignatureTheMethod         SignatureMethod
SignatureReference         Reference          ## Signed info reference
```

Struct SignatureX509Data

```
String     X509SubjectName
String     X509Certificate
```

Struct SignatureKeyInfo

```
SignatureX509Data  X509Data
```

Audit API Method Calls

Struct XMLSignature

```
SignatureSignedInfo SignedInfo
String SignatureValue
SignatureKeyInfo KeyInfo
```

Struct SignedAuth

```
String version ## Version of the schema for signed authorization
String authId ## UID in the string format
String authCreated ## Date String in UTC format
String deviceId ## Device unique ID such as serial number
String technician ## Name of the technician requesting the authorization
UserRole userRole ## What role to manage the FAR
String startDateTime ## Date in UTC string to indicate valid-from
String endDateTime ## Date in UTC string to indicate valid-to
XmlSignature Signature ## The signature info to be passed to FAR
```

Struct SignedAuthorization

```
SignedAuth signedAuth
DeviceInfo deviceInfo ##[Optional]
```

Struct SignedAuthorizationResponse

```
SignedAuthorization[] signedAuthorization
```

Action RequestSignedAuthorization**Input:**

```
String technicianUserName ## The technician username registered with NMS
String workOrderNumber ## If the technician knows a specific name, he can
## put it here; otherwise put null string will
## retrieve all the orders assigned to him
```

Output:

```
SignedAuthorizationResponse RequestSignedAuthorizationResponse
```

SOAP XML Request Format Request

```
POST /nbapi/workorder HTTP/1.1
Host: 128.154.157.111:8443
Content-Length: nnn
SOAPAction: http://workorder.nbapi.cgms.cisco.com/RequestSignedAuthorization
Authorization: Basic eWfqD54DefCDef4B3aA=
Connection: close
Content-type: text/xml; charset="UTF-8"
User-Agent: Cisco Device Management Application

<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
  <SOAP-ENV:Body>
    <m:RequestSignedAuthorization>
      <technicianUserName>bob</technicianUserName>
      <workOrderNumber>abcd-efgh-hijk</workOrderNumber>
    </m:RequestSignedAuthorization>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Audit API Method Calls

Response

HTTP/1.1 200 OK

Content-type: text/xml; charset="UTF-8"

Content-Length: nnn

```

<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
  <SOAP-ENV:Body>
    <m:RequestSignedAuthorizationResponse xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
      <signedAuthorization>
        <signedAuth>
          <version>1</version>
          <orderNumber>9429C098-495A-402C-9456-57F3CC7475BF</orderNumber>
          <authCreated>2011-09-20T03:48:28Z</authCreated>
          <userRole>tech</userRole>
          <technicianUserName>bob</technicianUserName>
          <deviceId>AB193AQ</deviceId>
          <startDate>2011-09-20T03:48:28Z</startDate>
          <endDate>2011-09-20T09:48:28Z</endDate>
          <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
            <SignedInfo>
              <CanonicalizationMethod
Algorithm="http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments"/>
              <SignatureMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1"/>
              <Reference URI="">
                <Transforms>
                  <TransformMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"/>
                </Transforms>
                <DigestMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>
                <DigestValue>CpJhSOAalu8QJeUX2wiaGG0ZGEk=</DigestValue>
              </Reference>
            </SignedInfo>
            <SignatureValue>
              lgkxD0wRdaAU0vKTVyzbdsLL0c4ONB51LTmmOdWXCYMERwMSy53nWUencU
              h14cmR4rPsumdYWJzCqJik2oci6p8uMnLDCv8=
            </SignatureValue>
            <KeyInfo>
              <X509Data>
                <X509SubjectName>
                  CN=My Name,O=Test Certificates Inc.,C=US
                </X509SubjectName>
                <X509Certificate>
                  MIIB9zCCAWCgAwIBAgIERZwdkzANBgkqhkiG9w0BAQUFADBAMQswCQYD
                  VQQGEwJVUzEfMB0GA1UEChMWVGZzdCBDZXJ0aWZpY2F0ZXZMgSW5jLjE
                  MA4GA1UEAxMHTXkgTmFtZTAeFw0wNzAxMDMyMTE4MTFaFw0zMTA4M
                  ...
                </X509Certificate>
              </X509Data>
            </KeyInfo>
          </Signature>
        </signedAuth>
      </deviceInfo>
      <deviceInfo>
        <deviceId>AB193AQ</deviceId>
        <ssid>testfar</ssid>
        <passphrase>cisco123</passphrase>
        <firmwareVersion>1.2.3</firmwareVersion>
        <configurationId>123.234</configurationId>
      </deviceInfo>
    </signedAuthorization>
  </signedAuthorization>
  ... ..

```

Audit API Method Calls

```
        <signedAuthorization>  
    </m:RequestSignedAuthorizationResponse>  
    </SOAP-ENV:Body>  
</SOAP-ENV:Envelope>
```

UploadServiceReport

This call uploads the service report to the cloud service. IoT FND tracks the service status for a work order, and prompts the utility technician to mark status field as job complete, job expired, job incomplete, and so on. Once work order status is reported, the work order can be safely removed from IoT FND. Work orders are archived on the NMS server.

Enum ServiceReportResult

```
"REPORT_OK"
"REPORT_FAIL"
```

Enum ServiceStatus

```
"Completed"      # The work is done
"Incomplete"     # The work can not be completed due to some reasons
"Expired"        # The work authorization is expired
```

Struct ServiceStatusReport

```
String      orderNumber
String      deviceId
String      technicianUserName
ServiceStaus status
```

Struct ServiceStatusResponse

```
ServiceReportResult result
String               comment      ## [Optional]
```

Struct ServiceReportResponse

```
ServiceStatusResponse serviceReportResponse
```

Action UploadServiceReport

Input:

```
ServiceStatusReport [] serviceStatusReport
```

Output:

```
ServiceReportResponse UploadServiceReportResponse
```

SOAP XML Request Format

```
POST /nms/fieldtool HTTP/1.1
Host: sample.cisco.com:8080
Content-Length: nnn
Authorization: Basic bW2eFaHdD3K
SOAPAction: [http://workorder.nbapi.cgms.cisco.com/UploadServiceReport
] Connection: close
Content-type: text/xml; charset="UTF-8"
User-Agent: Cisco Device Management Application

<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
  <SOAP-ENV:Body>
    <m:UploadServiceReport>
      <m:serviceStatusReport>
        <orderNumber>9429C098-495A-402C-9456-57F3CC7475BF </orderNumber>
        <deviceId>AB193BQ</deviceId>
        <technicianUserName>Bob</technicianUserName>
```


Audit API Method Calls

```
        <status>Completed</status>
    </serviceStatusReport>
    <serviceStatusReport>
        <orderNumber>8688C098-495A-402C-2356-57F3CC7475BF </orderNumber>
        <deviceId>CC210EQ</deviceId>
        <technicianUserName>Alex</technicianUserName>
        <status>Expired</status>
    </serviceStatusReport>
</m:UploadServiceReport>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Response

HTTP/1.1 200 OK

Content-type: text/xml; charset="UTF-8"

Content-Length: nnn

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
  <SOAP-ENV:Body>
    <m:UploadServiceReportResponse xmlns:m="http://workorder.nbapi.cgms.cisco.com/">
      <serviceReportResponse>
        <result>REPORT_FAIL</result>
        <comment>Syntax Error</comment>
      </serviceReportResponse>
    </m:UploadServiceReportResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

