

Release Notes for Cisco Resilient Mesh Release 6.0

First Published: 2018-08-02

Release Notes for Cisco Resilient Mesh Release 6.0

These release notes contain the latest information about using Cisco Resilient Mesh (formerly known as CG-Mesh) with IPv6 Resilient Mesh Endpoints (RMEs) such as meters and the Cisco IR500 Series WPAN Gateway Range Extenders.

Cisco Resilient Mesh is an embedded network stack for Smart Grid assets within a Neighborhood Area Network. Cisco Resilient Mesh provides end-to-end IPv6 communication and implements open-standard protocols at every layer in the network stack, including but not limited to IEEE 802.15.4e/g, 6LoWPAN, IPv6, RPL, UDP, and CoAP. In Smart Grid assets such as residential electric meters, the Cisco Resilient Mesh software functions within a dedicated Communications Module that connects to an Application Module through a PPP link.



Note

For a detailed description of the Cisco Resilient Mesh software in Release 6.0, refer to Cisco Connected Grid WPAN Module for CGR 1000 Series Installation and Cisco Resilient Mesh Configuration Guide.

New Features for This Release

The following table lists the enhancements specific to this release.

Table 1: Enhancements for Cisco Resilient Mesh Release 6.0

Platform	Enhancement	Description	First Cisco IOS/CG-OS Release that Supports the Feature
IR510 IR530	Field Troubleshooting Support	Support for noise measurement/read, Link quality test between two nodes, and notch of high noise/interference channels on specified nodes.	15.8(3)M
IR510 IR530	Parent Selection enhancement	Support to switch between two ETX calculation algorithms for parent selection.	15.8(3)M

Platform	Enhancement	Description	First Cisco IOS/CG-OS Release that Supports the Feature
IR510 IR530	Adaptive Modulation enhancement	Support for self-adapting data rates based on the channel condition.	15.8(3)M
IR510	Access control list support	Support for Access Control based on MAC/IP. Support to send syslog to FND if there is an access violation.	15.8(3)M
IR510	IR510 GPS	Support to report GPS location while register to FND for IR510.	15.8(3)M
IR510 IR530	MAC layer QoS	Support for MAC layer QoS on IR510 and IR530.	15.8(3)M
IR510 IR530	Enhanced firmware download	Firmware download with MPL (RFC 7731).	15.8(3)M
CGR WPAN	CGR High Availability	Provide chassis-based and module based HA for the FAN solution.	15.8(3)M
OFDM WPAN	OFDM WPAN backward compatible with FSK mesh	Enable FSK mode on OFDM WPAN to support 5.6 end points.	15.8(3)M
All platforms	CoAP IETF RFC7252 Compliance	Update CoAP implementation of CSMP from CoAP draft to RFC7252. Resilient Mesh Release 6.0 requires FND Release 4.3 and later for this enhancement.	15.8(3)M

System Requirements

If you plan to run Cisco Resilient Mesh Release 6.0, you must have the following required hardware and software components:

Platform	Minimum Cisco IOS/CG-OS Software Release Required
Cisco 1000 Series Connected Grid Router	Cisco IOS Release 15.8(3)M
Cisco IR530	cg-mesh-node-6.0-6019-ir530-7bee575.bin

Platform	Minimum Cisco IOS/CG-OS Software Release Required
Cisco IR529	cg-mesh-node-6.0-6019-ir529-7bee575.bin
Cisco IR510	cg-mesh-dagw-6.0-6019-ir510-7bee575.bin
Cisco IR509	cg-mesh-dagw-6.0-6019-ir509-7bee575.bin
WPAN module (CGM-WPAN-FSK-NA)	cg-mesh-bridge-ITRDPKG-6.0-6019-iron30-7bee575.bin
OFDM WPAN (CGM-WPAN-OFDM-FCC)	cg-mesh-bridge-6.0-6019-ir510-7bee575.bin
IoT Field Network Director	Release 4.3
IOX	AC8

Supported Software Features

This section covers the supported software features.

Compromised Node Eviction

A compromised node is one where the device can no longer be trusted by the network and/or operators. Nodes within an IEEE 802.15.4 PAN must possess the currently valid Group Temporal Key (GTK) to send and receive link-layer messages. The GTK is shared among all devices within the PAN and is refreshed periodically or on-demand. By communicating new GTKs to only trusted devices, compromised nodes may be evicted from the network.

RPL

In its route-over architecture, Cisco Resilient Mesh performs routing at the network layer using the Routing Protocol for Low-Power and Lossy Networks (RPL).

Cisco Resilient Mesh requires a Cisco 1000 Series Connected Grid Router (CGR) to provide connectivity to other IPv6 networks. The CGR (Field Area Router (FAR)) must serve as a RPL Directed Acyclic Graph (DAG) root and store information reported in DAO messages to forward datagrams to individual nodes within the mesh network.

6LoWPAN

The 6LoWPAN adaptation layer adapts IPv6 to operate efficiently over low-power and lossy links such as IEEE 802.15.4. The adaptation layer sits between the IPv6 and IEEE 802.15.4 layers and provides IPv6 header compression, IPv6 datagram fragmentation, and optimized IPv6 Neighbor Discovery.

Frequency Hopping

Cisco Resilient Mesh implements frequency hopping across 64 channels with 400-kHz spacing in the 902 to 928 MHz ISM band. The frequency-hopping protocol used by Cisco Resilient Mesh maximizes the use of the available spectrum by allowing multiple sender-receiver pairs to communicate simultaneously on different channels. The frequency hopping protocol also mitigates the negative effects of narrowband interferers.



Note For IR510 and IR530 endpoints, high data rates 800kHz with 31 channels are also supported.

Firmware Upgrade Procedure

The Cisco Resilient Mesh bridge firmware can be installed by CLI or from IoT FND.

For more information on upgrading the firmware, see the latest Release Notes for Cisco 1000 Series Connected Grid Routers for Cisco IOS Release at: www.cisco.com/go/cgr1000-docs.

FND Configuration

Cisco Resilient Mesh solution is managed and monitored by the Cisco IoT Field Network Director (FND), which provides the necessary backend network configuration, monitoring, event notification services, network stack firmware upgrade, as well as FND outage and meter registration. IoT FND also retrieves statistics on network traffic from the interface.



Note For a detailed description on the Cisco Resilient Mesh CLI, refer to [Cisco Connected Grid WPAN Module for CGR 1000 Series Installation and Cisco Resilient Mesh Configuration Guide \(Cisco IOS\)](#).



Note IR510 and IR530 will be supported only with FND Release 4.1 or greater. Refer to the [Cisco IoT Field Network Director User Guides](#) for details.

CoAP Simple Management Protocol

Cisco Resilient Mesh implements the CoAP Simple Management Protocol (CSMP) for remote configuration, monitoring, and event generation over the IPv6 network. The CSMP service is exposed over both the mesh and serial interfaces.

Power-outage Notification

Cisco Resilient Mesh supports timely and efficient reporting of power outages and restorations.

In the event of a power outage, Cisco Resilient Mesh enters power-outage notification mode and the node stops listening for traffic to conserve energy. Cisco Resilient Mesh triggers functions to conserve energy by notifying the communication module and neighboring nodes of the outage. The outage notification is sent using the same security settings as any other UDP/IPv6 datagram transmission.

In the event of a power restoration, a Cisco Resilient Mesh node sends a restoration notification using the same communication method as the outage notification. The communication modules unaffected by the power outage event deliver the restoration notification.

Registration of Endpoint

You can register and manage Cisco Resilient Mesh Endpoints (RMEs) such as (meters) using the CSMP protocol.

Limitations and Restrictions

Cisco recommends that you review this section before you begin working with the module. These are known limitations that will not be fixed, and there is not always a workaround for these issues. Some features might not work as documented, and some features might be affected by recent changes to the CG-OS router hardware or software.

- **CSCub49104**

Symptom: Output from **show mesh-security session all** does not show all current mesh security sessions.

Conditions: This issue occurs in the output of the **show mesh-security session all** command.

Workaround: To find out the mesh-key status of a meter, use the **show mesh-security session mac <mac-address>** command.

Caveats

This section addresses the Open and Resolved caveats that are relevant to Cisco Resilient Mesh. This section also provides information on how to use the Bug Tool Kit to find further details on the caveats.

Open Caveats

This section summarizes open caveats to the Cisco Resilient Mesh.

- **CSCvg11696**

Symptom: IR510: IPv6 Ethernet address is shown as lowpan address.

Workaround: When configuring FND global IPv6 address, the **address-match-length** of FND and node's lowpan address should be greater than that of FND and node's Ethernet address.

- **CSCvg13367**

Symptom: Node could not display more than 13 PLC hardware link neighbors in TLV95.

Condition: Because the limitation of CSMP packet size, one packet can only hold 13 PLC neighbor information.

- **CSCvk44604**

Symptom: Node detaches to its parents in adaptive mode when average resend times larger than four.

Condition: This occurs when adaptive modulation is enabled with IR510 or IR530.

Workaround: Make the signal good or avoid heavy traffic congestion, and node will restore to its parents.

Resolved Caveats

This section summarizes resolved caveats to the Cisco Resilient Mesh.

- **CSCvf50506**

IR510: Node fast reform online with backup parent takes more than 20 mins.

- **CSCvf78106**

IR510: Node switch parent frequently on OTA testbed.

- CSCvg87873

1/1000 Duplicated Packets on PLC media when node have only one parent.

- CSCvh03696

Node probably fails to sync with beac schedule in master-slave mode.

Accessing Bug Search Tool

You can use the Bug Search Tool to find information about caveats for this release, including a description of the problems and available workarounds. The Bug Search Tool lists both open and resolved caveats.

To access Bug Search Tool, you need the following items:

- Internet connection
- Web browser
- Cisco.com user ID and password

To access the Bug Search Tool, enter the following URL:

<https://tools.cisco.com/bugsearch/search>

Accessing Error Message Decoder

You can look up explanations for console error message strings found in system logs at the following location:

http://www.cisco.com/en/US/partner/support/tsd_most_requested_tools.html

Feature History

Feature	Cisco IOS/CG-OS Release	Feature information
Cisco Resilient Mesh firmware 6.0	Cisco IOS Release 15.8(3)M	Cisco Resilient Mesh enhancement.

Related Documentation

Consult the following resources for related information about the Connected Grid WPAN Module for technical assistance.

Hardware Overview and Installation

- IR510 WPAN Gateway and IR530 WPAN Range Extender Hardware Installation Guide

https://www.cisco.com/c/en/us/td/docs/routers/ir510-ir530/hig/ir5X0_wpan_HIG.html

- Cisco CG-OS Release Notes for CGR 1000

<http://www.cisco.com/go/cgr1000-docs>

- Cisco Connected Grid Module Guides
<http://www.cisco.com/go/cg-modules>
- Cisco CGR 1240 Hardware Installation Guide
<http://www.cisco.com/go/cgr1000-docs>
- Cisco CGR 1120 Hardware Installation Guide
<http://www.cisco.com/go/cgr1000-docs>

Supported Cisco Antennas and Accessories

Cisco CGR 1000 and 2000 Series Connected Grid Antennas Guides

http://www.cisco.com/en/US/docs/routers/connectedgrid/antennas/installing_cg_antenna_install_guide.html

Regulatory Compliance and Safety Information

Cisco Network Modules and Interface Cards Regulatory Compliance and Safety Information

<http://www.cisco.com/en/US/docs/routers/access/interfaces/rcsi/IOHrcsi.html>

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com go trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2018 Cisco Systems, Inc. All rights reserved.