



Virtual Private LAN Services Commands

This module describes the commands used to configure, monitor, and troubleshoot Virtual Private LAN Services (VPLS).

For detailed information about virtual private network concepts, configuration tasks, and examples, refer to the *Virtual Private Configuration Guide*.

- [action \(VPLS\), page 3](#)
- [aging \(VPLS\), page 5](#)
- [bridge-domain \(VPLS\), page 7](#)
- [bridge group \(VPLS\), page 9](#)
- [clear l2vpn bridge-domain \(VPLS\), page 11](#)
- [flooding disable, page 13](#)
- [interface \(VPLS\), page 15](#)
- [learning disable \(VPLS\), page 17](#)
- [limit \(VPLS\), page 19](#)
- [mac \(VPLS\), page 21](#)
- [maximum \(VPLS\), page 23](#)
- [mpls static label \(VPLS\), page 25](#)
- [mtu \(VPLS\), page 27](#)
- [neighbor \(VPLS\), page 29](#)
- [notification \(VPLS\), page 31](#)
- [port-down flush disable \(VPLS\), page 33](#)
- [pw-class \(VFI\), page 35](#)
- [show l2vpn bridge-domain \(VPLS\), page 37](#)
- [show l2vpn forwarding bridge-domain \(VPLS\), page 45](#)
- [show l2vpn forwarding bridge-domain mac-address \(VPLS\), page 59](#)
- [shutdown \(Bridge Domain\), page 69](#)

- [shutdown \(VFI\), page 71](#)
- [static-address \(VPLS\), page 73](#)
- [static-mac-address \(VPLS\), page 75](#)
- [time \(VPLS\), page 77](#)
- [type \(VPLS\), page 79](#)
- [vfi \(VPLS\), page 81](#)
- [withdraw \(VPLS\), page 83](#)

action (VPLS)

To configure the bridge behavior when the number of learned MAC addresses reaches the MAC limit configured, use the **action** command in L2VPN bridge group bridge domain MAC limit configuration mode. To disable this feature, use the **no** form of this command.

action {**flood**| **no-flood**| **shutdown**}

no action {**flood**| **no-flood**| **shutdown**}

Syntax Description

flood	Configures the action to flood all unknown unicast packets when the MAC limit is reached. If the action is set to flood, all unknown unicast packets, with unknown destinations addresses, are flooded over the bridge.
no-flood	Configures the action to no-flood so all unknown unicast packets are dropped when the MAC limit is reached. If the action is set to no-flood, all unknown unicast packets, with unknown destination addresses, are dropped.
shutdown	Stops forwarding when the MAC limit is reached. If the action is set to shutdown, all packets are dropped.

Command Default

No action is taken when the MAC address limit is reached.

Command Modes

L2VPN bridge group bridge domain MAC limit configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **action** command to specify the type of action to be taken when the action is violated.

The configured action has no impact if the MAC limit has not been reached.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to configure the bridge bar to flood all unknown unicast packets when the number of MAC addresses learned by the bridge reaches 10:

```
RP/0/RP0/CPU0:router#configure
RP/0/RP0/CPU0:router (config)#l2vpn
RP/0/RP0/CPU0:router (config-l2vpn)#bridge group 1
RP/0/RP0/CPU0:router (config-l2vpn-bg)#bridge-domain bar
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd)#mac
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-mac)#limit
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-mac-limit)#action flood
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-mac-limit)#maximum 10
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
limit (VPLS), on page 19	Sets the MAC address limit for action, maximum, and notification and enters L2VPN bridge group bridge domain MAC limit configuration mode.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
maximum (VPLS), on page 23	Configures the specified action when the number of MAC addresses learned on a bridge is reached.
notification (VPLS), on page 31	Specifies the type of notification that is sent when the number of learned MAC addresses exceeds the configured limit.

aging (VPLS)

To enter the MAC aging configuration submode to set the aging parameters such as time and type, use the **aging** command in L2VPN bridge group bridge domain configuration mode. To return to the default value for all parameters that are attached to this configuration submode, use the **no** form of this command.

aging

no aging

Syntax Description This command has no keywords or arguments.

Command Default No defaults are attached to this parameter since it is used as a configuration submode. See defaults that are assigned to the [time \(VPLS\), on page 77](#) and the [type \(VPLS\), on page 79](#) parameters.

Command Modes L2VPN bridge group bridge domain MAC configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **aging** command to enter L2VPN bridge group bridge domain MAC aging configuration mode.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to enter MAC aging configuration submode and to set the MAC aging time to 120 seconds:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# aging
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-aging)# time 120
```

Related Commands

Commands	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then assigns network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
time (VPLS), on page 77	Configures the maximum aging time.
type (VPLS), on page 79	Configures the type for MAC address aging.

bridge-domain (VPLS)

To establish a bridge domain and to enter L2VPN bridge group bridge domain configuration mode, use the **bridge-domain** command in L2VPN bridge group configuration mode. To return to a single bridge domain, use the **no** form of this command.

bridge-domain *bridge-domain-name*

no bridge-domain *bridge-domain-name*

Syntax Description

bridge-domain-name

Name of the bridge domain.

Note The maximum number of characters that can be specified in the bridge domain name is 27.

Command Default

The default value is a single bridge domain.

Command Modes

L2VPN bridge group configuration

Command History

Release

Modification

Release 3.8.0

This command was introduced.

Usage Guidelines

Use the **bridge-domain** command to enter L2VPN bridge group bridge domain configuration mode.

Task ID

Task ID

Operations

l2vpn

read, write

Examples

The following example shows how to configure a bridge domain:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)#
```

Related Commands

Command	Description
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.

bridge group (VPLS)

To create a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain, use the **bridge group** command in L2VPN configuration mode. To remove all the bridge domains that are created under this bridge group and to remove all network interfaces that are assigned under this bridge group, use the **no** form of this command.

bridge group *bridge-group-name*

no bridge-group *bridge-group-name*

Syntax Description	
<i>bridge-group-name</i>	Number of the bridge group to which the interface belongs.

Command Default No bridge group is created.

Command Modes L2VPN configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **bridge group** command to enter L2VPN bridge group configuration mode.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows that bridge group 1 is assigned:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)#
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
l2vpn	Enters L2VPN configuration mode.

clear l2vpn bridge-domain (VPLS)

To clear the MAC addresses and to restart the bridge domains on the router, use the **clear l2vpn bridge-domain** command in EXEC mode.

```
clear l2vpn bridge-domain {all| bd-name name| group group}
```

Syntax Description		
all		Clears and restarts all the bridge domains on the router.
bd-name <i>name</i>		Clears and restarts the specified bridge domain. The <i>name</i> argument specifies the name of the bridge-domain.
group <i>group</i>		Clears and restarts all the bridge domains that are part of the bridge group.

Command Default None

Command Modes EXEC

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

This is the method that allows a bridge to forward again after it was put in Shutdown state as a result of exceeding the configured MAC limit.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to clear all the MAC addresses and to restart all the bridge domains on the router:

```
RP/0/RP0/CPU0:router# clear l2vpn bridge-domain all
```

clear l2vpn bridge-domain (VPLS)**Related Commands**

Command	Description
show l2vpn bridge-domain (VPLS) , on page 37	Display information for the bridge ports such as attachment circuits and pseudowires for the specific bridge domains.

flooding disable

To configure flooding for traffic at the bridge domain level or at the bridge port level, use the **flooding disable** command in L2VPN bridge group bridge domain configuration mode. To return the bridge to normal flooding behavior when all unknown unicast packets, all broadcast packets, and all multicast packets are flooded over all other bridge domain network interfaces, use the **no** form of this command.

flooding disable

no flooding disable

This command has no keywords or arguments.

Command Default

The default behavior is that packets are flooded when their destination MAC address is not found.

Command Modes

L2VPN bridge group bridge domain configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **flooding disable** command to override the parent bridge configuration.

By default, bridge ports inherit the flooding behavior of the bridge domain.

When flooding is disabled, all unknown unicast packets, all broadcast packets, and all multicast packets are discarded.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to disable flooding on the bridge domain called bar:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# flooding disable
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mtu (VPLS), on page 27	Adjusts the maximum packet size or maximum transmission unit (MTU) size for the bridge domain.

interface (VPLS)

To add an interface to a bridge domain that allows packets to be forwarded and received from other interfaces that are part of the same bridge domain, use the **interface** command in L2VPN bridge group bridge domain configuration mode. To remove an interface from a bridge domain, use the **no** form of this command.

interface *type interface-path-id*

no interface *type interface-path-id*

Syntax Description

<i>type</i>	Interface type. For more information, use the question mark (?) online help function.
<i>interface-path-id</i>	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.

Command Default

None

Command Modes

L2VPN bridge group bridge domain configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **interface** command to enter L2VPN bridge group bridge domain attachment circuit configuration mode. In addition, the **interface** command enters the interface configuration submode to configure parameters specific to the interface.

By default, an interface is not part of a bridge.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to configure the bundle Ethernet interface as an attachment circuit:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router (config)# l2vpn
RP/0/RP0/CPU0:router (config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router (config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd)# interface gigabitethernet 0/1/0/9
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-ac)#
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.

learning disable (VPLS)

To override the MAC learning configuration of a parent bridge or to set the MAC learning configuration of a bridge, use the **learning disable** command in L2VPN bridge group bridge domain MAC configuration mode. To disable this feature, use the **no** form of this command.

learning disable

no learning disable

Syntax Description This command has no keywords or arguments.

Command Default By default, learning is enabled on all bridge domains and all interfaces on that bridge inherits this behavior.

Command Modes L2VPN bridge group bridge domain MAC configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

When set, the **learning disable** command stops all MAC learning either on the specified interface or the bridge domain.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples In the following example, MAC learning is disabled on all ports in the bridge domain called bar, which is applied to all interfaces in the bridge unless the interface has its own MAC learning enable command.

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# learning disable
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.

limit (VPLS)

To set the MAC address limit for action, maximum, and notification and to enter L2VPN bridge group bridge domain MAC limit configuration mode, use the **limit** command in L2VPN bridge group bridge domain MAC configuration mode. To remove all limits that were previously configured under the MAC configuration submodes, use the **no** form of this command.

limit

no limit

Syntax Description This command has no keywords or arguments.

Command Default None

Command Modes L2VPN bridge group bridge domain MAC configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **limit** command to enter L2VPN bridge group bridge domain MAC limit configuration mode. The **limit** command specifies that one syslog message is sent or a corresponding trap is generated with the MAC limit when the action is violated.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how the MAC limit for the bridge bar is set to 100 with an action of shutdown. After the configuration, the bridge stops all forwarding after 100 MAC addresses are learned. When this happens, a syslog message and an SNMP trap are created.

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
```

```

RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# limit
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-limit)# maximum 100
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-limit)# action shutdown
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-limit)# notification both

```

Related Commands

Command	Description
action (VPLS), on page 3	Configures bridge behavior when the number of learned MAC addresses reaches the MAC limit configured.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
maximum (VPLS), on page 23	Configures the specified action when the number of MAC addresses learned on a bridge is reached.
notification (VPLS), on page 31	Specifies the type of notification that is sent when the number of learned MAC addresses exceeds the configured limit.

mac (VPLS)

To enter L2VPN bridge group bridge domain MAC configuration mode, use the **mac** command in L2VPN bridge group bridge domain configuration mode. To disable all configurations added under the MAC configuration submodes, use the **no** form of this command.

mac

no mac

Syntax Description This command has no keywords or arguments.

Command Default None

Command Modes L2VPN bridge group bridge domain configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **mac** command to enter L2VPN bridge group bridge domain MAC configuration mode.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to enter L2VPN bridge group bridge domain MAC configuration mode:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)#
```

Related Commands

Command	Description
aging (VPLS), on page 5	Enters the MAC aging configuration submode to set the aging parameters such as time and type.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
learning disable (VPLS), on page 17	Overrides the MAC learning configuration of a parent bridge or sets the MAC learning configuration of a bridge.
limit (VPLS), on page 19	Sets the MAC address limit for action, maximum, and notification and enters L2VPN bridge group bridge domain MAC limit configuration mode.
static-address (VPLS), on page 73	Adds static entries to the MAC address for filtering.
withdraw (VPLS), on page 83	Disables MAC address withdrawal for a specified bridge domain

maximum (VPLS)

To configure the specified action when the number of MAC addresses learned on a bridge is reached, use the **maximum** command in L2VPN bridge group bridge domain MAC limit configuration mode. To disable this feature, use the **no** form of this command.

maximum *value*

no maximum *value*

Syntax Description

<i>value</i>	Maximum number of learned MAC addresses. The range is from 5 to 512000.
--------------	--

Command Default

The default maximum value is 4000.

Command Modes

L2VPN bridge group bridge domain MAC limit configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The action can either be flood, no flood, or shutdown. Depending on the configuration, a syslog, an SNMP trap notification, or both are issued.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows when the number of MAC address learned on the bridge reaches 5000 and the bridge stops learning but continues flooding:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
```

```
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# limit
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-limit)# maximum 5000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-limit)# action no-flood
```

Related Commands

Command	Description
action (VPLS), on page 3	Configures bridge behavior when the number of learned MAC addresses reaches the MAC limit configured.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
limit (VPLS), on page 19	Sets the MAC address limit for action, maximum, and notification and enters L2VPN bridge group bridge domain MAC limit configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
notification (VPLS), on page 31	Specifies the type of notification that is sent when the number of learned MAC addresses exceeds the configured limit.

mpls static label (VPLS)

To configure the MPLS static labels and the static labels for the access pseudowire configuration, use the **mpls static label** command in L2VPN bridge group bridge domain VFI pseudowire configuration mode. To assign the dynamic MPLS labels to either the virtual forwarding interface (VFI) pseudowire or the access pseudowire, use the **no** form of this command.

mpls static label local *value value* **remote** *value*

no mpls static label local *value value* **remote** *value*

Syntax Description

local <i>value</i>	Configures the local pseudowire label. Note Use the show mpls label range command to obtain the range for the local labels.
remote <i>value</i>	Configures the remote pseudowire label. Note The range of values for the remote labels depends on the label allocator of the remote router.

Command Default

By default, the router attempts to assign dynamic labels to the pseudowire.

Command Modes

L2VPN bridge group bridge domain Access/VFI pseudowire configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Ensure that both ends of the pseudowire have matching static labels.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to configure the VFI pseudowire 10.1.1.2 with pseudowire ID of 1000 to use MPLS label 800 and remote MPLS label 500:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi model
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)# neighbor 10.1.1.2 pw-id 1000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi-pw)# mpls static label local 800 remote 500
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
neighbor (VPLS), on page 29	Adds an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI).
pw-class (VFI), on page 35	Configures the pseudowire class template name to use for the pseudowire.
vfi (VPLS), on page 81	Configures virtual forwarding interface (VFI) parameters.

mtu (VPLS)

To adjust the maximum packet size or maximum transmission unit (MTU) size for the bridge domain, use the **mtu** command in L2VPN bridge group bridge domain configuration mode. To disable this feature, use the **no** form of this command.

mtu *bytes*

no mtu

Syntax Description

bytes MTU size, in bytes. The range is from 46 to 65535.

Command Default

The default MTU value is 1500.

Command Modes

L2VPN bridge group bridge domain configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Each interface has a default maximum packet size or MTU size. This number generally defaults to the largest size possible for that interface type. On serial interfaces, the MTU size varies, but cannot be set smaller than 64 bytes.

The MTU for the bridge domain includes only the payload of the packet. For example, a configured bridge MTU of 1500 allows tagged packets of 1518 bytes (6 bytes DA, 6 bytes SA, 2 bytes ethertype, or 4 bytes qtag).

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example specifies an MTU of 1000 bytes:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
```

```
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mtu 1000
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
flooding disable, on page 13	Configures flooding for traffic at the bridge domain level or at the bridge port level.
l2vpn	Enters L2VPN configuration mode.

neighbor (VPLS)

To add an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI), use the **neighbor** command in the appropriate L2VPN bridge group bridge domain configuration submode. To remove the pseudowire either from the bridge or from the VFI, use the **no** form of this command.

neighbor *A.B.C.D* **pw-id** *value*

no neighbor *A.B.C.D* **pw-id** *value*

Syntax Description

<i>A.B.C.D</i>	IP address of the cross-connect peer.
pw-id <i>value</i>	Configures the pseudowire ID and ID value. Range is 1 to 4294967295.

Command Default

None

Command Modes

L2VPN bridge group bridge domain configuration
L2VPN bridge group bridge domain VFI configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **neighbor** command to enter L2VPN bridge group bridge domain VFI pseudowire configuration mode. Alternatively, use the **neighbor** command to enter L2VPN bridge group bridge domain access pseudowire configuration mode.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to configure an access pseudowire directly under a bridge domain in L2VPN bridge group bridge domain configuration mode:

```
RP/0/RP0/CPU0:router# configure
```

```
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# neighbor 10.1.1.2 pw-id 1000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-pw)#
```

The following example shows how to configure the parameters for any pseudowire in L2VPN bridge group bridge domain VFI configuration mode:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi v1
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)# neighbor 10.1.1.2 pw-id 1000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi-pw)#
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mpls static label (VPLS), on page 25	Configures the MPLS static labels and the static labels for the access pseudowire configuration.
pw-class (VFI), on page 35	Configures the pseudowire class template name to use for the pseudowire.
static-mac-address (VPLS), on page 75	Configures the static MAC address to associate a remote MAC address with a pseudowire or any other bridge interface.
vfi (VPLS), on page 81	Configures virtual forwarding interface (VFI) parameters.

notification (VPLS)

To specify the type of notification that is sent when the number of learned MAC addresses exceeds the configured limit, use the **notification** command in L2VPN bridge group bridge domain MAC limit configuration mode. To use the notification as only a syslog entry, use the **no** form of this command.

notification {both| none| trap}

no notification {both| none| trap}

Syntax Description

both	Sends syslog and trap notifications when the action is violated.
none	Specifies no notification.
trap	Sends trap notifications when the action is violated.

Command Default

By default, only a syslog message is sent when the number of learned MAC addresses reaches the maximum configured.

Command Modes

L2VPN bridge group bridge domain MAC limit configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

A syslog message and an SNMP trap is generated. Alternatively, an SNMP trap is generated. Finally, no notification is generated.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how both a syslog message and an SNMP trap are generated with the bridge bar and learns more MAC addresses than the configured limit:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router (config)# l2vpn
RP/0/RP0/CPU0:router (config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router (config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-mac)# limit
RP/0/RP0/CPU0:router (config-l2vpn-bg-bd-mac-limit)# notification both
```

Related Commands

Command	Description
action (VPLS), on page 3	Configures bridge behavior when the number of learned MAC addresses reaches the MAC limit configured.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
maximum (VPLS), on page 23	Configures the specified action when the number of MAC addresses learned on a bridge is reached.

port-down flush disable (VPLS)

To disable MAC flush when the bridge port is nonfunctional, use the **port-down flush disable** command in the L2VPN bridge group bridge domain MAC configuration mode. Use the **no** form of this command to enable the MAC flush when the bridge port is nonfunctional.

port-down flush disable

no port-down flush disable

Syntax Description This command has no keywords or arguments.

Command Default None

Command Modes L2VPN bridge group bridge domain MAC configuration

Command History	Release	Modification
	Release 3.9.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **port-down flush disable** command disables the MAC flush when the bridge port is nonfunctional.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to disable MAC flush when the bridge port is nonfunctional:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# port-down flush disable
```

Related Commands

Command	Description
action (VPLS), on page 3	Configures bridge behavior when the number of learned MAC addresses reaches the MAC limit configured.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
maximum (VPLS), on page 23	Configures the specified action when the number of MAC addresses learned on a bridge is reached.
notification (VPLS), on page 31	Specifies the type of notification that is sent when the number of learned MAC addresses exceeds the configured limit.

pw-class (VFI)

To configure the pseudowire class template name to use for the pseudowire, use the **pw-class** command in L2VPN bridge group bridge domain VFI pseudowire configuration mode. To delete the pseudowire class, use the **no** form of this command.

pw-class *class-name*
no pw-class *class-name*

Syntax Description	<i>class-name</i>	Pseudowire class name.
---------------------------	-------------------	------------------------

Command Default	None
------------------------	------

Command Modes	L2VPN bridge group bridge domain VFI pseudowire configuration
----------------------	---

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines	To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.
-------------------------	---

Task ID	Task ID	Operations
	l2vpn	read, write

Examples	The following example shows how to attach the pseudowire class to the pseudowire:
-----------------	---

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi v1
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)# neighbor 10.1.1.2 pw-id 1000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi-pw)# pw-class canada
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mpls static label (VPLS), on page 25	Configures the MPLS static labels and the static labels for the access pseudowire configuration.
neighbor (VPLS), on page 29	Adds an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI).
vfi (VPLS), on page 81	Configures virtual forwarding interface (VFI) parameters.

show l2vpn bridge-domain (VPLS)

To display information for the bridge ports such as attachment circuits and pseudowires for the specific bridge domains, use the **show l2vpn bridge-domain** command in EXEC mode.

```
show l2vpn bridge-domain [bd-name bridge-domain-name | brief | detail | group bridge-domain-group-name
| interface type interface-path-id | pw-id value ] neighbor IP-address [pw-id value | summary]
```

Syntax Description

bd-name <i>bridge-domain-name</i>	(Optional) Displays the bridges by the bridge ID. The <i>bridge-domain-name</i> argument is used to name a bridge domain.
brief	(Optional) Displays brief information about the bridges.
detail	(Optional) Displays the output for the Layer 2 VPN (L2VPN) to indicate whether or not the MAC withdrawal feature is enabled and the number of MAC withdrawal messages that are sent or received from the pseudowire.
group <i>bridge-domain-group-name</i>	(Optional) Displays filter information on the bridge-domain group name. The <i>bridge-domain-group-name</i> argument is used to name the bridge domain group.
interface	(Optional) Displays the filter information for the interface on the bridge domain.
<i>type</i>	Interface type. For more information, use the question mark (?) online help function.
<i>interface-path-id</i>	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
neighbor <i>IP-address</i>	(Optional) Displays only the bridge domain that contains the pseudowires to match the filter for the neighbor. The <i>IP-address</i> argument is used to configure IP address of the neighbor.
pw-id <i>value</i>	(Optional) Displays the filter for the pseudowire ID. The range is from 1 to 4294967295.
summary	(Optional) Displays the summary information for the bridge domain.

Command Default None

Command Modes EXEC mode

Command History

Release	Modification
Release 3.8.0	This command was introduced.
Release 5.1.2	This command was modified to enable filtering the command output for specific pseudowire with just the pseudowire ID.

Usage Guidelines

To use commands of this module, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using any command, contact your AAA administrator for assistance.

Use the **interface** keyword to display only the bridge domain that contains the specified interface as an attachment circuit. In the sample output, only the attachment circuit matches the filter that is displayed. No pseudowires are displayed.

**Note**

For Cisco IOS XR software Release 5.1.2 and above, you can filter the command output for a specific pseudowire with just the pseudowire ID. However, in case of configurations with BGP Auto-discovery with BGP or LDP signaling (in VPLS), you can specify the pseudowire only with the combination of the neighbor filter and the pseudowire ID.

Task ID

Task ID	Operations
l2vpn	read

Examples

This is the sample output for **show l2vpn bridge-domain** command with VxLAN parameters configured:

```
RP/0/RP0/CPU0:router# show l2vpn bridge-domain bd-name bg1_bd1 detail
Legend: pp = Partially Programmed.
Bridge group: bg1, bridge-domain: bg1_bd1, id: 0, state: up, ShgId: 0, MSTi: 0
  Coupled state: disabled
  MAC learning: enabled
  MAC withdraw: enabled
    MAC withdraw for Access PW: enabled
    MAC withdraw sent on: bridge port up
    MAC withdraw relaying (access to access): disabled
  Flooding:
    Broadcast & Multicast: enabled
    Unknown unicast: enabled
  MAC aging time: 300 s, Type: inactivity
  MAC limit: 4000, Action: none, Notification: syslog
  MAC limit reached: no
  MAC port down flush: enabled
  MAC Secure: disabled, Logging: disabled
  Split Horizon Group: none
  Dynamic ARP Inspection: disabled, Logging: disabled
  IP Source Guard: disabled, Logging: disabled
  DHCPv4 snooping: disabled
```

```

IGMP Snooping: enabled
IGMP Snooping profile: none
MLD Snooping profile: none
Storm Control: disabled
Bridge MTU: 1500
MIB cvplsConfigIndex: 1
Filter MAC addresses:
P2MP PW: disabled
Create time: 30/03/2015 22:25:38 (00:26:08 ago)
No status change since creation
ACs: 2 (2 up), VFIs: 1, PWs: 0 (0 up), PBBs: 0 (0 up)
List of ACs:
  AC: BV11, state is up
    Type Routed-Interface
    MTU 1514; XC ID 0x80000001; interworking none
    BVI MAC address:
      1000.4444.0001
  AC: GigabitEthernet0/8/0/0.1, state is up
    Type VLAN; Num Ranges: 1
    Outer Tag: 1
    VLAN ranges: [1001, 1001]
    MTU 1508; XC ID 0x508000a; interworking none
    MAC learning: enabled
    Flooding:
      Broadcast & Multicast: enabled
      Unknown unicast: enabled
    MAC aging time: 300 s, Type: inactivity
    MAC limit: 4000, Action: none, Notification: syslog
    MAC limit reached: no
    MAC port down flush: enabled
    MAC Secure: disabled, Logging: disabled
    Split Horizon Group: none
    Dynamic ARP Inspection: disabled, Logging: disabled
    IP Source Guard: disabled, Logging: disabled
    DHCPv4 snooping: disabled
    IGMP Snooping: enabled
    IGMP Snooping profile: none
    MLD Snooping profile: none
    Storm Control: bridge-domain policer
    Static MAC addresses:

    Storm control drop counters:
      packets: broadcast 0, multicast 0, unknown unicast 0
      bytes: broadcast 0, multicast 0, unknown unicast 0
    Dynamic ARP inspection drop counters:
      packets: 0, bytes: 0
    IP source guard drop counters:
      packets: 0, bytes: 0
List of VNIs:
  VNI 1, state is up
    XC ID 0x80000014
    Encap type VXLAN
    Overlay nve100, Source 1.1.1.1, Multicast Group 225.1.1.1, UDP Port 4789
    Anycast VTEP 100.1.1.1, Anycast Multicast Group 224.10.10.1
    MAC learning: enabled
    Flooding:
      Broadcast & Multicast: enabled
      Unknown unicast: enabled
    MAC aging time: 300 s, Type: inactivity
    MAC limit: 4000, Action: none, Notification: syslog
    MAC limit reached: no
    MAC port down flush: enabled
    MAC Secure: disabled, Logging: disabled
    Split Horizon Group: none
    Dynamic ARP Inspection: disabled, Logging: disabled
    IP Source Guard: disabled, Logging: disabled
    DHCPv4 snooping: disabled
    IGMP Snooping: enabled
    IGMP Snooping profile: none
    MLD Snooping profile: none
    Storm Control: bridge-domain policer

List of Access PWs:

```

```
List of VFIs:
VFI bgl_bdl_vfi (up)
VFI Statistics:
drops: illegal VLAN 0, illegal length 0
```

This table describes the significant fields shown in the display.

The following sample output shows information for the bridge ports such as attachment circuits and pseudowires for the specific bridge domains:

```
RP/0/RP0/CPU0:router# show l2vpn bridge-domain

Bridge group: g1, bridge-domain: bdl, id: 0, state: up, ShgId: 0, MSTi: 0
Aging: 300 s, MAC limit: 4000, Action: none, Notification: syslog
Filter MAC addresses: 0
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of ACs:
  Gi0/1/0/0, state: up, Static MAC addresses: 2, MSTi: 0 (unprotected)
List of Access PWs:
List of VFIs:
  VFI 1
    Neighbor 10.1.1.1 pw-id 1, state: up, Static MAC addresses: 0
```

This table describes the significant fields shown in the display.

Table 1: show l2vpn bridge-domain Command Field Descriptions

Field	Description
Bridge group	Name of bridge domain group is displayed.
bridge-domain	Name of bridge domain is displayed.
id	ID assigned to this bridge domain is displayed.
state	Current state of the bridge domain is displayed.

The following example shows sample output for a bridge named bdl:

```
RP/0/RP0/CPU0:router# show l2vpn bridge-domain bd-name bdl

Bridge group: g1, bridge-domain: bdl, id: 0, state: up, ShgId: 0, MSTi: 0
Aging: 300 s, MAC limit: 4000, Action: none, Notification: syslog
Filter MAC addresses: 0
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of ACs:
  Gi0/1/0/0, state: up, Static MAC addresses: 2, MSTi: 0 (unprotected)
List of Access PWs:
List of VFIs:
  VFI 1
    Neighbor 10.1.1.1 pw-id 1, state: up, Static MAC addresses: 0
```

The following sample output shows brief information about the bridges:

```
RP/0/RP0/CPU0:router# show l2vpn bridge-domain brief

Bridge Group/Bridge-Domain Name  ID      State      Num ACs/up      Num PWs/up
-----
g1/bdl                            0       up          1/1              1/1
```

This table describes the significant fields shown in the display.

Table 2: show l2vpn bridge-domain brief Command Field Descriptions

Field	Description
Bridge Group/Bridge-Domain Name	Bridge domain group name followed by the bridge domain name are displayed.
ID	ID assigned to this bridge domain is displayed.
State	Current state of the bridge domain is displayed.
Num ACs/up	Total number of attachment circuits that are up in this bridge domain is displayed.
Num PWs/up	Total number of pseudowires that are up in this bridge domain is displayed. The count includes both VFI pseudowires and access pseudowires.

The following sample output shows detailed information:

```
RP/0/RP0/CPU0:router# show l2vpn bridge-domain detail

Bridge group: g1, bridge-domain: bd1, id: 0, state: up, ShgId: 0, MSTi: 0
MAC learning: enabled
MAC withdraw: disabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: yes
Security: disabled
DHCPv4 snooping: disabled
MTU: 1500
Filter MAC addresses:
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of ACs:
  AC: GigabitEthernet0/1/0/0, state is up
    Type Ethernet
    MTU 1500; XC ID 0x2000001; interworking none; MSTi 0 (unprotected)
    MAC learning: enabled
    Flooding:
      Broadcast & Multicast: enabled
      Unknown unicast: enabled
    MAC aging time: 300 s, Type: inactivity
    MAC limit: 4000, Action: none, Notification: syslog
    MAC limit reached: yes
    Security: disabled
    DHCPv4 snooping: disabled
    Static MAC addresses:
      0000.0000.0000
      0001.0002.0003
    Statistics:
      packet totals: receive 3919680,send 9328
      byte totals: receive 305735040,send 15022146
List of Access PWs:
List of VFIs:
  VFI 1
    PW: neighbor 1.1.1.1, PW ID 1, state is up ( established )
    PW class mpls, XC ID 0xff000001
    Encapsulation MPLS, protocol LDP
    PW type Ethernet, control word disabled, interworking none
    PW backup disable delay 0 sec
```

show l2vpn bridge-domain (VPLS)

```

Sequencing not set
MPLS              Local              Remote
-----
Label             16003              16003
Group ID          0x0                0x0
Interface         1                  1
MTU               1500              1500
Control word     disabled           disabled
PW type          Ethernet           Ethernet
VCCV CV type     0x2                0x2
                  (LSP ping verification)  (LSP ping verification)
VCCV CC type     0x2                0x2
                  (router alert label)    (router alert label)
-----
Create time: 12/03/2008 14:03:00 (17:17:30 ago)
Last time status changed: 13/03/2008 05:57:58 (01:22:31 ago)
MAC withdraw message: send 0 receive 0
Static MAC addresses:
Statistics:
  packet totals: receive 3918814, send 3918024
  byte totals: receive 305667492, send 321277968
VFI Statistics:
  drops: illegal VLAN 0, illegal length 0

```

The following sample output shows that when a bridge operates in VPWS mode, the irrelevant information for MAC learning is suppressed:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain detail

Bridge group: foo_group, bridge-domain: foo_bd, id: 0, state: up, ShgId: 0
  VPWS Mode
  MTU: 1500
  ACs: 1 (0 up), VFIs: 1, PWs: 2 (2 up)
  List of ACs:
    AC: GigabitEthernet0/5/1/4, state is admin down
      Type Ethernet      MTU 1500; XC ID 1; interworking none
      Static MAC addresses:
      Statistics:
        packet totals: receive 0, send 0
        byte totals: receive 0, send 0
  List of VFIs:
    VFI foo vfi
      PW: neighbor 1.1.1.1, PW ID 1, state is up ( established )
      PW class not set
      Encapsulation MPLS, protocol LDP
      PW type Ethernet, control word enabled, interworking none
      Sequencing not set
      MPLS              Local              Remote
      -----
      Label             16001              16001
      Group ID          unassigned         unknown
      Interface         siva/vfi           siva/vfi
      MTU               1500              1500
      Control word     enabled            enabled
      PW type          Ethernet           Ethernet
      VCCV CV type     0x2                0x2
                        (LSP ping verification)  (LSP ping verification)
      VCCV CC type     0x3                0x3
                        (control word)          (control word)
                        (router alert label)    (router alert label)
      -----
      Create time: 25/06/2007 05:29:42 (2w0d ago)
      Last time status changed: 27/06/2007 06:50:35 (1w5d ago)
      Static MAC addresses:
      PW: neighbor 1.1.1.1, PW ID 2, state is up ( established )
      PW class not set
      Encapsulation MPLS, protocol LDP
      PW type Ethernet, control word enabled, interworking none
      Sequencing not set
      MPLS              Local              Remote
      -----
      Label             16002              16002

```

```

Group ID      unassigned          unknown
Interface     siva/vfi            siva/vfi
MTU           1500                1500
Control word  enabled             enabled
PW type       Ethernet            Ethernet
VCCV CV type  0x2                 0x2
               (LSP ping verification)   (LSP ping verification)
VCCV CC type  0x3                 0x3
               (control word)           (control word)
               (router alert label)     (router alert label)
-----
Create time: 25/06/2007 05:29:42 (2w0d ago)
Last time status changed: 27/06/2007 06:50:35 (1w5d ago)
Static MAC addresses:
Statistics:
drops: illegal VLAN 0, illegal length 0

```

This table describes the significant fields shown in the display.

Table 3: show l2vpn bridge-domain detail Command Field Descriptions

Field	Description
Bridge group	Name of bridge domain group is displayed.
bridge-domain	Name of bridge domain is displayed.
ID	ID assigned to this bridge domain is displayed.
state	Current state of the bridge domain is displayed.
MSTi	ID for the Multiple Spanning Tree.

The following sample output shows filter information about the bridge-domain group named g1:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain group g1

Bridge group: g1, bridge-domain: bd1, id: 0, state: up, ShgId: 0, MSTi: 0
Aging: 300 s, MAC limit: 4000, Action: none, Notification: syslog
Filter MAC addresses: 0
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of ACs:
  Gi0/1/0/0, state: up, Static MAC addresses: 2, MSTi: 0 (unprotected)
List of Access PWs:
List of VFIs:
  VFI 1
    Neighbor 1.1.1.1 pw-id 1, state: up, Static MAC addresses: 0

```

The following sample output shows display the filter information for the interface on the bridge domain:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain interface gigabitEthernet 0/1/0/0

Bridge group: g1, bridge-domain: bd1, id: 0, state: up, ShgId: 0, MSTi: 0
Aging: 300 s, MAC limit: 4000, Action: none, Notification: syslog
Filter MAC addresses: 0
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of ACs:
  Gi0/1/0/0, state: up, Static MAC addresses: 2, MSTi: 0 (unprotected)

```

The following sample output shows that the bridge domain contains the pseudowires to match the filter for the neighbor:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain neighbor 1.1.1.1

```

show l2vpn bridge-domain (VPLS)

```

Bridge group: gl, bridge-domain: bdl, id: 0, state: up, ShgId: 0, MSTi: 0
Aging: 300 s, MAC limit: 4000, Action: none, Notification: syslog
Filter MAC addresses: 0
ACs: 1 (1 up), VFIs: 1, PWs: 1 (1 up)
List of Access PWs:
List of VFIs:
  VFI 1
    Neighbor 1.1.1.1 pw-id 1, state: up, Static MAC addresses: 0

```

The following sample output shows the summary information for the bridge domain:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain summary

Number of groups: 1, bridge-domains: 1, Up: 1, Shutdown: 0
Number of ACs: 1 Up: 1, Down: 0
Number of PWs: 1 Up: 1, Down: 0

```

This example shows the sample output of a configured flow label:

```

RP/0/RP0/CPU0:router# show l2vpn bridge-domain detail
Bridge group: gl, bridge-domain: dl, id: 0, state: up, ShgId: 0, MSTi: 0
.....
PW: neighbor 3.3.3.3, PW ID 2, state is up ( established )
  PW class class1, XC ID 0x1000002
  Encapsulation MPLS, protocol LDP
  PW type Ethernet, control word disabled, interworking none
  PW backup disable delay 0 sec
  Sequencing not set
  Flow label flags configured (Rx=1,Tx=1), negotiated (Rx=0,Tx=1)

```

This table describes the significant fields shown in the display.

Table 4: show l2vpn bridge-domain summary Command Field Descriptions

Field	Description
Number of groups	Number of configured bridge domain groups is displayed.
bridge-domains	Number of configured bridge domains is displayed.
Shutdown	Number of bridge domains that are in Shutdown state is displayed.
Number of ACs	Number of attachment circuits that are in Up state and Down state are displayed.
Number of PWs	Number of pseudowires that are in Up state and Down state are displayed. This includes the VFI pseudowire and the access pseudowire.

Related Commands

Command	Description
clear l2vpn bridge-domain (VPLS) , on page 11	Clears the MAC addresses and restarts the bridge domains on the router.

show l2vpn forwarding bridge-domain (VPLS)

To display information on the bridge that is used by the forwarding layer, use the **show l2vpn forwarding bridge-domain** command in EXEC mode.

```
show l2vpn forwarding bridge-domain [ bridge-domain-name ] {detail| hardware {egress| ingress}}
location node-id
```

Syntax Description

<i>bridge-domain-name</i>	(Optional) Name of a bridge domain.
detail	Displays all the detailed information on the attachment circuits and pseudowires.
hardware	Displays the hardware location entry.
egress	Reads information from the egress PSE.
ingress	Reads information from the ingress PSE.
location <i>node-id</i>	Displays the bridge-domain information for the specified location. The <i>node-id</i> argument is entered in the <i>rack/slot/module</i> notation.

Command Default

None

Command Modes

EXEC

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

For each bridge, you can display summary information about the number of bridge ports, number of MAC addresses, configured VXLANs and so forth.

The **detail** keyword displays detailed information on the attachment circuits and pseudowires, and is meant for field investigation by a specialized Cisco engineer.

**Note**

All bridge ports in the bridge domain on that line card are displayed. Therefore, if the bridge domain contains non-local bridge ports, those are displayed as well.

Task ID

Task ID	Operations
l2vpn	read

Examples

The following sample output shows bridge-domain information for location 0/1/CPU0:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain location 0/1/CPU0
Bridge-Domain Name          ID      Ports addr  Flooding Learning State
-----
g1:bd1

Bridge-domain name: g1:bd1, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: yes
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 2
Number of MAC addresses: 65536
Multi-spanning tree instance: 0

GigabitEthernet0/1/0/0, state: oper up
Number of MAC: 32770
Sent(Packets/Bytes): 0/21838568
Received(Packets/Bytes): 5704781/444972918

Nbor 1.1.1.1 pw-id 1
Number of MAC: 32766
Sent(Packets/Bytes): 0/0
Received(Packets/Bytes): 5703987/444910986
0          2          65536 Enabled Enabled UP
```

The following sample output shows detailed information for hardware location 0/1/CPU0 from the egress pse:

```
RP/0/RP0/CPU0:router

Bridge-domain name: g1:bd1, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: yes
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 2
Number of MAC addresses: 65536
Multi-spanning tree instance: 0
```

```

===== GSR HW Information =====
-----
SHG-TX rewrite details
-----
HW Rewrite 0 Detail :
-----
Rewrite HW Address : 0x00060000
packets 0 bytes 0
Raw data:
[ 0x04018180 04018190 040181a0 040181b0 ]
[ 0x04018170 00000000 80360000 000bfff4 ]
[ 0x00000000 00000000 00000000 00000000 ]
-----
SHG-TX encap details
-----
outer_etype:          0
outer_vlan_id:        0
gather_profile:       0
inner_vlan_id:        0
so_l2_len_adjust:    0
-----
SHG-TX mgid details
-----
Base MGIDs for default mgid
base_mgid[0]:         0x0003ffff
base_mgid[1]:         0x0003ffff
base_mgid[2]:         0x0003ffff
base_mgid[3]:         0x0003ffff
base_mgid[4]:         0x0003ffff
base_mgid[5]:         0x0003ffff
base_mgid[6]:         0x0003ffff
base_mgid[7]:         0x0003ffff
MGID Entries for default mgid
oi[0]:                0
oq[0]:                16384
xc_id[0]:              1
mgid_idx[0]:           0x00000000
next_mgid[0]:          0x00000000
-----
VMR 0 Details
-----
vmrid: 0x5f002010
Value: 0xc0 0x00 0x1f 0xff 0xff 0xff 0xff 0xff 0xff
Mask : 0x00 0x00 0x1f 0xff 0xff 0xff 0xff 0xff 0xe0
Result 0x32003000
=====

GigabitEthernet0/1/0/0, state: oper up
Number of MAC: 32770
Sent (Packets/Bytes): 749/22989834
Received (Packets/Bytes): 5732104/447104112

===== GSR HW Information =====
-----
BP-TX-AC rewrite details
-----
BP is local

-----
BP L2 Uidb Details
-----
l2fwd_enabled:        true
plim_enabled:         true
l2fwd_type:           4
l2_ac_type:           0
xconn_id:             0

```

show l2vpn forwarding bridge-domain (VPLS)

```

bridge_id:                0
shg_id:                   0
unicast flooding enabled:  0
multicast flooding enabled: 0
broadcast flooding enabled: 0
mac learning enabled:     0
Is AC Port mode?:        0
-----
HW Rewrite 0 Detail :
-----
Rewrite HW Address : 0x59eff314
packets 0 bytes 0
HFA Bits 0x0 gp 0 mtu 1580 (REW)
OI 0x3fffc OutputQ 0 Output-port 0x36 local_outputq 0x0
Raw data:
[ 0x00000000 0036062c 0003fffc 00000000 ]
[ 0x00000000 00000000 0d103600 00000010 ]
[ 0x00000000 00000000 00000000 00000000 ]
-----
BP OI/OQ Details
-----
oi[0]:          0x00000000      oq[0]          16384
oi[1]:          0x00000000      oq[1]          65535
oi[2]:          0x00000000      oq[2]          65535
oi[3]:          0x00000000      oq[3]          65535
oi[4]:          0x00000000      oq[4]          65535
oi[5]:          0x00000000      oq[5]          65535
oi[6]:          0x00000000      oq[6]          65535
oi[7]:          0x00000000      oq[7]          65535
-----
Sram table entry details
-----
sram_data: 0xa000400c
=====

Nbor 1.1.1.1 pw-id 1
Number of MAC: 32766
Sent(Packets/Bytes): 0/0
Received(Packets/Bytes): 5731250/447037500
===== GSR HW Information =====

-----
BP-TX-AC rewrite details
-----
BP OI/OQ Details
-----
oi[0]:          0x00000000      oq[0]          65535
oi[1]:          0x00000000      oq[1]          65535
oi[2]:          0x00000000      oq[2]          65535
oi[3]:          0x00000000      oq[3]          65535
oi[4]:          0x00000000      oq[4]          65535
oi[5]:          0x00000000      oq[5]          65535
oi[6]:          0x00000000      oq[6]          65535
oi[7]:          0x00000000      oq[7]          65535
-----
BP Encap Info
-----
mac_length:      0
mac_string:
egress_slot:    2
num_tags:        1
tags:           {16001, }
if_handle:       0x03000500
=====

```

The following sample output shows the bridge-domain information for the specified location:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain g1:bd1 location 0/1/CPU0
```

```
Bridge-Domain Name          ID      Ports addr   Flooding Learning State
```



```
-----
g1:bd1                                0      2      65536  Enabled  Enabled  UP
```

The following sample output shows the hardware information for a specific bridge-domain:

```
RP/0/RP0/CPU0:router#show l2vpn bridge-domain hardware

Bridge group: aa, bridge-domain name: g1, id:0
  FGID Boardcast [version 1]:
    Allocate_count: 2048, Retry_count: 0, Realloc_on: Off
    Status_flag: (0x4) Replay-end
    ALL 44032, VFI 44033

Bridge group: aa, bridge-domain name: g2, id:1
  FGID Boardcast [version 1]:
    Allocate_count: 2048, Retry_count: 0, Realloc_on: Off
    Status_flag: (0x4) Replay-end
    ALL 44034, VFI 44035
```

The following sample output shows the hardware information for the line card, for a specific bridge-domain on the ingress detail location:

```
RP/0/RP0/CPU0:router#
show l2vpn forwarding bridge-domain hardware ingress detail location 0/2/CPU0

Bridge-domain name: aa:g1, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 4
Number of MAC addresses: 0
Multi-spanning tree instance: 0

  INGRESS BRIDGE [version, state]: [1, CREATED]

    TCAM entry seq#: 1024 Key: [BID: 0 MAC: default]
    HW: 0x4c000000 0x000080ac 0x00010000 0x80ac0100
    SW: 0x4c000000 0x000080ac 0x00010000 0x80ac0100

    SMAC: action: PUNT state: NO REFRESH
    DMAC: action: FLOOD, flood_enable: enable
    FGID: All: 44032, VFI: 44033, MCAST_Sponge_q: 16
    Fabric_multicast1: 1 Fabric_multicast2: 1

    Admin State: UP
    MTU: 1500
    Number of MAC addresses: 1 (0 MAC + 1 default)
    ACL NAME (ACL-ID): VPLS Special (4096)
    TCAM region handle : 5

GigabitEthernet0/2/0/1.1, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

  INGRESS BRIDGE PORT [version, state]: [1, BOUND]
    Bridge Port Type: AC
    XID: 0/2/CPU0 : 1 (0x1280001)
    Bridge ID: 0, Split Horizon ID: 0
    RX TLU1 : 0x4c00
    RX TLU2 : 0x1013c00
    RX TLU3 : 0x200ba00
    RX TLU4 : 0x3000c00
```

show l2vpn forwarding bridge-domain (VPLS)

```

INGRESS AC [version, state]: [1, BOUND]

Xconnect-ID: [1] TCAM-Key: (UIDB:0x2 O-vlan:1 I-vlan:0 Ether-Type:0x8100)
HW: 0x24001000 0x01280001 0x10128000 0xc7ff7d00
SW: 0x24001000 0x01280001 0x10128000 0xc7ff7d00

Service type: 4 (bridging pmp)
Entry type: 1 (fwd)
Bridge_ID : 0
ACL_ID : 4096
Xconnect_ID : 0x1280001
SplitHorizonGroup_ID : 0
Rewrite supported: 0 (No)
PW mode: 0 (vc-type 5)
AC-type: 1 (vlan-mode)
Interface handle: 0x128000
Ingress AC stats: 0x7ff7d

SMAC Learning: enable
DMAC Flooding: enable

GigabitEthernet0/2/0/1.2, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
Bridge Port Type: AC
XID: 0/2/CPU0 : 2 (0x1280002)
Bridge ID: 0, Split Horizon ID: 0
RX TLU1 : 0x4c01
RX TLU2 : 0x1013c01
RX TLU3 : 0x200ba01
RX TLU4 : 0x3000c01

INGRESS AC [version, state]: [1, BOUND]

Xconnect-ID: [2] TCAM-Key: (UIDB:0x2 O-vlan:2 I-vlan:0 Ether-Type:0x8100)
HW: 0x24001000 0x01280002 0x10128002 0xc7ff7a00
SW: 0x24001000 0x01280002 0x10128002 0xc7ff7a00

Service type: 4 (bridging pmp)
Entry type: 1 (fwd)
Bridge_ID : 0
ACL_ID : 4096
Xconnect_ID : 0x1280002
SplitHorizonGroup_ID : 0
Rewrite supported: 0 (No)
PW mode: 0 (vc-type 5)
AC-type: 1 (vlan-mode)
Interface handle: 0x128002
Ingress AC stats: 0x7ff7a

SMAC Learning: enable
DMAC Flooding: enable

GigabitEthernet0/2/0/1.3, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
Bridge Port Type: AC
XID: 0/2/CPU0 : 3 (0x1280003)
Bridge ID: 0, Split Horizon ID: 0
RX TLU1 : 0x4c02
RX TLU2 : 0x1013c02
RX TLU3 : 0x200ba02
RX TLU4 : 0x3000c02

```

```

INGRESS AC [version, state]: [1, BOUND]

    Xconnect-ID: [3] TCAM-Key: (UIDB:0x2 O-vlan:3 I-vlan:0 Ether-Type:0x8100)
    HW: 0x24001000 0x01280003 0x10128004 0xc7ff7700
    SW: 0x24001000 0x01280003 0x10128004 0xc7ff7700

    Service type: 4 (bridging pmp)
    Entry type: 1 (fwd)
    Bridge_ID : 0
    ACL_ID : 4096
    Xconnect_ID : 0x1280003
    SplitHorizonGroup_ID : 0
    Rewrite supported: 0 (No)
    PW_mode: 0 (vc-type 5)
    AC-type: 1 (vlan-mode)
    Interface handle: 0x128004
    Ingress AC stats: 0x7ff77

    SMAC Learning: enable
    DMAC Flooding: enable

Nbor 5.0.0.5 pw-id 1
  Number of MAC: 0
  Statistics:
    packets: received 0, sent 0
    bytes: received 0, sent 0

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: ATOM
  XID: 127/15/CPU0 : 1 (0xffff80001)
  Bridge ID: 0, Split Horizon ID: 1
  VC label: 16006
  Control-word supported: No

Bridge-domain name: aa:g2, id: 1, state: up
  MAC learning: enabled
  Flooding:
    Broadcast & Multicast: enabled
    Unknown unicast: enabled
  MAC aging time: 300 s, Type: inactivity
  MAC limit: 4000, Action: none, Notification: syslog
  MAC limit reached: no
  Security: disabled
  DHCPv4 snooping: profile not known on this node
  Bridge MTU: 1500 bytes
  Number of bridge ports: 2
  Number of MAC addresses: 0
  Multi-spanning tree instance: 0

INGRESS BRIDGE [version, state]: [1, CREATED]

  TCAM entry seq#: 1025 Key: [BID: 1 MAC: default]
  HW: 0x4c000000 0x000080ac 0x02010000 0x80ac0300
  SW: 0x4c000000 0x000080ac 0x02010000 0x80ac0300

  SMAC: action: PUNT state: NO REFRESH
  DMAC: action: FLOOD, flood_enable: enable
  FGID: All: 44034, VFI: 44035, MCAST_Sponge_q: 16
  Fabric_multicast1: 1 Fabric_multicast2: 1

  Admin State: UP
  MTU: 1500
  Number of MAC addresses: 1 (0 MAC + 1 default)
  ACL NAME (ACL-ID): VPLS Special (4097)
  TCAM region handle : 5

GigabitEthernet0/2/0/1.4, state: oper up
  Number of MAC: 0
  Statistics:
    packets: received 0, sent 0
    bytes: received 0, sent 0

```

show l2vpn forwarding bridge-domain (VPLS)

```

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: AC
  XID: 0/2/CPU0 : 4 (0x1280004)
  Bridge ID: 1, Split Horizon ID: 0
  RX TLU1   : 0x4c03
  RX TLU2   : 0x1013c03
  RX TLU3   : 0x200ba03
  RX TLU4   : 0x3000c03

INGRESS AC [version, state]: [1, BOUND]

  Xconnect-ID: [4] TCAM-Key: (UIDB:0x2 O-vlan:4 I-vlan:0 Ether-Type:0x8100)
  HW: 0x24003001 0x01280004 0x10128006 0xc7ff7400
  SW: 0x24003001 0x01280004 0x10128006 0xc7ff7400

  Service type: 4 (bridging pmp)
  Entry type: 1 (fwd)
  Bridge_ID : 1
  ACL_ID : 4097
  Xconnect_ID : 0x1280004
  SplitHorizonGroup_ID : 0
  Rewrite supported: 0 (No)
  PW_mode: 0 (vc-type 5)
  AC-type: 1 (vlan-mode)
  Interface handle: 0x128006
  Ingress AC stats: 0x7ff74

  SMAC Learning: enable
  DMAC Flooding: enable

Nbor 5.0.0.5 pw-id 2
  Number of MAC: 0
  Statistics:
    packets: received 0, sent 0
    bytes: received 0, sent 0

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: ATOM
  XID: 127/15/CPU0 : 2 (0xffff80002)
  Bridge ID: 1, Split Horizon ID: 1
  VC label: 16008
  Control-word supported: No

```

The following sample output shows the hardware information of the route processor, for a specific bridge-domain on the ingress detail location:

```

RP/0/RP0/CPU0:router#show l2vpn forwarding bridge-domain hardware ingress detail location
0/RP0/CPU0

Bridge-domain name: aa:gl, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 4
Number of MAC addresses: 0
Multi-spanning tree instance: 0

BRIDGE [version, state]: [1, CREATED]
  Bridge ID: 0
  FGID1: 44032   NodeCount: 1   Info_len: 24   XID_count: 4
  FGID2: 44033   NodeCount: 1   Info_len: 20   XID_count: 3

  FGID1 Membership list:
    node-id: 0/2/CPU0 (0x21)   RSI: 0x25   XID_count: 4

```

```

XID: 0x1280001      0x1280002      0x1280003      0xffff80001

FGID2 Membership list:
node-id: 0/2/CPU0 (0x21)  RSI: 0x25  XID_count: 3
XID: 0x1280001      0x1280002      0x1280003

GigabitEthernet0/2/0/1.1, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

AC [version, state]: [1, BOUND]
  XID: 0x1280001  RSI: 0x25  Bridging: TRUE

GigabitEthernet0/2/0/1.2, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

AC [version, state]: [1, BOUND]
  XID: 0x1280002  RSI: 0x25  Bridging: TRUE

GigabitEthernet0/2/0/1.3, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

AC [version, state]: [1, BOUND]
  XID: 0x1280003  RSI: 0x25  Bridging: TRUE

Nbor 5.0.0.5 pw-id 1
Number of MAC: 0

Bridge-domain name: aa:g2, id: 1, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 2
Number of MAC addresses: 0
Multi-spanning tree instance: 0

BRIDGE [version, state]: [1, CREATED]
Bridge ID: 1
FGID1: 44034  NodeCount: 1  Info_len: 16  XID_count: 2
FGID2: 44035  NodeCount: 1  Info_len: 12  XID_count: 1

FGID1 Membership list:
node-id: 0/2/CPU0 (0x21)  RSI: 0x25  XID_count: 2
XID: 0x1280004      0xffff80002

FGID2 Membership list:
node-id: 0/2/CPU0 (0x21)  RSI: 0x25  XID_count: 1
XID: 0x1280004

GigabitEthernet0/2/0/1.4, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

```

show l2vpn forwarding bridge-domain (VPLS)

```
AC [version, state]: [1, BOUND]
  XID: 0x1280004   RSI: 0x25   Bridging: TRUE
```

```
Nbor 5.0.0.5 pw-id 2
  Number of MAC: 0
```

The following sample output shows the hardware information of the line card, for a specific bridge-domain on the egress detail location:

```
RP/0/RP0/CPU0:router#show l2vpn forwarding bridge-domain hardware egress detail location 0/2/CPU0
```

```
Bridge-domain name: aa:gl, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 4
Number of MAC addresses: 0
Multi-spanning tree instance: 0

EGRESS BRIDGE [version, state]: [1, CREATED]

  BID: 0   Total_oif_count: 4
  AC:   oif_count: 3   head_ptr: 0x9ff6e4f8   tail_ptr: 0x9ff6e480
  PW:   oif_count: 1   head_ptr: 0x9ff6e570

  PLU RESULT Key[Bridge-ID: 0]
  HW: 0x04008000 0x000a01c0 0x00000000 0x00000000
  SW: 0x04008000 0x000a01c0 0x00000000 0x00000000
  Entry_type: 1
  OLIST pointer: 0xa01
  OLIST channel: 3
  OLIST count: 4

  OIF[0] seg_type: AC xid: 0x1280003 Gi0/2/0/1.3 (ifh: 0x1280042)
  TLU RESULT tlu_addr: 0x3000a01 ch: 3 seg_type: 1
  HW: 0x80000002 0x00ba0080 0x01280003 0x00000000
  SW: 0x80000002 0x00ba0080 0x01280003 0x00000000
  SHG: 0
  UIDB: 2
  XID: 0x1280003
  OLIST pointer: 0xba00
  OLIST channel: 2

  OIF[1] seg_type: AC xid: 0x1280002 Gi0/2/0/1.2 (ifh: 0x1280022)
  TLU RESULT tlu_addr: 0x200ba00 ch: 2 seg_type: 1
  HW: 0x80000002 0x000a00c0 0x01280002 0x00000000
  SW: 0x80000002 0x000a00c0 0x01280002 0x00000000
  SHG: 0
  UIDB: 2
  XID: 0x1280002
  OLIST pointer: 0xa00
  OLIST channel: 3

  OIF[2] seg_type: AC xid: 0x1280001 Gi0/2/0/1.1 (ifh: 0x1280002)
  TLU RESULT tlu_addr: 0x3000a00 ch: 3 seg_type: 1
  HW: 0x80000002 0x00ba0180 0x01280001 0x00000000
  SW: 0x80000002 0x00ba0180 0x01280001 0x00000000
  SHG: 0
  UIDB: 2
  XID: 0x1280001
  OLIST pointer: 0xba01
  OLIST channel: 2
```

```

OIF[3] seg_type: PW xid: 0xffff80001 ecd_ptr: 0x5206
TLU RESULT tlu addr: 0x200ba01 ch: 2 seg_type: 0
HW: 0x01005206 0x00000000 0xffff80001 0x03e86000
SW: 0x01005206 0x00000000 0xffff80001 0x03e86000
SHG: 1
XID: 0xffff80001
OLIST pointer: 0x0
OLIST channel: 0
Control Word: Disabled
VC label: 16006
ECD/TLU1 pointer: 0x5206

GigabitEthernet0/2/0/1.1, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: AC
  XID: 0/2/CPU0 : 1 (0x1280001)
  Bridge ID: 0, Split Horizon ID: 0
  RX TLU1 : 0x4c00
  RX TLU2 : 0x1013c00
  RX TLU3 : 0x200ba00
  RX TLU4 : 0x3000c00

EGRESS AC [version, state]: [1, BOUND]

  Xconnect-ID: [1] TLU2-entry-addr: [0x200a001]
  HW: 0x8018b000 0x0000000b 0x00004001 0xfb7ba000
  SW: 0x8018b000 0x0000000b 0x00004001 0xfb7ba000

  Entry status: 1 (Fwd)
  AC_type: 1 (vlan-mode)
  Outer-vlan: 1
  Inner-vlan: 0
  Outer Ether Type: 0 (dot1q)
  AC_mtu: 1580
  Adjacency_type: 0
  Default EgressQ (SharqQ): 11
  PW mode: 0 (vc-type 5)
  Rewrite supported: 0 (No)
  Control-word supported: 0 (No)
  Egress AC stats: 0x7dbdd

GigabitEthernet0/2/0/1.2, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: AC
  XID: 0/2/CPU0 : 2 (0x1280002)
  Bridge ID: 0, Split Horizon ID: 0
  RX TLU1 : 0x4c01
  RX TLU2 : 0x1013c01
  RX TLU3 : 0x200ba01
  RX TLU4 : 0x3000c01

EGRESS AC [version, state]: [1, BOUND]

  Xconnect-ID: [2] TLU2-entry-addr: [0x200a002]
  HW: 0x8018b000 0x0000000b 0x00004002 0xfb7b4000
  SW: 0x8018b000 0x0000000b 0x00004002 0xfb7b4000

  Entry status: 1 (Fwd)
  AC_type: 1 (vlan-mode)
  Outer-vlan: 2
  Inner-vlan: 0

```

show l2vpn forwarding bridge-domain (VPLS)

```

Outer Ether Type: 0 (dot1q)
AC_mtu: 1580
Adjacency_type: 0
Default EgressQ (SharqQ): 11
PW mode: 0 (vc-type 5)
Rewrite supported: 0 (No)
Control-word supported: 0 (No)
Egress AC stats: 0x7dbda

```

```

GigabitEthernet0/2/0/1.3, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

```

```

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
Bridge Port Type: AC
XID: 0/2/CPU0 : 3 (0x1280003)
Bridge ID: 0, Split Horizon ID: 0
RX TLU1   : 0x4c02
RX TLU2   : 0x1013c02
RX TLU3   : 0x200ba02
RX TLU4   : 0x3000c02

```

```

EGRESS AC [version, state]: [1, BOUND]

```

```

Xconnect-ID: [3] TLU2-entry-addr: [0x200a003]
HW: 0x8018b000 0x0000000b 0x00004003 0xfb7ae000
SW: 0x8018b000 0x0000000b 0x00004003 0xfb7ae000

```

```

Entry status: 1 (Fwd)
AC_type: 1 (vlan-mode)
Outer-vlan: 3
Inner-vlan: 0
Outer Ether Type: 0 (dot1q)
AC_mtu: 1580
Adjacency_type: 0
Default EgressQ (SharqQ): 11
PW mode: 0 (vc-type 5)
Rewrite supported: 0 (No)
Control-word supported: 0 (No)
Egress AC stats: 0x7dbd7

```

```

Nbor 5.0.0.5 pw-id 1
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

```

```

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
Bridge Port Type: ATOM
XID: 127/15/CPU0 : 1 (0xffff80001)
Bridge ID: 0, Split Horizon ID: 1
VC label: 16006
Control-word supported: No

```

```

Bridge-domain name: aa:g2, id: 1, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 2

```



```

Number of MAC addresses: 0
Multi-spanning tree instance: 0

EGRESS BRIDGE [version, state]: [1, CREATED]

  BID: 1   Total_oif_count: 2
  AC:   oif_count: 1   head_ptr: 0x9ff6e534   tail_ptr: 0x9ff6e534
  PW:   oif_count: 1   head_ptr: 0x9ff6e5ac

  PLU RESULT Key[Bridge-ID: 1]
  HW: 0x04004000 0x000a02c0 0x00000000 0x00000000
  SW: 0x04004000 0x000a02c0 0x00000000 0x00000000
  Entry_type: 1
  OLIST pointer: 0xa02
  OLIST channel: 3
  OLIST count: 2

  OIF[0] seg_type: AC xid: 0x1280004 Gi0/2/0/1.4 (ifh: 0x1280062)
  TLU RESULT tlu_addr: 0x3000a02 ch: 3 seg_type: 1
  HW: 0x80000002 0x00ba0280 0x01280004 0x00000000
  SW: 0x80000002 0x00ba0280 0x01280004 0x00000000
  SHG: 0
  UIDB: 2
  XID: 0x1280004
  OLIST pointer: 0xba02
  OLIST channel: 2

  OIF[1] seg_type: PW xid: 0xffff80002 ecd_ptr: 0x5200
  TLU RESULT tlu_addr: 0x200ba02 ch: 2 seg_type: 0
  HW: 0x01005200 0x00000000 0xffff80002 0x03e88000
  SW: 0x01005200 0x00000000 0xffff80002 0x03e88000
  SHG: 1
  XID: 0xffff80002
  OLIST pointer: 0x0
  OLIST channel: 0
  Control Word: Disabled
  VC label: 16008
  ECD/TLU1 pointer: 0x5200

GigabitEthernet0/2/0/1.4, state: oper up
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: AC
  XID: 0/2/CPU0 : 4 (0x1280004)
  Bridge ID: 1, Split Horizon ID: 0
  RX TLU1 : 0x4c03
  RX TLU2 : 0x1013c03
  RX TLU3 : 0x200ba03
  RX TLU4 : 0x3000c03

EGRESS AC [version, state]: [1, BOUND]

  Xconnect-ID: [4] TLU2-entry-addr: [0x200a004]
  HW: 0x8018b000 0x0000000b 0x00004004 0xfb7a8000
  SW: 0x8018b000 0x0000000b 0x00004004 0xfb7a8000

  Entry status: 1 (Fwd)
  AC_type: 1 (vlan-mode)
  Outer-vlan: 4
  Inner-vlan: 0
  Outer Ether Type: 0 (dot1q)
  AC_mtu: 1580
  Adjacency_type: 0
  Default EgressQ (SharqQ): 11
  PW mode: 0 (vc-type 5)
  Rewrite supported: 0 (No)
  Control-word supported: 0 (No)
  Egress AC stats: 0x7dbd4

```

show l2vpn forwarding bridge-domain (VPLS)

```

Nbor 5.0.0.5 pw-id 2
Number of MAC: 0
Statistics:
  packets: received 0, sent 0
  bytes: received 0, sent 0

EGRESS BRIDGE PORT [version, state]: [1, BOUND]
Bridge Port Type: ATOM
XID: 127/15/CPU0 : 2 (0xffff80002)
Bridge ID: 1, Split Horizon ID: 1
VC label: 16008
Control-word supported: No

```

This table describes the significant fields shown in the display.

Table 5: show l2vpn forwarding bridge-domain Command Field Descriptions

Field	Description
Bridge-Domain Name	Name of bridge domain is displayed.
Bridge ID	ID assigned to this bridge domain is displayed.
Ports	Number of ports that are part of this bridge domain is displayed.
MAC Addr	Number of MAC addresses that are learned on this bridge domain is displayed.
Flooding	Flooding of packets are displayed if they are enabled on this bridge domain.
Learning	Learning of MAC addresses are displayed if they are enabled on this bridge domain.
State	Current state of the bridge domain is displayed.

Related Commands

Command	Description
clear l2vpn bridge-domain (VPLS) , on page 11	Clears the MAC addresses and restarts the bridge domains on the router.

show l2vpn forwarding bridge-domain mac-address (VPLS)

To display the summary information for the MAC address, use the **show l2vpn forwarding bridge-domain mac-address** command in EXEC mode.

```
show l2vpn forwarding bridge-domain [ bridge-domain-name ] mac-address {MAC-address} detail
hardware {egress| ingress}| interface type interface-path-id| neighbor address pw-id pw-id; location
node-id
```

Syntax Description

<i>bridge-domain-name</i>	(Optional) Name of a bridge domain.
<i>MAC-address</i>	MAC address.
detail	Displays detailed information for the MAC address.
hardware	Reads information from the hardware.
egress	Reads information from the egress PSE.
ingress	Reads information from the ingress PSE.
interface	Displays the match for the attachment circuit subinterface.
<i>type</i>	Interface type. For more information, use the question mark (?) online help function.
<i>interface-path-id</i>	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
neighbor address	Displays the match for the neighbor IP address.
pw-id pw-id	Displays the match for the pseudowire ID.
location node-id	Displays the bridge-domain information for the MAC address of the specified location. The <i>node-id</i> argument is entered in the <i>rack/slot/module</i> notation.

Command Default None

Command Modes EXEC

Command History

Release	Modification
Release 3.7.0	This command was introduced.
Release 3.7.2	This command was introduced.
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID

Task ID	Operations
l2vpn	read

Examples

The following sample output shows the specified location of the bridge-domain name g1:bd1 for the MAC address:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain g1:bd1 location 0/1/CPU0
Bridge-ID      Ports  MAC addr  Flooding  Learning  State
-----
g1:bd1        0      2      65536  Enabled  Enabled  UP
```

The following sample output shows the list of MAC addresses that are learned on a specified bridge and summary information for the addresses:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain mac-address location 0/1/CPU0
Mac Address   Type      Learned from/Filtered on  LC learned Age
-----
0000.0000.0000 static   Gi0/1/0/0                 N/A           N/A
0000.0001.0101 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0102 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0103 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0104 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0105 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0106 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0107 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0108 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0109 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010a dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010b dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010c dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010d dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010e dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.010f dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0110 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0111 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
0000.0001.0112 dynamic  Gi0/1/0/0                 0/1/CPU0     0d 0h 2m 22s
....
```

The following sample output shows the MAC address on a specified interface on a specified bridge:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain g1:bd1 mac-address 1.2.3 location 0/1/CPU0
```

Mac Address	Type	Learned from/Filtered on	LC learned	Age
0001.0002.0003	static	Gi0/1/0/0	N/A	N/A

The following sample output shows the hardware information from the egress pse:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain g1:bd1 mac-address hardware egress location 0/1/CPU0
```

Mac Address	Type	Learned from/Filtered on	LC learned	Age
0000.0000.0000	static	Gi0/1/0/0	N/A	N/A
0000.0001.0101	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0102	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0103	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0104	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0105	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0106	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0107	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0108	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0109	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010a	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010b	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010c	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010d	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010e	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.010f	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0110	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0111	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0112	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0113	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
0000.0001.0114	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 24s
...				

The following sample output shows the MAC addresses that are learned on a specified pseudowire on a specified bridge:

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain mac-address neighbor 1.1.1.1 pw-id 1 location 0/1/CPU0
```

Mac Address	Type	Learned from/Filtered on	LC learned	Age
0000.0003.0101	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0102	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0103	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0104	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0105	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0106	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0107	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0108	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0109	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010a	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010b	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010c	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010d	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010e	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.010f	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0110	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0111	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0112	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0113	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0114	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
0000.0003.0115	dynamic	1.1.1.1, 1	0/1/CPU0	0d 0h 0m 30s
...				

show l2vpn forwarding bridge-domain mac-address (VPLS)

The following sample output shows the detailed information for MAC addresses that are learned on a specified interface and on specified bridge of a specified interface card. The sample output lists all the MAC addresses, the learned location, and the current age.

```
RP/0/RP0/CPU0:router# show l2vpn forwarding bridge-domain g1:bd1 mac-address interface
gigabitEthernet 0/1/0/0 location 0/1/CPU0
```

Mac Address	Type	Learned from/Filtered on	LC learned	Age
0000.0000.0000	static	Gi0/1/0/0	N/A	N/A
0000.0001.0101	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0102	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0103	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0104	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0105	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0106	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0107	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0108	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0109	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010a	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010b	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010c	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010d	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010e	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.010f	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0110	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0111	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0112	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0113	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s
0000.0001.0114	dynamic	Gi0/1/0/0	0/1/CPU0	0d 0h 2m 14s

The following sample output shows the MAC address hardware information on the line card, for a specific bridge-domain on the ingress detail location:

```
RP/0/RP0/CPU0:router#show l2vpn forwarding bridge-domain mac hardware ingress detail location
0/2/CPU0
```

```
Bridge-domain name: aa:g1, id: 0, state: up
MAC learning: enabled
Flooding:
  Broadcast & Multicast: enabled
  Unknown unicast: enabled
MAC aging time: 300 s, Type: inactivity
MAC limit: 4000, Action: none, Notification: syslog
MAC limit reached: no
Security: disabled
DHCPv4 snooping: profile not known on this node
Bridge MTU: 1500 bytes
Number of bridge ports: 4
Number of MAC addresses: 10
Multi-spanning tree instance: 0

INGRESS BRIDGE [version, state]: [1, CREATED]

TCAM entry seq#: 1024 Key: [BID: 0 MAC: default]
HW: 0x4c000000 0x000080ac 0x00010000 0x80ac0100
SW: 0x4c000000 0x000080ac 0x00010000 0x80ac0100

SMAC: action: PUNT state: NO REFRESH
DMAC: action: FLOOD, flood enable: enable
FGID: All: 44032, VFI: 44033, MCAST_Sponge_q: 16
Fabric_multicast1: 1 Fabric_multicast2: 1

Admin State: UP
MTU: 1500
Number of MAC addresses: 11 (10 MAC + 1 default)
ACL NAME (ACL-ID): VPLS Special (4096)
TCAM region handle : 5
```

```

GigabitEthernet0/2/0/1.1, state: oper up
Number of MAC: 10
Statistics:
  packets: received 0, sent 121515
  bytes: received 0, sent 7290900

INGRESS BRIDGE PORT [version, state]: [1, BOUND]
  Bridge Port Type: AC
  XID: 0/2/CPU0 : 1 (0x1280001)
  Bridge ID: 0, Split Horizon ID: 0
  RX TLU1 : 0x4c00
  RX TLU2 : 0x1013c00
  RX TLU3 : 0x200ba00
  RX TLU4 : 0x3000c00

INGRESS AC [version, state]: [1, BOUND]

  Xconnect-ID: [1] TCAM-Key: (UIDB:0x2 O-vlan:1 I-vlan:0 Ether-Type:0x8100)
  HW: 0x24001000 0x01280001 0x10128000 0xc7ff7d00
  SW: 0x24001000 0x01280001 0x10128000 0xc7ff7d00

  Service type: 4 (bridging pmp)
  Entry type: 1 (fwd)
  Bridge_ID : 0
  ACL_ID : 4096
  Xconnect_ID : 0x1280001
  SplitHorizonGroup_ID : 0
  Rewrite supported: 0 (No)
  PW mode: 0 (vc-type 5)
  AC-type: 1 (vlan-mode)
  Interface handle: 0x128000
  Ingress AC stats: 0x7ff7d

  SMAC Learning: enable
  DMAC Flooding: enable

Mac Address: 0000.0022.2222, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

INGRESS MAC [version, state]: [1, CREATED]

  TCAM entry seq#: 0 Key: [BID: 0 MAC: 0000.0022.2222]
  HW: 0x22004c00 0x00000001 0x00000000 0x01280001
  SW: 0x22004c00 0x00000001 0x00000000 0x01280001

  SMAC: action: FWD state: REFRESH
  XID: 0/2/CPU0 : 1 (0x1280001)
  DMAC: action: FWD, BridgePort type: AC
  SHG ID : 0
  Entry Flag : FWD
  Entry Type : DYNAMIC
  Local Switching: enabled
  Next (tlu0) addr: 0x4c00
  Control-word supported: No

  Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

  TLU1 : 0x4c00
  [HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label: 0 num of labels: 0
  entry type: FWD next ptr: 0x00013c00
  num of entries: 1
  BGP next-hop: 0.0.0.0

  TLU2 : 0x1013c00
  [HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1: 1 label2: 0
  num of labels: 1 next ptr: 0x0000ba00

  TLU3 : 0x200ba00
  [HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1

```

show l2vpn forwarding bridge-domain mac-address (VPLS)

```

        num. labels : 0
        label 1    : 0
        label 2    : 0
        next ptr   : 0xc00

TLU4      : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr : 0x20
  sponge queue : 130
  egress port : 0x128004
  rp destined  : no
  rp drop     : no
  hash type   : 0
  uidb index  : 0x2

Mac Address: 0000.0022.2223, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

INGRESS MAC [version, state]: [1, CREATED]

TCAM entry seq#: 1 Key: [BID: 0 MAC: 0000.0022.2223]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID : 0
Entry Flag : FWD
Entry Type : DYNAMIC
Local Switching: enabled
Next (tlu0) addr: 0x4c00
Control-word supported: No

Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

TLU1      : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label: 0 num of labels: 0
  entry type: FWD next ptr: 0x00013c00
  num of entries: 1
  BGP next-hop: 0.0.0.0

TLU2      : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1: 1 label2: 0
  num of labels: 1 next ptr: 0x0000ba00

TLU3      : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1
  num. labels  : 0
  label 1     : 0
  label 2     : 0
  next ptr    : 0xc00

TLU4      : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr : 0x20
  sponge queue : 130
  egress port : 0x128004
  rp destined  : no
  rp drop     : no
  hash type   : 0
  uidb index  : 0x2

Mac Address: 0000.0022.2224, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

INGRESS MAC [version, state]: [1, CREATED]

```



```

TCAM entry seq#: 2 Key: [BID: 0 MAC: 0000.0022.2224]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID      : 0
Entry Flag  : FWD
Entry Type  : DYNAMIC
Local Switching: enabled
Next (tlu0) addr: 0x4c00
Control-word supported: No

Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

TLU1          : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label:      0      num of labels: 0
  entry type: FWD    next ptr:    0x00013c00
  num of entries: 1
  BGP next-hop: 0.0.0.0

TLU2          : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1:    1      label2:    0
  num of labels: 1      next ptr: 0x0000ba00

TLU3          : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1
  num. labels  : 0
  label 1     : 0
  label 2     : 0
  next ptr    : 0xc00

TLU4          : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr   : 0x20
  sponge queue : 130
  egress port  : 0x128004
  rp destined  : no
  rp drop      : no
  hash type    : 0
  uidb index   : 0x2

Mac Address: 0000.0022.2225, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

```

```
INGRESS MAC [version, state]: [1, CREATED]
```

```

TCAM entry seq#: 3 Key: [BID: 0 MAC: 0000.0022.2225]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID      : 0
Entry Flag  : FWD
Entry Type  : DYNAMIC
Local Switching: enabled
Next (tlu0) addr: 0x4c00
Control-word supported: No

Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

TLU1          : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label:      0      num of labels: 0
  entry type: FWD    next ptr:    0x00013c00
  num of entries: 1

```

show l2vpn forwarding bridge-domain mac-address (VPLS)

```

      BGP next-hop: 0.0.0.0

TLU2      : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1:      1      label2:      0
  num of labels: 1      next ptr: 0x0000ba00

TLU3      : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1
  num. labels  : 0
  label 1     : 0
  label 2     : 0
  next ptr    : 0xc00

TLU4      : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr   : 0x20
  sponge queue : 130
  egress port  : 0x128004
  rp destined  : no
  rp drop      : no
  hash type    : 0
  uidb index   : 0x2

Mac Address: 0000.0022.2226, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

INGRESS MAC [version, state]: [1, CREATED]

TCAM entry seq#: 4 Key: [BID: 0 MAC: 0000.0022.2226]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID      : 0
Entry Flag  : FWD
Entry Type  : DYNAMIC
Local Switching: enabled
Next (tlu0) addr: 0x4c00
Control-word supported: No

Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

TLU1      : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label:      0      num of labels: 0
  entry type: FWD      next ptr: 0x00013c00
  num of entries: 1
  BGP next-hop: 0.0.0.0

TLU2      : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1:      1      label2:      0
  num of labels: 1      next ptr: 0x0000ba00

TLU3      : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1
  num. labels  : 0
  label 1     : 0
  label 2     : 0
  next ptr    : 0xc00

TLU4      : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr   : 0x20
  sponge queue : 130
  egress port  : 0x128004
  rp destined  : no

```

```

rp drop      : no
hash type    : 0
uidb index   : 0x2

```

```

Mac Address: 0000.0022.2227, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

```

```
INGRESS MAC [version, state]: [1, CREATED]
```

```

TCAM entry seq#: 5 Key: [BID: 0 MAC: 0000.0022.2227]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

```

```

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID      : 0
Entry Flag  : FWD
Entry Type  : DYNAMIC
Local Switching: enabled
Next (tlu0) addr: 0x4c00
Control-word supported: No

```

```
Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)
```

```

TLU1        : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
label:      0          num of labels: 0
entry type: FWD       next ptr: 0x00013c00
num of entries: 1
BGP next-hop: 0.0.0.0

```

```

TLU2        : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
label1:     1          label2: 0
num of labels: 1      next ptr: 0x0000ba00

```

```

TLU3        : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
num. entries : 1
num. labels  : 0
label 1     : 0
label 2     : 0
next ptr    : 0xc00

```

```

TLU4        : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
dest. addr  : 0x20
sponge queue : 130
egress port : 0x128004
rp destined  : no
rp drop     : no
hash type   : 0
uidb index  : 0x2

```

```

Mac Address: 0000.0022.2228, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

```

```
INGRESS MAC [version, state]: [1, CREATED]
```

```

TCAM entry seq#: 6 Key: [BID: 0 MAC: 0000.0022.2228]
HW: 0x22004c00 0x00000001 0x00000000 0x01280001
SW: 0x22004c00 0x00000001 0x00000000 0x01280001

```

```

SMAC: action: FWD state: REFRESH
XID: 0/2/CPU0 : 1 (0x1280001)
DMAC: action: FWD, BridgePort type: AC
SHG ID      : 0
Entry Flag  : FWD
Entry Type  : DYNAMIC
Local Switching: enabled

```

show l2vpn forwarding bridge-domain mac-address (VPLS)

```

Next (tlu0) addr: 0x4c00
Control-word supported: No

Destination AC: Gi0/2/0/1.1 (ifh: 0x1280002)

TLU1          : 0x4c00
[HW: 0x00000000 0x00013c00 0x00000000 0x00000100]
  label:      0      num of labels:      0
  entry type: FWD    next ptr:      0x00013c00
  num of entries: 1
  BGP next-hop: 0.0.0.0

TLU2          : 0x1013c00
[HW: 0x00000008 0x00000000 0x00001000 0x00ba0000]
  label1:     1      label2:      0
  num of labels: 1      next ptr: 0x0000ba00

TLU3          : 0x200ba00
[HW: 0x00010000 0x00000000 0x00000000 0x000c0000]
  num. entries : 1
  num. labels  : 0
  label 1     : 0
  label 2     : 0
  next ptr    : 0xc00

TLU4          : 0x3000c00
[HW: 0x00000000 0x20082000 0x01280040 0x00020000]
  dest. addr   : 0x20
  sponge queue : 130
  egress port  : 0x128004
  rp destined  : no
  rp drop      : no
  hash type    : 0
  uidb index   : 0x2

```

```

Mac Address: 0000.0022.2229, LC learned: 0/2/CPU0
Age: 0d 0h 0m 21s, Flag: local

```

Related Commands

Command	Description
show l2vpn forwarding bridge-domain (VPLS) , on page 45	Displays information on the bridge that is used by the forwarding layer.

shutdown (Bridge Domain)

To shut down a bridge domain to bring the bridge and all attachment circuits and pseudowires under it to admin down state, use the **shutdown** command in L2VPN bridge group bridge domain configuration mode. To re-enable the bridge domain, use the **no** form of this command.

shutdown

no shutdown

Syntax Description This command has no keywords or arguments.

Command Default By default, the bridge is not shutdown.

Command Modes L2VPN bridge group bridge domain configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

When a bridge domain is disabled, all VFIs associated with the bridge domain are disabled. You can still attach or detach members to or from the bridge domain as well as the VFIs associated with the bridge domain.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to disable the bridge domain named bar:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# shutdown
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.

shutdown (VFI)

To disable virtual forwarding interface (VFI), use the **shutdown** command in L2VPN bridge group bridge domain VFI configuration mode. To re-enable VFI, use the **no** form of this command.

shutdown

no shutdown

Syntax Description This command has no keywords or arguments.

Command Default By default, the VFI is not shutdown.

Command Modes L2VPN bridge group bridge domain VFI configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to disable VFI:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi v1
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)# shutdown
```

Related Commands	Command	Description
	bridge-domain (VPLS) , on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.

Command	Description
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mpls static label (VPLS), on page 25	Configures the MPLS static labels and the static labels for the access pseudowire configuration.
neighbor (VPLS), on page 29	Adds an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI).

static-address (VPLS)

To add static entries to the MAC address for filtering, use the **static-address** command in L2VPN bridge group bridge domain MAC configuration mode. To remove entries profiled by the combination of a specified entry information, use the **no** form of this command.

static-address *MAC-address* **drop**

no static-address *MAC-address* **drop**

Syntax Description

<i>MAC-address</i>	Static MAC address that is used to filter on the bridge domain.
drop	Drops all traffic that is going to the configured MAC address.

Command Default

No static MAC address is configured.

Command Modes

L2VPN bridge group bridge domain MAC configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to add static MAC entries in L2VPN bridge group bridge domain MAC configuration mode. This entry causes all packets with destination MAC address 1.1.1 to be dropped.

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# static-address 1.1.1 drop
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.

static-mac-address (VPLS)

To configure the static MAC address to associate a remote MAC address with a pseudowire or any other bridge interface, use the **static-mac-address** command in the appropriate L2VPN bridge group bridge domain configuration submenu. To disable this feature, use the **no** form of this command.

static-mac-address *MAC-address*

no static-mac-address *MAC-address*

Syntax Description	<i>MAC-address</i>	Static address to add to the MAC address.
---------------------------	--------------------	---

Command Default	None
------------------------	------

Command Modes	L2VPN bridge group bridge domain VFI pseudowire configuration L2VPN bridge group bridge domain attachment circuit configuration
----------------------	--

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines	To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.
-------------------------	---

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to associate a remote MAC address with a pseudowire:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi model
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)# neighbor 10.1.1.2 pw-id 1000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi-pw)# static-mac-address 1.1.1
```

The following example shows how to associate a GigabitEthernet interface from a bridge domain to static MAC address 1.1.1:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# interface GigabitEthernet 0/1/0/0
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-ac)# static-mac-address 1.1.1
```

The following example shows how to associate an access pseudowire to static MAC address 2.2.2:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# neighbor 10.1.1.2 pw-id 2000
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-pw)# static-mac-address 2.2.2
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mpls static label (VPLS), on page 25	Configures the MPLS static labels and the static labels for the access pseudowire configuration.
neighbor (VPLS), on page 29	Adds an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI).
vfi (VPLS), on page 81	Configures virtual forwarding interface (VFI) parameters.

time (VPLS)

To configure the maximum aging time, use the **time** command in L2VPN bridge group bridge domain MAC aging configuration mode. To disable this feature, use the **no** form of this command.

time *seconds*

no time *seconds*

Syntax Description

<i>seconds</i>	MAC address table entry maximum age. The range is from 300 to 30000 seconds. Aging time is counted from the last time that the switch saw the MAC address. The default value is 300 seconds.
----------------	--

Command Default

seconds: 300

Command Modes

L2VPN bridge group bridge domain MAC aging configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

If no packets are received from the MAC address for the duration of the maximum aging time, the dynamic MAC entry previously learned is removed from the forwarding table.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to increase the maximum aging time to 600 seconds. After 600 seconds of inactivity from a MAC address, the MAC address is removed from the forwarding table.

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
```

```
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac) # aging
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-aging) # time 600
```

Related Commands

Command	Description
aging (VPLS), on page 5	Enters the MAC aging configuration submode to set the aging parameters such as time and type.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
type (VPLS), on page 79	Configures the type for MAC address aging.

type (VPLS)

To configure the type for MAC address aging, use the **type** command in L2VPN bridge group bridge domain MAC aging configuration mode. To disable this feature, use the **no** form of this command.

type {absolute| inactivity}

no type {absolute| inactivity}

Syntax Description

absolute	Configures the absolute aging type.
inactivity	Configures the inactivity aging type.

Command Default

By default, the inactivity type is configured.

Command Modes

L2VPN bridge group bridge domain MAC aging configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

In general, the type is set to inactivity. With an inactivity type configuration, a MAC address is removed from the forwarding table after the MAC address is inactive for the configured aging time.

With an absolute type configuration, a MAC address is always removed from the forwarding table after the aging time has elapsed once it is initially learned.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to configure the MAC address aging type to absolute for every member of the bridge domain named bar:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
```

```

RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# aging
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac-aging)# type absolute

```

Related Commands

Command	Description
aging (VPLS), on page 5	Enters the MAC aging configuration submode to set the aging parameters such as time and type.
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.
time (VPLS), on page 77	Configures the maximum aging time.

vfi (VPLS)

To configure virtual forwarding interface (VFI) parameters and to enter L2VPN bridge group bridge domain VFI configuration mode, use the **vfi** command in L2VPN bridge group bridge domain configuration mode. To remove all configurations that are made under the specified VFI, use the **no** form of this command.

vfi *vfi-name*

no vfi *vfi-name*

Syntax Description

<i>vfi-name</i>	Name of the specified virtual forwarding interface.
-----------------	---

Command Default

None

Command Modes

L2VPN bridge group bridge domain configuration

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **vfi** command to enter L2VPN bridge group bridge domain VFI configuration mode.

You cannot configure a pseudowire directly under a bridge domain. Therefore, a pseudowire must be configured under a VFI, which is configured under a bridge domain.

Task ID

Task ID	Operations
l2vpn	read, write

Examples

The following example shows how to create a VFI:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# vfi vl
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-vfi)#
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mpls static label (VPLS), on page 25	Configures the MPLS static labels and the static labels for the access pseudowire configuration.
neighbor (VPLS), on page 29	Adds an access pseudowire port to a bridge domain or a pseudowire to a bridge virtual forwarding interface (VFI).

withdraw (VPLS)

To enable MAC address withdrawal for a specified bridge domain, use the **withdraw** command in L2VPN bridge group bridge domain MAC configuration mode. To disable this feature, use the **no** form of this command

```
withdraw { disable }
```

```
no withdraw { disable }
```

Syntax Description	disable	Disables MAC address withdrawal.
--------------------	---------	----------------------------------

Command Default By default, MAC address withdrawal is enabled.

Command Modes L2VPN bridge group bridge domain MAC configuration

Command History	Release	Modification
	Release 3.8.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID	Task ID	Operations
	l2vpn	read, write

Examples The following example shows how to enable disable MAC withdrawal:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd)# mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac)# withdraw disable
```

The following example shows how to disable sending MAC withdrawal messages to access pseudowires:

```
RP/0/RP0/CPU0:router# configure
RP/0/RP0/CPU0:router(config)# l2vpn
RP/0/RP0/CPU0:router(config-l2vpn)# bridge group 1
RP/0/RP0/CPU0:router(config-l2vpn-bg)# bridge-domain bar
```

```
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd) # mac
RP/0/RP0/CPU0:router(config-l2vpn-bg-bd-mac) # withdraw access-pw disable
```

Related Commands

Command	Description
bridge-domain (VPLS), on page 7	Establishes a bridge domain, and enters L2VPN bridge group bridge domain configuration mode.
bridge group (VPLS), on page 9	Creates a bridge group so that it can contain bridge domains and then to assign network interfaces to the bridge domain.
l2vpn	Enters L2VPN configuration mode.
mac (VPLS), on page 21	Enters L2VPN bridge group bridge domain MAC configuration mode.