



New and Changed Information for Segment Routing Features

This table summarizes the new and changed feature information for the *Segment Routing Configuration Guide for the Cisco CRS Router*, and lists where they are documented.

- [New and Changed Information, on page 1](#)

New and Changed Information

Table 1: New and Changed Features

Feature	Description	Introduced/Changed in Release	Where Documented
IOS XR Traffic Controller (XTC)	This feature was introduced.	Release 6.2.1	<i>Configure IOS XR Traffic Controller (XTC)</i>
Segment Routing Microloop Avoidance	This feature was introduced.	Release 6.2.1	<i>Configure Segment Routing Microloop Avoidance</i>
IS-IS Multi-Domain Prefix SID and Domain Stitching	This feature was introduced.	Release 6.2.1	<i>Configure Segment Routing for IS-IS Protocol</i>
Strict SPF Segment IDs for IS-IS	This feature was introduced.	Release 6.2.1	<i>Configure Segment Routing for IS-IS Protocol</i>
Prefix Attribute TLV for IS-IS	This feature was introduced.	Release 6.2.1	<i>Configure Segment Routing for IS-IS Protocol</i>
MPLS Ping and Traceroute for Prefix-SID	This feature was introduced.	Release 6.2.1	<i>Using Segment Routing OAM</i>

