



## Modular QoS Overview

---

Quality of Service (QoS) is the technique of prioritizing traffic flows and providing preferential forwarding for higher-priority packets. The fundamental reason for implementing QoS in your network is to provide better service for certain traffic flows. A traffic flow can be defined as a combination of source and destination addresses, source and destination socket numbers, and the session identifier. A traffic flow can more broadly be described as a packet moving from an incoming interface that is destined for transmission to an outgoing interface. The traffic flow must be identified, classified, and prioritized on all routers and passed along the data forwarding path throughout the network to achieve end-to-end QoS delivery. The terms *traffic flow* and *packet* are used interchangeably throughout this module.

To implement QoS on a network requires the configuration of QoS features that provide better and more predictable network service by supporting bandwidth allocation, improving loss characteristics, avoiding and managing network congestion, metering network traffic, or setting traffic flow priorities across the network.

This module contains overview information about modular QoS features within a service provider network.

- [Information About Modular Quality of Service Overview, on page 1](#)
- [Supported Capability Matrix, on page 5](#)
- [Where to Go Next, on page 8](#)
- [Additional References, on page 8](#)

## Information About Modular Quality of Service Overview

Before configuring modular QoS on your network, you must understand these concepts:

### Benefits of Cisco IOS XR QoS Features

The Cisco IOS XR QoS features enable networks to control and predictably service a variety of networked applications and traffic types. Implementing Cisco IOS XR QoS in your network promotes these benefits:

- **Control over resources.** You have control over which resources (bandwidth, equipment, wide-area facilities, and so on) are being used. For example, you can limit bandwidth consumed over a backbone link by FTP transfers or give priority to an important database access.
- **Tailored services.** If you are an Internet Service Provider (ISP), the control and visibility provided by QoS enables you to offer carefully tailored grades of service differentiation to your customers.
- **Coexistence of mission-critical applications.** Cisco IOS XR QoS features ensure:

- That bandwidth and minimum delays required by time-sensitive multimedia and voice applications are available.
- That your WAN is used efficiently by mission-critical applications that are most important to your business.
- That bandwidth and minimum delays required by time-sensitive multimedia and voice applications are available.
- That other applications using the link get their fair service without interfering with mission-critical traffic.

## QoS Techniques

QoS on Cisco IOS XR software relies on these techniques to provide for end-to-end QoS delivery across a heterogeneous network:

- Packet classification
- Congestion management
- Congestion avoidance

Before implementing the QoS features for these techniques, you should identify and evaluate the traffic characteristics of your network because not all techniques are appropriate for your network environment.

## Packet Classification

Packet classification techniques identify the traffic flow, and provide the capability to partition network traffic into multiple priority levels or classes of service. After traffic flow is identified, it can be marked as a traffic class.

Identification of a traffic flow can be performed by using several methods within a single router: access control lists (ACLs), protocol match, IP precedence, IP differentiated service code point (DSCP), and so on.

Marking of a traffic flow is performed by:

- Setting IP Precedence or DSCP bits in the IP Type of Service (ToS) byte.
- Setting Class of Service (CoS) bits in the Layer 2 headers (Ethernet, Spatial Reuse Protocol [SRP], and so on).
- Setting EXP bits within the imposed or the topmost Multiprotocol Label Switching (MPLS) label.
- Setting qos-group and discard-class bits.

Marking can be carried out:

- Unconditionally—As part of the class-action.
- Conditionally—As part of a policer-action.
- Combination of conditionally and unconditionally.



---

**Note** The Cisco CRS Series Modular Services Card 140G (CRS-MS-140G) does not support SRP interfaces.

---

For detailed conceptual and configuration information about packet marking, see the [Configuring Modular Quality of Service Packet Classification on Cisco IOS XR Software](#) module for unconditional marking, and [Configuring Modular Quality of Service Congestion Management on Cisco IOS XR Software](#) module for conditional marking.

## Congestion Management

Congestion management techniques control congestion after it has occurred. One way that network elements handle an overflow of arriving traffic is to use a queuing algorithm to sort the traffic, then determine some servicing method of prioritizing it onto an output link.

Cisco IOS XR software implements the low-latency Queuing (LLQ) feature, which brings strict priority queuing (PQ) to the Modified Deficit Round Robin (MDRR) scheduling mechanism. LLQ with strict PQ allows delay-sensitive data such as voice, to be dequeued and sent before packets in other queues are dequeued.

Cisco IOS XR software includes traffic policing capabilities available on a per-class basis as well as class-based shaping.

The traffic policing feature limits the input or output transmission rate of a class of traffic based on user-defined criteria, and can mark packets by setting values such as IP Precedence, QoS group, or DSCP value.

Traffic shaping allows control over the traffic that leaves an interface to match its flow to the speed of the remote target interface and ensure that the traffic conforms to the policies contracted for it. Thus, traffic adhering to a particular profile can be shaped to meet downstream requirements, thereby eliminating bottlenecks in topologies with data-rate mismatches.

Cisco IOS XR software supports a class-based traffic shaping method through a CLI mechanism in which parameters are applied per class.

For detailed conceptual and configuration information about congestion management, see the [Configuring Modular Quality of Service Congestion Management on Cisco IOS XR Software](#) module.

## Congestion Avoidance

Congestion avoidance techniques monitor network traffic flows in an effort to anticipate and avoid congestion at common network and internetwork bottlenecks before problems occur. These techniques are designed to provide preferential treatment for traffic (such as a video stream) that has been classified as real-time critical under congestion situations while concurrently maximizing network throughput and capacity utilization and minimizing packet loss and delay. Cisco IOS XR software supports the Random Early Detection (RED), Weighted RED (WRED), and tail drop QoS congestion avoidance features.

For detailed conceptual and configuration information about congestion avoidance techniques, see the [Configuring Modular Quality of Service Congestion Management on Cisco IOS XR Software](#) module.

## Differentiated Service Model for Cisco IOS XR Software

Cisco IOS XR software supports a differentiated service that is a multiple-service model that can satisfy different QoS requirements. However, unlike in the integrated service model, an application using differentiated service does not explicitly signal the router before sending data.

For differentiated service, the network tries to deliver a particular kind of service based on the QoS specified by each packet. This specification can occur in different ways, for example, using the IP Precedence bit settings in IP packets or source and destination addresses. The network uses the QoS specification to classify, mark, shape, and police traffic, and to perform intelligent queuing.

The differentiated service model is used for several mission-critical applications and for providing end-to-end QoS. Typically, this service model is appropriate for aggregate flows because it performs a relatively coarse level of traffic classification.

## Additional Cisco IOS XR QoS Supported Features

These sections describe the additional features that play an important role in the implementation of QoS on Cisco IOS XR software.

### Modular QoS Command-Line Interface

In Cisco IOS XR software, QoS features are enabled through the Modular QoS command-line interface (MQC) feature. The *MQC* is a command-line interface (CLI) structure that allows you to create traffic policies and attach these policies to interfaces. A traffic policy contains a traffic class and one or more QoS features. A traffic class is used to classify traffic, whereas the QoS features in the traffic policy determine how to treat the classified traffic. One of the main goals of MQC is to provide a platform-independent interface for configuring QoS across Cisco platforms.

For detailed conceptual and configuration information about the MQC feature, see the Configuring Modular Quality of Service Packet Classification on Cisco IOS XR Software module.

### Fabric QoS

The fabricq queue selection mechanism is known as *Fabric QoS*. These ports are defined:

- High-priority port for internal control traffic and classified high-priority traffic
- Low-priority port for assured-forwarding (AF) traffic, and
- Best-effort port (BE) for low-priority traffic.

Each port has a queue associated with every physical interface on the line card. The queues map to a physical egress interface and are assigned when the interface is created. The associated quanta for each of the queues are derived from the bandwidth of the physical or logical interfaces in relative terms to the other interfaces present on that line card or PLIM.

## Interfaces Supported on CRS-MSC-140G

Some interfaces that are used in examples in this guide and are supported on the Cisco CRS Series Modular Services Card 40G (CRS-MSC-40G), are not supported on the Cisco CRS Series Modular Services Card 140G (CRS-MSC-140G). For information about interfaces supported on the CRS-MSC-140G, see the Compatibility Matrix table and the Supported PLIMs table in the CRS system description documents.

## Supported Capability Matrix

Feature	Support on CRS-1	Support on CRS-3	Support on CRS-X	Notes
<b>Classification (Match Criteria)</b>				
ANY	No	No	Yes	—
ALL	No	No	Yes	—
NOT	Yes	Yes	Yes	For CRS-X cards, the <b>match not</b> classification is not supported for <b>match access-group</b> , <b>match class-map</b> , or <b>match vlan</b> commands.
ACCESS-GROUP	Yes	Yes	Yes	—
COS INNER	Yes	Yes	Yes	—
COS	Yes	Yes	Yes	
DSCP	Yes	Yes	Yes	IP DSCP is supported for IPv4 and IPv6.
PRECEDENCE	Yes	Yes	Yes	—
MPLS EXPERIMENTAL TOPMOST	Yes	Yes	Yes	—
VLAN	Yes	Yes	Yes	Inner label matching is not supported for QOS on QinQ interfaces.
QOS-GROUP	Yes	Yes	Yes	—
PROTOCOL	Yes	Yes	Yes	—
DISCARD-CLASS	Yes	Yes	Yes	—
VPLS	Yes	Yes	Yes	—
DESTINATION ADDRESS MAC	Yes	Yes	No	—
SOURCE ADDRESS MAC	Yes	Yes	No	—
Frame Relay DLCI	Yes	No	No	
<b>Marking</b>				

Feature	Support on CRS-1	Support on CRS-3	Support on CRS-X	Notes
COS	Yes	Yes	Yes	For CRS-X cards, users can create up to four sets with the following combinations: <ul style="list-style-type: none"> <li>• Ingress: set qos-group+ set discard-class + Two additional sets</li> <li>• Egress: set inner cos + set outer cos + Two additional sets</li> </ul>
DISCARD-CLASS	Yes	Yes	Yes	—
QOS-GROUP	Yes	Yes	Yes	—
DSCP	Yes	Yes	Yes	—
DSCP TUNNEL	Yes	Yes	Yes	—
PRECEDENCE	Yes	Yes	Yes	—
GRE Tunnel Precedence	Yes	Yes	No	—
GRE Tunnel DSCP	Yes	Yes	No	—
MPLS EXPERIMENTAL TOPMOST	Yes	Yes	Yes	—
MPLS (EXPERIMENTAL) IMPOSITION	Yes	Yes	Yes	—
Spatial Reuse Protocol (SRP) priority	Yes	Yes	No	—
ATM-CLP (cell loss priority)	Yes	No	No	—
<b>Queuing</b>				
Ingress Queuing	Yes	Yes	No	—
Ingress Priority	Yes	Yes	Yes	—
Egress Queuing	Yes	Yes	Yes	—

Feature	Support on CRS-1	Support on CRS-3	Support on CRS-X	Notes
Egress Priority	Yes (priority level 1)	Yes (priority level 1, 2)	Yes (priority level 1,2)	—
<b>Congestion Management</b>				
Bandwidth	Yes	Yes	Yes	For CRS-X cards, <b>bandwidth, bandwidth remaining</b> and <b>shape</b> are supported only on Egress.
Bandwidth Remaining	Yes	Yes	Yes	
Shape	Yes	Yes	Yes	
<b>Congestion Avoidance</b>				
Random Detect	Yes	Yes	Yes	For CRS-X cards, random detect and queue limit is supported only on egress.
Random Detect Discard-class-based	Yes	Yes	Yes	
Random Detect COS	Yes	Yes	Yes	
Random Detect MPLS EXP	Yes	Yes	Yes	
Random Detect Precedence	Yes	Yes	Yes	
Random Detect DSCP	Yes	Yes	Yes	
Queue Limit	Yes	Yes	Yes	
<b>HQOS</b>	Yes (2-level)	Yes (2-level)	Yes (3-level)	
<b>Rate Limiting</b>				
1R2C	Yes	Yes	Yes	—
1R3C	Yes	Yes	Yes	
2R3C	Yes	Yes	Yes	
<b>QPPB</b>				
QoS Policy Propagation through BGP	No	Yes	Yes	For CRS-X cards, QPPB is supported from Release 5.1.3.

## Where to Go Next

To configure the packet classification features that involve identification and marking of traffic flows, see the Configuring Modular Quality of Service Packet Classification module in this guide.

To configure the queuing, scheduling, policing, and shaping features, see the Configuring Modular Quality of Service Congestion Management module in this guide.

To configure the WRED and RED features, see the Configuring Modular QoS Congestion Avoidance module in this guide.

To configure fabric QoS, see the Configuring Fabric Quality of Service Policies and Classes on Cisco IOS XR Software module.

## Additional References

The following sections provide references related to implementing QoS.

## Related Documents

Related Topic	Document Title
Initial system bootup and configuration	<i>Cisco IOS XR Getting Started Guide for the Cisco CRS Router</i>
Interface types supported on the CRS-MS-140G	Compatibility Matrix table and Supported PLIMs table in the CRS system description documents
QoS commands	Cisco IOS XR Modular Quality of Service Command Reference for the Cisco CRS Router
User groups and task IDs	“ <i>Configuring AAA Services on Cisco IOS XR Software</i> ” module of <i>Cisco IOS XR System Security Configuration Guide</i>

## Standards

Standards	Title
No new or modified standards are supported by this feature, and support for existing standards has not been modified by this feature.	—



## MIBs

MIBs	MIBs Link
—	To locate and download MIBs using Cisco IOS XR software, use the Cisco MIB Locator found at the following URL and choose a platform under the Cisco Access Products menu: <a href="http://cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml">http://cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml</a>

## RFCs

RFCs	Title
No new or modified RFCs are supported by this feature, and support for existing RFCs has not been modified by this feature.	—

## Technical Assistance

Description	Link
The Cisco Technical Support website contains thousands of pages of searchable technical content, including links to products, technologies, solutions, technical tips, and tools. Registered Cisco.com users can log in from this page to access even more content.	<a href="http://www.cisco.com/cisco/web/support/index.html">http://www.cisco.com/cisco/web/support/index.html</a>

