



# Preface

---

- [Preface, on page 1](#)

## Preface

This preface describes the objectives and organization of this document and explains how to find additional information on related products and services. This preface contains the following sections:

## Objectives

This document provides an overview of the Cisco CSR 1000V Series Cloud Services Router deployment on Amazon Web Services. It is not intended as a comprehensive guide to all of the software features that can be run using the Cisco CSR 1000V Series router. For more information, see the [Cisco CSR 1000V Series Cloud Services Router Software Configuration Guide](#).

For information on general software features that are also available on the Cisco CSR 1000V Series router, see the [Cisco IOS XE technology guide](#) for that specific software feature.

## Revision History

The Revision History records technical changes to this document. The table shows the Cisco IOS XE software release number, the date of the change, and a brief summary of the change

Release	Date	Change Summary
Cisco IOS XE Release 3.11S	November 21, 2013	First release.
Cisco IOS XE Release 3.11S	March 26, 2014	Second release, adding support for Hourly-Billed Amazon Machine Images (AMIs).
Cisco IOS XE Release 3.13S	September 15, 2014	Third release, adding support for 1-Click Launch and changes for Cisco IOS XE 3.13S licenses.
Cisco IOS XE Release 3.14S	November, 2014	Updated AMI options.
Cisco IOS XE Release 3.16S	August, 2015	Updated ios-config options.

Release	Date	Change Summary
Cisco IOS XE Denali 16.3.1	August, 2016	Updated sections such as launching the CSR AMI using the 1-Click Launch and launching the CSR AMI using the Manual Launch.

## Related Documentation

For further information about deploying Cisco CSR 1000v using High Availability on AWS, see: [CSR1000v HA Redundancy Deployment Guide on Amazon AWS](#).

For further information about the Cisco CSR 1000v, refer to the following documentation.

- [Cisco CSR 1000v Series Cloud Services Router Software Configuration Guide](#)
- [Cisco CSR 1000v Series Roadmaps](#)
- [Cisco CSR 1000v Series Cloud Services Router Release Notes](#)
- [Cisco CSR 1000v Series Cloud Services Router Software Configuration Guide](#)
- [Cisco CSR 1000v Series Cloud Services Router REST API Management Reference Guide](#)

For information about software features, see the [CSR 1000v configuration guides](#).

For information on commands, see the: [Cisco IOS XE Software Command References](#).

## Document Conventions

This documentation uses the following conventions:

Convention	Description
<b>^</b> or <b>Ctrl</b>	The <b>^</b> and <b>Ctrl</b> symbols represent the Control key. For example, the key combination <b>^D</b> or <b>Ctrl-D</b> means hold down the <b>Control</b> key while you press the <b>D</b> key. Keys are indicated in capital letters but are not case sensitive.
<i>string</i>	A string is a nonquoted set of characters shown in italics. For example, when setting an SNMP community string to public, do not use quotation marks around the string or the string will include the quotation marks.

Command syntax descriptions use the following conventions:

Convention	Description
<b>bold</b>	Bold text indicates commands and keywords that you enter exactly as shown.
<i>italics</i>	Italic text indicates arguments for which you supply values.
[x]	Square brackets enclose an optional element (keyword or argument).
	A vertical line indicates a choice within an optional or required set of keywords or arguments.

Convention	Description
[x   y]	Square brackets enclosing keywords or arguments separated by a vertical line indicate an optional choice.
{x   y}	Braces enclosing keywords or arguments separated by a vertical line indicate a required choice.
[x {y   z}]	Braces and a vertical line within square brackets indicate a required choice within an optional element.

Examples use the following conventions:

Convention	Description
screen	Examples of information displayed on the screen are set in Courier font.
<b>bold screen</b>	Examples of text that you must enter are set in Courier bold font.
< >	Angle brackets enclose text that is not printed to the screen, such as passwords.
!	An exclamation point at the beginning of a line indicates a comment line. (Exclamation points are also displayed by the Cisco IOS XE software for certain processes.)
[ ]	Square brackets enclose default responses to system prompts.

The following conventions are used to attract the attention of the reader:




---

**Note** Means *reader take note*. Notes contain helpful suggestions or references to materials that may not be contained in this manual.

---




---

**Caution** Means *reader be careful*. In this situation, you might do something that could result in equipment damage or loss of data.

---

## Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

<http://www.cisco.com/c/en/us/td/docs/general/whatsnew/whatsnew.html>

Subscribe to the *What's New in Cisco Product Documentation* as a Really Simple Syndication (RSS) feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service and Cisco currently supports RSS version 2.0.

