



## Traffic Steering by Dropping Invalid Paths

If the SR-TE policy has no valid paths defined, the paths are dropped, and the traffic that is being steered through the policy falls back to the default (unconstrained IGP) forwarding path. Also, when an SR-TE policy carrying best-effort traffic fails, the traffic is re-routed and which in turn impacts the SLA(service level agreements) for premium traffic.

To solve the issue of SR-TE policy failing, the traffic in the data plane is dropped but kept in the control plane. Therefore, other segment routing policies, which could be potentially be carrying premium traffic, are not impacted.

- [Feature Information for Traffic Steering by Dropping Invalid Paths, on page 1](#)
- [How to Configure Traffic Steering by Dropping Invalid Paths , on page 2](#)

## Feature Information for Traffic Steering by Dropping Invalid Paths

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

**Table 1: Feature Information for Performance Measurement for Traffic Engineering**

Feature Name	Releases	Feature Information
Traffic Steering By Dropping Invalid Paths	Cisco IOS XE Bengaluru 17.5	If the SR-TE policy fails, the traffic in the data plane is dropped but kept in the control plane. Therefore, other segment routing policies, potentially carrying premium traffic, are not impacted.

## Overview

If the SR-TE policy has no valid paths defined, the paths are dropped, and the traffic that is being steered through the policy falls back to the default (unconstrained IGP) forwarding path. Also, when an SR-TE policy carrying best-effort traffic fails, the traffic is re-routed and which in turn impacts the SLA(service level agreements) for premium traffic.

To solve the issue of SR-TE policy failing, the traffic in the data plane is dropped but kept in the control plane. Therefore, other segment routing policies, which could be potentially be carrying premium traffic, are not impacted

This feature can be configured by using the **path-invalidation drop** command.

## Before You Begin

This feature should not be enabled if you have already configured segment routing BFD or performance liveness monitoring. If this feature is enabled, segment routing BFD or performance liveness notification is ignored. In such a scenario, no logging or syslog notification is generated for segment routing BFD or performance liveness events.

Note that if the SR-TE policy is in Down state and this feature is configured, the state of the SR-TE policy is not affected.

## Benefits

- Configuring this feature ensures that other segment routing policies that are configured to route premium traffic are not impacted thereby ensuring that SLA guidelines are not affected.

## Restrictions

- This feature cannot be enabled in combination with segment routing BFD or performance monitoring liveness check.

# How to Configure Traffic Steering by Dropping Invalid Paths

## Configuring for a PCC Profile

This configuration results in a PCE-initiated policy having the path-invalidation functionality enabled for a policy instantiated with a profile ID matching the configured value:

```
segment-routing traffic-eng
  pcc
  profile <number >
  steering
  path-invalidation drop
```

## Configuring for Static Policies

This configuration results in a configuring path validation drop for a segment routing static policy:

```
segment-routing traffic-eng
  policy <name>
    steering
      path-invalidation drop
```

## Configuring for On-Demand Next Hop for SR-TE Policies

This configuration results in a configuring path validation drop for an on-demand segment routing policy for a specific color:

```
segment-routing traffic-eng
  on-demand color <>
    steering
      path-invalidation drop
```

## Show Commands

Use the **show segment-routing traffic-eng policy name** command to view path invalidation event types and invalidation drop status.

```
device#show segment-routing traffic-eng policy name foo detail
Name: foo (Color: 10 End-point: 192.168.0.8)
Owners : CLI
Status:
  Admin: up, Operational: up for 00:00:08 (since 09-17 10:19:54.536)
Candidate-paths:
  Preference 100 (CLI):
    Dynamic (active)
      Status: Invalidation drop
      Metric Type: TE
Attributes:
  Binding SID: 20
  Allocation mode: dynamic
  State: Programmed
Autoroute:
  Include all
Tunnel ID: 65536 (Interface Handle: 0x9)
Per owner configs:
  CLI
  Binding SID: dynamic
Stats:
  5 minute output rate 0 bits/sec, 0 packets/sec
  Packets: 0 Bytes: 0

Event history:
Timestamp                Client          Event type          Context: Value
-----                -
09-17 10:19:54.536      CLI            Policy created      Name: CLI
09-17 10:19:54.537      CLI            Path Invalidation   Drop: Configured
09-17 10:19:58.744      CLI            Set colour          Colour: 10
09-17 10:19:58.744      CLI            Set end point       End-point: 192.168.0.8

09-17 10:19:58.752      CLI            Set dynamic         Path option: dynamic

09-17 10:19:58.753      CLI            BSID allocated      FWD: label 20
09-17 10:19:58.755      FH Resolution    Policy state UP     Status: PATH RESOLVED
```

```
CP: 100
  09-17 10:19:58.760  FH Resolution      REOPT triggered      Status: REOPTIMIZED
CP: 100
  09-17 10:19:58.780  CLI                Path Invalidation   Drop: Unconfigured
  09-17 10:19:59.537  CLI                Path Invalidation   Drop: Set
  09-17 10:20:00.853  FH Resolution      Path Invalidation   Status: Drop
  09-17 10:20:01.853  FH Resolution      Path Invalidation   Status: No Drop
  09-17 10:20:02.853  FH Resolution      Path Invalidation   Status: Drop
```