



Release Notes for Cisco NCS 540 Series Routers, Cisco IOS XR Release 26.2.2

Contents

Cisco NCS 540 Series Routers, Release 26.2.2 3

New software features..... 3

New hardware 3

Changes in behavior 3

Open issues..... 3

Known issues..... 3

Compatibility..... 3

Supported software packages 4

Related resources..... 8

Legal information 9

Cisco NCS 540 Series Routers, Release 26.2.2

There are no new software features or hardware introduced in this release.

For more details on the Cisco IOS XR release model and associated support, see [Software Lifecycle Support Statement - IOS XR](#).

New software features

There are no new software features introduced in this release.

New hardware

There is no new hardware introduced in this release.

Changes in behavior

There are no changes in behavior in this release.

Open issues

Table 1. Open issues for Cisco NCS 540 Series Routers, Release 26.2.2

Bug ID	Description
CSCwv44897	IP multicast packet's DSCP is incorrectly changed by "set mpls experimental imposition" action, despite the absence of an MPLS encapsulation.

Known issues

There are no known issues in this release.

Compatibility

Compatibility Matrix for EPNM and Crosswork with Cisco IOS XR Software

The compatibility matrix lists the version of EPNM and Crosswork that are supported with Cisco IOS XR Release software in this release.

Table 2. Compatibility Matrix for Cisco NCS 540 Series Routers, Release 26.2.2

Cisco IOS XR	Crosswork	EPNM
Release 26.2.2	Cisco Crosswork Network Controller 8.0	Evolved Programmable Network Manager 8.1.4

System requirements

Use the **show hw-module fpd** command in EXEC and Admin mode to view the hardware components with their current FPD version and status. The status of the hardware must be CURRENT; Running and Programmed version must be the same. You can also use the **show fpd package** command in Admin mode to check the fpd versions.

Software Version

To verify the software version running on the router, use **show version** command in the EXEC mode.

```
RP/0/RP0/CPU0#show version
Thu Sep 10 09:33:24.600 UTC
Cisco IOS XR Software, Version 26.2.2
Copyright (c) 2013-2026 by Cisco Systems, Inc.
```

Build Information:

```
Built By      : swtools
Built On     : Wed Sep  9 20:09:30 PDT 2026
Built Host   : iox-lnx-055
Workspace    : /auto/srcarchive13/prod/26.2.2/ncs540/ws
Version      : 26.2.2
Location     : /opt/cisco/XR/packages/
Label       : 26.2.2-iso
```

```
cisco NCS-540 () processor
System uptime is 30 minutes
```

Supported software packages

The following tables list the supported base images and optional packages and their corresponding file names.

Visit the [Cisco Software Download page](#) to download the Cisco IOS XR software images.

Table 3. Release 26.2.2 software for N540-24Z8Q2C-SYS, N540-ACC-SYS, and N540X-ACC-SYS

Package	Filename	Description
Base image		
IOS XR Base Image	ncs540-mini-x-26.2.2.iso	IOS XR mandatory base image.
USB Boot Package	ncs540-usb_boot-26.2.2.zip	Package required to perform USB Boot. Includes the same packages as the base image.
Optional packages not included in the base image		
IOS XR Manageability	ncs540-mgbl-1.0.0.0-r2622.x86_64.rpm	Supports Extensible Markup Language (XML) Parser, Telemetry, Netconf, gRPC and HTTP server
IOS XR MPLS	ncs540-mpls-1.0.0.0-r2622.x86_64.rpm ncs540-mpls-te-rsvp-1.0.0.0-r2622.x86_64.rpm	Supports MPLS and MPLS Traffic Engineering (MPLS-TE)
IOS XR Security	ncs540-k9sec-1.0.0.0-r2622.x86_64.rpm	Supports MACsec and 802.1X
IOS XR ISIS	ncs540-isis-1.0.0.0-r2622.x86_64.rpm	Supports ISIS

Package	Filename	Description
IOS XR OSPF	ncs540-ospf-1.0.0.0-r2622.x86_64.rpm	Supports OSPF
IOS XR Lawful Intercept	ncs540-li-1.0.0.0-r2622.x86_64.rpm	Supports Lawful Intercept (LI)
IOS XR Multicast	ncs540-mcast-1.0.0.0-r2622.x86_64.rpm	Supports Multicast
IOS XR EIGRP	ncs540-eigrp-1.0.0.0-r2622.x86_64.rpm	Supports EIGRP
IOS XR LI-CTRL	ncs540-lictrl-1.0.0.0-r2622.x86_64.rpm	Supports LI-CTRL

Table 4. Release 26.2.2 Software for N540-24Q8L2DD-SYS, N540-24Q2C2DD-SYS, N540X-16Z4G8Q2C-A/D, N540-28Z4C-SYS-A/D, N540X-12Z16G-SYS-A/D, N540-12Z20G-SYS-A/D, N540-FH-CSR-SYS, N540X-16Z8Q2C-D, and N540-FH-AGG-SYS

Package	Filename	Description
Base Image		
IOS XR Base Image	ncs540l-x64-26.2.2.iso	IOS XR base image with mandatory packages. The base ISO image also includes the following optional packages: - xr-bgp - xr-cdp - xr-eigrp - xr-ipsla - xr-is-is - xr-k9sec - xr-lictrl - xr-ldp - xr-mcast - xr-mpls-oam - xr-netflow - xr-ospf - xr-perf-meas - xr-perfmgmt - xr-rip - xr-telnet - xr-track These optional packages are also included in NCS540l-iosxr-26.2.2.tar.
USB Boot Package	ncs540l-usb_boot-26.2.2.zip	Package required to perform USB Boot. Includes the same packages as the base image.
Optional packages not included in the base image		

Package	Filename	Description
IOS XR Telnet (xr-telnet)	NCS540I-iosxr-26.2.2.tar	Supports Telnet
IOS XR EIGRP (xr-eigrp)	NCS540I-iosxr-26.2.2.tar	Supports EIGRP
IOS XR CDP (xr-cdp)	NCS540I-iosxr-26.2.2.tar	Supports CDP
IOS XR k9sec (xr-k9sec)	NCS540I-k9sec-rpms.26.2.2.tar	Supports 802.1X
IOS XR RIP (xr-rip)	NCS540I-iosxr-26.2.2.tar	Supports RIP

Table 5. Release 26.2.2 Software for N540X-4Z14G2Q-A/D, N540X-8Z16G-SYS-A/D, N540-6Z14S-SYS-D, N540-6Z18G-SYS-A/D, N540X-6Z18G-SYS-A/D, and N540X-6Z6G-SYS

Package	Filename	Description
Base image		

Package	Filename	Description
IOS XR Base Image	ncs540l-aarch64-26.2.2.iso	IOS XR base image with mandatory packages. The ISO image also includes the following optional packages: - xr-bgp - xr-cdp - xr-eigrp - xr-ipsla - xr-is-is - xr-k9sec - xr-lictrl - xr-ldp - xr-mcast - xr-mpls-oam - xr-ncs540l-mcast - xr-ncs540l-netflow - xr-netflow - xr-ospf - xr-perf-meas - xr-perfmgmt - xr-rip - xr-telnet - xr-track These optional packages are also included in NCS540l aarch64 iosxr optional rpms-26.2.2.tar.
USB Boot Package	ncs540l-aarch64-usb_boot-26.2.2.zip	Package required to perform USB Boot. Includes the same packages as the base image.
Optional packages not included in the base image		
Package	Filename	Description
IOS XR Telnet (xr-telnet)	NCS540l-aarch64-iosxr-optional-rpms-26.2.2.tar	Supports Telnet
IOS XR EIGRP (xr-eigrp)	NCS540l-aarch64-iosxr-optional-rpms-26.2.2.tar	Supports EIGRP
IOS XR CDP (xr-cdp)	NCS540l-aarch64-iosxr-optional-rpms-26.2.2.tar	Supports CDP

Package	Filename	Description
IOS XR k9sec (xr-k9sec)	NCS540I-aarch64-k9sec-rpms.26.2.2.tar	Supports 802.1X
IOS XR RIP (xr-rip)	NCS540I-aarch64-iosxr-optional-rpms-26.2.2.tar	Supports RIP

Related resources

Table 6. Related resources

Document	Description
Ask AI about this product	Provides access to Cisco product documentation for checking feature support details.
Cisco feature finder	An interactive tool that assists in locating features introduced across Cisco IOS XR releases and platforms.
Cisco IOS XR error messages	Search by release number, error strings, or compare release numbers to view a detailed repository of error messages and descriptions.
Cisco IOS XR MIBs	Select the MIB of your choice from a drop-down to explore an extensive repository of MIB information.
Cisco NCS 540 documentation	CCO Documentation for Cisco NCS 540 Series Routers
Feature deprecation and removal details	Outlines the features currently supported by each operating system.
Feature deprecation phasing out insecure capabilities	Provides a list of insecure features and protocols that are scheduled for systematic deprecation and eventual removal from specified Cisco products.
Feature removal and suggested alternatives	Details the reasons why certain features or protocols are deemed insecure and offers secure alternatives when available.
Smart licensing	Information about Smart Licensing Using Policy solutions and their deployment on IOS XR Routers.
Transceiver Module Group (TMG) compatibility matrix	Search by product family, product ID, data rate, reach, cable type, or form factor to determine the transceivers that Cisco hardware device supports.
YANG data models	A user-friendly reference designed to easily explore and understand the various data models supported in Cisco IOS XR platforms and releases.
Yang data models in Github	Repository containing the folders with yang data models introduced and enhanced in every IOS XR release.

Legal information

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2026 Cisco Systems, Inc. All rights reserved.