



System Specifications

This appendix contains tables that list the specifications for the main components of the Cisco NCS 4016 chassis.

- [Chassis Specifications, on page 1](#)
- [Power Specifications, on page 2](#)
- [Environmental Specifications, on page 3](#)
- [Regulatory, Compliance, and Safety Specifications, on page 4](#)

Chassis Specifications

This appendix contains tables that list the specifications for the main components of the Cisco NCS 4016 chassis.

Table 1: Cisco NCS 4016 Chassis Specifications

| | |
|------------------------------------|--|
| Supported Cards and Modules | <ul style="list-style-type: none"> • Upto sixteen lincards • Four fabric cards • Two route processor cards • Two fan trays |
| Chassis Dimensions | |
| Height | 42 in. (106.68 cm) as shipped |
| Width | 19.5 in. (49.53 cm) with front door 18.5 in. (47 cm) without front door |
| Depth | AC version: 19.05 in. (48.39 cm) with front door DC version: 17.73 in. (45.03 cm) with front door |
| Aisle spacing | To install chassis (front): 48 in. (122 cm) To service FRUs (front): 31.7 in. (80.5 cm) To service FRUs (rear): 14.0 in. (35.6 cm) |
| Weights | |

| | |
|---|--------------------------------|
| Chassis as shipped | 250 lb (113.5 kg) |
| Chassis in shipping crate with pallet | 319 lb (145 kg) |
| Chassis, fully loaded with power, fan trays, cards, and cosmetics | 412 lb (187 kg) |
| Floor Loading | |
| Chassis in rack footprint(floor contact area) | Chassis: 2.5 sq ft (0.23 sq m) |
| Maximum floor loading | 263 lb/sq ft |
| Chassis Cooling | Two fan trays |
| Chassis airflow | 45,300 liters per minute |
| DC power system airflow | 6796 liters per minute |
| AC power system airflow | 5097 liters per minute |

Power Specifications

Table 2: Cisco NCS 4016 Chassis Power Specifications

| | |
|-----------------------------|--|
| Power Specifications | |
| Power Trays | Either two AC or two DC power trays (cannot mix AC and DC power trays) |
| DC power tray | Up to four DC PMs per tray |
| AC power tray | Up to four AC PMs per tray |
| Power Redundancy | |
| DC | Up to 8 power modules can be installed, and only 7 are needed to be active at any time. This allows support for 7+1 power redundancy and A and B battery plant dual feeds redundancy. |
| AC | Up to 8 power modules can be installed, and only 4 are needed to be active at any time. This allows support for 4+4 power redundancy by using two independent AC power sources (4 feeds each). |
| DC Input | |
| Nominal input voltage | -48 VDC or -60 VDC (tolerance range: -40 to -72 VDC) |
| Input current | 50 A max at -48 VDC 40 A max at -60 VDC 60 A at -40 VDC (maximum) |
| AC Input | Single-phase |
| Nominal input voltage | 200 to 240 VAC (range 180 to 264 VAC) |

| | |
|-----------------------------|--|
| Power Specifications | |
| Nominal line frequency | 50/60 Hz (range 47 to 63 Hz) |
| Recommended AC service | 30-A (North America) dedicated branch circuit 30-A (International) dedicated branch circuit |
| AC Power Cord Length | 167 in. (4.25 m) |

Environmental Specifications

Table 3: Cisco NCS 4016 Chassis Environmental Specifications

| | |
|------------------------------------|--|
| Temperature | Operating, nominal: 41 to 104°F (5° to 40°C) Operating, short-term: 23 to 122°F (−5° to 50°C) ¹ Nonoperating: −40 to 158°F (−40° to 70°C) |
| Humidity | Operating, nominal: 5 to 85%, noncondensing Operating, short-term: 5 to 90%, noncondensing Nonoperating: 5 to 93%, noncondensing |
| Altitude | Operating: −200 to 13,100 ft (−61 to 4000 m) at 104°F (40°C) Nonoperating: Up to 16,000 ft (4877 m) at −13°F (−25°C), short-term |
| Chassis airflow | Up to 70,792 liters per minute |
| Power system airflow | Up to 6800 liters per minute |
| Air exhaust temperature | 95°F (35°C)—at room temperatures of 77 to 84°F (25 to 29°C) 140°F (50°C)—at room temperatures of 95 to 102°F (35 to 39°C) 158°F (60°C)—maximum exhaust temperature on a fully loaded system during worst-case operating conditions (50°C and 6000 ft altitude) Note Air temperature rise is 68°F (20°C) on a fully loaded system with fans running at maximum speed. |
| Air velocity (at exhaust) | 500 ft/min (2.55m/s) under typical conditions 27°C 1000 ft/min (5.1m/s) at maximum speed Note Software controls the speed of the fans based on measurements from the chassis thermal sensors. |
| Sound power level(AC and DC power) | Fan speed 5000 RPM, temperature 80°F (27°C):76.1 dB—modular configuration power |
| Shock and vibration | Designed and tested to meet the NEBS shock and vibration standards defined in GR-63 Issue 4 2012. |

¹ Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. This refers to a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period.

Regulatory, Compliance, and Safety Specifications

For information about the regulatory, compliance, and safety standards to which the Cisco NCS 4016 chassis conforms, see Regulatory Compliance and Safety Information for the Cisco Network Convergence System 4000 Series.