System Portal Commands

system portal access

To enable or disable the Cisco Enterprise NFVIS portal access, use the **system portal access** command in global configuration mode.

system portal access {**enable** | **disable**}

Syntax Description	enable	Enables the portal access.
	disable	Disables the portal access.

Command Default Portal access is enabled by default.

Command Modes Global configuration (config)

Command History

Release	Modification
3.5.1	This command was introduced.

Example

The following example shows how to disable the portal access:

```
nfvis(config)# system portal access disable
nfvis(config)# commit
nfvis(config)# end
```

show system portal status

To verify the Cisco Enterprise NFVIS portal access status, use the **show system portal status**command in privileged EXEC mode.

show system portal status

Syntax Description	This command has no arguments or keywords.

Command Default	None

Command Modes	Privileged EXEC (#)

Command History	**Release**	**Modification**
	3.5.1	This command was introduced.

Example

The following is a sample output of the **show system portal status** command:

```
nfvis# show system portal status
system portal status "access disabled"
```

show running-config system portal access

To display the running configuration for the Cisco Enterprise NFVIS portal access, use the **show running-config system portal access** command in privileged EXEC mode.

show running-config system portal access

Syntax Description	This command has no arguments or keywords.

Command Default	None

Command Modes	Privileged EXEC (#)

Command History

Release	Modification
3.5.1	This command was introduced.

Example

```
nfvis# show running-config system portal access
system portal access enabled
```