



## Using Policy Groups for SD-Routing Devices

**First Published:** 2024-04-30

**Last Modified:** 2024-04-30

### **Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
<http://www.cisco.com>  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883





# CONTENTS

---

## CHAPTER 1

### **Policy Groups 1**

- Policy Groups 1
- Information About Policy Groups 1
  - Overview of Policy Groups 1
  - Overview of Policy Group Workflows 2
  - Benefits of Policy Groups 2
- Restrictions for Policy Groups 2
- Configure a Group of Interest for Policy Group 2
- Configure Policy Group 8

---

## CHAPTER 2

### **Security Policy Using Policy Groups 9**

- Security Policy Using Policy Groups 9
- Information About Security Policy 10
- Enable RBAC for Security Policy 10
- Restrictions for Security Policy 11
- Configure a Security Policy Using a Policy Group 11
- Configure a Group of Interest for a Security Policy 11
- Configure Application Priority and SLA 22
- Configure NGFW 24
- Configure a Secure Internet Gateway 26
- Configure Secure Service Edge 31
- Configure DNS Security 31





# CHAPTER 1

## Policy Groups

- [Policy Groups, on page 1](#)
- [Information About Policy Groups, on page 1](#)
- [Restrictions for Policy Groups, on page 2](#)
- [Configure a Group of Interest for Policy Group, on page 2](#)
- [Configure Policy Group, on page 8](#)

## Policy Groups

*Table 1: Feature History*

Feature Name	Release Information	Description
Policy Groups	Cisco IOS XE 26.1.1a	The information in this document is carried forward from Cisco IOS XE Release 17.18.x, with no new features introduced in Cisco IOS XE Release 26.1. This release maintains the existing functionality and enhancements from Cisco IOS XE Release 17.18.x without adding any additional capabilities.

## Information About Policy Groups

Policy groups simplify the experience of configuring and deploying various policies on SD-Routing devices. Policy groups are a collection of different policies that you can configure through workflows and associate with and deploy on different SD-Routing devices.

## Overview of Policy Groups

Policy Groups provide a simple, reusable, and structured approach for configuring policies and policy objects in SD-Routing devices.

Policy groups are a collection of various policies and policy parameters that you can configure quickly through a simplified workflow. Policy groups allows you to configure the basic and necessary policies with defaults to get your systems up and running. The more advanced user can switch to the **Advanced** layout to take complete control and configure detailed policy parameters such as service-level agreement (SLA) class,

Quality of Service (QoS) Maps, and Match-Action parameters pertaining to the traffic policy. After creating a policy group, you can associate it with one or more sites or a single device at the site in the network and deploy it on devices managed by configuration groups.

After you've configured a policy group, you can deploy it by using the [Deploy Policy Group Workflow](#).

## Overview of Policy Group Workflows

The policy group workflow guides you in creating a policy group for one or more sites or a single device at the site in the network that is managed by configuration groups in SD-Routing devices. The workflow provides you with an improved configuration and troubleshooting experience. The workflow has the following features:

- You can review the various configuration values on a single page within the workflow.
- You can easily identify and fix incorrect values that appear highlighted in red. In addition, an asterisk that is adjacent to a field name helps you identify the mandatory values within the workflow.

### Deploy Policy Group Workflow

You can access the workflow by choosing **Workflows > Deploy Policy Group** menu in Cisco SD-WAN Manager.

The **Deploy Policy Group** workflow enables you to associate devices with a previously created policy group and deploy the policy group to the selected devices. You can review device configurations to further add Site IDs and other variables that must be provided as part of a policy group before deploying the policy group.

## Benefits of Policy Groups

- Simplified user experience through an intuitive UI that allows you to quickly configure the basic policies that are required to get your deployments up and running.
- Option to edit policy groups based on the changing needs of your network and save the configuration. You can choose to deploy these changes only when needed - during maintenance windows or in off-production hours.
- A **Preview CLI** option to preview the difference in configuration for relevant devices such as Cisco SD-WAN device and SD-Routing device in one location.
- Workflows to deploy policy groups.

## Restrictions for Policy Groups

- You cannot deploy policy groups to devices that are not already managed by a configurations group.

## Configure a Group of Interest for Policy Group

Group of interest provides a list of related policy objects that you can configure and call in the match or action components of a policy. Click **Group of Interest** to create new objects for the policy group as described in the following sections:

### Application List

1. Click **Application List**.
2. Click **Add Application List**.
3. From the **Application/Application family list** drop-down, choose the required applications or application families.
4. Click **Save**.

A few application lists are preconfigured. You cannot edit or delete these lists.

**Microsoft\_Apps**: Includes Microsoft applications, such as Excel, Skype, and Xbox. To display a full list of Microsoft applications, click the list in the **Entries** column.

**Google\_Apps**: Includes Google applications, such as Gmail, Google Maps, and YouTube. To display a full list of Google applications, click the list in the **Entries** column.

### App Probe Class

1. Click **Add App Probe Class**.
2. In the **App Probe** dialog box, specify the following:

Field	Description
<b>Probe Class Name</b>	Enter a name for the probe class.
<b>Forwarding Class</b>	Choose the forwarding class from the drop-down list.
<b>Color</b>	Choose the color from the drop-down list.
<b>DSCP</b>	Enter the DSCP value.

3. You can add more entries if needed by clicking on **+ icon**.
4. Click **Save**.

To configure multiple colors in a single list, you can choose multiple colors from the drop-down list.

### Color

1. Click **Color**.
2. Click **New Color List** and specify the following:

Field	Description
<b>Color List Name</b>	Enter a name for the list.
<b>Select Color</b>	Choose one or more color lists types from the drop-down list.

3. Click **Add**.

To configure multiple colors in a single list, you can choose multiple colors from the drop-down list.

### Community List

A community list is used to create groups of communities to use in a match clause of a route map. A community list can be used to control which routes are accepted, preferred, distributed, or advertised. You can also use a community list to set, append, or modify the communities of a route.

1. Click **Community List**.
2. Click **Add Community List** and specify the following:

Field	Description
<b>Community List Name</b>	Enter a name of the community list.
<b>Add Community</b>	<p>Enter one or more communities separated by commas.</p> <ul style="list-style-type: none"> <li>• <b>aa:nn</b>: Autonomous System (AS) number and network number. Each number is a 2-byte value with a range from 1 to 65535. For example, 65526.</li> <li>• <b>internet</b>: Routes in this community are advertised to the internet community. This community comprises all BGP-speaking networking devices.</li> <li>• <b>local-as</b>: Routes in this community are not advertised outside the local AS number.</li> <li>• <b>no-advertise</b>: Attaches the NO_ADVERTISE community to routes. Routes in this community are not advertised to other BGP peers.</li> <li>• <b>no-export</b>: Attaches the NO_EXPORT community to routes. Routes in this community are not advertised outside the local AS or outside a BGP confederation boundary. To configure multiple BGP communities in a single list, include multiple <b>community</b> options, specifying one community in each option.</li> </ul>

3. Click **Save**.

### Data Prefix

1. Click **Data Prefix**.
2. Click **Add Data Prefix**.
3. In the **Data Prefix list** dialog box, specify the following:

Field	Description
<b>Data Prefix List Name</b>	Enter a name for the data prefix list.
<b>Add Data Prefix</b>	Enter one or more data prefixes separated by commas.

4. Click **Save**.

**Data Prefix IPv6**

1. Click **Data Prefix IPv6**.
2. Click **Add Data Prefix IPv6**.
3. In the **Data Prefix List** dialog box, specify the following:

Field	Description
<b>Data Prefix List Name</b>	Enter a name for the IPv6 data prefix list.
<b>Add Data Prefix</b>	Enter one or more IPv6 data prefixes separated by commas.

4. Click **Save**.

**Expanded Community List**

1. Click **Expanded Community List**.
2. Click **Add Expanded Community List** and specify the following:

Field	Description
<b>Community List Name</b>	Enter a name for the community list.
<b>Add Community</b>	Specify details of the expanded community list that is used to filter communities using a regular expression.

**Forwarding Class**

1. Click **Add Forwarding Class** and specify the following:

Field	Description
<b>Forwarding Class</b>	Enter a name for the forwarding class.
<b>Queue</b>	Choose a value for the queue from the drop-down list.

2. Click **Save**.

**Policer**

1. Click **Policer**.
2. Click **Add Policer** and specify the following:

Field	Description
<b>Policer List Name</b>	Enter a name for the policer list.
<b>Burst (bytes)</b>	Enter the maximum traffic burst size. The range is from 15,000 to 10,000,000 bytes.

Field	Description
<b>Exceed</b>	Choose the action to take when the burst size or traffic rate is exceeded. The options are: <ul style="list-style-type: none"> <li>• Drop: sets the packet loss priority (PLP) to low</li> <li>• Remark: sets the packet loss priority (PLP) to high</li> </ul>
<b>Rate</b>	Enter the maximum traffic rate, a value from 8 through 10 <sup>11</sup> bits per second (bps).

3. Click **Save**.

### Preferred Color Group

1. Click **Add Preferred Color Group**.
2. In the **Preferred Color Group Name** field, enter a name for the preferred color group.
3. Choose the color preference and path preference for the primary, secondary, and tertiary colors from the **Color Preference** and the **Path Preference** drop-down lists.

Field	Description
<b>Preferred Color Group Name</b>	Enter a name for the preferred color group.
<b>Color Preference</b>	Choose the color preference from the drop-down list. You can choose multiple colors.
<b>Path Preference</b>	Choose the path preference from the drop-down list. The options are: <ul style="list-style-type: none"> <li>• Direct Path</li> <li>• Multi Hop Path</li> <li>• All Paths</li> </ul>

4. Click **Save**.

### Prefix List

1. Click **Prefix List**.
2. Click **Add Prefix List** and specify the following:

Field	Description
<b>Prefix List Name</b>	Enter a name for the IPv4 prefix list.
<b>Add Prefix</b>	Enter one or more IPv4 prefixes separated by commas.

3. Click **Save**.

**Prefix List IPv6**

1. Click **Prefix List IPv6**.
2. Click **Add Prefix List** and specify the following:

Field	Description
<b>Prefix List Name</b>	Enter a name for the IPv6 prefix list.
<b>Add Prefix</b>	Enter one or more IPv6 prefixes separated by commas.

3. Click **Save**.

**SLA Class**

1. Click **SLA Class**.
2. Click **Add SLA Class** and specify the following:

Field	Description
<b>SLA Class List Name</b>	Enter a name of the SLA class list.
<b>Loss (%)</b>	Enter the maximum packet loss on the connection, a value from 0 through 100.
<b>Latency</b>	Enter the maximum packet latency on the connection, a value from 1 through 1,000 milliseconds.
<b>Jitter</b>	Enter the maximum jitter on the connection, a value from 1 through 1,000 milliseconds.
<b>App Probe Class</b>	Choose the app probe class from the drop-down list or click <b>Create New</b> to create one.
<b>Fallback Best Tunnel</b>	Choose this option to enable the best tunnel criteria.

3. Click **Save**.

**TLOC List**

1. Click **TLOC List**.
2. Click **Add TLOC List** and specify the following:

Field	Description
<b>List Name</b>	Enter a name for the TLOC list.
<b>TLOC IP</b>	Specify the IP address for TLOC.
<b>Color</b>	Choose the color from the drop-down list.

Field	Description
<b>Encapsulation</b>	Choose the value from the drop-down list. The options are: <ul style="list-style-type: none"> <li>• IPSec</li> <li>• GRE</li> </ul>
<b>Preference</b>	Choose a preference to associate with the TLOC. The range is 0 to 4294967295.

3. Click **Save**.

## Configure Policy Group

To create a new policy group, follow the steps below and configure the values in the following table. If you have already created a policy group, click the policy group from the list of available policy groups to edit.

1. From the Cisco SD-WAN Manager menu, choose **Configuration > Policy Groups > Add Policy Group**.
2. Enter a **Policy Group Name** and provide a description (optional).
3. Select **SD-Routing** as the **Solution** from the drop-down list.
4. Click **Create** and configure the following:

*Table 2: Policy group parameters*

Field	Description
<b>Policy Group Name</b>	Specify the name of the policy group.
<b>Description</b>	Provide a description for the policy group. It can contain up to 2048 characters including spaces.
<b>Policy</b>	
<b>NGFW</b>	Choose an NGFW policy from the drop-downlist. Click <b>Create New</b> to create a new policy.
<b>Secure Internet Gateway (SIG)/ Secure Service Edge (SSE)</b>	Configure SIG or SSE tunnels before you apply a data policy for redirecting application traffic. Select an SSE or SIG policy from the drop-down list. Click <b>Create New</b> to create a new policy.

5. Click **Save** to save your configuration.
6. Click **Deploy** to select sites and deploy the policy group.



## CHAPTER 2

# Security Policy Using Policy Groups

- [Security Policy Using Policy Groups, on page 9](#)
- [Information About Security Policy, on page 10](#)
- [Enable RBAC for Security Policy, on page 10](#)
- [Restrictions for Security Policy, on page 11](#)
- [Configure a Security Policy Using a Policy Group, on page 11](#)
- [Configure a Group of Interest for a Security Policy, on page 11](#)
- [Configure Application Priority and SLA, on page 22](#)
- [Configure NGFW, on page 24](#)
- [Configure a Secure Internet Gateway, on page 26](#)
- [Configure Secure Service Edge, on page 31](#)
- [Configure DNS Security, on page 31](#)

## Security Policy Using Policy Groups

*Table 3: Feature History*

Feature Name	Release Information	Description
Security Policy Using Policy Groups	Cisco IOS XE 17.14.1a	<p>This feature provides a simple, reusable, and structured approach for configuring security policies . You can create a security policy, that is, a logical grouping of policies that is applied to one or more sites or a single device at a site in the network.</p> <p>The Deploy Policy Group workflow provides a guided method to choose previously created policy groups and deploy them to sites or a single device at a site that is managed by configuration groups.</p>

# Information About Security Policy

Configuring security policies using policy groups simplifies the experience of configuring and deploying policies on SD-Routing devices. Use a workflow to configure policies and associate them with devices in the network.

The **Policy Groups** page includes the following:

- **Policy Group**
- **Application Priority and SLA**
- **NGFW**
- **Secure Internet Gateway**
- **Secure Service Edge**
- **DNS Security Configuration**

# Enable RBAC for Security Policy

To create a policy group and security feature profiles using configuration groups, role-based access control (RBAC) must provide read and write permissions on the following profiles to access each feature. Set the permissions of the user group to enable access to policy groups from **Configuration > Policy Groups**.

1. From the Cisco SD-WAN Manager menu, choose **Administration > Manage Users > User Groups**.
2. Click **Add User Group**.
3. Enter **User Group Name**.
4. Check a **Read** or **Write** check box for the **Policy Group**, **Device** and **Deploy** feature that you want to assign to a user group.
5. Check a **Read** or **Write** check box for the following features that you want to assign to a user group:
  - **Feature Profile > Embedded Security > Legacy Policy**
  - **Feature Profile > Embedded Security > NGFirewall**
  - **Feature Profile > Embedded Security > Policy**
  - **Feature Profile > Policy Object > Advanced Inspection Profile**

The **Advanced Inspection Profile** has the following subfeature profiles:

- **Advanced Malware Protection**
- **Intrusion Prevention**
- **SSL Decryption**
- **SSL Decryption Profile**
- **URL Filtering**

6. Click **Add**.

## Restrictions for Security Policy

Security policy does not support matching traffic using a custom application in a custom-defined application list.

## Configure a Security Policy Using a Policy Group

Using the Create Security Policy workflow, you can create a security policy, add sub-policy, add rules to existing sub-policies, and so on.

1. From the Cisco SD-WAN Manager menu, choose **Workflows > Workflow Library > Create Security Policy**. Alternatively, choose **Configuration > Policy Groups**.
2. Click **Embedded Security**.
3. On the **Embedded Security** page, click **Add Security Policy**. This launches the Security Policy workflow.
4. Enter **Policy Name** and **Description** and click **Next**.
5. On the **Select the optional Configuration Group to associate with the security policy** page, choose the configuration groups and click **Next**.
6. Click **Add Sub-Policy**.
7. Click **Submit**. You can view the new security policy in the **Embedded Security** tab.

## Configure a Group of Interest for a Security Policy

1. From the Cisco SD-WAN Manager menu, choose **Configuration > Policy Groups > Objects and Profiles**.
2. Click the **Security Objects** tab. The list of security objects and profiles appears.

Use the following tables to configure a different group of lists for security policy:

### Application

Field	Description
<b>Application List Name</b>	Name of the application list.
<b>Applications</b>	Choose one or more application types from the drop-down list. For example, Third Party Control, ABC News, Microsoft Teams, and so on.  Choose one or more application family types from the drop-down list. For example, application-service, audio_video, authentication, behavioral, compression, database, encrypted, and so on.

**Data Prefix**

Field	Description
<b>Data Prefix List Name</b>	Name of the prefix list.
<b>Data Prefix</b>	The data prefix value.

**Data Prefix IPv6**

From Cisco IOS XE 17.18.2, you can configure an object group.

Field	Description
<b>Data Prefix List Name</b>	Name of the prefix list.
<b>Data Prefix</b>	The data prefix IPv6 value.

**Rule Set**

From Cisco IOS XE 17.18.2, you can configure an object group.

Field	Description
<b>Rule Set Name</b>	Name of the rule set.
<b>Type</b>	You can choose IPv6 or IPv4.

To configure rules within a rule set, see [Configure Firewall Policies for SD-Routing Devices](#).

**Object Group**

From Cisco IOS XE 17.18.2, you can configure an object group.

Field	Description
<b>Object Group Name</b>	Name of the object group.
<b>Description</b>	Description of the object group.
<b>Type</b>	You can choose IPv6 or IPv4.

For more information on match conditions, see [Configure Firewall Policies for SD-Routing Devices](#).

**FQDN (Fully Qualified Domain Name)**

The FQDN is intended to be used for matching standalone servers in data centers or a private cloud. When matching public URLs, the recommended match action is **drop**. If you use **inspect** for public URLs, you must define all related sub URLs and redirect URLs.

Field	Description
<b>FQDN List Name</b>	Name of the FQDN list.
<b>FQDN</b>	The URL names separated by comma. For example, cisco.com.

**Geo Location**

Field	Description
<b>Geo Location List Name</b>	Name of the geolocation list.
<b>Geo Location</b>	Select one or more geo locations from the drop-down list. For example, Africa, Antartic, Asia, Europe, and so on.

**Local Domain**

Field	Description
<b>Local Domain List Name</b>	Name of the local domain list.
<b>Local Domain</b>	The local domain values separated by comma. For example, cisco.com.

**Port**

Field	Description
<b>Port List Name</b>	Name of the port list.
<b>Port</b>	The port values separated by comma. The range is 0 to 65530.

**Protocol**

Field	Description
<b>Protocol List Name</b>	Name of the protocol list.
<b>Protocols</b>	Select one or more protocol names from the drop-down list. For example, snmp, tcp, udp, icmp, echo, telnet, and so on.

## Signature

The signature set blocks vulnerability with a Common Vulnerability Scoring System (CVSS) score that is greater than or equal to 9. It also blocks Common Vulnerabilities and Exposures (CVEs) published in the last two years and that have the rule categories: Malware CNC, Exploit Kits, SQL Injection or blocked list.

Field	Description
<b>IPS Signature List Name</b>	Name of the IPS signature list.
<b>IPS Signature</b>	The signatures in the format <code>Generator ID:Signature ID</code> , separated with commas. For example, 1234:5678.  Range is 0 to 4294967295

## Signature Set

Field	Description
<b>IPS Signature Set Name</b>	Name of the IPS signature set.
<b>Base Signature Set</b>	<p>Choose a Base Signature Set from the following options:</p> <ul style="list-style-type: none"> <li>• <b>Connectivity:</b> Delivers basic security by applying fewer rules, prioritizing higher network throughput and performance while offering less restrictive protection</li> <li>• <b>Balanced:</b> Provides balanced security that actively protects the system while maintaining high network throughput and minimizing false positives, ensuring strong protection without compromising performance</li> <li>• <b>Security:</b> Provides enhanced security with increased detection capabilities, offering greater protection than the Balanced level. Designed for administrators who are willing to accept some network latency and a low rate of false positives to identify more potential threats.</li> <li>• <b>Max-detect:</b> This ruleset is designed specifically for use in testing environments and is not optimized for production performance. A higher rate of false positives is anticipated and acceptable for many of the rules included in this policy. As a result, investigations into false positives will generally not be conducted.</li> <li>• <b>No-Rules-Active:</b> No detection rules enabled; used for testing or troubleshooting.</li> </ul> <p><b>Note</b> For more information on creating custom signature sets, refer <a href="#">Custom IPS Signature Sets</a>.</p>

## URL Allow

List-based filtering allows the user to control access by permitting or denying access based on allowed or blocked lists. Here are some important points to note about these lists:

- URLs that are allowed are not subjected to any category-based filtering.

- If the same item is configured under both the allowed and blocked list, the traffic is allowed.
- If the traffic does not match either the allowed or blocked lists, then it is subjected to category-based and reputation-based filtering.

Field	Description
<b>Allow URL List Name</b>	Name of the Allow URL list.
<b>Allow URL</b>	The URLs to allow.

### URL Block

List-based filtering allows the user to control access by permitting or denying access based on allowed or blocked lists.

Field	Description
<b>Block URL List Name</b>	Name of the Block URL list.
<b>Block URL</b>	The URLs to block.

### Zone

Field	Description
<b>Zone List Name</b>	Name of the zone list.
<b>VPN</b>	Choose to configure zones with zone type as <b>VPN</b> . Add the VPNs to the zones from the drop-down list. The options are: <ul style="list-style-type: none"> <li>• Payment Processing Network</li> <li>• Corporate Users</li> <li>• Local Internet for Guests</li> <li>• Physical Security Devices</li> </ul>
<b>Interface</b>	Choose to configure zones with zone type as <b>Interface</b> . Add the interfaces to the zones from the <b>Add Interface</b> drop-down list. The options are: <ul style="list-style-type: none"> <li>• Ethernet</li> <li>• FastEthernet</li> <li>• FiveGigabitEthernet</li> <li>• FortyGigabitEthernet</li> <li>• GigabitEthernet</li> <li>• HundredGigE</li> </ul>

The security group of interest has the following profiles:

- Advanced Inspection Profile
- Advanced Malware Protection
- Intrusion Prevention Policy
- TLS/SSL Decryption
- TLS/SSL Profile
- URL Filtering

### Advanced Inspection Profile

Field	Description
<b>Profile Name</b>	Name of the advanced inspection profile.
<b>Description</b>	The description of the profile.
<b>Intrusion Prevention</b>	Choose an intrusion prevention option from the drop-down list.
<b>URL Filtering</b>	Choose a URL filter from the drop-down list.
<b>Advanced Malware Protection</b>	Choose an advanced malware protection.
<b>TLS Action</b>	Choose the TLS action. The options are: <ul style="list-style-type: none"> <li>• Decrypt</li> <li>• Pass Through</li> <li>• Do not Decrypt</li> </ul>
<b>TLS/SSL Decryption</b>	Choose a TLS/SSL Decryption profile from the drop-down list or click <b>Create New</b> to create a new no decrypt domain list. <ol style="list-style-type: none"> <li>1. Enter <b>No Decrypt Domain List Name</b>.</li> <li>2. Enter <b>No Decrypt Domain</b></li> <li>3. Click <b>Add</b>.</li> </ol>

### Advanced Malware Protection Policy

Field	Description
<b>Profile Name</b>	Name of the advanced malware protection policy name.

Field	Description
<b>AMP Cloud Region</b>	Select AMT Cloud region. The options are: <ul style="list-style-type: none"> <li>• NAM</li> <li>• EU</li> <li>• APJC</li> </ul>
<b>Alert Log Level</b>	Choose the alert log level. The options are: <ul style="list-style-type: none"> <li>• Critical</li> <li>• Warning</li> <li>• Info</li> </ul>
<b>File Analysis</b>	Enable file analysis.
<b>TG Cloud Region</b>	Select TG Cloud region. The options are NAM and EU.
<b>Alert Log Level</b>	Choose the alert log level. The options are: <ul style="list-style-type: none"> <li>• Critical</li> <li>• Warning</li> <li>• Info</li> </ul>
<b>Select one or more file types</b>	Select one or more file types. The options are, pdf, ms-exe, new-office, rtf, mdb, mscab, msole2, wri, xlw, flv, and swf.

#### Intrusion Prevention Policy

Field	Description
<b>Profile Name</b>	Name of the intrusion prevention policy.

Field	Description
<b>Signature Set</b>	<p>Choose a signature set that defines the rules for an evaluating traffic from the <b>Signature Set</b> drop-down list. The following options are available.</p> <ul style="list-style-type: none"> <li>• <b>Balanced</b>: Provides protection without significant effect on system performance.</li> <li>• <b>Connectivity</b>: Less restrictive and provide better performance by imposing fewer rules.</li> <li>• <b>Security</b>: Provides more protection than Balanced but with an impact on performance.</li> <li>• <b>Max-Detect</b>: Most restrictive; enables all detection rules for maximum protection, with the highest performance impact.</li> <li>• <b>No-Rules-Active</b>: No detection rules enabled; used for testing or troubleshooting, with no protection or performance impact.</li> </ul> <p>From 17.18.1a, you can select a previously created custom signature set or create a custom signature set by selecting + <b>Create New</b> and customize your own signature set. For more information, refer <a href="#">Custom IPS signature sets</a>.</p>
<b>Inspection Mode</b>	<p>Choose the inspection mode. The following options are available:</p> <ul style="list-style-type: none"> <li>• <b>Detection</b>: Choose this option for intrusion detection mode.</li> <li>• <b>Protection</b>: Choose this option for intrusion protection mode.</li> </ul>
<b>Advanced Options</b>	
<b>Custom Signature Set</b>	Enable the Global custom signature set using the <b>radio button</b> .
<b>Signature Allow List</b>	Select a signature allow list.
<b>Alerts Log Level</b>	<p>Choose the alert log level:</p> <ul style="list-style-type: none"> <li>• Error</li> <li>• Emergency</li> <li>• Alert</li> <li>• Critical</li> <li>• Warning</li> <li>• Notice</li> <li>• Info</li> <li>• Debug</li> </ul>

### TLS/SSL Decryption

Field Name	Description
<b>Add TLS/SSL Decryption</b>	Click <b>Add TLS/SSL Decryption</b> . A dialog box will appear.
<b>Configure Certificate Authority (CA)</b>	Click <b>Configure Certificate Authority</b> to set up the CA required for decryption.  <b>Note</b> The TLS/SSL Proxy feature will now allow SAIE to decrypt encrypted connections for malware detection and to enforce security policies based on higher-layer traffic. For more information, refer <a href="#">Configure an SD-Routing Device as an SSL/TLS Proxy</a> .
<b>Policy Name</b>	Name of the policy. The name can contain a maximum of 32 characters.
<b>Server Certificate Checks</b>	
<b>Expired Certificate</b>	Defines what the policy should do if the server certificate has expired. The options are: <ul style="list-style-type: none"> <li>• <b>Drop</b>: Drop traffic</li> <li>• <b>Decrypt</b>: Decrypt traffic</li> </ul>
<b>Untrusted Certificate</b>	Defines what the policy should do if the server certificate is not trusted. The options are: <ul style="list-style-type: none"> <li>• <b>Drop</b>: Drop traffic</li> <li>• <b>Decrypt</b>: Decrypt traffic</li> </ul>
<b>Certificate Revocation Status</b>	Defines whether the Online Certificate Status Protocol (OCSP) should be used to check the revocation status of the server certificate. The options are <b>Enabled</b> or <b>Disabled</b> .
<b>Unknown Revocation Status</b>	Defines what the policy does, if the OCSP revocation status is <b>unknown</b> . <ul style="list-style-type: none"> <li>• <b>Drop</b>: Drop traffic</li> <li>• <b>Decrypt</b>: Decrypt traffic</li> </ul>
<b>Unsupported Mode Checks</b>	

Field Name	Description
<b>Unsupported Protocol Versions</b>	Defines the unsupported protocol versions. <ul style="list-style-type: none"> <li>• <b>Drop:</b> Drop the unsupported protocol versions.</li> <li>• <b>Decrypt:</b> Decrypt the unsupported protocol versions.</li> </ul>
<b>Unsupported Cipher Suites</b>	Defines the unsupported cipher suites. <ul style="list-style-type: none"> <li>• <b>Drop:</b> Drop the unsupported cipher suites.</li> <li>• <b>Decrypt:</b> Decrypt the unsupported cipher suites.</li> </ul>
<b>Failure Mode</b>	Defines the failure mode. The options are close and open.
<b>Certificate Bundle</b>	Check the <b>Use default CA certificate bundle</b> checkbox to use the default CA.
<b>Minimum TLS Version</b>	Sets the minimum version of TLS that the proxy should support. The options are: <ul style="list-style-type: none"> <li>• <b>TLS 1.0</b></li> <li>• <b>TLS 1.1</b></li> <li>• <b>TLS 1.2</b></li> </ul>
<b>Proxy Certificate Attributes</b>	
<b>RSA Keypair Modules</b>	Defines the Proxy Certificate RSA Key modules. The options are: <ul style="list-style-type: none"> <li>• <b>1024 bit RSA</b></li> <li>• <b>2048 bit RSA</b></li> <li>• <b>4096 bit RSA</b></li> </ul>
<b>Ec Key Type</b>	Defines the key type. The options are: <ul style="list-style-type: none"> <li>• <b>P256</b></li> <li>• <b>P384</b></li> <li>• <b>P521</b></li> </ul>
<b>Certificate Lifetime (in Days)</b>	Sets the lifetime of the proxy certificate, in days.

**TLS/SSL Profile**

Field	Description
<b>Profile Name</b>	Name of the TLS/SSL profile.

Field	Description
<b>Categories to assign action</b>	Set the categories between the actions—Decrypt, No Decrypt, and Pass Through URL Categories.  Alternatively, choose multiple categories and set the action.
<b>Reputation</b>	Enable reputation to choose the <b>Decrypt Threshold</b> . The decrypt threshold options are: <ul style="list-style-type: none"> <li>• High Risk</li> <li>• Suspicious</li> <li>• Moderate Risk</li> <li>• Low Risk</li> <li>• Trustworthy</li> </ul>
<b>Advanced Options</b>	
<b>Decrypt Domain list</b>	Choose the decrypt domain list or click <b>Create New</b> to create a new decrypt domain list. <ol style="list-style-type: none"> <li>1. Enter <b>Decrypt Domain List Name</b>.</li> <li>2. Enter <b>Decrypt Domain</b></li> <li>3. Click <b>Add</b>.</li> </ol>
<b>No Decrypt Domain list</b>	Choose the no decrypt domain list or click <b>Create New</b> to create a new no decrypt domain list. <ol style="list-style-type: none"> <li>1. Enter <b>No Decrypt Domain List Name</b>.</li> <li>2. Enter <b>No Decrypt Domain</b></li> <li>3. Click <b>Add</b>.</li> </ol>
<b>Fail Decrypt</b>	Enable the fail decrypt option, if decryption fails.

### URL Filtering Policy

Field	Description
<b>Profile Name</b>	Name of the URL filtering policy.
<b>Web Category</b>	Choose the web category. The options are Block and Allow.
<b>Web categories</b>	Select one or more web categories from the drop-down list. The categories are: abortion, abused-drugs, auctions, and so on.
<b>Allow URL list</b>	Select an allow URL list.
<b>Block URL list</b>	Select a block URL list.

Field	Description
<b>Block Page Server</b>	Choose one of the options: <ul style="list-style-type: none"> <li>• Block Page Content: Enter the default content header and content body.</li> <li>• Redirect URL: Enter the redirect URL.</li> </ul>
<b>Alerts and Logs</b>	Choose the alert and log type: <ul style="list-style-type: none"> <li>• Blocklist</li> <li>• Allowlist</li> <li>• Reputation/Category</li> </ul>

## Configure Application Priority and SLA

The application priority and SLA policies allows you to configure the app route policy, data policy, and QoS Map policies that route and prioritize traffic for best performance. All the basic information is preconfigured. You can specify a name and description for a policy group and configure the basic policy values. You can quickly configure the basic values to get started with the traffic policy.

To configure Application Priority & SLA, follow the steps below:

1. Click **Application Priority & SLA policy**.
2. Enter the **Policy Name** and **description**.
3. Click **Create**.

Choose one of the following options and configure the values that are based on the likely business relevance of the applications, and to give higher priority to business-relevant applications:

- **Gold** (Business-relevant): Likely to be important for business operations, for example, WebEx software.
- **Silver** (Default): No determination of relevance to business operations.
- **Bronze** (Business-irrelevant): Unlikely to be important for business operations, for example, gaming software.

Within each of the business-relevance categories, the workflow groups the applications into application lists, such as broadcast video, multimedia conferencing, VoIP telephony, and so on.

Table 4: Cisco Catalyst SD-WAN Fabric Traffic Policy

Field	Description
<b>Preferred Path</b>	To configure a preferred path, select one or more data plane tunnel colors from the drop-down list. Traffic will be load-balanced across all selected tunnels. If no tunnels meet the SLA requirements, data traffic is sent through any available tunnel. Preferences are applied in order of priority to determine the forwarding path or color.
<b>When SLA not met</b>	Choose <b>Strict/Drop</b> to perform strict matching of the SLA class. If no data plane tunnel is available that satisfies the SLA criteria, traffic is dropped.  Choose <b>Fallback to best path</b> to configure the best available tunnel to avoid a packet drop. This is the default.
<b>Backup Path</b>	To configure an alternate traffic path, select a backup path from the drop-down list. This path is used if the primary path fails.
<b>Traffic Filtering</b>	Click <b>Edit</b> to view and update application classification based on business relevance. Choose a service provider class and organize applications into classes like Gold or Bronze. Click <b>Save</b> to update the configuration.
<b>SLA</b>	Add the SLA class to the traffic policy. Click <b>Edit</b> to adjust the SLA class values for Loss (%), Latency (ms), or Jitter (ms).
<b>QoS Queues</b>	Click <b>Add QoS Policy</b> to add a QoS queue. Click <b>Edit</b> to configure the QoS queues. Choose one of the following values for the QoS queuing model: <ul style="list-style-type: none"> <li>• 4 Queues</li> <li>• 5 Queues</li> <li>• 6 Queues</li> <li>• 8 Queues</li> </ul>

Table 5: Internet Offload Traffic

Field	Description
<b>Secure Internet Gateway</b>	Choose an application or family list to direct traffic through a Secure Internet Gateway. Enable fallback routing for traffic when SIG tunnels are down.

Field	Description
Direct Internet Access	Select an application or family list for direct internet access. Enable fallback routing for traffic if Direct Internet Access (DIA) is not available.

Table 6: Apply Policy

Field	Description
Target	<p>Configure the following parameters:</p> <ul style="list-style-type: none"> <li>• <b>Direction:</b> Choose the direction for applying the policy: <ul style="list-style-type: none"> <li>• <b>All:</b> Bidirection traffic flow</li> <li>• <b>Service:</b> Incoming traffic from service.</li> <li>• <b>Tunnel:</b> Incoming traffic from the tunnel.</li> </ul> </li> <li>• <b>VPN:</b> Choose a target VPN from the drop-down list.</li> <li>• <b>Interface:</b> Specify a value or a variable for the Ethernet interface or DSL PPPoE interface type for applying the QoS policy.</li> </ul>

## Configure NGFW

Security is a critical element of today's networking infrastructure. Network administrators and security officers are hard pressed to defend their networks against attacks and breaches. Due to hybrid clouds and remote employee connectivity, the security perimeter around networks is disappearing.

The Enterprise Firewall with Application Awareness uses a flexible and easily understood zone-based model for traffic inspection, compared to the older interface-based model.

A firewall policy is a type of localized security policy that allows stateful inspection of TCP, UDP, and ICMP data traffic flows. Traffic flows that originate in a given zone are allowed to proceed to another zone based on the policy between the two zones. A zone is a grouping of one or more VPNs. Grouping VPNs into zones allows you to establish security boundaries in your overlay network so that you can control all data traffic that passes between zones. For more information on Embedded Security, see [Enterprise Firewall with Application Awareness](#).

Follow the below steps to create NGFW Policy:

1. From the Cisco SD-WAN Manager menu, choose **Configuration > Policy Groups > NGFW**.
2. Click **Add NGFW Policy**.
3. In the **Create NGFW Policy** dialog box, click **Let's do it**.
4. In the NGFW tab,

- Enter the **Policy Name** and **description**.
  - Select **SD-Routing** as the device solution.
  - Click **Next**.
5. (Optional) Select Configuration Groups – Not applicable for SD-Routing policies. Click **Next**.
6. In the Create Sub Policies tab,
- Click **Add Sub-Policy**
  - Choose **Source Zone**
  - Choose **Destination Zone**
  - Click **Save**
7. In the **Add Rule** dialogue box, configure the following and save.

Field	Description
Rule Name	The name of the rule.
Sequence	Specify the sequence.
Match	Choose the desired match conditions from the <b>Add Conditions</b> drop-down list.
Traffic Source - Data Prefix	(Optional) Enter the Data Prefix of the Traffic Source.
Traffic Destination - Data Prefix	(Optional) Enter the Data Prefix of the Traffic Destination.
Protocol	(Optional) Select the preferred protocol.
Application	(Optional) Select the preferred application.
Action	(Optional) Choose the preferred action conditions.

8. (Optional) Click **Additional Settings** and configure the following:

Field	Description
TCP SYN Flood Limit	Specify the threshold of SYN flood packets per second for each destination address.
Max Incomplete	Specify the timeout limits for the firewall policy. A Max Incomplete timeout limit protects firewall resources and keeps these resources from being used up.
TCP Limit	Specify the maximum TCP half-open sessions allowed on a device.

Field	Description
UDP Limit	Specify the maximum UDP half-open sessions allowed on a device.
ICMP Limit	Specify the maximum ICMP half-open sessions allowed on a device.
Audit Trail	Enable the Audit Trail option. This option is only applicable for rules with an inspect action.
Unified Logging	Enable the unified logging feature.
Optimized Policy	Enable the optimized policy option.
Session Reclassify Allow	Allow re-classification of traffic on policy change.
ICMP Unreachable Allow	Allow ICMP unreachable packets to pass through.
Advanced Inspection Profile	Attach a global advanced inspection profile (AIP) at a device level. All the rules in the device that match the traffic to be inspected are inspected using the advance inspection profile.
TLS/SSL Decryption	Choose the TLS/SSL decryption profile from the drop-down list
High Speed Logging Source File	Add security logging servers. You can configure 4 source interfaces for HSL
External Syslog Server	Select and configure the source interface for UTD.

- Click **Save**.
- Select **Next**.

9. In the Summary tab, verify and edit the details if required and Click **Create NGFW Policy**.

## Configure a Secure Internet Gateway

Cisco Catalyst SD-WAN edge devices support routing, security, and other LAN access features that can be managed centrally. On high-end devices, you can enable all these features while providing the scale and performance required by large enterprises. However, on lower-end devices, enabling all the security features simultaneously can degrade performance. To avoid the performance degradation, integrate lower-end devices with Secure Internet Gateways (SIG) that do most of the processing to secure enterprise traffic. When you integrate a Cisco Catalyst SD-WAN edge device with a SIG, all client internet traffic, based on routing or policy, is forwarded to the SIG.

To configure a secure internet gateway, follow the below steps:

1. From the Cisco SD-WAN Manager menu **Configuration > Policy Groups > Secure Internet Gateway/Secure Service Edge**.

2. Click **Add Secure Internet Gateway (SIG)**.
3. Enter a **name** and provide a **description** (optional).
4. Click **Create**
5. Choose an **SIG Provider** from the options below:
  - Umbrella
  - Zscaler
  - Generic

### Umbrella Configuration

To configure Umbrella SIG Provider, follow the these steps:

1. Select **Click here to add Umbrella credentials**.
2. In the Add **Umbrella credentials** dialog box, configure the following and click **Add**.

*Table 7: Cisco Umbrella Credentials*

Field	Description
<b>Organization ID</b>	Enter the Cisco Umbrella organization ID (Org ID) for your organization.
<b>Scope Credentials</b>	Enter the API Key and API Secret.
<b>Legacy Credentials</b>	Enter the API Key and API Secret.

### Zscaler Configuration

You can access Zscaler credentials from **Administration > Settings > Cloud Provider Credentials**.

To configure Zscaler SIG Provider follow the below steps:

- Select **Click here to add Zscaler credentials**.
- In the Add **Zscaler credentials** dialog box, configure the following and click **Add**.

*Table 8: Zscaler Credentials*

Field	Description
<b>Organization ID</b>	Enter the name of the organization in Zscaler cloud.
<b>Partner base URI</b>	Enter Partner base URI. This is the base URI that Cisco SD-WAN Manager uses in REST API calls.
<b>Partner Key</b>	Enter Partner API key.
<b>Username</b>	Enter username of the Cisco Catalyst SD-Routing partner account.
<b>Password</b>	Enter username of the Cisco Catalyst SD-Routing partner account.

## Generic Configuration

### Tracker Configuration

To create one or more trackers to monitor tunnel health, do the following under **Tracker**:

1. Enter a **source IP address** for the probe packets.
2. Click **Add Tracker**.
3. In the **Add Tracker** dialog box, configure the following and click **Add**.

Field	Description
Name	Name of the tracker. The name can be up to 128 alphanumeric characters.
API URL of Endpoint	Specify the API URL for the SIG endpoint of the tunnel.
Threshold	Enter the wait time for the probe to return a response before declaring that the configured endpoint is down. Range: 100 to 1000 milliseconds Default: 300 milliseconds
Probe Interval	Enter the time interval between probes to determine the status of the configured endpoint. Range: 20 to 600 seconds Default: 60 seconds
Multiplier	Enter the number of times to resend probes before determining that a tunnel is down. Range: 1 to 10 Default: 3

### Tunnel Configuration

To create tunnels, do the following under **Configuration**:

1. Click **Add Tunnel**.
2. In the **Add Tunnel** dialog box, configure the following and click **Add**.

*Table 9: Basic Settings*

Field	Description
Tunnel Type	Click <b>ipsec</b> or <b>gre</b> .
Interface Name (1..255)	Name of the interface.
Description	Description for the interface.
Tracker	By default, a tracker is attached to monitor the health of tunnels.

Field	Description
<b>Tunnel Source Interface</b>	Name of the source interface of the tunnel. This interface should be an egress interface and is typically the internet-facing interface.
<b>Tunnel Destination IP Address/FQDN</b>	The IP address of the SIG provider endpoint. The configuration of FQDN for Tunnel Destination IP address is not supported.
<b>Preshared Key</b>	This field is displayed only if you choose <b>ipsec</b> as the <b>Tunnel Type</b> .  Enter the password to use with the preshared key. This field is displayed only if you choose ipsec as the Tunnel Type.
<b>Advanced Options</b>	
<b>Shutdown</b>	Click to enable the interface.  Default: disabled.
<b>IP MTU</b>	Specify the maximum MTU size of packets on the interface.  Range: 576 to 2000 bytes  Default: 1400 bytes
<b>TCP MSS</b>	Specify the maximum segment size (MSS) of TPC SYN packets. By default, the MSS is dynamically adjusted based on the interface or tunnel MTU such that TCP SYN packets are never fragmented.  Range: 500 to 1460 bytes  Default: None
<b>DPD Interval</b>	Specify the interval for IKE to send Hello packets on the connection.  Range: 10 to 3600 seconds  Default: 10
<b>DPD Retries</b>	Specify the number of seconds between DPD retry messages if the DPD retry message is missed by the peer.  After one DPD message is missed by the peer, the router changes the state and sends a DPD retry message at a faster retry interval, which is the number of seconds between DPD retries if the DPD message is missed by the peer. The default DPD retry message is sent every 2 seconds. Five DPD retry messages can be missed before the tunnel is marked as down.  Range: 2 to 60 seconds  Default: 3
<b>IKE</b>	
<b>IKE Rekey Interval</b>	Specify the interval for refreshing IKE keys.  Range: 3600 to 1209600 seconds (1 hour to 14 days)  Default: 14400 seconds

Field	Description
<b>IKE Cipher Suite</b>	Specify the type of authentication and encryption to use during IKE key exchange.
<b>IKE Diffie-Hellman Group</b>	Specify the Diffie-Hellman group to use in IKE key exchange, whether IKEv1 or IKEv2.
<b>IKE ID for Local End Point</b>	Specify the IKE ID for Local End Point.
<b>IKE ID for Remote End Point</b>	Specify the IKE ID for Remote End Point.
<b>IPSec</b>	
<b>IPsec Rekey Interval</b>	Specify the interval for refreshing IPsec keys. Range: 3600 to 1209600 seconds (1 hour to 14 days) Default: 3600 seconds
<b>IPsec Replay Window</b>	Specify the replay window size for the IPsec tunnel. Options: 64, 128, 256, 512, 1024, 2048, 4096. Default: 512
<b>IPsec Cipher Suite</b>	Specify the authentication and encryption to use on the IPsec tunnel. Default: AES 256 GCM
<b>Perfect Forward Secrecy</b>	Specify the PFS settings to use on the IPsec tunnel.

### High Availability Configuration

To designate active and back-up tunnels and distribute traffic among tunnels, click **High Availability** and do the following:

1. Click **Add Interface Pair**.
2. In the **Add Interface Pair** dialog box, configure the following and click **Add**

Field	Description
<b>Active Interface</b>	Choose a tunnel that connects to the primary data center.
<b>Active Interface Weight</b>	Enter weight (weight range 1 to 255) for load balancing.
<b>Backup Interface</b>	To designate a back-up tunnel, choose a tunnel that connects to the secondary data center. To omit designating a back-up tunnel, choose <b>None</b> .
<b>Backup Interface Weight</b>	Enter weight (weight range 1 to 255) for load balancing.

## Configure Secure Service Edge

Cisco Secure Access is a cloud-based platform that provides multiple levels of defense against internet-based threats. To configure Secure Service Edge (SSE), choose Cisco Secure Access as the provider in the SSE policy group in Cisco SD-WAN Manager. The SSE policy group defines IPsec tunnels and tunnel parameters. You can provision network tunnel groups in Cisco Secure Access and provide attributes to the edge devices that are needed to setup IPsec tunnels.

### Before You Begin

Create the Cisco SSE credentials from **Administration > Settings > Cloud Credentials**.

To configure Secure Service Edge, follow these steps:

1. From the Cisco SD-WAN Manager menu **Configuration > Policy Groups > Secure Internet Gateway/Secure Service Edge**.
2. Click **Add Secure Service Edge(SSE)**
3. Enter a **name** and select **SD-Routing** from the Solution drop down list
4. (Optional) Provide a description.
5. Click **Create**.
6. Select **Click here to add cisco-sse credentials** and configure the following:

Field	Description
Cisco SSE Organization ID	Cisco Secure Access organization ID for your organization.
Cisco SSE API Key	Cisco Secure Access API Key.
Cisco SSE API Secret	Cisco Secure Access API Secret.

7. Click **Add**

## Configure DNS Security

The Cisco Catalyst SD-WAN Umbrella Integration feature enables the cloud-based security service by inspecting the Domain Name System (DNS) query that is sent to the DNS server through the device. The security administrator configures policies on the Umbrella portal to either allow or deny traffic toward the fully qualified domain name (FQDN). The router acts as a DNS forwarder on the network edge, transparently intercepts DNS traffic, and forwards the DNS queries to the Umbrella cloud.

To configure DNS Security, follow the steps below:

1. From the Cisco SD-WAN Manager menu, choose **Configuration > Policy Groups > DNS Security**.
2. Click **Add DNS Security Policy**.
3. Enter a **name** and provide a **description** (optional)

4. Click **Create** and configure the following:

Field	Description
<b>Umbrella Registration Status</b>	Displays the status of the API Token configuration.
<b>Manage Umbrella Registration</b>	<p>Click <b>Manage Umbrella Registration</b> to add Cisco Umbrella Registration Key and Secret. Enter the following details:</p> <p><b>a. Scope Credentials</b></p> <ul style="list-style-type: none"> <li>• Enter <b>Organization ID</b>.</li> <li>• Enter <b>API Key</b></li> <li>• Enter <b>Secret</b>.</li> </ul> <p><b>b. Legacy Credentials</b></p> <ul style="list-style-type: none"> <li>• Enter <b>API Key</b></li> <li>• Enter <b>Secret</b></li> </ul> <p><b>c. Click Save Changes.</b></p> <p><b>Note</b> Note, you can edit the umbrella credentials from <b>Administration &gt; Settings &gt; Cloud Provider</b>.</p>
<b>Match All VPN</b>	
<b>Match All VPN</b>	Click <b>Match All VPN</b> to keep the same configuration for all the available VPNs.
<b>Local Domain Bypass List</b>	Choose the local domain bypass from the drop down list or <b>Create New</b> .
<b>DNS Server IP</b>	<p>Configure <b>DNS Server IP</b> from the following options:</p> <ul style="list-style-type: none"> <li>• <b>Umbrella Default</b></li> <li>• <b>Custom DNS</b></li> </ul>
<b>DNSCrypt</b>	Enable or disable the DNSCrypt.
<b>Custom VPN Configuration</b>	
<b>Custom VPN Configuration</b>	choose <b>Custom VPN Configuration</b> to input the specific VPNs.
<b>Local Domain Bypass List</b>	Choose the domain bypass from the drop down list or <b>Create New</b> .
<b>DNSCrypt</b>	DNSCrypt is disabled by default.

Field	Description
Target VPN	<p>Click <b>Add Target VPN</b> and enter the following fields:</p> <ol style="list-style-type: none"><li data-bbox="976 373 1523 428"><b>a.</b> VPNs - Select the VPN from the drop-down list.</li><li data-bbox="976 457 1523 613"><b>b.</b> DNS Server IP - Configure <b>DNS Server IP</b> from the following options:<ul style="list-style-type: none"><li data-bbox="1057 533 1279 562">• <b>Umbrella Default</b></li><li data-bbox="1057 583 1227 613">• <b>Custom DNS</b></li></ul></li><li data-bbox="976 655 1523 709"><b>c.</b> Local Domain Bypass - Choose the domain bypass and <b>Save</b> changes</li></ol>

5. Click **Save**.

