



## Troubleshoot NAT

---

- [Support document links, on page 1](#)
- [Support Articles, on page 1](#)
- [Submit feedback for a support document, on page 2](#)
- [Disclaimer and caution, on page 2](#)

### Support document links

A support document link is a resource that

- provides access to documents authored by Cisco subject matter experts
- helps resolve technical issues without requiring a support ticket, and
- offers guidance about the data to collect and add to a support ticket if escalation is needed.

#### Community and support escalation information

This section describes additional resources for resolving technical issues and guidance for support escalation.

- If the documents do not resolve your issue, visit the applicable [Cisco Community](#) for information and advice from fellow Cisco customers.
- If you cannot find a resolution on the Community, raise a support ticket at [Cisco Support](#).
- When raising a support ticket, specify the support document you referred to so TAC can create an improvement request with the document owner.

### Support Articles

The documents in this section were created using specific software and hardware listed in the Components Used section of each article. However, this does not mean that they are limited to what is listed in Components Used, and generally remain relevant for later versions of software and hardware. Note that there could be some changes in the software or hardware that can cause commands to stop working, the syntax to change, or GUIs and CLIs to look different from one release to another.

The following support article is associated with this technology:

Document	Description
<a href="#">Configure Service to Transport Static NAT on a Cisco IOS XE Catalyst SD-WAN Router</a>	This document describes the configuration to perform a static NAT from the service side VRF to the transport VRF on a Cisco IOS XE Catalyst SD-WAN device.
<a href="#">Configure Service-Side Static NAT on a Cisco IOS XE Catalyst SD-WAN Router</a>	This document describes the configuration to perform a static NAT to and from service side VRF on a Cisco IOS-XE <sup>®</sup> SD-WAN Router.
<a href="#">Implement Direct Internet Access (DIA) for Cisco Catalyst SD-WAN</a>	This document describes how to implement Cisco Catalyst SD-WAN DIA. It refers to the configuration when Internet traffic breaks out directly from branch router.

## Submit feedback for a support document

### Procedure

- 
- Step 1** Provide feedback using the **Feedback** button located at the right panel of the corresponding article. The document owner will be notified and will either update the article or flag it for removal.
- Step 2** Include information regarding the section, area, or issue you had with the document and what could be improved. Provide as much detail as possible to help the document owner understand and address your feedback.
- 

After submitting feedback, the document owner will review your input and may update the article or flag it for removal based on your suggestions.

## Disclaimer and caution

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, ensure that you understand the potential impact of any command.