



Security CLI Reference



Note To achieve simplification and consistency, the Cisco SD-WAN solution has been rebranded as Cisco Catalyst SD-WAN. In addition, from Cisco IOS XE SD-WAN Release 17.12.1a and Cisco Catalyst SD-WAN Release 20.12.1, the following component changes are applicable: **Cisco vManage** to **Cisco Catalyst SD-WAN Manager**, **Cisco vAnalytics** to **Cisco Catalyst SD-WAN Analytics**, **Cisco vBond** to **Cisco Catalyst SD-WAN Validator**, and **Cisco vSmart** to **Cisco Catalyst SD-WAN Controller**. See the latest Release Notes for a comprehensive list of all the component brand name changes. While we transition to the new names, some inconsistencies might be present in the documentation set because of a phased approach to the user interface updates of the software product.

CLI commands for configuring and monitoring security.

Security Configuration Commands

Use the following commands to configure security parameters:

```
security
  control
    protocol (dtls | tls)
    tls-port number
  ipsec
    authentication-type type
    rekey seconds
    replay-window number
  vpn vpn-id
    interface ipsecnumber
      access-list acl-name
      block-non-source-ip
      clear-dont-fragment
      dead-peer-detection interval seconds retries number
      description text
    ike
      authentication-type type
      local-id id
      pre-shared-secret password
      remote-id id
      cipher-suite suite
      group number
      mode mode
      rekey seconds
      version number
    ip address ipv4-prefix/length
```

```
ipsec
  cipher-suite suite
  perfect-forward-secrecy pfs-setting
  rekey seconds
  replay-window number
  mtu bytes
  policer policer-name
  rewrite-rule rule-name
  [no] shutdown
  tcp-mss-adjust bytes
  tunnel-destination (dns-name | ipv4-address)
  (tunnel-source ip-address | tunnel-source-interface interface-name)
```

Security Monitoring Commands

- **show control connections**
- **show security-info**