



# Server Recommendations (On-Prem) for Cisco vManage Release 20.3.x

## Single Tenant

The supported hardware specifications for the Cisco vBond Orchestrator, Cisco vManage, and the Cisco vSmart Controller are as follows:



**Note** For cloud deployments, the Cisco operation teams actively monitor the customer deployment and add resource in collaboration with the customer. This topic does not include recommendations for Cisco cloud deployments.

*Table 1: Cisco vManage Server Recommendations*

Devices	Aggregated Statistics from Edge Devices	Nodes and Deployment Models	vCPUs *	RAM*	Storage Size*	Deployment Type
<b>On-Prem</b>						
<b>DPI Disabled</b>						
<250	N/A	One Node vManage (All Services)	16 vCPUs	32 GB RAM	500 GB	UCS
250-1000	N/A	One Node vManage (All Services)	32 vCPUs	64 GB RAM	1 TB	UCS
1000-1500	N/A	One Node vManage (All Services)	32 vCPUs	128 GB RAM	1 TB	UCS
1000-2000	N/A	Three Node vManage Cluster (All Services)	32 vCPUs	64 GB RAM	1 TB	UCS
2000-5000	N/A	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB RAM	1 TB	UCS
0-2000	N/A	Three Node vManage Cluster (All Services)	32 vCPUs	64 GB RAM	1 TB	HX

Devices	Aggregated Statistics from Edge Devices	Nodes and Deployment Models	vCPUs *	RAM*	Storage Size*	Deployment Type
2000-5000	N/A	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB RAM	1 TB	HX
<b>DPI Enabled</b>						
<250	50 GB/Day	One Node vManage (All Services)	32 vCPUs	128 GB	10 TB	UCS
250-1000	100 GB/Day	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB	10 TB	UCS
1000-2000	1.2 TB/Day	Six Node vManage Cluster (3 Node with ConfigDB, AppServer), 3 Nodes (Stats, AppServer) all nodes messaging server	32 vCPUs	128 GB	10 TB	UCS

\* vCPU, RAM, and Storage Size numbers are on per Cisco vManage basis. The Storage Size numbers are the maximum tested values by Cisco, you can allocate smaller storage sizes.

To achieve scale beyond the above mentioned numbers, deploy multiple overlays.

**Table 2: Cisco vBond Orchestrator Server Recommendations for HX/UCS**

Devices	vCPUs	RAM	OS Volume	vNICs
1-50	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
51-250	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
251-1000	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
1001 or more	4	8 GB	10 GB	2 (one for tunnel interface, one for management)

**Table 3: Cisco vSmart Controller Server Recommendations for HX/UCS**

Devices	vCPUs	RAM	OS Volume	vNICs
1-50	2	4 GB	16 GB	2 (one for tunnel interface, one for management)
51-250	4	8 GB	16 GB	2 (one for tunnel interface, one for management)
251-1000	4	16 GB	16 GB	2 (one for tunnel interface, one for management)
1001 or more	8	16 GB	16 GB	2 (one for tunnel interface, one for management)

## Testbed Specifications

**Table 4: Testbed specifications for UCS Platforms**

Hardware SKU	Specifications
UCSC-C240-M5SX	UCS C240 M5 24 SFF + 2 rear drives without CPU, memory cards, hard disk, PCIe, PS
UCS-MR-X16G1RT-H	16GB DDR4-2933-MHz RDIMM/1Rx4/1.2v
UCS-CPU-I6248R	Intel 6248R 3GHz/205W 24C/35.75MB DDR4 2933MHz
UCS-SD16T123X-EP	1.6TB 2.5in Enterprise Performance 12G SAS SSD (3X endurance)

Drive specifications:

- Interface Speed— 12.0 Gbit per second
- Read speed (64KB) —1800 MB per second
- Write speed (64KB)—850 MB per second



### Note

- The recommended numbers are based on the test setup specifications. Systems below these requirements may have challenges processing high volume of statistics data like DPI.
- Tested with 10 TB Volume (8 X 1.6 TB SSD Drives Raid 0).
- Default hyperthreading is enabled.
- Slower disks can impact processing speed.

**Table 5: Testbed specifications for HX Platforms**

Hardware SKU	Specifications
HXAF240-M5SX	Cisco HyperFlex HX240c M5 All Flash Node
HX-MR-X32G2RT-H	32GB DDR4-2933-MHz RDIMM/2Rx4/1.2v
HX-CPU-I6248	Intel 6248 2.5GHz/150W 20C/24.75MB 3DX DDR4 2933 MHz
HX-SD38T61X-EV	3.8TB 2.5 inch Enterprise Value 6G SATA SSD
HX-NVMEXPB-I375	375GB 2.5 inch Intel Optane NVMe Extreme Performance SSD

Drive specifications:

- The tested replication factor is 3.
- The default compression on the HX system is applicable to all cases. This compression is automatically determined by the system and cannot be configured.