



# Configuration Management Commands on the Cisco IOS XR Software

---

This module describes the Cisco IOS XR commands used to manage your basic configuration.

For detailed information about configuration management concepts, tasks, and examples, see *Cisco IOS XR Getting Started Guide for the Cisco XR 12000 Series Router*.

- [abort](#), page 4
- [admin](#), page 6
- [alias](#), page 8
- [apply-template](#), page 11
- [clear comment](#), page 13
- [clear configuration commits](#), page 15
- [clear configuration inconsistency](#), page 17
- [clear configuration inconsistency replica](#), page 20
- [clear configuration sessions](#), page 22
- [commit](#), page 24
- [configuration commit auto-save](#), page 29
- [configure](#), page 31
- [description \(interface\)](#), page 34
- [do](#), page 36
- [end](#), page 38
- [end-template](#), page 40
- [exit](#), page 42
- [hostname](#), page 45
- [load](#), page 47
- [load commit changes](#), page 49

- [load configuration failed](#), page 51
- [load configuration removed](#), page 53
- [load rollback changes](#), page 55
- [man](#), page 57
- [more](#), page 60
- [pwd \(config\)](#), page 65
- [rollback configuration](#), page 66
- [root](#), page 70
- [save configuration](#), page 72
- [save configuration changes](#), page 74
- [save configuration commit changes](#), page 76
- [save configuration failed](#), page 78
- [save configuration merge](#), page 80
- [save configuration removed](#), page 82
- [save rollback changes](#), page 84
- [set default-afi](#), page 86
- [set default-safi](#), page 88
- [set default-vrf](#), page 90
- [show](#), page 93
- [show aliases](#), page 97
- [show configuration \(config\)](#), page 99
- [show configuration changes](#), page 102
- [show configuration commit changes](#), page 104
- [show configuration commit list](#), page 107
- [show configuration failed \(config\)](#), page 110
- [show configuration failed incompatible](#), page 113
- [show configuration failed remove](#), page 114
- [show configuration failed rollback](#), page 116
- [show configuration failed startup](#), page 118
- [show configuration history](#), page 120
- [show configuration inconsistency replica](#), page 124
- [show configuration persistent](#), page 126
- [show configuration removed](#), page 128

- [show configuration rollback changes, page 130](#)
- [show configuration running, page 133](#)
- [show configuration running-config, page 135](#)
- [show configuration sessions, page 138](#)
- [show default-afi-safi-vrf, page 140](#)
- [show history, page 142](#)
- [show running-config, page 144](#)
- [template, page 148](#)

# abort

To terminate a configuration session and discard all uncommitted changes without system confirmations, use the **abort** command in any configuration mode.

**abort**

## Syntax Description

This command has no keywords or arguments.

## Command Default

None

## Command Modes

Any configuration mode

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **abort** command to terminate a configuration session and return to EXEC mode from any configuration mode. This command discards all uncommitted configuration changes. You are prompted to commit the changes.

## Task ID

Task ID	Operations
Task ID for the feature or mode impacted by the command	Operation for the feature or mode impacted by the command

## Examples

The following example shows how to use the **abort** command to discard all changes made during a configuration session:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/0
RP/0/0/CPU0:router(config-if)# ipv4 address 1.1.1.1 255.0.0.0
RP/0/0/CPU0:router(config-if)# abort
RP/0/0/CPU0:router#
```

## Related Commands

Command	Description
<a href="#">end</a>	Terminates a session and returns the router to EXEC mode from any configuration mode.
<a href="#">exit</a>	Exits from the current configuration mode to the next higher command mode or logs out of the terminal session.

# admin

To enter administration EXEC mode, use the **admin** command in EXEC mode.

**admin**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **admin** command to enter administration EXEC mode. Administration commands are used to configure secure domain routers (SDRs) and to execute various administration plane commands.



### Note

Administration commands can be run only by entering administration mode and not by prefixing the **admin** command with the keyword in EXEC mode.

**Task ID**

Task ID	Operations
admin	read, write, execute

**Examples**

The following example shows how to enter administration EXEC mode:

```
RP/0/0/CPU0:router# admin
RP/0/0/CPU0:router(admin)#
```

To use administration configuration mode, use the **configure** command in administration EXEC mode:

```
RP/0/0/CPU0:router# admin
RP/0/0/CPU0:router(admin)# configure
RP/0/0/CPU0:router(admin-config)#
```

**Related Commands**

Command	Description
<a href="#">configure</a>	Enters global configuration mode.

# alias

To create a command alias, use the **alias** command in global configuration mode. To delete an alias, use the **no** form of this command.

**alias***alias-name* [*param-list*] *content*

**no alias** *alias-name*

## Syntax Description

<i>alias-name</i>	Name of the command alias. Alias names can be a single word or multiple words joined by a hyphen (-) or an underscore (_).
<i>param-list</i>	(Optional) Parameters assigned to the alias. These parameters are filled in at execution time.
<i>content</i>	Original command syntax. Valid abbreviations of the original command syntax can be entered for the <i>content</i> argument.

## Command Default

No command aliases are configured.

## Command Modes

Global configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.



**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Cisco IOS XR software supports generic alias definitions for various entities. Any physical or logical entity can have an alias as a reference. For example, an alias can refer to a command, a partial command, a group of commands, a location, or an IP address.

An alias must first be defined. The alias can then be used in command lines in place of the defined entity.

Following is a list of properties for an alias:

- An alias can be used anywhere and in any mode.
- An alias can have zero, one, or many parameters.
- An alias can refer to those parameters with the \$ sign.
- If an alias refers to more than one command, the commands must be separated by a semicolon (;).
- The size of the **alias** command is limited to 1024 characters.

The alias command can be used anywhere. If the content referenced by the alias is invalid or inappropriate in that context or mode, the system issues a warning message containing the substituted content.

An alias name should not be a subset of the keywords that it represents as alias. Substitution is done only when the entered input match fails completely. For instance, the attempt to define an alias with “config□?” as the alias name fails, as shown in the following example:

```
RP/0/RP0/CPU0:router# (config)# alias config set_host hostname router
RP/0/RP0/CPU0:router# (config)# show configuration

alias set_host hostname router
```

Use the **show aliases** command to display all command aliases or the command aliases in a specified mode.

**Task ID**

Task ID	Operations
logging	read, write

**Examples**

The following example shows how to create an alias named ipbr for the **show ipv4 interface brief** command, commit the configuration, enter EXEC mode, and then enter the configured alias:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# alias ipbr show ipv4 interface brief
RP/0/0/CPU0:router(config)# show configuration

Building configuration...
alias ipbr show ipv4 interface brief
end
RP/0/0/CPU0:router(config)# commit
RP/0/0/CPU0:Feb 21 04:42:57.017 : config[65689]: %MGBL-LIBTARCFG-6-COMMIT :
Configuration committed by user 'lab'. Use 'show configuration commit changes 100000022'
to view the changes.
RP/0/0/CPU0:router(config)# end
```

```
RP/0/RP0/CPU0:Mar 27 22:19:05 : config[65739]: %SYS-5-CONFIG_I : Configured from console
by lab
RP/0/0/CPU0:router# ipbr
RP/0/0/CPU0:router# show ipv4 interface brief

Interface                               IP-Address      Status          Protocol
Loopback0                               1.1.1.1         Up              Up
Loopback999                             unassigned      Up              Up
MgmtEth0/0/CPU0/0                       12.29.56.21     Up              Up
RP/0/0/CPU0:router#
```

The following example shows how to define an alias, mycompany-10ge, for POS interface 1/0/2/3 and then how to use that alias to shut down the interface:

```
RP/0/0/CPU0:router(config)# alias mycompany-10ge gigabitethernet1/0/2/3
RP/0/0/CPU0:router(config)# interface mycompany-10ge
RP/0/0/CPU0:router(config-if)# shutdown
RP/0/0/CPU0:router(config-if)# exit
RP/0/0/CPU0:router(config)#
```

The following example shows the use of a parameter name in an alias definition:

```
RP/0/0/CPU0:router(config)# alias shint (intname) show interface $intname
```

The following example shows an alias defined with one parameter and two commands:

```
RP/0/0/CPU0:router(config)# alias shint_both (intname) show interface $intname;show run
interface $intname
```

The following example shows the use of the alias shint\_both in EXEC mode:

```
RP/0/0/CPU0:router(exec)# shint_both(gigabitethernet1/2/3/4)
```

Two commands are issued, as follows:

```
RP/0/0/CPU0:router(exec)# show interface gigabitethernet1/2/3/4; show run interface
gigabitethernet1/2/3/4
```

## Related Commands

Command	Description
<a href="#">show aliases</a>	Displays a summary of all command aliases.

# apply-template

To apply a template to the target configuration, use the **apply-template** command in global configuration mode.

**apply-template** *template-name* [(*param-list*)]

## Syntax Description

<i>template-name</i>	Name of the template to be applied to the running configuration. Use the <b>template</b> command to define a template.
<i>param-list</i>	(Optional) Up to five template parameters.

## Command Default

No templates are applied to the target configuration.

## Command Modes

Global configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **apply-template** command to apply a template to the target configuration. Templates allow you to create a template name that represents a group of configuration commands.

Use the **template** command to define a template. Use the **end-template** command to exit template configuration mode and return to global configuration mode. Use the **show-running** command with the optional **template template-name** keyword and argument to display the contents of a template.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to define a template and then apply the template to the target configuration:

```
RP/0/0/CPU0:router(config)# template hostname-template
RP/0/0/CPU0:router(config-TPL)# hostname router1
RP/0/0/CPU0:router(config-TPL)# end-template
RP/0/0/CPU0:router(config)# apply-template hostname-template
```

**Related Commands**

Command	Description
<a href="#">end-template</a>	Exits template configuration mode.
<a href="#">show running-config</a>	Displays the current running (active) configuration.
<a href="#">template</a>	Defines a template.

# clear comment

To discard a comment associated with a configuration, use the **clear comment** command in any configuration mode.

**clear comment**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** Any configuration mode

Release	Modification
Release 3.6.0	This command was introduced.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **clear comment** command clears any comments that were added for a specific configuration in the configuration file. After you enter the **clear comment** command, enter the configuration for which you want to delete the comment on a separate line.

To enter configuration comments, enter ! followed by the comment. The comment you enter is associated with the next configuration entered. For example:

```
RP/0/0/CPU0:router#!router1 is located in xxx
RP/0/0/CPU0:router# hostname router1
RP/0/0/CPU0:router# commit
```

The comment is displayed in the output of the **show running-config** command:

```
RP/0/0/CPU0:router# show running-config
...
!router1 is located in xxx
hostname router1
...
```

**Task ID**

<b>Task ID</b>	<b>Operations</b>
Task ID for the feature or configuration mode impacted by the command	Operation for the feature or configuration mode impacted by the command

**Examples**

The following example shows how to discard the comment associated with the configuration ipv4 address 1.1.1.1 255.0.0.0.

```
RP/0/0/CPU0:router(config-if)# clear comment
RP/0/0/CPU0:router(config-if)# ipv4 address 1.1.1.1 255.0.0.0
```

# clear configuration commits

To delete old commit IDs from the commit database to free up disk space, use the **clear configuration commits** command in EXEC or administration EXEC mode.

**clear configuration commits** {*diskspace kilobytes*| *oldest number-of-commits*}

## Syntax Description

<b>diskspace</b> <i>kilobytes</i>	Deletes as many commit IDs (beginning with the oldest available commit ID) from the commit database as required to free the number of kilobytes (KB) specified for the <i>kilobytes</i> argument. The range for the number of kilobytes of disk space to free is 1 to 4194304.
	<b>Note</b> The amount of disk space freed may vary depending on the size and number of commits present in the commit database.
<b>oldest</b> <i>number-of-commits</i>	Deletes the number of commit IDs specified for the <i>number-of-commits</i> argument.
	<b>Note</b> Use the online help ( ? ) function to display the range of commit IDs available for deletion.

## Command Default

None

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for administration EXEC mode.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **clear configuration commits** command to delete the number of commit IDs available for rollback operations. The most recent 100 commits are retained by the system. As new commit IDs are added, the oldest commit IDs are discarded and are no longer available for rollback operations.



**Note** The **clear configuration commits** command deletes commits from the commit database only. The running configuration, thus, is not changed.



**Note** When a commit ID is deleted from the commit database, it is no longer available for rollback and can no longer be used to display commit changes (with the **show configuration rollback changes** command).

Use the **rollback configuration** command to roll back the current running configuration to a previous configuration. Use the **show configuration rollback changes** command to display a list of the commit IDs available for rollback operations or to display the changes that would be made by the **rollback configuration** command.

**Task ID**

Task ID	Operations
config-services	execute

**Examples**

The following example shows how to delete the oldest 16 commit IDs to free up disk space. After entering this command, you will be prompted to confirm the deletion.

```
RP/0/0/CPU0:router# clear configuration commits oldest 16

Deleting 16 rollback points '1000000021' to '1000000036'
256 KB of disk space will be freed. Continue with deletion?[confirm] y
```

**Related Commands**

Command	Description
<a href="#">rollback configuration</a>	Rolls back the configuration to a previous commit.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.



# clear configuration inconsistency

To clear an inconsistency alarm for an SDR configuration or admin plane configuration, use the **clear configuration inconsistency** command in EXEC or administration EXEC mode.

**clear configuration inconsistency**

## Syntax Description

This command has no keywords or arguments.

## Command Default

Administration EXEC mode: Clears the inconsistency alarms for the admin plane configuration.

EXEC mode: Clears the inconsistency alarms for an SDR configuration.

## Command Modes

EXEC

Administration EXEC

## Command History

Release	Modification
Release 3.4.0	This command was introduced.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

An inconsistency alarm is set when there is a failure to restore the configuration; this can occur during router startup, or when a line card or route processor (RP) card is inserted or removed.

If an inconsistency alarm is set, a message similar to the following example is displayed:

```
RP/0/0/CPU0:May 26 11:58:40.662 : cfgmgr-rp[130]: %MGBL-CONFIGCLI-3
  BATCH_CONFIG_FAIL : 28 config(s) failed during startup. To view
  failed config(s) use the command - "show configuration failed startup"

RP/0/0/CPU0:May 26 11:58:41.731 : cfgmgr-rp[130]:
  %MGBL-CONFIG-3-ADMIN_INCONSISTENCY_ALARM : Admin plane configuration
  inconsistency alarm has been raised. Configuration commits will be
  blocked until an ADMIN plane 'clear configuration inconsistency' command
  has been run to synchronize persisted admin plane configuration with
```

running admin configuration.

When the inconsistency alarm is set, all configuration commit operations fail until the alarm is cleared using the **clear configuration inconsistency** command. This command clears the alarm and removes the failed configuration.

For example, the following configuration commit fails to finish due to an existing inconsistency alarm:

```
RP/0/0/CPU0:router# configure

ADMIN plane running configuration is inconsistent with persistent
configuration.
No configuration commits will be allowed until an admin plane
'clear configuration inconsistency' command is performed.
RP/0/0/CPU0:router(config)# hostname router2
RP/0/0/CPU0:router(config)#commit

ADMIN plane running configuration is inconsistent with persistent
configuration.
No configuration commits will be allowed until an admin plane
'clear configuration inconsistency' command is performed.
```

Enter the **clear configuration inconsistency** command to clear the alarm and allow commit operations to continue.



#### Note

To reapply the failed configuration, you must reapply and recommit the configuration. Use the **load configuration failed** command with the **startup** keyword to populate the target configuration with the contents of the previous failed configuration from the startup configuration.

Use the **show configuration history** command with the **alarm** keyword to view the inconsistency alarm set and alarm clear events in the configuration history log.

#### Command Modes

To clear the inconsistency alarms for the admin plane configuration, enter the **clear configuration inconsistency** command in administration EXEC mode.

To clear the inconsistency alarms for an SDR configuration, enter the **clear configuration inconsistency** command in EXEC mode for that SDR.

#### Task ID

Task ID	Operations
config-services	execute

#### Examples

The following example shows how to clear the inconsistency alarms for the admin plane configuration by entering the **clear configuration inconsistency** command in administration EXEC mode:

```
RP/0/0/CPU0:router# admin
RP/0/0/CPU0:router(admin)# clear configuration inconsistency

Creating any missing directories in Configuration File system...OK
Initializing Configuration Version Manager...OK
Syncing ADMIN commit database with running configuration...OK
Re-initializing cache files...OK
Updating Commit Database. Please wait...[OK]
```

The following example shows how to clear the inconsistency alarms for an SDR configuration. The command is entered in EXEC mode and impacts only that SDR.

```
RP/0/0/CPU0:router# clear configuration inconsistency

Creating any missing directories in Configuration File system...OK
Initializing Configuration Version Manager...OK
Syncing commit database with running configuration...OK
Re-initializing cache files...OK
Updating Commit Database. Please wait...[OK]
```

In the following example, a history of the inconsistency alarms set and cleared for the SDR configuration are displayed using the **show configuration history** command with the **alarm** keyword:

```
RP/0/0/CPU0:router# show configuration history alarm

Sno.  Event      Info                                     Time Stamp
~~~~  ~~~~~
1     alarm      inconsistency alarm raised             Thu Jun 22 15:23:15 2009
2     alarm      inconsistency alarm cleared           Thu Jun 22 15:42:30 2009
3     alarm      inconsistency alarm raised             Sun Jul 9 13:39:57 2009
4     alarm      inconsistency alarm cleared           Sun Jul 9 14:15:48 2009
5     alarm      inconsistency alarm raised             Sat Jul 15 18:18:26 2009
6     alarm      inconsistency alarm cleared           Sat Jul 15 19:21:03 2009
```

#### Related Commands

Command	Description
<a href="#">load configuration failed</a>	Populates the target configuration with the contents of the previous failed configuration from the startup configuration.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.

# clear configuration inconsistency replica

To resolve configuration inconsistencies on a replica node, use the **clear configuration inconsistency replica** command in EXEC or administration EXEC mode.

**clear configuration inconsistency replica location** *node-id*

## Syntax Description

<b>location</b> <i>node-id</i>	Resolves the configuration inconsistencies on the designated node. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation.
--------------------------------	--

## Command Default

Administration EXEC mode: Resolves any configuration inconsistencies for the admin plane configuration.  
EXEC mode: Resolves any configuration inconsistencies for the SDR configuration.

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.6.0	This command was introduced.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

In administration EXEC mode, the replica node for the **clear configuration inconsistency replica** command is the standby designated system controller (DSC). In EXEC mode, the replica nodes are the route processors (RPs) that can become the designated secure domain router shelf controller (DSDRSC) .

Use the **clear configuration inconsistency replica** command if there is a configuration inconsistency between the standby DSC and the current active DSC; or alternatively, if the configuration on any nodes that could become the DSC is not the same as the configuration on the current DSC. To determine if you have a configuration inconsistency, use the **show configuration inconsistency replica** command.

To clear configuration inconsistencies for the admin plane configuration, enter the **clear configuration inconsistency replica** command in administration EXEC mode.

To clear configuration inconsistencies for an SDR configuration, enter the **clear configuration inconsistency replica** command in EXEC mode for that SDR.

### Task ID

Task ID	Operations
config-services	execute

### Examples

The following example shows how to clear any configuration inconsistencies for the DSC configuration by using the **clear configuration inconsistency replica** command in EXEC mode:

```
RP/0/0/CPU0:router# clear configuration inconsistency replica location 0/rp1/cpu0
The replica has been repaired.
```

### Related Commands

Command	Description
<a href="#">show configuration inconsistency replica</a>	Displays any configuration inconsistencies on a standby node.

## clear configuration sessions

To clear (end) an active configuration session, use the **clear configuration sessions** command in EXEC or administration EXEC mode.

**clear configuration sessions** *session-id*

### Syntax Description

<i>session-id</i>	Identifier for the configuration session to be terminated.
-------------------	--

### Command Default

None

### Command Modes

EXEC  
Administration EXEC

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **clear configuration sessions** command to clear a configuration session. This command can be used to end the configuration sessions of another user. Any uncommitted changes to a user's target configuration are discarded.

Use the **show configuration sessions** command to identify active configuration sessions.

When a configuration session is cleared, a message is displayed on the terminal of the terminated user. For example:

```
RP/0/0/CPU0:router(config)# This configuration session was terminated by user 'user_a' from
line 'aux0_0_CPU0'
```

### Task ID

Task ID	Operations
config-services	execute

### Examples

The following example shows how to clear an active configuration session. In this example, the **show configuration sessions** command displays the active configuration session. The **clear configuration sessions** command clears the active configuration session.

```
RP/0/0/CPU0:router# show configuration sessions

Current Configuration Session  Line          User          Date          Lock
00000211-002c409b-00000000    con0_RPs1_CPU0  UNKNOWN      Mon Feb  2 01:02:09 2009

RP/0/0/CPU0:router# clear configuration sessions 00000211-002c409b-00000000

session ID '00000211-002cb09b-00000000' terminated
```

### Related Commands

Command	Description
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.

# commit

To commit the target configuration to the active (running) configuration, use the **commit** command in any configuration mode.

**commit** [**best-effort**] [**comment** *line*] [**confirmed** [*seconds* | **minutes** *minutes*]] [**force**] [**label** *line*] [**replace**] [**save-running filename** *file\_path*]

## Syntax Description

<b>best-effort</b>	(Optional) Merges the target configuration with the running configuration and commits only valid changes (best effort). Some configuration changes might fail due to semantic errors.
<b>comment</b> <i>line</i>	(Optional) Assigns a comment to a commit. This text comment is displayed in the commit entry displayed in the output for the <b>show configuration commit list</b> command with the optional <b>detail</b> keyword.
<b>confirmed</b> [ <i>seconds</i>   <b>minutes</b> <i>minutes</i> ]	(Optional) Commits the configuration on a trial basis for the time specified in seconds or minutes. <b>Note</b> The <b>confirmed</b> option is not available in administration configuration mode.
<b>force</b>	(Optional) Forces a commit operation in low-memory conditions.
<b>label</b> <i>line</i>	(Optional) Assigns a meaningful label. This label is displayed (instead of the autogenerated commit ID) in the output for the <b>show configuration commit list</b> .
<b>replace</b>	(Optional) Replaces the entire running configuration with the contents of the target configuration.
<b>save-running filename</b> <i>file_path</i>	(Optional) Saves the running configuration to a specified file.

## Command Default

The default behavior is *pseudo-atomic*, meaning that all changes must succeed for the entire commit operation to succeed. If any errors are found, none of the configuration changes take effect.

## Command Modes

Any configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.



Release	Modification
Release 3.3.0	The <b>confirmed</b> <i>minutes</i> keyword and argument were added. The <b>confirmed</b> option is not available in administration configuration mode.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	Support was added for the <b>save-running filename</b> <i>file_path</i> keywords and argument in global configuration mode.
Release 3.8.0	Support was added for the <b>save-running filename</b> <i>file_path</i> keywords and argument in administration configuration mode.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Changes made during a configuration session are inactive until the **commit** command is entered. By default, the commit operation is *pseudo-atomic*, meaning that all changes must succeed for the entire commit operation to succeed. If any errors are found, none of the configuration changes takes effect.

To replace the default numeric ID for the commit, use the optional **label** keyword. This label is displayed (instead of the autogenerated commit ID) in the output for the **show configuration commit list** command.

Enter an optional comment with the **comment** keyword to provide additional information about the commit action. This comment is displayed in the output for the **show configuration commit list** command with the **detail** keyword.

Use the optional **confirmed** *minutes* keyword and argument to commit a configuration on a trial basis for a minimum of 30 seconds and a maximum of 300 seconds (5 minutes). During the trial configuration period, enter the **commit** command to confirm the configuration. If the **commit** command is not entered, then the system reverts to the previous configuration when the trial time period expires. The confirmed option is not available in administration configuration mode.

You can use the **commit** command in conjunction with the **load** command. Load a new configuration with the **load** command, and use the **commit** command with the **replace** keyword to have the loaded configuration become the active (running) configuration.

Use the optional **save-running filename** *file\_path* keywords and argument to save the running configuration to a specified file. To configure automatic saving of the configuration file on every commit, use the **configuration commit auto-save** command. If automatic saving of the configuration file is already enabled, specifying **save-running filename** *file\_path* with the **commit** command has no additional effect.

**Caution**

Saving the running configuration to a file is CPU intensive.

**Note**

If you use the **commit** command without previously loading a target configuration, a blank configuration is committed.

**Note**

If you use the **commit** command with the **replace** keyword, it does not affect the mode of an 8-port E1/T1 SPA. If the mode is E1 before using the **commit replace** command, it remains E1. However, since the default mode is T1, the router does not recognize that the mode is E1. To change the mode to T1, you must first use the **hw-module subslot cardtype e1** command to add the E1 mode into the configuration so that it correlates with the system. Then manually reload the router and it boots in T1 mode.

For more information regarding the **hw-module subslot cardtype** command, refer to *Cisco IOS XR Interface and Hardware Component Command Reference for the Cisco XR 12000 Series Router*.

**Task ID**

Task ID	Operations
Task ID for the feature or configuration mode impacted by the command	Operation for the feature or configuration mode impacted by the command

**Examples**

The following example shows how to commit the target configuration to the active running configuration. In this example, the **commit** command saves changes to the router hostname.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# hostname router1
RP/0/0/CPU0:router(config)# commit

RP/0/0/CPU0:Feb 21 04:42:57.017 : config[65689]: %MGBL-LIBTARCFG-6-COMMIT :
Configuration committed by user 'user_a'.
Use 'show configuration commit changes 1000000033' to view the changes.
```

**Examples**

The following example shows how to use the **commit** command with the optional **comment line** keyword and argument to assign a text description to the commit operation. The comment is then displayed in the output of the **show configuration commit list** command with the **detail** keyword.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# hostname router2
RP/0/0/CPU0:router(config)# commit comment new name for router

RP/0/RP0/CPU0:Feb 21 04:42:57.017 : config[65689]: %MGBL-LIBTARCFG-6-COMMIT :
Configuration committed by user 'user_a'. Use 'show configuration commit
changes 1000000226' to view the changes.

RP/0/0/CPU0:router2(config)# end
RP/0/0/CPU0:router2# show configuration commit list detail
```

```

1) CommitId: 1000000226          Label: NONE
   UserId:    user_a             Line:  con0_RP1_CPU0
   Client:    CLI                Time:  12:59:26 UTC Wed Feb 04 2004
   Comment:   new name for router

2) CommitId: 1000000225          Label: NONE
   UserId:    user_a             Line:  con0_RP1_CPU0
   Client:    CLI                Time:  12:58:32 UTC Wed Feb 04 2004
   Comment:   NONE

```

## Examples

The following example shows how to use the **commit** command with the optional **label line** keyword and argument to change the commit ID to a text label for easier identification. The label is then displayed in the output of the **show configuration commit list** command.

```

RP/0/0/CPU0:router2# configure
RP/0/0/CPU0:router2(config)# hostname router3
RP/0/0/CPU0:router2(config)# commit label new_name

RP/0/RP0/CPU0:Feb 21 04:42:57.017 : config[65689]: %MGBL-LIBTARCFG-6-COMMIT :
Configuration committed by user 'user_a'.
Use 'show configuration commit changes 1000000227' to view the changes.

RP/0/0/CPU0:router3(config)# end
RP/0/0/CPU0:router3# show configuration commit list

SNo. Label/ID      User      Line      Client      Time Stamp
~~~~ ~~~~~~
1     new_name      user_a    con0_RPs1_C  CLI        13:00:53 UTC Wed Feb 04 2004
2     1000000226    user_a    con0_RPs1_C  CLI        12:59:26 UTC Wed Feb 04 2004
3     1000000225    user_a    con0_RPs1_C  CLI        12:58:32 UTC Wed Feb 04 2004

```

## Examples

The following example shows how to use the **commit** command with the optional **confirmed** keyword and number *argument*. The configuration changes are committed only for the specified number of seconds. You can then either confirm the commit operation or discard the changes.

```

RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# hostname router3
RP/0/0/CPU0:router(config)# commit confirmed 30
RP/0/0/CPU0:router3(config)# end

```

## Related Commands

Command	Description
<a href="#">abort</a>	Ends a configuration session without saving changes to the target configuration.
<a href="#">configuration commit auto-save</a>	Configures automatic saving of the running configuration to a specified file on every commit.
<a href="#">end</a>	Terminates a session and returns the router to EXEC mode from any configuration mode.
<a href="#">exit</a>	Exits from the current configuration mode to the next higher command mode or logs out of the terminal session.
<a href="#">load</a>	Populates the target configuration with the contents of a previously saved configuration file.

Command	Description
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

## configuration commit auto-save

To enable automatic saving of the running configuration to a specified file on every commit, use the **configuration commit auto-save** command in global configuration mode. To disable automatic saving of the running configuration to a specified file on every commit, use the **no** form of the command.



### Caution

Saving the running configuration to a file is CPU intensive.

```
configuration commit auto-save filename file_path
no configuration commit auto-save
```

### Syntax Description

<b>filename</b> <i>file_path</i>	Specifies the location to which to save the running configuration.
----------------------------------	--

### Command Default

None

### Command Modes

Global configuration  
Administration configuration

### Command History

Release	Modification
Release 3.7.0	This command was introduced.
Release 3.8.0	This command was first supported in administration configuration mode.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **configuration commit auto-save** command configures the system to save the running configuration to the specified file and location every time a **commit** command is run. Alternatively, you can save the configuration on a one-time basis by specifying the **save-running** keyword when you run the **commit** command.

### Task ID

Task ID	Operations
config-services	write

### Examples

The following example shows how to configure the system to save the running configuration to the file `disk0:/usr` whenever the **commit** command is used:

```
RP/0/0/CPU0:router(config)# configuration commit auto-save filename disk0:/usr
```

### Related Commands

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.

# configure

To enter global configuration mode or administration configuration mode, use the **configure** command in EXEC or administration EXEC mode.

**configure** [**exclusive**| **terminal**]

## Syntax Description

<b>exclusive</b>	(Optional) Locks the router configuration. The system configuration can be made only from the login terminal.
<b>terminal</b>	(Optional) Configures the system from the login terminal. This is the default.

## Command Default

If the **configure** command is entered without a keyword, the system is configured from the login terminal.

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Configuration modes are used to enter changes to a target configuration session and commit those changes to the running configuration. A router running Cisco IOS XR software contains multiple configurations:

- The configuration for a specific secure domain router (SDR). Each SDR has its own configuration that is modified when a user logs into an SDR and enters global configuration mode. This mode is used to configure SDR-specific features such as routing protocols.
- The administration configuration for system-wide resources and settings. Some features, such as creating SDRs, can be configured only in administration configuration mode.

### Global Configuration Mode

Use the **configure** command in EXEC mode to enter global configuration mode and create a new target configuration for an SDR. From global configuration mode, you can enter any configuration mode. Configuration changes entered in global configuration mode impact the SDR to which the user is currently logged in.

### Administration Configuration Mode

Use the **configure** command in administration EXEC mode to enter administration configuration mode and create a new target configuration. From administration configuration mode, you can enter any administration configuration mode. Configuration changes entered in administration configuration mode can impact resources for the entire router. See the command reference documentation for a specific command to determine the impact of commands entered in administration configuration mode.

### Router Prompt

After you enter the **configure** command, the system appends “(config)” to the router prompt, indicating that the router is in a configuration mode. For example:

- The following prompt indicates that you are in global configuration mode for an SDR:  
RP/0/0/CPU0:router (config) #
- The following prompt indicates that you are in administration configuration mode:  
RP/0/0/CPU0:router (admin-config) #

### Locking a Configuration Session

To lock the configuration so that no other user can commit changes to the running configuration during your configuration session, issue the **configure** command with the **exclusive** keyword.

### Committing Changes and Returning to EXEC or Administration EXEC Mode

Changes to the target configuration remain inactive until the **commit** command is entered. To leave global configuration or administration configuration mode and return to the EXEC or administration EXEC prompt, issue the **end** or **exit** command; you are prompted to commit any uncommitted changes.

To leave configuration mode and return directly to EXEC or administration EXEC mode without being prompted to commit changes and without saving changes to the target configuration, enter the **abort** command in any configuration mode.

### Examples

The following example shows how to enter global configuration mode from EXEC mode and then enter interface configuration mode to configure an IPv4 address for Gigabit Ethernet interface 0/1/0/0. In the



example, the **configure** command commits the configuration, and the **end** command terminates the configuration session and return the router to EXEC mode.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/1/0/0
RP/0/0/CPU0:router(config-if)# ipv4 address 1.1.1.1 255.0.0.0
RP/0/0/CPU0:router(config-if)# commit
RP/0/0/CPU0:router(config-if)# end
RP/0/0/CPU0:router#
```

The following example shows how to enter administration configuration mode and then configure an SDR. In this example, the user also enters SDR configuration mode.

```
RP/0/0/CPU0:router# admin
RP/0/0/CPU0:router(admin)# configure
RP/0/0/CPU0:router(admin-config)# sdr rname
RP/0/0/CPU0:router(admin-config-sdr:rname)# location 0/0/*
RP/0/0/CPU0:router(admin-config-sdr:rname)# location 0/5/*
RP/0/0/CPU0:router(admin-config-sdr:rname)# end
```

#### Related Commands

Command	Description
<a href="#">abort</a>	Ends a configuration session without saving changes to the target configuration.
<a href="#">end</a>	Terminates a session and returns the router to EXEC mode from any configuration mode.
<a href="#">exit</a>	Exits from the current configuration mode to the next higher command mode or logs out of the terminal session.
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

## description (interface)

To add a description to an interface configuration, use the **description** command in interface configuration mode. To remove the description, use the **no** form of this command.

**description** *comment*

**no description**

### Syntax Description

<i>comment</i>	Comment or a description applied to the interface. The maximum number of characters is 1022.
----------------	--

### Command Default

No description is configured.

### Command Modes

Interface configuration

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **description** command to add a description to an interface configuration. The maximum number of characters is 1022.

**Task ID**

Task ID	Operations
interface	read, write

**Examples**

The following example shows how to add a description to an interface configuration. In this example, the **description** command names a Management Ethernet interface.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface mgmteth 0/
RP
1/CPU0/0
RP/0/0/CPU0:router(config-if)# description Management Ethernet Interface
```

**Related Commands**

Command	Description
show interfaces	Displays statistics for all interfaces configured on the router or for a specific node.

# do

To execute an EXEC mode command from a configuration mode, use the **do** command in any configuration mode.

**do** *exec-command*

## Syntax Description

<i>exec-command</i>	EXEC mode command to be executed.
---------------------	-----------------------------------

## Command Default

None

## Command Modes

Any configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

To display the various EXEC mode commands that are available to execute with the **do** command, use the online help (?) function at the configuration mode prompt.



### Note

The **configure** and **describe** commands are not supported with the **do** command.

**Task ID**

Task ID	Operations
Task ID for the EXEC command that you are using	read

**Examples**

The following example shows how to execute an EXEC command from interface configuration mode. In this example, the **do** command displays output from the **show protocols** command within interface configuration mode:

```
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/1/0/1
RP/0/0/CPU0:router(config-if)# do show protocols

Routing Protocol "BGP 1"

Address Family IPv4 Unicast:
  Distance: external 20 internal 200 local 200
```

# end

To terminate a configuration session and return directly to EXEC or administration EXEC mode, use the **end** command in any configuration mode.

**end**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** Any configuration mode

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **end** command to exit any configuration mode and return directly to EXEC or administration EXEC mode. If you enter this command without committing the changes to the target configuration, you are prompted to do so:

```
Uncommitted changes found, commit them before exiting(yes/no/cancel)?[cancel]:
```

- Entering **yes** saves configuration changes to the running configuration file, exits the configuration session, and returns the router to EXEC or administration EXEC mode.  
If errors are found in the running configuration, the configuration session does not end. To view the errors, enter the **show configuration** (config) command with the **failed** keyword.

- Entering **no** exits the configuration session and returns the router to EXEC or administration EXEC mode without committing the configuration changes.
- Entering **cancel** leaves the router in the current configuration session without exiting or committing the configuration changes.



**Note** Entering **Ctrl-Z** is functionally equivalent to entering the **end** command.

Use the **abort** command to exit the configuration session and return to EXEC or administration EXEC mode without being prompted to commit changes and without saving changes to the target configuration.

### Task ID

Task ID	Operations
config-services	read, write

### Examples

The following example shows how to use the **end** command to end a configuration session. Changes stored in the target configuration are committed by answering **yes**.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/0
RP/0/0/CPU0:router(config-if)# ipv4 address 1.1.1.1 255.0.0.0
RP/0/0/CPU0:router(config-if)# end
```

```
Uncommitted changes found, commit them before exiting(yes/no/cancel)? [cancel]: yes
RP/0/0/CPU0:router#
```

### Related Commands

Command	Description
<a href="#">abort</a>	Ends a configuration session without saving changes to the target configuration.
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">exit</a>	Exits from the current configuration mode to the next higher command mode or logs out of the terminal session.
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.

# end-template

To exit template configuration mode and return to global configuration mode, use the **end-template** command in template configuration mode.

## end-template

### Syntax Description

This command has no keywords or arguments.

### Command Default

No default behavior or values.

### Command Modes

Template configuration

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **end-template** command to exit template configuration mode after you have completed the template definition.

To define a template, use the **template** command. To apply a template to the target configuration, use the **apply-template** command. To view the contents of a template, use the **show running-config** command with the optional **template** *template-name* keyword and argument.



**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to enter template configuration mode, define a template named “hostname-template” and then exit from template configuration mode:

```
RP/0/0/CPU0:router(config)# template hostname-template
RP/0/0/CPU0:router(config-TPL)# hostname router-cs1
RP/0/0/CPU0:router(config-TPL)# end-template
RP/0/0/CPU0:router(config)#
```

**Related Commands**

Command	Description
<a href="#">end</a>	Terminates a session and returns the router to EXEC mode from any configuration mode.

# exit

To close an active terminal session and log off the router, use the **exit** command in EXEC or administration EXEC mode.

To return the router to the next higher configuration mode, use the **exit** command in any configuration mode.

**exit**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** EXEC  
Any configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

To log off from a terminal session, enter the **exit** command in EXEC or administration EXEC mode.

When exiting from global or administration configuration mode to EXEC or administration EXEC mode, you are prompted to commit any uncommitted configuration changes.

```
Uncommitted changes found, commit them before exiting(yes/no/cancel)?[cancel]:
```

- Entering **yes** saves configuration changes to the running configuration file, exits the configuration session, and returns the router to EXEC or administration EXEC mode. If errors are found in the running configuration, the configuration session does not end. To view the errors, enter the **show configuration** (config) command with the **failed** keyword.
- Entering **no** exits the configuration session and returns the router to EXEC or administration EXEC mode without committing the configuration changes.
- Entering **cancel** leaves the router in the current configuration session without exiting or committing the configuration changes.



**Note** Entering the **exit** command from global configuration is functionally equivalent to entering the **end** command.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to return the router to the next higher command mode. In this example, the **exit** command exits from interface configuration mode and returns to global configuration mode. The **exit** command is entered a second time to exit from global configuration mode and return to EXEC mode. Because the configuration has not been committed explicitly (with the **commit** command), the system prompts to commit the configuration changes made during the session.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface tengige 0/2/0/0
RP/0/0/CPU0:router(config-if)# ipv4 address 1.1.1.1 255.0.0.0
RP/0/0/CPU0:router(config-if)# exit
RP/0/0/CPU0:router(config)# exit
Uncommitted changes found, commit them before exiting(yes/no/cancel)?[cancel]: yes
```

The following example shows how to use the **exit** command from EXEC mode to log off from a terminal session:

```
RP/0/0/CPU0:router# exit
router con0_RP1_CPU0 is now available
Press RETURN to get started.
```

**Related Commands**

Command	Description
<a href="#">abort</a>	Ends a configuration session without saving changes to the target configuration.
<a href="#">commit</a>	Merges the target configuration to the running configuration.

Command	Description
<a href="#">end</a>	Terminates a session and returns the router to EXEC mode from any configuration mode.

# hostname

To specify or modify the hostname for the router, use the **hostname** command in global configuration mode.

**hostname** *name*

## Syntax Description

<i>name</i>	New hostname for the router.
-------------	------------------------------

## Command Default

The factory-assigned default hostname is “ios.”

## Command Modes

Global configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The hostname is used in prompts and default configuration filenames.

No blank or space characters are permitted as part of a name. Do not expect case to be preserved. Uppercase and lowercase characters look the same to many Internet software applications. It may seem appropriate to capitalize a name the same way you might do in English, but conventions dictate that computer names appear all lowercase. For more information, see RFC 1178, *Choosing a Name for Your Computer*.

**Task ID**

<b>Task ID</b>	<b>Operations</b>
root-lr	read, write

**Examples**

The following example shows how to change the router hostname:

```
RP/0/0/CPU0:router(config)# hostname router1
```

# load

To populate the target configuration with the contents of a previously saved configuration file, use the **load** command in global configuration or administration configuration mode.

**load** *device:directory-path*

## Syntax Description

<i>device: directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.
-------------------------------	---

## Command Default

If the full path of the file is not specified, the present working directory is used.

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **load** command to populate the target configuration with the contents of a previously saved configuration. When loading a file, you must specify the device, directory path, and filename of the configuration file.

Use the **commit** command in conjunction with the **load** command. Load a new configuration with the **load** command, and use the **commit** command with the **replace** keyword to have the loaded configuration become the active (running) configuration.

Use the **show configuration failed (config)** command with the optional **load** keyword to display syntax errors that occurred during the last load operation.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to load a target configuration file into the current configuration session. The current configuration session is then populated with the contents of the file.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# load disk1:myconfig.cfg
RP/0/0/CPU0:router(config)# show config

Building configuration...
interface TenGigE 0/3/0/0
  description My 10 GE Interface
  ipv4 address 10.10.11.20 255.0.0.0
!
end
```

**Related Commands**

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.



# load commit changes

To populate the target configuration with changes from previous configuration commits, use the **load commit changes** command in global configuration or administration configuration mode.

**load commit changes** {*commit-id*| **since** *commit-id*| **last** *number-of-commits*}

## Syntax Description

<i>commit-id</i>	Specific configuration commit.
<b>since</b> <i>commit-id</i>	Loads all configuration changes committed into the target buffer since (and including) a specific configuration commit, <i>commit-id</i> .
<b>last</b> <i>number-of-commits</i>	Loads the configuration changes into the target buffer that have been made during the last number of configuration commits specified with the <i>number-of-commits</i> argument.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **load commit changes** command to populate the target configuration with changes from previous configuration commits. The changes are not applied until you enter the **commit** command.

Use the **show configuration** (config) command to display the target configuration.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to populate the target configuration with changes from a previous configuration commit:

```
RP/0/0/CPU0:router(config)# load commit changes since 1000000006
Building configuration...
Loading.
223 bytes parsed in 1 sec (222)bytes/sec
```

# load configuration failed

To populate the target configuration with the contents of the previous failed configuration commit, use the **load configuration failed** command in global configuration or administration configuration mode.

```
load configuration failed {commit| startup [previous number-of-reloads] [noerror]}
```

## Syntax Description

<b>commit</b>	Loads the failed configuration from the last commit.
<b>startup</b>	Loads the failed configuration from the startup configuration.
<b>previous <i>number-of-reloads</i></b>	(Optional) Loads the failed configurations from a previous router reload. Valid <i>number-of-reloads</i> values are 1 to 4.
<b>noerror</b>	(Optional) Excludes the error reasons when the failed configurations are loaded.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for the <b>commit</b> keyword. Support was added for the <b>startup</b> keyword. Support was added for the <b>previous <i>number-of-reloads</i></b> keyword and argument. Support was added for the <b>noerror</b> keyword.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.

Release	Modification
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **load configuration failed** command to populate the target configuration with the contents of the previous failed configuration commit.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to populate the target configuration with the contents of the previous failed configuration commit:

```
RP/0/0/CPU0:router(config)# load configuration failed
```

**Related Commands**

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.

# load configuration removed

To populate the target configuration with the contents of the previous removed configuration, use the **load configuration removed** command in global configuration or administration configuration mode.

**load configuration removed** *config-id*

<b>Syntax Description</b>	<i>config-id</i>	Identifier of the removed configuration to load.
---------------------------	------------------	--

<b>Command Default</b>	None
------------------------	------

<b>Command Modes</b>	Global configuration Administration configuration
----------------------	--

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	Release 3.5.0	This command was introduced.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **load configuration removed** command to populate the target configuration with the contents of the removed configuration during installation operations.

<b>Task ID</b>	<b>Task ID</b>	<b>Operations</b>
	config-services	read, write

**Examples**

The following example shows how to populate the target configuration with the contents of the removed configuration during installation:

```
RP/0/0/CPU0:router(config)# load configuration removed 20070316021626.cfg
```

**Related Commands**

Command	Description
<a href="#">show configuration persistent</a>	Displays the configuration removed during installation operations.

# load rollback changes

To populate the target configuration with the contents of a previous configuration, use the **load rollback changes** command in global configuration or administration configuration mode.

**load rollback changes** {*commit-id*| **last** *number-of-commits*| **to** *commit-id*}

## Syntax Description

<i>commit-id</i>	Rolls back the configuration changes for a specific configuration commit.
<b>last</b> <i>number-of-commits</i>	Rolls back to the configuration that existed before the last number of commits (specified with the <i>number-of-commits</i> argument) were made.
<b>to</b> <i>commit-id</i>	Rolls back to the running configuration that existed before the configuration specified with the <i>commit-id</i> argument.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for administration configuration mode.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **load rollback changes** command to load rollback configuration changes to the target configuration. This command is similar to the **rollback configuration** command. The difference between the commands is that the **load rollback changes** command copies the rollback changes to the target configuration and does not commit the changes until the changes are explicitly committed with the **commit** command.

Use the **show configuration rollback changes** command to display rollback changes.

**Task ID**

Task ID	Operations
config-services	read, write

**Examples**

The following example shows how to populate the target configuration with the contents of a previous configuration:

```
RP/0/0/CPU0:router(config)# load rollback changes 1000000004
Building configuration...
Loading.
302 bytes parsed in 1 sec (301)bytes/sec
```



# man

Cisco IOS XR software provides online help for standard command-line interface (CLI) commands using manual (man) pages. To display manual pages, use the **man** command in EXEC mode.

**man** {**command** *command-name*| **feature** [*feature-name* ]| **keyword** *keywords*}

## Syntax Description

<b>command</b> <i>command-name</i>	Displays the manual pages for a specific command. The <i>command-name</i> argument must include the complete command name.
<b>feature</b> [ <i>feature-name</i> ]	Displays all commands available in the feature. Use the <b>man</b> command with the <b>feature</b> keyword to list the available feature names.
<b>keyword</b> <i>keywords</i>	Displays a list of command names that match the keywords. Enter one or more keywords to match in a command. When entering multiple keywords, the keywords must be entered in the same sequential order as they are in the command.

## Command Default

None

## Command Modes

EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

You must have the documentation PIE installed before you can use the **man** command. If you attempt to run this command without the documentation PIE installed, an error is displayed as shown in the following example:

```
RP/0/0/CPU0:router# man command show install

Building index table...
Warning. Unable to get directory info for '/pkg/man' :No such file or directory.
Discarding!
man [5521656]:Building index table failed. No entries found
```

For information about installing optional software PIEs, see the *Upgrading and Managing Cisco IOS XR Software* module in *Cisco IOS XR System Management Configuration Guide for the Cisco XR 12000 Series Router*.

Use the **man** command to display the manual pages for a specific command on the basis of the command name, a feature, or a keyword. Each man page contains the command name, syntax, command mode, usage, examples, and related commands.

The **man** command queries and displays command information about the router. A query can be based on keywords or a feature. The **feature** *feature-name* keyword and argument display all commands that match the feature. For example, entering **man feature c12k - base-1** displays all commands that match the c12k-base-1 feature. The **keyword** *keywords* keyword and argument display all commands that contain the specified keyword. For example, **man keyword ipv4** displays all commands that contain ipv4.

**Task ID**

Task ID	Operations
basic-services	read

**Examples**

The following example shows how to display the manual page for the **arp timeout** command:

```
RP/0/0/CPU0:router# man command arp timeout
```

```
COMMAND
arp timeout
```

```
DESCRIPTION
```

```
To specify how long dynamic entries learned on an interface remain in the
Address Resolution Protocol (ARP) cache, use the arp timeout command in
interface configuration mode. To remove the arp timeout command from the
configuration file and restore the system to its default condition with
respect to this command, use the no form of this command.
```

```
arp timeout seconds
```

```
no arp timeout<seconds>
```

```
SYNTAX DESCRIPTION
```

```
seconds
```

Time, in seconds, for which an entry remains in the ARP cache. The range is from 0 to 4294967. A value of 0 means that entries are never cleared from the cache. The default is 14400.

DEFAULTS

Entries remain in the ARP cache for 14400 seconds (4 hours).

COMMAND MODES

Interface configuration

COMMAND HISTORY

Release  
Modification

Release 2.0  
This command was introduced.

USAGE GUIDELINES

To use the arp timeout command, you must be a member of a user group associated with the cef task ID.

For detailed information about user groups and task IDs, refer to the Configuring AAA Services on Cisco IOS-XR Software module of the Cisco IOS-XR System Security Configuration Guide.

This command is ignored when issued on interfaces that do not use ARP. Also, ARP entries that correspond to the local interface or that are statically configured by the user never time out.

The show interfaces command displays the ARP timeout value in hours:minutes:seconds, as follows:

```
* * * * * START OF LISTING * * * * *
ARP type: ARPA, ARP Timeout 04:00:00
* * * * * END OF LISTING * * * * *
```

EXAMPLES

The following example shows how to set the ARP timeout to 3600 seconds to allow entries to time out more quickly than the default:

```
* * * * * START OF LISTING * * * * *
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface MgmtEth 0/RP1/CPU0/0
RP/0/0/CPU0:router(config-if)# arp timeout 3600
* * * * * END OF LISTING * * * * *
```

RELATED COMMANDS

Command  
Description

clear arp-cache  
Deletes all dynamic entries from the ARP cache.

show arp (cache)  
Displays the entries in the ARP table.

show interfaces  
Displays statistics for all interfaces configured on the networking device.

## more

To display the contents of a file, use the **more** command in EXEC or administration EXEC mode.

```
more [/ascii|/binary|/ebcdic] filesystem:directory-path location [node-id| all] { | begin regular-expression | exclude regular-expression | | include regular-expression }
```

### Syntax Description

<b>/ascii</b>	(Optional) Displays a binary file in ASCII format.
<b>/binary</b>	(Optional) Displays a file in hexadecimal or text format.
<b>/ebcdic</b>	(Optional) Displays a binary file in ebcdic format.
<i>filesystem:directory-path</i>	File system location of the file to be displayed. Include the file system alias for the <i>filesystem</i> argument, followed by a colon, and the directory path of the file to be displayed.
<b>location</b> [node-id   all]	(Optional) Displays the contents of a file on a designated node or all nodes.
<i>regular-expression</i>	(Optional) Regular expression found in the file.
	Vertical bar (the “pipe” symbol) indicates that an output processing specification follows.
<b>begin</b>	(Optional) Begins unfiltered output of the <b>more</b> command with the first line that contains the regular expression.
<b>exclude</b>	(Optional) Displays output lines that do not contain the regular expression.
<b>include</b>	(Optional) Displays output lines that contain the regular expression.

### Command Default

None

### Command Modes

EXEC  
Administration EXEC

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.

Release	Modification
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **more** command to display any text file, especially an ASCII file stored on the router or accessible through the network. The file can be a configuration file or any other text file.

### Filtering Output

This table shows filter options for the output displayed by the **more** command.

**Table 1: Filtering Options**

Command	Purpose
<b>more filesystem:</b>   <b>begin</b> <i>regular-expression</i>	Begins unfiltered output of the <b>more</b> command with the first line that contains the regular expression.
<b>more filesystem:</b>   <b>exclude</b> <i>regular-expression</i>	Displays output lines that do not contain the regular expression.
<b>more filesystem:</b>   <b>include</b> <i>regular-expression</i>	Displays output lines that contain the regular expression.

### Adding a Filter at the --More-- Prompt

You can also specify a filter at the --More-- prompt of a **more** command output. To filter output from the --More-- prompt, enter a forward slash ( / ) followed by a regular expression. The filter remains active until the command output finishes or is interrupted (using **Ctrl-Z** or **Ctrl-C**).

- A second filter cannot be specified at a --More-- prompt if a filter has already been specified at the original command or at a previous --More-- prompt.
- The minus sign ( - ) preceding a regular expression displays output lines that do not contain the regular expression.

- The plus sign (+) preceding a regular expression displays output lines that contain the regular expression.

**Note**

After you specify a filter for a **more** command, you cannot specify another filter at the next **--More--** prompt. The first specified filter remains until the **more begin** command output finishes or until you interrupt the output. The use of the keyword does not constitute a filter.

**Task ID**

Task ID	Operations
filesystem	execute

**Examples**

The following example shows partial sample output from the **more** command. The output displays a configuration file saved on the hard disk drive.

```
SDR# more harddisk:/user/alternate.cfg
!! Last configuration change at 15:52:55 UTC Fri Feb 13 2009 by UNKNOWN
!
line console
exec-timeout 0 0
!
interface MgmtEth0/RP1/CPU0/0
  ipv4 address 10.32.45.154 255.0.0.0
!
interface TenGigE0/1/0/0
  ipv4 address 10.32.45.155 255.0.0.0
  keepalive disable
!
interface TenGigE0/1/0/1
  ipv4 address 10.32.45.156 255.0.0.0
  keepalive disable
!
interface TenGigE0/1/0/2
/ip
  ipv4 address 10.32.45.157 255.0.0.0
  keepalive disable
!
interface TenGigE0/1/0/3
  ipv4 address 10.32.45.158 255.0.0.0
  keepalive disable
!
interface TenGigE0/2/0/0
  ipv4 address 10.32.45.159 255.0.0.0
  keepalive disable
!
--More--
```

The following example shows partial sample output from the **more** command. The output begins with unfiltered output from the first line that contains the regular expression “ipv4.” In this example, a new search is specified that begins with output lines that contain the regular expression “ipv4.”

```
RP/0/0/CPU0:router# more disk0:config.backup | begin ipv4
ipv4 address 2.2.2.2 255.255.255.255
!
interface TenGigE0/3/1/0
  shutdown
```

```

!
interface TenGigE0/3/1/2
 shutdown
!
interface TenGigE0/2/1/0
 ipv4 address 1.1.1.1 255.255.255.0
 keepalive disable
!
interface TenGigE0/2/1/1
 ipv4 address 1.1.1.1 255.255.255.0
 keepalive disable
!
interface TenGigE0/2/1/2
 ipv4 address 1.1.1.1 255.255.255.0
 keepalive disable
!
interface TenGigE0/2/1/3
 shutdown
!
 /ipv4

filtering...
 ipv4 address 1.1.1.1 255.255.255.0
 proxy-arp disable
 shutdown
!
interface TenGigE 0/1/0/0
 ipv4 address 1.1.1.1 255.255.255.0
 proxy-arp disable
!
route ipv4 0.0.0.0/0 12.25.26.5
route ipv4 223.255.254.254/32 12.25.0.1
end

```

The following example shows partial sample output of the **more** command on the sample file `config.backup` in `disk0`. The command usage is `more disk0:config.backup | include log`. At the `--More--` prompt, a new search is specified that begins with output lines that contain the regular expression “aaa.”

```

RP/0/0/CPU0:router# more disk0:config.backup | include log

logging trap
logging trap informational
logging console debugging
logging history size 1
.
.
.

/aaa

filtering...
aaa authentication login default none

```

The following example shows partial sample output from the **more** command. The output excludes lines that contain the regular expression “alias.” In this example, at the `--More--` prompt, a new search is specified, beginning with output lines that contain the regular expression “ipv4 address.”

```

RP/0/0/CPU0:router# more disk0:myconfig/file | exclude alias

Building configuration...
!! Last configuration change at 18:17:00 UTC Thu May 16 2009 by lab
!
hostname router
line console
 exec-timeout 0 0
 width 132
 length 0
 session-timeout 0
/ipv4 address

```

 more

```
filtering...
ipv4 address 10.10.1.1 255.255.255.255
!
interface Loopback200
  ipv4 address 10.20.1.1 255.255.255.255
!
interface TenGigE0/0/0/0
  ipv4 address 10.30.1.1 255.255.0.0
  keepalive 100
!
interface preconfigure TenGigE0/1/0/1
  shutdown
end
```

**Related Commands**

Command	Description
<a href="#">show</a>	Displays system status and configuration.



## pwd (config)

To display the current configuration submode from a configuration submode, use the **pwd** command in any supported configuration submode.

**pwd**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** Any subconfiguration mode

Command History	Release	Modification
	Release 3.5.0	This command was introduced.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

**Examples** The following example shows how to use the **pwd** command from an interface configuration submode:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface tengige 0/6/4/5
RP/0/0/CPU0:router(config-if)# pwd

interface TenGigE0/6/4/5
RP/0/0/CPU0:router(config-if)#
```

## rollback configuration

To roll back the running configuration to a previous configuration, use the **rollback configuration** command in EXEC or administration EXEC mode.

**rollback configuration** {*last number-of-commits*| *to commit-id*} {*best-effort*| **force**} [*label label*] **comment** *comment*

### Syntax Description

<b>last</b> <i>number-of-commits</i>	Rolls back to the configuration that existed before the last number of commits (specified with the <i>number-of-commits</i> argument) were made.
<b>to</b> <i>commit-id</i>	Rolls back to the running configuration that existed before the configuration specified with the <i>commit-id</i> argument.
<b>best-effort</b>	Rolls back to the configuration that existed before the last n commits, and commits only valid changes (best effort). Some configuration changes might fail due to semantic errors.
<b>force</b>	(Optional) Specifies to override any commit blocks.
<b>label</b> <i>label</i>	(Optional) Assigns a text label to this rollback. The <i>label</i> argument must begin with a letter.
<b>comment</b> <i>comment</i>	(Optional) Assigns a text comment to this rollback. The <i>comment</i> argument can be up to 60 characters long.

### Command Default

None

### Command Modes

EXEC  
Administration EXEC

**Command History**

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	This command was added to administration EXEC mode.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.
Release 4.0.0	The <b>best-effort</b> keyword was added.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Each time the **commit** command is entered, a commit ID is assigned to the new configuration. You can revert the system to the configuration of a previous commit ID with the **rollback configuration** command:

- Use the **to** keyword to revert to the configuration that existed *before* the configuration specified with the *commit-id* argument.
- Use the **last** keyword to revert to the configuration that existed *before* the last number of configuration commits (specified with the *number-of-commits* argument) were made.
- Use **show configuration commit list** to display a list of the commit IDs available for rollback operations.

**Note**

The most recent 100 commits are retained by the system. As new commit IDs are added, the oldest commit IDs are discarded and are no longer available for rollback operations.

Use the **force** keyword to override commits that would fail otherwise. This is useful in the event of a low-memory condition on the router, to revert to a commit that would remove a configuration that caused the low-memory condition.

**Note**

The rollback operation may fail if you try to rollback two (or more) commits where the individual commits involve the configuration and removing of the configuration of the same item, and there is a dependency of one item over another in any of the individual commit operations.

**Task ID**

Task ID	Operations
root-lr (EXEC)	read, write
root-system (administration EXEC)	read, write

**Examples****Rolling Back to a Specific Commit ID**

The following example shows how to roll back to a specific commit ID. In this example, the **show configuration commit list** command displays the available rollback points. The configuration is then rolled back to a prior commit with the **rollback configuration** command.

```
RP/0/0/CPU0:router# show configuration commit list

SNo. Label/ID      User      Line      Client      Time Stamp
~~~~ ~~~~~~      ~~~~~
 1   1000000009 lab      con0_RPs0_C  Rollback    02:41:08 UTC Sun Sep 26 2009
 2   1000000008 lab      con0_RPs0_C  CLI         02:40:30 UTC Sun Sep 26 2009
 3   1000000007 lab      con0_RPs0_C  CLI         02:39:54 UTC Sun Sep 26 2009
 4   1000000006 lab      con0_RPs0_C  Rollback    02:38:40 UTC Sun Sep 26 2009
 5   1000000005 lab      con0_RPs0_C  CLI         02:37:35 UTC Sun Sep 26 2009
 6   1000000004 lab      con0_RPs0_C  CLI         02:37:04 UTC Sun Sep 26 2009

RP/0/0/CPU0:router# rollback configuration to 1000000008

Loading Rollback Changes.
Loaded Rollback Changes in 1 sec
Committing.
1 items committed in 1 sec (0)items/sec
Updating.RP/0/RP0/CPU0:Sep 26 02:42:09.318 : config_rollback[65707]: %LIBTARCFG-
6-COMMIT : Configuration committed by user 'lab'. Use 'show commit changes 100
0000010' to view the changes.

Updated Commit database in 1 sec
Configuration successfully rolled back to '1000000008'.
```

**Examples****Rolling Back to a Span of Configuration Commits**

The following example shows how to roll back to the configuration that existed prior to the last two configuration commits:

```
RP/0/0/CPU0:router# rollback configuration last 2

Loading Rollback Changes.
Loaded Rollback Changes in 1 sec
Committing.
1 items committed in 1 sec (0)items/sec
Updating.
Updated Commit database in 1 sec
Configuration successfully rolled back 2 commits.
```

**Related Commands**

Command	Description
<a href="#">load rollback changes</a>	Populates the target configuration with the contents of a previous configuration.

Command	Description
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

# root

To return to configuration mode from a configuration submode, use the **root** command in any supported configuration submode.

**root**

## Syntax Description

This command has no keywords or arguments.

## Command Default

None

## Command Modes

Any subconfiguration mode except the following:

- The **root** command is not available under the route-policy submodes, because it requires the **end-policy** command to exit out of the configuration.
- The **root** command is not available in template submode, but is available in the submodes configurable under the template submode.

## Command History

Release	Modification
Release 3.4.0	This command was introduced.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

## Task ID

Task ID	Operations
config-services	read

## Examples

The following example shows how to use the **root** command to return to configuration mode from the interface configuration submode:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface tengige 0/1/0/0
RP/0/0/CPU0:router(config-if)# root
RP/0/0/CPU0:router(config)#
```

The following example shows how to use the **root** command from a submode configurable under the template submode. In this example, the **root** command is used to return to configuration mode from the username submode:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# template test
RP/0/0/CPU0:router(config-TPL)# username xyz
RP/0/0/CPU0:router(config-un)# root
RP/0/0/CPU0:router(config)# show conf
```

```
Building configuration...
template test
  username xyz
  !
end-template
end
```



### Tip

---

The **root** command is not available from the template submode, but is available in the submodes configurable under the template submode.

---

# save configuration

To save the contents of a configuration to a file, use the **save configuration** command in global configuration or administration configuration mode.

**save configuration** [**running**] *device:directory-path*

## Syntax Description

<b>running</b>	(Optional) Saves the contents of the running configuration.
<i>device: directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

To save a configuration to a file, use the **save configuration** command.

To save a configuration that failed to a file, use the **save configuration failed** command.



**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows the configuration saved to disk0: from EXEC mode:

```
RP/0/0/CPU0:router(config)# save configuration disk0:sample3
Destination file name (control-c to abort): [/sample3]?
Building configuration.
1 lines built in 1 second
[OK]
```

The following example shows the configuration saved to disk1 from administration EXEC mode:

```
RP/0/0/CPU0:router(admin-config)# save configuration disk1:sample4
Destination file name (control-c to abort): [/sample4]?
Building configuration.
1 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration commit changes</a>	Saves the changes for a commit, or a series of commits, to a file.
<a href="#">save configuration failed</a>	Saves the contents of the failed configuration.
<a href="#">save configuration merge</a>	Saves the changes for a merged configuration to a file.
<a href="#">save configuration removed</a>	Saves the contents of a removed configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

# save configuration changes

To save the changes of a configuration to a file, use the **save configuration changes** command in global configuration or administration configuration mode.

**save configuration changes** *device:directory-path*

## Syntax Description

<i>device: directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.
-------------------------------	---

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

To save the configuration changes to be made during a replace operation to a file, use the **save configuration changes** command.

## Task ID

Task ID	Operations
config-services	read

**Examples**

The following example shows the configuration saved to disk0: from EXEC mode:

```
RP/0/0/CPU0:router(config)# save configuration changes disk0:sample3
Destination file name (control-c to abort): [/sample3]?
Building configuration.
1 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration commit changes</a>	Saves the changes for a commit, or a series of commits, to a file.
<a href="#">save configuration failed</a>	Saves the contents of the failed configuration.
<a href="#">save configuration merge</a>	Saves the changes for a merged configuration to a file.
<a href="#">save configuration removed</a>	Saves the contents of a removed configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

## save configuration commit changes

To save the changes for a commit, or a series of commits, to a file, use the **save configuration commit changes** command in global configuration or administration configuration mode.

**save configuration commit changes** {*commit-id*| **last** *number-of-commits*| **since** *commit-id*}  
*device:directory-path*

### Syntax Description

<i>commit-id</i>	Specific commit ID.
<b>last</b> <i>number-of-commits</i>	Saves changes made in the most recent <i>number-of-commits</i> .
<b>since</b> <i>commit-id</i>	Saves changes made since (and including) a specific <i>commit-id</i> .
<i>device: directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.

### Command Default

None

### Command Modes

Global configuration  
Administration configuration

### Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **save configuration commit changes** command to save the changes made in a commit operation to a file. You can specify a specific commit ID, all the changes since a specified commit ID, or the changes that occurred during the last *n* commits.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example saves the changes from the last two commit operations to disk0:

```
RP/0/0/CPU0:router(admin-config)# save configuration commit changes last 2 disk0:sample1
Destination file name (control-c to abort): [/sample1]?
Building configuration.
5 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration</a>	Saves the contents of a configuration to a file.
<a href="#">save configuration changes</a>	Saves the changes of a configuration to a file.
<a href="#">save configuration failed</a>	Saves the contents of the failed configuration.
<a href="#">save configuration merge</a>	Saves the changes for a merged configuration to a file.
<a href="#">save configuration removed</a>	Saves the contents of a removed configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

## save configuration failed

To save the contents of the failed configuration, use the **save configuration failed** command in global configuration or administration configuration mode.

**save configuration failed** [**load**| **noerrors**]| **startup** [**previous** *number*] [**noerror**]] *device:directory-path*

### Syntax Description

<b>load</b>	(Optional) Saves the failed configuration (syntax errors) in the last reload.
<b>noerrors</b>	(Optional) Excludes the error reasons from the saved configuration.
<b>startup</b>	(Optional) Saves the failed configuration during startup.
<b>previous</b> <i>number</i>	(Optional) Saves a failed startup configuration from the specified previous sessions. The <i>number</i> argument is a value between 1 and 4 that indicates how many failed startup configurations to save.
<i>device: directory-path</i>	Storage device and directory path of the configuration file to be saved.

### Command Default

None

### Command Modes

Global configuration  
Administration configuration

### Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	The <b>startup</b> keyword was added in administration configuration mode.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

To save a configuration to a file, use the **save configuration** command.

To save a configuration that failed to a file, use the **save configuration failed** command.

To save a configuration that failed during startup to a file, use the **save configuration failed** command with the **startup** keyword.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example saves the failed configuration to disk0:

```
RP/0/0/CPU0:router(admin-config)# save configuration failed disk1:/configs
```

**Related Commands**

Command	Description
<a href="#">save configuration removed</a>	Saves the contents of a removed configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

# save configuration merge

To save the contents of a merged configuration to a file, use the **save configuration merge** command in global configuration or administration configuration mode.

**save configuration merge** *device:directory-path*

## Syntax Description

<i>device : directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.
--------------------------------	---

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

## Task ID

Task ID	Operations
config-services	read



**Examples**

The following example shows the configuration saved to disk0:

```
RP/0/0/CPU0:router(admin-config)# save configuration merge disk0:sample3

Destination file name (control-c to abort): [/sample3]?
Building configuration.
1 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration removed</a>	Saves the contents of a removed configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

# save configuration removed

To save the contents of a removed configuration to a file, use the **save configuration removed** command in global configuration or administration configuration mode.

**save configuration removed** *removed-configuration-file* *device:directory-path*

## Syntax Description

<i>removed-configuration-file</i>	Specifies the name of the removed configuration file.
<i>device:directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

When a package is deactivated, the configuration belonging to that package is removed from the running configuration and saved to a file. To save a copy of the removed configuration file, use the **save configuration removed** command.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

To view a list of the available removed configuration files, use the **save configuration removed** command followed by a question mark:

```
RP/0/0/CPU0:router(config)# save configuration removed ?
      20051208042507.cfg  Removed configuration.
      20051208044553.cfg  Removed configuration.
      <cr>
```

In the following example, a removed configuration is saved to disk0: and assigned the filename "sample3."

```
RP/0/0/CPU0:router(config)# save configuration removed 20051208042507.cfg disk0:sample3
Destination file name (control-c to abort): [/sample3]?
Building configuration.
1 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration</a>	Saves the contents of a configuration to a file.
<a href="#">save configuration commit changes</a>	Saves the changes for a commit, or a series of commits, to a file.
<a href="#">save configuration failed</a>	Saves the contents of the failed configuration.
<a href="#">save configuration merge</a>	Saves the changes for a merged configuration to a file.
<a href="#">save rollback changes</a>	Saves rollback changes for a commit ID or a group of commits.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

# save rollback changes

To save the rollback changes, use the **save rollback changes** command in global configuration or administration configuration mode.

**save rollback changes** {*commit-id*| **last** *number-of-commits*| **to** *commit-id*} *device:directory-path*

## Syntax Description

<i>commit-id</i>	Specific commit ID.
<b>last</b> <i>number-of-commits</i>	Saves the rollback changes for the last <i>n</i> commits
<b>to</b> <i>commit-id</i>	Saves rollback changes up to a specific <i>commit-id</i> .
<i>device: directory-path</i>	Storage device and directory path of the configuration file to be loaded into the target configuration.

## Command Default

None

## Command Modes

Global configuration  
Administration configuration

## Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **save rollback changes** command to save the changes that would be made in a configuration rollback to a specific commit point or for a series of commits.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows that the rollback changes for the commit point 5 are saved to the file sample4 on disk0:

```
RP/0/0/CPU0:router(admin-config)# save rollback changes last 1 disk0:sample4
Destination file name (control-c to abort): [/sample4]?
Building configuration.
6 lines built in 1 second
[OK]
```

**Related Commands**

Command	Description
<a href="#">save configuration</a>	Saves the contents of a configuration to a file.
<a href="#">save configuration commit changes</a>	Saves the changes for a commit, or a series of commits, to a file.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

## set default-afi

To set the default address family identifier (AFI) for the current session, use the **set default-afi** command in EXEC mode.

```
set default-afi {all| ipv4| ipv6}
```

### Syntax Description

<b>all</b>	Sets the default AFI to IPv4 and IPv6 for the current session.
<b>ipv4</b>	Sets the default AFI to IPv4 for the current session. This is the default setting.
<b>ipv6</b>	Sets the default AFI to IPv6 for the current session.

### Command Default

The default AFI setting is set to IPv4 for all sessions.

### Command Modes

EXEC

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **set default-afi** command to set the default AFI for the current session. This command acts as a keystroke shortcut for **show** commands. If the default AFI setting is set to IPv4, then you would not have to specify the **ipv4** keyword for **show** commands that support the **ipv4** keyword. For example, if the AFI setting

is set to IPv4, you could issue the **show route** command without specifying the **ipv4** keyword to display IPv4 routes in the Routing Information Base (RIB).

Use the **show default-afi-safi-vrf** command to display the default AFI setting.

### Task ID

Task ID	Operations
basic-services	read, write

### Examples

The following example shows how to set the default AFI to IPv6:

```
RP/0/0/CPU0:router# set default-afi ipv6
%% Default Address Family Identifier is set to 'ipv6'
```

### Related Commands

Command	Description
<a href="#">set default-safi</a>	Sets the default SAFI for the current session.
<a href="#">set default-vrf</a>	Sets the default VRF instance for the current session.
<a href="#">show default-afi-safi-vrf</a>	Displays the default AFI, SAFI, and VRF instance for the current session.

## set default-safi

To set the default subaddress family identifier (SAFI) for the current session, use the **set default-safi** command in EXEC mode.

```
set default-safi {all| multicast| unicast}
```

### Syntax Description

<b>all</b>	Sets the default SAFI to multicast and unicast for the current session.
<b>multicast</b>	Sets the default SAFI to multicast for the current session.
<b>unicast</b>	Sets the default SAFI to unicast for the current session. This is the default setting.

### Command Default

The default SAFI setting is set to unicast for all sessions.

### Command Modes

EXEC

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **set default-safi** command to set the default SAFI setting for the current session. This command acts as a keystroke shortcut for **show** commands. If the default SAFI setting is set to unicast, you would not have



to specify the **unicast** keyword for **show** commands that support that keyword. For example, if the default SAFI setting is set to unicast, you could issue the **show router** command without specifying the **unicast** keyword to display information about unicast address prefixes in the Routing Information Base (RIB).

Use the **show default-afi-safi-vrf** command to display the default SAFI setting.

### Task ID

Task ID	Operations
basic-services	read, write

### Examples

The following example shows how to set the default SAFI to multicast:

```
RP/0/0/CPU0:router# set default-safi multicast
%% Default Sub-Address Family Identifier is set to 'multicast'
```

### Related Commands

Command	Description
<a href="#">set default-afi</a>	Sets the default AFI for the current session.
<a href="#">set default-vrf</a>	Sets the default VRF instance for the current session.
<a href="#">show default-afi-safi-vrf</a>	Displays the default AFI, SAFI, and VRF instance for the current session.

## set default-vrf

To set the default VPN routing and forwarding (VRF) instance for the current session, use the **set default-vrf** command in EXEC mode.

```
set default-vrf {name| none}
```

### Syntax Description

<i>name</i>	Default VPN routing and forwarding name.
<b>none</b>	Sets the default VPN routing and forwarding name to empty.

### Command Default

The default VRF setting is set to empty.

### Command Modes

EXEC

### Command History

Release	Modification
Release 3.3.0	This command was introduced.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **set default-vrf** command to set the default VRF setting for the current session. This command acts as a keystroke shortcut for **show** commands. For example, if the default VRF is configured, you can issue the **show route** command without specifying the VRF name.

When the default VRF for the session is set to **none**, then IPv4 routes for the system default VRF are displayed.



**Note** To override the default VRF setting, specify the VRF name in the **show** command.

Use the **show default-afi-safi-vrf** command to display the default VRF setting.

**Task ID**

Task ID	Operations
basic-services	read, write

**Examples**

In the following example, the default VRF is set to "dft\_vrf:"

```
RP/0/0/CPU0:router# set default-vrf dft_vrf
%% Default Virtual Routing/Forwarding is set to 'dft_vrf'
```

In the following command, the **show route** command is entered without specifying a VRF name. The results for the "dft\_vrf" VRF are displayed because the default VRF was set to "dft\_vrf."

```
RP/0/0/CPU0:router# show route ipv4
% No matching vrf found
```

When the default VRF for the session is set to **none**, the system default VRF routes are displayed. In the following example, the default VRF is set to (empty) and the **show route** command displays the system default VRF information:

```
RP/0/0/CPU0:router# set default-vrf none
%% Default Virtual Routing/Forwarding is set to ''
RP/0/0/CPU0:router# show route ipv4

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
        i - ISIS, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, su - IS-IS summary null, * - candidate default
        U - per-user static route, o - ODR, L - local

Gateway of last resort is 12.29.0.1 to network 0.0.0.0

S* 0.0.0.0/0 [1/0] via 12.29.0.1, 00:31:30
L 10.10.10.10/32 is directly connected, 3d02h, Loopback1
C 12.29.0.0/16 is directly connected, 00:31:30, MgmtEth0/0/CPU0/0
L 12.29.56.21/32 is directly connected, 00:31:30, MgmtEth0/0/CPU0/0
```

**Related Commands**

Command	Description
<a href="#">set default-afi</a>	Sets the default AFI for the current session.
<a href="#">set default-safi</a>	Sets the default SAFI for the current session.

Command	Description
<a href="#">show default-afi-safi-vrf</a>	Displays the default AFI, SAFI, and VRF instance for the current session.

# show

To display information about the system configuration or operational state, use the **show** command in EXEC mode, administration EXEC mode, or any configuration mode.

**show** *command* [**begin** *regular-expression* | **exclude** *regular-expression* | **file** *filesystem:* | **include** *regular-expression*]

## Syntax Description

<i>command</i>	Supported <b>show</b> command.
	Vertical bar (the “pipe” symbol) indicates that an output processing specification follows.
<i>regular-expression</i>	(Optional) Regular expression found in <b>show</b> command output.
<b>begin</b>	(Optional) Begins unfiltered output of the <b>show</b> command with the first line that contains the regular expression.
<b>exclude</b>	(Optional) Displays output lines that do not contain the regular expression.
<b>file</b> <i>filesystem:</i>	(Optional) Writes the output lines that contain the regular expression to the specified file on the specified file system. Include the file system alias for the <i>filesystem</i> argument, followed by a colon, and the directory path and filename.
<b>include</b>	(Optional) Displays output lines that contain the regular expression.

## Command Default

None

## Command Modes

EXEC  
Administration EXEC  
Any configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.

Release	Modification
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **show** commands display information about the system and its configuration. To display a list of the available **show** commands, use the question mark (?) online help function.

### Filtering Output

Search options for the **show** command are shown in this table.

**Table 2: Show Command Search Options**

Command	Purpose
<b>show command</b>   <b>begin</b> <i>regular-expression</i>	Begins unfiltered output of the <b>show</b> command with the first line that contains the regular expression.
<b>show command</b>   <b>exclude</b> <i>regular-expression</i>	Displays output lines that do not contain the regular expression.
<b>show command</b>   <b>include</b> <i>regular-expression</i>	Displays output lines that contain the regular expression.
<b>show command</b>   <b>file</b> <i>filesystem:</i>	Writes the output lines that contain the regular expression to the specified file on the specified file system.

### Adding a Filter at the --More-- Prompt

You can also specify a filter at the --More-- prompt of a **show** command output. To filter output from the --More-- prompt, enter a forward slash (/) followed by a regular expression. The filter remains active until the command output finishes or is interrupted (using **Ctrl-Z** or **Ctrl-C**).

- If a filter is specified at the original command or a previous --More-- prompt, a second filter cannot be applied.
- The use of the **begin** keyword does not constitute a filter.
- The minus sign (–) preceding a regular expression displays output lines that do not contain the regular expression.

- The plus sign (+) preceding a regular expression displays output lines that contain the regular expression.

**Task ID**

Task ID	Operations
Task ID for the feature used with the <b>show</b> command	read

For example, the **show interfaces** command requires read privileges in the interface task ID.

**Examples**

The following example shows output from the **show interface | include protocol** command. In this example, the **show** command includes only lines in which the regular expression “protocol” appears:

```
RP/0/0/CPU0:router# show interface | include protocol

Null0 is up, line protocol is up
0 drops for unrecognized upper-level protocol
TenGigE0/2/0/0 is administratively down, line protocol is administratively down
0 drops for unrecognized upper-level protocol
TenGigE0/2/0/1 is administratively down, line protocol is administratively down
0 drops for unrecognized upper-level protocol
TenGigE0/2/0/2 is administratively down, line protocol is administratively down
0 drops for unrecognized upper-level protocol
TenGigE0/2/0/3 is administratively down, line protocol is administratively down
0 drops for unrecognized upper-level protocol
FastEthernet0/RP0/CPU0/0 is administratively down, line protocol is administratively
down
FastEthernet0/RP0/CPU0/0 is administratively down, line protocol is administratively
down
0 drops for unrecognized upper-level protocol
```

On most systems, the **Ctrl-Z** key combination can be entered at any time to interrupt the output and return to EXEC mode. For example, use the **show running-config | begin hostname** command to start the display of the running configuration file at the line containing the hostname setting, then use **Ctrl-Z** when you get to the end of the information you are interested in.

The following example shows sample output from the **show configuration running | begin line** command. The output begins with unfiltered output from the first line that contains the regular expression “line.” In this example, at the --More-- prompt, a new search is specified that begins with output lines that contain the regular expression “ipv4.”

**Note**

The use of the **begin** keyword does not constitute a filter.

```
RP/0/0/CPU0:router# show configuration running | begin line

Building configuration...
line console
  exec-timeout 120 120
!
logging trap
--More--
/ipv4

filtering...
route ipv4 0.0.0.0 255.255.0.0 pos0/2/0/0
interface TenGigE0/2/0/0
  ipv4 address 172.19.73.215 255.255.0.0
```

 show

end

**Related Commands**

Command	Description
<a href="#">more</a>	Displays output from a text file.



# show aliases

To display all defined aliases or the aliases defined in a specified mode, use the **show aliases** command in EXEC mode.

**show aliases**

**Syntax Description** This command has no keywords or arguments.

**Command Default** Displays all aliases currently configured on the system.

**Command Modes** EXEC

Command History	Release	Modification
	Release 3.2	This command was introduced.
	Release 3.3.0	No modification.
	Release 3.4.0	No modification.
	Release 3.5.0	No modification.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show aliases** command to display all aliases currently configured on the system.

Task ID	Task ID	Operations
	basic-services	read

## Examples

The following example illustrates sample output from the **show aliases** command. The output displays a summary of all the command aliases configured.

```
RP/0/0/CPU0:router# show aliases

exec mode aliases:
ipv4_brief          show ipv4 interface brief

interface mode aliases:
sample_int         tengige 0/2/0/0
```

## Related Commands

Command	Description
<a href="#">alias</a>	Creates a command alias.

## show configuration (config)

To display information about the current configuration session (target configuration), use the **show configuration** command in any configuration mode.

**show configuration [merge] [running]**

### Syntax Description

<b>merge</b>	(Optional) Displays the configuration that occurs if the contents of the uncommitted changed (target configuration) are committed to the running configuration.
<b>running</b>	(Optional) Displays the running (committed) configuration.

### Command Default

When the **show configuration** command is entered without an argument, the uncommitted changes to the target configuration are displayed.

### Command Modes

Any configuration

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show configuration** command to display details on uncommitted configuration changes.

Use the **show configuration** command with the **running** keyword to display the running (active) configuration.

**show configuration (config)**

Prior to committing the target configuration, use the **show configuration** command with the **merge** keyword from any configuration mode to display the result of merging the target configuration with the running configuration.

**Task ID**

Task ID	Operations
basic-services	read

**Examples**

In this example, the **show configuration** command displays uncommitted changes made during a configuration session:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface tengige0/3/0/3
RP/0/0/CPU0:router(config-if)# description faq
RP/0/0/CPU0:router(config-if)# ipv4 address 10.10.11.20 255.0.0.0
RP/0/0/CPU0:router(config-if)# show configuration

Building configuration...
interface TenGigE0/3/0/3
  description faq
  ipv4 address 10.10.11.20 255.0.0.0
end
```

The following example shows sample output from the **show configuration** command with the optional **merge** keyword. The command is entered during a configuration session. The output displays the result of merging the target and running configuration, without committing the changes.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# interface tengige0/3/0/3
RP/0/0/CPU0:router(config-if)# description faq
RP/0/0/CPU0:router(config-if)# ipv4 address 10.10.11.20 255.0.0.0
RP/0/0/CPU0:router(config-if)# show configuration merge

Building configuration...
hostname router
interface TenGigE0/0/0/0
  ipv4 address 1.2.3.4 255.0.0.0
  exit
interface TenGigE0/3/0/3
  description faq
  ipv4 address 1.1.1.1 255.0.0.0
  shutdown
end
```

**Related Commands**

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">load</a>	Populates the target configuration with the contents of a previously saved configuration file.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.

Command	Description
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration changes

To display the configuration changes to be made during a replace operation, use the **show configuration changes** command in global configuration or administration configuration mode.

**show configuration changes [diff]**

<b>Syntax Description</b>	<b>diff</b> (Optional) Displays the changes in UNIX-like format.
---------------------------	--

<b>Command Default</b>	None
------------------------	------

<b>Command Modes</b>	Global configuration Administration configuration
----------------------	--

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	Release 3.3.0	This command was introduced.
	Release 3.4.0	No modification.
	Release 3.5.0	No modification.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

<b>Usage Guidelines</b>	To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.
-------------------------	---

<b>Task ID</b>	<b>Task ID</b>	<b>Operations</b>
	config-services	read
	basic-services	read

**Examples**

The following example shows the changes to be made during a replace operation:

```
RP/0/0/CPU0:router(config)# show configuration changes diff
```

```
Building configuration...
# hostname router
# hostname bla
- logging console
- telnet vrf default ipv4 server disable
- domain ipv4 host xhu-u5
- domain ipv4 host coax-u10
- domain ipv4 host coax-u10.cisco.com
- domain name
- interface Loopback1
- ipv4 address 10.0.0.2 255.255.255.224
- !
- interface Loopback2
- description
- !
- interface Loopback5
- description
- !
- interface Loopback6
- description
- !
- interface MgmtEth0/0/CPU0/0
- ipv4 address 10.0.0.1 255.255.255.224
- !
- interface GigabitEthernet0/2/0/0
- shutdown
- !
- interface GigabitEthernet0/2/0/1
- shutdown
- !
- interface GigabitEthernet0/2/0/2
- shutdown
- !
- router static
- address-family ipv4 unicast
- 0.0.0.0/0 255.255.255.224
- !
- !
end
```

## show configuration commit changes

To display the changes made to the running configuration by previous configuration commits, a configuration commit, or for a range of configuration commits, use the **show configuration commit changes** command in EXEC, administration EXEC, administration configuration, or global configuration mode.

**show configuration commit changes** {*commit-id*| **since** *commit-id*| **last** *number-of-commits*} [**diff**]

### Syntax Description

<b>since</b>	Displays all changes committed to the running configuration since (and including) a specific configuration commit.
<i>commit-id</i>	Displays configuration changes for a specific configuration commit.
<b>last</b> <i>number-of-commits</i>	Displays the changes made to the running configuration during the last number of configuration commits specified for the <i>number-of-commits</i> argument.
<b>diff</b>	(Optional) Displays added lines, changed lines, and deleted lines.

### Command Default

None

### Command Modes

EXEC  
Administration EXEC  
Administration configuration  
Global configuration

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for administration EXEC and administration configuration modes. Support was added for the <b>diff</b> keyword.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.



Release	Modification
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Each time a configuration is committed with the **commit** command, the configuration commit operation is assigned a commit ID. The **show configuration commit changes** command displays the configuration changes made since the specified commit.

To display a list of the available commit IDs, enter the **show configuration commit list** command. You can also display the commit IDs by entering the **show configuration commit changes** command with the online help function (?).

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows sample output from the **show configuration commit changes** command. The output displays commit IDs.

```
RP/0/0/CPU0:router# show configuration commit list
SNo. Label/ID      User      Line      Client      Time Stamp
~~~~ ~~~~~~      ~~~~~      ~~~~~      ~~~~~      ~~~~~~
1      1000000077      lab      con0_RPs1_C  CLI      15:42:45 UTC Fri Jan 30 2009
2      1000000076      lab      con0_RPs1_C  Rollback 15:30:39 UTC Fri Jan 30 2009
3      1000000075      lab      con0_RPs1_C  Rollback 15:25:26 UTC Fri Jan 30 2009
4      1000000074      lab      con0_RPs1_C  Rollback 15:04:29 UTC Fri Jan 30 2009
5      1000000073      lab      con0_RPs1_C  CLI      14:49:07 UTC Fri Jan 30 2009
6      1000000072      lab      con0_RPs1_C  CLI      14:48:35 UTC Fri Jan 30 2009
```

The following example shows sample output from the **show configuration commit changes** command with the *commit-id* argument. In this example, the output displays the changes made in the configuration commit assigned commit ID 1000000077.

```
RP/0/0/CPU0:router# show configuration commit changes 1000000077
Building configuration...
alias exec shrun show configuration running
alias exec shver show version
end
```

The following example shows sample output from the **show configuration commit changes** command with the *since commit-id* keyword and argument. In this example, the output displays the configuration changes made since the configuration commit assigned commit ID 1000000077 was committed.

```
RP/0/0/CPU0:router# show configuration commit changes since 1000000077
Building configuration...
no hw-module node 0/RP0/CPU0 shutdown
```

**show configuration commit changes**

```

hostname router
logging trap
no logging console
logging history size 1
alias exec shrun show configuration running
alias exec shver show version
interface MgmtEth0/RP1/CPU0/0
  ipv4 address 12.25.34.10 255.255.0.0
  no shutdown
  !
interface preconfigure MgmtEth0/RP0/CPU0/0
  no shutdown
  !
no route ipv4 0.0.0.0/0 12.7.0.1
route ipv4 0.0.0.0/0 12.25.0.1
route ipv4 223.255.254.254/32 12.25.0.1
telnet ipv4 server enable
end

```

The following example shows sample output from the **show configuration commit changes** command with the **diff** keyword. In the display, the following symbols signify changes:

+ indicates an added line.

– indicates a deleted line.

# indicates a modified line.

```

RP/0/0/CPU0:router# show configuration commit changes last 1 diff

Building configuration...
+ interface Loopback1000
+ ipv4 address 190.190.180.1 255.255.255.255
!
end

+ interface Loopback1000
+ ipv4 address 190.190.180.1 255.255.255.255
!
end

```

**Related Commands**

Command	Description
<a href="#">rollback configuration</a>	Rolls back the configuration to a previous commit.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.

## show configuration commit list

To display information about the configuration commits stored in the commit database, use the **show configuration commit list** command in EXEC, administration EXEC, administration configuration, or global configuration mode.

**show configuration commit list** [ *number-of-commits* ] [**detail**]

### Syntax Description

<i>number-of-commits</i>	(Optional) Number of commits (beginning with the most recent commit) that are available for rollback.
<b>detail</b>	(Optional) Displays detailed commit information, including comments.

### Command Default

If this command is entered without any optional arguments or keywords, the output displays information about all the configuration commits stored in the commit database.

### Command Modes

EXEC  
Administration EXEC  
Administration configuration  
Global configuration

### Command History

Release	Modification
Release 3.3.0	This command was introduced.  This command replaced the <b>show rollback points</b> command, which was available in previous releases.
Release 3.4.0	Support was added for the administration EXEC and administration configuration modes.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show configuration commit list** command to list the commit IDs (up to 100) that are available for rollback.

**Note**

The most recent 100 commits are retained by the system. As new commit IDs are added, the oldest commit IDs are discarded and are no longer available for rollback operations.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows sample output from the **show configuration commit list** command. The output displays the commit IDs that are available for rollback.

```
RP/0/0/CPU0:router# show configuration commit list

SNo.  Label/ID      User      Line      Client      Time Stamp
~~~~  ~~~~~~      ~~~~     ~~~~     ~~~~~~     ~~~~~~
1      1000000010    UNKNOWN  con0_RP0_C  Rollback    02:25:53 UTC Fri Feb 06 2009
2      1000000009    UNKNOWN  con0_RP0_C  CLI         02:23:09 UTC Fri Feb 06 2009
3      1000000008    UNKNOWN  con0_RP0_C  CLI         02:22:54 UTC Fri Feb 06 2009
4      1000000007    UNKNOWN  con0_RP0_C  CLI         02:22:18 UTC Fri Feb 06 2009
5      1000000006    UNKNOWN  con0_RP0_C  CLI         02:07:21 UTC Fri Feb 06 2009
```

[Table 3: show configuration commit list Field Descriptions, on page 108](#) describes the significant fields shown in the display.

**Table 3: show configuration commit list Field Descriptions**

Field	Description
SNo.	Serial number of the commit entry.
Label/ID	If a label was assigned to a commit, the first 10 characters of the label display; otherwise, the autogenerated commit ID displays.
User	User who executed the commit.
Line	Line in which the user session was established. In some cases, this field may display "UNKNOWN" or "SYSTEM". These fields indicate that an internal commit was made by the system.

Field	Description
Client	The management interface used to make the commit.
Time Stamp	Time and date when the commit was executed.

**Related Commands**

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

## show configuration failed (config)

To display information about a configuration that failed during the last commit, use the **show configuration failed** command in any configuration mode.

**show configuration failed** [load|noerrors]

### Syntax Description

<b>load</b>	(Optional) Displays any syntax errors found in a configuration loaded with the <b>load</b> command.
<b>noerrors</b>	(Optional) Displays the configuration that failed in last commit without the error reasons.

### Command Default

Displays the details of the failed configuration including error reasons.

### Command Modes

Any configuration

### Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

**Task ID**

Task ID	Operations
basic-services	read

**Examples**

The following example shows a failed commit operation:

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# taskgroup bgp
RP/0/0/CPU0:router(config-tg)# description this is an example of an invalid task group
RP/0/0/CPU0:router(config-tg)# commit
% Failed to commit one or more configuration items.
Please use 'show configuration failed' to view the errors
```

The following example shows sample output from the **show configuration failed** command. The output displays the configuration items that failed during the last commit operation.

```
RP/0/0/CPU0:router(config-tg)# show configuration failed

!! CONFIGURATION FAILED DUE TO SEMANTIC ERRORS
taskgroup bgp
!!% Usergroup/Taskgroup names cannot be taskid names
!
```

The following example shows sample output from the **show configuration failed** command with the optional **no errors** keyword. The output displays the configuration items that failed during the last commit operation without an error description.

```
RP/0/0/CPU0:router(config-tg)# show configuration failed noerrors

!! CONFIGURATION FAILED DUE TO SEMANTIC ERRORS
taskgroup bgp
!
```

**Related Commands**

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.

Command	Description
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.



# show configuration failed incompatible

To display any configurations that were removed from the running configuration because they were not understood by the software being activated, use the **show configuration failed incompatible** command in EXEC or administration EXEC mode.

**show configuration failed incompatible**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** EXEC  
Administration EXEC

Command History	Release	Modification
	Release 3.6.0	This command was introduced.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Any configurations in the running configuration that are not understood by new software being installed are removed from the running configuration. To see which configurations were removed, use the **show configuration failed incompatible** command.

Task ID	Task ID	Operations
	config-services	read

Related Commands	Command	Description
	<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration failed remove

To display information about a configuration that failed while being removed during installation operations, use the **show configuration failed remove** command in EXEC or administration EXEC mode.

**show configuration failed remove**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** EXEC  
Administration EXEC

Command History	Release	Modification
	Release 3.5.0	This command was introduced.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID	Task ID	Operations
	config-services	read

**Examples** The following example shows a failed commit operation:

```
RP/0/0/CPU0:router# show configuration failed remove
!! SEMANTIC ERRORS: This configuration was rejected by
!! the system due to semantic errors. The individual
!! errors with each failed configuration command can be
```

```
!! found below.
multicast-routing
 no address-family ipv4
  !!% Process did not respond to sysmgr
 address-family ipv4
  no interface all enable
!!% Process did not respond to sysmgr
!
!
```

Because the configuration failed to be removed, it is still displayed in the output from the **show running-configuration** command as expected:

```
RP/0/0/CPU0:router# show running-configuration
...
router pim vrf default address-family ipv4
 auto-rp candidate-rp GigabitEthernet0/2/0/3 scope 255 group-list 224/4 interval 10
!
multicast-routing
 address-family ipv4
  interface all enable
!
!
```

## Related Commands

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration failed rollback

To display information about a configuration that failed in the last rollback operation, use the **show configuration failed rollback** command in EXEC or administration EXEC mode.

**show configuration failed rollback**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes**  
EXEC  
Administration EXEC

Command History	Release	Modification
	Release 3.5.0	This command was introduced.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID	Task ID	Operations
	config-services	read
	root-lr	read

Related Commands	Command	Description
	<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.

Command	Description
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration failed startup

To display information about a configuration that failed at startup, use the **show configuration failed** command in EXEC or administration EXEC mode.

**show configuration failed startup** [**noerror**| *previous number*]

## Syntax Description

<b>noerror</b>	(Optional) Displays the configuration that failed at startup without an error reason.
<b>previous number</b>	(Optional) Displays the previous failed startup configuration or configurations. The <i>number</i> argument is a value from 1 to 4, which displays the failed startup configurations in previous of sessions.

## Command Default

If no keywords are specified, this command displays the details of the failed startup configuration including error reasons.

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for the <b>previous number</b> keyword and argument.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

**Task ID**

Task ID	Operations
config-services	read

**Related Commands**

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration history

To display a history of configuration events, use the **show configuration history** command in EXEC, administration EXEC, administration configuration, or global configuration mode.

**show configuration history** [**alarm**|**backup**|**cfs-check**|**commit**|**rebase**|**shutdown**|**startup**] [**first number**|**last number**] **reverse**] [**detail**]

## Syntax Description

<b>alarm</b>	(Optional) Displays alarm events.
<b>backup</b>	(Optional) Displays configuration backup events.
<b>cfs-check</b>	(Optional) Displays CFS check events.
<b>commit</b>	(Optional) Displays commit events.
<b>rebase</b>	(Optional) Displays commit database consolidation events.
<b>shutdown</b>	(Optional) Displays shutdown events.
<b>startup</b>	(Optional) Displays startup events, including alternate configurations, failed configurations, and other events.
<b>first number</b>	(Optional) Displays the first x number of events, where x is the <i>number</i> argument.
<b>last number</b>	(Optional) Displays the last x <i>number</i> events. Replace with the number of events to display.
<b>reverse</b>	(Optional) Displays the most recent events first.
<b>detail</b>	(Optional) Displays detailed information, including comments.

## Command Default

When entered without any optional arguments or keywords, this command displays all configuration events. The oldest events are displayed at the top of the list for each event type.

## Command Modes

EXEC  
Administration EXEC  
Administration configuration  
Global configuration



**Command History**

Release	Modification
Release 3.4.0	This command was introduced.
Release 3.5.0	The <b>backup</b> and <b>rebase</b> keywords were added.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	Support for the <b>oir</b> keyword was removed.
Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show configuration history** command to display information about the last (up to) 1500 configuration events.

Use one of the available keywords to display the configuration event only for that event type. Use the **first number** and **last number** keywords and arguments to display a specified number of events. Use the **reverse** keyword to display the newest events at the top of the list.

The **show configuration history** command in administration EXEC mode does not display records from releases earlier than Cisco IOS XR Release 3.6.0. To see information about commits prior to an upgrade from before Release 3.6.0, use the **show configuration commit list** command in administration EXEC mode.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

In the following example, the **show configuration history** command is used to display the history of all configuration events for an SDR:

```
RP/0/0/CPU0:router# show configuration history
```

```
Sno.  Event      Info                               Time Stamp
~~~~  ~~~~~      ~~~~                               ~~~~~
1      alarm      inconsistency alarm raised        Thu Jun 22 15:23:15 2009
2      startup    configuration applied             Thu Jun 22 15:23:32 2009
3      OIR config restore               Thu Jun 22 15:23:25 2009
4      OIR config restore               Thu Jun 22 15:23:33 2009
5      OIR config restore               Thu Jun 22 15:23:33 2009
6      OIR config restore               Thu Jun 22 15:23:34 2009
7      OIR config restore               Thu Jun 22 15:23:34 2009
8      OIR config restore               Thu Jun 22 15:23:35 2009
9      OIR config restore               Thu Jun 22 15:23:36 2009
```

## show configuration history

```

10 OIR config restore Thu Jun 22 15:23:37 2009
11 OIR config restore Thu Jun 22 15:23:37 2009
12 OIR config restore Thu Jun 22 15:23:38 2009
13 OIR config restore Thu Jun 22 15:23:38 2009
14 OIR config restore Thu Jun 22 15:23:39 2009
15 OIR config restore Thu Jun 22 15:23:39 2009
16 OIR config restore Thu Jun 22 15:23:40 2009
17 OIR config restore Thu Jun 22 15:23:40 2009
18 OIR config restore Thu Jun 22 15:23:42 2009
19 OIR config restore Thu Jun 22 15:23:42 2009
20 OIR config restore Thu Jun 22 15:23:42 2009
21 OIR config restore Thu Jun 22 15:23:43 2009
--More--

```

In the following example, the **show configuration history** command is used to display only the startup configuration events:

```
RP/0/0/CPU0:router# show configuration history startup
```

```

Sno.  Event      Info                               Time Stamp
~~~~  ~~~~~
1     startup   configuration applied             Thu Jun 22 15:23:32 2009
2     startup   configuration applied             Sat Jul 1 15:02:24 2009
3     startup   configuration applied             Sat Jul 8 17:36:52 2009
4     startup   configuration applied             Sun Jul 9 13:40:27 2009
5     startup   configuration applied             Sat Jul 15 18:18:54 2009

```

In the following example, the **show configuration history** command with the **commit detail** keywords is used to display additional details regarding the commit events:

```
RP/0/0/CPU0:router# show configuration history commit detail
```

```

1) Event: commit           Time: Thu Jun 22 15:44:33 2009
   Commit ID: 1000000001 Label:
   User: lab                Line: vty0
   Client: CLI              Comment:

2) Event: commit           Time: Thu Jun 22 16:58:18 2009
   Commit ID: 1000000002 Label:
   User: lab                Line: vty2
   Client: CLI              Comment:

3) Event: commit           Time: Thu Jun 22 16:58:39 2009
   Commit ID: 1000000003 Label:
   User: lab                Line: vty2
   Client: CLI              Comment:

4) Event: commit           Time: Sat Jul 1 15:29:31 2009
   Commit ID: 1000000001 Label:
   User: lab                Line: vty0
   Client: CLI              Comment:

5) Event: commit           Time: Sat Jul 1 15:32:25 2009
   Commit ID: 1000000002 Label:
   User: lab                Line: vty0
--More--

```

**Table 4: show configuration history Field Descriptions**

Field	Description
SNo.	Serial number of the entry.
Event	Type of configuration event.

Field	Description
Info	Summary of the configuration action.
Time Stamp	Time and date when the event was run.
Label/ID	If a label was assigned to a commit, the first 10 characters display; otherwise, the autogenerated commit ID displays.
User	User who issued the command.
Line	Line in which the user session was established. In some cases, this field may display "UNKNOWN" or "SYSTEM". These fields indicate that an internal action was made by the system.
Client	The management interface used to make the event.

**Related Commands**

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration inconsistency replica

To display any configuration inconsistencies on a replica node, use the **show configuration inconsistency replica** command in EXEC or administration EXEC mode.

**show configuration inconsistency replica location *node-id* [detail]**

## Syntax Description

<b>location</b> <i>node-id</i>	Displays any configuration inconsistencies on the designated node. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation.
<b>detail</b>	Displays a detailed list of inconsistencies.

## Command Default

Administration EXEC mode: Displays configuration inconsistencies for the admin plane configuration.  
EXEC mode: Displays configuration inconsistencies for an SDR configuration.

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.6.0	This command was introduced.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

In administration EXEC mode, the replica node for the **show configuration inconsistency replica** command is the standby designated system controller (DSC). In EXEC mode, the replica nodes are the route processors (RPs) that can become the designated secure domain router system controller (DSDRSC).

Use the **show configuration inconsistency replica** command, before performing a manual switchover or DSC migration, to verify that the node in line to take over for the DSC or DSDRSC is in good shape. If any problems are reported, use the **clear configuration inconsistency replica** command to correct them.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows a configuration with inconsistencies:

```
RP/0/0/CPU0:router# show configuration inconsistency replica location 0/5/cpu0
```

```
The replica at location 0/5/CPU0 is inconsistent.  
Please run 'clear configuration inconsistency replica location 0/5/CPU0'.
```

The following example shows sample output after the inconsistencies have been resolved:

```
RP/0/0/CPU0:Router# show configuration inconsistency replica location 0/5/cpu0
```

```
Replica is consistent
```

**Related Commands**

Command	Description
<a href="#">clear configuration inconsistency replica</a>	Resolves configuration inconsistencies on a standby node.

# show configuration persistent

To display the persistent configuration, use the **show configuration persistent** command in EXEC mode.

**show configuration persistent [diff]**

## Syntax Description

<b>diff</b>	(Optional) Displays the difference between the running configuration and persistent configuration. This option is available only on the DSDRSC .
-------------	--

## Command Default

If no argument is specified, the **show configuration persistent** command displays the entire contents of the persistent configuration file.

## Command Modes

EXEC

## Command History

Release	Modification
Release 3.7.0	This command was introduced.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The persistent configuration is the configuration stored in nonvolatile memory, from which the running configuration is restored after the router is reloaded. The running configuration should be the same as the persistent configuration. Use the **show configuration persistent** command with the **diff** keyword to check if there is a difference between the running configuration and the persistent configuration.

## Task ID

Task ID	Operations
config-services	read

## Examples

The following example shows that there is no difference between the running configuration and the persistent configuration:

```
RP/0/0/CPU0:router# show configuration persistent diff
```

```
Building configuration...
end
```

The following example shows a difference between the running configuration and the persistent configuration:

```
RP/0/0/CPU0:router# show configuration persistent diff

Building configuration...
router vrrp
interface gigabitethernet0/1/0/1.1
vrrp 1 preempt delay 300
!
interface gigabitethernet0/1/0/1.2
vrrp 1 preempt delay 300
!
interface gigabitethernet0/1/0/1.3
vrrp 1 preempt delay 300
```

#### Related Commands

Command	Description
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration removed

To display a configuration removed during installation operations, use the **show configuration removed** command in EXEC or administration EXEC mode.

**show configuration removed** *config-id*

## Syntax Description

<i>config-id</i>	Name of removed configuration. Type (?) to see a list of the names of all removed configurations.
------------------	---

## Command Default

None

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	This command was added to the administration EXEC mode.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

## Task ID

Task ID	Operations
config-services	read



**Examples**

The following example shows a removed configuration:

```
RP/0/0/CPU0:router# show configuration removed 20060301112919.cfg

xml agent corba
http server
end
```

**Related Commands**

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">load</a>	Populates the target configuration with the contents of a previously saved configuration file.
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration rollback changes

To display changes that would be made by the **rollback configuration** command or to display the list of commit IDs, use the **show configuration rollback changes** command in EXEC, administration EXEC, administration configuration, or global configuration mode.

**show configuration rollback changes** {*commit-id*| **to** *commit-id*| **last** *number-of-commits*} [**diff**]

## Syntax Description

<i>commit-id</i>	Name of configuration. When a specific <i>commit-id</i> is specified, only the changes that would occur if only the specified commit is rolled back are displayed.
<b>to</b> <i>commit-id</i>	Displays the changes that will occur to the running configuration if the system is rolled back to the configuration specified with the <i>commit-id</i> argument.
<b>last</b> <i>number-of-commits</i>	Displays the changes that will occur to the running configuration if the system is rolled back to the last number of commits specified with the <i>number-of-commits</i> argument.
<b>diff</b>	(Optional) Displays added lines, changed lines, and deleted lines.

## Command Default

None

## Command Modes

EXEC  
Administration EXEC  
Administration configuration  
Global configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for the <b>diff</b> keyword.
Release 3.4.0	No modification.
Release 3.5.0	This command was added to administration EXEC mode.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.

Release	Modification
Release 3.9.0	No modification.

### Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.



#### Note

The most recent 100 commits are retained by the system. As new commit IDs are added, the oldest commit IDs are discarded and are no longer available for rollback operations.

Use the *commit-id* argument without the **to** keyword to display the changes for a particular commit. This can be useful for troubleshooting actions of the **rollback configuration** command.

### Task ID

Task ID	Operations
config-services	read

### Examples

The following example shows sample output from the **show configuration rollback changes** command with the **to commit-id** keyword and argument. The output displays the configuration changes that would occur if the configuration were to be rolled back to the configuration commit specified for the argument.

```
RP/0/0/CPU0:router# show configuration rollback changes to 1000000007
Building configuration...
hostname old-name
end
```

The following example shows sample output from the **show configuration rollback changes** command **last number-of-commits** keyword and argument. The output displays the configuration changes that would occur if the configuration were to be rolled back to the number of configuration commits specified for the argument.

```
RP/0/0/CPU0:router# show configuration rollback changes last 2
Building configuration...
hostname orig_name
interface POS0/1/0/1
 shutdown
!
end
```

The following example shows sample output from the **show configuration rollback changes** command with the **diff** keyword.

In the display, the following symbols signify changes:

- + indicates an added line.
- – indicates a deleted line.

**show configuration rollback changes**

- # indicates a modified line.

```
RP/0/0/CPU0:router
show configuration rollback changes last 1 diff

Building configuration...
 interface Loopback1000
#  ipv4 address 1.1.1.1 255.255.255.255
!
end
```

**Related Commands**

Command	Description
<a href="#">load rollback changes</a>	Populates the target configuration with the contents of a previous configuration.
<a href="#">rollback configuration</a>	Rolls back the configuration to a previous commit.

# show configuration running

To display the running configuration, use the **show configuration running** command in the appropriate mode.

**show configuration running** [ *config-keyword* ]

<b>Syntax Description</b>	<i>config-keyword</i>	(Optional) Specific configuration to display.
---------------------------	-----------------------	---

<b>Command Default</b>	None
------------------------	------

<b>Command Modes</b>	Administration EXEC Administration configuration Global configuration
----------------------	---

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	Release 3.2	This command was introduced.
	Release 3.3.0	No modification.
	Release 3.4.0	No modification.
	Release 3.5.0	No modification.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

<b>Usage Guidelines</b>	To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.
-------------------------	---

Use the **show configuration running** command to display the currently active configuration.

**Task ID**

Task ID	Operations
basic-services	read

**Examples**

This example shows the currently running (committed) configuration from administration mode.

```
RP/0/0/CPU0:router(admin)# show configuration running

Building configuration...
username lab
 secret 5 $1$XNWt$j8RscNdncKSRoMSnqSpbj/
 group root-system
!
end
```

**Related Commands**

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">load</a>	Populates the target configuration with the contents of a previously saved configuration file.
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration running-config

To display the running configuration, use the **show configuration running-config** command in EXEC mode.

**show configuration running-config** [ *config-keyword* ]

<b>Syntax Description</b>	<i>config-keyword</i>	(Optional) Specific configuration to display.
---------------------------	-----------------------	---

<b>Command Default</b>	None
------------------------	------

<b>Command Modes</b>	EXEC
----------------------	------

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	Release 3.2	This command was introduced.
	Release 3.3.0	No modification.
	Release 3.4.0	No modification.
	Release 3.5.0	No modification.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the *config-keyword* argument to display the running configuration for a specific keyword only.

<b>Task ID</b>	<b>Task ID</b>	<b>Operations</b>
	basic-services	read

**Examples**

This example shows the currently running (committed) configuration:

```
RP/0/0/CPU0:router# show configuration running-config

Building configuration...

    !! Last configuration change at 15:36:31 UTC Thu Nov 17 2009 by lab
    sessions Users with active configuration sess
!n
hostname router
line consolestartup Sh
  exec-timeout 0 0onfiguration
!
logging console debugging
  | Ou
snmp-server community public RW
<cr>
RP/0/0/
ipv4 source-routeadmin)#show confi
key chain IPSLA ?
  key 10
    key-string password 1
    ipv4 address 10.0.0.0 255.255.255.0
    encapsulation ppp
    keepalive disable
!
interface POS0/7/0/0
  shutdown
!
interface POS0/7/0/1
  shutdown
!
interface POS0/7/0/2
  shutdown
!
interface POS0/7/0/3
  shutdown
!
  route ipv4 0.0.0.0/0 12.7.0.1
ipsla
  responder
!
!
end
```

**Related Commands**

Command	Description
<a href="#">commit</a>	Merges the target configuration to the running configuration.
<a href="#">load</a>	Populates the target configuration with the contents of a previously saved configuration file.
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.
<a href="#">show configuration commit changes</a>	Displays the changes made to the running configuration by previous configuration commits.
<a href="#">show configuration commit list</a>	Displays information about the configuration commits stored in the commit database.
<a href="#">show configuration failed (config)</a>	Displays information about a configuration that failed during the last commit.



Command	Description
<a href="#">show configuration failed startup</a>	Displays information about a configuration that failed at startup.
<a href="#">show configuration history</a>	Displays history of configuration changes.
<a href="#">show configuration rollback changes</a>	Displays changes that would be made by rolling back the configuration or displays the list of commit IDs.
<a href="#">show configuration running</a>	Displays the contents of the committed configuration.
<a href="#">show configuration sessions</a>	Displays the active configuration sessions.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

# show configuration sessions

To display the active configuration sessions, use the **show configuration sessions** command in administration EXEC mode or in EXEC mode.

**show configuration sessions [detail]**

## Syntax Description

<b>detail</b>	(Optional) Displays detailed information.
---------------	---

## Command Default

None

## Command Modes

EXEC  
Administration EXEC

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Support was added for the <b>detail</b> keyword.
Release 3.4.0	No modification.
Release 3.5.0	<i>Session</i> changed to <i>Current Configuration Session</i> in the display output.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show configuration sessions** command to display the active configuration sessions. Use the **clear configuration sessions** command to clear a configuration session. The **show configuration sessions** command can be used with the **clear configuration sessions** command to verify that an active configuration session was cleared.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

The following example shows sample output from the **show configuration sessions** command:

```
RP/0/0/CPU0:router# show configuration sessions
```

```
Current Configuration Session Line      User      Date                               Lock
00000050-001200bb-00000000      con0_5_CPU cisco     Fri Feb 16 17:23:47 2007
```

**Table 5: show configuration sessions Field Descriptions**

Field	Description
Session	System-generated configuration session ID number.
Line	Line in which the user session was established. In some cases, this field may display “UNKNOWN” or “SYSTEM.” These fields indicate that an internal commit was made by the system.
User	User who initiated the configuration session.
Date	Time and date the configuration session was started.
Lock	Locked running-configuration. An asterisk (*) displayed in this field means the session has been locked. Only one session can lock the running configuration at a time.

**Related Commands**

Command	Description
<a href="#">clear configuration sessions</a>	Clears an active configuration session.

## show default-afi-safi-vrf

To display the default address family identifier (AFI), subaddress family identifier (SAFI), and VPN routing and forwarding (VRF) instance for the current session, use the **show default-afi-safi-vrf** command in EXEC mode.

**show default-afi-safi-vrf**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** EXEC

Command History	Release	Modification
	Release 3.2	This command was introduced.
	Release 3.3.0	Display of the default VPN routing and forwarding (VRF) instance was supported.
	Release 3.4.0	No modification.
	Release 3.5.0	No modification.
	Release 3.6.0	No modification.
	Release 3.7.0	No modification.
	Release 3.8.0	No modification.
	Release 3.9.0	No modification.

**Usage Guidelines** To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show default-afi-safi-vrf** command to display the default AFI and SAFI settings for the current session. The AFI and SAFI settings are controlled by the following commands:

- [set default-afi](#), on page 86
- [set default-safi](#), on page 88
- [set default-vrf](#), on page 90

Task ID	Task ID	Operations
	basic-services	read

### Examples

The following example shows sample output from the **show default-afi-safi-vrf** command:

```
RP/0/0/CPU0:router# show default-afi-safi-vrf

%% Default AFI/SAFI/VRF for this session is:
   Address Family Identifier:   'ipv4'
   Sub-Address Family Identifier: 'unicast'
   Virtual Routing/Forwarding:  ''
```

### Related Commands

Command	Description
<a href="#">set default-afi</a>	Sets the default AFI for the current session.
<a href="#">set default-safi</a>	Sets the default SAFI for the current session.
<a href="#">set default-vrf</a>	Sets the default VRF instance for the current session.

# show history

To display a history of commands executed in EXEC, administration EXEC, administration configuration, or global configuration mode use the **show history** command in one of the supported modes.

**show history [detail]**

## Syntax Description

<b>detail</b>	(Optional) Displays detailed history information.
---------------	---

## Command Default

None

## Command Modes

EXEC  
Administration EXEC  
Administration configuration  
Global configuration

## Command History

Release	Modification
Release 3.4.0	This command was introduced.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **show history** command displays a history of the command entered for the current command mode. For example, enter the **show history** command to display a history of commands entered in EXEC mode. Enter the **show history** command in global configuration mode to display a history of the commands entered in global configuration mode.

Task ID	Task ID	Operations
	config-services	read
	basic-services	read

### Examples

In the following example, the **show history** command is run in EXEC mode to display a history of the command entered in EXEC mode:

```
RP/0/0/CPU0:router# show history
configure
admin
show history
```

In the following example, the **show history** command is run in global configuration mode to display a history of the command entered in global configuration mode:

```
RP/0/0/CPU0:router(config)# show history
interface pos 0/1/0/0
ipv4 address 10.0.0.0
root
end
describe line default autocommand config
line default autocommand configure
end
show history
```

# show running-config

To display the contents of the currently running configuration or a subset of that configuration, use the **show running-config** command in the appropriate mode.

**show running-config** [[**exclude**] *command*] [**sanitized**]

## Syntax Description

<b>exclude</b>	(Optional) Excludes a specific configuration from the display.
<i>command</i>	(Optional) Command for which to display the configuration.
<b>sanitized</b>	(Optional) Displays a sanitized configuration for safe distribution and analysis.

## Command Default

The **show running-config** command without any arguments or keywords displays the entire contents of the running configuration file.

## Command Modes

EXEC  
Administration EXEC  
Any configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.



**Usage Guidelines**

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

You can display either the entire running configuration, or a subset of the running configuration. The subset may be all the commands within a specified command mode.

**Note**

In Cisco IOS XR software, the running configuration is automatically used at system startup, reset, or power cycle. The running configuration is the committed configuration.

**Sanitized Output**

Use the **show running-config** command with the **sanitized** keyword to display the contents of the active running configuration without installation-specific parameters. Some configuration details, such as IP addresses, are replaced with different addresses. The sanitized configuration can be used to share a configuration without exposing the configuration details.

**Command Modes**

When the **show running-config** command is entered in administration configuration mode, the configuration for the administration plane is displayed, including the configured logical routers for the system. When the **show running-config** command is entered in any global configuration mode, or in EXEC mode, the configuration for the specific secure domain router (SDR) is displayed.

The **inheritance** and **no-annotations** keywords are not supported in administration EXEC or configuration modes.

**Excluding Parts of the Display**

Use the **exclude** keyword followed by a *command* argument to exclude a specific configuration from the display.

**Task ID**

Task ID	Operations
config-services	read

**Examples**

This example shows how to enter the **show running-config** command with the question mark (?) online help function to display the available subsets of the running configuration that can be entered to display a subset of the running configuration:

```
RP/0/0/CPU0:router# show running-config ?
aaa                Authentication, Authorization and Accounting
alias              Create an alias for entity
aps                Configure SONET Automatic Protection Switching (APS)
arp                Global ARP configuration subcommands
as-path            BGP autonomous system path filter
as-path-set        Define an AS-path set
```

## show running-config

```

banner          Define a login banner
cdp             Enable CDP, or configure global CDP subcommands
cef            CEF configuration commands
cinetd         Global Cisco inetd configuration commands
class-map      Configure QoS Class-map command
clock         Configure time-of-day clock
community-list Add a community list entry
community-set  Define a community set
controller     Controller configuration subcommands
dhcp          Dynamic Host Configuration Protocol
domain        Domain service related commands
exception     Coredump configuration commands
exclude       Exclude a feature or configuration item from display
explicit-path Explicit-path config commands
extcommunity-set Define an extended community set
fault         Fault related commands
forward-protocol Controls forwarding of physical and directed IP broadcasts
ftp          Global FTP configuration commands
--More--

```

In this example, the **show running-config** command is used to display the running configuration for Packet-over-SONET/SDH (POS) interface 0/2/0/1:

```

RP/0/0/CPU0:router# show running-config interface pos 0/2/0/1

interface POS0/2/0/1
ipv4 address 10.0.0.0 255.0.0.0

```

This example shows sample output from the **show running-config** command with the **sanitized** keyword displays a sanitized version of the running configuration. The sanitized configuration can be used to share a configuration without exposing specific configuration details.

```

RP/0/0/CPU0:router# show running-config sanitized

Building configuration...

!! Last configuration change at 05:26:50 UTC Thu Jan 19 2009 by <removed>
!
snmp-server traps fabric plane
snmp-server traps fabric bundle state
hostname <removed>
line console
exec-timeout 0 0
!
exception choice 1 compress off filepath <removed>
logging console debugging
telnet vrf <removed> ipv4 server max-servers no-limit
snmp-server ifindex persist
snmp-server host 10.0.0.1 traps version <removed> priv <removed> udp-port 2555
snmp-server view <removed> <removed> included
snmp-server community <removed> RO LROwner
snmp-server community <removed> RO LROwner
snmp-server group <removed> v3 priv read <removed> write <removed>
snmp-server traps snmp
snmp-server traps syslog
interface Loopback10
!
interface Loopback1000
!
--More--

```

## Related Commands

Command	Description
<a href="#">show configuration (config)</a>	Displays the contents of the target configuration.

Command	Description
<a href="#">show configuration running-config</a>	Displays the contents of the committed configuration.

# template

To create a template name and enter template configuration mode, use the **template** command in global configuration mode. To remove a template definition, use the **no** form of this command.

**template** *name*

**no template** *name*

## Syntax Description

<i>name</i>	Unique name for the template to be created.
-------------	---

## Command Default

No templates are defined.

## Command Modes

Global configuration

## Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	No modification.
Release 3.4.0	No modification.
Release 3.5.0	No modification.
Release 3.6.0	No modification.
Release 3.7.0	No modification.
Release 3.8.0	No modification.
Release 3.9.0	No modification.

## Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **template** command to enter template configuration mode. From template configuration mode, you can group a subset of configuration commands in a named template. Commonly used sets of configuration commands can be grouped into a named template. Defining a template is similar to creating a C macro function. A template provides modularity and ease of use during user configuration.

Use the **end-template** command to exit template configuration mode. After defining a template, use the **apply-template** command to apply the template. Use the **show running-config** command with the optional **template** keyword and *template-name* argument to display the contents of a template.

### Task ID

Task ID	Operations
config-services	read, write

### Examples

The following example shows how to enter template configuration mode to create a template. In this example, a template named “pre-pos” is defined for the preconfigured Packet-over-SONET/SDH (POS) interface 0/1/0/1. The **end-template** command is used to exit from template configuration mode.

```
RP/0/0/CPU0:router# configure
RP/0/0/CPU0:router(config)# template pre-pos
RP/0/0/CPU0:router(config-TPL)# interface preconfigure pos0/1/0/0
RP/0/0/CPU0:router(config-if-pre)# ipv4 address 10.3.32.154 255.0.0.0
RP/0/0/CPU0:router(config-if-pre)# end-template
RP/0/0/CPU0:router(config)#
```



#### Note

After configuring a template, you may want to display the contents of the configured template. To display a template configuration, use the **show running-config** command with the **template name** keyword and argument.

The following example shows sample output from the **show running-config** command with the **template name** keyword and argument. In this example, the output displays the contents of a template named “pre-pos.”

```
RP/0/0/CPU0:router# show running-config template pre-pos

template pre-pos
 interface preconfigure POS0/1/0/0
   ipv4 address 10.3.32.154 255.0.0.0
 !
end-template
```

### Related Commands

Command	Description
<a href="#">apply-template</a>	Applies a template to the target configuration.
<a href="#">end-template</a>	Exits template configuration mode.
<a href="#">show running-config</a>	Displays the current running (active) configuration.

