



Release Notes for the Cisco Firepower Management Center Remediation Module for ACI, Version 1.0.1_6

Published: September 30, 2016

Updated: May 26, 2021



Features Supported in Version 1.0.1_6

This release enables you to quarantine offending endpoints that are detected by the Cisco Firepower Management Center 5.4.x, using the Application Policy Infrastructure Controller (APIC) version 2.1(1h). Version 1.0.1_6 supports the following features:

	AVS	DVS	Bare Metal
Verified in IPS inline mode	Yes	Yes	Yes
EPG bridge mode	Yes	Yes	Yes
EPG routed mode	Yes	No	No
Multiple IP to one MAC checking	No	Yes	Yes
Create only an IP address filter uSeg attribute	Yes	No	No
Create both an IP address filter and a MAC address filter uSeg attribute	No	Yes	Yes

Downloading and Installing the Software

For instructions on how to download and install the software, see the [Cisco Firepower Management Center Remediation Module for ACI, Version 1.0.1_6 Quick Start Guide](#).

Bug Search

If you're a registered Cisco.com user, view more information about each caveat using the Bug Search tool:

<https://tools.cisco.com/bugsearch>

Resolved Caveats in Version 1.0.1_6

There are no resolved caveats for the Cisco Firepower Management Center Remediation Module for ACI, Version 1.0.1_6.

Open Caveats in Version 1.0.1_6

There are no open caveats for the Cisco Firepower Management Center Remediation Module for ACI, Version 1.0.1_6.

Resolved Enhancement Requests in Version 1.0.1_6

There are no resolved enhancement requests the Cisco Firepower Management Center Remediation Module for ACI, Version 1.0.1_6.

Related Documentation

For additional information about the Cisco Firepower Management Center 6.1 and FireSIGHT Management Center 5.4.x, see the *Configuration Guide for the appropriate version*.

For additional information about the Cisco APIC, see [APIC Documentation](#) and [Cisco Application Centric Infrastructure Security Solution](#).

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see *What's New in Cisco Product Documentation* at: <http://www.cisco.com/c/en/us/td/docs/general/whatsnew/whatsnew.html>.

Subscribe to *What's New in Cisco Product Documentation*, which lists all new and revised Cisco technical documentation as an RSS feed and delivers content directly to your desktop using a reader application. The RSS feeds are a free service

This document is to be used in conjunction with the documents listed in the “[Related Documentation](#)” section.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

©2016-2018 Cisco Systems, Inc. All rights reserved.