

Firewall Information

This chapter contains the following sections:

- Firewall Information, on page 1
- Firewall Information for File Reputation and File Analysis Services, on page 4
- Protecting Email Gateway from Network Attacks, on page 6

Firewall Information

The following table lists the possible ports that may need to be opened for proper operation of Cisco Secure Email Gateway (these are the default values).

Default Port	Protocol	In/Out	Hostname	Purpose	
20/21	ТСР	In or out	AsyncOS IPs, FTP server	FTP for aggregation of log files.	
				Data ports TCP 1024 and higher must also all be open.	
				For more information, search for	
				FTP port information in the Knowledge Base. See	
				Knowledge Base.	
22	ТСР	In	AsyncOS IPs	SSH access to the CLI, aggregation of log files.	
22	ТСР	Out	SSH Server	SSH aggregation of log files.	
22	ТСР	Out	SCP server	SCP push to log server.	
25	ТСР	Out	Any	SMTP to send email.	
25	ТСР	In	AsyncOS IPs	SMTP to receive bounced email or if injecting email from outside firewall.	

Table 1: Firewall Ports

I

53	UDP/TCP	Out	DNS servers	DNS if configured to use Internet root servers or other DNS servers outside the firewall. Also for SenderBase queries.	
80	НТТР	In	AsyncOS IPs	HTTP access to the GUI for system monitoring.	
80	НТТР	Out	downloads.ironport.com	and McAfee definitions.	
80	НТТР	Out	updates.ironport.com	AsyncOS upgradesand McAfee definitions.	
80	НТТР	Out	TAXII servers	Used to allow your email gateway to consume external threat feeds.	
82	НТТР	In	AsyncOS IPs	Used for viewing the spam quarantine.	
83	HTTPS	In	AsyncOS IPs	Used for viewing the spam quarantine.	
110	ТСР	Out	POP server	POP authentication for end users for spam quarantine.	
123	UDP	In & Out	NTP server	NTP if time servers are outside firewall.	
143	ТСР	Out	IMAP server	IMAP authentication for end users for spam quarantine.	
161	UDP	In	AsyncOS IPs	SNMP Queries.	
162	UDP	Out	Management station	SNMP Traps.	
389 or 3268	LDAP	Out	LDAP servers	LDAP if LDAP directory servers are outside firewall. LDAP authentication for Cisco Spam Quarantine.	
636 or 3269	LDAPS	Out	LDAPS	LDAPS — ActiveDirectory's global catalog server (uses SSL).	
443	ТСР	In	AsyncOS IPs	Secure HTTP (https) access to the GUI for system monitoring.	
443	ТСР	Out	res.cisco.com	Verify the latest files for the update server.	
443	ТСР	Out	update-manifests.ironport.com	Obtain the list of the latest files from the update server (for physical hardware email gateways.)	

443	ТСР	Out	update-manifests.sco.cisco.com	Obtain the list of the latest files from the update server (for virtual email gateways.)	
443	ТСР	Out	serviceconfig.talos.cisco.com	Cisco Talos Intelligence Services - to obtain IP reputation, URL	
			grpc.talos.cisco.com	reputation and category, and to	
			email-sender-ip-rep-grpc.talos.cisco.com	send Service Logs details.	
			For IP -based firewall:		
			146.112.62.0/24		
			146.112.63.0/24		
			146.112.255.0/24		
			146.112.59.0/24		
			2a04:e4c7:ffff::/48		
			2a04:e4c7:fffe::/48		
443	ТСР	Out	kinesis.us-west-2.amazonaws.com	U U	
			sensor-provisioner.ep.prod	to Cisco Advanced Phishing Protection cloud service.	
			.agari.com		
			houston.sensor.prod.agari.com		
443	ТСР	In & Out	outlook.office365.com login.microsoftonline.com.	Access to Office 365 services for mailbox auto remediation.	
443	ТСР	In & Out	Hostname of the Microsoft On-premise exchange server	Access to Microsoft On-premise exchange servers for remedating messages from the mailbox.	
443	ТСР	Out	aggregator.cisco.com	Access to the Cisco Aggregator server.	
443	HTTPS	Out	logapi.ces.cisco.com	To upload the debug logs that are collected by Cisco TAC.	
443	HTTPS	Out	TAXII servers	Used to allow your email gateway to consume external threat feeds.	
443	HTTPS	In and Out	api-sse.cisco.com	Used to register your email gateway with Cisco SecureX or Cisco Threat Response.	
443	HTTPS	In and Out	api.eu.sse.itd.cisco.com	Used to register your email gateway with Cisco SecureX or Cisco Threat Response.	

443	HTTPS	In and Out	api.apj.sse.itd.cisco.com	Used to register your email gateway with Cisco SecureX or Cisco Threat Response.	
443	HTTPS	In and Out	est.sco.cisco.com	Used to download a certificate to verify whether your email gateway is accessing a verified site when registering to Cisco SecureX or Cisco Threat Response.	
443	HTTPS	In and Out	AsyncOS IPs	HTTPS access to the GUI using trailblazerconfig CLI command.	
514	UDP/TCP	Out	Syslog server	Syslog logging.	
628	ТСР	In & In	AsyncOS IPs	QMQP if injecting email from outside firewall.	
990	TCP/FTP	Out	cxd.cisco.com	To upload the debug logs that are collected by Cisco TAC.	
1024 and higher	_	_		See information above for Port 21 (FTP.)	
2222	CCS	In & In	AsyncOS IPs	Cluster Communication Service (for Centralized Management).	
	ТСР	Out	AsyncOS IPs	Cisco Spam Quarantine.	
7025	ТСР	In and out	AsyncOS IPs	Pass policy, virus, and outbreak quarantine data between Cisco Secure Email Gateways and Cisco Secure Manager Email and Web Gateways when this feature is centralized.	
6080	НТТР	In or Out	AsyncOS IPs	Access to API ports for HTTP Server	
6443	HTTPS	In or Out	AsyncOS IPs	Access to API ports for HTTPS Server	

Firewall Information for File Reputation and File Analysis Services

The following table lists the possible ports that may need to be opened for proper operation of File Reputation and File Analysis services configured in your email gateway (these are the default values).

Region	Purpose	Hostname	Default Port	Protocol	In / Out
US and North America	File Reputation	cloud-esa-asn. amp.cisco.com cloud-esa-est. amp.cisco.com	443	ТСР	Out.
	File Analysis	panacea.threatgrid.com	443	ТСР	Out
	API	api.amp.cisco.com	443	ТСР	Out
	Event Server	intake.amp.cisco.com	443	ТСР	Out
	Management Server	mgmt.amp.cisco.com	443	ТСР	Out
Canada	File Analysis	panacea.threatgrid.ca	443	ТСР	Out
Europe	File Reputation	cloud-esa-asn. eu.amp.cisco.com cloud-esa-est. eu.amp.cisco.com	443	ТСР	Out
	File Analysis	panacea.threatgrid.eu	443	ТСР	Out
	API	api.eu.amp.cisco.com	443	ТСР	Out
	Event Server	intake.eu.amp.cisco.com	443	ТСР	Out
	Management Server	mgmt.eu.amp.cisco.com	443	ТСР	Out
Australia	File Analysis	panacea.threatgrid.com.au	443	ТСР	Out

Table 2: Firewall Ports

Asia Pacific, Japan, China	File Reputation	cloud-esa-asn. apjc.amp.cisco.com cloud-esa-est. apjc.amp.cisco.com	443	ТСР	Out
	File Analysis	Use European or North American hostnames	443	ТСР	Out
	API	api.apjc.amp.cisco.com	443	ТСР	Out
	Event Server	intake.apjc.amp.cisco.com	443	ТСР	Out
	Management Server	mgmt.apjc.amp.cisco.com	443	ТСР	Out

Protecting Email Gateway from Network Attacks

Make sure that you perform the following prerequisites to protect your email gateway from network attacks:

- Do not expose port 22 (SSH) to your email gateway external IP address.
- Enable only specific IP addresses to manage your email gateway using the web interface and CLI configuration settings.
- [If required] Enable Host Header protection using the adminaccessconfig CLI command.
- Enable Cross Scripting protection using the adminaccessconfig CLI command.
- Do not configure a Relay rule on a public listener.



If you require a relay rule on an external listener, configure 'SMTP AUTH' on a normal public listener.