

Troubleshooting Transient Faults

Transient faults can occur during initial set up and discovery or when a server or virtual machine starts up. You can typically ignore these transient faults, as Firepower Chassis Manager clears them automatically.

This chapter includes the following sections:

- Initial Setup and Discovery Faults, page 4-1
- Virtual Machine Startup Faults, page 4-5

Initial Setup and Discovery Faults

ſ

Table 4-1 describes the transient faults that you may see during the initial setup and discovery process. The Firepower Chassis Manager clears these faults. If you see them during the initial setup or discovery process, you can safely ignore these faults.

| Fault Code | Fault Text | Description |
|------------|---|--|
| F16581 | [FSM:STAGE:RETRY:]: user configuration to secondary(FSM-STAGE:sam:dme: AaaUserEpUpdateUserEp:SetUserPeer) | The FSM could not send the user configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |
| F16745 | [FSM:STAGE:RETRY:]: QoS Classification Definition classification configuration on secondary(FSM-STAGE:sam:dme:QosclassDef initionConfigGlobalQoS:SetPeer) | The FSM could not send the quality of the service configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |
| F16725 | [FSM:STAGE:RETRY:]: VM profile configuration on external VM manager(FSM-STAGE:sam:dme:VnicProfileSe tConfigVmm:SetLocal) | The FSM could not send the VM profile configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |
| F16580 | [FSM:STAGE:RETRY:]: realm configuration to secondary(FSM-STAGE:sam:dme: AaaRealmUpdateRealm:SetRealmPeer) | The FSM could not send the security configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |

 Table 4-1
 Transient Faults that Occur during Initial Setup and Discovery Process

1

| Fault Code | Fault Text | Description (continued) |
|------------|---|--|
| F16724 | <pre>[FSM:STAGE:RETRY:]: external VM manager configuration on local fabric(FSM-STAGE:sam:dme:ExtvmmEpConfig :SetLocal)</pre> | The FSM could not send the VM manager configuration to the primary fabric interconnect during the initial cluster configuration or the setup. |
| F16579 | [FSM:STAGE:RETRY:]: external aaa server configuration to secondary(FSM-STAGE: sam:dme:AaaEpUpdateEp:SetEpPeer) | The FSM could not send the security configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |
| F16749 | [FSM:STAGE:RETRY:]: Uplink eth port configuration on B(FSM-STAGE: sam:dme:SwEthLanBorderDeploy: UpdateConnectivity) | The FSM could not send the eth-uplink configuration to the fabric interconnects during the initial cluster configuration or the setup. |
| F16749 | [FSM:STAGE:RETRY:]: internal network configuration on B(FSM-STAGE: sam:dme:SwAccessDomainDeploy: UpdateConnectivity) | The FSM could not send the internal network configuration to the fabric interconnects during the initial cluster configuration or the setup. |
| F16749 | [FSM:STAGE:RETRY:]: Uplink fc port configuration on B(FSM-STAGE:sam: dme:SwFcSanBorderDeploy: UpdateConnectivity) | The FSM could not send the fibre channel uplink configuration to the fabric interconnects during the initial cluster configuration or the setup. |
| F16680 | [FSM:STAGE:RETRY:]: Enable virtual interface on local fabric interconnect (FSM-STAGE:sam:dme:MgmtIfEnableVip: Local) | The FSM could not send the virtual interface configuration to the fabric interconnects during the initial cluster configuration or the setup. |
| F16579 | [FSM:STAGE:RETRY:]: keyring configuration on secondary(FSM-STAGE: sam:dme:PkiEpUpdateEp:SetKeyRingPeer) | The FSM could not send the security configuration to the subordinate fabric interconnect during the initial cluster configuration or the setup. |
| F16539 | <pre>[FSM:STAGE:RETRY:]: Fabric interconnect mode configuration to primary(FSM-STAGE: sam:dme:FabricLanCloudSwitchMode: SwConfigPeer)</pre> | The FSM could not send the end-host mode configuration on to the primary fabric interconnect during the initial cluster configuration or the setup. |
| F0429 | Fabric Interconnect A, HA functionality not ready | The cluster configuration cannot be completed until the chassis discovery is completed. |
| F0400 | Chassis 1 connectivity configuration: un-acknowledged | Firepower Chassis Manager discovered the chassis with only one link in the first attempt although the chassis discovery policy is configured for four links. Firepower Chassis Manager reacknowledges the chassis to activate the other links. |

 Table 4-1
 Transient Faults that Occur during Initial Setup and Discovery (continued)Process

Γ

| Fault Code | Fault Text | Description (continued) |
|------------|--|--|
| F0401 | IOM 1/2 (B) current connectivity does not match discovery policy: unsupported-connectivity | Firepower Chassis Manager discovered the chassis with only one link in the first attempt although the chassis discovery policy is configured for four links. |
| | | Firepower Chassis Manager can clear this fault when the communication is established between the chassis and the fabric interconnect with that link. |
| F0440 | Chassis discovery policy conflict: Link IOM 1/2/2 to fabric interconnect B:1/1 not configured | Firepower Chassis Manager discovered the chassis with only one link in the first attempt although the chassis discovery policy is configured for four links. Until the discovery is successful with that link, the remaining links cannot be marked as active. |
| | | Firepower Chassis Manager can clear this fault when the communication is established between the chassis and the fabric interconnect with that link. |
| F0332 | AssociatePnuOSLocalDiskConfig fails with Service-Unavailable | During discovery, the server association failed due to an error when configuring the local disk controller. |
| | | The associated remote invocation error code is 4106. |
| F0277 | ether port 1 on fabric interconnect B oper state: link-up, reason: FEX not configured | Firepower Chassis Manager discovered the chassis with only one link in the first attempt although the chassis discovery policy is configured for four links. Until the discovery is successful with that link, the remaining links cannot be marked as active. |
| F0276 | ether port 4 on fabric interconnect B oper state: link-down, reason: Link failure or not-connected | One or more of the links on the chassis flapped during the initial discovery. This fault is generated when the link is down during the flapping. |
| F0206 | Adapter 1/2/1 is unreachable | During discovery, the adapter information cannot be accessed from the server. This fault clears as soon as the information is available. |
| F0283 | VIF 1 / 2 B-42/44 down, reason: Bound Physical Interface Down | The internal VIF that the Firepower Chassis Manager uses during discovery failed. |

1

| Fault Code | Fault Text | Description (continued) |
|------------|--|--|
| F0367 | No link between IOM port 1/1/2 and fabric interconnect A:1/2 | The ethernet server ports flapped on the fabric interconnect during the initial discovery, because the discovery policy was configured for more than one link. |
| | | Firepower Chassis Manager clears this fault when the initial discovery succeeds with one link and the other links can be marked as active. |
| F0399 | Current connectivity for chassis 1 does not match discovery policy: unsupported-connectivity | Firepower Chassis Manager discovered the chassis with only one link in the first attempt although the chassis discovery policy is configured for four links. Until the discovery is successful with that link, the remaining links cannot be marked as active. |
| F16520 | [FSM:STAGE:RETRY:]: Identify pre-boot environment agent on server 1/2 (FSM-STAGE:sam:dme:ComputeBlade Discover:PnuOSIdent) | The FSM failed to identify the pre-boot environment on the server during discovery. |
| F77960 | [FSM:STAGE:REMOTE-ERROR]: Result: end-point-unavailable Code: unspecified Message: Waiting for BIOS POST Completion information from IBMC(sam:dme:ComputeBladeDiscover: BiosPostCompletion) | The FSM did not receive a response from the server during discovery and is waiting for the BIOS POST completion information. |
| F0320 | Server 1/1 (service profile:) has an invalid FRU: mismatch-identity-unestablishable | Firepower Chassis Manager could not identify the FRUs from the servers during initial discovery. |
| F77959 | <pre>[FSM:STAGE:REMOTE-ERROR]: Result: unidentified-fail Code: ERR-0505-IBMC-fru-retrieval-error Message: Could not get Fru from 7f060101, dn=fabric/server/chassis-1/slot-1 (sam:dme:FabricComputeSlotEpIdentify:Ex ecuteLocal)</pre> | Firepower Chassis Manager could not identify the FRUs from the servers during initial discovery. |
| F16406 | <pre>[FSM:STAGE:RETRY:]: triggering chassis discovery via IOM 1/2(right)(FSM-STAGE:sam:dme:EquipmentI OCardFeConn:DiscoverChassis)</pre> | In a cluster configuration, after the Firepower Chassis Manager discovers the chassis through the I/O module connected to the primary fabric interconnect, it raises discovery through the I/O module connected to the secondary fabric interconnect. |

 Table 4-1
 Transient Faults that Occur during Initial Setup and Discovery (continued)Process

I

Virtual Machine Startup Faults

When you power on a virtual machine on a server that has network adaptors connected to a distributed virtual wwitch through a port profile, the Events tab of the VMware vCenter may display the following event:

Virtual machine powered On with vNICs connected to dvPorts that have a port level configuration, which might be different from the dvPort group configuration.

If you see this event, you can safely ignore it.

