



## Secure Firewall Migration Tool Best Practices Guide

### [Overview](#) 2

[Best Practices Before Migration](#) 2

[Best Practices During Migration](#) 2

[Best Practices After Migration](#) 3

[Troubleshooting for Firewall Migration Tool](#) 4

[Full Cisco Trademarks with Software License](#) ?

# Overview

This guide provides essential best practices to ensure a smooth, secure, and efficient transfer of settings and policies from a source to a target firewall, minimizing disruption and optimizing security posture post-migration.

## Best Practices Before Migration

Thorough preparation is crucial for successful firewall migration. Adhere to the following best practices:

- **Identify Devices and Software Versions:** Clearly identify both your source and target firewall devices and their respective software versions. For more information, see [Cisco Secure Firewall Migration Tool Compatibility Guide](#).
- **Define Migration Scope:** Determine precisely what you intend to migrate: a full configuration, partial settings, or specific policies.
- **Engage Stakeholders:** Involve all relevant stakeholders, such as Network, Security, and Chain Management teams, to align on migration goals and timelines.
- **Document Network Topology:** Create a comprehensive map of your current network architecture. This will help you understand dependencies and plan the migration effectively.
- **Confirm Maintenance Window:** Secure a tentative or fixed maintenance window to minimize any potential disruption to services.
- **Backup Everything:** Perform a full configuration backup of the source firewall. This must include certificates, VPN keys, and any connect packages.
- **Validate Access and Licenses:** Ensure you have SSH, HTTPS, or console access to both the source and destination firewalls. Additionally, validate that all necessary licenses are active on the target device.
- **Perform Health Checks:** Conduct health checks on all devices involved in the migration to confirm their readiness.
- **Prepare Target Firewall:** If required, perform a factory reset or clear existing configurations on the target firewall. Confirm that its software version matches your migration plan.

## Best Practices During Migration

After the preparations are complete, follow these best practices while actively using the Secure Firewall Migration Tool:

- **Install the Latest Firewall Migration Tool:** Download and install the most current version of the Firewall Migration Tool from [Software Download](#) page. Then, validate the tool's functionality before starting any migration.
- **Perform Dry Run or Test:** Execute a dry-run migration. Test the process in a lab environment, or use the demo mode in the Firewall Migration Tool. These actions help identify and resolve potential issues in advance. Review the pre-migration instructions available on the Firewall Migration Tool homepage.

**Select Source Configuration**

Source Firewall Vendor  
Cisco ASA (8.4+)

Start Migration Demo Mode

**Cisco ASA (8.4+) Pre-Migration Instructions**

This migration may take a while. Do not make any changes to the Firewall Management Center (FMC) when migration is in progress.

**Session Telemetry:**  
Cisco collects the firewall telemetry set forth below in connection with this migration. By completing the migration, you consent to Cisco's collection and use of this telemetry data for By completing the migration, you consent to Cisco's collection and use of this telemetry data for purposes of tracking and following up on firewall device migrations and performing related migration analytics.

**Acronyms used:**  
FMT: Firewall Migration Tool  
FMC: Firewall Management Center  
FTD: Firewall Threat Defense

Before you begin your Adaptive Security Appliance (ASA) to Firewall Threat Defense migration, you must have the following items:

- Stable IP Connection:**  
Ensure that the connection is stable between FMT and FMC.
- FMC Version:**  
Ensure that the FMC version is 6.2.3 or later. For optimal migration time, improved software quality and stability, use the suggested release for your FTD and FMC. Refer to the gold star on CCO for the suggested release.
- FMC Account:**  
Create a dedicated user account with administrative privileges for the FMT and use the credentials during migration.
- FTD (Optional):**  
To migrate the device configurations like interfaces, routes, and so on, add the target device to FMC. Skip this step if you want to migrate only the shared configurations like objects, NAT, ACL, and so on.
- ASA Configuration Requirements:**  
Export configuration file from ASA to .cfg or .txt format. Connect to live ASA to extract the configuration file for one or more contexts. To migrate following features in ASA:
  - Time Based ACLs:** FMC and FTD must be on 6.6 or later versions.
  - IP SLA Monitor:** FMC must be on 6.6 or later and FTD must be on 6.2.3 or later.
  - Object Group Search:** FMC and FTD must be on 6.6 or later versions.

- **Freeze Configuration Changes:** Do not make any configuration changes on the source firewall during the migration process. If any changes must occur, ensure they are applied to the target firewall after migration.
- **Push Configuration:** Ensure that all prior steps are completed and the system is ready. Then, use the Firewall Migration Tool to push the configuration to the target firewall.

## Best Practices After Migration

Post-migration verification and optimization are critical to ensure a successful and secure transition:

- **Download Post-Migration Report:** Always download the post-migration report generated by FMT. In case of any failures or issues, contact TAC (Technical Assistance Center) immediately.

**Complete Migration**

Source:  
Target :

**Migration Status**

Click Here to download troubleshooting bundle

**Manual Upload:** Fortinet Config.conf

**Migration Summary (Post Push)**

Please download the Post Migration Report for a detailed summary. Download Report

New Migration

- **Verify Connectivity:** Test network connectivity by using ping or traceroute tools on key IP addresses in your environment.

- **Test VPNs and Rules:** Validate the functionality of Site-to-Site and remote access VPNs, access rules, NAT functionality, and logging.
- **Review Integrations:** Check that all integrated services, such as syslog, SNMP, NTP, DNS, and monitoring tools, are running as expected.
- **Optimize Policies:** After confirming connectivity, use the policy analyzer and policy optimizer in Security Cloud Control to refine your access policies.

## Troubleshooting for Firewall Migration Tool

This section describes troubleshooting steps and resources for the Firewall Migration Tool.

Migration failures often occur during the upload of the source configuration file or during the push of the migrated configuration to the Firewall Management Center.

Common causes include:

- Invalid or unexpected files in the source configuration archive.
- Missing or incomplete configuration elements.
- Unsupported file formats or compression types.
- Parsing errors due to unrecognized or malformed configuration lines.
- Network connectivity issues during migration.

## Firewall Migration Tool Support Bundle

The Firewall Migration Tool provides a support bundle that contains valuable troubleshooting information such as log files, DB, and configuration files. To download the support bundle:

1. On the **Complete Migration** screen, click the **Support** button.
2. Check the **Support Bundle** check box and then select the configuration files to download.




---

**Note** The Log and DB files are selected for download by default.

---

3. Click **Download**.

The support bundle downloads as a zip file to your local path. Extract the zip file to view the log, database, and configuration files.

4. Click **Email us** to email the failure details to the technical team.

You can also attach the downloaded support files to your email.

5. Click **Visit TAC page** to create a Cisco Technical Assistance Center (TAC) case for this failure.




---

**Note** You can open a TAC case, at any time during the migration, from the support page.

---

## Logs and Other Files Used for Troubleshooting

The table lists the names and locations of files used for identifying and troubleshooting issues.

File	Location
log file	<migration_tool_folder>\logs
pre-migration report	<migration_tool_folder>\resources
post-migration report	<migration_tool_folder>\resources
unparsed file	<migration_tool_folder>\resources

## Error Messages with Workaround

This section lists errors reported in the Firewall Migration Tool and their recommended actions.

**Error:** Error While Pushing Network Groups: No Data

Explanation	Recommended Action
This error occurs in the source configuration file, when there is an object that has no IP Address or port value defined to it.	Check the verbose logs on the Firewall Migration Tool to identify the file that has the error. Extract the configuration file again using the Web Visualization Tool. This problem occurs because of an export issue in Check Point. If the issue persists, contact TAC to create a case for this failure and provide the support bundle downloaded from the Firewall Migration Tool.  For information on how to download support bundle, see <a href="#">Firewall Migration Tool Support Bundle, on page 4</a> .

**Error:** VLAN Interface Type is Not Supported on This Device Model

Explanation	Recommended Action
This error occurs if you are using an older version of the Firewall Migration Tool.	Download the latest version of the Firewall Migration Tool to proceed with the migration.

**Error:** Access-list in bulk [1 - 1000] Another operation by another user prevented this operation. Please retry.

Explanation	Recommended Action
This error occurs when multiple users try to connect to the management center as the Firewall Migration Tool during the migration.	Avoid multiple connections to the management center when the Firewall Migration Tool is migrating a configuration.

**Error:** Another operation by another user prevented this operation. Please retry after sometime.

Explanation	Recommended Action
This error occurs when multiple users try to connect to the management center as the Firewall Migration Tool during the migration.	Avoid multiple connections to the management center when the Firewall Migration Tool is migrating a configuration.

**Error:** Object deletion restricted for Outside. Remove object from the following: Device - AUMEL DHCP Relay Se

Explanation	Recommended Action
This error occurs when the management center has several existing configurations and the Firewall Migration Tool is unable to clear the attributes of the device-specific configurations during the Push Phase.	Clear the existing configurations on the management center and proceed with the migration. If the issue persists, contact Cisco TAC to create a TAC case for this failure and provide the support bundle downloaded from the Firewall Migration Tool.

**Error:** Invalid logical name used by Ethernet1/2. The name is being used in policies that are not supported by the Migration Tool. We recommend that you use a clean device for migration

Explanation	Recommended Action
This error occurs when the management center has several existing configurations and the Firewall Migration Tool is unable to clear the attributes of the device-specific configurations during the Push Phase.	Clear the existing configurations on the management center and proceed with the migration. If the issue persists, contact Cisco TAC to create a TAC case for this failure and provide them with the support bundle downloaded from the Firewall Migration Tool.

**Error:** System experienced internal issues, please check the logs

Explanation	Recommended Action
This error occurs when the management center has several existing configurations and the Firewall Migration Tool is unable to clear the attributes of the device-specific configurations during the Push Phase.	Clear the existing configurations on the management center and proceed with the migration. If the issue persists, contact Cisco TAC to create a TAC case for this failure and provide them with the support bundle downloaded from the Firewall Migration Tool.

**Error:** [PushException(PushException(Exception('Cannot modify the interface which is a member of EtherChannel interface.'),)), 'interfaces']

Explanation	Recommended Action
This error occurs when the management center has several existing configurations and the Firewall Migration Tool is unable to clear the attributes of the device-specific configurations during the Push Phase.	Clear the existing configurations on the management center and proceed with the migration. If the issue persists, contact Cisco TAC to create a TAC case for this failure and provide them with the support bundle downloaded from the Firewall Migration Tool.

**Error:** Management Center Connection Issue

Explanation	Recommended Action
This error occurs when the Firewall Migration Tool loses connectivity to the management center.	Check the network connectivity.

**Error:** Invalid URL

Explanation	Recommended Action
This error occurs when the Firewall Migration Tool supports the migration of a particular feature. For example, ACE Category Migration. The management center or the threat defense is not of the version that has the API support for the feature.	Refer to the Firewall Migration Tool User Guide and upgrade the management center or threat defense to the required version.

**Error:** No Resource Found

Explanation	Recommended Action
This error occurs when the Firewall Migration Tool supports the migration of a particular feature. For example, ACE Category Migration. The management center or the threat defense is not of the version that has the API support for the feature.	Refer to the Firewall Migration Tool user guide, and upgrade the management center or threat defense to the required version.

**Error:** network objects of type [host] bulk on [1-50] - {"error":{"category":"FRAMEWORK","messages":[{"description":"Invalid object ? is not allowed as the last character in an object description Please remove or replace ? and retry"}],"severity":"ERROR"}}

Explanation	Recommended Action
This error occurs when there are special characters in the Object description parameter of an object.	Check the verbose logs to identify the source configuration and the object that include special characters, that management center does not support. Correct the source configuration, then upload and migrate the configuration again by using the Firewall Migration Tool.

**Error:** Object with the same name already exists

Explanation	Recommended Action
This error occurs when Firewall Migration Tool is unable to validate the parsed configuration against the configuration elements available on the management center such as objects. This can be caused by any one of several reasons such as loss of connectivity.	Resume the migration, revalidate, and push the configuration by selecting <b>resume &gt; validate &gt; push</b> .

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2025 Cisco Systems, Inc. All rights reserved.





**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA 95134-1706  
USA

**Asia Pacific Headquarters**  
CiscoSystems(USA)Pte.Ltd.  
Singapore

**Europe Headquarters**  
CiscoSystemsInternationalBV  
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).