



Reference

- [Traffic Flow and Inspection, on page 1](#)
- [Time and Disk Space, on page 4](#)
- [Upgrade Feature History, on page 5](#)

Traffic Flow and Inspection

Schedule maintenance windows when upgrade will have the least impact, considering any effect on traffic flow and inspection.

Traffic Flow and Inspection for Firewall Threat Defense Upgrades

Software Upgrades for Standalone Devices

Devices operate in maintenance mode while they upgrade. Entering maintenance mode at the beginning of the upgrade causes a 2-3 second interruption in traffic inspection. Interface configurations determine how a standalone device handles traffic both then and during the upgrade.

Table 1: Traffic Flow and Inspection: Software Upgrades for Standalone Devices

Interface Configuration		Traffic Behavior
Firewall interfaces	Routed or switched including EtherChannel, redundant, subinterfaces. Switched interfaces are also known as bridge group or transparent interfaces.	Dropped. For bridge group interfaces on the ISA 3000 only, you can use a FlexConfig policy to configure hardware bypass for power failure. This causes traffic to drop during software upgrades but pass without inspection while the device completes its post-upgrade reboot.

Interface Configuration		Traffic Behavior
IPS-only interfaces	Inline set, hardware bypass force-enabled: Bypass: Force	Passed without inspection until you either disable hardware bypass, or set it back to standby mode.
	Inline set, hardware bypass standby mode: Bypass: Standby	Dropped during the upgrade, while the device is in maintenance mode. Then, passed without inspection while the device completes its post-upgrade reboot.
	Inline set, hardware bypass disabled: Bypass: Disabled	Dropped.
	Inline set, no hardware bypass module.	Dropped.
	Inline set, tap mode.	Egress packet immediately, copy not inspected.
	Passive, ERSPAN passive.	Uninterrupted, not inspected.

Software Upgrades for High Availability and Clustered Devices

You should not experience interruptions in traffic flow or inspection while upgrading high availability or clustered devices. For high availability pairs, the standby device upgrades first. The devices switch roles, then the new standby upgrades.

For clusters, the data security module or modules upgrade first, then the control module. During the control security module upgrade, although traffic inspection and handling continues normally, the system stops logging events. Events for traffic processed during the logging downtime appear with out-of-sync timestamps after the upgrade is completed. However, if the logging downtime is significant, the system may prune the oldest events before they can be logged.

Note that hitless upgrades are not supported for single-unit clusters. Interruptions to traffic flow and inspection depend on interface configurations of the active unit, just as with standalone devices.

Software Revert (Major/Maintenance Releases)

You should expect interruptions to traffic flow and inspection during revert, even in a high availability/scalability deployment. This is because revert is more successful when all units are reverted simultaneously. Simultaneous revert means that interruptions to traffic flow and inspection depend on interface configurations only, as if every device were standalone.

Software Uninstall (Patches)

For standalone devices, interruptions to traffic flow and inspection during patch uninstall are the same as for upgrade. In high availability/scalability deployments, you must explicitly plan an uninstall order that minimizes disruption. This is because you uninstall patches from devices individually, even those that you upgraded as a unit.

Traffic Flow and Inspection for Chassis Upgrades

Upgrading FXOS reboots the chassis. For FXOS upgrades to Version 2.14.1+ that include firmware upgrades, the chassis reboots twice—once for FXOS and once for the firmware. This includes Version 7.4.1+ chassis upgrades for the Secure Firewall 3100/4200 in multi-instance mode.

Even in high availability or clustered deployments, you upgrade FXOS on each chassis independently. To minimize disruption, upgrade one chassis at a time; see [Upgrade Order](#).

Table 2: Traffic Flow and Inspection: FXOS Upgrades

Firewall Threat Defense Deployment	Traffic Behavior	Method
Standalone	Dropped.	—
High availability	Unaffected.	Best Practice: Update FXOS on the standby, switch active peers, upgrade the new standby.
	Dropped until one peer is online.	Upgrade FXOS on the active peer before the standby is finished upgrading.
Inter-chassis cluster	Unaffected.	Best Practice: Upgrade one chassis at a time so at least one module is always online.
	Dropped until at least one module is online.	Upgrade chassis at the same time, so all modules are down at some point.
Intra-chassis cluster (Firepower 9300 only)	Passed without inspection.	Hardware bypass enabled: Bypass: Standby or Bypass-Force .
	Dropped until at least one module is online.	Hardware bypass disabled: Bypass: Disabled .
	Dropped until at least one module is online.	No hardware bypass module.

Traffic Flow and Inspection when Deploying Configurations

Snort typically restarts during the first deployment immediately after upgrade. This means that for Cloud-Delivered Firewall Management Center upgrades, Snort could restart on all managed devices. Snort does not restart after subsequent deployments unless, before deploying, you modify specific policy or device configurations.

Restarting the Snort process briefly interrupts traffic flow and inspection on all devices, including those configured for high availability/scalability. Interface configurations determine whether traffic drops or passes without inspection during the interruption. When you deploy without restarting Snort, resource demands may result in a small number of packets dropping without inspection.

Table 3: Traffic Flow and Inspection: Deploying Configuration Changes

Interface Configuration		Traffic Behavior
Firewall interfaces	Routed or switched including EtherChannel, redundant, subinterfaces. Switched interfaces are also known as bridge group or transparent interfaces.	Dropped.
IPS-only interfaces	Inline set, Failsafe enabled or disabled.	Passed without inspection. A few packets might drop if Failsafe is disabled and Snort is busy but not down.
	Inline set, Snort Fail Open: Down: disabled.	Dropped.
	Inline set, Snort Fail Open: Down: enabled.	Passed without inspection.
	Inline set, tap mode.	Egress packet immediately, copy not inspected.
	Passive, ERSPAN passive.	Uninterrupted, not inspected.

Time and Disk Space

Time to Upgrade

We recommend you track and record your own upgrade times so you can use them as future benchmarks. The following table lists some things that can affect upgrade time.



Caution Do not make or deploy configuration changes during upgrade. Even if the system appears inactive, do not manually reboot or shut down. In most cases, do not restart an upgrade in progress. You could place the system in an unusable state and require a reimage. If you encounter issues with the upgrade, including a failed upgrade or unresponsive appliance, see [Unresponsive and Failed Firewall Threat Defense Upgrades](#).

Table 4: Upgrade Time Considerations

Consideration	Details
Versions	Upgrade time usually increases if your upgrade skips versions.
Models	Upgrade time usually increases with lower-end models.
Virtual appliances	Upgrade time in virtual deployments is highly hardware dependent.

Consideration	Details
High availability and clustering	In a high availability or clustered configuration, devices upgrade one at a time to preserve continuity of operations, with each device operating in maintenance mode while it upgrades. Upgrading a device pair or entire cluster, therefore, takes longer than upgrading a standalone device.
Configurations	Upgrade time can increase with the complexity of your configurations.
Components	You may need additional time to perform operating system or virtual hosting upgrades, upgrade package transfers, readiness checks, VDB and intrusion rule (SRU/LSP) updates, configuration deployment, and other related tasks.

Disk Space to Upgrade

To upgrade, the upgrade package must be on the device. For device upgrades where the device does not have access to the internet, you must also have enough space on the Cloud-Delivered Firewall Management Center (in either /Volume or /var) for the device upgrade package. Or, you can use an internal server to store them. Readiness checks should indicate whether you have enough disk space to perform the upgrade. Without enough free disk space, the upgrade fails. For more information, see [Configuration and Deployment Checks](#).

Upgrade Feature History

Table 5: Device Upgrade Feature History

Feature	Minimum Management Center	Minimum Threat Defense	Details
New device and chassis upgrade wizard	20251121	Any	<p>A new, streamlined upgrade wizard makes it easier to select and prepare devices for upgrade, and to identify issues preventing upgrade.</p> <p>Note that the Firewall Threat Defense wizard takes advantage of a new prepare-only option for unattended mode. This means that while the wizard copies packages and checks readiness, you may see messages about unattended mode running even if you did not explicitly start it.</p>
Prepare-only and skip-checks options for unattended Firewall Threat Defense upgrade	20251121	Any	<p>With unattended Firewall Threat Defense upgrades:</p> <ul style="list-style-type: none"> • Prepare for upgrade only—copy packages and check readiness, but do not perform the actual upgrade. • Skip readiness checks for devices that already passed. <p>These new options are available when you start unattended mode.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
New options for downloading upgrade packages	20251121	Any	<p>You can now:</p> <ul style="list-style-type: none"> Prevent devices from downloading upgrade packages from the internet. That is, you can now require that devices get upgrade packages from the Cloud-Delivered Firewall Management Center or an internal server, even if the devices have internet access. Specify how long devices retry failed downloads from an internal server or the internet. This setting does not apply to transfers between the Cloud-Delivered Firewall Management Center and device. <p>New/modified screens: Administration > Product Upgrades > Global upgrade settings</p>
Deprecated: Monitor device revert in the Message Center	20251121	Any	<p>You can no longer monitor device revert from the Message Center. Instead, use the Device Management page (Devices > Device Management). On the Upgrade tab, click View Details next to the device you are reverting.</p>
Upgrade Firewall Threat Defense or chassis without a manual readiness check.	20250219	7.7.0	<p>You no longer have to run time-consuming pre-upgrade readiness checks for Firewall Threat Defense or chassis upgrades. Instead, these checks are now regularly run by the system and reported in the health monitor. This allows you to preemptively fix any issues that will block upgrade.</p> <ul style="list-style-type: none"> The Database module, new for devices, manages monitors database schema and configuration data (<i>EO</i>) integrity. The FXOS Health module, new for devices, monitors the FXOS httpd service on FXOS-based devices. The Disk Status module is now more robust, alerting on disk health issues reported by daily running of smartctl (a Linux utility for monitoring reliability, predicting failures, and performing other self-tests). <p>Version restrictions: This feature is supported for upgrades <i>from</i> Version 7.7+. Devices running earlier versions still require the in-upgrade readiness check.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Devices with internet access download upgrade packages from the internet.	20250219	Any	<p>You can now begin device and chassis upgrades without the upgrade package. At the appropriate time, devices will get the package directly from the internet. This saves time and Cloud-Delivered Firewall Management Center disk space.</p> <p>Devices without internet access can continue to get the package from the Cloud-Delivered Firewall Management Center or an internal server. Note that devices try the internal server (if configured) before either the internet or the Cloud-Delivered Firewall Management Center. If the internal server download fails, newer devices with internet access try the internet then the Cloud-Delivered Firewall Management Center, while older devices and devices without internet access just try the Cloud-Delivered Firewall Management Center. (In this context, "newer" means Firewall Threat Defense 7.6+ or chassis 7.4.1+.)</p> <p>Restrictions: Cloud-Delivered Firewall Management Center and devices must be able to access the internet. There is no way to force a device with internet access to try the Cloud-Delivered Firewall Management Center before it tries the internet. Not supported for hotfixes.</p> <p>Download location: https://cdo-ftd-images.s3-us-west-2.amazonaws.com/</p>
Generate and download post-upgrade configuration change reports from the Firewall Threat Defense and chassis upgrade wizards.	20240808	Any	<p>You can now generate and download post-upgrade configuration change reports from the Firewall Threat Defense and chassis upgrade wizards, as long as you have not cleared your upgrade workflow.</p> <p>Previously, you used the Advanced Deploy screens to generate the reports and the Message Center to download them. Note that you can still use this method, which is useful if you want to quickly generate change reports for multiple devices, or if you cleared your workflow.</p> <p>New/modified screens:</p> <ul style="list-style-type: none"> • Devices > Threat Defense Upgrade > Configuration Changes • Devices > Chassis Upgrade > Configuration Changes
Chassis upgrade for the Secure Firewall 3100 in multi-instance mode.	20240808	7.4.1	<p>For the Secure Firewall 3100 in multi-instance mode, you upgrade the operating system and the firmware (<i>chassis upgrade</i>) separately from the container instances (<i>Firewall Threat Defense upgrade</i>).</p> <p>New/modified screens:</p> <ul style="list-style-type: none"> • Upgrade the chassis: Devices > Chassis Upgrade • Upgrade Firewall Threat Defense Devices > Threat Defense Upgrade

Feature	Minimum Management Center	Minimum Threat Defense	Details
Firmware upgrades included in FXOS upgrades.	20240203	Any	<p>Chassis/FXOS upgrade impact. Firmware upgrades cause an extra reboot.</p> <p>For the Firepower 4100/9300, FXOS upgrades to Version 2.14.1 now include firmware upgrades. Secure Firewall 3100 in multi-instance mode (new in Version 7.4.1) also bundles FXOS and firmware upgrades. If any firmware component on the device is older than the one included in the FXOS bundle, the FXOS upgrade also updates the firmware. If the firmware is upgraded, the device reboots twice—once for FXOS and once for the firmware.</p> <p>Just as with software and operating system upgrades, do not make or deploy configuration changes during firmware upgrade. Even if the system appears inactive, do not manually reboot or shut down during firmware upgrade.</p> <p>See: Cisco Firepower 4100/9300 FXOS Firmware Upgrade Guide</p>
Choose and direct-download upgrade packages to the Cloud-Delivered Firewall Management Center.		Any	<p>You can now choose which Firewall Threat Defense upgrade packages you want to direct download to the Cloud-Delivered Firewall Management Center. Use the new Download Updates sub-tab on > Updates > Product Updates.</p> <p>Version restrictions: this feature is replaced by an improved package management system in Version 20240203.</p>
Auto-upgrade to Snort 3 after successful Firewall Threat Defense upgrade is no longer optional.		Any	<p>Upgrade impact. All eligible devices upgrade to Snort 3 when you deploy.</p> <p>When you upgrade Firewall Threat Defense to Version 7.3+, you can no longer disable the Upgrade Snort 2 to Snort 3 option.</p> <p>After the software upgrade, all eligible devices will upgrade from Snort 2 to Snort 3 when you deploy configurations. Although you can switch individual devices back, Snort 2 is not supported on Firewall Threat Defense 7.7+. You should stop using it now.</p> <p>For devices that are ineligible for auto-upgrade because they use custom intrusion or network analysis policies, manually upgrade to Snort 3 for improved detection and performance. For migration assistance, see the Custom Snort 3 Intrusion Policies for Access Control for your version.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Combined upgrade and install package for Secure Firewall 3100.		7.3.0	<p>Reimage Impact.</p> <p>In Version 7.3, we combined the Firewall Threat Defense install and upgrade package for the Secure Firewall 3100, as follows:</p> <ul style="list-style-type: none"> • Version 7.1–7.2 install package: <code>cisco-ftd-fp3k.version.SPA</code> • Version 7.1–7.2 upgrade package: <code>Cisco_FTD_SSP_FP3K_Upgrade-version-build.sh.REL.tar</code> • Version 7.3+ combined package: <code>Cisco_FTD_SSP_FP3K_Upgrade-version-build.sh.REL.tar</code> <p>Although you can upgrade Firewall Threat Defense without issue, you cannot reimage from older Firewall Threat Defense and ASA versions directly to Firewall Threat Defense Version 7.3+. This is due to a ROMMON update required by the new image type. To reimage from those older versions, you must "go through" ASA 9.19+, which is supported with the old ROMMON but also updates to the new ROMMON. There is no separate ROMMON updater.</p> <p>To get to Firewall Threat Defense Version 7.3+, your options are:</p> <ul style="list-style-type: none"> • Upgrade from Firewall Threat Defense Version 7.1 or 7.2 — use the normal upgrade process. See the appropriate Upgrade Guide. • Reimage from Firewall Threat Defense Version 7.1 or 7.2 — reimage to ASA 9.19+ first, then reimage to Firewall Threat Defense Version 7.3+. See <i>Threat Defense→ASA: Firepower 1000, 2100; Secure Firewall 3100</i> and then <i>ASA→Threat Defense: Firepower 1000, 2100 Appliance Mode; Secure Firewall 3100</i> in the Cisco Secure Firewall ASA and Secure Firewall Threat Defense Reimage Guide. • Reimage from ASA 9.17 or 9.18 — upgrade to ASA 9.19+ first, then reimage to Firewall Threat Defense Version 7.3+. See the Cisco Secure Firewall ASA Upgrade Guide and then <i>ASA→Threat Defense: Firepower 1000, 2100 Appliance Mode; Secure Firewall 3100</i> in the Cisco Secure Firewall ASA and Secure Firewall Threat Defense Reimage Guide. • Reimage from Firewall Threat Defense Version 7.3+ — use the normal reimage process. See <i>Reimage the System with a New Software Version</i> in the Cisco FXOS Troubleshooting Guide for the Firewall Threat Defense.

Feature	Minimum Management Center	Minimum Threat Defense	Details
Firewall Threat Defense and chassis upgrade wizards optimized for lower resolution screens.		Any	<p>We optimized the Firewall Threat Defense and chassis upgrade wizards for lower resolution screens (and smaller browser windows). Text appears smaller and certain screen elements are hidden. If you change your resolution or window size mid-session, you may need to refresh the page for the web interface to adjust. Note that the minimum screen resolution to use the Cloud-Delivered Firewall Management Center is 1280 x 720.</p> <p>New/modified screens:</p> <ul style="list-style-type: none"> • Devices > Threat Defense Upgrade • Devices > Chassis Upgrade
Enable revert from the Firewall Threat Defense upgrade wizard.	20240203	Any, if upgrading to 7.1+	<p>You can now enable revert from the Firewall Threat Defense upgrade wizard.</p> <p>Version restrictions: You must be upgrading Firewall Threat Defense to Version 7.2+.</p>
View detailed upgrade status from the Firewall Threat Defense upgrade wizard.	20240203	Any	<p>The final page of the Firewall Threat Defense upgrade wizard now allows you to monitor upgrade progress. This is in addition to the existing monitoring capability on the Upgrade tab on the Device Management page, and on the Message Center. Note that as long as you have not started a new upgrade flow, Devices > Threat Defense Upgrade brings you back to this final wizard page, where you can view the detailed status for the current (or most recently complete) device upgrade.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Improved upgrade starting page and package management.	20240203	Any	<p>A new upgrade page makes it easier to choose, download, manage, and apply upgrades to your entire deployment. The page lists all upgrade packages that apply to your current deployment, with suggested releases specially marked. You can easily choose and direct-download packages from Cisco, as well as manually upload and delete packages.</p> <p>Patches are not listed unless you have at least one appliance at the appropriate maintenance release (or you manually uploaded the patch). You must manually upload hotfixes.</p> <p>New/modified screens:</p> <ul style="list-style-type: none"> • System(⚙️) > Product Upgrades is now where you upgrade devices, as well as manage upgrade packages. • System(⚙️) > Content Updates is now where you update intrusion rules, the VDB, and the GeoDB. • Devices > Threat Defense Upgrade takes you directly to the Firewall Threat Defense upgrade wizard. <p>Deprecated screens/options:</p> <ul style="list-style-type: none"> • System(⚙️) > Updates is deprecated. All Firewall Threat Defense upgrades now use the wizard. • The Add Upgrade Package button on the Firewall Threat Defense upgrade wizard has been replaced by a Manage Upgrade Packages link to the new upgrade page.
Suggested release notifications.	20240203	Any	<p>The Cloud-Delivered Firewall Management Center now notifies you when a new suggested release is available. If you don't want to upgrade right now, you can have the system remind you later, or defer reminders until the next suggested release. The new upgrade page also indicates suggested releases.</p> <p>See: Cisco Secure Firewall Management Center New Features by Release</p>
Select devices to upgrade from the Firewall Threat Defense upgrade wizard.		Any	<p>Use the wizard to select devices to upgrade.</p> <p>You can now use the Firewall Threat Defense upgrade wizard to select or refine the devices to upgrade. On the wizard, you can toggle the view between selected devices, remaining upgrade candidates, ineligible devices (with reasons why), devices that need the upgrade package, and so on. Previously, you could only use the Device Management page and the process was much less flexible.</p>
Unattended Firewall Threat Defense upgrades.		Any	<p>The Firewall Threat Defense upgrade wizard now supports unattended upgrades, using a new Unattended Mode menu. You just need to select the target version and the devices you want to upgrade, specify a few upgrade options, and step away. You can even log out or close the browser.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Simultaneous Firewall Threat Defense upgrade workflows by different users.		Any	We now allow simultaneous upgrade workflows by different users, as long as you are upgrading different devices. The system prevents you from upgrading devices already in someone else's workflow. Previously, only one upgrade workflow was allowed at a time across all users.
Skip pre-upgrade troubleshoot generation for Firewall Threat Defense.		Any	<p>You can now skip the automatic generating of troubleshooting files before major and maintenance upgrades by disabling the new Generate troubleshooting files before upgrade begins option. This saves time and disk space.</p> <p>To manually generate troubleshooting files for a Firewall Threat Defense device, choose System (⚙️) > Health > Monitor, click the device in the left panel, then View System & Troubleshoot Details, then Generate Troubleshooting Files.</p>
Auto-upgrade to Snort 3 after successful Firewall Threat Defense upgrade.	Any	Any	<p>When you use a Version 7.2+ Cloud-Delivered Firewall Management Center to upgrade Firewall Threat Defense to Version 7.2+, you can now choose whether to Upgrade Snort 2 to Snort 3.</p> <p>After the software upgrade, eligible devices upgrade from Snort 2 to Snort 3 when you deploy configurations. For devices that are ineligible because they use custom intrusion or network analysis policies, we strongly recommend you manually upgrade to Snort 3 for improved detection and performance. For help, see the Custom Snort 3 Intrusion Policies for Access Control for your version.</p> <p>Version restrictions: Not supported for Firewall Threat Defense upgrades to Version 7.0.x.</p>
Upgrade for single-node clusters.	Any	Any	<p>You can now use the device upgrade page (Devices > Device Upgrade) to upgrade clusters with only one active node. Any deactivated nodes are also upgraded. Previously, this type of upgrade would fail. This feature is not supported from the system updates page (System > Updates).</p> <p>Hitless upgrades are also not supported in this case. Interruptions to traffic flow and inspection depend on the interface configurations of the lone active unit, just as with standalone devices.</p> <p>Supported platforms: Firepower 4100/9300, Secure Firewall 3100</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Revert a successful device upgrade.	Any	7.2.0	<p>You can now revert major and maintenance upgrades to FTD. Reverting returns the software to its state just before the last upgrade, also called a <i>snapshot</i>. If you revert an upgrade after installing a patch, you revert the patch as well as the major and/or maintenance upgrade.</p> <p>Important If you think you might need to revert, you must use System > Updates to upgrade FTD. The System Updates page is the only place you can enable the Enable revert after successful upgrade option, which configures the system to save a revert snapshot when you initiate the upgrade. This is in contrast to our usual recommendation to use the wizard on the Devices > Device Upgrade page.</p> <p>This feature is not supported for container instances.</p> <p>Minimum FTD: 7.1</p>
Improvements to the upgrade workflow for clustered and high availability devices.	Any	Any	<p>We made the following improvements to the upgrade workflow for clustered and high availability devices:</p> <ul style="list-style-type: none"> • The upgrade wizard now correctly displays clustered and high availability units as groups, rather than as individual devices. The system can identify, report, and preemptively require fixes for group-related issues you might have. For example, you cannot upgrade a cluster on the Firepower 4100/9300 if you have made unsynced changes on Firepower Chassis Manager. • We improved the speed and efficiency of copying upgrade packages to clusters and high availability pairs. Previously, the FMC copied the package to each group member sequentially. Now, group members can get the package from each other as part of their normal sync process. • You can now specify the upgrade order of data units in a cluster. The control unit always upgrades last.
Improved FTD upgrade performance and status reporting.	Any	Any	<p>FTD upgrades are now easier faster, more reliable, and take up less disk space. A new Upgrades tab in the Message Center provides further enhancements to upgrade status and error reporting.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Easy-to-follow upgrade workflow for FTD devices.	Any	Any	<p>A new device upgrade page (Devices > Device Upgrade) on the FMC provides an easy-to-follow wizard for upgrading Version 6.4+ FTD devices. It walks you through important pre-upgrade stages, including selecting devices to upgrade, copying the upgrade package to the devices, and compatibility and readiness checks.</p> <p>To begin, use the new Upgrade Firepower Software action on the Device Management page Devices > Device Management > Selection.</p> <p>As you proceed, the system displays basic information about your selected devices, as well as the current upgrade-related status. This includes any reasons why you cannot upgrade. If a device does not "pass" a stage in the wizard, it does not appear in the next stage.</p> <p>If you navigate away from wizard, your progress is preserved, although other users with Administrator access can reset, modify, or continue the wizard.</p> <p>Note You must still use System > Updates to upload or specify the location of FTD upgrade packages. You must also use the System Updates page to upgrade the FMC itself, as well as all non-FTD managed devices.</p> <p>Note In Version 7.0, the wizard does not correctly display devices in clusters or high availability pairs. Even though you must select and upgrade these devices as a unit, the wizard displays them as standalone devices. Device status and upgrade readiness are evaluated and reported on an individual basis. This means it is possible for one unit to appear to "pass" to the next stage while the other unit or units do not. However, these devices are still grouped. Running a readiness check on one, runs it on all. Starting the upgrade on one, starts it on all.</p> <p>To avoid possible time-consuming upgrade failures, <i>manually</i> ensure all group members are ready to move on to the next step of the wizard before you click Next.</p>
Upgrade more FTD devices at once.	Any	Any	<p>The number of devices you can upgrade at once is now limited by your management network bandwidth—not the system's ability to manage simultaneous upgrades. Previously, we recommended against upgrading more than five devices at a time.</p> <p>Important Only upgrades to FTD Version 6.7+ using the FTD upgrade wizard see this improvement. If you are upgrading devices to an older FTD release—even if you are using the new upgrade wizard—we still recommend you limit to five devices at a time.</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Upgrade different device models together.	Any	Any	<p>You can now use the FTD upgrade wizard to queue and invoke upgrades for all FTD models at the same time, as long as the system has access to the appropriate upgrade packages.</p> <p>Previously, you would choose an upgrade package, then choose the devices to upgrade using that package. That meant that you could upgrade multiple devices at the same time <i>only</i> if they shared an upgrade package. For example, you could upgrade two Firepower 2100 series devices at the same time, but not a Firepower 2100 series and a Firepower 1000 series.</p>
Upgrades remove PCAP files to save disk space.	Any	Any	<p>Upgrades now remove locally stored PCAP files. To upgrade, you must have enough free disk space or the upgrade fails.</p>
Improved FTD upgrade status reporting and cancel/retry options.	Any	Any	<p>You can now view the status of FTD device upgrades and readiness checks in progress on the Device Management page, as well as a 7-day history of upgrade success/failures. The Message Center also provides enhanced status and error messages.</p> <p>A new Upgrade Status pop-up, accessible from both Device Management and the Message Center with a single click, shows detailed upgrade information, including percentage/time remaining, specific upgrade stage, success/failure data, upgrade logs, and so on.</p> <p>Also on this pop-up, you can manually cancel failed or in-progress upgrades (Cancel Upgrade), or retry failed upgrades (Retry Upgrade). Canceling an upgrade reverts the device to its pre-upgrade state.</p> <p>Note To be able to manually cancel or retry a failed upgrade, you must disable the new auto-cancel option, which appears when you use the FMC to upgrade an FTD device: Automatically cancel on upgrade failure and roll back to the previous version. With the option enabled, the device automatically reverts to its pre-upgrade state upon upgrade failure.</p> <p>Auto-cancel is not supported for patches. In an HA or clustered deployment, auto-cancel applies to each device individually. That is, if the upgrade fails on one device, only that device is reverted.</p> <p>New/modified screens:</p> <ul style="list-style-type: none"> • System > Updates > Product Updates > Available Updates > Install icon for the FTD upgrade package • Devices > Device Management > Upgrade • Message Center > Tasks <p>New/modified CLI commands: show upgrade status detail, show upgrade status continuous, show upgrade status, upgrade cancel, upgrade retry</p>

Feature	Minimum Management Center	Minimum Threat Defense	Details
Get FTD upgrade packages from an internal web server.	Any	Any	<p>FTD devices can now get upgrade packages from your own internal web server, rather than from the FMC. This is especially useful if you have limited bandwidth between the FMC and its devices. It also saves space on the FMC.</p> <p>Note This feature is supported only for FTD devices running Version 6.6+. It is not supported for upgrades <i>to</i> Version 6.6, nor is it supported for the FMC or Classic devices.</p> <p>New/modified screens: We added a Specify software update source option to the page where you upload upgrade packages.</p>
Copy upgrade packages to managed devices before the upgrade.	Any	Any	<p>You can now copy (or push) an upgrade package from the FMC to a managed device before you run the actual upgrade. This is useful because you can push during times of low bandwidth use, outside of the upgrade maintenance window.</p> <p>When you push to high availability, clustered, or stacked devices, the system sends the upgrade package to the active/control/primary first. Then, it sends the package to the standby/data/secondary.</p> <p>New/modified screens: System > Updates</p>