



## APIs for Web

---

- [Reporting APIs, on page 1](#)
- [Schedule and Archive APIs, on page 9](#)
- [Tracking APIs, on page 22](#)
- [Configuration APIs, on page 29](#)

### Reporting APIs

Reporting queries can be used to fetch data from report groups, for all reports under a specific group, or for a specific report.

<b>Synopsis</b>	<code>GET /api/v2.0/reporting/report?resource_attribute</code> <code>GET /api/v2.0/reporting/report/counter?resource_attribute</code>
-----------------	--

<b>Supported Resource Attributes</b>	Duration	<p>This is a required parameter. All API queries should be accompanied with this parameter.</p> <pre>startdate=YYYY-MM-DDThh:mm:00.000Z&amp;endDate=YYYY-MM-DDThh:mm:00.000Z</pre> <p>Aggregate report(s) for the specified duration.</p>
	Query Type	<ul style="list-style-type: none"> <li>• <code>query_type=graph</code> Receive data that can be represented as graphs.</li> <li>• <code>query_type=export</code> Receive data in the export format.</li> </ul>
	Sorting	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>orderBy=&lt;value&gt;</code> Specify the attribute by which to order the data in the response. For example, <code>orderBy=total_clean_recipients</code></li> <li>• <code>orderDir=&lt;value&gt;</code> Specify sort direction. The valid options are: <ul style="list-style-type: none"> <li>• <code>asc</code> Order the results in ascending order.</li> <li>• <code>desc</code> Order the results in descending order.</li> </ul> </li> </ul>
	Lazy Loading	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>offset=&lt;value&gt;</code> Specify an offset value to retrieve a subset of records starting with the offset value. Offset works with limit, which determines how many records to retrieve starting from the offset.</li> <li>• <code>limit=&lt;value&gt;</code> Specify the number of records to retrieve.</li> </ul>
	Data Retrieval Option	<ul style="list-style-type: none"> <li>• <code>top=&lt;value&gt;</code> Specify the number of records with the highest values to return.</li> </ul>
Filtering		

		<p>Filter parameters restrict the data to be included the response.</p> <ul style="list-style-type: none"> <li>• <code>filterValue=&lt;value&gt;</code> The value to search for.</li> <li>• <code>filterBy=&lt;value&gt;</code> Filter the data to be retrieved according to the filter property and value.</li> <li>• <code>filterOperator=&lt;value&gt;</code> The valid options are: <ul style="list-style-type: none"> <li>• <code>begins_with</code> Filter the response data based on the value specified. This is not an exact value.</li> <li>• <code>is</code> Filter the response data based on the exact value specified.</li> </ul> </li> </ul>
	Device	<ul style="list-style-type: none"> <li>• <code>device_type=wsa</code> Specify the device type. This is a required parameter. All API queries must be accompanied with this parameter.</li> <li>• <code>device_name=&lt;value&gt;</code> Specify the device name.</li> </ul>
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Comparing API Data with the Web Interface Data

The new web interface uses the AsyncOS APIs to fetch data with the duration attribute specified in the GMT time zone. If you plan to compare the data from your API query with the new web interface data, ensure that your API query has the same time range (in ISO8601 time format) as the new web interface API query.

## Examples

Examples of the types of reporting queries are shown below:

- [Retrieving a Single Value for a Counter, on page 4](#)
- [Retrieving Multiple Values for a Counter, on page 4](#)
- [Retrieving Single Values for Each Counter in a Counter Group, on page 5](#)
- [Retrieving Multiple Values for Multiple Counters, on page 6](#)
- [Retrieving Multiple Values for Multiple Counters, with Multiple Values for Each Counter, on page 7](#)

## Retrieving a Single Value for a Counter

This example shows a query to retrieve a single value for a counter.

### Sample Request

```
GET /wsa/api/v2.0/reporting/web_malware_category_malware_name_user_detail/
blocked_malware?startDate=2017-11-14T02:00+00:00&endDate=2018-02-18T01:00+00:00&
filterValue=23&filterBy=na&filterOperator=is&device_type=wsa
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: wsa.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Server: API/2.0
Date: Mon, 26 Nov 2018 16:29:33 GMT
Content-type: application/json
Content-Length: 193
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "meta": {
    "totalCount": 4
  },
  "data": {
    "type": "blocked_malware",
    "resultSet": {
      "blocked_malware": [
        {
          "10.8.93.12": 137511
        },
        {
          "10.8.93.20": 112554
        },
        {
          "10.8.93.11": 92839
        },
        {
          "10.225.98.234": 6
        }
      ]
    }
  }
}
```

## Retrieving Multiple Values for a Counter

This example shows a query to retrieve multiple values for a counter with the order direction and device type parameters.

### Sample Request

```
GET /wsa/api/v2.0/reporting/web_services_summary?orderBy=transaction_total&
orderDir=desc&startDate=2018-08-16T18:00:00.000Z&endDate=2018-11-15T10:00:00.000Z&device_type=wsa
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: 10.8.159.21:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Server: API/2.0
Date: Sun, 18 Nov 2018 15:38:52 GMT
Content-type: application/json
Content-Length: 403
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "meta": {
    "totalCount": -1
  },
  "data": {
    "type": "web_services_summary",
    "resultSet": [
      {"detected_by_traffic_monitor": 0},
      {"detected_malware_total": 42},
      {"high_risk_transaction_total": 7109},
      {"blocked_by_admin_policy": 0},
      {"detected_by_amp": 0},
      {"allowed_transaction_total": 26369},
      {"transaction_total": 33478},
      {"blocked_or_warned_by_webcat": 29},
      {"blocked_by_wbrs": 7038},
      {"blocked_by_avc": 0}
    ]
  }
}
```

## Retrieving Single Values for Each Counter in a Counter Group

A counter group may have multiple counters. This example shows a query to retrieve single values for each counter in a counter group with the filter, device type, and top parameters.

### Sample Request

```
GET /wsa/api/v2.0/reporting/web_application_type_detail/bw_not_limited?startDate=
2017-09-10T19:00:00.000Z&endDate=2018-09-24T23:00:00.000Z&device_type=wsa&filterValue=
F&filterOperator=begins_with&filterBy=na&top=2
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: 10.8.159.21:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```

HTTP/1.1 200 OK
Server: API/2.0
Date: Sun, 18 Nov 2018 15:48:21 GMT
Content-type: application/json
Content-Length: 138
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
{
  "meta": {
    "totalCount": 2
  },
  "data": {
    "type": "bw_not_limited",
    "resultSet": {
      "bw_not_limited": [
        {"File Sharing": 84},
        {"Facebook": 42}
      ]
    }
  }
}

```

## Retrieving Multiple Values for Multiple Counters

Here is an example of a query that retrieves multiple values for multiple counters, including offset, limit, and device type parameters.

### Sample Request

```

GET /wsa/api/v2.0/reporting/web_services_summary?offset=0&limit=20&
startDate=2020-04-10T07:00:00.000Z&endDate=2020-04-11T08:00:00.000Z&device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: 692fd2a6-3da7-4bc1-b581-f4b478b5a304
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Sat, 11 Apr 2020 07:42:04 GMT
Content-type: application/json
Content-Length: 387
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"meta": {"totalCount": -1}, "data": {"type": "web_services_summary", "resultSet":
[{"detected_by_traffic_monitor": 0}, {"detected_malware_total": 0},
{"high_risk_transaction_total": 0},
{"blocked_by_admin_policy": 0}, {"detected_by_amp": 0}, {"allowed_transaction_total": 0},

```

```
{"transaction_total": 0}, {"blocked_or_warned_by_webcat": 0}, {"blocked_by_wbrs": 0}, {"blocked_by_avc": 0}]}}
```

## Retrieving Multiple Values for Multiple Counters, with Multiple Values for Each Counter

This example shows a query to retrieve multiple values for multiple counters with the offset and limit parameters and query type parameters.

### Sample Request

```
GET /wsa/api/v2.0/reporting/web_application_name_application_type_detail?startDate=2017-08-16T18:00:00.000Z&endDate=2018-11-15T15:00:00.000Z&device_type=wsa&query_type=export HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: 10.8.159.21:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Server: API/2.0
Date: Sun, 18 Nov 2018 15:55:50 GMT
Content-type: application/json
Content-Length: 1258
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "meta": {
    "totalCount": -1
  },
  "data": {
    "type": "web_application_name_application_type_detail",
    "resultSet": {
      "time_intervals": [
        {
          "end_timestamp": 1538332199,
          "counter_values": [
            {
              "counter_values": [
                42,
                25932,
                0,
                42,
                0,
                42,
                0
              ],
              "application_type": "File Sharing",
              "counter_key": "4shared"
            }
          ],
          "counter_values": [
            2,
            109614,
            0,

```

```

        2,
        0,
        2,
        0
    ],
    "application_type": "Media",
    "counter_key": "Dailymotion"
},
{
    "counter_values": [
        42,
        20748,
        0,
        42,
        0,
        42,
        0
    ],
    "application_type": "Facebook",
    "counter_key": "Facebook General"
},
{
    "counter_values": [
        42,
        20580,
        0,
        42,
        0,
        42,
        0
    ],
    "application_type": "File Sharing",
    "counter_key": "MediaFire"
},
{
    "counter_values": [
        229,
        158838,
        0,
        229,
        0,
        229,
        0
    ],
    "application_type": "Social Networking",
    "counter_key": "Twitter"
},
{
    "counter_values": [
        1,
        86334,
        0,
        1,
        0,
        1,
        0
    ],
    "application_type": "Instant Messaging",
    "counter_key": "Wechat_web"
},
{
    "counter_values": [
        44,
        40876,

```





<p><b>Supported Resource Attributes</b></p>	<p>Sorting</p>	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>orderBy=&lt;value&gt;</code> <p>The valid options are:</p> <ul style="list-style-type: none"> <li>• <code>periodic_report_display_name</code> Order the results based on the display name of the report.</li> <li>• <code>periodic_report_title</code> Order the results based on the type of the report.</li> <li>• <code>periodic_report_type</code> Order the results based on the type of the report.</li> <li>• <code>periodic_report_time_range</code> Order the results based on the time range of the report.</li> <li>• <code>periodic_report_delivery</code> Order the results based on the delivery options of the report.</li> <li>• <code>periodic_report_format</code> Order the results based on the format of the report.</li> <li>• <code>periodic_report_schedule_type</code> Order the results based on the type of the schedule selected for the report.</li> <li>• <code>periodic_report_tier</code> Order the results based on the required web gateway.</li> <li>• <code>periodic_report_next_run_date</code> Order the results based on the scheduling options of the report.</li> </ul> </li> <li>• <code>orderDir=&lt;value&gt;</code> <p>Specify sort direction.</p> <p>The valid options are:</p> <ul style="list-style-type: none"> <li>• <code>asc</code> Order the results in ascending order.</li> <li>• <code>desc</code> Order the results in descending order.</li> </ul> </li> </ul>
---	----------------	--

	Lazy Loading	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>offset=&lt;value&gt;</code></li> </ul> <p>Specify an offset value to retrieve a subset of records starting with the offset value. Offset works with limit, which determines how many records to retrieve starting from the offset.</p> <ul style="list-style-type: none"> <li>• <code>limit=&lt;value&gt;</code></li> </ul> <p>Specify the number of records to retrieve.</p>
	Device	<ul style="list-style-type: none"> <li>• <code>device_type=wsa</code></li> </ul> <p>Specify the device type. This is a required parameter. All API queries must be accompanied with this parameter.</p>
Request Headers		Host, Accept, Authorization
Response Headers		Content-Type, Content-Length, Connection

## Examples

The following are some examples for the types of schedule reports queries:

- [Retrieving Scheduling Reports, on page 11](#)
- [Retrieving the Details of a Schedule Report Entry, on page 13](#)
- [Adding a Scheduled Report Entry, on page 13](#)
- [Editing a Scheduled Report Entry, on page 14](#)
- [Deleting Scheduled Reports, on page 15](#)

### Retrieving Scheduling Reports

The following example shows how to retrieve the list of all available scheduled report entries:

#### Sample Request

```
GET /wsa/api/v2.0/config/periodic_reports?device_type=wsa HTTP/1.1
cache-control: no-cache
Postman-Token: 2a8a85d4-50cc-49fd-9ac5-20e07775e1db
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 10 Apr 2020 10:41:02 GMT
Content-type: application/json
Content-Length: 3691
Connection: close
Access-Control-Allow-Origin: *
```

```

Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": {"periodic_reports": [{"20200409064843_Web Sites Report_calendar_week":
{"periodic_report_type": "coeus", "periodic_report_schedule": {"periodic_report_second":
0,
"periodic_report_day": "", "periodic_report_month": "", "periodic_report_minute": 0,
"periodic_report_weekday": "", "periodic_report_year": "", "periodic_report_hour": 1,
"periodic_report_schedule_type": "Daily"}, "periodic_report_options": {"periodic_report_rows":
20,
"periodic_report_charts": {"wsa_web_sites_top_blocked_domains":
"DOMAINS.BLOCKED_TRANSACTION_TOTAL",
"wsa_web_sites_top_domains": "DOMAINS.TRANSACTION_TOTAL"}, "periodic_report_format": "PDF",

"periodic_report_lang": "en-us", "periodic_report_sort_columns":
{"wsa_web_sites_domains_matched":
"DOMAINS.TRANSACTION_TOTAL"}, "periodic_report_time_range": "Previous calendar month",
"periodic_report_user_name": "admin", "periodic_report_product_type": "WSA",
"periodic_report_type_name": "Web Sites", "periodic_report_delivery": "Archived Only",
"periodic_report_recipients": [], "periodic_report_tier": "All Web Appliances",
"periodic_report_next_run_date": "11 Apr 2020 01:00 (GMT)", "periodic_report_title": "Web
Sites Report_2_Edit"}},
{"20200402042756_Users_calendar_week": {"periodic_report_type": "coeus",
"periodic_report_schedule":
{"periodic_report_second": 0, "periodic_report_day": "", "periodic_report_month": "",
"periodic_report_minute": 0,
"periodic_report_weekday": "", "periodic_report_year": "", "periodic_report_hour": 1,
"periodic_report_schedule_type": "Daily"}, "periodic_report_options": {"periodic_report_rows":
10,
"periodic_report_charts": {"wsa_users_top_users_bandwidth_used":
"WEB_USER_DETAIL.BANDWIDTH_USED",
"wsa_users_top_users_blocked_transactions": "WEB_USER_DETAIL.BLOCKED_TRANSACTION_TOTAL"},
"periodic_report_format": "PDF", "periodic_report_lang": "en-us",
"periodic_report_sort_columns":
{"wsa_users_users_table": "WEB_USER_DETAIL.BLOCKED_TRANSACTION_TOTAL"},
"periodic_report_time_range":
"Previous 7 calendar days"}, "periodic_report_user_name": "admin",
"periodic_report_product_type": "WSA",
"periodic_report_type_name": "Users", "periodic_report_delivery": "Emailed Only",
"periodic_report_recipients": ["abc@cic.com"], "periodic_report_tier": "All Web Appliances",

"periodic_report_next_run_date": "11 Apr 2020 01:00 (GMT)", "periodic_report_title":
"Users"}},
{"20200403094854_Application Visibility_calendar_month": {"periodic_report_type": "coeus",

"periodic_report_schedule": {"periodic_report_second": 0, "periodic_report_day": "",
"periodic_report_month": "", "periodic_report_minute": 0, "periodic_report_weekday": "",
"periodic_report_year": "", "periodic_report_hour": 1, "periodic_report_schedule_type":
"Daily"},
"periodic_report_options": {"periodic_report_rows": 10, "periodic_report_charts":
{"wsa_applications_blocked":
"WEB_APPLICATION_NAME_APPLICATION_TYPE_DETAIL.BLOCKED_BY_AVC", "wsa_applications_top_types":
"WEB_APPLICATION_TYPE_DETAIL.TRANSACTION_TOTAL"}, "periodic_report_format": "PDF",
"periodic_report_lang": "en-us", "periodic_report_sort_columns": {"wsa_applications_total":
"WEB_APPLICATION_NAME_APPLICATION_TYPE_DETAIL.TRANSACTION_TOTAL",
"wsa_applications_types_total":
"WEB_APPLICATION_TYPE_DETAIL.BANDWIDTH_USED"}, "periodic_report_time_range": "Previous
calendar month"},
"periodic_report_user_name": "admin", "periodic_report_product_type": "WSA",
"periodic_report_type_name": "Application Visibility", "periodic_report_delivery": "Archived

```

```

Only",
"periodic_report_recipients": [], "periodic_report_tier": "All Web Appliances",
"periodic_report_next_run_date": "11 Apr 2020 01:00 (GMT)", "periodic_report_title":
"Application Visibility"}]],
"meta": {"totalCount": 3}}

```

## Retrieving the Details of a Schedule Report Entry

The following example shows how to retrieve the details of one particular scheduled report by passing the report ID:

### Sample Request

```

GET /wsa/api/v2.0/config/periodic_reports/20200402042756_Users_calendar_week?
device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: b7038e94-4182-4b35-9aae-73a1a1e35249
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Fri, 10 Apr 2020 10:43:07 GMT
Content-type: application/json
Content-Length: 1130
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": {"periodic_reports": {"20200402042756_Users_calendar_week": {"periodic_report_type":
"coeus", "periodic_report_schedule": {"periodic_report_second": 0, "periodic_report_day":
"",
"periodic_report_month": "", "periodic_report_minute": 0, "periodic_report_weekday": "",
"periodic_report_year": "", "periodic_report_hour": 1, "periodic_report_schedule_type":
"Daily"},
"periodic_report_options": {"periodic_report_rows": 10, "periodic_report_charts": [{"column":
"Bandwidth Used", "Chart": "Top Users (Right)"}, {"column": "Transactions Blocked", "Chart":
"Top Users (Left)"}]}, "periodic_report_format": "PDF", "periodic_report_lang": "en-us",
"periodic_report_sort_columns": [{"column": "Transactions Blocked", "table": "Users"}]},
"periodic_report_time_range": "Previous 7 calendar days", "periodic_report_user_name":
"admin",
"periodic_report_product_type": "WSA", "periodic_report_type_name": "Users",
"periodic_report_delivery": "Emailed Only", "periodic_report_recipients": ["abc@cic.com"],
"periodic_report_tier": "All Web Appliances", "periodic_report_next_run_date": 1586566800,
"periodic_report_title": "Users"}}}}

```

## Adding a Scheduled Report Entry

The following example shows how to add a scheduled report with report type, report title, device type and other options:

### Sample Request

```
POST /wsa/api/v2.0/config/periodic_reports?device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: 32a1d150-a8a0-47f2-b9bf-2c7c5b2e8e8a
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
Content-Type: text/plain
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
content-length: 833
Connection: keep-alive

{"data":{"periodic_reports":[{"periodic_report_delivery":"Emailed and Archived",
"periodic_report_options":{"periodic_report_format":"pdf","periodic_report_lang":"en-us",
"periodic_report_rows":10,"periodic_report_sort_columns":[{"table":"Domains Matched","column":
"Total Transactions"}],"periodic_report_charts":[{"Chart":"Top Domains (Left)","Data to
display":
"Total Transactions"}, {"Chart":"Top Domains (Right)","Data to display":"Transactions
Blocked"}],
"periodic_report_time_range":"Previous 7 calendar days"},"periodic_report_title":"Web Sites
Report",
"periodic_report_type":"coeus","periodic_report_type_name":"Web Sites",
"periodic_report_user_name":"admin","periodic_report_schedule":{"periodic_report_hour":1,
"periodic_report_minute":0,"periodic_report_schedule_type":"daily"},
"periodic_report_recipients":["abc@test.com"]}]}}
```

### Sample Response

```
HTTP/1.1 201 Created
Date: Thu, 09 Apr 2020 06:50:18 GMT
Content-type: application/json
Content-Length: 49
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": "Scheduled Report created Successfully"}
```

## Editing a Scheduled Report Entry

The following example shows how to modify a scheduled report with a schedule report ID:

### Sample Request

```
PUT /wsa/api/v2.0/config/periodic_reports/20200409064843_Web%20Sites%20Report_calendar_week?
device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: 2d168727-6e8a-470a-909f-0af9a5dc1e85
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
Content-Type: text/plain
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
content-length: 786
Connection: keep-alive

{"data":{"periodic_reports":[{"periodic_report_delivery":"Archived Only",
```

```
"periodic_report_options":{"periodic_report_format":"pdf","periodic_report_lang":"en-us",
"periodic_report_rows":20,"periodic_report_sort_columns":[{"table":"Domains Matched","column":
"Total Transactions"}],"periodic_report_charts":[{"Chart":"Top Domains (Left)","Data to
display":
"Total Transactions"}, {"Chart":"Top Domains (Right)","Data to display":"Transactions
Blocked"}],
"periodic_report_time_range":"Previous calendar month"},"periodic_report_title":
"Web Sites Report_1 Edit","periodic_report_type":"coeus","periodic_report_type_name":
"Web Sites","periodic_report_user_name":"admin","periodic_report_schedule":
{"periodic_report_hour":1,"periodic_report_minute":0,"periodic_report_schedule_type":"daily"}}}}
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 09 Apr 2020 06:54:19 GMT
Content-type: application/json
Content-Length: 49
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": "Scheduled Report Updated Successfully"}
```

## Deleting Scheduled Reports

The following example shows how to delete a scheduled report with device type and a schedule report ID:

### Sample Request

```
DELETE /wsa/api/v2.0/config/periodic_reports?id=20200409065018_Web%20Sites
%20Report_calendar_week&device_type=wsa HTTP/1.1
cache-control: no-cache
Postman-Token: 7e09e87c-40c2-410a-a99e-98f73c6e0bf8
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
content-length: 0
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 09 Apr 2020 07:07:05 GMT
Content-type: application/json
Content-Length: 52
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
{"data": {"message": "1 item deleted successfully"}}
```

## Archive APIs

<b>Synopsis</b>	GET /wsa/api/v2.0/config/archived_reports?resource_attribute  GET wsa/api/v2.0/config/archived_reports/view/archived_report_id?resource_attribute  POST /wsa/api/v2.0/config/archived_reports?resource_attribute  DELETE /wsa/api/v2.0/config/archived_reports?id=archived_report_id(To delete single report)  DELETE /wsa/api/v2.0/config/archived_reports?id=all (To delete all archived reports)
-----------------	--



<p><b>Supported Resource Attributes</b></p>	<p>Sorting</p>	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>orderBy=&lt;value&gt;</code></li> </ul> <p>The valid options are:</p> <ul style="list-style-type: none"> <li>• <code>periodic_report_generated</code> Order the results based on the date and time the report is generated.</li> <li>• <code>periodic_report_display_name</code> Order the results based on the display name of the report.</li> <li>• <code>periodic_report_format</code> Order the results based on the format of the report.</li> <li>• <code>periodic_report_title</code> Order the results based on the type of the report.</li> <li>• <code>periodic_report_time_range</code> Order the results based on the time range of the report.</li> <li>• <code>periodic_report_type</code> Order the results based on the type of the report.</li> <li>• <code>periodic_report_tier</code> Order the results based on the required email gateway.</li> </ul> <ul style="list-style-type: none"> <li>• <code>orderDir=&lt;value&gt;</code></li> </ul> <p>Specify sort direction.</p> <p>The valid options are:</p> <ul style="list-style-type: none"> <li>• <code>asc</code> Order the results in ascending order.</li> <li>• <code>desc</code> Order the results in descending order.</li> </ul>
	<p>Lazy Loading</p>	<p>You should use both these parameters. If you use either, you will not receive data in the response.</p> <ul style="list-style-type: none"> <li>• <code>offset=&lt;value&gt;</code></li> </ul> <p>Specify an offset value to retrieve a subset of records starting with the offset value. Offset works with limit, which determines how many records to retrieve starting from the offset.</p> <ul style="list-style-type: none"> <li>• <code>limit=&lt;value&gt;</code></li> </ul> <p>Specify the number of records to retrieve.</p>

	Filtering	<p>Filter parameters restrict the data to be included the response.</p> <ul style="list-style-type: none"> <li>• <code>filterByTitle=&lt;value&gt;</code> Filter the data to be retrieved according to the title of the report and value.</li> <li>• <code>filterByReportTypeName=&lt;value&gt;</code> Filter the data to be retrieved according to the type of the report and value.</li> <li>• <code>filterByTimeRange=&lt;value&gt;</code> Filter the data to be retrieved according to the time range of the report and value.</li> </ul>
	Device	<ul style="list-style-type: none"> <li>• <code>device_type=wsa</code> Specify the device type. This is a required parameter. All API queries must be accompanied with this parameter.</li> </ul>
Request Headers		Host, Accept, Authorization
Response Headers		Content-Type, Content-Length, Connection

## Examples

The following are some examples for the types of archived reports queries:

- [Searching Archived Reports, on page 18](#)
- [Retrieving Archived Reports, on page 19](#)
- [Retrieving the Details of a Archive Report Entry, on page 20](#)
- [Adding an Archive Report Entry, on page 21](#)
- [Deleting an Archived Report Entry, on page 22](#)

### Searching Archived Reports

The following example shows how to search for a list of the top 20 archived reports based on the report title and sorted by the date and time the report was generated, in ascending order:

#### Sample Request

```
GET /wsa/api/v2.0/config/archived_reports?orderBy=periodic_report_title&
device_type=wsa&filterByTitle=Application&orderDir=asc&offset=0&limit=20& HTTP/1.1
cache-Control: no-cache
Postman-Token: elf6fac5-f047-4ab5-9be2-467132a3b29d
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

#### Sample Response

```

HTTP/1.1 200 OK
Date: Thu, 09 Apr 2020 07:27:25 GMT
Content-type: application/json
Content-Length: 1262
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": {"meta": {"totalCount": 3}, "archived_reports": [{"20200404010011_Application
Visibility_calendar_month.pdf": {"periodic_report_format": "PDF",
"periodic_report_type_name": "Application Visibility", "periodic_report_generated":
"04 Apr 2020 01:00 (GMT)", "periodic_report_time_range": "Previous calendar month",
"periodic_report_tier": "All Web Appliances", "periodic_report_title": "Application
Visibility",
"periodic_report_product_type": "wsa"}}, {"20200409010011_Application
Visibility_calendar_month.pdf":
{"periodic_report_format": "PDF", "periodic_report_type_name": "Application Visibility",
"periodic_report_generated": "09 Apr 2020 01:00 (GMT)", "periodic_report_time_range":
"Previous calendar month", "periodic_report_tier": "All Web Appliances",
"periodic_report_title":
"Application Visibility", "periodic_report_product_type": "wsa"}},
{"20200408010011_Application
Visibility_calendar_month.pdf": {"periodic_report_format": "PDF", "periodic_report_type_name":
"Application Visibility", "periodic_report_generated": "08 Apr 2020 01:00 (GMT)",
"periodic_report_time_range": "Previous calendar month", "periodic_report_tier":
"All Web Appliances", "periodic_report_title": "Application Visibility",
"periodic_report_product_type": "wsa"}]}}

```

## Retrieving Archived Reports

The following example shows how to retrieve a list of the top 25 archived reports, sorted by the time range of the report in descending order:

### Sample Request

```

GET /wsa/api/v2.0/config/archived_reports?device_type=wsa&limit=25&
offset=0&orderBy=periodic_report_generated&orderDir=desc HTTP/1.1
cache-control: no-cache
Postman-Token: 9cf1ebad-774d-4e86-af29-fd6d25c446ce
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
Connection: keep-alive

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Fri, 10 Apr 2020 10:48:31 GMT
Content-type: application/json
Content-Length: 2792
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": {"meta": {"totalCount": 7}, "archived_reports": [{"20200410010016_Application
Visibility_

```

```

calendar_month.pdf": {"periodic_report_format": "PDF", "periodic_report_type_name":
"Application Visibility", "periodic_report_generated": "10 Apr 2020 01:00 (GMT)",
"periodic_report_time_range": "Previous calendar month", "periodic_report_tier": "All Web
Appliances",
"periodic_report_title": "Application Visibility", "periodic_report_product_type": "wsa"}},

{"20200410010009_Web Sites Report_2 Edit_calendar_month.pdf": {"periodic_report_format":
"PDF",
"periodic_report_type_name": "Web Sites", "periodic_report_generated": "10 Apr 2020 01:00
(GMT)",
"periodic_report_time_range": "Previous calendar month", "periodic_report_tier": "All Web
Appliances",
"periodic_report_title": "Web Sites Report_2 Edit", "periodic_report_product_type": "wsa"}},

{"20200409071005_URL Categories_calendar_week.pdf": {"periodic_report_format": "PDF",
"periodic_report_type_name": "URL Categories", "periodic_report_generated": "09 Apr 2020
07:10 (GMT)",
"periodic_report_time_range": "Previous 7 calendar days", "periodic_report_tier": "All Web
Appliances",
"periodic_report_title": "URL Categories", "periodic_report_product_type": "wsa"}},
{"20200409070946_Web Sites_calendar_week.pdf": {"periodic_report_format": "PDF",
"periodic_report_type_name": "Web Sites", "periodic_report_generated": "09 Apr 2020 07:09
(GMT)",
"periodic_report_time_range": "Previous 7 calendar days", "periodic_report_tier":
"All Web Appliances", "periodic_report_title": "Web Sites", "periodic_report_product_type":
"wsa"}},
{"20200409010011_Application Visibility_calendar_month.pdf": {"periodic_report_format":
"PDF", "periodic_report_type_name": "Application Visibility", "periodic_report_generated":
"09 Apr 2020 01:00 (GMT)", "periodic_report_time_range": "Previous calendar month",
"periodic_report_tier": "All Web Appliances", "periodic_report_title": "Application
Visibility",
"periodic_report_product_type": "wsa"}}, {"20200408010011_Application
Visibility_calendar_month.pdf":
{"periodic_report_format": "PDF", "periodic_report_type_name": "Application Visibility",
"periodic_report_generated": "08 Apr 2020 01:00 (GMT)", "periodic_report_time_range":
"Previous calendar month", "periodic_report_tier": "All Web Appliances",
"periodic_report_title":
"Application Visibility", "periodic_report_product_type": "wsa"}},
{"20200404010011_Application
Visibility_calendar_month.pdf": {"periodic_report_format": "PDF", "periodic_report_type_name":
"Application Visibility", "periodic_report_generated": "04 Apr 2020 01:00 (GMT)",
"periodic_report_time_range": "Previous calendar month", "periodic_report_tier": "All Web
Appliances",
"periodic_report_title": "Application Visibility",
"periodic_report_product_type": "wsa"}}}}}

```

## Retrieving the Details of a Archive Report Entry

The following example shows how to retrieve an archived report entry with device type and an archived report ID:

### Sample Request

```

GET /wsa/api/v2.0/config/archived_reports/view/20200409070946_Web%20
Sites_calendar_week.pdf?device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: 986e7426-c8a2-4bbb-9aa5-5b87e9a5ff56
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080

```

```
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 10 Apr 2020 10:45:27 GMT
Content-type: application/pdf
Content-Disposition: filename="20200409070946_Web Sites_calendar_week.pdf"
Content-Length: 111175
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

%PDF-1.4
.....
.....
%%EOF
```

## Adding an Archive Report Entry

The following example shows how to add an archived report with report title, report type, device type, and other options:

### Sample Request

```
POST /wsa/api/v2.0/config/archived_reports?device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: a144b273-13ff-4f48-bf4c-4232fa5db6f2
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
Content-Type: text/plain
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
content-length: 644
Connection: keep-alive
```

```
{"data":{"archived_reports":[{"periodic_report_delivery":"Archived Only",
"periodic_report_options":{"periodic_report_format":"pdf","periodic_report_lang":"en-us",
"periodic_report_rows":20,"periodic_report_sort_columns":[{"table":"Users","column":
"Transactions Blocked"}],"periodic_report_charts":[{"Chart":"Top Users (Left)","Data to
display":
"Transactions Blocked"}, {"Chart":"Top Users (Right)","Data to display":"Bandwidth Used"}],
"periodic_report_time_range":"Previous calendar month"},"periodic_report_title":"Users
Archive Report 2",
"periodic_report_type":"coeus","periodic_report_type_name":"Users",
"periodic_report_user_name":"admin"}]}}
```

### Sample Response

```
HTTP/1.1 201 Created
Date: Fri, 10 Apr 2020 10:51:41 GMT
Content-type: application/json
Content-Length: 46
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{"data": {"message": "Archived successfully"}}
```

## Deleting an Archived Report Entry

The following example shows how to delete an archived report with device type and an archived report ID:

### Sample Request

```
DELETE /wsa/api/v2.0/config/archived_reports?id=20200409071005_URL%20
Categories_calendar_week.pdf&device_type=wsa& HTTP/1.1
cache-control: no-cache
Postman-Token: f183a45c-7bcb-40fd-bff1-2940824684b3
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: PostmanRuntime/7.6.0
Accept: */*
Host: pod1224-wsa04.ibwsa.sgg.cisco.com:6080
accept-encoding: gzip, deflate
content-length: 0
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 10 Apr 2020 11:07:27 GMT
Content-type: application/json
Content-Length: 52
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"data": {"message": "1 item deleted successfully"}}
```

## Tracking APIs

You can use web tracking APIs to search for and get details about individual transactions or patterns of transactions. Web tracking APIs are:

- [Proxy Services](#), on page 22
- [Layer 4 Traffic Monitor](#), on page 25
- [SOCKS Proxy](#), on page 27

## Proxy Services

You can retrieve information about web usage for a particular user or for all users using multiple attributes.

<b>Synopsis</b>	GET /api/v2.0/web-tracking/web_transaction?resource_attribute
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve transactions processed by the proxy services, with the duration, filtering, offset and limit, ordering, and transactions status parameters:

### Sample Request

```
GET /wsa/api/v2.0/web-tracking/web_transaction?startDate=2016-09-30T18:00:00.000Z
&endDate=2018-10-31T19:00:00.000Z&filterBy=proxy_services&filterOperator=is&limit=20&offset=0
&device_type=wsa&orderBy=timestamp&orderDir=desc&transactionStatus=all&
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: 10.225.99.234:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Server: API/2.0
Date: Mon, 19 Nov 2018 14:43:38 GMT
Content-type: application/json
Content-Length: 26617
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "meta": {
    "totalCount": 20
  },
  "data": [
    {
      "attributes": {
        "webCategory": "Computers and Internet",
        "contentType": "-",
        "pageResources":
"http://update.googleapis.com/service/update2?cup2key=8:128910954&cup2hreq=
3a51fa0a72aa94fcba12403f2eb11c4884b27862dd31a779133c03a0e61d334d",
        "applicationBehavior": "-",
        "malwareCategory": "-",
        "fileName": "-",
        "SHA": "-",
        "bandwidth": 0,
        "policyType": "Access",
        "user": "192.168.0.158",
        "srcIP": "192.168.0.158",
        "relatedTransCount": 1,
        "malwareName": "-",
        "applicationName": "-",

```

```

        "policyName": "DefaultGroup",
        "threatType": "Computers and Internet",
        "ampFileVerdict": "-",
        "destinationIP": "-",
        "userType": "[-]",
        "threatReason": "Information about computers and software, such as hardware,
software, software
    support, information for software engineers, programming and networking,
website design, the web
    and Internet in general, computer science, computer graphics and clipart.
Freeware and Shareware
    is a separate category.",
        "serialNo": "4229C3B46A609471867D-0720DA1A8A64",
        "wbrsScore": "No Score",
        "decisionSrc": "WEBCAT",
        "url":
"http://update.googleapis.com/service/update2?cup2key=8:128910954&cup2hreq=3a51fa0a72aa94f
cba12403f2eb11c4884b27862dd31a779133c03a0e61d334d",
        "applicationType": "-",
        "timestamp": 1540275265,
        "transactionStatus": "BLOCK",
        "ampVerdict": "-"
    }
},
{
    "attributes": {
        "webCategory": "Business and Industry",
        "contentType": "-",
        "pageResources":
"http://www.purple.com/,http://www.purple.com/,http://www.purple.com/",
        "applicationBehavior": "-",
        "malwareCategory": "-",
        "fileName": "-",
        "SHA": "-",
        "bandwidth": 0,
        "policyType": "Access",
        "user": "10.10.5.105",
        "srcIP": "10.10.5.105",
        "relatedTransCount": 3,
        "malwareName": "-",
        "applicationName": "-",
        "policyName": "DefaultGroup",
        "threatType": "Business and Industry",
        "ampFileVerdict": "-",
        "destinationIP": "-",
        "userType": "[-]",
        "threatReason": "Marketing, commerce, corporations, business practices,
workforce, human resources
    , transportation, payroll, security and venture capital, office supplies,
industrial equipment
    (process equipment), machines and mechanical systems, heating equipment,
cooling equipment,
    materials handling equipment, packaging equipment, manufacturing: solids
handling, metal fabrication
    , construction and building, passenger transportation, commerce, industrial
design, construction
    , building materials, shipping and freight (freight services, trucking,
freight forwarders,
    truckload carriers, freight and transportation brokers, expedited services,
load and freight matching
    , track and trace, rail shipping, ocean shipping, road feeder services,
moving and storage).",
        "serialNo": "4229C3B46A609471867D-0720DA1A8A64",
        "wbrsScore": "No Score",

```



```

        "decisionSrc": "WEBCAT",
        "url": "ftp://www.purple.com/",
        "applicationType": "-",
        "timestamp": 1540274946,
        "transactionStatus": "BLOCK",
        "ampVerdict": "-"
    },
    ...
    ...
    {
        "attributes": {
            "webCategory": "Business and Industry",
            "contentType": "-",
            "pageResources":
"ftp://www.purple.com/,http://www.purple.com/,http://www.purple.com/",
            "applicationBehavior": "-",
            "malwareCategory": "-",
            "fileName": "-",
            "SHA": "-",
            "bandwidth": 0,
            "policyType": "Access",
            "user": "10.10.5.105",
            "srcIP": "10.10.5.105",
            "relatedTransCount": 3,
            "malwareName": "-",
            "applicationName": "-",
            "policyName": "DefaultGroup",
            "threatType": "Business and Industry",
            "ampFileVerdict": "-",
            "destinationIP": "-",
            "userType": "[-]",
            "threatReason": "Marketing, commerce, corporations, business practices,
workforce, human resources...
            "serialNo": "4229C3B46A609471867D-0720DA1A8A64",
            "wbrsScore": "No Score",
            "decisionSrc": "WEBCAT",
            "url": "ftp://www.purple.com/",
            "applicationType": "-",
            "timestamp": 1540263898,
            "transactionStatus": "BLOCK",
            "ampVerdict": "-"
        }
    }
}
]
}

```

## Layer 4 Traffic Monitor

You can retrieve information about connections to malware sites and ports using multiple attributes.

<b>Synopsis</b>	GET /api/v2.0/web-tracking/web_transaction?resource_attribute	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization

<b>Response Headers</b>	Content-Type, Content-Length, Connection
-------------------------	--

### Example

This example shows a query to retrieve transactions processed by the Layer 4 Traffic Monitor, with the duration, filtering, offset and limit, ordering, and transaction status parameters:

### Sample Request

```
GET /wsa/api/v2.0/web-tracking/web_transaction?startDate=2016-09-30T18:00:00.000Z
&endDate=2018-10-31T19:00:00.000Z&filterBy=l4tm&filterOperator=is&limit=20&offset=0&device_type=
wsa&orderBy=timestamp&orderDir=desc&transactionStatus=all&
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: */*
Host: 10.225.99.234:6080
accept-encoding: gzip, deflate
Connection: keep-alive
```

### Sample Response

```
HTTP/1.1 200 OK
Server: API/2.0
Date: Mon, 19 Nov 2018 14:58:11 GMT
Content-type: application/json
Content-Length: 12
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "meta": {
    "totalCount": 20
  },
  "data": [
    {
      "attributes": {
        "l4tmDestDomain": "ticketbooking.com",
        "l4tmUser": "10.10.99.68",
        "timestamp": 1534143578,
        "l4tmPort": 443,
        "serialNo": "42292E04F63C3DE54F13-E5D7466DA42E",
        "l4tmDestIpWithDomain": "103.117.180.6@ticketbooking.com",
        "transactionStatus": "BLOCKED"
      }
    },
    {
      "attributes": {
        "l4tmDestDomain": "ticketbooking.com",
        "l4tmUser": "10.10.99.68",
        "timestamp": 1534143578,
        "l4tmPort": 443,
        "serialNo": "42292E04F63C3DE54F13-E5D7466DA42E",
        "l4tmDestIpWithDomain": "103.117.180.6@ticketbooking.com",
        "transactionStatus": "BLOCKED"
      }
    },
    ...
  ]
}
```

```

...
    {
      "attributes": {
        "l4tmDestDomain": "ticketbooking.com",
        "l4tmUser": "10.10.99.68",
        "timestamp": 1534143577,
        "l4tmPort": 443,
        "serialNo": "42292E04F63C3DE54F13-E5D7466DA42E",
        "l4tmDestIpWithDomain": "103.117.180.6@ticketbooking.com",
        "transactionStatus": "BLOCKED"
      }
    }
  ]
}

```

## SOCKS Proxy

You can retrieve information about transactions processed through the SOCKS proxy, including information about top destinations and users.

<b>Synopsis</b>	GET /api/v2.0/web-tracking/web_transaction?resource_attribute	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve transactions processed by the SOCKS Proxy Services, with the duration, filtering, offset and limit, ordering, and transaction status parameters:

#### Sample Request

```

GET /wsa/api/v2.0/web-tracking/web_transaction?startDate=2016-09-30T18:00:00.000Z&
endDate=2018-10-31T19:00:00.000Z&filterBy=socks_proxy&filterOperator=is&limit=20&offset=0&
device_type=wsa&orderBy=timestamp&orderDir=desc&socksTransportProtocol=all&transactionStatus=all&
HTTP/1.1
cache-control: no-cache
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
User-Agent: curl/7.54.0
Accept: /*/*
Host: 10.225.99.234:6080
accept-encoding: gzip, deflate
Connection: keep-alive

```

#### Sample Response

```

HTTP/1.1 200 OK
Server: API/2.0
Date: Mon, 19 Nov 2018 14:53:33 GMT
Content-type: application/json
Content-Length: 6629
Connection: close
Access-Control-Allow-Origin: *

```

```

Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "meta": {
    "totalCount": 20
  },
  "data": [
    {
      "attributes": {
        "socksUser": "10.10.5.106",
        "socksBandwidth": 0,
        "socksUserType": "[-]",
        "timestamp": 1538044948,
        "socksTransportProtocol": "TCP",
        "socksPort": 80,
        "socksSrcIp": "10.10.5.106",
        "socksDestinationIp": "-",
        "socksPolicyName": "DefaultGroup",
        "socksHostName": "concede.fmtlib.net",
        "transactionStatus": "BLOCK"
      }
    },
    {
      "attributes": {
        "socksUser": "10.10.5.106",
        "socksBandwidth": 0,
        "socksUserType": "[-]",
        "timestamp": 1538044948,
        "socksTransportProtocol": "TCP",
        "socksPort": 80,
        "socksSrcIp": "10.10.5.106",
        "socksDestinationIp": "-",
        "socksPolicyName": "DefaultGroup",
        "socksHostName": "erupt.fernetmoretti.com.ar",
        "transactionStatus": "BLOCK"
      }
    },
    ...
    ...
    {
      "attributes": {
        "socksUser": "10.10.5.106",
        "socksBandwidth": 0,
        "socksUserType": "[-]",
        "timestamp": 1538044947,
        "socksTransportProtocol": "TCP",
        "socksPort": 80,
        "socksSrcIp": "10.10.5.106",
        "socksDestinationIp": "-",
        "socksPolicyName": "DefaultGroup",
        "socksHostName": "boots.fotopyra.pl",
        "transactionStatus": "BLOCK"
      }
    }
  ]
}

```

# Configuration APIs

You can use configuring APIs to search for and get details about individual transactions or patterns of transactions. Configuring APIs are:

- [Overall Bandwidth](#)
- [PAC File Host Settings](#)
- [Identification Profiles](#)
- [Access Policies](#)
- [Domain Map](#)
- [Upstream Proxy](#)
- [HTTPS Proxy](#)
- [Log Subscriptions](#)
- [Header Based Authentication](#)
- [Request Header Rewrite Profiles](#)
- [Smart Software Licenses](#), on page 96
- [System Setup Wizard](#), on page 104
- [Decryption Policy](#), on page 107
- [Routing Policy](#), on page 115
- [IP Spoofing Profile](#), on page 119
- [Configuration Files](#), on page 122
- [Authentication Realms](#), on page 127
- [Umbrella Seamless ID](#), on page 133
- [Secure DNSSEC Settings](#), on page 136
- [Identity Service Engine](#), on page 137
- [Anti-Malware Reputation](#), on page 143

## Overall Bandwidth

This section contains the following topics:

- [Retrieving the Overall Bandwidth Details](#)
- [Modifying the Overall Bandwidth Details](#)

## Retrieving the Overall Bandwidth Details

You can retrieve information about the overall bandwidth for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v3.0/web_security/overall_bandwidth_limit	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the overall bandwidth configuration on the device.

### Sample Request

```
GET /wsa/api/v3.0/web_security/overall_bandwidth_limit
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 08:22:28 GMT
Content-type: application/json
Content-Length: 22
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "bandwidth_limit": 0
}
```

## Modifying the Overall Bandwidth Details

You can modify the overall bandwidth control for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	PUT wsa/api/v3.0/configure/web_security/overall_bandwidth_limit	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization

<b>Response Headers</b>		Content-Type, Content-Length, Connection
-------------------------	--	--

### Example

This example shows how to modify and set the overall bandwidth configuration on the device.

### Sample Request

```
PUT /wsa/api/v3.0/configure/web_security/overall_bandwidth_limit
HTTP/1.1
Host: wsa.example.com:6443
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 31
```

```
{
    "bandwidth_limit": 128
}
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 08:28:32 GMT
Content-type: application/json
Content-Length: 24
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
    "bandwidth_limit": 128
}
```

## PAC File Host Settings

This section contains the following topics:

- [Retrieving the PAC File Basic Settings](#)
- [Modifying the PAC File Basic Settings](#)
- [Retrieving the PAC Files](#)
- [Retrieving the List of PAC Files](#)
- [Adding a New PAC File](#)
- [Modifying the Existing PAC Files](#)
- [Deleting a PAC File](#)
- [Retrieving a PAC File and the Hostname Association](#)
- [Adding a PAC File and the Hostname Association](#)
- [Modifying the Existing PAC File and the Hostname Association](#)

- [Deleting a PAC File and the Hostname Association](#)

## Retrieving the PAC File Basic Settings

You can retrieve and set the PAC File hosting status, the PAC File expiration, and the PAC File expiration limit.

<b>Synopsis</b>	GET /wsa/api/v3.0/security_services/pac_basic_setting	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the PAC File hosting status, the PAC File expiration status, PAC file server ports, and the PAC File expiration interval.

### Sample Request

```
GET /wsa/api/v3.0/security_services/pac_basic_setting HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 08:33:01 GMT
Content-type: application/json
Content-Length: 135
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "pac_basic_setting": {
    "status": "enable",
    "pac_file_expiry": "enable",
    "pac_server_ports": [
      "3344"
    ],
    "pac_expiration_interval": 1234
  }
}
```

## Modifying the PAC File Basic Settings

You can modify the basic settings for PAC File hosting.



<b>Synopsis</b>	PUT /wsa/api/v3.0/security_services/pac_basic_setting	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the PAC File hosting status, the PAC File expiration status, PAC file server ports, and the PAC File expiration interval.

### Sample Request

```
PUT /wsa/api/v3.0/security_services/pac_basic_setting
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
Content-Type: text/plain
Content-Length: 170
{
  "status": "enable",
  "pac_file_expiry": "enable",
  "pac_server_ports": [
    3345
  ],
  "pac_expiration_interval": 1233
}
```

### Sample Response

```
HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 08:12:48 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

## Retrieving the PAC Files

You can retrieve the PAC files hosted on the Secure Web Appliance. The 'file\_name' parameter can be used to get a particular file from the Secure Web Appliance.

<b>Synopsis</b>	GET /wsa/api/v3.0/security_services/pac_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the list of all PAC files hosted on the Secure Web Appliance.

### Sample Request

```
GET /wsa/api/v3.0/security_services/pac_file?file_name=sample_pac_file.pac
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 13 Jan 2021 09:18:25 GMT
Content-Description: File Transfer
Content-type: application/octet-stream
Content-Disposition: attachment; filename=sample_pac_file.pac
Content-Length: 1195
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
<
function FindProxyForURL(url, host) {

// If the hostname matches, send direct.
    if (dnsDomainIs(host, "intranet.domain.com") ||
        shExpMatch(host, "(*.abcdomain.com|abcdomain.com)"))
        return "DIRECT";

// If the protocol or URL matches, send direct.
    if (url.substring(0, 4)=="ftp:" ||
        shExpMatch(url, "http://abcdomain.com/folder/*"))
        return "DIRECT";

// If the requested website is hosted within the internal network, send direct.
    if (isPlainHostName(host) ||
        shExpMatch(host, "*.local") ||
        isInNet(dnsResolve(host), "10.0.0.0", "255.0.0.0") ||
        isInNet(dnsResolve(host), "172.16.0.0", "255.240.0.0") ||
        isInNet(dnsResolve(host), "192.168.0.0", "255.255.0.0") ||
        isInNet(dnsResolve(host), "127.0.0.0", "255.255.255.0"))
        return "DIRECT";

// If the IP address of the local machine is within a defined
// subnet, send to a specific proxy.
    if (isInNet(myIpAddress(), "10.10.5.0", "255.255.255.0"))
        return "PROXY 1.2.3.4:8080";

// DEFAULT RULE: All other traffic, use below proxies, in fail-over order.
    return "PROXY 4.5.6.7:8080; PROXY 7.8.9.10:8080";
```

## Retrieving the List of PAC Files

You can retrieve the list of all the PAC files hosted on the Secure Web Appliance. The 'file\_name' parameter can be used to get a particular file from the Secure Web Appliance.

<b>Synopsis</b>	GET /wsa/api/v3.0/security_services/pac_file	
<b>Supported Resource Attributes</b>	For information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the list of all PAC files hosted on the Secure Web Appliance.

### Sample Request

```
GET /wsa/api/v3.0/security_services/pac_file
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 08:41:59 GMT
Content-type: application/json
Content-Length: 38
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "pac_files": [
    "sample_pac_file.pac"
  ]
}
```

## Adding a New PAC File

You can upload a new PAC file. Multiple files can be uploaded in a single request.

<b>Synopsis</b>	POST /wsa/api/v3.0/security_services/pac_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to add a new PAC file.

**Sample Request**

```
POST /wsa/api/v3.0/security_services/pac_file
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzY28xMjMk
Content-Length: 1384
Expect: 100-continue
Content-Type: multipart/form-data; boundary=-----6b685d35de1f2379
```

**Sample Response**

```
HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 08:52:28 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

**Modifying the Existing PAC Files**

You can modify an existing PAC file.



**Note** The file with the same file name must exist.

<b>Synopsis</b>	PUT /wsa/api/v3.0/security_services/pac_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to modify existing PAC files.

### Sample Request

```

PUT /wsa/api/v3.0/security_services/pac_file
HTTP/1.1
Host: wsa.example.com:6443
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Length: 221
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary7MA4YWxkTrZu0gW

----WebKitFormBoundary7MA4YWxkTrZu0gW
Content-Disposition: form-data; name="";
filename="/C:/Users/Admin/Desktop/sample_pac_file.pac"
Content-Type: <Content-Type header here>

(data)
----WebKitFormBoundary7MA4YWxkTrZu0gW

```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 08:55:59 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

## Deleting a PAC File

You can now delete a PAC file.

<b>Synopsis</b>	DELETE /wsa/api/v3.0/security_services/pac_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete a PAC file.

#### Sample Request

```

DELETE /wsa/api/v3.0/security_services/pac_file?file_name=sample_pac_file2.pac
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q21zY28xMjMk

```

#### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 08:58:39 GMT
Connection: close

```

```

Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

## Retrieving a PAC File and the Hostname Association

You can retrieve PAC files and their associated hostnames.

<b>Synopsis</b>	GET /wsa/api/v3.0/security_services/pacfile_host	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve PAC files and the associated hostnames.

#### Sample Request

```

GET /wsa/api/v3.0/security_services/pacfile_host
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzyY28xMjMk

```

#### Sample Response

```

HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 09:00:51 GMT
Content-type: application/json
Content-Length: 160
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "hostname_pac_mapping": {
    "wsa3101": "sample_pac_file.pac",
    "wsa333": "sample_pac_file.pac",
    "wsa3103": "sample_pac_file.pac",
    "wsa332": "sample_pac_file.pac"
  }
}

```

## Adding a PAC File and the Hostname Association

You can create a PAC file and their associated hostname.

<b>Synopsis</b>	POST /wsa/api/v3.0/security_services/pacfile_host
-----------------	---

<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add a PAC file and their associated hostname.

#### Sample Request

```
POST /wsa/api/v3.0/security_services/pacfile_host
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
Content-Type: application/json
Content-Length: 247
{
  "hostname_pac_mapping": [
    {
      "hostname": "wsa1332",
      "pac_filename": "sample_pac_file.pac"
    },
    {
      "hostname": "wsa13101",
      "pac_filename": "sample_pac_file.pac"
    }
  ]
}
```

#### Sample Response

```
HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 09:04:16 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

## Modifying the Existing PAC File and the Hostname Association

You can modify an existing PAC file and the associated hostname.



**Note** The mapping for the given or provided hostname must exist.

<b>Synopsis</b>	PUT /wsa/api/v3.0/security_services/pacfile_host
-----------------	--

<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to map the PAC files with the hostnames.

#### Sample Request

```
PUT /wsa/api/v3.0/security_services/pacfile_host
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzY28xMjMk
Content-Type: application/json
Content-Length: 247
{
  "hostname_pac_mapping": [
    {
      "hostname": "wsa1332",
      "pac_filename": "sample_pac_file.pac"
    },
    {
      "hostname": "wsa13101",
      "pac_filename": "sample_pac_file.pac"
    }
  ]
}
```

#### Sample Response

```
HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 09:06:44 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

## Deleting a PAC File and the Hostname Association

You can delete the existing PAC file and the associated hostname.



**Note** The mapping for the given or provided hostname must exist.

<b>Synopsis</b>	DELETE /wsa/api/v3.0/security_services/pacfile_host
-----------------	---



<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete a PAC file and the associated hostname.

### Sample Request

```
DELETE /wsa/api/v3.0/security_services/pacfile_host?host_name=wsa1332
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

### Sample Response

```
HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 09:09:18 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

## Identification Profiles

This section contains the following topics:

- [Retrieving the Identification Details](#)
- [Modifying the Identification Profiles](#)
- [Adding the Identification Profiles](#)
- [Deleting the Identification Profile](#)

### Retrieving the Identification Details

You can retrieve the identification profiles for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v3.0/web_security/identification_profiles
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the identification profiles.

#### Sample Request

```
GET /wsa/api/v3.0/web_security/identification_profiles
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 14:18:53 GMT
Content-type: application/json
Content-Length: 598
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "identification_profiles": [
    {
      "status": "enable",
      "description": "Sample ID profile",
      "identification_method": {
        "auth_scheme": [
          "NTLMSSP"
        ],
        "auth_sequence": "ldaprealm",
        "auth_surrogate_by_proto": {
          "ftp": "ip",
          "http": "ip",
          "https": "ip"
        },
        "prompt_on_sso_failure": "authenticate",
        "use_forward_surrogates": 0,
        "sso_scheme": "sso_none",
        "use_guest_on_auth_failure": 1
      },
      "profile_name": "idsample",
      "members": {
        "protocols": [
          "http",
          "https",
          "ftp"
        ]
      },
      "order": 1
    },
  ],
}
```

```

        "status": "enable",
        "profile_name": "global_identification_profile",
        "description": "Default settings",
        "identification_method": {}
    }
]
}

```

## Modifying the Identification Profiles

You can modify the identification profiles for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	PUT /wsa/api/v3.0/web_security/identification_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add the identification profile.

#### Sample Request

```

PUT /wsa/api/v3.0/web_security/identification_profiles
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 275
{
  "identification_profiles": [
    {
      "profile_name": "sample ID",
      "new_profile_name": "sample ID modifiedw"
    },
    {
      "status": "disable",
      "profile_name": "idsample",
      "order": 1
    }
  ]
}

```

#### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 14:28:03 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email

```

```
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

## Adding the Identification Profiles

You can create the identification profiles for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	POST /wsa/api/v3.0/web_security/identification_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the identification profiles.

### Sample Request

```
POST /wsa/api/v3.0/web_security/identification_profiles
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 900
{
  "identification_profiles": [
    {
      "status": "enable",
      "description": "Sample description",
      "identification_method": {
        "auth_scheme": [
          "Basic"
        ],
        "auth_sequence": "ldaprealm",
        "auth_surrogate_by_proto": {
          "ftp": "ip",
          "http": "ip",
          "https": "ip"
        },
        "prompt_on_sso_failure": "authenticate",
        "use_forward_surrogates": 1,
        "sso_scheme": "sso_none",
        "use_guest_on_auth_failure": 0
      },
      "profile_name": "sample ID",
      "members": {
        "protocols": [
          "http",
          "https",
          "ftp" ]
      }
    }
  ]
}
```

```

    },
    "order": 1
  }
]
}

```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 08:12:48 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

## Deleting the Identification Profile

You can delete an identification profile for the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v3.0/web_security/identification_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the identification profile.

### Sample Request

```

DELETE
/wsa/api/v3.0/web_security/identification_profiles?profile_names=idsample,%20sample%20ID%20profile

HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

### Sample Response

```

HTTP/1.1 207
Date: Mon, 11 Jan 2021 14:31:21 GMT
Content-type: application/json
Content-Length: 258
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken
{

```

```

"success_list": [
  {
    "status": 200,
    "message": "success",
    "profile_name": "idsample"
  }
],
"failure_list": [
  {
    "status": 404,
    "message": "profile_name 'sample ID profile' doesn't exist",
    "profile_name": "sample ID profile"
  }
],
"success_count": 1,
"failure_count": 1
}

```

## Access Policies

This section contains the following topics:

- [Retrieving an Access Policy](#)
- [Modifying an Access Policy](#)
- [Adding an Access Policy](#)
- [Deleting an Access Policy](#)

### Retrieving an Access Policy

You can retrieve a list of access policies configured on the Secure Web Appliance.

<b>Synopsis</b>	GET /wsa/api/v3.0/web_security/access_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

#### Example

This example shows a query to retrieve an access policy with the policy name "AP106"

#### Sample Request

```

GET /wsa/api/v3.0/web_security/access_policies?policy_names=AP106
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

## Sample Response

```

HTTP/1.1 200 OK
Date: Mon, 11 Jan 2021 14:34:52 GMT
Content-type: application/json
Content-Length: 1143
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

```

```

Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "access_policies": [
    {
      "policy_expiry": "",
      "policy_status": "enable",
      "policy_name": "AP106",
      "membership": {
        "identification_profiles": [
          {
            "_all_": {
              "auth": "No Authentication"
            }
          }
        ],
        "url_categories": [
          {
            "id_profile": "",
            "value": {
              "predefined": [
                "Advertisements",
                "Alcohol",
                "Arts",
                "Astrology"
              ]
            }
          }
        ]
      }
    },
    {
      "objects": {
        "state": "use_global"
      },
      "protocols_user_agents": {
        "state": "use_global"
      },
      "http_rewrite_profile": "use_global",
      "avc": {
        "state": "use_global"
      },
      "policy_description": "new test policy",
      "policy_order": 1,
      "url_filtering": {
        "safe_search": {
          "status": "use_global"
        },
        "content_rating": {
          "status": "use_global"
        }
      },
      "yt_cats": {
        "use_global": [
          "Film & Animation",
          "Autos & Vehicles",

```

```

    "Music",
    "Pets & Animals",
    "Sports",
    "Travel & Events",
    "Gaming",
    "People & Blogs",
    "Comedy",
    "Entertainment",
    "News & Politics",
    "Howto & Style",
    "Education",
    "Science & Technology",
    "Nonprofits & Activism"
  ]
},
"state": "custom",
"exception_referred_embedded_content": {
  "state": "disable"
},
"update_cats_action": "use_global",
"predefined_cats": {
  "use_global": [
    "Advertisements",
    "Alcohol",
    "Arts",
    "Astrology"
  ]
}
},
"amw_reputation": {
  "state": "use_global"
}
}
]
}

```

## Modifying an Access Policy

You can modify a list of access policies and their configuration payload.

<b>Synopsis</b>	PUT /wsa/api/v3.0/web_security/access_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify an access policy.

### Sample Request

```

PUT /wsa/api/v3.0/web_security/access_policies
HTTP/1.1
Host: wsa.example.com:6443

```



```

User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 721
{
  "access_policies": [
    {
      "policy_name": "global policy",
      "protocols_user_agents": {
        "state": "custom",
        "block_protocols": [
          "http",
          "https"
        ]
      }
    },
    {
      "policy_name": "sample AP",
      "protocols_user_agents": {
        "block_protocols": [
          "http"
        ]
      }
    },
    {
      "policy_name": "AP106",
      "protocols_user_agents": {
        "state": "custom",
        "block_protocols": [
          "https"
        ]
      }
    }
  ]
}

```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 14:28:03 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

## Adding an Access Policy

You can create a list of access policies along with their configurations.

<b>Synopsis</b>	POST /wsa/api/v3.0/web_security/access_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Example

This example shows how to create an access policy.

### Sample Request

```
POST /wsa/api/v3.0/web_security/access_policies
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 1350
Expect: 100-continue
{
  "access_policies": [
    {
      "policy_status": "enable",
      "policy_name": "sample AP",
      "policy_order": 1,
      "membership": {
        "identification_profiles": [
          {
            "profile_name": "",
            "auth": "No Authentication"
          }
        ],
        "user_agents": {
          "predefined": [
            "Firefox",
            "Safari",
            "MSIE/10"
          ],
          "custom": [
            "Mozilla/. Gecko/. Firefox/"
          ],
          "is_inverse": 0
        }
      },
      "protocols_user_agents": {
        "state": "custom",
        "allow_connect_ports": [
          "20",
          "21",
          "1-65535"
        ],
        "block_protocols": [
          "ftp",
          "http",
          "https",
          "nativeftp"
        ],
        "block_custom_user_agents": [
          "Mozilla/* Gecko/* Firefox/, Mozilla/4.0 (compatible; MSIE 5.5;)",
          "test"
        ]
      }
    }
  ]
}
```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Mon, 11 Jan 2021 14:28:03 GMT
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

## Deleting an Access Policy

You can delete an access policy using the policy name.

<b>Synopsis</b>	DELETE /wsa/api/v3.0/web_security/access_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete multiple access policies at once.

### Sample Request

```

DELETE /wsa/api/v3.0/web_security/access_policies?policy_names=AP105,%20sample%20AP,%20AP110

HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

### Sample Response

```

HTTP/1.1 207
Date: Mon, 11 Jan 2021 14:44:21 GMT
Content-type: application/json
Content-Length: 289
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "success_list": [
    {
      "status": 200,
      "message": "success",
      "policy_name": "AP105"
    },
    {

```

```

        "status": 200,
        "message": "success",
        "policy_name": "sample AP"
    }
],
"failure_list": [
    {
        "status": 404,
        "message": "policy name does not exist.",
        "policy_name": "AP110"
    }
],
"success_count": 2,
"failure_count": 1
}

```

## Domain Map

This section contains the following topics:

- [Retrieving the Domain Map Details](#)
- [Modifying the Domain Map Details](#)
- [Adding a Domain Map](#)
- [Deleting the Domain Map](#)

## Retrieving the Domain Map Details

You can retrieve the domain map details for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/web_security/domain_map	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the domain map details.

### Sample Request

```

GET /wsa/api/v2.0/configure/web_security/domain_map
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

## Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 08:41:26 GMT
Content-type: application/json
Content-Length: 239
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data": [
    {
      "IP_addresses": [
        "10.10.1.1"
      ],
      "domain_name": "example.cisco.com",
      "order": 1
    },
    {
      "domain_name": "sample.cisco.com",
      "IP_addresses": [
        "10.10.2.25"
      ],
      "order": 2
    }
  ],
  "res_message": "Data received successfully.",
  "res_code": 200
}

```

## Modifying the Domain Map Details

You can modify the domain map details.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/web_security/domain_map	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the domain map details.

### Sample Request

```

PUT /wsa/api/v2.0/configure/web_security/domain_map
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*

```

```

Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 247

[
  {
    "new_domain_name": "abcd.com",
    "domain_name": "abc.com",
    "order": 102,
    "IP_addresses": [
      "002:45:32::00:12/24", "2.2.2.1-10"
    ]
  }
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:03:24 GMT
Content-type: application/json
Content-Length: 204
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "res_data":
  {
    "update_success":
    [
      {
        "order": 4,
        "domain_name":
        "abcd.com",
        "server_list":
        [
          "2:45:32::12/24",
          "2.2.2.1-10"
        ]
      }
    ],
    "update_failure":
    [
    ],
  },
  "res_message":
  "Success: 1,
  Failure: 0",
  "res_code": 200
}

```

## Adding a Domain Map

You can create a domain map along with their configurations.

<b>Synopsis</b>	POST /wsa/api/v2.0/configure/web_security/domain_map
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to create a domain map.

### Sample Request

```
POST /wsa/api/v2.0/configure/web_security/domain_map
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 414
```

```
[
  {
    "domain_name": "abc.com",
    "order": 102,
    "IP_addresses": [
      "002:45:32::00:12/24", "2.2.2.1-10"
    ]
  },
  {
    "domain_name": "xyz.com",
    "order": 102,
    "IP_addresses": [
      "002:55:34::00:12/24", "2.5.5.1-10"
    ]
  }
]
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 08:51:49 GMT
Content-type: application/json
Content-Length: 286
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data":
  {
    "add_failure":
    [
    ],
    "add_success":
    [
      {
        "domain_name":
        "abc.com",
        "order": 4,

```

```

        "server_list":
          [
            "2:45:32::12/24",
            "2.2.2.1-10"
          ]
      },
      {
        "domain_name": "xyz.com",
        "order": 5,
        "server_list":
          [
            "2:55:34::12/24",
            "2.5.5.1-10"
          ]
      }
    ]
  },
  "res_message":
  "Success: 2,
  Failure: 0",
  "res_code": 201
}

```

## Deleting the Domain Map

You can delete a domain map for the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v2.0/configure/web_security/domain_map	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the domain map.

#### Sample Request

```

DELETE /wsa/api/v2.0/configure/web_security/domain_map
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 33

{
  "domain_name": "xyz.com"
}

```

#### Sample Response



```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:10:08 GMT
Content-type: application/json
Content-Length: 103
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition,
jwtToken

{
  "res_data":
  {
    "delete_success":
    [
      "xyz.com"
    ]
  },
  "res_message":
  "Success: 1,
  Failure: 0",
  "res_code": 200
}

```

## Upstream Proxy

This section contains the following topics:

- [Retrieving the Upstream Proxy Details](#)
- [Modifying the Upstream Proxy Settings](#)
- [Adding an Upstream Proxy](#)
- [Deleting the Upstream Proxy](#)
- [Modifying the Upstream Proxy Servers](#)
- [Adding an Upstream Proxy Server](#)
- [Deleting the Upstream Proxy Servers](#)

## Retrieving the Upstream Proxy Details

You can retrieve the upstream proxy details for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/ network/upstream_proxy
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.
<b>Request Headers</b>	Host, Accept, Authorization

<b>Response Headers</b>	Content-Type, Content-Length, Connection
-------------------------	--

### Example

This example shows a query to retrieve the upstream proxy details.

### Sample Request

```
GET /wsa/api/v2.0/configure/network/upstream_proxy
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:17:25 GMT
Content-type: application/json
Content-Length: 253
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data": [
    {
      "used_by_ocsp": true,
      "proxy_servers": [
        {
          "retries": 2,
          "host": "dut058.perf8",
          "port": 3128
        }
      ],
      "load_balancing": "none",
      "failure_handling": "connect",
      "group_name": "Test"
    }
  ],
  "res_message": "Data received successfully.",
  "res_code": 200
}
```

## Modifying the Upstream Proxy Settings

You can modify the upstream proxy setting for the Secure Web Appliance.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/network/upstream_proxy
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.
<b>Request Headers</b>	Host, Accept, Authorization

<b>Response Headers</b>	Content-Type, Content-Length, Connection
-------------------------	--

**Example**

This example shows how to modify the group name, new group name, failure handling, and load balancing properties of the upstream proxy.

**Sample Request**

```
PUT /wsa/api/v2.0/configure/network/upstream_proxy
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 170
```

```
[
  {
    "group_name": "Test11",
    "new_group_name": "Test1",
    "failure_handling": "drop",
    "load_balancing": "none"
  }
]
```

**Sample Response**

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:35:27 GMT
Content-type: application/json
Content-Length: 187
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"res_data":
{
  "modify_success":
  [
    {
      "new_group_name": "Test1",
      "failure_handling":
      "drop",
      "load_balancing": "none",
      "group_name": "Test11"
    }
  ]
},
"res_message":
"Success: 1",
"res_code": 200}
```

**Adding an Upstream Proxy**

You can create an upstream proxy along with their configurations.

<b>Synopsis</b>	POST /wsa/api/v2.0/configure/network/upstream_proxy
-----------------	---

<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to create an upstream proxy.

#### Sample Request

```
POST /wsa/api/v2.0/configure/network/upstream_proxy
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 252
```

```
{
  "group_name": "Test2",
  "failure_handling": "connect",
  "load_balancing": "none",
  "proxy_servers": [
    {
      "host": "www.google.com",
      "retries": 1,
      "port": 22
    }
  ]
}
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:30:52 GMT
Content-type: application/json
Content-Length: 232
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data":
  {
    "add_success":
    [
      {
        "proxy_servers":
        [
          {
            "retries": 1,
            "host":
```

```

        "www.google.com",
        "port": 22
    }
  ],
  "load_balancing":
    "none",
  "failure_handling":
    "connect",
  "group_name":
    "Test2"
}
]
},
"res_message":
"Success: 1",
"res_code": 201
}

```

## Deleting the Upstream Proxy

You can delete an upstream proxy for the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v2.0/configure/network/upstream_proxy	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the upstream proxy.

### Sample Request

```

DELETE /wsa/api/v2.0/configure/network/upstream_proxy HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 30

```

```

{
  "proxy_group": "Test1"
}

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 09:39:38 GMT
Content-type: application/json
Content-Length: 160
Connection: close
Access-Control-Allow-Origin: *

```

```

Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data": {
    "delete_success": [
      "Test1"
    ]
  },
  "res_message": "Success: 1",
  "res_code": 200
}

```

## Modifying the Upstream Proxy Servers

You can modify the upstream proxy server settings.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/network/upstream_proxy/servers	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the name of the upstream proxy servers.

### Sample Request

```

PUT /wsa/api/v2.0/configure/network/upstream_proxy/servers
HTTP/1.1
Host: wsas.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 243

```

```

[
  {
    "group_name": "Test3",
    "proxy_servers": [
      {
        "retries": 1,
        "host": "7.7.7.7",
        "new_host": "7.7.8.8",
        "port": 22
      }
    ]
  }
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 10:17:00 GMT
Content-type: application/json
Content-Length: 194
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{"res_data": {"modify_success": [{"proxy_servers": [{"retries": 1,
"host": "7.7.7.7", "port": 22, "new_host": "7.7.8.8"}], "group_name": "Test3"}]},
"res_message": "Success: 1", "res_code": 200}

```

## Adding an Upstream Proxy Server

You can create an upstream proxy server along with their configurations.

<b>Synopsis</b>	POST /wsa/api/v2.0/configure/network/upstream_proxy/servers	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add an upstream proxy server to the configuration.

### Sample Request

```

POST /wsa/api/v2.0/configure/network/upstream_proxy/servers
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 204

```

```

[
  {
    "group_name": "Test3",
    "proxy_servers": [
      {
        "retries": 1,
        "host": "4.4.4.4",
        "port": 22
      }
    ]
  }
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 10:09:43 GMT
Content-type: application/json
Content-Length: 168
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data": {
    "add_success": [
      {
        "proxy_servers": [
          {
            "retries": 1,
            "host": "4.4.4.4",
            "port": 22
          }
        ],
        "group_name": "Test3"
      }
    ]
  },
  "res_message": "Success: 1",
  "res_code": 201
}

```

## Deleting the Upstream Proxy Servers

You can delete the configuration for upstream proxy servers for the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v2.0/configure/network/upstream_proxy/servers	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the configuration for upstream proxy servers.

.

### Sample Request

```

DELETE /wsa/api/v2.0/configure/network/upstream_proxy/servers
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1

```



```

Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 204

```

```

[
  {
    "group_name": "Test3",
    "proxy_servers": [
      {
        "retries": 1,
        "host": "7.7.8.8",
        "port": 22
      }
    ]
  }
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 10:28:07 GMT
Content-type: application/json
Content-Length: 171
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "res_data":
  {
    "delete_success":
    [
      {
        "proxy_servers":
        [
          {
            "retries": 1,
            "host": "7.7.8.8",
            "port": 22
          }
        ],
        "group_name": "Test3"
      }
    ],
    "res_message":
    "Success: 1",
    "res_code": 200
  }
}

```

## HTTPS Proxy

This section contains the following topics:

- [Retrieving the HTTPS Proxy Details](#)
- [Modifying the HTTP Proxy Settings](#)
- [Retrieving the HTTP Proxy—Download Certificate File](#)

- [Retrieving the HTTP Proxy OCSP Settings](#)
- [Modifying the HTTPS Proxy—OCSP Settings](#)

## Retrieving the HTTPS Proxy Details

You can retrieve the HTTPS proxy details for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/security_services/proxy/https	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the HTTPS proxy details.

#### Sample Request

```
GET /wsa/api/v2.0/configure/security_services/proxy/https
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 06:31:10 GMT
Content-type: application/json
Content-Length: 659
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
<
* Closing connection 0
* TLSv1.1 (OUT), TLS alert, Client hello (1):
{
  "res_data":
  {
    "uploaded_cert_data": null,
    "decrypt":
    {
      "user_notification": true,
      "user_acknowledgement": true,
      "authentication": true,
      "application_visibility": false
    },
  },
}
```

```

"current_cert_type":
"generated",
"invalid_cert_handling":
{
  "expired_cert":
  "scan",
  "invalid_leaf_cert":
  "drop",
  "unrecognized_root":
  "drop",
  "invalid_signing_cert":
  "drop",
  "mismatched_hostname":
  "scan",
  "other_error":
  "drop"
},
"generated_cert_data":
{
  "is_x509v3_critical": false,
  "expires": 1768407685,
  "country":
  "US",
  "org_unit":
  "SBG",
  "common_name": "CISCO",
  "org": "CISCO"
},
  "https_ports": "443",
  "https_enabled": false
},
"res_message":
"Data received successfully.",
"res_code": 200
}

```

## Modifying the HTTP Proxy Settings

You can modify the HTTP Proxy settings.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/security_services/proxy/https	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify HTTP Proxy settings.

### Sample Request

```

PUT /wsa/api/v2.0/configure/security_services/proxy/https
HTTP/1.1
Host: wsa.example.com:6443

```

```

User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Length: 2237
Expect: 100-continue
Content-Type: multipart/form-data; boundary=-----23fc1d072de41043
--form 'https_enabled="true" ' \
--form 'https_ports="9443" ' \
--form 'authentication="true" ' \
--form 'user_acknowledgement="true" ' \
--form 'application_visibility="false" ' \
--form 'user_notification="false" ' \
--form 'expired_cert="drop" ' \
--form 'invalid_leaf_cert="drop" ' \
--form 'unrecognized_root="drop" ' \
--form 'invalid_signing_cert="drop" ' \
--form 'mismatched_hostname="drop" ' \
--form 'other_error="drop" ' \
--form 'current_cert_type="generated" ' \
--form 'accept_license="true" ' \
--form 'common_name="dut037.perf8" ' \
--form 'org="CISCOSBG" ' \
--form 'org_unit="CS" ' \
--form 'country="IN" ' \
--form 'expires="35" ' \
--form 'is_x509v3_critical="true" '

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 07:51:13 GMT
Content-type: application/json
Content-Length: 691
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
<
* Closing connection 0
* TLSv1.1 (OUT), TLS alert, Client hello (1):
{
  "res_data": {
    "expired_cert": "drop",
    "is_x509v3_critical": true,
    "expires": 35,
    "invalid_leaf_cert": "drop",
    "unrecognized_root": "drop",
    "invalid_signing_cert": "drop",
    "user_acknowledgement": true,
    "country": "IN",
    "common_name": "dut037.perf8",
    "org_unit": "CS",
    "mismatched_hostname": "drop",
    "current_cert_type": "generated",
    "user_notification": false,
    "authentication": true,
    "https_ports": "9443",
    "https_enabled": true,
    "org": "CISCOSBG",
    "application_visibility": false,
    "other_error": "drop"
  },
  "res_message": "Data updated successfully."
}

```





```

        "ocsp_valid_response_cache_timeout": 3600,
        "ocsp_proxy_group": "",
        "ocsp_enabled": true,
        "ocsp_invalid_response_cache_timeout": 120,
        "ocsp_proxy_group_exempt_list": [],
        "ocsp_clock_skew": 300,
        "ocsp_network_error_cache_timeout": 60,
        "ocsp_use_upstream_proxy": false,
        "ocsp_use_nonce": false
    },
    "res_message": "Data received successfully.",
    "res_code": 200
}

```

## Modifying the HTTP Proxy—OCSP Settings

You can modify the HTTP proxy OCSP settings.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/security_services/proxy/ocsp	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the HTTP proxy OCSP settings.

### Sample Request

```

PUT /wsa/api/v2.0/configure/security_services/proxy/ocsp
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 528

```

```

{
  "ocsp_enabled": true,
  "ocsp_valid_response_cache_timeout": 1200,
  "ocsp_invalid_response_cache_timeout": 120,
  "ocsp_network_error_cache_timeout": 34324,
  "ocsp_clock_skew": 23,
  "ocsp_network_error_timeout": 3,
  "ocsp_result_handling":
    { "unknown": "scan",
      "revoked": "decrypt",
      "error": "scan"
    },
  "ocsp_use_nonce": true,
  "ocsp_use_upstream_proxy": true,
  "ocsp_proxy_group": "Test",

```

```

    "ocsp_proxy_group_exempt_list": []
  }

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 08:27:32 GMT
Content-type: application/json
Content-Length: 489
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data": {
    "ocsp_enabled": true,
    "ocsp_result_handling": {
      "unknown": "scan",
      "revoked": "decrypt",
      "error": "scan"
    },
    "ocsp_network_error_timeout": 3,
    "ocsp_invalid_response_cache_timeout": 120,
    "ocsp_proxy_group_exempt_list": [],
    "ocsp_valid_response_cache_timeout": 1200,
    "ocsp_clock_skew": 23,
    "ocsp_proxy_group": "Test",
    "ocsp_network_error_cache_timeout": 34324,
    "ocsp_use_upstream_proxy": true,
    "ocsp_use_nonce": true
  },
  "res_message": "Data updated successfully.",
  "res_code": 200
}

```

## Log Subscriptions

This section contains the following topics:

- [Retrieving the Log Subscriptions](#)
- [Modifying the Log Subscriptions](#)
- [Adding the Log Subscriptions](#)
- [Deleting the Log Subscriptions](#)
- [Modifying the Log Subscriptions—Rollover](#)
- [Retrieving the Log Subscriptions for the Fetch Field Lists](#)
- [Retrieving the Log Subscriptions to Fetch Default Values for a Log Type](#)
- [Adding the Log Subscriptions—Deanonimization](#)



## Retrieving the Log Subscriptions

You can retrieve the log subscriptions for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/system/log_subscriptions	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the log subscriptions.

#### Sample Request

```
GET /wsa/api/v2.0/configure/system/log_subscriptions
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 10:34:48 GMT
Content-type: application/json
Content-Length: 7945
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data": [
    {
      "rollover_interval": "none",
      "log_name": "accesslogs",
      "log_type": "Access Logs",
      "log_file_name": "aclog",
      "enable_deanonymization": true
    },
    {
      "rollover_interval": "none",
      "log_name": "amp_logs",
      "log_type": "AMP Engine Logs",
      "log_file_name": "amp",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
```

```

    "log_name": "archiveinspect_logs",
    "log_type": "ArchiveInspect Logs",
    "log_file_name": "archiveinspect_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "audit_logs",
    "log_type": "Audit Logs",
    "log_file_name": "audit_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "authlogs",
    "log_type": "Authentication Framework Logs",
    "log_file_name": "authlog",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "avc_logs",
    "log_type": "AVC Engine Logs",
    "log_file_name": "avc_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "bypasslogs",
    "log_type": "Proxy Bypass Logs",
    "log_file_name": "tmon_bypass",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "cli_logs",
    "log_type": "CLI Audit Logs",
    "log_file_name": "cli",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "configdefragd_logs",
    "log_type": "Configuration Logs",
    "log_file_name": "configdefragd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "csid_logs",
    "log_type": "CSI Service Logs",
    "log_file_name": "csid_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "dca_logs",
    "log_type": "DCA Engine Logs",
    "log_file_name": "dca_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "external_auth_logs",

```

```
    "log_type": "External Authentication Logs",
    "log_file_name": "external_auth_logs",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "feedback_logs",
    "log_type": "Feedback Logs",
    "log_file_name": "feedback_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "feedsd_logs",
    "log_type": "Feedsd Logs",
    "log_file_name": "feedsd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "fips_logs",
    "log_type": "FIPS Logs",
    "log_file_name": "fips_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "ftpd_logs",
    "log_type": "FTP Server Logs",
    "log_file_name": "ftpd",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "gui_logs",
    "log_type": "GUI Logs",
    "log_file_name": "gui",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "haystackd_logs",
    "log_type": "Haystack Logs",
    "log_file_name": "haystackd",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "httpslog",
    "log_type": "HTTPS Logs",
    "log_file_name": "httpslog",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "hybridd_logs",
    "log_type": "Hybrid Service Logs",
    "log_file_name": "hybridd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "idsdataloss_logs",
    "log_type": "Data Security Logs",
```

```

    "log_file_name": "idsdataloss_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "ise_service_log",
    "log_type": "ISE Service Logs",
    "log_file_name": "ise_service_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "logderrorlogs",
    "log_type": "Logging Logs",
    "log_file_name": "logderrlog",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "mcafee_logs",
    "log_type": "McAfee Logs",
    "log_file_name": "mcafee_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "musd_logs",
    "log_type": "AnyConnect Secure Mobility Daemon Logs",
    "log_file_name": "musd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "ocspd_logs",
    "log_type": "OCSP Logs",
    "log_file_name": "ocspd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "pacd_logs",
    "log_type": "PAC File Hosting Daemon Logs",
    "log_file_name": "pacd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "policyinspectord_logs",
    "log_type": "Policy Inspector Logs",
    "log_file_name": "policyinspectord_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "proxylogs",
    "log_type": "Default Proxy Logs",
    "log_file_name": "proxyerrlog",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "reportd_logs",
    "log_type": "Reporting Logs",
    "log_file_name": "reportd",

```

```

    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "reportqueryd_logs",
    "log_type": "Reporting Query Logs",
    "log_file_name": "reportqueryd",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "saas_auth_log",
    "log_type": "SaaS Auth Logs",
    "log_file_name": "saas_auth_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "shd_logs",
    "log_type": "SHD Logs",
    "log_file_name": "shd",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "sl_usercountd_logs",
    "log_type": "SL Usercount Logs",
    "log_file_name": "sl_usercountd_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "smartlicense",
    "log_type": "Smartlicense Logs",
    "log_file_name": "smartlicense",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "snmp_logs",
    "log_type": "SNMP Logs",
    "log_file_name": "snmp_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "sntpd_logs",
    "log_type": "NTP Logs",
    "log_file_name": "sntpd",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "sophos_logs",
    "log_type": "Sophos Logs",
    "log_file_name": "sophos_log",
    "enable_deanonymization": false
  },
  {
    "rollover_interval": "none",
    "log_name": "sse_connectord_logs",
    "log_type": "SSE Connector Daemon Logs",
    "log_file_name": "sse_connectord_log",
    "enable_deanonymization": false
  }
}

```

```

    },
    {
      "rollover_interval": "none",
      "log_name": "status",
      "log_type": "Status Logs",
      "log_file_name": "status.log",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "system_logs",
      "log_type": "System Logs",
      "log_file_name": "system",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "trafmon_errlogs",
      "log_type": "Traffic Monitor Error Logs",
      "log_file_name": "tmon_err",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "trafmonlogs",
      "log_type": "Traffic Monitor Logs",
      "log_file_name": "tmon_misc",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "uds_logs",
      "log_type": "UDS Logs",
      "log_file_name": "uds_log",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "updater_logs",
      "log_type": "Updater Logs",
      "log_file_name": "updater_log",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "upgrade_logs",
      "log_type": "Upgrade Logs",
      "log_file_name": "upgrade_logs",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "wbnp_logs",
      "log_type": "WBNP Logs",
      "log_file_name": "wbnp_log",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "webcat_logs",
      "log_type": "Web Categorization Logs",
      "log_file_name": "webcat_log",
      "enable_deanonymization": false
    },
  ],

```

```

    {
      "rollover_interval": "none",
      "log_name": "webrootlogs",
      "log_type": "Webroot Logs",
      "log_file_name": "webrootlog",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "webtapd_logs",
      "log_type": "Webtapd Logs",
      "log_file_name": "webtapd",
      "enable_deanonymization": false
    },
    {
      "rollover_interval": "none",
      "log_name": "welcomeack_logs",
      "log_type": "Welcome Page Acknowledgement Logs",
      "log_file_name": "welcomeack_log",
      "enable_deanonymization": false
    }
  ],
  "res_message": "Data received successfully.",
  "res_code": 200
}

```

## Modifying the Log Subscriptions

You can modify the basic settings for log subscriptions.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/system/log_subscriptions	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the basic settings for log subscriptions.

### Sample Request

```

PUT /wsa/api/v2.0/configure/system/log_subscriptions
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 501

```

```

[
  {
    "log_name": "logs_1",
    "new_log_name": "logs_4",

```

```

    "log_level": "debug",
    "log_type": "CLI Audit Logs",
    "log_file_name": "cli_file_name",
    "rollover_file_size": 10240,
    "retrieval_method":
    {
        "max_num_files": 10,
        "method": "local"
    },
    "rollover_by_time":
    {
        "rollover_interval": "custom",
        "rollover_custom_time": 17280
    }
}
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 12:03:46 GMT
Content-type: application/json
Content-Length: 491
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "res_data":
  {
    "update_success":
    [
    ],
    "update_failure": [
    {
      "content":
      {
        "rollover_file_size": 10240,
        "log_name": "logs_1",
        "retrieval_method":
        {
          "max_num_files": 10,
          "method": "local"},
          "new_log_name":
          "logs_4",
          "log_level":
          "debug", "log_type":
          "CLI Audit Logs",
          "log_file_name":
          "cli_file_name",
          "rollover_by_time":
          {
            "rollover_interval":
            "custom",
            "rollover_custom_time":
            17280
          }
        },
        "error_msg":
        "'log_name':
        'logs_1' does not exist."}
      ]
    },
  }
}

```



```

    "res_message":
    "Success: 0,
    Failure: 1",
    "res_code": 400
  }

```

## Adding the Log Subscriptions

You can create log subscriptions along with their configurations.

<b>Synopsis</b>	POST /wsa/api/v2.0/configure/system/log_subscriptions	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to create log subscriptions.

### Sample Request

```

POST /wsa/api/v2.0/configure/system/log_subscriptions
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 527

```

```

[
  {
    "new_log_name": "logs_2",
    "log_level": "debug",
    "log_type": "CLI Audit Logs",
    "log_file_name": "cli_file_name",
    "rollover_file_size": 10240,
    "retrieval_method":
    {
      "max_num_files": 10,
      "method": "local"
    },
    "rollover_by_time":
    {
      "rollover_interval": "custom",
      "rollover_custom_time": 17280
    }
  }
]

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 11:16:58 GMT

```

```

Content-type: application/json
Content-Length: 481
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data":
  {
    "add_failure":
    [
    ],
    "add_success":
    [
      {
        "rollover_file_size": 10240,
        "log_name":
        "logs_2",
        "retrieval_method":
        {
          "scp_key_method":
          "auto",
          "syslog_protocol":
          "UDP",
          "scp_port": 22,
          "max_num_files": 10,
          "syslog_port": 514,
          "method": "local"
        },
        "log_level":
        "debug",
        "log_type":
        "CLI Audit Logs",
        "log_file_name":
        "cli_file_name",
        "rollover_by_time":
        {
          "rollover_interval":
          "custom",
          "rollover_custom_time": 17280
        }
      }
    ],
    "res_message":
    "Success: 1,
    Failure: 0",
    "res_code": 201
  }
}

```

## Deleting the Log Subscriptions

You can delete the log subscriptions for the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v2.0/configure/system/log_subscriptions
-----------------	---

<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the log subscriptions.

#### Sample Request

```
DELETE /wsa/api/v2.0/configure/system/log_subscriptions
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 54
```

```
{
  "delete_all": false,
  "log_name": "logs_2"
}
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 12:45:26 GMT
Content-type: application/json
Content-Length: 102
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data":
  {
    "delete_success":
    [
      "logs_2"
    ]
  },
  "res_message":
  "Success: 1,
  Failure: 0",
  "res_code": 200
}
```

## Modifying the Log Subscriptions—Rollover

You can modify the log subscriptions rollover settings.

<b>Synopsis</b>	PUT /wsa/api/v2.0/configure/system/log_subscriptions/rollover	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the log subscriptions rollover settings.

#### Sample Request

```
PUT /wsa/api/v2.0/configure/system/log_subscriptions/rollover
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 34
{
  "log_name": "mcafee_logs"
}
```

#### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 12:51:41 GMT
Content-type: application/json
Content-Length: 109
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

{
  "res_data":
  {
    "rollover_success":
    [
      "mcafee_logs"
    ]
  },
  "res_message":
  "Success: 1,
  Failure: 0",
  "res_code": 200
}
```

## Retrieving the Log Subscriptions for the Fetch Field Lists

You can retrieve the log subscriptions for the fetch field lists for Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/ system/log_subscriptions/fields	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the log subscriptions for the fetch field lists.

### Sample Request

```
GET /wsa/api/v2.0/configure/system/log_subscriptions/fields?fetch=facility_list
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 12:59:40 GMT
Content-type: application/json
Content-Length: 240
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken
```

```
{
  "res_data":
  [
    "auth",
    "authpriv",
    "console",
    "daemon",
    "ftp",
    "local0",
    "local1",
    "local2",
    "local3",
    "local4",
    "local5",
    "local6",
    "local7",
    "mail",
    "ntp",
```

```

        "security",
        "user"
    ],
    "res_message":
    "Data received successfully.",
    "res_code": 200
}

```

## Retrieving the Log Subscriptions to Fetch Default Values for a Log Type

You can retrieve the log subscriptions to fetch the default values for a log type. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v2.0/configure/system/log_subscriptions/defaults	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve the log subscriptions to fetch the default values for a log type.

### Sample Request

```

GET /wsa/api/v2.0/configure/system/log_subscriptions/defaults?log_type=Audit%20Logs
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 13:14:45 GMT
Content-type: application/json
Content-Length: 460
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "res_data":
  {
    "fetch_success":
    [
      {
        "log_style":
        "apache",
        "rollover_file_size": 10485760,
        "retrieval_method":

```

```

    {
      "scp_key_method":
      "auto",
      "syslog_facility":
      "user",
      "syslog_protocol":
      "UDP",
      "scp_port": 22,
      "max_num_files": 10,
      "syslog_port": 514,
      "method": "local"
    },
    {
      "log_level":
      "information",
      "log_type":
      "Audit Logs",
      "log_file_name":
      "audit_log",
      "rollover_by_time":
      {
        "rollover_interval":
        "none"
      }
    }
  ]
},
"res_message":
"Success: 1,
Failure: 0",
"res_code":
200
}

```

## Adding the Log Subscriptions—Deanonimization

You can add the Log Subscriptions—Deanonimization.

<b>Synopsis</b>	POST /wsa/api/v2.0/configure/system/log_subscriptions/deanonimization	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add the log subscriptions for Deanonimization.

### Sample Request

```

POST /wsa/api/v2.0/configure/system/log_subscriptions/deanonimization
HTTP/1.1
Host: wsa.example.com:6443
User-Agent: curl/7.55.1
Accept: */*
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

```

Content-Length: 688
Expect: 100-continue
Content-Type: multipart/form-data; boundary=-----7786918e29034048
--header 'Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz' \
--form 'log_name="accesslogs" \
--form 'passphrase="Agt@1111" \
--form 'encrypted_content="encrypted_text" \
--form 'paste_encrypted_text="\H/6VZtZeUccgwRWM1Ty3MVz8ijfKs/JT2HEEobmKyB0=,
H/6VZtZeUccgwRWM1Ty3MVz8ijfKs/JT2HEEobmKyB0=\ "' \
--form 'download_as_file="false"

```

### Sample Response

```

HTTP/1.1 200 OK
Date: Tue, 19 Jan 2021 13:52:10 GMT
Content-type: application/json
Content-Length: 230
Connection: close
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, DELETE, PUT, OPTIONS
Access-Control-Expose-Headers: Content-Disposition, jwtToken

```

```

{
  "res_data":
  {
    "deanonymized_list":
    [
      [
        "H/6VZtZeUccgwRWM1Ty3MVz8ijfKs/JT2HEEobmKyB0=",
        "10.10.57.34"
      ],
      [
        "H/6VZtZeUccgwRWM1Ty3MVz8ijfKs/JT2HEEobmKyB0=",
        "10.10.57.34"
      ]
    ]
  },
  "res_message":
  "Data received successfully.",
  "res_code": 201
}

```

## Header Based Authentication

This section contains the following topics:

- [Retrieve the Header Based Authentication Details](#)
- [Modifying the Header Based Authentication Details](#)

### Retrieve the Header Based Authentication Details

You can retrieve the Header Based Authentication details configured on the Secure Web Appliance.

<b>Synopsis</b>	GET /wsa/api/v3.0/network/xauth_header_setting
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.



<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to enable the header based authentication details.

#### Sample Request

```
GET /wsa/api/v3.0/network/xauth_header_setting
HTTP/1.1
```

#### Sample Response

```
Status Code: 200 OK
access-control-allow-credentials: true
access-control-allow-headers: content-type, jwttoken, mid, h, email
access-control-allow-methods: GET, POST, DELETE, PUT, OPTIONS
access-control-allow-origin: *
access-control-expose-headers: Content-Disposition, jwtToken
connection: close
content-length: 329
content-type: application/json
```

```
{
  "xauth_header_setting":
  {
    "xauth_std_user": {"text_format": "ASCII", "Binary_encoding": "No Encoding"},
    "xauth_std_group": {"text_format": "ASCII", "Binary_encoding": "No Encoding"},
    "xauth_use_group_header": "disable",
    "xauth_header_mode": "standard",
    "xauth_retain_auth_egress": "disable",
    "xauth_header_based_auth": "enable"
  }
}
```

### Configuring Header Based Authentication with Different Parameters

#### Example

This example shows how to configure a list of parameters related to Header Based Authentication Settings.

#### Sample Request

```
PUT /wsa/api/v3.0/network/xauth_header_setting
HTTP/1.1
```

```
{
  "xauth_header_based_auth" : "enable",
  "xauth_use_group_header" : "enable",
  "xauth_retain_auth_egress" : "enable",
  "xauth_header_mode": "standard",
  "xauth_std_user" : {"text_format": "UTF8", "Binary_encoding": "Base64"},
  "xauth_std_group" : {"text_format": "UTF8", "Binary_encoding": "Base64"}
}
```

#### Sample Response

```
Status Code: 204 No Content
access-control-allow-credentials: true
access-control-allow-headers: content-type, jwttoken, mid, h, email
access-control-allow-methods: GET, POST, DELETE, PUT, OPTIONS
access-control-allow-origin: *
access-control-expose-headers: Content-Disposition, jwtToken
connection: close
content-length: 3
content-type: application/json
```

## Modifying the Header Based Authentication Details

You can modify the header based authentication details.

<b>Synopsis</b>	PUT /wsa/api/v3.0/network/xauth_header_setting	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the header based authentication settings

#### Sample Request

```
PUT /wsa/api/v3.0/network/xauth_header_setting
HTTP/1.1
{
  "xauth_header_based_auth":"enable",
  "xauth_use_group_header":"enable",
  "xauth_retain_auth_egress":"enable",
  "xauth_header_mode":"custom",
  "xauth_custom_user":{"name":"user","text_format":"ASCII","Binary_encoding":"No Encoding"},
  "xauth_custom_group":{"name":"group","text_format":"ASCII","Binary_encoding":"No Encoding"}
}
```

#### Sample Response

```
Status Code: 204 No Content
access-control-allow-credentials: true
access-control-allow-headers: content-type, jwttoken, mid, h, email
access-control-allow-methods: GET, POST, DELETE, PUT, OPTIONS
access-control-allow-origin: *
access-control-expose-headers: Content-Disposition, jwtToken
connection: close
content-length: 3
content-type: application/json
```

### Example

This example shows how to enable the header based authentication details.

#### Sample Request

```
PUT /wsa/api/v3.0/network/xauth_header_setting
HTTP/1.1
{
  "xauth_header_based_auth":"enable"
}
```

### Sample Response

```
Status Code: 204 No Content
access-control-allow-credentials: true
access-control-allow-headers: content-type, jwttoken, mid, h, email
access-control-allow-methods: GET, POST, DELETE, PUT, OPTIONS
access-control-allow-origin: *
access-control-expose-headers: Content-Disposition, jwtToken
connection: close
content-length: 3
content-type: application/json
```

### Example

This example shows how to disable the header based authentication details.

### Sample Request

```
PUT /wsa/api/v3.0/network/xauth_header_setting
HTTP/1.1
{
  "xauth_header_based_auth":"disable"
}
```

### Sample Response

```
Status Code: 204 No Content
access-control-allow-credentials: true
access-control-allow-headers: content-type, jwttoken, mid, h, email
access-control-allow-methods: GET, POST, DELETE, PUT, OPTIONS
access-control-allow-origin: *
access-control-expose-headers: Content-Disposition, jwtToken
connection: close
content-length: 3
content-type: application/json
```

## Request Header Rewrite Profiles

This section contains the following topics:

- [Retrieving the Request Header Rewrite Details](#)
- [Modifying the Request Header Rewrite Details](#)
- [Adding a Request Header Rewrite Profile](#)
- [Deleting the Request Header Rewrite Profile](#)

### Retrieving the Request Header Rewrite Details

You can retrieve the request Header Profiles and X-Authenticated Header Global Settings configured on the Secure Web Appliance. The syntax and supported attributes are as follows:

<b>Synopsis</b>	GET /wsa/api/v3.0/web_security/http_rewrite_profiles
-----------------	--

<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows a query to retrieve request header profiles and X-Authenticated Header Global Settings.

### Sample Request

```
GET /wsa/api/v3.0/web_security/http_rewrite_profiles
HTTP/1.1
Host: wsa.example.com:4431
Authorization: Basic YWRtaW46Q2lzyY28xMjMk
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 17 Mar 2021 11:38:22 GMT
Content-Type: application/json; charset=UTF-8
Content-Length: 533
Connection: keep-alive
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

{
  "global_settings": {
    "delimiter_for_groups": ",",
    "rewrite_format_for_user": "$authMechanism://$domainName/$userName",
    "rewrite_format_for_groups": "$authMechanism://$domainName/$groupName"
  },
  "http_rewrite_profiles": [
    {
      "headers": [
        {
          "header_value": "Username-($ReqMeta[X-Authenticated-User])",
          "text_format": "ASCII",
          "header_name": "X-Authenticated-User",
          "binary_encoding": "No Encoding"
        },
        {
          "header_value": "1.2.3.4",
          "text_format": "ASCII",
          "header_name": "X-Client-IP",
          "binary_encoding": "No Encoding"
        }
      ],
      "profile_name": "RHR"
    }
  ]
}
```

## Modifying the Request Header Rewrite Details

You can modify the request header rewrite profiles and X-Authenticated Header Global Settings.

<b>Synopsis</b>	PUT /wsa/api/v3.0/web_security/http_rewrite_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the request header rewrite details.

### Sample Request

```
PUT /wsa/api/v3.0/web_security/http_rewrite_profiles
HTTP/1.1
Host: wsa.example.com:4431
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
Content-Type: text/plain
Content-Length: 1347
```

```
{
  "http_rewrite_profiles": [
    {
      "profile_name": "Profile 4",
      "new_profile_name": "Updated Profile",
      "headers": [
        {
          "header_name": "Header1",
          "header_value": "Value1",
          "text_format": "ASCII",
          "binary_encoding": "No Encoding"
        },
        {
          "header_name": "Header2",
          "header_value": "Value2",
          "text_format": "ASCII",
          "binary_encoding": "Base64"
        },
        {
          "header_name": "Header3",
          "header_value": "val",
          "text_format": "UTF-8",
          "binary_encoding": "No Encoding"
        },
        {
          "header_name": "Header4",
          "header_value": "val",
          "text_format": "UTF-8",
          "binary_encoding": "Base64"
        }
      ]
    }
  ]
}
```

```

    ],
    "global_settings": {
      "rewrite_format_for_user": "$authMechanism:\\\\$domainName\\\$userName",
      "rewrite_format_for_groups": "$authMechanism:\\\\$domainName\\\$groupName",
      "delimiter_for_groups": ":"
    }
  }
}

```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Wed, 17 Mar 2021 11:38:22 GMT
Connection: keep-alive
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

```

## Adding a Request Header Rewrite Profile

You can create a list of request header rewrite profiles and update X-Authenticated Header Global Settings.

<b>Synopsis</b>	POST /wsa/api/v3.0/web_security/http_rewrite_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to create request header rewrite profile and update X-Authenticated Header Global Settings.

### Sample Request

```

POST /wsa/api/v3.0/web_security/http_rewrite_profiles
HTTP/1.1
Host: wsa.example.com:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
Content-Type: application/json
Content-Length: 1295

```

```

{
  "http_rewrite_profiles": [
    {
      "profile_name": "Profile 4",
      "headers": [
        {
          "header_name": "Header1",
          "header_value": "Value1",
          "text_format": "ASCII",
          "binary_encoding": "No Encoding"
        },
        {

```

```

        "header_name": "Header2",
        "header_value": "Value2",
        "text_format": "ASCII",
        "binary_encoding": "Base64"
    },
    {
        "header_name": "Header3",
        "header_value": "val",
        "text_format": "UTF-8",
        "binary_encoding": "No Encoding"
    },
    {
        "header_name": "Header4",
        "header_value": "val",
        "text_format": "UTF-8",
        "binary_encoding": "Base64"
    }
]
}
},
"global_settings": {
    "rewrite_format_for_user": "$authMechanism:\\\\$domainName\\$userName",
    "rewrite_format_for_groups": "$authMechanism:\\\\$domainName\\$groupName",
    "delimiter_for_groups": ":"
}
}
}

```

### Sample Response

```

HTTP/1.1 204 No Content
Date: Wed, 17 Mar 2021 11:38:22 GMT
Connection: keep-alive
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true

```

## Deleting the Request Header Rewrite Profile

You can delete request header rewrite profile by using `profile_name` and select alternate profile to be replaced in access policy using `alternate_profile_name`. The syntax and supported attributes are as follows:

<b>Synopsis</b>	DELETE /wsa/api/v3.0/web_security/http_rewrite_profiles?alternate_profile_name=None&profile_name=RHR	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the request header rewrite profile.

### Sample Request

```
DELETE
/wsa/api/v3.0/web_security/http_rewrite_profiles?alternate_profile_name=None&profile_name=RHR

HTTP/1.1
Host: wsa.example.com:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

### Sample Response

```
HTTP/1.1 204 No Content
Date: Wed, 17 Mar 2021 11:38:22 GMT
Connection: keep-alive
Access-Control-Allow-Origin: *
Access-Control-Allow-Headers: content-type, jwttoken, mid, h, email
Access-Control-Allow-Credentials: true
```

## Smart Software Licenses

This section contains the following topics:

- [Retrieving the Smart Software Licenses, on page 96](#)
- [Modifying the Smart Software Licenses, on page 98](#)
- [Retrieve the Smart License Agent Status, on page 100](#)
- [Modifying the Smart License Agent Status, on page 101](#)
- [Retrieving the Smart Software Licenses Status, on page 102](#)
- [Modifying the Smart Software Licenses Status, on page 102](#)

## Retrieving the Smart Software Licenses

You can retrieve the list of license details with license name and authentication status.

The grace period is returned if the authentication status of any of the licenses is "Out Of Compliance."

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/sl_licenses	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the list of license details with license name and authentication status.

#### Sample Request 1

```
GET wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```



**Sample Response 1**

```
[
  {
    "license_name": "Secure Web Appliance Cisco Web Usage Controls",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance Anti-Virus Webroot",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance L4 Traffic Monitor",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance Cisco AnyConnect SM for AnyConnect",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance Malware Analytics Reputation",
    "auth_status": "Not requested"
  },
  {
    "license_name": "Secure Web Appliance Anti-Virus Sophos",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance Web Reputation Filters",
    "auth_status": "Not requested"
  },
  {
    "license_name": "Secure Web Appliance Malware Analytics",
    "auth_status": "Not requested"
  },
  {
    "license_name": "Secure Web Appliance Anti-Virus McAfee",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance Web Proxy and DVS Engine",
    "auth_status": "In Compliance"
  },
  {
    "license_name": "Secure Web Appliance HTTPs Decryption",
    "auth_status": "In Compliance"
  }
]
```

**Sample Response 2**

```
[
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Cisco Web Usage Controls",
    "auth_status": "In Compliance"
  },
  {
    "grace_period": "Expired",
    "license_name": "Secure Web Appliance Anti-Virus Webroot",
    "auth_status": "Out Of Compliance"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance L4 Traffic Monitor",
  }
]
```

```

    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Cisco AnyConnect SM for AnyConnect",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Malware Analytics Reputation",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Anti-Virus Sophos",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Web Reputation Filters",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Malware Analytics",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Anti-Virus McAfee",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance Web Proxy and DVS Engine",
    "auth_status": "Not requested"
  },
  {
    "grace_period": "N/A",
    "license_name": "Secure Web Appliance HTTPs Decryption",
    "auth_status": "Not requested"
  }
]

```

## Modifying the Smart Software Licenses

You can modify the list of license details with the license name and authentication status.

The grace period is returned if the authentication status of any of the licenses is "Out Of Compliance."

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/sl_licenses	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Example

This example shows how to modify the list of license details with license name and authentication status.

### Sample Request 1

```
PUT /wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

```
Body:
{
  "request": ["Secure Web Appliance L4 Traffic Monitor", "Secure Web Appliance Malware Analytics"]
  "release": ["Secure Web Appliance Cisco AnyConnect SM for AnyConnect", "Secure Web Appliance HTTPs Decryption"]
}
```

Sample Response 1: 202 Accepted

```
{
  "message": "The request or release for the licenses is in progress."
}
```

### Sample Request 2

```
PUT /wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

```
Body:
{
  "request": [],
  "release": ["Secure Web Appliance Malware Analytics", "Secure Web Appliance Malware Analytics"]
}
```

Sample Response 2: 400

```
{
  "error": {
    "message": "Invalid request: License name 'Secure Web Appliance Malware Analytics' is repeated in ['release'].",
    "code": "400",
    "explanation": "400 = Bad request syntax or unsupported method."
  }
}
```

### Sample Request 3

```
PUT /wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

```
Body:
{
  "request": ["Secure Web Appliance Malware Analytics"],
  "release": ["Secure Web Appliance Malware Analytics"]
}
```

Sample Response 3: 400

```
{
  "error": {
    "message": "Invalid request: License name 'Secure Web Appliance Malware Analytics' is found in both ['release'] and ['request'].",
    "code": "400",
    "explanation": "400 = Bad request syntax or unsupported method."
  }
}
```

```
    }
  }
```

#### Sample Request 4

```
PUT /wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

Body:

```
{
  "request": ["Secure Web Appliance L4 Traffic Monitor", "Secure Web Appliance Malware
Analytics"]
  "release": ["invalid name"]
}
```

Sample Response 4: 400

```
{
  "error": {
    "message": "Invalid request[release][0]. 'invalid name' should be one of these:
['Secure Web Appliance Web Reputation Filters', 'Secure Web Appliance Malware Analytics
Reputation', 'Secure Web Appliance Anti-Virus McAfee', 'Secure Web Appliance Web Proxy and
DVS Engine', 'Secure Web Appliance Cisco Web Usage Controls', 'Secure Web Appliance
Anti-Virus Webroot', 'Secure Web Appliance L4 Traffic Monitor', 'Secure Web Appliance Cisco
AnyConnect SM for AnyConnect', 'Secure Web Appliance Anti-Virus Sophos', 'Secure Web
Appliance Malware Analytics', 'Secure Web Appliance HTTPs Decryption'].",
    "code": "400",
    "explanation": "400 = Bad request syntax or unsupported method."
  }
}
```

#### Sample Request 5

```
PUT /wsa/api/v3.0/system_admin/sl_licenses
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk
```

Body:

```
{
  "request": ["Secure Web Appliance L4 Traffic Monitor", "Secure Web Appliance Malware
Analytics"]
  "release": ["Secure Web Appliance Web Reputation Filters"]
}
```

Sample Response 5: 400

```
{
  "error": {
    "message": "Cannot release license 'Secure Web Appliance Web Reputation Filters'
as the current authorization status of the license is 'Not requested'.",
    "code": "400",
    "explanation": "400 = Bad request syntax or unsupported method."
  }
}
```

## Retrieve the Smart License Agent Status

You can retrieve the details of Cisco Smart Software License configuration such as enable or disable status, registration status, and so on.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/smart_agent_status
-----------------	--

<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the details of Cisco Smart Software License configurations such as enable or disable status, registration status, and so on.

### Sample Request

```
GET wsa/api/v3.0/system_admin/smart_agent_status HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTlz
```

### Sample Response

```
{
  "file_type": "Smart License Agent",
  "version": "3.1.4",
  "new_update": "Failed to fetch manifest",
  "last_update": "Never updated"
}
```

## Modifying the Smart License Agent Status

You can modify the details of Cisco Smart Software License configurations such as enable or disable status, registration status, and so on.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/smart_agent_status	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the details of Cisco Smart Software License configurations such as enable or disable status, registration status, and so on.

### Sample Request

```
PUT /wsa/api/v3.0/system_admin/smart_agent_status HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTlz
```

Content-Type: application/json  
Content-Length: 202

## Retrieving the Smart Software Licenses Status

You can retrieve the list of details of Cisco Smart Software License configurations such as enable or disable status, registration status and so on.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/smart_software_licensing_status HTTP/1.1	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the list of details of Cisco Smart Software License configuration such as enable or disable status, registration status and so on.

### Sample Request

```
GET /wsa/api/v3.0/system_admin/smart_software_licensing_status HTTP/1.1
Host: wsa353.csl:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
{
  "smart_account_name": "InternalTestDemoAccount9.cisco.com",
  "virtual_account_name": "WSA2",
  "registration_last_renew": "SUCCEEDED on 29 Sep 2021 06:08",
  "last_auth_renewal_attempt_status": "SUCCEEDED on 29 Sep 2021 06:08",
  "transport_url": "https://smartreceiver.cisco.com/licservice/license",
  "transport_mode": "direct",
  "test_interface": "Management",
  "eval_period": "Not In Use",
  "eval_period_remaining": "90 days",
  "smart_lic_status": "AUTHORIZED",
  "authorization_status": "Authorized ( 29 Sep 2021 06:08 ) Authorization Expires on: (
28 Dec 2021 06:04 )",
  "product_instance_name": "wsa353.csl",
  "registration_status": "Registered ( 29 Sep 2021 06:08 ) Registration Expires on: (
29 Sep 2022 06:04 )"
}
```

## Modifying the Smart Software Licenses Status

You can modify the list of details of Cisco Smart Software License configurations such as enable or disable status, registration status, and so on.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/smart_software_licensing_status
-----------------	---



## System Setup Wizard

This section contains the following topics:

- [Retrieving the End User License Agreement Details, on page 104](#)
- [Modifying the System Setup Wizard Settings, on page 106](#)

### Retrieving the End User License Agreement Details

You can retrieve the end user license agreement details.



**Note** You must go through the EULA agreement before performing the PUT request to setup the system setup wizard.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/cisco_end_user_license_agreement	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

#### Example

This example shows how to retrieve the end user license agreement details.

##### Sample Request 1

```
PUT /wsa/api/v3.0/system_admin/system_setup_wizard
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2l2Y28xMjMk
```

```
{
  "cisco_license_agreement": "accept",
  "appliance_mode": "standard",
  "system_settings": {
    "hostname": "dut058.perf8",
    "dns_servers": {
      "dns_choice": "self",
      "user_dns": [
        "192.168.0.252"
      ]
    },
    "ntp_server": {
      "query_interval_time": 23434,
      "sync_up_delay_ms": 500,
      "server_name": "time.sco.cisco.com",
      "server_auth": {
        "status": "enable",
        "key_id": 123,
      }
    }
  }
}
```



```

        "key_val": "MTIzNA==",
        "key_type": "sha1"
    },
    "timezone": {
        "region": "Europe"
    }
},
"network_context": {
    "other_proxy": "no"
},
"network_interface": {
    "m1": {
        "management_only": "no",
        "ipv4_address_netmask": "10.10.194.68/24",
        "hostname": "dut058.perf8"
    }
},
"network_l4tm": {
    "wiring_type": "duplex"
},
"network_routes": {
    "management": {
        "default_gateway": "10.10.194.1"
    }
},
"transparent_connection": {
    "redirection_device": "wccp_v2_router",
    "wccp_v2_router": {
        "standard_service_id": {
            "status": "disable"
        }
    }
},
"network_admin": {
    "passphrase": "Q21zY28xMjMk",
    "mail_to_addrs": ["sandhgan@cisco.com"],
    "autosupport": "enable",
    "network_participation": {
        "status": "enable",
        "participation_level": "standard"
    }
},
"network_security": {
    "global_policy_default_action": "monitor",
    "l4_traffic_monitor": "monitor",
    "cisco_data_security_filtering": "enable"
}
}

```

### Sample Response 1

204 No-content

### Sample Request 2

```

PUT /wsa/api/v3.0/system_admin/config_backup_server
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk

```

```

{
    "network_admin": {
        "passphrase": "Q21zY28xMjMk",
        "mail_to_addrs": "sandhgan@cisco.com",

```

```
    }
  }
```

### Sample Response 2

```
204 No-content
```

## Modifying the System Setup Wizard Settings

You can modify the objects with system setup wizard settings.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/system_setup_wizard	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the objects with system setup wizard settings.

### Sample Request 1

```
PUT /wsa/api/v3.0/system_admin/system_setup_wizard
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

```
{
  "cisco_license_agreement": "accept",
  "appliance_mode": "standard",
  "system_settings": {
    "hostname": "dut058.perf8",
    "dns_servers": {
      "dns_choice": "self",
      "user_dns": [
        "192.168.0.252"
      ]
    },
  },
  "ntp_server": {
    "query_interval_time": 23434,
    "sync_up_delay_ms": 500,
    "server_name": "time.sco.cisco.com",
    "server_auth": {
      "status": "enable",
      "key_id": 123,
      "key_val": "MTIzNA==",
      "key_type": "sha1"
    }
  },
  "timezone": {
    "region": "Europe"
  }
},
"network_context": {
  "other_proxy": "no"
}
```

```

    },
    "network_interface": {
      "m1": {
        "management_only": "no",
        "ipv4_address_netmask": "10.10.194.68/24",
        "hostname": "dut058.perf8"
      }
    },
    "network_l4tm": {
      "wiring_type": "duplex"
    },
    "network_routes": {
      "management": {
        "default_gateway": "10.10.194.1"
      }
    },
    "transparent_connection": {
      "redirection_device": "wccp_v2_router",
      "wccp_v2_router": {
        "standard_service_id": {
          "status": "disable"
        }
      }
    },
    "network_admin": {
      "passphrase": "Q21zY28xMjMk",
      "mail_to_addrs": ["sandhgan@cisco.com"],
      "autosupport": "enable",
      "network_participation": {
        "status": "enable",
        "participation_level": "standard"
      }
    },
    "network_security": {
      "global_policy_default_action": "monitor",
      "l4_traffic_monitor": "monitor",
      "cisco_data_security_filtering": "enable"
    }
  }
}

```

**Sample Response 1**

204 No-content

**Sample Request 2**

```

PUT /wsa/api/v3.0/system_admin/config_backup_server
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk

```

```

{
  "network_admin": {
    "passphrase": "Q21zY28xMjMk",
    "mail_to_addrs": "sandhgan@cisco.com",
  }
}

```

**Sample Response 2**

204 No-content

## Decryption Policy

This section contains the following topics:

- [Retrieving the Decryption Policy, on page 108](#)
- [Modifying the Decryption Policy, on page 110](#)
- [Adding the Decryption Policy, on page 111](#)
- [Deleting the Decryption Policy, on page 114](#)

## Retrieving the Decryption Policy

You can retrieve the decryption policies available and their configuration.

<b>Synopsis</b>	GET wsa/api/v3.0/web_security/decryption_policies	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the decryption policies available and their configuration.

### Sample Request

```
GET /wsa/api/v3.0/web_security/decryption_policies?policy_names=DP1 HTTP/1.1
Host: dut058.perf8:6443
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
{
  "decryption_policies": [
    {
      "policy_status": "enable",
      "policy_name": "DP1",
      "policy_description": "",
      "policy_order": 2,
      "policy_expiry": "",
      "membership": {
        "identification_profiles": [
          {
            "global_identification_profile": {
              "auth": "No Authentication"
            }
          }
        ]
      },
      "url_filtering": {
        "custom_cats": {
          "use_global": [
            "GM Global External No Auth Custom URL",
            "Block Netflix",
            "Secure Admin Workstation Allow List",
            "GM Global External Office 365 No Auth",
          ]
        }
      }
    }
  ]
}
```

```
        "MFG Allow Custom URL",
        "Internet DENY Allow List",
        "Mobile Link GME Ogrinal Custom URL",
        "ESRS Server No Auth GME Original Custom URL",
        "CiscoEURservers No Auth GME Oiginal Custom URL"
    ]
},
"predefined_cats": {
    "use_global": [
        "Adult",
        "Advertisements",
        "Alcohol",
        "Arts",
        "Astrology",
        "Auctions",
        "Business and Industry",
        "Chat and Instant Messaging",
        "Cheating and Plagiarism",
        "Child Abuse Content",
        "Computer Security",
        "Computers and Internet",
        "DIY Projects",
        "Dating",
        "Digital Postcards",
        "Dining and Drinking",
        "Dynamic and Residential",
        "Education",
        "Entertainment",
        "Extreme",
        "Fashion",
        "File Transfer Services",
        "Filter Avoidance",
        "Finance",
        "Freeware and Shareware",
        "Gambling",
        "Games",
        "Government and Law",
        "Hacking",
        "Hate Speech",
        "Health and Nutrition",
        "Humor",
        "Hunting",
        "Illegal Activities",
        "Illegal Downloads",
        "Illegal Drugs",
        "Infrastructure and Content Delivery Networks",
        "Internet Telephony",
        "Job Search",
        "Lingerie and Swimsuits",
        "Lotteries",
        "Military",
        "Mobile Phones",
        "Nature",
        "News",
        "Non-governmental Organizations",
        "Non-sexual Nudity",
        "Online Communities",
        "Online Meetings",
        "Online Storage and Backup",
        "Online Trading",
        "Organizational Email",
        "Paranormal",
        "Parked Domains",
        "Peer File Transfer",
    ]
}
```

```

        "Personal Sites",
        "Personal VPN",
        "Photo Search and Images",
        "Politics",
        "Pornography",
        "Professional Networking",
        "Real Estate",
        "Reference",
        "Religion",
        "SaaS and B2B",
        "Safe for Kids",
        "Science and Technology",
        "Search Engines and Portals",
        "Sex Education",
        "Shopping",
        "Social Networking",
        "Social Science",
        "Society and Culture",
        "Software Updates",
        "Sports and Recreation",
        "Streaming Audio",
        "Streaming Video",
        "Tobacco",
        "Transportation",
        "Travel",
        "Weapons",
        "Web Hosting",
        "Web Page Translation",
        "Web-based Email"
    ]
  },
  "state": "custom",
  "update_cats_action": "use_global",
  "uncategorized_url": "use_global"
},
"web_reputation": {
  "state": "custom",
  "score": {
    "drop": [
      "-10.0",
      "10.0"
    ],
    "decrypt": [],
    "pass_through": []
  },
  "wbrs_no_score_action": "monitor"
},
"default_action": "use_global"
}
]
}

```

## Modifying the Decryption Policy

You can modify the decryption policies available and their configuration.

<b>Synopsis</b>	PUT wsa/api/v3.0/web_security/decryption_policies
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.

<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the decryption policies available and their configuration.

#### Sample Request

```
PUT /wsa/api/v3.0/web_security/decryption_policies HTTP/1.1
Host: dut058.perf8:6443
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTlz
Content-Type: application/json
Content-Length: 1151
```

```
{
  "decryption_policies": [
    {
      "policy_status": "enable",
      "policy_name": "DP1",
      "policy_description": "",
      "policy_order": 1,
      "policy_expiry": "12/2/2024 22:00",
      "membership": {
        "identification_profiles": [
          {
            "profile_name": "AllowISEIdentity",
            "auth": "No Authentication"
          }
        ]
      },
      "web_reputation": {
        "state": "custom",
        "score": {
          "drop": [
            "-10.0",
            "5.0"
          ],
          "pass_through": [
            "7.0",
            "10.0"
          ]
        },
        "wbrs_no_score_action": "drop"
      },
      "default_action": "pass_through"
    }
  ]
}
```

#### Sample Response

```
204 (No-content)
```

## Adding the Decryption Policy

You can add the decryption policies available and their configuration.

<b>Synopsis</b>	POST wsa/api/v3.0/web_security/decryption_policies	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add the decryption policies available and their configuration.

### Sample Request

```
POST /wsa/api/v3.0/configure/web_security/decryption_policies HTTP/1.1
Host: dut058.perf8:6443
Authorization: Basic YWRtaW46aXJvbnBvcnQ=
Content-Type: text/plain
Content-Length: 1518
```

```
{
  "decryption_policies": [
    {
      "policy_status": "enable",
      "policy_name": "DP1",
      "policy_description": "",
      "policy_order": 1,
      "policy_expiry": "12/2/2024 22:00",
      "membership": {
        "identification_profiles": [
          {
            "profile_name": "AllowISEIdentity",
            "auth": "No Authentication"
          }
        ]
      }
    },
    "url_filtering": {
      "custom_cats": {
        "use_global": [
          "GM Global External No Auth Custom URL",
          "Block Netflix",
          "Secure Admin Workstation Allow List",
          "GM Global External Office 365 No Auth",
          "MFG Allow Custom URL",
          "Internet DENY Allow List",
          "Mobile Link GME Ogrinal Custom URL",
          "ESRS Server No Auth GME Orginal Custom URL",
          "CiscoEURservers No Auth GME Oiginal Custom URL"
        ]
      }
    },
    "predefined_cats": {
      "use_global": [
        "Adult",
        "Advertisements",
        "Alcohol",
        "Arts",
        "Astrology",

```



"Auctions",  
"Business and Industry",  
"Chat and Instant Messaging",  
"Cheating and Plagiarism",  
"Child Abuse Content",  
"Computer Security",  
"Computers and Internet",  
"DIY Projects",  
"Dating",  
"Digital Postcards",  
"Dining and Drinking",  
"Dynamic and Residential",  
"Education",  
"Entertainment",  
"Extreme",  
"Fashion",  
"File Transfer Services",  
"Filter Avoidance",  
"Finance",  
"Freeware and Shareware",  
"Gambling",  
"Games",  
"Government and Law",  
"Hacking",  
"Hate Speech",  
"Health and Nutrition",  
"Humor",  
"Hunting",  
"Illegal Activities",  
"Illegal Downloads",  
"Illegal Drugs",  
"Infrastructure and Content Delivery Networks",  
"Internet Telephony",  
"Job Search",  
"Lingerie and Swimsuits",  
"Lotteries",  
"Military",  
"Mobile Phones",  
"Nature",  
"News",  
"Non-governmental Organizations",  
"Non-sexual Nudity",  
"Online Communities",  
"Online Meetings",  
"Online Storage and Backup",  
"Online Trading",  
"Organizational Email",  
"Paranormal",  
"Parked Domains",  
"Peer File Transfer",  
"Personal Sites",  
"Personal VPN",  
"Photo Search and Images",  
"Politics",  
"Pornography",  
"Professional Networking",  
"Real Estate",  
"Reference",  
"Religion",  
"SaaS and B2B",  
"Safe for Kids",  
"Science and Technology",  
"Search Engines and Portals",  
"Sex Education",

```

        "Shopping",
        "Social Networking",
        "Social Science",
        "Society and Culture",
        "Software Updates",
        "Sports and Recreation",
        "Streaming Audio",
        "Streaming Video",
        "Tobacco",
        "Transportation",
        "Travel",
        "Weapons",
        "Web Hosting",
        "Web Page Translation",
        "Web-based Email"
    ]
  },
  "state": "custom",
  "update_cats_action": "use_global",
  "uncategorized_url": "use_global"
},
"web_reputation": {
  "state": "custom",
  "score": {
    "drop": [
      "-10.0",
      "10.0"
    ],
    "decrypt": [],
    "pass_through": []
  },
  "wbrs_no_score_action": "monitor"
},
"default_action": "use_global"
}
]
}

```

**Sample Response**

204 (No-content)

**Deleting the Decryption Policy**

You can delete available decryption policies and their configurations..

<b>Synopsis</b>	DELETE wsa/api/v3.0/web_security/decryption_policies	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to delete available decryption policies and their configurations.

### Sample Request

```
DELETE /wsa/api/v3.0/web_security/decryption_policies?policy_names=DP1,DP2,DP3 HTTP/1.1
Host: dut058.perf8:6443
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
{
  "success_list": [
    {
      "status": 200,
      "message": "success",
      "policy_name": "DP1"
    },
    {
      "status": 200,
      "message": "success",
      "policy_name": "DP2"
    }
  ],
  "failure_list": [
    {
      "status": 404,
      "message": "policy name does not exist.",
      "policy_name": "DP3"
    }
  ],
  "success_count": 2,
  "failure_count": 1
}
```

## Routing Policy

This section contains the following topics:

- [Retrieving a Routing Policy, on page 115](#)
- [Modifying a Routing Policy, on page 116](#)
- [Adding a Routing Policy, on page 117](#)
- [Deleting a Routing Policy, on page 118](#)

### Retrieving a Routing Policy

You can retrieve the list of routing policies with the matching policy names to be returned.

<b>Synopsis</b>	GET wsa/api/v3.0/web_security/routing_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Example

This example shows how to retrieve the list of routing policies with the matching policy names to be returned.

### Sample Request

```
GET /wsa/api/v3.0/web_security/routing_policies?policy_names=RP1 HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW5DaXNjbzEyMyQ=
```

### Sample Response

```
{
  "routing_policies": [
    {
      "policy_description": "test protocol policy",
      "ip_spoofing": "Do not use IP Spoofing",
      "policy_order": 1,
      "policy_status": "enable",
      "policy_name": "RP1",
      "membership": {
        "identification_profiles": [
          {
            "global_identification_profile": {
              "auth": "No Authentication"
            }
          }
        ]
      },
      "routing_destination": {
        "upstream_proxy_group": "use_global"
      }
    }
  ]
}
```

## Modifying a Routing Policy

You can modify the list of routing policies and their configuration payload.

<b>Synopsis</b>	PUT wsa/api/v3.0/web_security/routing_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Example

This example shows how to modify the list of routing policies and their configuration payload.

### Sample Request

```
PUT /wsa/api/v3.0/web_security/routing_policies HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW5DaXNjbzEyMyQ=
Content-Type: application/json
```

```

Content-Length: 621

{
  "routing_policies": [
    {
      "policy_status": "enable",
      "policy_name": "RP2",
      "policy_description": "test protcol policy",
      "policy_order": 1,
      "membership": {
        "identification_profiles": [
          {
            "profile_name": "ID1",
            "auth": "No Authentication"
          }
        ]
      },
      "ip_spoofing": "IP1",
      "routing_destination": {
        "upstream_proxy_group": "UPProxy1"
      }
    }
  ]
}

```

### Sample Response

204 (No-content)

## Adding a Routing Policy

You can add the list of routing policies and their configuration payload.

<b>Synopsis</b>	POST wsa/api/v3.0/web_security/routing_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to add the list of routing policies and their configuration payload.

### Sample Request

```

POST /wsa/api/v3.0/web_security/routing_policies HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW5DaXNjbzEyMyQ=
Content-Type: application/json
Content-Length: 561

```

```

{
  "routing_policies": [
    {
      "policy_status": "enable",

```

```

    "policy_name": "RP1",
    "policy_description": "test protocol policy",
    "policy_order": 1,
    "membership": {
      "identification_profiles": [
        {
          "profile_name": "global_identification_profile",
          "auth": "No Authentication"
        }
      ]
    },
    "ip_spoofing": "Do not use IP Spoofing"
  }
]
}

```

### Sample Response

204 (No-content)

## Deleting a Routing Policy

You can delete the list of routing policies with the matching policy names to be deleted.

<b>Synopsis</b>	DELETE wsa/api/v3.0/web_security/routing_policies	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to delete the list of routing policies with the matching policy names to be deleted.

### Sample Request

```

DELETE /wsa/api/v3.0/web_security/routing_policies?policy_names=RP1 HTTP/1.1
Host: dut058.perf8:6443
Authorization: Basic YWRtaW5DaXNjbzEyMyQ=

```

### Sample Response

```

{
  "success_list": [
    {
      "status": 200,
      "message": "success",
      "policy_name": "RP1"
    }
  ],
  "failure_list": [
    {
      "status": 404,
      "message": "policy name does not exist.",
      "policy_name": "RP2"
    }
  ]
}

```

```

    ],
    "success_count": 1,
    "failure_count": 1
  }

```

## IP Spoofing Profile

This section contains the following topics:

- [Retrieving the IP Spoofing Profile, on page 119](#)
- [Modifying the IP Spoofing Profile, on page 120](#)
- [Adding the IP Spoofing Profile, on page 120](#)
- [Deleting the IP Spoofing Profile, on page 121](#)

## Retrieving the IP Spoofing Profile

You can retrieve the list of IP spoofing profiles and their configuration payload.

<b>Synopsis</b>	GET wsa/api/v3.0/web_security/ip_spoofing_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the list of IP spoofing profiles and their configuration payload.

### Sample Request

```

GET /wsa/api/v3.0/web_security/ip_spoofing_profiles?profile_names=spooof2,spooof3
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk

```

### Sample Response

```

{
  "ip_spoofing_profiles": [
    {
      "profile_name": "spooof3",
      "ip_address": "1.1.1.1"
    },
    {
      "profile_name": "spooof2",
      "ip_address": "2001:420:80:1::15"
    }
  ]
}

```

## Modifying the IP Spoofing Profile

You can modify the list of IP spoofing profiles and their configuration payload.

<b>Synopsis</b>	PUT wsa/api/v3.0/web_security/ip_spoofing_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the list of IP spoofing profiles and their configuration payload.

### Sample Request

```
PUT /wsa/api/v3.0/web_security/ip_spoofing_profiles
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzY28xMjMk

{
  "ip_spoofing_profiles": [
    {
      "profile_name": "spooof1"
    },
    {
      "profile_name": "spooof2",
      "new_profile_name": "newspooof2"
    },
    {
      "profile_name": "spooof3",
      "new_profile_name": "newspooof3",
      "ip_address": "2001:420:80:1::15"
    }
  ]
}
```

### Sample Response

```
204 (No-content)
```

## Adding the IP Spoofing Profile

You can add the list of IP spoofing profiles and their configuration payload.

<b>Synopsis</b>	POST wsa/api/v3.0/web_security/ip_spoofing_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	



<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to add the list of IP spoofing profiles and their configuration payload.

**Sample Request**

```
POST /wsa/api/v3.0/web_security/ip_spoofing_profiles
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk
```

```
{
  "ip_spoofing_profiles": [
    {
      "profile_name": "spoo1",
      "ip_address": "1.1.1.1"
    },
    {
      "profile_name": "spoo2",
      "ip_address": "2001:420:80:1::15"
    }
  ]
}
```

**Sample Response**

```
204 (No-content)
```

## Deleting the IP Spoofing Profile

You can delete the list of IP spoofing profiles and their configuration payload.

<b>Synopsis</b>	DELETE wsa/api/v3.0/web_security/ip_spoofing_profiles	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to delete the list of IP spoofing profiles and their configuration payload.

**Sample Request**

```
GET /wsa/api/v3.0/web_security/ip_spoofing_profiles
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk
```

### Sample Response

```
{
  "success_list": [
    {
      "status": 200,
      "message": "success",
      "profile_name": "spooof4"
    }
  ],
  "failure_list": [
    {
      "status": 404,
      "message": "profile_name 'spooof5' doesn't exist",
      "profile_name": "spooof5"
    }
  ],
  "success_count": 1,
  "failure_count": 1
}
```

## Configuration Files

This section contains the following topics:

- [Retrieving the Configuration Files, on page 122](#)
- [Modifying the Configuration Files, on page 123](#)
- [Retrieving the Configuration Files—Backup Settings, on page 124](#)
- [Modifying the Configuration Files—Backup Settings, on page 125](#)
- [Modifying the Configuration Files—Reset, on page 126](#)

### Retrieving the Configuration Files

You can download, save, or load a configuration file on a Secure Web Appliance.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/configuration_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

#### Example

This example shows how to download, save, or load a configuration file on a Secure Web Appliance.

#### Sample Request

```
curl --location --request GET
'https://wsa308.cs1:4431/wsa/api/v3.0/system_admin/configuration_file?mail_to=xyz123@cisco.com'
--header 'Authorization: Basic YWRtaW46Q2lzMzY29AMTIz'
```

Sample Response:

```
{
  "message": "config sent to these mails: ['xyz123@cisco.com']"
}
```

## Modifying the Configuration Files

You can download, save, or load a configuration file on a Secure Web Appliance.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/configuration_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to download, save, or load a configuration file on a Secure Web Appliance.

### Sample Request

```
curl --location --request PUT
'https://wsa308.cs1:4431/wsa/api/v3.0/system_admin/configuration_file' --header
'Authorization: Basic YWRtaW46Q2lzMzY29AMTIz' --form 'action="save"'
```

### Sample Response

```
{
  "message": "Saved Successfully."
}
```

## Viewing the Appliance Configuration Files

You can view the available configuration files saved on the Secure Web Appliance.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/appliance_config_files	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to view the available configuration files saved on the Secure Web Appliance.

### Sample Request

```
curl --location --request GET
'https://wsa308.cs1:4431/wsa/api/v3.0/system_admin/appliance_config_files' --header
'Authorization: Basic YWRtaW46Q2lzY29AMTlz'
```

### Sample Response

```
{
  "appliance_config_files": [
    "EUN_DEFAULT.tar.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210623T062911-14.5.0-253.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210623T114735-14.5.0-253.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210623T114850-14.5.0-253.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T051947-14.5.0-253.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T052026-14.5.0-253.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T052309-14.5.0-253.xml",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T064846-14.5.0-275.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T091022-14.5.0-275.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T091225-14.5.0-275.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T091249-14.5.0-275.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T091451-14.5.0-275.xml.audit_bkp.gz",
    "S600V-4229463E3D1973742FFF-274CC33B68AB-20210624T091603-14.5.0-275.xml.audit_bkp",
    "config.dtd"
  ]
}
```

## Retrieving the Configuration Files—Backup Settings

You can retrieve the current settings of the configuration backup server.

<b>Synopsis</b>	GET wsa/api/v3.0/system_admin/config_backup_server	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to retrieve the current settings of the configuration backup server.

**Sample Request 1**

```
GET /wsa/api/v3.0/system_admin/config_backup_server
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

**Sample Response 1**

```
{
  "config_backup_status": "disable"
}
```

**Sample Request 2**

```
GET /wsa/api/v3.0/system_admin/config_backup_server
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q2lzMjY28xMjMk
```

**Sample Response 2**

```
{
  "config_backup_settings": {
    "save_passphrase": false,
    "retrieval_method": "ftp_push",
    "ftp_settings": {
      "directory": "/data/db",
      "username": "sandhgan",
      "ftp_host": "dut058.perf8"
    }
  }
}
```

**Modifying the Configuration Files—Backup Settings**

You can modify the current settings of the configuration backup server.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/config_backup_server	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to modify the current settings of the configuration backup server.

**Sample Request 1**

```
PUT /wsa/api/v3.0/system_admin/config_backup_server
Host: dut058.perf8:4431
```





**Caution** Resetting your configuration reverts your appliance to factory default settings, including the IP address. It is strongly recommended that the configuration is saved before performing these actions.

<b>Synopsis</b>	PUT wsa/api/v3.0/system_admin/configuration_file	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to reset the configuration of the box to factory settings.

### Sample Request

```
curl --location --request PUT
'http://wsa301.cs1:6080/wsa/api/v3.0/system_admin/configuration_file' \
--header 'Authorization: Basic YWRtaW46aXJvbnBvcnQ=' \
--form 'action="reset"' \
--form 'reset_network_settings="True"'
```

### Sample Response

```
{
  "message": "All settings have been restored to the factory defaults."
}
```

## Authentication Realms

This section contains the following topics:

- [Retrieving the Authentication Realm Settings, on page 128](#)
- [Adding the Authentication Realm Settings, on page 128](#)
- [Retrieving the Global Authentication Settings, on page 132](#)
- [Modifying the Global Authentication Settings, on page 133](#)
- [Adding the Authentication Realm Sequence Settings, on page 131](#)
- [Modifying the Authentication Realm Sequence Settings, on page 130](#)
- [Retrieving the Authentication Realm Sequence Settings, on page 129](#)

## Retrieving the Authentication Realm Settings

You can view and retrieve the authentication realm settings.

<b>Synopsis</b>	GET wsa/api/v3.0/network/auth_realms	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to view and retrieve the authentication realm settings.

### Sample Request

```
curl --location --request GET
'https://wsa308.cs1:6443/wsa/api/v3.0/network/auth_realms?realm_names=ad1' --header
'Authorization: Basic YWRtaW46Q2lzY29AMTIz'
```

### Sample Response

```
{
  "auth_realms": [
    {
      "ad_account": {
        "domain_joined": false,
        "trusted_domain_lookup_enabled": true,
        "computer_account": "Computers",
        "ad_domain": "ABCD2121.COM"
      },
      "ad_server": {
        "interface": "Management",
        "servers": [
          {
            "host": "xyz234.com"
          }
        ]
      },
      "scheme": [
        "Negotiate",
        "NTLMSSP",
        "Basic"
      ],
      "type": "AD",
      "name": "ad1"
    }
  ]
}
```

## Adding the Authentication Realm Settings

You can view and add the authentication realm settings.



<b>Synopsis</b>	POST wsa/api/v3.0/network/auth_sequences	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to view and add the authentication realm settings.

**Sample Request**

```
curl --location --request POST 'https://wsa308.cs1:6443/wsa/api/v3.0/network/auth_sequences'
--header 'Authorization: Basic YWRtaW46aXJvbnBvcnQ=' --header 'Content-Type:
application/json' --data-raw '{
  "auth_sequences": [
    {
      "schemes": {
        "Kerberos": [
          "myADRealm"
        ],
        "Basic": [
          "myRealm",
          "myADRealm"
        ]
      },
      "name": "myAuthSequence2"
    }
  ]
}'
```

**Sample Response**

```
204 No-content
```

**Retrieving the Authentication Realm Sequence Settings**

You can view and change authentication realm sequence settings.

<b>Synopsis</b>	GET wsa/api/v3.0/network/auth_sequences	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

## Example

This example shows how to view and change authentication realm sequence settings.

## Sample Request

```
curl --location --request GET 'https://wsa308.cs1:4431/wsa/api/v3.0/network/auth_sequences'
--header 'Authorization: Basic YWRtaW46aXJvbnBvcnQ='
```

## Sample Response

```
{
  "auth_sequences": [
    {
      "schemes": {
        "Kerberos": [
          "myADRealm"
        ],
        "NTLMSSP": [
          "myADRealm"
        ],
        "Basic": [
          "myRealm",
          "myADRealm",
          "myBasicRealm"
        ]
      },
      "name": "All Realms"
    },
    {
      "schemes": {
        "Kerberos": [
          "myADRealm"
        ],
        "Basic": [
          "myRealm",
          "myADRealm"
        ]
      },
      "name": "myAuthSequence"
    }
  ]
}
```

## Modifying the Authentication Realm Sequence Settings

You can view and modify the authentication realm sequence settings.

<b>Synopsis</b>	PUT wsa/api/v3.0/network/auth_sequences	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the authentication sequence settings.

#### Sample Request

```
curl --location --request PUT 'https://wsa308.cs1:6443/wsa/api/v3.0/network/auth_sequences'
--header 'Authorization: Basic YWRtaW46aXJvbnBvcnQ=' --header 'Content-Type:
application/json' --data-raw '{
  "auth_sequences": [
    {
      "schemes": {
        "Basic": [
          "myRealm",
          "myADRealm",
          "myBasicRealm"
        ]
      },
      "name": "myAuthSequence2"
    }
  ]
}'
```

#### Sample Response

204 No-content

## Adding the Authentication Realm Sequence Settings

You can view and add the authentication realm sequence settings.

<b>Synopsis</b>	POST wsa/api/v3.0/network/auth_sequences	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to view and add the authentication realm sequence settings.

#### Sample Request

```
curl --location --request POST 'https://wsa308.cs1:6443/wsa/api/v3.0/network/auth_sequences'
--header 'Authorization: Basic YWRtaW46aXJvbnBvcnQ=' --header 'Content-Type:
application/json' --data-raw '{
  "auth_sequences": [
    {
      "schemes": {
        "Kerberos": [
          "myADRealm"
        ],
        "Basic": [
          "myRealm",
          "myADRealm"
        ]
      }
    }
  ]
}'
```

```

    },
    "name": "myAuthSequence2"
  }
]
}'

```

**Sample Response**

204 No-content

**Retrieving the Global Authentication Settings**

You can retrieve the details of global authentication settings available and configurations such as Authentication Token TTL, Credential Encryption, Header Based Authentication, and so on.

<b>Synopsis</b>	GET wsa/api/v3.0/network/global_auth_setting
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.
<b>Request Headers</b>	Host, Accept, Authorization
<b>Response Headers</b>	Content-Type, Content-Length, Connection

**Example**

This example shows how to retrieve the global authentication settings.

**Sample Request**

```

GET /wsa/api/v3.0/network/global_auth_setting HTTP/1.1
Host: wsa353.csl:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz

```

**Sample Response**

```

{
  "global_auth_settings": {
    "failed_auth_handling": "UserSubmitted",
    "re_authentication": "disabled",
    "basic_auth_token_ttl": 3600,
    "action_auth_service_unavailable": "Permit",
    "auth_settings": {
      "ssl_certificate": {
        "country": "IN",
        "basic_constraints": "Critical",
        "org_unit": "WSA",
        "expiry_date": "Jun 16 11:43:16 2041 GMT",
        "common_name": "Cisco",
        "org": "Cisco"
      },
      "header_based_authentication": {
        "xauth_std_user": {
          "text_format": "ASCII",
          "Binary_encoding": "No Encoding"
        },
        "xauth_std_group": {
          "text_format": "ASCII",

```



## Retrieving the Cisco Umbrella Seamless ID

You can retrieve details of Cisco Umbrella Seamless ID present and configurations such as host, ports, and organization ID.

<b>Synopsis</b>	GET wsa/api/v3.0/web_security/umbrella_seamless_id	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the details of Cisco Umbrella Seamless ID present and configurations such as host, ports, and organization ID.

### Sample Request

```
GET /wsa/api/v3.0/web_security/umbrella_seamless_id HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

### Sample Response

```
{
  "cisco_umbrella_seamless_id": {
    "swg_proxy": {
      "host": "54.185.245.81",
      "ports": [
        "80", "443"
      ]
    },
    "org_id": "4709668"
  }
}
```

## Modifying the Cisco Umbrella Seamless ID

You can modify details of Cisco Umbrella Seamless ID present and configurations such as host, ports, and organization ID.

<b>Synopsis</b>	PUT wsa/api/v3.0/web_security/umbrella_seamless_id	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the details of Cisco Umbrella Seamless ID present and configurations such as host, ports, and organization ID.

### Sample Request

```
PUT /wsa/api/v3.0/web_security/umbrella_seamless_id HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Content-Type: application/json
Content-Length: 1151
```

```
{
  "cisco_umbrella_seamless_id": {
    "swg_proxy": {
      "host": "54.185.245.81",
      "ports": ["80", "443"]
    },
    "org_id": "4709668"
  }
}
```

### Sample Response

```
204 (No-content)
```

## Performing Start Test for Umbrella Seamless ID

You can perform the start test for the umbrella seamless ID.

<b>Synopsis</b>	GET wsa/api/v3.0/web_security/swg_connectivity_test	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to perform the start test for the umbrella seamless ID.

### Sample Request

```
GET wsa/api/v3.0/web_security/swg_connectivity_test HTTP/1.1
Host: wsa353.cs1:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
Query Paramteres: host: wsa353.cs1
Ports: 11
```

### Sample Response

```
{
  "swg_connectivity_test": [
    {
      "host": "wsa353.cs1",

```

```

        "port 11": {
            "status": "Failed",
            "message": "Connection to ip and port is refused. Connection to the SWG
Proxy failed. "
        },
        "certificate_validation": {
            "message": "Connect Exception: Error opening publickey fetch server URL.
Certificate validation failed. "
        }
    }
}
]
}

```

## Secure DNSSec Settings

This section contains the following topics:

- [Retrieving the Secure DNS Settings, on page 136](#)
- [Modifying the Secure DNS Settings, on page 136](#)

### Retrieving the Secure DNS Settings

You can enable or disable the secure DNS settings.

<b>Synopsis</b>	GET wsa/api/v2.0/configure/network/dns/dnssec	
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

#### Example

This example shows how to enable or disable the secure DNS settings.

#### Sample Request

```

{
  "res_data": {
    "secure_dns": false
  },
  "res_message": "Data received successfully.",
  "res_code": 200
}

```

### Modifying the Secure DNS Settings

You can enable or disable the secure DNS settings.

<b>Synopsis</b>	PUT wsa/api/v2.0/configure/network/dns/dnssec
-----------------	---



<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to enable or disable the secure DNS settings.

#### Sample Request—Enable Secure DNS

```
{
  "secure_dns": true
}
```

#### Sample Response—Enable Secure DNS

```
{
  "res_data": {
    "update_success": [
      {
        "secure_dns": true
      }
    ]
  },
  "res_message": "Success: 1",
  "res_code": 200
}
```

#### Sample Request—Disable Secure DNS

```
{
  "secure_dns": false
}
```

#### Sample Response—Disable Secure DNS

```
{
  "res_data": {
    "update_success": [
      {
        "secure_dns": false
      }
    ]
  },
  "res_message": "Success: 1",
  "res_code": 200
}
```

## Identity Service Engine

This section contains the following topics:

- [Retrieving the Identity Service Engine Settings, on page 138](#)

- [Modifying the Identity Service Engine Settings, on page 139](#)
- [Uploading the Identity Service Engine Certificate Details, on page 140](#)
- [Downloading the Identity Service Engine Certificate Details, on page 140](#)
- [Performing Start Test for the Identity Service Engine, on page 141](#)

## Retrieving the Identity Service Engine Settings

You can retrieve the current settings of the identify service engine.

<b>Synopsis</b>	GET wsa/api/v3.0/network/ise	
<b>Supported Resource Attributes</b>	See <i>AsyncOS 14.5 API - Addendum to the Getting Started Guide for Cisco Secure Web Appliances</i> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the identify service engine settings.

#### Sample Request 1

```
GET wsa/api/v3.0/network/ise
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk
```

#### Sample Response 1

```
{
  "ise_service_status": "disable"
}
```

#### Sample Request 2

```
GET wsa/api/v3.0/network/ise
Host: dut058.perf8:4431
Authorization: Basic YWRtaW46Q21zY28xMjMk
```

#### Sample Response 2

```
{
  "ers_settings": {
    "status": "disable"
  },
  "wa_client_cert": {
    "uploaded": {
      "country": "IN",
      "basic_constraints": "critical",
      "org_unit": "WSA",
      "expiry_date": "Jun 16 11:43:16 2041 GMT",
      "common_name": "Cisco",
      "organization": "Cisco"
    }
  },
}
```

```

        "current_cert": "uploaded"
    },
    "sxp_status": "enable",
    "primary_ise_pxgrid": {
        "host": "dut058.perf8",
        "certificate": {
            "country": "",
            "basic_constraints": "critical",
            "org_unit": "",
            "expiry_date": "Apr 1 08:15:56 2030 GMT",
            "common_name": "Certificate Services Endpoint Sub CA - ise-server12",
            "organization": ""
        }
    }
}
}

```

## Modifying the Identity Service Engine Settings

You can modify the identify service engine settings.

<b>Synopsis</b>	PUT wsa/api/v3.0/network/ise	
<b>Supported Resource Attributes</b>	See <i>AsyncOS 14.5 API - Addendum to the Getting Started Guide for Cisco Secure Web Appliances</i> for more information.	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to modify the identify service engine settings.

### Sample Request

```

PUT '/wsa/api/v3.0/network/ise' HTTP/1.1
Content-Type: text/plain

```

```

{
  "ise_service_status" : "enable",
  "primary_ise_pxgrid": {
    "host": "1.2.3.3"
  },
  "secondary_ise_pxgrid": {
    "host": "1.2.3.9"
  },
  "wa_client_cert": {
    "generated": {
      "expiry_duration": 60,
      "country": "IN",
      "basic_constraints": "not critical",
      "org_unit": "WSA",
      "common_name": "Cisco",
      "organization": "Cisco"
    },
    "current_cert": "generated"
  },
  "sxp_status": "disable",
}

```

```

    "ers_settings": {
      "status": "enable",
      "username": "qwer-12",
      "password": "YWJjZGVmZW==",
      "secondary_server": "ise-server12.cs1.devit.ciscolabs.com",
      "ers_same_as_ise": false,
      "port": 9061,
      "primary_server": "ise-server12.cs1.devit.ciscolabs.com2"
    }
  }
}

```

**Sample Response**

204 (No-content)

## Uploading the Identity Service Engine Certificate Details

You can upload the identify service engine certificate details.

<b>Synopsis</b>	POST wsa/api/v3.0/network/ise_cert
<b>Supported Resource Attributes</b>	See <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> for more information.
<b>Request Headers</b>	Host, Accept, Authorization
<b>Response Headers</b>	Content-Type, Content-Length, Connection

**Example**

This example shows how to upload the identify service engine certificate details.

**Sample Request 1**

```

POST '/wsa/api/v3.0/network/ise_cert?cert_type=primary_pxgrid' HTTP/1.1
--form 'file=@"/C:/Users/admin/Desktop/rsa-ca.cert.pem"'

```

**Sample Request 2**

204 (No-content)

**Sample Request 2**

```

POST '/wsa/api/v3.0/network/ise_cert?cert_type=wa_client_uploaded' HTTP/1.1
--form 'file=@"/C:/Users/admin/Desktop/rsa-ca.cert.pem"'
--form 'key=@"/C:/Users/admin/Desktop/rsa-ca.key.pem"'
--form 'key_phrase="aXJvbnBvcnQ="'

```

**Sample Response 2**

204 (No-content)

## Downloading the Identity Service Engine Certificate Details

You can download the identify service engine certificate details.

<b>Synopsis</b>	GET wsa/api/v3.0/network/ise_download_cert
-----------------	--



## Example

This example shows how to perform the start test for the current settings of the identify service engine.

### Sample Request 1

```
GET wsa/api/v3.0/network/ise/start_test
Host: dut054.perf8:4431
Authorization: Basic YWRtaW46Q2l2Y28xMjMk
```

### Sample Response 1

```
{
  "test_result": "Failure",
  "test_logs": [
    "Checking DNS resolution of ISE pxGrid Node hostname(s) ...",
    "Success: Resolved 'ise-server56.csl.devit.ciscolabs.com' address: 10.10.201.56",
    "Validating WSA client certificate ...",
    "Success: Certificate validation successful",
    "Validating ISE pxGrid Node certificate(s) ...",
    "Success: Certificate validation successful",
    "Checking connection to ISE pxGrid Node(s) ...",
    "Trying primary PxGrid server...",
    "SXP not enabled.",
    "Preparing TLS connection...",
    "",
    "Completed TLS handshake with PxGrid successfully.",
    "",
    "",
    "Trying download SGT from (https://ise-server56.csl.devit.ciscolabs.com:8910)...",
    "",
    "Able to Download 19 SGTs.",
    "",
    "Skipping all SXP related service requests as SXP is not configured.",
    "",
    " ",
    "Trying download user-session from
(https://ise-server56.csl.devit.ciscolabs.com:8910)...",
    "",
    "Failure: Failed to download user-sessions.",
    "Trying connecting to primary ERS service...",
    "",
    "Failure: Unable to communicate with ERS Server.",
    "",
    "Certificate validation error Timeout: connect timed out: 10.10.201.56:9061.",
    "",
    "Failure: Connection to ISE pxGrid Node failed.",
    ""
  ]
}
```

### Sample Response 2

```
Response Code - 400 Bad Request
{
  "error": {
    "message": "ers status is disabled, Unable to initiate ISE test.",
    "code": "400",
    "explanation": "400 = Bad request syntax or unsupported method."
  }
}
```

## Anti-Malware Reputation

This section contains the following topics:

- [Retrieving Anti-Malware Reputation Details, on page 143](#)
- [Modifying the Anti-Malware Reputation Details, on page 150](#)
- [Registering the Anti-Malware Analytics Console, on page 157](#)
- [Deleting the Anti-Malware Analytics Console Registration, on page 158](#)

### Retrieving Anti-Malware Reputation Details

You can retrieve the objects containing details of anti-malware scanning services, web reputation services, and malware analytics services settings.

<b>Synopsis</b>	GET wsa/api/v3.0/security_services/anti_malware_and_reputation	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> .	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

#### Example

This example shows how to modify the objects containing details of anti-malware scanning services, web reputation services, and malware analytics services settings..

#### Sample Request

```
GET wsa/api/v3.0/security_services/anti_malware_and_reputation HTTP/1.1
Host: dut037.perf8:4431
Authorization: Basic YWRtaW46SXJvbnBvcnRAMTIz
```

#### Sample Response

```
{
  "anti_malware_scanning_services": {
    "dvs_max_object_size_mb": 32,
    "webroot": "enable",
    "sophos": "enable",
    "mcafee": "enable",
    "mcafee_heuristic_scanning": "enable",
    "webroot_threat_risk_threshold": 90
  },
  "web_reputation_services": {
    "web_reputaion_filtering": "enable",
    "adaptive_scanning": "enable"
  },
  "malware_analytics_services": {
    "file_analysis": "enable",
    "analysis_file_types": {
      "Executables": {
```

```

"selected": [
  "Access.LockFile.14(.ldb)",
  "Application.Reference(.appref-ms)",
  "Piffile(.pif)",
  "Exefile(.exe)"
],
"not_selected": [
  "AWFile(.aw)",
  "VBEFile(.VBE)",
  "WSHFile(.WSH)",
  "Microsoft.PowerShellData.1(.psd1)",
  "LnkFile(.lnk)",
  "Inffile(.inf)",
  "Microsoft.PowerShellScript.1(.ps1)",
  "Word.Wizard.8(.wiz)",
  "JSEFile(.JSE)",
  "Odcfile(.odc)",
  "Htafile(.hta)",
  "VisualStudio.Launcher.suo(.suo)",
  "ShockwaveFlash.ShockwaveFlash(.swf)",
  "Application.Manifest(.application)",
  "Msi.Package(.msi)",
  "FlashPlayer.AudioForFlashPlayer(.f4a)",
  "Diagnostic.Perfmon.Document(.blg)",
  "MSCFile(.msc)",
  "Regfile(.reg)",
  "Microsoft.PowerShellModule.1(.psm)",
  "Textfile(.wtx)",
  "PowerPoint.Wizard.8(.pwz)",
  "JSFile(.js)",
  "FlashPlayer.FlashVideo(.flv)",
  "Oqyfile(.oqy)",
  "OPCFile(.opc)",
  "LEXFile(.lex)",
  "Gmmpfile(.gmmp)",
  "Batfile(.bat)",
  "MSInfoFile(.nfo)",
  "Evtfile(.evt)",
  "Cmdfile(.cmd)",
  "Drvfile(.drv)",
  "VBSFile(.vbs)",
  "WebppnpFile(.webppnp)",
  "Windows.IsoFile(.iso)",
  "Comfile(.com)"
]
},
"Configuration": {
  "selected": [
    "Hlpfile(.hlp)",
    "Diagnostic.Config(.diagcfg)",
    "Outlook.File.nk2.14(.nk2)",
    "CRTXFile(.crtx)",
    "LibraryFolder(.library-ms)",
    "Inifile(.ini)",
    "VisualStudio.Launcher._vstasln80(.vstasln80)",
    "CLSID\\{9E56BE60-C50F-11CF-9A2C-00A0C90A90CE}(.mapimail)",
    "Hlwfile(.H1W)",
    "Aspfile(.cdx)",
    "XEV.GenericApp(.xevgenxml)",
    "VisualStudio.Launcher._sln71(.sln71)",
    "VisualStudio.Launcher._sln70(.sln70)",
    "JNLPPFILE(.jnlpp)",
    "VisualStudio.Launcher._vjsxsln80(.vjsxsln80)",
    "BrmFile(.printerExport)",

```



```

"Group_wab_auto_file(.group)",
"Icmfile(.icm)",
"XTPFILE(.xtp)",
"Vxdfile(.vxd)",
"Outlook.File.hol.14(.hol)",
"Hlsfile(.HlS)",
"Hltfile(.HlT)",
"Jtpfile(.jtp)",
"Hlvfile(.HlV)",
"GCSXFile(.gcsx)",
"Hlhfile(.HlH)",
"Ocxfile(.ocx)",
"AcroExch.SecStore(.secstore)",
"Hlkfile(.HlK)",
"MSGGraph.Chart.8(.gra)",
"RDBFileProperties.1(.sfcache)",
"InfoPath.SolutionManifest.3(.xsf)",
"Scrfile(.scr)",
"Hldfile(.HlD)",
"Wmffile(.wmf)",
"Hlffile(.HlF)",
"MediaCatalogMGC(.mgc)",
"GQSXFile(.gqsx)",
"MediaCenter.MCL(.mcl)",
"Migfile(.mig)",
"InternetShortcut(.URL)",
"Windows.gadget(.gadget)",
"Outlook.File.ics.14(.ics)",
"MediaCenter.C2R(.c2r)",
"OneNote.TableOfContents.12(.onetoc2)",
"Sysfile(.sys)",
"MediaCatalogMML(.mml)",
"JobObject(.job)",
"Emffile(.emf)",
"SavedDsQuery(.qds)",
"VisualStudio.Launcher._vcsxsln80(. _vcsxsln80)",
"CSSFile(.css)",
"VisualStudio.Launcher._sln(. _sln)",
"XTP2FILE(.xtp2)",
"RemoteAssistance.1(.msrcincident)",
"Microsoft.PowerShellXMLData.1(.pslxml)",
"Diagnostic.Perfmon.Config(.perfmoncfg)",
"LpkSetup.1(.mlc)",
"VisualStudio.Launcher._sln80(. _sln80)",
"GrooveLinkFile(.glk)",
"Cplfile(.cpl)",
"RDP.File(.rdp)",
"PDXFileType(.pdx)",
"Microsoft.WindowsCardSpaceBackup(.crds)",
"Cdmpfile(.cdmp)",
"Campfile(.camp)",
"PCBFILE(.pcb)",
"VisualStudio.Launcher._sln60(. _sln60)",
"VisualStudio.Launcher._vbxsln80(. _vbxsln80)",
"VisualStudio.Launcher.sln(.sln)",
"Contact_wab_auto_file(.contact)",
"OfficeListShortcut(.ols)",
"Hlcfile(.HlC)",
"Wcxfile(.wcx)",
"OneNote.TableOfContents(.onetoc)",
"CABFolder(.cab)",
"VisualStudio.Launcher._vcppxsln80(. _vcppxsln80)",
"MSSppPackageFile(.slupkg-ms)",
"CRLFile(.crl)",

```

```

    "Ratfile(.rat)"
  ],
  "not_selected": [
    "MediaPackageFile(.mpf)",
    "Prffile(.prf)",
    "GrooveStub(.gfs)",
    "SHCmdFile(.scf)"
  ]
},
"Microsoft Documents": {
  "selected": [],
  "not_selected": [
    "Excel.TemplateMacroEnabled(.xltn)",
    "PowerPoint.Addin.8(.ppa)",
    "VisualStudio.Launcher._vwdxsl80(._vwdxsl80)",
    "Wordhtmlfile(.dohtml)",
    "PowerPoint.Template.8(.pot)",
    "Excel.OpenDocumentSpreadsheet.12(.ods)",
    "Outlook.File.ost.14(.ost)",
    "Excelhtmlfile(.xlshtml)",
    "PowerPoint.SlideShow.8(.pps)",
    "Powerpointhtmlfile(.ppthtml)",
    "Excel.Template(.xltx)",
    "Powerpointhtmltemplate(.pothtml)",
    "Wordxml(.docxml)",
    "Publisherhtmlfile(.pubhtml)",
    "PowerPoint.SlideShow.12(.ppsx)",
    "GrooveFile(.grv)",
    "Powerpointmhtmlfile(.pptmhtml)",
    "Excel.SheetBinaryMacroEnabled.12(.xlsb)",
    "PowerPoint.Template.12(.potx)",
    "H1qfile(.H1Q)",
    "PowerPoint.Addin.12(.ppam)",
    "Dqyfile(.dqy)",
    "PowerPoint.TemplateMacroEnabled.12(.potm)",
    "Excelhtmltemplate(.xlthtml)",
    "VisioViewer.Viewer(.vtx)",
    "Excel.CSV(.csv)",
    "Excel.Addin(.xla)",
    "PowerPoint.Show.12(.pptx)",
    "Excel.Sheet.12(.xlsx)",
    "Word.Document.12(.docx)",
    "Outlook.File.otm.14(.otm)",
    "Powerpointxmlfile(.pptxml)",
    "Word.Template.12(.dotx)",
    "Publisher.Document.14(.pub)",
    "Wordhtmltemplate(.dohtml)",
    "Excel.SheetMacroEnabled.12(.xlsm)",
    "PowerPoint.ShowMacroEnabled.12(.pptm)",
    "Wordhtmlfile(.docm)",
    "OneNote.Section.1(.one)",
    "Word.TemplateMacroEnabled.12(.dotm)",
    "PowerPoint.SlideShowMacroEnabled.12(.ppsm)",
    "OneNote.Package(.onepkg)",
    "Publishermhtmlfile(.pubmhtml)",
    "Outlook.File.det.14(.det)",
    "Excel.AddInMacroEnabled(.xlam)",
    "OfficeTheme.12(.thmx)",
    "PowerPoint.Show.8(.ppt)",
    "Word.Addin.8(.wll)",
    "Outlook.File.oft.14(.oft)",
    "Word.Document.8(.doc)",
    "Excel.Template.8(.xlt)",
    "Excel.Sheet.8(.xls)",

```

```

    "Word.Template.8(.dot)"
  ]
},
"Database": {
  "selected": [
    "Access.MDBFile(.mdb)",
    "Access.Extension.14(.mda)",
    "Access.MDEFile.14(.mde)"
  ],
  "not_selected": [
    "Access.Application.14(.accdb)",
    "Access.ACDCFile.14(.accdc)",
    "Access.ACDDAExtension.14(.accda)",
    "Access.ACDEFile.14(.accde)",
    "Access.ACDDRFile.14(.accdr)",
    "Access.Shortcut.Report.1(.mar)",
    "Access.WebApplicationReference.14(.accdw)",
    "Access.ACDDTFile.14(.accdt)",
    "Access.WizardUserDataFile.14(.accdu)",
    "CATFile(.cat)",
    "Access.ACFFTFile.14(.accft)",
    "Access.Workgroup.14(.mdw)",
    "Access.Shortcut.Table.1(.mdt)",
    "Access.Project.14(.adp)",
    "Access.ADEFile.14(.ade)",
    "Access.BlankProjectTemplate.14(.adn)",
    "Access.Shortcut.Query.1(.maq)",
    "Access.Shortcut.StoredProcedure.1(.mas)",
    "Accesshtmlfile(.mdbhtml)",
    "Access.Shortcut.Function.1(.mau)",
    "Access.Shortcut.Table.1(.mat)",
    "Access.Shortcut.DataAccessPage.1(.maw)",
    "Accesshtmltemplate(.wizhtml)",
    "Dbfile(.db)",
    "Microsoft.Jet.OLEDB.4.0(.jod)",
    "Access.Shortcut.Module.1(.mad)",
    "Access.Shortcut.Diagram.1(.mag)",
    "Access.Shortcut.Form.1(.maf)",
    "Access.Shortcut.Macro.1(.mam)",
    "Accesshtmlfile(.mfp)",
    "Odctablefile(.odctablefile)",
    "ACLFile(.acl)",
    "MSDASC(.UDL)",
    "Odcnewfile(.odcnewfile)",
    "Odcdatabasefile(.odcdatabasefile)"
  ]
},
"Miscellaneous": {
  "selected": [],
  "not_selected": [
    "Microsoft.Website(.website)",
    "Dllfile(.rll)",
    "Diagnostic.Cabinet(.diagcab)",
    "IE.AssocFile.PARTIAL(.partial)",
    "CLSID\\{9E56BE61-C50F-11CF-9A2C-00A0C90A90CE}(.desklink)",
    "STLFile(.stl)",
    "Diagnostic.Document(.diagpkg)",
    "Chkfile(.chk)",
    "Pfmfile(.pfm)",
    "Label(.label)",
    "MSDASQL(.dsn)",
    "Windows.CompositeFont(.compositefont)",
    "Microsoft.InformationCard(.crd)",
    "AcroExch.acrobatsecuritysettings(.acrobatsecuritysettings)",

```

```

        "PKOFile(.pko)",
        "MediaCatalogMMW(.mmw)"
    ]
},
"Encoded and Encrypted": {
    "selected": [],
    "not_selected": [
        "SPCFile(.spc)",
        "P7RFile(.p7r)",
        "P7SFile(.p7s)",
        "CertificateStoreFile(.sst)",
        "CERFile(.der)",
        "P10File(.p10)",
        "Certificate_wab_auto_file(.p7c)",
        "MSSpLicenseFile(.xrm-ms)",
        "PFXFile(.pfx)",
        "P7MFile(.p7m)"
    ]
},
"Document": {
    "selected": [],
    "not_selected": [
        "Word.RTF.8(.rtf)",
        "Jntfile(.jnt)",
        "AcroExch.XFDFDocAcroExch.XFDFDoc(.xdf)",
        "InfoPath.Document.3(.infopathxml)",
        "Word.OpenDocumentText.12(.odt)",
        "AcroExch.Plugin(.api)",
        "MSHelp.hxc.2.5(.hxc)",
        "Shtmlfile(.shtml)",
        "MSHelp.hxf.2.5(.hxf)",
        "MSHelp.hxe.2.5(.hxe)",
        "MSHelp.hxd.2.5(.hxd)",
        "MSHelp.hxk.2.5(.hxk)",
        "MSHelp.hxi.2.5(.hxi)",
        "MSHelp.hxh.2.5(.hxh)",
        "Chm.file(.chm)",
        "MSHelp.hxs.2.5(.hxs)",
        "MSHelp.hxr.2.5(.hxr)",
        "MSHelp.hxq.2.5(.hxq)",
        "Htmlfile(.html)",
        "MSHelp.hxw.2.5(.hxw)",
        "MSHelp.hxv.2.5(.hxv)",
        "Windows.XPSReachViewer(.xps)",
        "Xhtmlfile(.xhtml)",
        "Mhtmlfile(.mhtml)",
        "Xmlfile(.xml)",
        "Odccubefile(.odccubefile)",
        "Otffile(.otf)",
        "AcroExch.XDPDoc(.xdp)",
        "AcroExch.FDFDoc(.fdf)",
        "AcroExch.pdfxml(.pdfxml)",
        "Outlook.File.fdm.14(.fdm)",
        "GrooveVCard(.vcg)",
        "GrooveSpaceArchive(.gsa)",
        "AcroExch.Document(.pdf)",
        "Windows.DVD.Maker(.msdvd)"
    ]
},
"Email": {
    "selected": [],
    "not_selected": [
        "Outlook.File.vcf.14(.vcf)",
        "Outlook.File.eml.14(.eml)",
    ]
}

```

```

    "Microsoft.PowerShellConsole.1(.pscl)",
    "Outlook.File ofs.14(.ofs)",
    "Outlook.File.pab.14(.pab)",
    "Outlook.File.msg.14(.msg)"
  ]
},
"Archived and compressed": {
  "selected": [
    "GrooveToolArchive(.gta)",
    "GLOXFile(.glox)",
    "7zFile(.7z)"
  ],
  "not_selected": [
    "TarFile(.tar)",
    "ZipFile(.zip)",
    "LzxFile(.lzx)",
    "Microsoft.System.Update.1(.msu)",
    "Jarfile(.jar)",
    "GzFile(.gz)",
    "LzhFile(.lzh)",
    "RarFile(.rar)",
    "VisualStudio.ContentInstaller.vsi(.vsi)",
    "Pbkfile(.pbk)"
  ]
}
},
"file_reputation_filtering": "enable",
"advanced_settings": {
  "file_analysis_threshold": {
    "score": 95,
    "cloud_service": "enable"
  },
  "routing_table": "Management",
  "file_reputation": {
    "query_timeout": 15,
    "client_id": "a581d63d-4501-4876-8d7c-ff0e1c308372",
    "heart_beat_interval": 900,
    "proxy_settings": {
      "username": "swarchak",
      "port": 80,
      "relax_cert_validation": "enable",
      "server": "testserver.com"
    },
    "server": {
      "uploaded_cert_details": {
        "subject": "C=IN, O=sbg, OU=in, CN=tesy",
        "expiry_date": "Nov 3 16:07:48 2022 GMT",
        "issuer": "C=AU, ST=Some-State, O=Internet Widgits Pty Ltd"
      },
      "cert_authority": "Use Uploaded Certificate Authority",
      "cloud_server": "private",
      "available_servers": [
        "AMERICAS (cloud-sa.amp.cisco.com)",
        "AMERICAS(Legacy) (cloud-sa.amp.sourcefire.com)",
        "EUROPE (cloud-sa.eu.amp.cisco.com)",
        "Private Cloud"
      ],
      "server": "testfilerepserver.com"
    }
  },
  "cache_expiry_period": {
    "unknown": 1800,
    "malicious": 172800,
    "clean": 604800
  }
}

```



Content-Type: multipart/form-data; boundary=-----591659103622018736729500  
 Content-Length: 17917

```

"malware_analytics_services": {
  "file_analysis": "enable",
  "analysis_file_types": {
    "Executables": {
      "selected": [
        "AWFile(.aw)",
        "VBEFile(.VBE)",
        "WSHFile(.WSH)",
        "Piffile(.pif)",
        "LnkFile(.lnk)",
        "Inffile(.inf)",
        "Exefile(.exe)"
      ],
      "not_selected": [
        "Access.LockFile.14(.ldb)",
        "Application.Reference(.appref-ms)",
        "Drvfile(.drv)",
        "Microsoft.PowerShellData.1(.psdl)",
        "Odcfile(.odc)",
        "Word.Wizard.8(.wiz)",
        "JSEFile(.JSE)",
        "Microsoft.PowerShellScript.1(.ps1)",
        "htafile(.hta)",
        "VisualStudio.Launcher.suo(.suo)",
        "ShockwaveFlash.ShockwaveFlash(.swf)",
        "Application.Manifest(.application)",
        "Msi.Package(.msi)",
        "Diagnostic.Perfmon.Document(.blg)",
        "MSCFile(.msc)",
        "Regfile(.reg)",
        "Microsoft.PowerShellModule.1(.psm)",
        "Textfile(.wtx)",
        "PowerPoint.Wizard.8(.pwz)",
        "JSFile(.js)",
        "Oqyfile(.oqy)",
        "OPCFile(.opc)",
        "LEXFile(.lex)",
        "Gmmpfile(.gmmp)",
        "Batfile(.bat)",
        "MSInfoFile(.nfo)",
        "Comfile(.com)",
        "Cmdfile(.cmd)",
        "VBSFile(.vbs)",
        "FlashPlayer.FlashVideo(.flv)",
        "FlashPlayer.AudioForFlashPlayer(.f4a)",
        "WebpnpFile(.webpnp)",
        "Windows.IsoFile(.iso)",
        "Evtfile(.evt)"
      ]
    }
  },
  "Document": {
    "selected": [],
    "not_selected": [
      "Word.RTF.8(.rtf)",
      "Jntfile(.jnt)",
      "AcroExch.XFDFDocAcroExch.XFDFDoc(.xpdf)",
      "InfoPath.Document.3(.infopathxml)",
      "Word.OpenDocumentText.12(.odt)",
      "AcroExch.Plugin(.api)",
      "MSHelp.hxc.2.5(.hxc)",
      "Shtmlfile(.shtml)",
    ]
  }
}

```

```

"MSHelp.hxf.2.5(.hxf)",
"MSHelp.hxe.2.5(.hxe)",
"MSHelp.hxd.2.5(.hxd)",
"MSHelp.hxk.2.5(.hxk)",
"MSHelp.hxi.2.5(.hxi)",
"MSHelp.hxh.2.5(.hxh)",
"Chm.file(.chm)",
"MSHelp.hxs.2.5(.hxs)",
"MSHelp.hxr.2.5(.hxr)",
"MSHelp.hxq.2.5(.hxq)",
"Htmlfile(.html)",
"MSHelp.hxw.2.5(.hxw)",
"MSHelp.hxv.2.5(.hxv)",
"Windows.XPSReachViewer(.xps)",
"Xhtmlfile(.xhtml)",
"Mhtmlfile(.mhtml)",
"Xmlfile(.xml)",
"Odccubefile(.odccubefile)",
"Otffile(.otf)",
"AcroExch.XDPDoc(.xdp)",
"AcroExch.FDFDoc(.fdf)",
"AcroExch.pdfxml(.pdfxml)",
"Outlook.File.fdm.14(.fdm)",
"GrooveVCard(.vcg)",
"GrooveSpaceArchive(.gsa)",
"AcroExch.Document(.pdf)",
"Windows.DVD.Maker(.msdvd)"
]
},
"Microsoft Documents": {
  "selected": [],
  "not_selected": [
    "Excel.TemplateMacroEnabled(.xltm)",
    "PowerPoint.Addin.8(.ppa)",
    "VisualStudio.Launcher._vwdxsln80(._vwdxsln80)",
    "Wordhtmlfile(.dohtml)",
    "PowerPoint.Template.8(.pot)",
    "Excel.OpenDocumentSpreadsheet.12(.ods)",
    "Outlook.File.ost.14(.ost)",
    "Excelhtmlfile(.xlshtml)",
    "PowerPoint.SlideShow.8(.pps)",
    "Excel.AddInMacroEnabled(.xlam)",
    "Excel.Template(.xltx)",
    "Powerpointhtmltemplate(.pothtml)",
    "Wordxml(.docxml)",
    "Publisherhtmlfile(.pubhtml)",
    "PowerPoint.SlideShow.12(.ppsx)",
    "GrooveFile(.grv)",
    "Powerpointmhtmlfile(.pptmhtml)",
    "OneNote.Section.1(.one)",
    "PowerPoint.Template.12(.potx)",
    "H1qfile(.H1Q)",
    "PowerPoint.Addin.12(.ppam)",
    "Dqyfile(.dqy)",
    "PowerPoint.TemplateMacroEnabled.12(.potm)",
    "Word.Addin.8(.wll)",
    "Excelhtmltemplate(.xlthtml)",
    "VisioViewer.Viewer(.vtx)",
    "Excel.CSV(.csv)",
    "PowerPoint.Show.12(.pptx)",
    "Excel.Sheet.12(.xlsx)",
    "Word.Document.12(.docx)",
    "Outlook.File.otm.14(.otm)",
    "Powerpointxmlfile(.pptxml)",

```



```

"Word.Template.12(.dotx)",
"Publisher.Document.14(.pub)",
"Excel.SheetMacroEnabled.12(.xlsm)",
"PowerPoint.ShowMacroEnabled.12(.pptm)",
"Wordhtmlfile(.docm)",
"Excel.SheetBinaryMacroEnabled.12(.xlsb)",
"Word.TemplateMacroEnabled.12(.dotm)",
"PowerPoint.SlideShowMacroEnabled.12(.ppsm)",
"OneNote.Package(.onepkg)",
"Wordhtmltemplate(.dothtml)",
"Outlook.File.det.14(.det)",
"Excel.Addin(.xla)",
"OfficeTheme.12(.thmx)",
"PowerPoint.Show.8(.ppt)",
"Word.Document.8(.doc)",
"Powerpointhtmlfile(.ppthtml)",
"Outlook.File.oft.14(.oft)",
"Publishermhtmlfile(.pubmhtml)",
"Excel.Template.8(.xlt)",
"Excel.Sheet.8(.xls)",
"Word.Template.8(.dot)"
]
},
"Database": {
  "selected": [],
  "not_selected": [
    "Access.Application.14(.accdb)",
    "Access.ACDCFile.14(.accdc)",
    "Access.ACDAExtension.14(.accda)",
    "Access.ACCDEFile.14(.accde)",
    "Access.MDBFile(.mdb)",
    "Access.Extension.14(.mda)",
    "Access.MDEFile.14(.mde)",
    "Access.ACDDRFile.14(.accdr)",
    "Access.Shortcut.Report.1(.mar)",
    "Access.WebApplicationReference.14(.accdw)",
    "Access.ACCTFile.14(.accdt)",
    "Access.WizardUserDataFile.14(.accdu)",
    "ACLFile(.acl)",
    "Access.ACCFTFile.14(.accft)",
    "Access.Workgroup.14(.mdw)",
    "Access.Shortcut.Table.1(.mdt)",
    "Access.Project.14(.adp)",
    "Access.ADEFile.14(.ade)",
    "Access.BlankProjectTemplate.14(.adn)",
    "Access.Shortcut.Query.1(.maq)",
    "Access.Shortcut.StoredProcedure.1(.mas)",
    "Accesshtmlfile(.mdbhtml)",
    "Access.Shortcut.Function.1(.mau)",
    "Access.Shortcut.Table.1(.mat)",
    "Access.Shortcut.DataAccessPage.1(.maw)",
    "Accesshtmltemplate(.wizhtml)",
    "Dbfile(.db)",
    "Microsoft.Jet.OLEDB.4.0(.jod)",
    "Access.Shortcut.Module.1(.mad)",
    "Access.Shortcut.Diagram.1(.mag)",
    "Access.Shortcut.Form.1(.maf)",
    "Access.Shortcut.Macro.1(.mam)",
    "Accesshtmlfile(.mfp)",
    "Odctablefile(.odctablefile)",
    "CATFile(.cat)",
    "Odcdatabasefile(.odcdatabasefile)",
    "Odcnewfile(.odcnewfile)",
    "MSDASC(.UDL)"
  ]
}

```

```

    ]
  },
  "Miscellaneous": {
    "selected": [],
    "not_selected": [
      "Microsoft.Website(.website)",
      "Dllfile(.rll)",
      "Diagnostic.Cabinet(.diagcab)",
      "IE.AssocFile.PARTIAL(.partial)",
      "CLSID\\{9E56BE61-C50F-11CF-9A2C-00A0C90A90CE}(.desklink)",
      "STLFile(.stl)",
      "Diagnostic.Document(.diagpkg)",
      "Chkfile(.chk)",
      "Pfmfile(.pfm)",
      "Label(.label)",
      "MSDASQL(.dsn)",
      "Windows.CompositeFont(.compositefont)",
      "Microsoft.InformationCard(.crd)",
      "AcroExch.acrobatsecuritysettings(.acrobatsecuritysettings)",
      "PKOFile(.pko)",
      "MediaCatalogMMW(.mmw)"
    ]
  },
  "Encoded and Encrypted": {
    "selected": [],
    "not_selected": [
      "P7MFile(.p7m)",
      "P7RFile(.p7r)",
      "P7SFile(.p7s)",
      "CertificateStoreFile(.sst)",
      "CERFile(.der)",
      "P10File(.p10)",
      "Certificate_wab_auto_file(.p7c)",
      "MSSpLicenseFile(.xrm-ms)",
      "PFXFile(.pfx)",
      "SPCFile(.spc)"
    ]
  },
  "Configuration": {
    "selected": [],
    "not_selected": [
      "MediaCatalogMGC(.mgc)",
      "Prffile(.prf)",
      "GrooveStub(.gfs)",
      "SHCmdFile(.scf)",
      "Hlpfile(.hlp)",
      "H1cfile(.H1C)",
      "Outlook.File.nk2.14(.nk2)",
      "CRTXFile(.crtx)",
      "LibraryFolder(.library-ms)",
      "Inifile(.ini)",
      "VisualStudio.Launcher._vstasln80(. _vstasln80)",
      "MediaCatalogMML(.mml)",
      "CLSID\\{9E56BE60-C50F-11CF-9A2C-00A0C90A90CE}(.mapimail)",
      "GCSXFile(.gcsx)",
      "Aspfile(.cdx)",
      "XEV.GenericApp(.xevgenxml)",
      "VisualStudio.Launcher._sln71(. _sln71)",
      "VisualStudio.Launcher._sln70(. _sln70)",
      "JNLPFILE(.jnlp)",
      "VisualStudio.Launcher._vjsxsln80(. _vjsxsln80)",
      "Campfile(.camp)",
      "BrmFile(.printerExport)",
      "Group_wab_auto_file(.group)"
    ]
  }
}

```

```

"Icmfile(.icm)",
"XTPFILE(.xtp)",
"Vxdfile(.vxd)",
"Outlook.File.hol.14(.hol)",
"Hlsfile(.HlS)",
"Hltfile(.HlT)",
"Jtpfile(.jtp)",
"Hlvfile(.HlV)",
"Hlwfile(.HlW)",
"Hlhfile(.HlH)",
"Ocxfile(.ocx)",
"AcroExch.SecStore(.secstore)",
"Hlkfile(.HlK)",
"Contact_wab_auto_file(.contact)",
"MSGGraph.Chart.8(.gra)",
"RDBFileProperties.1(.sfcache)",
"Scrfile(.scr)",
"Hldfile(.HlD)",
"Wmffile(.wmf)",
"Hlffile(.HlF)",
"CRLFile(.crl)",
"MediaPackageFile(.mpf)",
"GQSXFile(.gqsx)",
"MediaCenter.MCL(.mcl)",
"Migfile(.mig)",
"InternetShortcut(.URL)",
"Windows.gadget(.gadget)",
"OneNote.TableOfContents.12(.onetoc2)",
"Sysfile(.sys)",
"Outlook.File.ics.14(.ics)",
"JobObject(.job)",
"GrooveLinkFile(.glk)",
"SavedDsQuery(.qds)",
"VisualStudio.Launcher._vcxsln80(.vcxsln80)",
"VisualStudio.Launcher._sln(.sln)",
"XTP2FILE(.xtp2)",
"RemoteAssistance.1(.msrcincident)",
"Microsoft.PowerShellXMLData.1(.pslxml)",
"Diagnostic.Perfmon.Config(.perfmoncfg)",
"LpkSetup.1(.mlc)",
"VisualStudio.Launcher._sln80(.sln80)",
"Emffile(.emf)",
"Cplfile(.cpl)",
"RDP.File(.rdp)",
"PDXFileType(.pdx)",
"Microsoft.WindowsCardSpaceBackup(.crds)",
"Cdmpfile(.cdmp)",
"MediaCenter.C2R(.c2r)",
"PCBFILE(.pcb)",
"VisualStudio.Launcher._sln60(.sln60)",
"VisualStudio.Launcher._vbxsln80(.vbxsln80)",
"VisualStudio.Launcher.sln(.sln)",
"OfficeListShortcut(.ols)",
"InfoPath.SolutionManifest.3(.xsf)",
"CSSFile(.css)",
"Wcxfile(.wcx)",
"OneNote.TableOfContents(.onetoc)",
"CABFolder(.cab)",
"VisualStudio.Launcher._vcppxsln80(.vcppxsln80)",
"MSSpPackageFile(.slupkg-ms)",
"Diagnostic.Config(.diagcfg)",
"Ratfile(.rat)"
]
},

```

```

"Email": {
  "selected": [],
  "not_selected": [
    "Outlook.File.vcf.14(.vcf)",
    "Outlook.File.eml.14(.eml)",
    "Microsoft.PowerShellConsole.1(.pscl)",
    "Outlook.File ofs.14(.ofs)",
    "Outlook.File.pab.14(.pab)",
    "Outlook.File.msg.14(.msg)"
  ]
},
"Archived and compressed": {
  "selected": [],
  "not_selected": [
    "GrooveToolArchive(.gta)",
    "TarFile(.tar)",
    "ZipFile(.zip)",
    "LzxFile(.lzx)",
    "Microsoft.System.Update.1(.msu)",
    "Jarfile(.jar)",
    "GzFile(.gz)",
    "GLOXFile(.glox)",
    "LzhFile(.lzh)",
    "RarFile(.rar)",
    "VisualStudio.ContentInstaller.vsi(.vsi)",
    "7zFile(.7z)",
    "Pbkfile(.pbk)"
  ]
},
"file_reputation_filtering": "enable",
"advanced_settings": {
  "file_analysis_threshold": {
    "score": 95,
    "cloud_service": "enable"
  },
  "routing_table": "Management",
  "file_reputation": {
    "query_timeout": 15,
    "client_id": "ab54d0e2-a978-466c-a37f-e9451d173ac6",
    "heart_beat_interval": 900,
    "proxy_settings": {
      "username": "",
      "port": 80,
      "relax_cert_validation": "disable",
      "server": ""
    },
    "server": {
      "uploaded_cert_details": {
        "subject": "C=IN, O=Cisco, OU=Cisco, CN=Cisco",
        "expiry_date": "Apr 6 13:43:19 2026 GMT",
        "issuer": "C=IN, O=Cisco, OU=Cisco, CN=Cisco"
      },
      "cert_authority": "Use Uploaded Certificate Authority",
      "cloud_server": "private",
      "available_servers": [
        "AMERICAS (cloud-sa.amp.cisco.com)",
        "AMERICAS(Legacy) (cloud-sa.amp.sourcefire.com)",
        "EUROPE (cloud-sa.eu.amp.cisco.com)",
        "Private Cloud"
      ],
      "server": "testfilerepserver.com"
    }
  }
},

```

```

    "cache_expiry_period": {
      "unknown": 900,
      "malicious": 86400,
      "clean": 604800
    },
    "file_analysis": {
      "client_id":
"02_VLNWSA9294_4229DB97298D40B6DB38-2F09FC0ABBD9_S300V_0000000000",
      "proxy_settings": {
        "use_file_reputation_proxy": "disable",
        "username": "testadmin123",
        "port": 635,
        "server": "testdomain.com"
      },
      "server": {
        "uploaded_cert_details": {
          "subject": "C=IN, O=Cisco, OU=Cisco, CN=Cisco",
          "expiry_date": "Apr  6 13:43:19 2026 GMT",
          "issuer": "C=IN, O=Cisco, OU=Cisco, CN=Cisco"
        },
        "cert_authority": "Use Uploaded Certificate Authority",
        "cloud_server": "private",
        "tg_servers": [
          "analysis_server.com"
        ],
        "available_servers": [
          "AMERICAS (https://panacea.threatgrid.com)",
          "EUROPE (https://panacea.threatgrid.eu)",
          "Private Cloud"
        ]
      }
    }
  }
}

```

### Sample Response

Response: 204 (No-content)

## Registering the Anti-Malware Analytics Console

You can retrieve a list of objects containing details of malware analytics console endpoints registration status.

<b>Synopsis</b>	GET wsa/api/v3.0/security_services/malware_analytics_endpoints_console_registration	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> .	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

### Example

This example shows how to retrieve the list of objects containing details of malware analytics console endpoints registration status.

**Sample Request**

```
GET wsa/api/v3.0/security_services/malware_analytics_endpoints_console_registration HTTP/1.1
Host: wsall8.cs14:10118
Authorization: Basic Auth
```

**Sample Response 1—Before Registration**

```
{ "status": "Not registered" }
```

**Sample Response 2—After Registration**

```
{
  "status": "Registered",
  "device_name": "VLNWSA9294_42292897BFE970627FA5-0E60982C2E26"
}
```

**Deleting the Anti-Malware Analytics Console Registration**

You can delete the list of objects containing details of malware analytics console endpoints registration status.

<b>Synopsis</b>	DELETE wsa/api/v3.0/security_services/malware_analytics_endpoints_console_registration	
<b>Supported Resource Attributes</b>	For more information, see <a href="#">AsyncOS API - Addendum to the Getting Started Guide for Secure Web Appliance</a> .	
<b>Request Headers</b>		Host, Accept, Authorization
<b>Response Headers</b>		Content-Type, Content-Length, Connection

**Example**

This example shows how to delete the list of objects containing details of malware analytics console endpoints registration status.

**Sample Request**

```
DELETE wsa/api/v3.0/security_services/malware_analytics_endpoints_console_registration HTTP/1.1
Host: wsall8.cs14:10118
Authorization: Basic Auth
```

**Sample Response**

```
""Successfully deregistered from Malware Analytics for Endpoints.""
```