



## Usage Scenarios

---

This chapter describes how the changes that are made in the Service Delivery Platform (SDP) and Smart+Connected MS applications affect the end user's experience when working with the devices and other features. You can navigate to the sections that provide information on all the sub-tasks that need to be performed in order to achieve the key tasks.

This chapter includes the following sections:

- [Lights Scenarios, page 13-1](#)
- [Window Blinds Scenario, page 13-2](#)
- [Temperature Control Scenario, page 13-2](#)
- [Audio/Visual Equipment Scenario, page 13-3](#)
- [Fault Reporting Scenarios, page 13-3](#)
- [Signage Messaging Scenarios, page 13-4](#)
- [Meeting Details Scenarios, page 13-5](#)
- [Room Booking Scenario, page 13-6](#)
- [Room Mode Scenario, page 13-7](#)
- [Room Setup Scenarios, page 13-7](#)
- [Smart+Connected EN Scenarios, page 13-8](#)
- [Smart+Connected IS Scenarios, page 13-10](#)
- [Smart+Connected GA Scenarios, page 13-15](#)


### Lights Scenarios

- [Scenario 1: Lights Control, page 13-1](#)
- [Scenario 2: Dimmer Control, page 13-2](#)


#### Scenario 1: Lights Control

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Ensure that the Building Management System (BMS) adapter properties are configured in the database.


***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

3. Create a device “Lights” for the conference room created in Step 1 using the Devices tab in the SDP.
4. Create a device “IP Phone” for the conference room.
5. Assign a configuration, which has the Lights On/Off Control feature, to the location.
6. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
7. Select the service and ensure that the lights control  icon is displayed on the IP phone.
8. When a user taps the lights control icon, the options to switch the lights on and off are displayed.

## Scenario 2: Dimmer Control

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Ensure that the BMS adapter properties are configured in the database.
3. Create a device “Dimmer” for the conference room created in Step 1 using the Devices tab in the SDP.
4. Create a device “IP Phone” for the conference room.
5. Assign a configuration, which has the Lights Dimmer Control feature, to the location.
6. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
7. Select the service and ensure that the lights control  icon is displayed on the IP phone.
8. When a user taps the lights control icon and selects the required light device, the options for setting the brightness levels are displayed. For example: 3%, 30%, 50%, 75%, and 100% brightness.
9. Set the brightness level of the lights using IP phone by tapping the required icon.


## Window Blinds Scenario

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor..
2. Ensure that the BMS adapter properties are configured in the database.
3. Create a device “Blinds” for the conference room created in Step 1 using the Devices tab in the SDP.
4. Create a device “IP Phone” for the conference room.
5. Assign a configuration, which has the Lights Dimmer Control feature, to the location.
6. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
7. Select the service and ensure that the blinds control  icon is displayed on the IP phone.
8. When a user taps the blinds control icon, the options to open and close the blinds are displayed.


## Temperature Control Scenario

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Ensure that the BMS adapter properties are configured in the database.

## ***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

3. Create a device “VAV” for the conference room created in Step 1 using the Devices tab in the SDP.
4. Create a device “IP Phone” for the conference room.
5. Assign a configuration, which has the Thermostat (On/Off) Control and Thermostat (Set Point) Control feature, to the location.
6. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
7. Select the service and ensure that the temperature control  icon is displayed on the IP phone.
8. When a user taps the temperature control icon, the options to switch the air conditioner on and off are displayed.
9. The user can also select the temperature degree by tapping any of the temperature set points that are displayed. The temperature set point range shown on the IP phone is based on the Minimum Temperature value and Maximum Temperature value given for the VAV device in the SDP.


## **Audio/Visual Equipment Scenario**

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Create a device “Audio Video Controller” for the conference room created in Step 1 using the Devices tab in the SDP.
3. Create a device “IP Phone” for the conference room.
4. Assign a configuration, which has the A/V Control feature, to the location.
5. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
6. Ensure that Audio/Video adapter properties are configured in the database.
7. Select the service and ensure that the A/V control  icon is displayed on the IP phone.
8. When a user taps the A/V control icon, the options to switch the projector on and off are displayed.

## **Fault Reporting Scenarios**

- [Scenario 1: Fault Reporting Using Remedy, page 13-3](#)
- [Scenario 2: Fault Reporting Using E-mail, page 13-4](#)
- [Scenario 3: Entering Invalid User ID, page 13-4](#)

### **Scenario 1: Fault Reporting Using Remedy**

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Assign a configuration, which has the case management feature, to the location.
3. Create a device “IP Phone” for the conference room using the Devices tab in the SDP.
4. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
5. Select the service and ensure that the faults  icon is displayed on the IP phone.

## ***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

6. Ensure that the Remedy adapter properties are configured in the database and the adapter is linked to the location, preferably the root location.
7. When user taps the faults icon, the list of predefined fault reporting options for the location will be displayed.
8. When a user selects a fault item, the user is prompted to enter the User ID. This is the ID that uniquely identifies the user in the corporate directory (LDAP). A case will be created in the trouble ticketing application and routed to the appropriate team for resolution. The user will see a confirmation message on the IP phone with the unique case number.




### **Note**

---

Ensure that the Smart+Connected MS application is integrated with the Active Directory or LDAP.

---

## **Scenario 2: Fault Reporting Using E-mail**

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Assign a configuration, which has the case management feature, to the location.
3. Create a device “IP Phone” for the conference room using the Devices tab in the SDP.
4. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
5. Select the service and ensure that the faults  icon is displayed on the IP phone.
6. Ensure that e-mail adapter properties are configured in the database.
7. When user taps the faults icon, the list of predefined fault reporting options for the location will be displayed.
8. When a user selects a fault item, the user is prompted to enter the User ID. This is the ID that uniquely identifies the user in the corporate directory (LDAP). A fault report is compiled with the relevant information such as location, the ID of the user who has raised the fault, and so on. The report is sent as an e-mail to the configured mail ID, ideally the e-mail ID of the facilities team, who can take action on the fault complaint. The user receives a confirmation message with the unique case number through e-mail.

## **Scenario 3: Entering Invalid User ID**


1. Assign an IP phone and a VAV to a conference room using the Devices tab in the SDP.
2. Add a configuration which has the fault item “Air conditioning is not cold” to the room.
3. A user who enters an invalid User ID, using the IP phone, will not be able to report the fault. The User ID is the ID that uniquely identifies the user in the corporate directory (LDAP).

## **Signage Messaging Scenarios**

- [Scenario 1: Displaying Message on Conference Room Signage, page 13-5](#)
- [Scenario 2: Fault Message Disabled in Configuration, page 13-5](#)
- [Scenario 3: Configuration Without Signage Messaging Feature, page 13-5](#)

***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

## Scenario 1: Displaying Message on Conference Room Signage

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Create a device “DMP/IEC” and associate it to the conference room created in Step 1 using the Devices tab in the SDP.
3. Create a device “IP Phone” for the conference room.
4. Assign a configuration, which has the signage messages feature, to a location.
5. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
6. Select the service and ensure that the signage messaging icon  is displayed on the IP phone.
7. When the user taps the signage messaging icon, the list of available messages that can be send to the digital signage/IEC is displayed.
8. Selecting any of the menu items will update the message section of the conference room digital signage/IEC display associated to the location of the IP phone.

## Scenario 2: Fault Message Disabled in Configuration

1. Assign an IP phone and a digital media player to a conference room using the Devices tab in the SDP.
2. Add a configuration to the room which has a message “Meeting has been extended for 5 minutes” but disable this message.
3. The user will not see the message “Meeting has been extended for 5 minutes” under the Faults list on the IP phone at the location.

## Scenario 3: Configuration Without Signage Messaging Feature

1. Assign an IP phone to a conference room using the Devices tab in the SDP. A DMP is assigned to this location.
2. Add a configuration that does not have the digital signage messaging feature.
3. A user will not see the digital signage messaging icon on the IP phone.

## Meeting Details Scenarios

- [Scenario 1: Displaying Meeting Details, page 13-5](#)
- [Scenario 2: Hiding Meeting Subject and Attendee List, page 13-6](#)

### Scenario 1: Displaying Meeting Details

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Create a device “IP Phone” for the conference room created in Step 1 by entering the Media Access Control (MAC) address of the IP phone.

***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

3. Assign a configuration, which has the conference room details feature, to the location.
4. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
5. Ensure that adapter properties are configured either for Microsoft Exchange 2007 or 2010 in the database.
6. Book the conference room using the mail client.
7. Meeting details should get displayed on the IP phone.
8. The current meeting and the next two meetings will be listed. The start and end time of the meetings, along with the meeting subject, are displayed on the IP phone.




**Note**

This scenario is applicable only for touchscreen IP phones; meeting details are not displayed on non-touchscreen IP phones.

## Scenario 2: Hiding Meeting Subject and Attendee List

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Create a device “DMP” for the conference room created in Step 1 using the Devices tab in the SDP.
3. Create a device “IP Phone” for the conference room by entering the MAC address of the IP phone.
4. Assign a configuration, which has the conference room details feature, to the location.
5. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
6. Select the conference room created in Step 1 from the location hierarchy, and click the Edit icon. In the Edit Location Properties list, click Private Subject and Private Attendees and check the check boxes that appear for these options.
7. A user books the conference room using the IP phone at the location/the Smart+Connected MS user portal and chooses the Mark as Confidential option. The meeting subject will be shown in format "Booked by <name of organizer>" and the meeting attendees list will not be shown on the digital signage when the room schedule is displayed.

## Room Booking Scenario

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Create a device “IP Phone” for the conference room created in Step 1 by entering the MAC address of the IP phone.
3. Assign a configuration, which has the conference room details feature, to the location.
4. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
5. Ensure that adapter properties are configured either for Microsoft Exchange 2007 or 2010 in the database.
6. Ensure that LDAP is configured.
7. Select the services and the features that should be displayed on the IP phone.
8. If the room is available, the icon for booking the room  will be shown.

## ***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***


9. When the user taps the book icon, options for time slots appear.
10. Once the time slot is selected, the user is prompted to enter the User ID. This is the ID that uniquely identifies the user in the corporate directory (LDAP).
11. The user must click Submit after entering the User ID.
12. The meeting is booked for the selected duration and the details are displayed on the IP phone.
13. The calendar of the conference room will be updated with the details of the meeting start and end time and the subject of the meeting: Booked by <userid.>



### **Note**

This scenario is applicable only for touchscreen IP phones as room booking is not possible using non-touchscreen IP phones.

## **Room Mode Scenario**

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Ensure that the BMS and projector adapter properties are configured in the database.
3. Create the devices IP Phone, Projector, Lights, and Blinds for the conference room created in Step 1 using the Devices tab in the SDP.
4. Assign a configuration, which has the Room Mode feature, to the location.
5. Subscribe to the Smart+Connected Meeting Spaces service for the IP phone using the call manager.
6. Select the service and ensure that the room mode icon  is displayed on the IP phone.
7. When the user taps the room mode icon, the Presentation Mode–Day and Presentation Mode–Night options will be displayed. These are one-touch controls for lights, projector, and projector screen. The Normal Mode is a toggle option from the Presentation Modes.

## **Room Setup Scenarios**

- [Scenario 1: Room Availability, page 13-7](#)
- [Scenario 2: Room Setup Notice Period, page 13-8](#)

### **Scenario 1: Room Availability**

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Use the Roomsetup tab and add the room setup options for the conference room created in Step 1.
3. Update the setup, de-setup time, and notice period for the room setups in SCMS\_ROOMSETUP\_MASTER. Provide the setup time and de-setup time as 30 minutes each and the notice period as two hours.
4. A user who searches for rooms using the Smart+Connected MS can click the image for any room setup type to notice period, setup/de-setup time and choose any of the room setup options. The conference room you created in Step 1 will show up in the search results.

## Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)

5. Add the email ID of the room facility admin as the value for the Room Facility Admin property in SDP under the location Campus.
6. The user books this conference room from 3 pm to 4 pm. A room setup request is sent to the facilities team that arranges the room as per the requested setup.
7. A room de-setup request is sent to the facilities admin who ensures that the room is rearranged after the meeting is over.
8. Though this room is unoccupied, it will appear in the search results only after 4.30 pm because the room de-setup time is 30 minutes.

## Scenario 2: Room Setup Notice Period

1. In the Location Hierarchy folder in the SDP, create a Location Type “Conference Room” under the desired floor.
2. Use the Roomsetup tab and add the room setup options for the conference room created in Step 1.
3. Update the setup, de-setup time, and notice period for the room setups in SCMS\_ROOMSETUP\_MASTER.
4. A user tries to book a room at 4 pm for the 6 pm slot using a room setup option. The user is asked to change the meeting start time because the selected room setup has a four hour notice period.
5. Alternatively, the user can search for available conference rooms without specifying any room setup or opt for a room setup option with a notice period of two hours or less.

## Smart+Connected EN Scenarios

- [Scenario 1: Sending Emergency Incident Messages on the Digital Signage/IEC, page 13-8](#)
- [Scenario 2: Sending Emergency Incident Messages on IP Phones, page 13-9](#)

## Scenario 1: Sending Emergency Incident Messages on the Digital Signage/IEC

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ (DMP) for the created location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>



**[Send documentation comments to scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**

Order	Tasks	See
4	Configure adapter properties for DMP Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Create or configure the template for emergency notification	“Adding Templates” section on page 12-2
6	Create the emergency incident message template	“Adding Templates” section on page 12-2
7	Create the emergency incident message, associate with location(s), and enable the message	“Adding or Enabling the Emergency Incident Messages” section on page 9-10

1. Locations can be mean either conference rooms, floor plan, or a building.

## Scenario 2: Sending Emergency Incident Messages on IP Phones

Order	Tasks	See
1	Import the CUCM certificate for the Cisco IP phone.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘IP phone’ for the location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for IP phone Bean in the database to display the emergency incident message on IP phone.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Set up content for the Cisco IP phone	“Adding the Emergency Incident Message Templates” section on page 9-5
6	Enable the emergency incident message	“Adding or Enabling the Emergency Incident Messages” section on page 9-10
7	Configure audio on IP phone.	“Configuring Audio Notification to IP Phone” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>

1. Locations can be mean either conference rooms, floor plan, or a building.

**[Send documentation comments to scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**

## Smart+Connected IS Scenarios

- [Scenario 1: Displaying Meeting Details on the Floor Plan Display, page 13-10](#)
- [Scenario 2: Displaying Meeting Room Details on the Conference Room Plan Display, page 13-11](#)
- [Scenario 3: Displaying Meeting Room Details in Building View, page 13-12](#)
- [Scenario 4: Displaying News Content on the Digital Signage/IEC, page 13-13](#)
- [Scenario 5: Displaying External Content on the Digital Signage/IEC, page 13-13](#)
- [Scenario 6: Adding Sequence to Signage Content using DMM, page 13-14](#)


### Scenario 1: Displaying Meeting Details on the Floor Plan Display

Order	Tasks	See
1	<ul style="list-style-type: none"> <li>• Import a DMP certificate for the DMP if it uses HTTPS.</li> <li>• Import the certificate for the Exchange</li> </ul>	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for DMP Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Add ‘floor plan’ as the signage content.	“Adding Signage Content” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>
6	Create a content link for the added ‘floor plan’.	<a href="#">“Adding the Content Links” section on page 10-6</a>
7	Add sequence to the added content link and provide the duration of display.	<a href="#">“Adding Sequence” section on page 10-9</a>
8	Book the conference room through a mail client or a Cisco IP Phone.	“Adding Configurations” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>

1. Locations can be mean either conference rooms, floor plan, or a building.

**[Send documentation comments to scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**


## Scenario 2: Displaying Meeting Room Details on the Conference Room Plan Display

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for DMP Bean in the database.   <b>Note</b> You must perform this step only if the DMP adaptor was not configured earlier.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Add ‘conference room plan’ as the signage content and select the Primary Conference Room check box to make the room as a primary preference.	“Adding Signage Content” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>
6	Create a content link for the added ‘conference room plan’ signage content.	“Adding the Content Links” section on page 10-6
7	Add sequence to the added content link and provide the duration of display.	“Adding Sequence” section on page 10-9
8	Book the conference room through a mail client or a Cisco IP Phone.	“Adding Configurations” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>

1. Locations can be mean either conference rooms, floor plan, or a building.

**Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**

## Scenario 3: Displaying Meeting Room Details in Building View

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for DMP Bean in the database.  <b>Note</b> You must perform this step only if the DMP adaptor was not configured earlier.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Add ‘building view’ as the signage content.	“Adding Signage Content” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>
6	Create a content link for the added ‘building view’ signage content.	<a href="#">“Adding the Content Links” section on page 10-6</a>
7	Add sequence to the added content link and provide the duration of display.	<a href="#">“Adding Sequence” section on page 10-9</a>
8	Book the building through an e-mail exchange or IP Phone.	“Adding Configurations” section in the <i>Cisco Smart+Connected Meeting Spaces Administrator Guide</i>

1. Locations can be mean either conference rooms, floor plan, or a building.

**[Send documentation comments to scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**

## Scenario 4: Displaying News Content on the Digital Signage/IEC

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for DMP Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Add and enable the news content for displaying on the digital signage/IEC.	<a href="#">“Adding or Enabling the News Content” section on page 10-2</a>
6	Create a content link for the added news content.	<a href="#">“Adding the Content Links” section on page 10-6</a>
7	Add sequence to the added content link and provide the duration of display.	<a href="#">“Adding Sequence” section on page 10-9</a>

1. Locations can be mean either conference rooms, floor plan, or a building.

## Scenario 5: Displaying External Content on the Digital Signage/IEC

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>

***Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)***

Order	Tasks (continued)	See (continued)
4	Configure adapter properties for DMP Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Create a content link for external URLs, such as Google, Yahoo, YouTube, and so on.	“Viewing the Content Links” section on page 10-7
6	Add sequence to the added content link and provide the duration of display.	“Adding Sequence” section on page 10-9

1. Locations can be mean either conference rooms, floor plan, or a building.

## Scenario 6: Adding Sequence to Signage Content using DMM

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Configure adapter properties for DMM Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Add a device ‘Digital Media Player’ to the required location(s).	<p>“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i></p> <p>After adding, the DMP device created for the location is automatically displayed in the Digital Signage tab.</p> <p>For the DMM integration, you must provide the MAC ID of the DMP device.</p>
5	Create a content link for the signage content.	“Adding the Content Links” section on page 10-6
6	Add sequence to the added content link and provide the duration of display.	“Adding Sequence” section on page 10-9

1. Locations can be mean either conference rooms, floor plan, or a building.

**Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)**

**Note**

There should be no entry of ADAPTER\_INSTANCE\_ID of the DMP Bean (5004) in the adapter tables of the database, if the DMM adaptor is to be used.'

## Smart+Connected GA Scenarios

- [Scenario 1: Displaying Green Advisor Content on the Digital Signage/IEC, page 13-15](#)
- [Scenario 2: Displaying the Telepresence Content, page 13-16](#)

### Scenario 1: Displaying Green Advisor Content on the Digital Signage/IEC

Order	Tasks	See
1	Import a DMP certificate for the DMP if it uses HTTPS.	“Importing SSL Certificates” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
2	Create location(s) <sup>1</sup> as required in the location hierarchy.	“Adding Locations” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
3	Create a device ‘Digital Media Player’ for the required location(s).	“Adding Devices” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
4	Configure adapter properties for DMP Bean in the database.	“Configuring Adapter Properties” section in the <i>Cisco Smart+Connected Meeting Spaces &amp; Cisco Smart+Connected Digital Signage Installation Guide</i>
5	Create a green advisor (GA) content for the required location(s).	<a href="#">“Adding a Green Fact” section on page 11-1</a>
6	Create a content link for the added GA content.	<a href="#">“Adding the Content Links” section on page 10-6</a>
7	Add sequence to the added content link and provide the duration of display.	<a href="#">“Adding Sequence” section on page 10-9</a>

## Send documentation comments to [scc-docfeedback@cisco.com](mailto:scc-docfeedback@cisco.com)

Order	Tasks	See
8	Create a new display of the GA content to appear on the digital signage/IEC by choosing the appropriate widget.	<a href="#">“Creating a New Display” section on page 11-6</a>
9	Display data for the widgets energy, water, and gas consumption in one of the following ways: <ul style="list-style-type: none"> <li>• Set up data collection.</li> <li>• Manually configure data using the usage data.</li> </ul>	<ul style="list-style-type: none"> <li>• To set up data collection, see the “Setting up Data Collection” section in the <i>Cisco Smart+Connected Digital Signage Installation Guide</i></li> <li>• To manually configure data using the usage data, see the <a href="#">“Adding the Usage Data” section on page 11-4</a></li> </ul>

1. Locations can be mean either conference rooms, floor plan, or a building.

## Scenario 2: Displaying the Telepresence Content

Order	Tasks	See
1	Create a new display by assigning the widget as ‘Telepresence’.	<a href="#">“Creating a New Display” section on page 11-6</a>
2	Configure the telepresence content using the usage data.	<a href="#">“Adding the Usage Data” section on page 11-4</a>
3	Create a content link for the telepresence content.	<a href="#">“Adding the Content Links” section on page 10-6</a>
4	Add sequence to the added content link and provide the duration of display.	<a href="#">“Adding Sequence” section on page 10-9</a>