



A

about

- cluster server setup [1-8](#)
- colocated server setup [1-6](#)
- database script for JBoss [3-3](#)
- database script for WebLogic [2-5](#)
- JMS properties file for JBoss [3-17](#)
- JMS properties file for WebLogic [2-12](#)
- LDAP properties file for JBoss [3-17](#)
- LDAP properties file for WebLogic [2-10](#)
- mod_cluster [3-35](#)
- non-cluster server setup [1-6](#)
- notification properties file for JBoss [3-18](#)
- notification service properties file for WebLogic [2-15](#)
- properties file for JBoss [3-17](#)
- properties file for WebLogic [2-10](#)
- reservation properties file for JBoss [3-18](#)
- reservation properties file for WebLogic [2-13](#)
- Smart+Connected PS [1-1](#)
- system architecture [1-1](#)

adapter

- about [4-16](#)
- sample configuration [4-16](#)

C

cluster

- configuring Apache Jackrabbit on JBoss [3-43](#)
- configuring Apache Jackrabbit on WebLogic [2-49](#)
- configuring cluster for JBoss [3-37](#)
- configuring JBoss profile [3-32](#)
- configuring on WebLogic [2-36](#)

- configuring proxy or admin server on WebLogic [2-34](#)
- deploying Apache Jackrabbit on WebLogic [2-46](#)
- example [2-29](#)
- installing application [2-30](#)
- installing mod_cluster for JBoss [3-35](#)
- installing on JBoss [3-29](#)
- installing on WebLogic [2-28](#)
- overview [1-8](#)
- setting up Apache Jackrabbit on JBoss [3-42](#)
- starting server for JBoss [3-45](#)

colocated

- deploying Apache Jackrabbit on JBoss [3-26](#)
- deploying Apache Jackrabbit on WebLogic [2-21, 2-42, 3-22, 3-38](#)
- installing on WebLogic [2-2](#)
- overview [1-6](#)

configuring

- adapter [4-13](#)
 - adapter properties [4-14](#)
 - adapter to location [4-16](#)
- BIRT engine for WebLogic [2-9](#)
- cluster for JBoss [3-37](#)
- cluster on WebLogic [2-36](#)
- customizing branding image [4-19](#)
- device [4-4, 4-8, 4-13](#)
- JMS for WebLogic [2-8](#)
- location [4-1](#)
- logging for WebLogic [2-10](#)
- proxy or admin server on WebLogic, for cluster [2-34](#)
- push-to-phone for JBoss [3-20](#)
- push-to-phone for WebLogic [2-20](#)
- room types [4-13](#)

Send documentation comments to scc-docfeedback@cisco.com

D

database script

- executing for JBoss [3-5](#)
- executing for WebLogic [2-5](#)

JBoss

- about [3-3](#)

WebLogic

- about [2-5](#)

device

- adding [4-8](#)
- configuring [4-4](#)
- deleting [4-13](#)

I

installing

- cluster server setup [2-30](#)
- executable file [2-3](#)
- JBoss
 - cluster server setup [3-29](#)
 - configuring Apache Jackrabbit for cluster [3-43](#)
 - configuring cluster [3-37](#)
 - configuring JBoss profile for cluster [3-32](#)
 - deploying Apache Jackrabbit for non-cluster or collocated [3-26](#)
 - importing SSL certificate [3-27](#)
 - installing mod_cluster for cluster [3-35](#)
 - non-cluster server setup [3-2](#)
 - prerequisite [3-1](#)
 - setting up Apache Jackrabbit for cluster [3-42](#)
 - setting up push-to-push feature [3-20](#)
 - setting up run parameter [3-19](#)
 - starting server [3-45](#)
 - updating LDAP and JMS properties files [3-18](#)
 - updating reservation and notification properties files [3-19](#)
- process [2-3](#)
- verifying for JBoss [3-28, 3-46](#)

- verifying for WebLogic [2-27, 2-51](#)

WebLogic [2-3](#)

- cluster server setup [2-28](#)
- colocated or non-cluster server setup [2-2](#)
- configuring Apache Jackrabbit for cluster [2-49](#)
- configuring audio notification [2-4](#)
- configuring cluster [2-36](#)
- configuring database [2-4](#)
- configuring JMS [2-8](#)
- configuring logging [2-10](#)
- configuring proxy or admin server for cluster [2-34](#)
- creating domain [2-5](#)
- deploying Apache Jackrabbit for cluster [2-46](#)
- deploying Apache Jackrabbit for non-cluster or collocated [2-21, 2-42, 3-22, 3-38](#)
- deploying Smart+Connected PS for cluster [2-47](#)
- deploying Smart+Connected PS for non-cluster or collocated [2-26](#)
- example of cluster server setup [2-29](#)
- extending domain [2-7](#)
- importing SSL certificate [2-26](#)
- prerequisite [2-1](#)
- restarting server [2-27](#)
- setting up BIRT engine [2-9](#)
- setting up push-to-push feature [2-20](#)
- starting managed server [2-48](#)
- starting server [2-8](#)
- updating domain configuration [2-16](#)
- updating LDAP and JMS properties files [2-15](#)
- updating reservation and notification properties files [2-16](#)

J

JBoss

- application server details [3-1](#)
- configuring profile [3-32](#)
- database server details [3-1](#)
- setting up run parameter [3-19](#)

Send documentation comments to scc-docfeedback@cisco.com

verifying network configuration [3-2](#)

JMS

configuring for WebLogic [2-8](#)

L

location

adding location [4-1, 4-2](#)

configuring [4-1](#)

location name [4-2](#)

location type [4-2](#)

N

non-cluster

deploying Apache Jackrabbit on JBoss [3-26](#)

deploying Apache Jackrabbit on WebLogic [2-21, 2-42, 3-22, 3-38](#)

installing on JBoss [3-2](#)

installing on WebLogic [2-2](#)

overview [1-6](#)

O

overview

cluster server setup [1-8](#)

colocated server setup [1-6](#)

JMS properties file for JBoss [3-17](#)

JMS properties file for WebLogic [2-12](#)

LDAP properties file for JBoss [3-17](#)

LDAP properties file for WebLogic [2-10](#)

mod_cluster [3-35](#)

non-cluster server setup [1-6](#)

notification properties file for JBoss [3-18](#)

notification service properties file for WebLogic [2-15](#)

properties file for JBoss [3-17](#)

properties file for WebLogic [2-10](#)

reservation properties file for JBoss [3-18](#)

reservation properties file for WebLogic [2-13](#)

Smart+Connected PS [1-1](#)

P

prerequisite

for installing on JBoss [3-1](#)

for installing on WebLogic [2-1](#)

properties file

JBoss

about [3-17](#)

updating LDAP and JMS properties files for JBoss [3-18](#)

updating LDAP and JMS properties files for WebLogic [2-15](#)

updating reservation and notification properties files for JBoss [3-19](#)

updating reservation and notification properties files for WebLogic [2-16](#)

WebLogic

about [2-10](#)

R

restarting

WebLogic server [2-27](#)

S

server setup

cluster [1-8](#)

colocated [1-6](#)

non-cluster [1-6](#)

type [1-5](#)

Smart+Connected PS

about [1-1](#)

accessing or verifying for JBoss [3-28, 3-46](#)

accessing or verifying for WebLogic [2-27, 2-51](#)

acronyms and abbreviations [1-3](#)

cluster server setup [1-8](#)

colocated server setup [1-6](#)

Send documentation comments to scc-docfeedback@cisco.com

deploying on WebLogic, for cluster [2-47](#)

deploying on WebLogic, for non-cluster or
colocated [2-26](#)

installing application [2-3, 2-21, 2-42, 3-22, 3-38](#)

installing on JBoss [3-1](#)

cluster [3-29](#)

colocated or non-cluster [3-2](#)

installing on WebLogic

cluster [2-28](#)

colocated or non-cluster [2-2](#)

non-cluster server setup [1-6](#)

server setup type [1-5](#)

system architecture [1-1](#)

SSL certificate

importing for JBoss [3-27](#)

importing for WebLogic [2-26](#)

starting

cluster for JBoss [3-45](#)

JBoss server for colocated or non-cluster [3-28](#)

proxy server for JBoss [3-45](#)

WebLogic server [2-8](#)

W

WebLogic

configuring audio notification [2-4](#)

configuring database [2-4](#)

creating domain [2-5](#)

extending domain [2-7](#)

restarting server [2-27](#)

starting server [2-8](#)

updating domain configuration [2-16](#)