



## INDEX

---

### A

aaa accounting dot1x command [2-1](#)  
aaa authentication dot1x command [2-3](#)  
aaa authorization network command [2-5](#)  
AAA methods [2-3](#)  
abort command [2-770](#)  
access control entries  
    See ACEs  
access control lists  
    See ACLs  
access groups  
    IP [2-145](#)  
    MAC, displaying [2-530](#)  
access list, IPv6 [2-210](#)  
access map configuration mode [2-277](#)  
access mode [2-712](#)  
access ports [2-712](#)  
ACEs [2-83](#), [2-345](#)  
ACLs  
    deny [2-81](#)  
    displaying [2-392](#)  
    for non-IP protocols [2-255](#)  
    IP [2-145](#)  
    matching [2-277](#)  
    on Layer 2 interfaces [2-145](#)  
    permit [2-343](#)  
action command [2-6](#)  
aggregate-port learner [2-332](#)  
allowed VLANs [2-732](#)  
apply command [2-770](#)  
archive copy-sw command [2-8](#)  
archive download-sw command [2-11](#)

archive tar command [2-15](#)  
archive upload-sw command [2-18](#)  
arp (boot loader) command [A-2](#)  
arp access-list command [2-20](#)  
authentication failed VLAN  
    See dot1x auth-fail vlan  
auth-fail max-attempts  
    See dot1x auth-fail max-attempts  
auth-fail vlan  
    See dot1x auth-fail vlan  
authorization state of controlled port [2-114](#)  
autonegotiation of duplex mode [2-123](#)  
auto qos voip command [2-22](#)

---

### B

BackboneFast, for STP [2-637](#)  
backup interfaces  
    configuring [2-707](#)  
    displaying [2-454](#)  
boot (boot loader) command [A-3](#)  
boot auto-copy-sw command [2-26](#)  
boot auto-download-sw command [2-27](#)  
boot config-file command [2-29](#)  
boot enable-break command [2-30](#)  
boot helper command [2-31](#)  
boot helper-config file command [2-32](#)  
booting  
    Cisco IOS image [2-35](#)  
    displaying environment variables [2-401](#)  
    interrupting [2-30](#)  
    manually [2-33](#)

## boot loader

- accessing [A-1](#)

- booting

- Cisco IOS image [A-3](#)

- helper image [2-31](#)

- directories

- creating [A-19](#)

- displaying a list of [A-8](#)

- removing [A-23](#)

- displaying

- available commands [A-13](#)

- memory heap utilization [A-14](#)

- version [A-30](#)

- environment variables

- described [A-24](#)

- displaying settings [A-24](#)

- location of [A-25](#)

- setting [A-24](#)

- unsetting [A-28](#)

- files

- copying [A-6](#)

- deleting [A-7](#)

- displaying a list of [A-8](#)

- displaying the contents of [A-5](#), [A-20](#), [A-27](#)

- renaming [A-21](#)

- file system

- formatting [A-11](#)

- initializing flash [A-10](#)

- running a consistency check [A-12](#)

- prompt [A-1](#)

- resetting the system [A-22](#)

- boot manual command [2-33](#)

- boot private-config-file command [2-34](#)

- boot system command [2-35](#)

- BPDU filtering, for spanning tree [2-638](#), [2-672](#)

- BPDU guard, for spanning tree [2-640](#), [2-672](#)

- broadcast storm control [2-693](#)

---

**C**

- cat (boot loader) command [A-5](#)

- CDP, enabling protocol tunneling for [2-236](#)

- channel-group command [2-37](#)

- channel-protocol command [2-41](#)

- Cisco SoftPhone

- auto-QoS configuration [2-22](#)

- trusting packets sent from [2-318](#)

- class command [2-42](#)

- class-map command [2-44](#)

- class maps

- creating [2-44](#)

- defining the match criteria [2-279](#)

- displaying [2-406](#)

- class of service

- See CoS

- clear dot1x command [2-46](#)

- clear eap command [2-47](#)

- clear errdisable interface [2-48](#)

- clear ip arp inspection log command [2-49](#)

- clear ip arp inspection statistics command [2-50](#)

- clear ipc command [2-55](#)

- clear ip dhcp snooping database command [2-51](#), [2-53](#)

- clear ipv6 dhcp conflict command [2-56](#)

- clear l2protocol-tunnel counters command [2-57](#)

- clear lacp command [2-58](#)

- clear logging command [2-59](#)

- clear mac address-table command [2-60](#), [2-61](#)

- clear pagp command [2-62](#)

- clear port-security command [2-63](#)

- clear spanning-tree counters command [2-65](#)

- clear spanning-tree detected-protocols command [2-66](#)

- clear vmps statistics command [2-67](#)

- clear vtp counters command [2-68](#)

- command modes defined [1-2](#)

- configuration files

- password recovery disable considerations [A-1](#)

- specifying the name [2-29](#), [2-34](#)

configuring multiple interfaces [2-141](#)

config-vlan mode

    commands [2-756](#)

    description [1-5](#)

    entering [2-755](#)

    summary [1-2](#)

copy (boot loader) command [A-6](#)

copy logging onboard command [2-69](#)

CoS

    assigning default value to incoming packets [2-288](#)

    assigning to Layer 2 protocol packets [2-239](#)

    overriding the incoming value [2-288](#)

CoS-to-DSCP map [2-292](#)

CPU ASIC statistics, displaying [2-407](#)

crashinfo files [2-132](#)

---

## D

debug auto qos command [B-2](#)

debug backup command [B-4](#)

debug dot1x command [B-5](#)

debug dtp command [B-6](#)

debug eap command [B-7](#)

debug etherchannel command [B-8](#)

debug fastethernet command [B-9](#)

debug interface command [B-12](#)

debug ip dhcp snooping command [B-10](#)

debug ip igmp filter command [B-13](#)

debug ip igmp max-groups command [B-14](#)

debug ip igmp snooping command [B-15](#)

debug ip verify source packet command [B-11](#)

debug lacp command [B-16](#)

debug mac-notification command [B-17](#)

debug matm command [B-18](#)

debug matm move update command [B-19](#)

debug monitor command [B-20](#)

debug mvrdbg command [B-21](#)

debug nvram command [B-22](#)

debug pagp command [B-23](#)

debug platform acl command [B-24](#)

debug platform backup interface command [B-25](#)

debug platform cli-redirect main command [B-26](#)

debug platform configuration command [B-27](#)

debug platform cpu-queues command [B-28](#)

debug platform device-manager command [B-30](#)

debug platform dot1x command [B-31](#)

debug platform etherchannel command [B-32](#)

debug platform fallback-bridging command [B-33](#)

debug platform ip arp inspection command [B-34](#)

debug platform ipc command [B-43](#)

debug platform ip dhcp command [B-35](#)

debug platform ip igmp snooping command [B-36](#)

debug platform ip multicast command [B-38](#)

debug platform ip unicast command [B-40](#)

debug platform ip wccp command [B-42](#)

debug platform led command [B-44](#)

debug platform matm command [B-45](#)

debug platform messaging application command [B-46](#)

debug platform phy command [B-47](#)

debug platform pm command [B-49](#)

debug platform port-asic command [B-51](#)

debug platform port-security command [B-52](#)

debug platform qos-acl-tcam command [B-53](#)

debug platform remote-commands command [B-54](#)

debug platform resource-manager command [B-55](#)

debug platform snmp command [B-56](#)

debug platform span command [B-57](#)

debug platform stack-manager command [B-58](#)

debug platform supervisor-asic command [B-59](#)

debug platform sw-bridge command [B-60](#)

debug platform tcam command [B-61](#)

debug platform udd command [B-64](#)

debug platform vlan command [B-65](#)

debug pm command [B-66](#)

debug port-security command [B-68](#)

debug qos-manager command [B-69](#)

debug spanning-tree backbonefast command [B-72](#)

debug spanning-tree bpdu command [B-73](#)

- debug spanning-tree bpdu-opt command [B-74](#)
- debug spanning-tree command [B-70](#)
- debug spanning-tree mstp command [B-75](#)
- debug spanning-tree switch command [B-77](#)
- debug spanning-tree uplinkfast command [B-79](#)
- debug sw-vlan command [B-80](#)
- debug sw-vlan ifs command [B-82](#)
- debug sw-vlan notification command [B-83](#)
- debug sw-vlan vtp command [B-85](#)
- debug udd command [B-87](#)
- debug vqpc command [B-89](#)
- define interface-range command [2-71](#)
- delete (boot loader) command [A-7](#)
- delete command [2-73](#)
- deny (ARP access-list configuration) command [2-74](#)
- deny (IPv6) command [2-76](#)
- deny command [2-81](#)
- detect mechanism, causes [2-124](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-173](#)
  - enabling
    - on a VLAN [2-179](#)
    - option 82 [2-171, 2-173](#)
    - trust on an interface [2-177](#)
  - error recovery timer [2-128](#)
  - rate limiting [2-176](#)
- DHCP snooping binding database
  - binding file, configuring [2-169](#)
  - bindings
    - adding [2-167](#)
    - deleting [2-167](#)
    - displaying [2-475](#)
  - clearing database agent statistics [2-51, 2-53](#)
  - database agent, configuring [2-169](#)
  - displaying
    - binding entries [2-475](#)
    - database agent status [2-477, 2-479](#)
  - renewing [2-373](#)
- dir (boot loader) command [A-8](#)
- directories, deleting [2-73](#)
- domain name, VTP [2-781, 2-785](#)
- dot1x auth-fail max-attempts [2-93](#)
- dot1x auth-fail vlan [2-95](#)
- dot1x command [2-91](#)
- dot1x control-direction command [2-97](#)
- dot1x critical global configuration command [2-99](#)
- dot1x critical interface configuration command [2-101](#)
- dot1x default command [2-103](#)
- dot1x fallback command [2-104](#)
- dot1x guest-vlan command [2-105](#)
- dot1x host-mode command [2-107](#)
- dot1x initialize command [2-108](#)
- dot1x mac-auth-bypass command [2-109](#)
- dot1x max-reauth-req command [2-111](#)
- dot1x max-req command [2-112](#)
- dot1x pae command [2-113](#)
- dot1x port-control command [2-114](#)
- dot1x re-authenticate command [2-116](#)
- dot1x reauthentication command [2-117](#)
- dot1x timeout command [2-118](#)
- dot1x violation-mode command [2-120](#)
- dropping packets, with ACL matches [2-6](#)
- drop threshold, Layer 2 protocol tunneling [2-236](#)
- DSCP-to-CoS map [2-292](#)
- DSCP-to-DSCP-mutation map [2-292](#)
- DTP [2-713](#)
- DTP flap
  - error detection for [2-124](#)
  - error recovery timer [2-128](#)
- DTP negotiation [2-717](#)
- dual IPv4 and IPv6 templates [2-338](#)
- duplex command [2-122](#)
- dynamic-access ports
  - configuring [2-703](#)
  - restrictions [2-704](#)

dynamic ARP inspection

- ARP ACLs
  - apply to a VLAN [2-153](#)
  - define [2-20](#)
  - deny packets [2-74](#)
  - display [2-396](#)
  - permit packets [2-336](#)
- clear
  - log buffer [2-49](#)
  - statistics [2-50](#)
- display
  - ARP ACLs [2-396](#)
  - configuration and operating state [2-470](#)
  - log buffer [2-470](#)
  - statistics [2-470](#)
  - trust state and rate limit [2-470](#)
- enable per VLAN [2-163](#)
- error detection for [2-124](#)
- error recovery timer [2-128](#)
- log buffer
  - clear [2-49](#)
  - configure [2-157](#)
  - display [2-470](#)
- rate-limit incoming ARP packets [2-155](#)
- statistics
  - clear [2-50](#)
  - display [2-470](#)
- trusted interface state [2-159](#)
- type of packet logged [2-164](#)
- validation checks [2-161](#)

dynamic auto VLAN membership mode [2-712](#)

dynamic desirable VLAN membership mode [2-712](#)

Dynamic Host Configuration Protocol (DHCP)

- See DHCP snooping

Dynamic Trunking Protocol

- See DTP

---

## E

EAP-request/identity frame

- maximum number to send [2-112](#)
- response time before retransmitting [2-118](#)

encapsulation methods [2-732](#)

environment variables, displaying [2-401](#)

errdisable detect cause command [2-124](#)

errdisable detect cause small-frame comand [2-126](#)

errdisable recovery cause small-frame [2-131](#)

errdisable recovery command [2-128](#)

error conditions, displaying [2-442](#)

error disable detection [2-124](#)

error-disabled interfaces, displaying [2-454](#)

EtherChannel

- assigning Ethernet interface to channel group [2-37](#)
- creating port-channel logical interface [2-139](#)
- debug EtherChannel/PAGP, display [B-8](#)
- debug platform-specific events, display [B-32](#)
- displaying [2-445](#)
- enabling Layer 2 protocol tunneling for
  - LACP [2-237](#)
  - PAGP [2-237](#)
  - UDLD [2-237](#)
- interface information, displaying [2-454](#)

LACP

- clearing channel-group information [2-58, 2-59](#)
- debug messages, display [B-16](#)
- displaying [2-516](#)
- modes [2-37](#)
- port priority for hot-standby ports [2-240](#)
- restricting a protocol [2-41](#)
- system priority [2-242](#)

## EtherChannel (continued)

## PAgP

- aggregate-port learner [2-332](#)
- clearing channel-group information [2-62](#)
- debug messages, display [B-23](#)
- displaying [2-576](#)
- error detection for [2-124](#)
- error recovery timer [2-128](#)
- learn method [2-332](#)
- modes [2-37](#)
- physical-port learner [2-332](#)
- priority of interface for transmitted traffic [2-334](#)

Ethernet controller, internal register display [2-409, 2-416](#)

Ethernet Management port, debugging [B-9](#)

Ethernet statistics, collecting [2-375](#)

exception crashinfo command [2-132, 2-137](#)

exit command [2-770](#)

## extended-range VLANs

- and allowed VLAN list [2-732](#)
- and pruning-eligible list [2-732](#)
- configuring [2-755](#)

extended system ID for STP [2-646](#)

**F**

fallback profile command [2-133](#)

fallback profiles, displaying [2-448](#)

fan information, displaying [2-438](#)

file name, VTP [2-781](#)

files, deleting [2-73](#)

flash\_init (boot loader) command [A-10](#)

## Flex Links

- configuring [2-707](#)
- displaying [2-454](#)

flowcontrol command [2-135](#)

format (boot loader) command [A-11](#)

forwarding packets, with ACL matches [2-6](#)

forwarding results, display [C-7](#)

frame forwarding information, displaying [C-7](#)

front-end controller counter and status information [C-9](#)

fsck (boot loader) command [A-12](#)

**G**

global configuration mode [1-2, 1-4](#)

**H**

hardware ACL statistics [2-392](#)

health monitoring diagnostic tests [2-84](#)

help (boot loader) command [A-13](#)

hierarchical policy maps [2-351](#)

host connection, port configuration [2-711](#)

host ports, private VLANs [2-715](#)

**I**

IEEE 802.1Q trunk ports and native VLANs [2-772](#)

## IEEE 802.1Q tunnel ports

- configuring [2-712](#)
- displaying [2-428](#)
- limitations [2-713](#)

## IEEE 802.1x

- and switchport modes [2-713](#)
- violation error recovery [2-128](#)
- See also port-based authentication

## IGMP filters

- applying [2-182](#)
- debug messages, display [B-13](#)

IGMP groups, setting maximum [2-184](#)

IGMP maximum groups, debugging [B-14](#)

## IGMP profiles

- creating [2-186](#)
- displaying [2-482](#)

- IGMP snooping
  - adding ports as a static member of a group [2-202](#)
  - displaying [2-483, 2-488, 2-490](#)
  - enabling [2-188](#)
  - enabling the configurable-leave timer [2-190](#)
  - enabling the Immediate-Leave feature [2-199](#)
  - flooding query count [2-196](#)
  - interface topology change notification behavior [2-198](#)
  - multicast table [2-486](#)
  - querier [2-192](#)
  - query solicitation [2-196](#)
  - report suppression [2-194](#)
  - switch topology change notification behavior [2-196](#)
- images
  - See software images
- Immediate-Leave processing
  - IGMP [2-199](#)
  - IPv6 [2-232](#)
  - MVR [2-328](#)
- interface configuration mode [1-2, 1-4](#)
- interface port-channel command [2-139](#)
- interface range command [2-141](#)
- interface-range macros [2-71](#)
- interfaces
  - assigning Ethernet interface to channel group [2-37](#)
  - configuring [2-122](#)
  - configuring multiple [2-141](#)
  - creating port-channel logical [2-139](#)
  - debug messages, display [B-12](#)
  - disabling [2-623](#)
  - displaying the MAC address table [2-542](#)
  - restarting [2-623](#)
- interface speed, configuring [2-683](#)
- interface vlan command [2-143](#)
- internal registers, displaying [2-409, 2-416, 2-419](#)
- Internet Group Management Protocol
  - See IGMP
- invalid GBIC
  - error detection for [2-124](#)
  - error recovery timer [2-128](#)
- ip access-group command [2-145](#)
- ip address command [2-148](#)
- IP addresses, setting [2-148](#)
- IP address matching [2-277](#)
- ip admission command [2-150](#)
- ip admission name proxy http command [2-151](#)
- ip arp inspection filter vlan command [2-153](#)
- ip arp inspection limit command [2-155](#)
- ip arp inspection log-buffer command [2-157](#)
- ip arp inspection trust command [2-159](#)
- ip arp inspection validate command [2-161](#)
- ip arp inspection vlan command [2-163](#)
- ip arp inspection vlan logging command [2-164](#)
- IP DHCP snooping
  - See DHCP snooping
  - ip dhcp snooping binding command [2-167](#)
  - ip dhcp snooping command [2-166](#)
  - ip dhcp snooping database command [2-169](#)
  - ip dhcp snooping information option allow-untrusted command [2-173](#)
  - ip dhcp snooping information option command [2-171](#)
  - ip dhcp snooping information option format remote-id command [2-175](#)
  - ip dhcp snooping limit rate command [2-176](#)
  - ip dhcp snooping trust command [2-177](#)
  - ip dhcp snooping verify command [2-178](#)
  - ip dhcp snooping vlan command [2-179](#)
  - ip dhcp snooping vlan information option format-type circuit-id string command [2-180](#)
  - ip igmp filter command [2-182](#)
  - ip igmp max-groups command [2-184](#)
  - ip igmp profile command [2-186](#)
  - ip igmp snooping command [2-188](#)
  - ip igmp snooping last-member-query-interval command [2-190](#)
  - ip igmp snooping querier command [2-192](#)
  - ip igmp snooping report-suppression command [2-194](#)

ip igmp snooping tcn command [2-196](#)  
 ip igmp snooping tcn flood command [2-198](#)  
 ip igmp snooping vlan immediate-leave command [2-199](#)  
 ip igmp snooping vlan mrouter command [2-200](#)  
 ip igmp snooping vlan static command [2-202](#)  
 IP multicast addresses [2-325](#)  
 IP phones  
     auto-QoS configuration [2-22](#)  
     trusting packets sent from [2-318](#)  
 IP-precedence-to-DSCP map [2-292](#)  
 ip snap forwarding command [2-204](#)  
 ip source binding command [2-205](#)  
 IP source guard  
     disabling [2-209](#)  
     displaying  
         binding entries [2-492](#)  
         configuration [2-494](#)  
         dynamic binding entries only [2-475](#)  
     enabling [2-209](#)  
     static IP source bindings [2-205](#)  
 ip ssh command [2-207](#)  
 IPv6 access list, deny conditions [2-76](#)  
 ipv6 access-list command [2-210](#)  
 ipv6 address dhcp command [2-212](#)  
 ipv6 dhcp client request vendor command [2-213](#)  
 ipv6 dhcp ping packets command [2-214](#)  
 ipv6 dhcp pool command [2-216](#)  
 ipv6 dhcp server command [2-218](#)  
 ipv6 mld snooping command [2-220](#)  
 ipv6 mld snooping last-listener-query count  
 command [2-222](#)  
 ipv6 mld snooping last-listener-query-interval  
 command [2-224](#)  
 ipv6 mld snooping listener-message-suppression  
 command [2-226](#)  
 ipv6 mld snooping robustness-variable command [2-228](#)  
 ipv6 mld snooping tcn command [2-230](#)  
 ipv6 mld snooping vlan command [2-232](#)  
 IPv6 SDM template [2-376](#)  
 ipv6 traffic-filter command [2-234](#)

ip verify source command [2-209](#)

---

## J

jumbo frames  
     See MTU

---

## L

l2protocol-tunnel command [2-236](#)  
 l2protocol-tunnel cos command [2-239](#)  
 LACP  
     See EtherChannel  
 lacp port-priority command [2-240](#)  
 lacp system-priority command [2-242](#)  
 Layer 2 mode, enabling [2-701](#)  
 Layer 2 protocol ports, displaying [2-513](#)  
 Layer 2 protocol-tunnel  
     error detection for [2-124](#)  
     error recovery timer [2-128](#)  
 Layer 2 protocol tunnel counters [2-57](#)  
 Layer 2 protocol tunneling error recovery [2-237](#)  
 Layer 2 traceroute  
     IP addresses [2-746](#)  
     MAC addresses [2-743](#)  
 Layer 3 mode, enabling [2-701](#)  
 line configuration mode [1-3, 1-6](#)  
 Link Aggregation Control Protocol  
     See EtherChannel  
 link flap  
     error detection for [2-124](#)  
     error recovery timer [2-128](#)  
 link state group command [2-244](#)  
 link state track command [2-246](#)  
 load-distribution methods for EtherChannel [2-353](#)  
 location (global configuration) command [2-247](#)  
 location (interface configuration) command [2-249](#)  
 logging file command [2-251](#)



logical interface [2-139](#)  
 loopback error  
   detection for [2-124](#)  
   recovery timer [2-128](#)  
 loop guard, for spanning tree [2-648, 2-652](#)

## M

mac access-group command [2-253](#)  
 MAC access-groups, displaying [2-530](#)  
 MAC access list configuration mode [2-255](#)  
 mac access-list extended command [2-255](#)  
 MAC access lists [2-81](#)  
 MAC addresses  
   disabling MAC address learning per VLAN [2-258](#)  
   displaying  
     aging time [2-536](#)  
     all [2-534](#)  
     dynamic [2-540](#)  
     MAC address-table move updates [2-545](#)  
     notification settings [2-544, 2-547](#)  
     number of addresses in a VLAN [2-538](#)  
     per interface [2-542](#)  
     per VLAN [2-551](#)  
     static [2-549](#)  
     static and dynamic entries [2-532](#)  
   dynamic  
     aging time [2-257](#)  
     deleting [2-60](#)  
     displaying [2-540](#)  
   enabling MAC address notification [2-262](#)  
   enabling MAC address-table move update [2-260](#)  
   matching [2-277](#)  
   persistent stack [2-691](#)  
   static  
     adding and removing [2-264](#)  
     displaying [2-549](#)  
     dropping on an interface [2-265](#)  
   tables [2-534](#)

MAC address notification, debugging [B-17](#)  
 mac address-table aging-time [2-253, 2-277](#)  
 mac address-table aging-time command [2-257](#)  
 mac address-table learning command [2-258](#)  
 mac address-table move update command [2-260](#)  
 mac address-table notification command [2-262](#)  
 mac address-table static command [2-264](#)  
 mac address-table static drop command [2-265](#)  
 MAC frames  
   See MTU  
 macro apply command [2-267](#)  
 macro description command [2-270](#)  
 macro global command [2-271](#)  
 macro global description command [2-274](#)  
 macro name command [2-275](#)  
 macros  
   adding a description [2-270](#)  
   adding a global description [2-274](#)  
   applying [2-271](#)  
   creating [2-275](#)  
   displaying [2-578](#)  
   interface range [2-71, 2-141](#)  
   specifying parameter values [2-271](#)  
   tracing [2-271](#)  
 maps  
   QoS  
     defining [2-292](#)  
     displaying [2-561](#)  
   VLAN  
     creating [2-767](#)  
     defining [2-277](#)  
     displaying [2-614](#)  
 match (access-map configuration) command [2-277](#)  
 match (class-map configuration) command [2-279](#)  
 maximum transmission unit  
   See MTU  
 mdix auto command [2-282](#)  
 memory (boot loader) command [A-14](#)  
 mgmt\_clr (boot loader) command [A-16](#)

- mgmt\_init (boot loader) command [A-17, A-18](#)
- mkdir (boot loader) command [A-19](#)
- MLD snooping
  - configuring [2-226, 2-228](#)
  - configuring queries [2-222, 2-224](#)
  - configuring topology change notification [2-230](#)
  - displaying [2-503, 2-505, 2-507, 2-509](#)
  - enabling [2-220](#)
  - enabling on a VLAN [2-232](#)
- mls qos aggregate-policer command [2-286](#)
- mls qos command [2-284](#)
- mls qos cos command [2-288](#)
- mls qos dscp-mutation command [2-290](#)
- mls qos map command [2-292](#)
- mls qos queue-set output buffers command [2-296](#)
- mls qos queue-set output threshold command [2-298](#)
- mls qos rewrite ip dscp command [2-300](#)
- mls qos srr-queue input bandwidth command [2-302](#)
- mls qos srr-queue input buffers command [2-304](#)
- mls qos-srr-queue input cos-map command [2-306](#)
- mls qos srr-queue input dscp-map command [2-308](#)
- mls qos srr-queue input priority-queue command [2-310](#)
- mls qos srr-queue input threshold command [2-312](#)
- mls qos-srr-queue output cos-map command [2-314](#)
- mls qos srr-queue output dscp-map command [2-316](#)
- mls qos trust command [2-318](#)
- mls qos vlan-based command [2-320](#)
- mode, MVR [2-325](#)
- Mode button, and password recovery [2-379](#)
- modes, commands [1-2](#)
- monitor session command [2-321](#)
- more (boot loader) command [A-20](#)
- MSTP
  - displaying [2-591, 2-592, 2-593](#)
  - interoperability [2-66](#)
- MSTP (continued)
  - link type [2-650](#)
  - MST region
    - aborting changes [2-656](#)
    - applying changes [2-656](#)
    - configuration name [2-656](#)
    - configuration revision number [2-656](#)
    - current or pending display [2-656](#)
    - displaying [2-591, 2-592, 2-593](#)
    - MST configuration mode [2-656](#)
    - VLANs-to-instance mapping [2-656](#)
  - path cost [2-658](#)
  - protocol mode [2-654](#)
  - restart protocol migration process [2-66](#)
  - root port
    - loop guard [2-648](#)
    - preventing from becoming designated [2-648](#)
    - restricting which can be root [2-648](#)
    - root guard [2-648](#)
  - root switch
    - affects of extended system ID [2-646](#)
    - hello-time [2-661, 2-668](#)
    - interval between BPDU messages [2-662](#)
    - interval between hello BPDU messages [2-661, 2-668](#)
    - max-age [2-662](#)
    - maximum hop count before discarding BPDU [2-663](#)
    - port priority for selection of [2-664](#)
    - primary or secondary [2-668](#)
    - switch priority [2-667](#)
  - state changes
    - blocking to forwarding state [2-675](#)
    - enabling BPDU filtering [2-638, 2-672](#)
    - enabling BPDU guard [2-640, 2-672](#)
    - enabling Port Fast [2-672, 2-675](#)
    - forward-delay time [2-660](#)

## MSTP (continued)

## state changes (continued)

- length of listening and learning states [2-660](#)
- rapid transition to forwarding [2-650](#)
- shutting down Port Fast-enabled ports [2-672](#)

state information display [2-590](#)

## MTU

- configuring size [2-740](#)
- displaying global setting [2-603](#)

## Multicast Listener Discovery

See MLD

multicast group address, MVR [2-328](#)multicast groups, MVR [2-326](#)

## Multicast Listener Discovery

See MLD

multicast router learning method [2-200](#)multicast router ports, configuring [2-200](#)multicast router ports, IPv6 [2-232](#)multicast storm control [2-693](#)multicast VLAN, MVR [2-325](#)

multicast VLAN registration

See MVR

multiple hosts on authorized port [2-107](#)

## Multiple Spanning Tree Protocol

See MSTP

## MVR

- configuring [2-325](#)
- configuring interfaces [2-328](#)
- debug messages, display [B-21](#)
- displaying [2-570](#)
- displaying interface information [2-572](#)
- members, displaying [2-574](#)

mvr (global configuration) command [2-325](#)mvr (interface configuration) command [2-328](#)mvr vlan group command [2-329](#)**N**native VLANs [2-732](#)native VLAN tagging [2-772](#)

## nonnegotiate

DTP messaging [2-717](#)speed [2-683](#)

## non-IP protocols

denying [2-81](#)forwarding [2-343](#)non-IP traffic access lists [2-255](#)

## non-IP traffic forwarding

denying [2-81](#)permitting [2-343](#)non-stop forwarding [2-330](#)normal-range VLANs [2-755, 2-761](#)no vlan command [2-755, 2-765](#)nsf command [2-330](#)**O**

## online diagnostics

configuring health monitoring diagnostic tests [2-84](#)

## displaying

- configured boot-up coverage level [2-423](#)
- current scheduled tasks [2-423](#)
- event logs [2-423](#)
- supported test suites [2-423](#)
- test ID [2-423](#)
- test results [2-423](#)
- test statistics [2-423](#)

## enabling

- scheduling [2-86](#)
- syslog messages [2-84](#)

## online diagnostics (continued)

## global configuration mode

clearing health monitoring diagnostic test schedule [2-84](#)

clearing test-based testing schedule [2-86](#)

setting health monitoring diagnostic testing [2-84](#)

setting test-based testing [2-86](#)

setting up health monitoring diagnostic test schedule [2-84](#)

setting up test-based testing [2-86](#)

removing scheduling [2-86](#)

## scheduled switchover

disabling [2-86](#)

enabling [2-86](#)

setting test interval [2-86](#)

specifying health monitoring diagnostic tests [2-84](#)

starting testing [2-88](#)

**P**

## PAgP

See EtherChannel

pagp learn-method command [2-332](#)

pagp port-priority command [2-334](#)

password, VTP [2-781, 2-785](#)

password-recovery mechanism, enabling and disabling [2-379](#)

permit (ARP access-list configuration) command [2-336](#)

permit (IPv6) command [2-338](#)

permit (MAC access-list configuration) command [2-343](#)

per-VLAN spanning-tree plus

See STP

physical-port learner [2-322](#)

PID, displaying [2-469](#)

PIM-DVMRP, as multicast router learning method [2-200](#)

police aggregate command [2-348](#)

police command [2-346](#)

policed-DSCP map [2-292](#)

policy-map command [2-350](#)

## policy maps

applying to an interface [2-381, 2-387](#)

creating [2-350](#)

displaying [2-581](#)

hierarchical [2-351](#)

## policers

displaying [2-554](#)

for a single class [2-346](#)

for multiple classes [2-286, 2-348](#)

policed-DSCP map [2-292](#)

## traffic classification

defining the class [2-42](#)

defining trust states [2-748](#)

setting DSCP or IP precedence values [2-385](#)

## Port Aggregation Protocol

See EtherChannel

## port-based authentication

AAA method list [2-3](#)

configuring violation modes [2-120](#)

debug messages, display [B-5](#)

enabling guest VLAN supplicant [2-94, 2-104](#)

enabling IEEE 802.1x

globally [2-91](#)

per interface [2-114](#)

guest VLAN [2-105](#)

host modes [2-107](#)

IEEE 802.1x AAA accounting methods [2-1](#)

initialize an interface [2-108](#)

MAC authentication bypass [2-109](#)

manual control of authorization state [2-114](#)

multiple hosts on authorized port [2-107](#)

PAE as authenticator [2-113](#)

periodic re-authentication

enabling [2-117](#)

time between attempts [2-118](#)

quiet period between failed authentication exchanges [2-118](#)

re-authenticating IEEE 802.1x-enabled ports [2-116](#)

resetting configurable IEEE 802.1x parameters [2-103](#)

- port-based authentication (continued)
  - switch-to-authentication server retransmission time [2-118](#)
  - switch-to-client frame-retransmission number [2-111 to 2-112](#)
  - switch-to-client retransmission time [2-118](#)
- port-channel load-balance command [2-353](#)
- Port Fast, for spanning tree [2-675](#)
- port ranges, defining [2-69, 2-71](#)
- ports, debugging [B-66](#)
- ports, protected [2-730](#)
- port security
  - aging [2-724](#)
  - debug messages, display [B-68](#)
  - enabling [2-719](#)
  - violation error recovery [2-128](#)
- port trust states for QoS [2-318](#)
- port types, MVR [2-328](#)
- power information, displaying [2-438](#)
- priority-queue command [2-355](#)
- priority value, stack member [2-600, 2-696](#)
- private-vlan command [2-357](#)
- private-vlan mapping command [2-360](#)
- private VLANs
  - association [2-728](#)
  - configuring [2-357](#)
  - configuring ports [2-715](#)
  - displaying [2-609](#)
  - host ports [2-715](#)
  - mapping
    - configuring [2-728](#)
    - displaying [2-454](#)
  - promiscuous ports [2-715](#)
- privileged EXEC mode [1-2, 1-3](#)
- product identification information, displaying [2-469](#)
- promiscuous ports, private VLANs [2-715](#)
- protected ports, displaying [2-460](#)

- pruning
  - VLANs [2-732](#)
  - VTP
    - displaying interface information [2-454](#)
    - enabling [2-781, 2-785](#)
- pruning-eligible VLAN list [2-734](#)
- PVST+
  - See STP

---

## Q

- QoS
  - auto-QoS
    - configuring [2-22](#)
    - debug messages, display [B-2](#)
    - displaying [2-397](#)
  - class maps
    - creating [2-44](#)
    - defining the match criteria [2-279](#)
    - displaying [2-406](#)
  - defining the CoS value for an incoming packet [2-288](#)
  - displaying configuration information [2-397, 2-553](#)
  - DSCP transparency [2-300](#)
  - DSCP trusted ports
    - applying DSCP-to-DSCP-mutation map to [2-290](#)
    - defining DSCP-to-DSCP-mutation map [2-292](#)
  - egress queues
    - allocating buffers [2-296](#)
    - defining the CoS output queue threshold map [2-314](#)
    - defining the DSCP output queue threshold map [2-316](#)
    - displaying buffer allocations [2-557](#)
    - displaying CoS output queue threshold map [2-561](#)
    - displaying DSCP output queue threshold map [2-561](#)
    - displaying queuing strategy [2-557](#)
    - displaying queue-set settings [2-564](#)

## QoS (continued)

## egress queues (continued)

- enabling bandwidth shaping and scheduling [2-687](#)
- enabling bandwidth sharing and scheduling [2-689](#)
- limiting the maximum output on a port [2-685](#)
- mapping a port to a queue-set [2-362](#)
- mapping CoS values to a queue and threshold [2-314](#)
- mapping DSCP values to a queue and threshold [2-316](#)
- setting maximum and reserved memory allocations [2-298](#)
- setting WTD thresholds [2-298](#)

enabling [2-284](#)

## ingress queues

- allocating buffers [2-304](#)
- assigning SRR scheduling weights [2-302](#)
- defining the CoS input queue threshold map [2-306](#)
- defining the DSCP input queue threshold map [2-308](#)
- displaying buffer allocations [2-557](#)
- displaying CoS input queue threshold map [2-561](#)
- displaying DSCP input queue threshold map [2-561](#)
- displaying queueing strategy [2-557](#)
- displaying settings for [2-555](#)
- enabling the priority queue [2-310](#)
- mapping CoS values to a queue and threshold [2-306](#)
- mapping DSCP values to a queue and threshold [2-308](#)
- setting WTD thresholds [2-312](#)

## maps

- defining [2-292](#), [2-306](#), [2-308](#), [2-314](#), [2-316](#)
- displaying [2-561](#)

## QoS (continued)

## policy maps

- applying an aggregate policer [2-348](#)
- applying to an interface [2-381](#), [2-387](#)
- creating [2-350](#)
- defining policers [2-286](#), [2-346](#)
- displaying policers [2-554](#)
- displaying policy maps [2-581](#)
- hierarchical [2-351](#)
- policed-DSCP map [2-292](#)
- setting DSCP or IP precedence values [2-385](#)
- traffic classifications [2-42](#)
- trust states [2-748](#)

port trust states [2-318](#)queues, enabling the expedite [2-355](#)

## statistics

- in-profile and out-of-profile packets [2-557](#)
- packets enqueued or dropped [2-557](#)
- sent and received CoS values [2-557](#)
- sent and received DSCP values [2-557](#)

trusted boundary for IP phones [2-318](#)VLAN-based [2-320](#)

## quality of service

## See QoS

querytime, MVR [2-325](#)queue-set command [2-362](#)

---

**R**radius-server dead-criteria command [2-363](#)radius-server host command [2-365](#)

## rapid per-VLAN spanning-tree plus

## See STP

## rapid PVST+

## See STP

re-authenticating IEEE 802.1x-enabled ports [2-116](#)

## re-authentication

periodic [2-117](#)time between attempts [2-118](#)

receiver ports, MVR [2-328](#)  
 receiving flow-control packets [2-135](#)  
 recovery mechanism  
     causes [2-128](#)  
     display [2-48, 2-404, 2-440, 2-443](#)  
     timer interval [2-129](#)  
 reload command [2-367](#)  
 remote command [2-369](#)  
 remote-span command [2-371](#)  
 Remote Switched Port Analyzer  
     See RSPAN  
 rename (boot loader) command [A-21](#)  
 renew ip dhcp snooping database command [2-373](#)  
 reset (boot loader) command [A-22](#)  
 reset command [2-770](#)  
 resource templates, displaying [2-586](#)  
 restricted VLAN  
     See dot1x auth-fail vlan  
 rmdir (boot loader) command [A-23](#)  
 rmon collection stats command [2-375](#)  
 root guard, for spanning tree [2-648](#)  
 routed ports  
     IP addresses on [2-149](#)  
     number supported [2-149](#)  
 routing frames  
     See MTU  
 RSPAN  
     configuring [2-321](#)  
     displaying [2-567](#)  
     filter RSPAN traffic [2-321](#)  
     remote-span command [2-371](#)  
     sessions  
         add interfaces to [2-321](#)  
         displaying [2-567](#)  
         start new [2-321](#)

---

## S

scheduled switchover  
     disabling [2-86](#)  
     enabling [2-86](#)  
 SDM mismatch mode [2-377, 2-601](#)  
 sdm prefer command [2-376](#)  
 SDM templates  
     allowed resources [2-377](#)  
     and stacking [2-377](#)  
     displaying [2-586](#)  
     dual IPv4 and IPv6 [2-376](#)  
 secure ports, limitations [2-721](#)  
 sending flow-control packets [2-135](#)  
 service password-recovery command [2-379](#)  
 service-policy command [2-381](#)  
 session command [2-384](#)  
 set (boot loader) command [A-24](#)  
 set command [2-385](#)  
 setup command [2-387](#)  
 setup express command [2-390](#)  
 show access-lists command [2-392](#)  
 show archive status command [2-395](#)  
 show arp access-list command [2-396](#)  
 show auto qos command [2-397](#)  
 show boot command [2-401](#)  
 show cable-diagnostics tdr command [2-404](#)  
 show changes command [2-770](#)  
 show class-map command [2-406](#)  
 show controllers cpu-interface command [2-407](#)  
 show controllers ethernet-controller command [2-409](#)  
 show controllers ethernet-controller fastethernet  
     command [2-416](#)  
 show controllers tcam command [2-419](#)  
 show controller utilization command [2-421](#)  
 show current command [2-770](#)  
 show dot1q-tunnel command [2-428](#)  
 show dot1x command [2-429](#)  
 show dtp [2-433](#)

- show eap command [2-435](#)
- show env command [2-438](#)
- show errdisable detect command [2-440](#)
- show errdisable flap-values command [2-442](#)
- show errdisable recovery command [2-443](#)
- show etherchannel command [2-445](#)
- show fallback profile command [2-448](#)
- show flowcontrol command [2-450](#)
- show idprom command [2-452](#)
- show interfaces command [2-454](#)
- show interfaces counters command [2-466](#)
- show inventory command [2-469](#)
- show ip arp inspection command [2-470](#)
- show ipc command [2-496](#)
- show ip dhcp snooping binding command [2-475](#)
- show ip dhcp snooping command [2-474](#)
- show ip dhcp snooping database command [2-477, 2-479](#)
- show ip igmp profile command [2-482](#)
- show ip igmp snooping address command [2-505](#)
- show ip igmp snooping command [2-483, 2-503](#)
- show ip igmp snooping groups command [2-486](#)
- show ip igmp snooping mrouter command [2-488, 2-507](#)
- show ip igmp snooping querier command [2-490, 2-509](#)
- show ip source binding command [2-492](#)
- show ipv6 access-list command [2-500](#)
- show ipv6 dhcp conflict command [2-502](#)
- show ipv6 route updated [2-511](#)
- show ip verify source command [2-494](#)
- show l2protocol-tunnel command [2-513](#)
- show lacp command [2-516](#)
- show link state group command [2-520](#)
- show location [2-522](#)
- show location command [2-522](#)
- show logging command [2-525](#)
- show mac access-group command [2-530](#)
- show mac address-table address command [2-534](#)
- show mac address-table aging time command [2-536](#)
- show mac address-table command [2-532](#)
- show mac address-table count command [2-538](#)
- show mac address-table dynamic command [2-540](#)
- show mac address-table interface command [2-542](#)
- show mac address-table learning command [2-544](#)
- show mac address-table move update command [2-545](#)
- show mac address-table notification command [2-61, 2-547, B-19](#)
- show mac address-table static command [2-549](#)
- show mac address-table vlan command [2-551](#)
- show mls qos aggregate-policer command [2-554](#)
- show mls qos command [2-553](#)
- show mls qos input-queue command [2-555](#)
- show mls qos interface command [2-557](#)
- show mls qos maps command [2-561](#)
- show mls qos queue-set command [2-564](#)
- show mls qos vlan command [2-566](#)
- show monitor command [2-567](#)
- show mvr command [2-570](#)
- show mvr interface command [2-572](#)
- show mvr members command [2-574](#)
- show pagp command [2-576](#)
- show parser macro command [2-578](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform dl command [C-5](#)
- show platform etherchannel command [C-6](#)
- show platform forward command [C-7](#)
- show platform frontend-controller command [C-9](#)
- show platform igmp snooping command [C-10](#)
- show platform ipc trace command [C-18](#)
- show platform ip multicast command [C-12](#)
- show platform ip unicast command [C-13](#)
- show platform ipv6 unicast command [C-19](#)
- show platform ip wccp command [C-17](#)
- show platform layer4op command [C-21](#)
- show platform mac-address-table command [C-22](#)
- show platform messaging command [C-23](#)
- show platform monitor command [C-24](#)
- show platform mvr table command [C-25](#)



- show platform pm command [C-26](#)
- show platform port-asic command [C-27](#)
- show platform port-security command [C-32](#)
- show platform qos command [C-33](#)
- show platform resource-manager command [C-34](#)
- show platform snmp counters command [C-36](#)
- show platform spanning-tree command [C-37](#)
- show platform stack-manager command [C-39](#)
- show platform stp-instance command [C-38](#)
- show platform tb command [C-41](#)
- show platform team command [C-43](#)
- show platform vlan command [C-46](#)
- show policy-map command [2-581](#)
- show port security command [2-583](#)
- show proposed command [2-770](#)
- show sdm prefer command [2-586](#)
- show setup express command [2-589](#)
- show spanning-tree command [2-590](#)
- show storm-control command [2-598](#)
- show switch command [2-600](#)
- show system mtu command [2-603](#)
- show trust command [2-748](#)
- show udd command [2-604](#)
- show version command [2-607](#)
- show vlan access-map command [2-614](#)
- show vlan command [2-609](#)
- show vlan command, fields [2-611](#)
- show vlan filter command [2-615](#)
- show vmpls command [2-616](#)
- show vtp command [2-618](#)
- shutdown command [2-623](#)
- shutdown threshold, Layer 2 protocol tunneling [2-236](#)
- shutdown vlan command [2-624](#)
- small violation-rate command [2-625](#)
- Smartports macros
  - See macros
- SNMP host, specifying [2-631](#)
- SNMP informs, enabling the sending of [2-627](#)
- snmp-server enable traps command [2-627](#)
- snmp-server host command [2-631](#)
- snmp trap mac-notification command [2-635](#)
- SNMP traps
  - enabling MAC address notification trap [2-635](#)
  - enabling the MAC address notification feature [2-262](#)
  - enabling the sending of [2-627](#)
- SoftPhone
  - See Cisco SoftPhone
- software images
  - copying [2-8](#)
  - deleting [2-73](#)
  - downloading [2-11](#)
  - upgrading [2-8, 2-11](#)
  - uploading [2-18](#)
- software version, displaying [2-607](#)
- source ports, MVR [2-328](#)
- SPAN
  - configuring [2-321](#)
  - debug messages, display [B-20](#)
  - displaying [2-567](#)
  - filter SPAN traffic [2-321](#)
  - sessions
    - add interfaces to [2-321](#)
    - displaying [2-567](#)
    - start new [2-321](#)
- spanning-tree backbonefast command [2-637](#)
- spanning-tree bpdudfilter command [2-638](#)
- spanning-tree bpduguard command [2-640](#)
- spanning-tree cost command [2-642](#)
- spanning-tree etherchannel command [2-644](#)
- spanning-tree extend system-id command [2-646](#)
- spanning-tree guard command [2-648](#)
- spanning-tree link-type command [2-650](#)
- spanning-tree loopguard default command [2-652](#)
- spanning-tree mode command [2-654](#)
- spanning-tree mst configuration command [2-656](#)
- spanning-tree mst cost command [2-658](#)
- spanning-tree mst forward-time command [2-660](#)
- spanning-tree mst hello-time command [2-661](#)

- spanning-tree mst max-age command [2-662](#)
- spanning-tree mst max-hops command [2-663](#)
- spanning-tree mst port-priority command [2-664](#)
- spanning-tree mst pre-standard command [2-666](#)
- spanning-tree mst priority command [2-667](#)
- spanning-tree mst root command [2-668](#)
- spanning-tree portfast (global configuration) command [2-672](#)
- spanning-tree portfast (interface configuration) command [2-675](#)
- spanning-tree port-priority command [2-670](#)
- Spanning Tree Protocol
  - See STP
- spanning-tree transmit hold-count command [2-677](#)
- spanning-tree uplinkfast command [2-678](#)
- spanning-tree vlan command [2-680](#)
- speed command [2-683](#)
- srr-queue bandwidth limit command [2-685](#)
- srr-queue bandwidth shape command [2-687](#)
- srr-queue bandwidth share command [2-689](#)
- SSH, configuring version [2-207](#)
- stack-mac persistent timer command [2-691](#)
- stack member
  - access [2-384](#)
  - number [2-600, 2-699](#)
  - priority value [2-696](#)
  - provisioning [2-697](#)
  - reloading [2-367](#)
- stacks, switch
  - MAC address [2-691](#)
  - provisioning a new member [2-697](#)
  - reloading [2-367](#)
  - stack member access [2-384](#)
  - stack member number [2-600, 2-699](#)
  - stack member priority value [2-600, 2-696](#)
- static-access ports, configuring [2-703](#)
- statistics, Ethernet group [2-375](#)
- sticky learning, enabling [2-719](#)
- storm-control command [2-693](#)
- STP
  - BackboneFast [2-637](#)
  - counters, clearing [2-65](#)
  - debug messages, display
    - BackboneFast events [B-72](#)
    - MSTP [B-75](#)
    - optimized BPDUs handling [B-74](#)
    - spanning-tree activity [B-70](#)
    - switch shim [B-77](#)
    - transmitted and received BPDUs [B-73](#)
    - UplinkFast [B-79](#)
  - detection of indirect link failures [2-637](#)
  - enabling protocol tunneling for [2-236](#)
  - EtherChannel misconfiguration [2-644](#)
  - extended system ID [2-646](#)
  - path cost [2-642](#)
  - protocol modes [2-654](#)
  - root port
    - accelerating choice of new [2-678](#)
    - loop guard [2-648](#)
    - preventing from becoming designated [2-648](#)
    - restricting which can be root [2-648](#)
    - root guard [2-648](#)
    - UplinkFast [2-678](#)
  - root switch
    - affects of extended system ID [2-646, 2-681](#)
    - hello-time [2-680](#)
    - interval between BDPU messages [2-680](#)
    - interval between hello BPDU messages [2-680](#)
    - max-age [2-680](#)
    - port priority for selection of [2-670](#)
    - primary or secondary [2-680](#)
    - switch priority [2-680](#)

## STP (continued)

## state changes

- blocking to forwarding state [2-675](#)
- enabling BPDU filtering [2-638, 2-672](#)
- enabling BPDU guard [2-640, 2-672](#)
- enabling Port Fast [2-672, 2-675](#)
- enabling timer to recover from error state [2-128](#)
- forward-delay time [2-680](#)
- length of listening and learning states [2-680](#)
- shutting down Port Fast-enabled ports [2-672](#)

state information display [2-590](#)VLAN options [2-667, 2-680](#)SVIs, creating [2-143](#)SVI status calculation [2-705](#)

## Switched Port Analyzer

See SPAN

## switching characteristics

- modifying [2-701](#)
- returning to interfaces [2-701](#)

switchport access command [2-703](#)switchport autostate exclude command [2-705](#)switchport backup interface command [2-707](#)switchport block command [2-710](#)switchport command [2-701](#)switchport host command [2-711](#)switchport mode command [2-712](#)switchport mode private-vlan command [2-715](#)switchport nonegotiate command [2-717](#)switchport port-security aging command [2-724](#)switchport port-security command [2-719](#)switchport priority extend command [2-726](#)switchport private-vlan command [2-728](#)switchport protected command [2-730](#)switchports, displaying [2-454](#)switchport trunk command [2-732](#)switchport voice detect [2-735](#)switchport voice vlan command [2-736](#)switch priority command [2-696](#)switch provision command [2-697](#)switch renumber command [2-699](#)system env temperature threshold yellow command [2-738](#)system message logging, save message to flash [2-251](#)system mtu command [2-740](#)system resource templates [2-376](#)

---

**T**tar files, creating, listing, and extracting [2-15](#)TDR, running [2-742](#)temperature information, displaying [2-438](#)templates, system resources [2-376](#)test cable-diagnostics tdr command [2-742](#)traceroute mac command [2-743](#)traceroute mac ip command [2-746](#)trunking, VLAN mode [2-712](#)trunk mode [2-712](#)trunk ports [2-712](#)trunks, to non-DTP device [2-713](#)trusted boundary for QoS [2-318](#)trusted port states for QoS [2-318](#)tunnel ports, Layer 2 protocol, displaying [2-513](#)type (boot loader) command [A-27](#)

---

**U**

## UDLD

aggressive mode [2-750, 2-752](#)debug messages, display [B-87](#)enable globally [2-750](#)enable per interface [2-752](#)error recovery timer [2-128](#)message timer [2-750](#)normal mode [2-750, 2-752](#)reset a shutdown interface [2-754](#)status [2-604](#)udld command [2-750](#)udld port command [2-752](#)

uddl reset command [2-754](#)  
 unicast storm control [2-693](#)  
 UniDirectional Link Detection  
     See UDLD  
 unknown multicast traffic, preventing [2-710](#)  
 unknown unicast traffic, preventing [2-710](#)  
 unset (boot loader) command [A-28](#)  
 upgrading  
     copying software images [2-8](#)  
     downloading software images [2-11](#)  
     software images, monitoring status of [2-395](#)  
 UplinkFast, for STP [2-678](#)  
 user EXEC mode [1-2, 1-3](#)

## V

version (boot loader) command [A-30](#)  
 version mismatch mode [2-601](#)  
 vlan (global configuration) command [2-755](#)  
 vlan (VLAN configuration) command [2-761](#)  
 vlan access-map command [2-767](#)  
 VLAN access map configuration mode [2-767](#)  
 VLAN access maps  
     actions [2-6](#)  
     displaying [2-614](#)  
 VLAN-based QoS [2-320](#)  
 VLAN configuration  
     rules [2-758, 2-763](#)  
     saving [2-755, 2-765](#)  
 VLAN configuration mode  
     commands  
         VLAN [2-761](#)  
         VTP [2-785](#)  
     description [1-5](#)  
     entering [2-769](#)  
     summary [1-3](#)  
 vlan database command [2-769](#)  
 vlan dot1q tag native command [2-772](#)  
 vlan filter command [2-774](#)  
 VLAN filters, displaying [2-615](#)  
 VLAN ID range [2-755, 2-761](#)  
 VLAN maps  
     applying [2-774](#)  
     creating [2-767](#)  
     defining [2-277](#)  
     displaying [2-614](#)  
 VLAN Query Protocol  
     See VQP  
 VLANs  
     adding [2-755](#)  
     configuring [2-755, 2-761](#)  
     debug messages, display  
         ISL [B-83](#)  
         VLAN IOS file system error tests [B-82](#)  
         VLAN manager activity [B-80](#)  
         VTP [B-85](#)  
     displaying configurations [2-609](#)  
     extended-range [2-755](#)  
     MAC addresses  
         displaying [2-551](#)  
         number of [2-538](#)  
     media types [2-758, 2-763](#)  
     normal-range [2-755, 2-761](#)  
     private [2-715](#)  
         configuring [2-357](#)  
         displaying [2-609](#)  
         See also private VLANs  
     restarting [2-624](#)  
     saving the configuration [2-755](#)  
     shutting down [2-624](#)  
     SNMP traps for VTP [2-629, 2-632](#)  
     suspending [2-624](#)  
     variables [2-761](#)  
 VLAN Trunking Protocol  
     See VTP  
 VM mode [2-601](#)

## VMPS

- configuring servers [2-779](#)
- displaying [2-616](#)
- error recovery timer [2-129](#)
- reconfirming dynamic VLAN assignments [2-776](#)

vmmps reconfirm (global configuration) command [2-777](#)

vmmps reconfirm (privileged EXEC) command [2-776](#)

vmmps retry command [2-778](#)

vmmps server command [2-779](#)

## voice VLAN

- configuring [2-735, 2-736](#)
- setting port priority [2-726](#)

## VQP

- and dynamic-access ports [2-704](#)
- clearing client statistics [2-67](#)
- displaying information [2-616](#)
- per-server retry count [2-778](#)
- reconfirmation interval [2-777](#)
- reconfirming dynamic VLAN assignments [2-776](#)

## VTP

changing characteristics [2-781](#)

clearing pruning counters [2-68](#)

## configuring

domain name [2-781, 2-785](#)

file name [2-781](#)

mode [2-781, 2-785](#)

password [2-781, 2-785](#)

counters display fields [2-619](#)

displaying information [2-618](#)

## enabling

pruning [2-781, 2-785](#)

tunneling for [2-236](#)

Version 2 [2-781, 2-785](#)

mode [2-781, 2-785](#)

pruning [2-781, 2-785](#)

saving the configuration [2-755, 2-765](#)

statistics [2-618](#)

status [2-618](#)

status display fields [2-620](#)

vtp (global configuration) command [2-781](#)

vtp (VLAN configuration) command [2-785](#)

