



INDEX

Numerics

10-Gigabit Ethernet interfaces **11-6**

A

AAA down policy, NAC Layer 2 IP validation **1-12**

abbreviating commands **2-3**

ABRs **39-32**

access

 templates **8-1**

access-class command **35-20**

access control entries

 See ACEs

access-denied response, VMPS **13-26**

access groups

 applying IPv4 ACLs to interfaces **35-21**

 Layer 2 **35-21**

 Layer 3 **35-21**

access groups, applying IPv4 ACLs to interfaces **35-21**

accessing stack members **7-26**

access lists

 See ACLs

access ports

 and Layer 2 protocol tunneling **17-11**

 defined **11-3**

access template **8-1**

accounting

 with 802.1x **9-51**

 with IEEE 802.1x **9-15**

 with RADIUS **6-35**

 with TACACS+ **6-11, 6-17**

ACEs

and QoS **37-8**

defined **35-2**

Ethernet **35-2**

IP **35-2**

ACLs

 ACEs **35-2**

 any keyword **35-13**

 applying

 on bridged packets **35-38**

 on multicast packets **35-39**

 on routed packets **35-39**

 on switched packets **35-37**

 time ranges to **35-17**

 to an interface **35-20, 36-8**

 to IPv6 interfaces **36-8**

 to QoS **37-8**

 classifying traffic for QoS **37-49**

 comments in **35-19**

 compiling **35-23**

 defined **35-2, 35-8**

 examples of **35-23, 37-49**

 extended IP, configuring for QoS classification **37-50**

 extended IPv4

 creating **35-11**

 matching criteria **35-8**

 hardware and software handling **35-22**

 host keyword **35-13**

 IP

 creating **35-8**

 fragments and QoS guidelines **37-38**

 implicit deny **35-10, 35-14, 35-17**

 implicit masks **35-10**

 matching criteria **35-8**

- undefined **35-21**
- IPv4
 - applying to interfaces **35-20**
 - creating **35-8**
 - matching criteria **35-8**
 - named **35-15**
 - numbers **35-8**
 - terminal lines, setting on **35-19**
 - unsupported features **35-7**
- IPv6
 - and stacking **36-4**
 - applying to interfaces **36-8**
 - configuring **36-4, 36-5**
 - displaying **36-9**
 - interactions with other features **36-5**
 - limitations **36-3**
 - matching criteria **36-3**
 - named **36-3**
 - precedence of **36-3**
 - unsupported features **36-3**
- Layer 4 information in **35-37**
- logging messages **35-9**
- MAC extended **35-28, 37-53**
- matching **35-8, 35-21**
- monitoring **35-40, 36-9**
- named
 - IPv4 **35-15**
 - IPv6 **36-3**
- names **36-5**
- number per QoS class map **37-38**
- port **35-2, 36-2**
- precedence of **35-3**
- QoS **37-8, 37-49**
- resequencing entries **35-15**
- router **35-2, 36-2**
- router ACLs and VLAN map configuration guidelines **35-37**
- standard IP, configuring for QoS classification **37-49, 37-51**
- standard IPv4
 - creating **35-10**
 - matching criteria **35-8**
 - support for **1-10**
 - support in hardware **35-22**
 - time ranges **35-17**
 - types supported **35-2**
 - unsupported features
 - IPv4 **35-7**
 - IPv6 **36-3**
 - using router ACLs with VLAN maps **35-36**
- VLAN maps
 - configuration guidelines **35-31**
 - configuring **35-30**
- active link **21-4, 21-5, 21-6**
- active links **21-2**
- active router **41-1**
- active traffic monitoring, IP SLAs **42-1**
- address aliasing **24-2**
- addresses
 - displaying the MAC address table **5-31**
 - dynamic
 - accelerated aging **18-9**
 - changing the aging time **5-21**
 - default aging **18-9**
 - defined **5-19**
 - learning **3-16, 5-20**
 - removing **5-22**
 - IPv6 **40-3**
 - MAC, discovering **5-31**
 - multicast
 - group address range **45-3**
 - STP address management **18-9**
 - static
 - adding and removing **5-27**
 - defined **5-19**
- address resolution **5-31, 39-10**
- Address Resolution Protocol
 - See ARP

- adjacency tables, with CEF **39-98**
- administrative distances
 - defined **39-111**
 - OSPF **39-39**
 - routing protocol defaults **39-100**
- advertisements
 - CDP **27-1**
 - LLDP **28-1, 28-2**
 - RIP **39-21**
 - VTP **13-18, 14-3, 14-4**
- aggregatable global unicast addresses **40-5**
- aggregate addresses, BGP **39-67**
- aggregated ports
 - See EtherChannel
- aggregate policers **37-72**
- aggregate policing **1-13**
- aging, accelerating **18-9**
- aging time
 - accelerated
 - for MSTP **19-24**
 - for STP **18-9, 18-23**
 - MAC address table **5-21**
 - maximum
 - for MSTP **19-25**
 - for STP **18-23, 18-24**
- alarms, RMON **31-4**
- allowed-VLAN list **13-20**
- application engines, redirecting traffic to **44-1**
- area border routers
 - See ABRs
- area routing
 - IS-IS **39-71**
 - ISO IGRP **39-71**
- ARP
 - configuring **39-11**
 - defined **1-6, 5-31, 39-11**
 - encapsulation **39-12**
 - static cache configuration **39-11**
 - table
- address resolution **5-31**
- managing **5-31**
- ASBRs **39-32**
- AS-path filters, BGP **39-61**
- asymmetrical links, and IEEE 802.1Q tunneling **17-4**
- attributes, RADIUS
 - vendor-proprietary **6-38**
 - vendor-specific **6-36**
 - attribute-value pairs **9-20, 9-21**
 - authentication
 - EIGRP **39-48**
 - HSRP **41-11**
 - local mode with AAA **6-44**
 - NTP associations **5-4**
 - open1x **9-30**
 - RADIUS
 - key **6-28**
 - login **6-30**
 - TACACS+
 - defined **6-11**
 - key **6-13**
 - login **6-14**
 - See also port-based authentication
 - authentication compatibility with Catalyst 6000 switches **9-9**
 - authentication failed VLAN
 - See restricted VLAN
 - authentication keys, and routing protocols **39-111**
 - authentication manager
 - CLI commands **9-9**
 - compatibility with older 802.1x CLI commands **9-10**
 - overview **9-8**
 - single session ID **9-33**
 - authoritative time source, described **5-2**
 - authorization
 - with RADIUS **6-34**
 - with TACACS+ **6-11, 6-16**
 - authorized ports with IEEE 802.1x **9-11**
 - autoconfiguration **3-4**

- auto enablement **9-32**
- automatic advise (auto-advise) in switch stacks **7-14**
- automatic copy (auto-copy) in switch stacks **7-13**
- automatic extraction (auto-extract) in switch stacks **7-13**
- automatic QoS
 See QoS
- automatic upgrades (auto-upgrade) in switch stacks **7-13**
- auto-MDIX
 configuring **11-22**
 described **11-22**
- autonegotiation
 duplex mode **1-4**
 interface configuration guidelines **11-18**
 mismatches **48-9**
- autonomous system boundary routers
 See ASBRs
- autonomous systems, in BGP **39-54**
- auto-QoS video devices **1-14**
- Auto-RP, described **45-6**
- autosensing, port speed **1-4**
- autostate exclude **11-6**
- auxiliary VLAN
 See voice VLAN
- availability, features **1-8**
-
- B**
- BackboneFast
 described **20-7**
 disabling **20-17**
 enabling **20-16**
 support for **1-8**
- backup interfaces
 See Flex Links
- backup links **21-2**
- banners
 configuring
 login **5-19**
 message-of-the-day login **5-18**
- BGP
 aggregate addresses **39-67**
 aggregate routes, configuring **39-67**
 CIDR **39-67**
 clear commands **39-70**
 community filtering **39-63**
 configuring neighbors **39-65**
 default configuration **39-51**
 described **39-50**
 enabling **39-54**
 monitoring **39-70**
 multipath support **39-58**
 neighbors, types of **39-54**
 path selection **39-58**
 peers, configuring **39-65**
 prefix filtering **39-62**
 resetting sessions **39-57**
 route dampening **39-69**
 route maps **39-60**
 route reflectors **39-68**
 routing domain confederation **39-67**
 routing session with multi-VRF CE **39-92**
 show commands **39-70**
 supernets **39-67**
 support for **1-14**
 Version 4 **39-51**
- binding database
 address, DHCP server
 See DHCP, Cisco IOS server database
- DHCP snooping
 See DHCP snooping binding database
- bindings
 address, Cisco IOS DHCP server **22-6**
 DHCP snooping database **22-6**
 IP source guard **22-16**
- binding table, DHCP snooping
 See DHCP snooping binding database

blocking packets **26-7**
 Boolean expressions in tracked lists **43-3**
 booting
 boot loader, function of **3-2**
 boot process **3-2**
 manually **3-22**
 specific image **3-23**
 boot loader
 accessing **3-24**
 described **3-2**
 environment variables **3-24**
 prompt **3-24**
 trap-door mechanism **3-2**
 bootstrap router (BSR), described **45-7**
 Border Gateway Protocol
 See BGP
 BPDU
 error-disabled state **20-2**
 filtering **20-3**
 RSTP format **19-13**
 BPDU filtering
 described **20-3**
 disabling **20-15**
 enabling **20-14**
 support for **1-8**
 BPDU guard
 described **20-2**
 disabling **20-14**
 enabling **20-13**
 support for **1-8**
 bridged packets, ACLs on **35-38**
 bridge groups
 See fallback bridging
 bridge protocol data unit
 See BPDU
 broadcast flooding **39-18**
 broadcast packets
 directed **39-15**
 flooded **39-15**

broadcast storm-control command **26-4**
 broadcast storms **26-1, 39-15**

C
 cables, monitoring for unidirectional links **29-1**
 Catalyst 6000 switches
 authentication compatibility **9-9**
 CA trustpoint
 configuring **6-53**
 defined **6-50**
 CDP
 and trusted boundary **37-45**
 configuring **27-2**
 default configuration **27-2**
 defined with LLDP **28-1**
 described **27-1**
 disabling for routing device **27-3 to 27-4**
 enabling and disabling
 on an interface **27-4**
 on a switch **27-3**
 Layer 2 protocol tunneling **17-8**
 monitoring **27-5**
 overview **27-1**
 support for **1-6**
 switch stack considerations **27-2**
 transmission timer and holdtime, setting **27-2**
 updates **27-2**
 CEF
 defined **39-97**
 distributed **39-98**
 IPv6 **40-21**
 CGMP
 as IGMP snooping learning method **24-9**
 clearing cached group entries **45-66**
 enabling server support **45-49**
 joining multicast group **24-3**
 overview **45-9**
 server support only **45-9**

- switch support of **1-4**
- CIDR **39-67**
- CipherSuites **6-51**
- Cisco 7960 IP Phone **15-1**
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco IOS IP SLAs **42-1**
- Cisco Secure ACS
 - attribute-value pairs for downloadable ACLs **9-21**
 - attribute-value pairs for redirect URL **9-20**
- Cisco Secure ACS configuration guide **9-63**
- Cisco StackWise Plus technology **1-3**
 - See also stacks, switch
- CiscoWorks 2000 **1-6, 33-4**
- CISP **9-32**
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- civic location **28-3**
- classless interdomain routing
 - See CIDR
- classless routing **39-9**
- class maps for QoS
 - configuring **37-54**
 - described **37-8**
 - displaying **37-92**
- class of service
 - See CoS
- clearing interfaces **11-29**
- CLI
- abbreviating commands **2-3**
- command modes **2-1**
- configuration logging **2-5**
- described **1-5**
- editing features
 - enabling and disabling **2-6**
 - keystroke editing **2-7**
 - wrapped lines **2-8**
- error messages **2-4**
- filtering command output **2-9**
- getting help **2-3**
- history
 - changing the buffer size **2-5**
 - described **2-5**
 - disabling **2-6**
 - recalling commands **2-6**
- no and default forms of commands **2-4**
- Client Information Signalling Protocol
 - See CISP
- client mode, VTP **14-3**
- client processes, tracking **43-1**
- CLNS
 - See ISO CLNS
- clock
 - See system clock
- CNS
 - Configuration Engine
 - configID, deviceID, hostname **4-3**
 - configuration service **4-2**
 - described **4-1**
 - event service **4-3**
 - embedded agents
 - described **4-5**
 - enabling automated configuration **4-7**
 - enabling configuration agent **4-9**
 - enabling event agent **4-8**
 - management functions **1-6**
- CoA Request Commands **6-23**
- command-line interface

- See CLI
- command modes **2-1**
- commands
 - abbreviating **2-3**
 - no and default **2-4**
- commands, setting privilege levels **6-8**
- common session ID
 - see single session ID **9-33**
- community list, BGP **39-64**
- community ports **16-2**
- community strings
 - configuring **33-8**
 - overview **33-4**
- community VLANs **16-2, 16-3**
- compatibility, feature **26-12**
- compatibility, software
 - See stacks, switch
- config.text **3-21**
- configurable leave timer, IGMP **24-6**
- configuration, initial
 - defaults **1-17**
 - Express Setup **1-3**
- configuration examples, network **1-19**
- configuration files
 - archiving **B-20**
 - clearing the startup configuration **B-20**
 - creating and using, guidelines for **B-10**
 - creating using a text editor **B-11**
 - default name **3-21**
 - deleting a stored configuration **B-20**
 - described **B-9**
 - downloading
 - automatically **3-21**
 - preparing **B-11, B-14, B-17**
 - reasons for **B-9**
 - using FTP **B-14**
 - using RCP **B-18**
 - using TFTP **B-12**
 - invalid combinations when copying **B-6**
- limiting TFTP server access **33-17**
- obtaining with DHCP **3-9**
- password recovery disable considerations **6-5**
- replacing and rolling back, guidelines for **B-22**
- replacing a running configuration **B-20, B-21**
- rolling back a running configuration **B-20, B-21**
- specifying the filename **3-22**
- system contact and location information **33-16**
- types and location **B-10**
- uploading
 - preparing **B-11, B-14, B-17**
 - reasons for **B-9**
 - using FTP **B-15**
 - using RCP **B-19**
 - using TFTP **B-13**
- configuration guidelines, multi-VRF CE **39-84**
- configuration logging **2-5**
- configuration replacement **B-20**
- configuration rollback **B-20**
- configuration settings, saving **3-19**
- configure terminal command **11-9**
- configuring multicast VRFs **39-90**
- configuring port-based authentication violation modes **9-38 to 9-39**
- configuring small-frame arrival rate **26-5**
- connections, secure remote **6-46**
- connectivity problems **48-10, 48-11, 48-13**
- consistency checks in VTP Version 2 **14-5**
- console port, connecting to **2-10**
- content-routing technology
 - See WCCP
- control protocol, IP SLAs **42-4**
- corrupted software, recovery steps with Xmodem **48-2**
- CoS
 - override priority **15-6**
 - trust priority **15-6**
 - CoS input queue threshold map for QoS **37-17**
 - CoS output queue threshold map for QoS **37-20**
 - CoS-to-DSCP map for QoS **37-74**

- counters, clearing interface **11-29**
- CPU utilization, troubleshooting **48-23**
- crashinfo file **48-20**
- critical authentication, IEEE 802.1x **9-55**
- critical VLAN **9-23**
- cross-stack EtherChannel
- configuration guidelines **38-12**
 - configuring
 - on Layer 2 interfaces **38-12**
 - on Layer 3 physical interfaces **38-16**
 - described **38-2**
 - illustration **38-3**
 - support for **1-8**
- cross-stack UplinkFast, STP
- described **20-5**
 - disabling **20-16**
 - enabling **20-16**
 - fast-convergence events **20-7**
 - Fast Uplink Transition Protocol **20-6**
 - normal-convergence events **20-7**
 - support for **1-8**
- cryptographic software image
- Kerberos **6-40**
 - SSL **6-50**
 - switch stack considerations **6-46, 7-2, 7-18**
- customer edge devices **39-82**
- customizable web pages, web-based authentication **10-6**
-
- D**
- DACL
- See downloadable ACL
- daylight saving time **5-13**
- dCEF in the switch stack **39-97**
- debugging
- enabling all system diagnostics **48-17**
 - enabling for a specific feature **48-16**
 - redirecting error message output **48-17**
 - using commands **48-16**
- default commands **2-4**
- default configuration
- 802.1x **9-35**
 - auto-QoS **37-22**
 - banners **5-17**
 - BGP **39-51**
 - booting **3-21**
 - CDP **27-2**
 - DHCP **22-8**
 - DHCP option 82 **22-8**
 - DHCP snooping **22-8**
 - DHCP snooping binding database **22-9**
 - DNS **5-16**
 - dynamic ARP inspection **23-5**
 - EIGRP **39-44**
 - EtherChannel **38-10**
 - Ethernet interfaces **11-17**
 - fallback bridging **47-4**
 - Flex Links **21-8**
 - HSRP **41-6**
 - IEEE 802.1Q tunneling **17-4**
 - IGMP **45-43**
 - IGMP filtering **24-25**
 - IGMP snooping **24-7, 25-6**
 - IGMP throttling **24-25**
 - initial switch information **3-3**
 - IP addressing, IP routing **39-7**
 - IP multicast routing **45-10**
 - IP SLAs **42-6**
 - IP source guard **22-18**
 - IPv6 **40-13**
 - IS-IS **39-73**
 - Layer 2 interfaces **11-17**
 - Layer 2 protocol tunneling **17-11**
 - LLDP **28-4**
 - MAC address table **5-21**
 - MAC address-table move update **21-8**
 - MSDP **46-4**
 - MSTP **19-15**

- multi-VRF CE **39-84**
- MVR **24-20**
- NTP **5-4**
- optional spanning-tree configuration **20-12**
- OSPF **39-32**
- password and privilege level **6-2**
- PIM **45-10**
- private VLANs **16-7**
- RADIUS **6-27**
- RIP **39-22**
- RMON **31-3**
- RSPAN **30-11**
- SDM template **8-4**
- SNMP **33-6**
- SPAN **30-11**
- SSL **6-52**
- standard QoS **37-36**
- STP **18-13**
- switch stacks **7-21**
- system message logging **32-4**
- system name and prompt **5-15**
- TACACS+ **6-13**
- UDLD **29-4**
- VLAN, Layer 2 Ethernet interfaces **13-17**
- VLANs **13-8**
- VMPS **13-27**
- voice VLAN **15-3**
- VTP **14-8**
- WCCP **44-6**
- default gateway **3-16, 39-13**
- default networks **39-101**
- default router preference
 - See DRP
- default routes **39-101**
- default routing **39-4**
- default web-based authentication configuration
 - 802.1X **10-9**
- deleting VLANs **13-9**
- denial-of-service attack **26-1**
- description command **11-23**
- designing your network, examples **1-19**
- desktop template **7-12**
- destination addresses
 - in IPv4 ACLs **35-12**
 - in IPv6 ACLs **36-6**
- destination-IP address-based forwarding, EtherChannel **38-8**
- destination-MAC address forwarding, EtherChannel **38-8**
- detecting indirect link failures, STP **20-8**
- device discovery protocol **27-1, 28-1**
- device manager
 - benefits **1-3**
 - described **1-3, 1-5**
 - in-band management **1-7**
- DHCP
 - Cisco IOS server database
 - configuring **22-14**
 - default configuration **22-9**
 - described **22-6**
 - DHCP for IPv6
 - See DHCPv6
 - enabling
 - relay agent **22-11**
 - server **22-10**
 - DHCP-based autoconfiguration
 - client request message exchange **3-4**
 - configuring
 - client side **3-4**
 - DNS **3-8**
 - relay device **3-8**
 - server side **3-7**
 - server-side **22-10**
 - TFTP server **3-7**
 - example **3-10**
 - lease options
 - for IP address information **3-7**
 - for receiving the configuration file **3-7**
 - overview **3-4**

- relationship to BOOTP **3-4**
- relay support **1-6, 1-15**
- support for **1-6**
- DHCP-based autoconfiguration and image update
 - configuring **3-13 to 3-15**
 - understanding **3-5 to 3-6, 3-11 to 3-12**
- DHCP binding database
 - See DHCP snooping binding database
- DHCP binding table
 - See DHCP snooping binding database
- DHCP option 82
 - circuit ID suboption **22-5**
 - configuration guidelines **22-9**
 - default configuration **22-8**
 - displaying **22-16**
 - forwarding address, specifying **22-11**
 - helper address **22-11**
 - overview **22-3**
 - packet format, suboption
 - circuit ID **22-5**
 - remote ID **22-5**
 - remote ID suboption **22-5**
- DHCP server port-based address allocation
 - configuration guidelines **22-27**
 - default configuration **22-27**
 - described **22-26**
 - displaying **22-30**
 - enabling **22-27**
 - reserved addresses **22-28**
- DHCP snooping
 - accepting untrusted packets from edge switch **22-3, 22-13**
 - and private VLANs **22-14**
 - binding database
 - See DHCP snooping binding database
 - configuration guidelines **22-9**
 - default configuration **22-8**
 - displaying binding tables **22-16**
 - message exchange process **22-4**
- option 82 data insertion **22-3**
- trusted interface **22-2**
- untrusted interface **22-2**
- untrusted messages **22-2**
- DHCP snooping binding database
 - adding bindings **22-15**
 - binding entries, displaying **22-16**
 - binding file
 - format **22-7**
 - location **22-6**
 - bindings **22-6**
 - clearing agent statistics **22-15**
 - configuration guidelines **22-10**
 - configuring **22-15**
 - default configuration **22-8, 22-9**
 - deleting
 - binding file **22-15**
 - bindings **22-16**
 - database agent **22-15**
 - described **22-6**
 - displaying **22-16**
 - binding entries **22-16**
 - status and statistics **22-16**
 - displaying status and statistics **22-16**
 - enabling **22-15**
 - entry **22-6**
 - renewing database **22-15**
 - resetting
 - delay value **22-15**
 - timeout value **22-15**
- DHCP snooping binding table
 - See DHCP snooping binding database
- DHCPv6
 - configuration guidelines **40-18**
 - default configuration **40-18**
 - described **40-7**
 - enabling client function **40-20**
 - enabling DHCPv6 server function **40-18**
 - diagnostic schedule command **49-2**

- Differentiated Services architecture, QoS **37-2**
- Differentiated Services Code Point **37-2**
- Diffusing Update Algorithm (DUAL) **39-42**
- directed unicast requests **1-6**
- directories
- changing **B-4**
 - creating and removing **B-5**
 - displaying the working **B-4**
- Distance Vector Multicast Routing Protocol
- See DVMRP
- distance-vector protocols **39-4**
- distribute-list command **39-110**
- DNS
- and DHCP-based autoconfiguration **3-8**
 - default configuration **5-16**
 - displaying the configuration **5-17**
 - in IPv6 **40-5**
 - overview **5-15**
 - setting up **5-16**
 - support for **1-6**
- domain names
- DNS **5-15**
 - VTP **14-9**
- Domain Name System
- See DNS
- domains, ISO IGRP routing **39-71**
- dot1q-tunnel switchport mode **13-16**
- double-tagged packets
- IEEE 802.1Q tunneling **17-2**
 - Layer 2 protocol tunneling **17-10**
- downloadable ACL **9-19, 9-21, 9-63**
- downloading
- configuration files
 - preparing **B-11, B-14, B-17**
 - reasons for **B-9**
 - using FTP **B-14**
 - using RCP **B-18**
 - using TFTP **B-12**
 - image files
- deleting old image **B-29**
- preparing **B-27, B-30, B-35**
- reasons for **B-24**
- using CMS **1-3**
- using FTP **B-31**
- using HTTP **1-3, B-24**
- using RCP **B-36**
- using TFTP **B-27**
- using the device manager or Network Assistant **B-24**
- drop threshold for Layer 2 protocol packets **17-11**
- DRP
- configuring **40-15**
 - described **40-6**
 - IPv6 **40-6**
 - DSCP **1-13, 37-2**
 - DSCP input queue threshold map for QoS **37-17**
 - DSCP output queue threshold map for QoS **37-20**
 - DSCP-to-CoS map for QoS **37-77**
 - DSCP-to-DSCP-mutation map for QoS **37-78**
 - DSCP transparency **37-45**
 - DTP **1-9, 13-16**
 - dual-action detection **38-6**
 - DUAL finite state machine, EIGRP **39-43**
 - dual IPv4 and IPv6 templates **8-2, 40-7**
 - dual protocol stacks
 - IPv4 and IPv6 **40-7**
 - SDM templates supporting **40-7**
- DVMRP
- autosummarization
 - configuring a summary address **45-63**
 - disabling **45-65**
 - connecting PIM domain to DVMRP router **45-55**
 - enabling unicast routing **45-59**
 - interoperability
 - with Cisco devices **45-53**
 - with Cisco IOS software **45-9**
 - mrinfo requests, responding to **45-58**
 - neighbors

- advertising the default route to **45-57**
- discovery with Probe messages **45-53**
- displaying information **45-58**
- prevent peering with nonpruning **45-61**
- rejecting nonpruning **45-60**
- overview **45-8**
- routes
 - adding a metric offset **45-65**
 - advertising all **45-65**
 - advertising the default route to neighbors **45-57**
 - caching DVMRP routes learned in report messages **45-59**
 - changing the threshold for syslog messages **45-62**
 - deleting **45-66**
 - displaying **45-67**
 - favoring one over another **45-65**
 - limiting the number injected into MBONE **45-62**
 - limiting unicast route advertisements **45-53**
- routing table **45-9**
- source distribution tree, building **45-9**
- support for **1-15**
- tunnels
 - configuring **45-55**
 - displaying neighbor information **45-58**
- dynamic access ports
 - characteristics **13-3**
 - configuring **13-29**
 - defined **11-3**
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning **23-1**
 - ARP requests, described **23-1**
 - ARP spoofing attack **23-1**
 - clearing
 - log buffer **23-15**
 - statistics **23-15**
 - configuration guidelines **23-6**
 - configuring
- ACLs for non-DHCP environments **23-8**
- in DHCP environments **23-7**
- log buffer **23-13**
- rate limit for incoming ARP packets **23-4, 23-10**
- default configuration **23-5**
- denial-of-service attacks, preventing **23-10**
- described **23-1**
- DHCP snooping binding database **23-2**
- displaying
 - ARP ACLs **23-14**
 - configuration and operating state **23-14**
 - log buffer **23-15**
 - statistics **23-15**
 - trust state and rate limit **23-14**
- error-disabled state for exceeding rate limit **23-4**
- function of **23-2**
- interface trust states **23-3**
- log buffer
 - clearing **23-15**
 - configuring **23-13**
 - displaying **23-15**
- logging of dropped packets, described **23-5**
- man-in-the middle attack, described **23-2**
- network security issues and interface trust states **23-3**
- priority of ARP ACLs and DHCP snooping entries **23-4**
- rate limiting of ARP packets
 - configuring **23-10**
 - described **23-4**
 - error-disabled state **23-4**
- statistics
 - clearing **23-15**
 - displaying **23-15**
 - validation checks, performing **23-12**
- dynamic auto trunking mode **13-16**
- dynamic desirable trunking mode **13-16**
- Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration
- dynamic port VLAN membership

- described **13-27**
 reconfirming **13-29, 13-30**
 troubleshooting **13-31**
 types of connections **13-29**
- dynamic routing **39-4**
 ISO CLNS **39-71**
- Dynamic Trunking Protocol
 See DTP
-
- E**
- EBGP **39-49**
 editing features
 enabling and disabling **2-6**
 keystrokes used **2-7**
 wrapped lines **2-8**
- EEM 3.2 **34-5**
- EIGRP
 authentication **39-48**
 components **39-43**
 configuring **39-46**
 default configuration **39-44**
 definition **39-42**
 interface parameters, configuring **39-47**
 monitoring **39-49**
 support for **1-14**
- EIGRP stub routing **39-29**
- elections
 See stack master
- ELIN location **28-3**
- embedded event manager
 3.2 **34-5**
 actions **34-4**
 configuring **34-1, 34-6**
 displaying information **34-8**
 environmental variables **34-5**
 event detectors **34-3**
 policies **34-4**
 registering and defining an applet **34-6**
- registering and defining a TCL script **34-7**
 understanding **34-1**
- enable password **6-3**
 enable secret password **6-3**
 encryption, CipherSuite **6-52**
 encryption for passwords **6-3**
- Enhanced IGRP
 See EIGRP
- enhanced object tracking
 defined **43-1**
 HSRP **43-6**
 IP routing state **43-2**
 IP SLAs **43-8**
 line-protocol state **43-2**
 tracked lists **43-3**
- environmental variables, embedded event manager **34-5**
 environment variables, function of **3-25**
 equal-cost routing **1-15, 39-99**
 error-disabled state, BPDU **20-2**
 error messages during command entry **2-4**
- EtherChannel
 automatic creation of **38-5, 38-6**
 channel groups
 binding physical and logical interfaces **38-4**
 numbering of **38-4**
 configuration guidelines **38-11**
 configuring
 Layer 2 interfaces **38-12**
 Layer 3 physical interfaces **38-16**
 Layer 3 port-channel logical interfaces **38-15**
 default configuration **38-10**
 described **38-2**
 displaying status **38-23**
 forwarding methods **38-8, 38-18**
 IEEE 802.3ad, described **38-6**
 interaction
 with STP **38-11**
 with VLANs **38-12**
- LACP

- described **38-6**
 - displaying status **38-23**
 - hot-standby ports **38-20**
 - interaction with other features **38-7**
 - modes **38-7**
 - port priority **38-22**
 - system priority **38-21**
 - Layer 3 interface **39-6**
 - load balancing **38-8, 38-18**
 - logical interfaces, described **38-4**
 - PAgP
 - aggregate-port learners **38-19**
 - compatibility with Catalyst 1900 **38-19**
 - described **38-5**
 - displaying status **38-23**
 - interaction with other features **38-6**
 - interaction with virtual switches **38-6**
 - learn method and priority configuration **38-19**
 - modes **38-5**
 - support for **1-4**
 - with dual-action detection **38-6**
 - port-channel interfaces
 - described **38-4**
 - numbering of **38-4**
 - port groups **11-6**
 - stack changes, effects of **38-9**
 - support for **1-4**
 - EtherChannel guard
 - described **20-10**
 - disabling **20-17**
 - enabling **20-17**
 - Ethernet management port, internal
 - and routing **11-15**
 - configuring **11-16**
 - default setting **11-15**
 - described **11-13**
 - Layer 3 routing guidelines **11-16**
 - supported features **11-16**
 - unsupported features **11-16**
 - Ethernet VLANs
 - adding **13-8**
 - defaults and ranges **13-8**
 - modifying **13-8**
 - EUI **40-5**
 - event detectors, embedded event manager **34-3**
 - events, RMON **31-4**
 - examples
 - network configuration **1-19**
 - expedite queue for QoS **37-91**
 - Express Setup **1-3**
 - See also getting started guide
 - extended crashinfo file **48-20**
 - extended-range VLANs
 - configuration guidelines **13-11**
 - configuring **13-11**
 - creating **13-12**
 - creating with an internal VLAN ID **13-13**
 - defined **13-1**
 - extended system ID
 - MSTP **19-18**
 - STP **18-4, 18-16**
 - extended universal identifier
 - See EUI
 - Extensible Authentication Protocol over LAN **9-2**
 - external BGP
 - See EBGP
 - external neighbors, BGP **39-54**
-
- F**
- Fa0 port
 - See Ethernet management port, internal
 - failover support **1-8**
 - fallback bridging
 - and protected ports **47-4**
 - bridge groups
 - creating **47-4**
 - described **47-2**

- displaying **47-11**
- function of **47-2**
- number supported **47-5**
- removing **47-5**
- bridge table
 - clearing **47-11**
 - displaying **47-11**
- configuration guidelines **47-4**
- connecting interfaces with **11-8**
- default configuration **47-4**
- described **47-1**
- frame forwarding
 - flooding packets **47-2**
 - forwarding packets **47-2**
- overview **47-1**
- protocol, unsupported **47-4**
- stack changes, effects of **47-3**
- STP
 - disabling on an interface **47-10**
 - forward-delay interval **47-9**
 - hello BPDU interval **47-9**
 - interface priority **47-7**
 - keepalive messages **18-2**
 - maximum-idle interval **47-10**
 - path cost **47-8**
 - VLAN-bridge spanning-tree priority **47-6**
 - VLAN-bridge STP **47-2**
- support for **1-14**
- SVIs and routed ports **47-1**
- unsupported protocols **47-4**
- VLAN-bridge STP **18-12**
- Fast Convergence **21-3**
- fastethernet0 port
 - See Ethernet management port, internal
- Fast Uplink Transition Protocol **20-6**
- features, incompatible **26-12**
- FIB **39-97**
- fiber-optic, detecting unidirectional links **29-1**
- files
 - basic crashinfo
 - description **48-20**
 - location **48-20**
 - copying **B-5**
 - crashinfo, description **48-20**
 - deleting **B-6**
 - displaying the contents of **B-8**
 - extended crashinfo
 - description **48-20**
 - location **48-20**
 - tar
 - creating **B-7**
 - displaying the contents of **B-7**
 - extracting **B-8**
 - image file format **B-25**
 - file system
 - displaying available file systems **B-2**
 - displaying file information **B-3**
 - local file system names **B-1**
 - network file system names **B-5**
 - setting the default **B-3**
 - filtering
 - in a VLAN **35-30**
 - IPv6 traffic **36-4, 36-8**
 - non-IP traffic **35-28**
 - show and more command output **2-9**
 - filtering show and more command output **2-9**
 - filters, IP
 - See ACLs, IP
 - flash device, number of **B-1**
 - flexible authentication ordering
 - configuring **9-66**
 - overview **9-30**
 - Flex Link Multicast Fast Convergence **21-3**
 - Flex Links
 - configuration guidelines **21-8**
 - configuring **21-9**
 - configuring preferred VLAN **21-12**
 - configuring VLAN load balancing **21-11**

- default configuration **21-8**
 description **21-2**
 link load balancing **21-3**
 monitoring **21-14**
 VLANs **21-3**
 flooded traffic, blocking **26-8**
 flow-based packet classification **1-13**
 flowcharts
 QoS classification **37-7**
 QoS egress queueing and scheduling **37-18**
 QoS ingress queueing and scheduling **37-16**
 QoS policing and marking **37-11**
 flowcontrol
 configuring **11-20**
 described **11-20**
 forward-delay time
 MSTP **19-24**
 STP **18-23**
 Forwarding Information Base
 See FIB
 forwarding nonroutable protocols **47-1**
 FTP
 accessing MIB files **A-4**
 configuration files
 downloading **B-14**
 overview **B-13**
 preparing the server **B-14**
 uploading **B-15**
 image files
 deleting old image **B-33**
 downloading **B-31**
 preparing the server **B-30**
 uploading **B-33**
-
- G**
- general query **21-5**
 Generating IGMP Reports **21-4**
 get-bulk-request operation **33-3**
 get-next-request operation **33-3, 33-4**
 get-request operation **33-3, 33-4**
 get-response operation **33-3**
 global configuration mode **2-2**
 global leave, IGMP **24-13**
 guest VLAN and IEEE 802.1x **9-21**
 guide mode **1-3**
 GUIs
 See device manager and Network Assistant
-
- H**
- hardware limitations and Layer 3 interfaces **11-24**
 hello time
 MSTP **19-23**
 STP **18-22**
 help, for the command line **2-3**
 hierarchical policy maps **37-9**
 configuration guidelines **37-39**
 configuring **37-64**
 described **37-12**
 history
 changing the buffer size **2-5**
 described **2-5**
 disabling **2-6**
 recalling commands **2-6**
 history table, level and number of syslog messages **32-10**
 host ports
 configuring **16-12**
 kinds of **16-2**
 hosts, limit on dynamic ports **13-31**
 Hot Standby Router Protocol
 See HSRP
- HP OpenView **1-6**
- HSRP
 authentication string **41-11**
 command-switch redundancy **1-2, 1-8**
 configuring **41-5**
 default configuration **41-6**

- definition **41-1**
- guidelines **41-6**
- monitoring **41-12**
- object tracking **43-6**
- overview **41-1**
- priority **41-8**
- routing redundancy **1-14**
- support for ICMP redirect messages **41-12**
- switch stack considerations **41-5**
- timers **41-11**
- tracking **41-8**
- HSRP for IPv6
 - configuring **40-27**
 - guidelines **40-26**
- HTTP over SSL
 - see HTTPS
- HTTPS
 - configuring **6-53**
 - described **6-50**
 - self-signed certificate **6-51**
- HTTP secure server **6-50**

- IBPG **39-49**
- ICMP
 - IPv6 **40-5**
 - redirect messages **39-13**
 - support for **1-15**
 - time-exceeded messages **48-13**
 - traceroute and **48-13**
 - unreachable messages **35-20**
 - unreachable messages and IPv6 **36-5**
 - unreachables and ACLs **35-22**
 - ICMP Echo operation
 - configuring **42-11**
 - IP SLAs **42-11**
 - ICMP ping
 - executing **48-10**
 - overview **48-10**
 - ICMP Router Discovery Protocol
 - See IRDP
 - ICMPv6 **40-5**
 - IDS appliances
 - and ingress RSPAN **30-23**
 - and ingress SPAN **30-15**
 - IEEE 802.1D
 - See STP
 - IEEE 802.1p **15-1**
 - IEEE 802.1Q
 - and trunk ports **11-3**
 - configuration limitations **13-17**
 - encapsulation **13-15**
 - native VLAN for untagged traffic **13-22**
 - tunneling
 - compatibility with other features **17-6**
 - defaults **17-4**
 - described **17-1**
 - tunnel ports with other features **17-6**
 - IEEE 802.1s
 - See MSTP
 - IEEE 802.1w
 - See RSTP
 - IEEE 802.1x
 - See port-based authentication
 - IEEE 802.3ad
 - See EtherChannel
 - IEEE 802.3x flow control **11-20**
 - ifIndex values, SNMP **33-5**
 - IFS **1-7**
 - IGMP
 - configurable leave timer
 - described **24-6**
 - enabling **24-12**
 - configuring the switch
 - as a member of a group **45-43**
 - statically connected member **45-48**
 - controlling access to groups **45-44**

- default configuration **45-43**
- deleting cache entries **45-67**
- displaying groups **45-67**
- fast switching **45-48**
- flooded multicast traffic
 - controlling the length of time **24-13**
 - disabling on an interface **24-14**
- global leave **24-13**
- query solicitation **24-13**
- recovering from flood mode **24-13**
- host-query interval, modifying **45-46**
- joining multicast group **24-3**
- join messages **24-3**
- leave processing, enabling **24-11, 25-9**
- leaving multicast group **24-5**
- multicast reachability **45-43**
- overview **45-2**
- queries **24-4**
- report suppression
 - described **24-6**
 - disabling **24-16, 25-11**
- supported versions **24-3**
- support for **1-4**
- Version 1
 - changing to Version 2 **45-45**
 - described **45-3**
- Version 2
 - changing to Version 1 **45-45**
 - described **45-3**
 - maximum query response time value **45-47**
 - pruning groups **45-47**
 - query timeout value **45-47**
- IGMP filtering
 - configuring **24-25**
 - default configuration **24-25**
 - described **24-24**
 - monitoring **24-29**
 - support for **1-5**
- IGMP groups
 - configuring filtering **24-28**
 - setting the maximum number **24-27**
- IGMP helper **45-6**
- IGMP Immediate Leave
 - configuration guidelines **24-12**
 - described **24-6**
 - enabling **24-11**
- IGMP profile
 - applying **24-27**
 - configuration mode **24-25**
 - configuring **24-26**
- IGMP snooping
 - and address aliasing **24-2**
 - and stack changes **24-7**
 - configuring **24-7**
 - default configuration **24-7, 25-6**
 - definition **24-2**
 - enabling and disabling **24-8, 25-7**
 - global configuration **24-8**
 - Immediate Leave **24-6**
 - in the switch stack **24-7**
 - method **24-9**
 - monitoring **24-16, 25-12**
 - querier
 - configuration guidelines **24-14**
 - configuring **24-14**
 - supported versions **24-3**
 - support for **1-4**
 - VLAN configuration **24-8**
- IGMP throttling
 - configuring **24-28**
 - default configuration **24-25**
 - described **24-25**
 - displaying action **24-29**
- IGP **39-31**
- Immediate Leave, IGMP
 - described **24-6**
 - enabling **25-9**
- inaccessible authentication bypass **9-23**

- support for multiauth ports [9-24](#)
- initial configuration
 - defaults [1-17](#)
 - Express Setup [1-3](#)
- interface
 - number [11-8](#)
 - range macros [11-12](#)
- interface command [11-8 to 11-9](#)
- interface configuration mode [2-2](#)
- interfaces
 - auto-MDIX, configuring [11-22](#)
 - configuring
 - procedure [11-9](#)
 - counters, clearing [11-29](#)
 - default configuration [11-17](#)
 - described [11-23](#)
 - descriptive name, adding [11-23](#)
 - displaying information about [11-28](#)
 - duplex and speed configuration guidelines [11-18](#)
 - flow control [11-20](#)
 - management [1-5](#)
 - monitoring [11-28](#)
 - naming [11-23](#)
 - physical, identifying [11-8](#)
 - range of [11-10](#)
 - restarting [11-29](#)
 - shutting down [11-29](#)
 - speed and duplex, configuring [11-19](#)
 - status [11-28](#)
 - supported [11-8](#)
 - types of [11-1](#)
- interfaces range macro command [11-12](#)
- interface types [11-8](#)
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP [39-54](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- inter-VLAN routing [1-14, 39-3](#)
- Intrusion Detection System
 - See IDS appliances
- inventory management TLV [28-3, 28-7](#)
- IP ACLs
 - for QoS classification [37-8](#)
 - implicit deny [35-10, 35-14](#)
 - implicit masks [35-10](#)
 - named [35-15](#)
 - undefined [35-21](#)
- IP addresses
 - 128-bit [40-3](#)
 - classes of [39-8](#)
 - default configuration [39-7](#)
 - discovering [5-31](#)
 - for IP routing [39-6](#)
 - IPv6 [40-3](#)
 - MAC address association [39-10](#)
 - monitoring [39-19](#)
- IP base feature set [1-2](#)
- IP broadcast address [39-17](#)
- ip cef distributed command [39-98](#)
- IP directed broadcasts [39-16](#)
- ip igmp profile command [24-25](#)
- IP information
 - assigned
 - manually [3-16](#)
 - through DHCP-based autoconfiguration [3-4](#)
 - default configuration [3-3](#)
- IP multicast routing
 - addresses
 - all-hosts [45-3](#)
 - all-multicast-routers [45-3](#)
 - host group address range [45-3](#)

- administratively-scoped boundaries, described **45-51**
- and IGMP snooping **24-2**
- Auto-RP
 - adding to an existing sparse-mode cloud **45-30**
 - benefits of **45-29**
 - clearing the cache **45-67**
 - configuration guidelines **45-12**
 - filtering incoming RP announcement messages **45-32**
 - overview **45-6**
 - preventing candidate RP spoofing **45-32**
 - preventing join messages to false RPs **45-31**
 - setting up in a new internetwork **45-30**
 - using with BSR **45-37**
- bootstrap router
 - configuration guidelines **45-12**
 - configuring candidate BSRs **45-35**
 - configuring candidate RPs **45-36**
 - defining the IP multicast boundary **45-35**
 - defining the PIM domain border **45-34**
 - overview **45-7**
 - using with Auto-RP **45-37**
- Cisco implementation **45-1**
- configuring
 - basic multicast routing **45-12**
 - IP multicast boundary **45-51**
- default configuration **45-10**
- enabling
 - multicast forwarding **45-13**
 - PIM mode **45-13**
- group-to-RP mappings
 - Auto-RP **45-6**
 - BSR **45-7**
- MBONE
 - deleting sdr cache entries **45-67**
 - described **45-50**
 - displaying sdr cache **45-68**
 - enabling sdr listener support **45-50**
 - limiting DVMRP routes advertised **45-62**
 - limiting sdr cache entry lifetime **45-50**
 - SAP packets for conference session announcement **45-50**
 - Session Directory (sdr) tool, described **45-50**
 - monitoring
 - packet rate loss **45-68**
 - peering devices **45-68**
 - tracing a path **45-68**
 - multicast forwarding, described **45-7**
 - PIMv1 and PIMv2 interoperability **45-11**
 - protocol interaction **45-2**
 - reverse path check (RPF) **45-7**
 - routing table
 - deleting **45-67**
 - displaying **45-67**
- RP
 - assigning manually **45-28**
 - configuring Auto-RP **45-29**
 - configuring PIMv2 BSR **45-33**
 - monitoring mapping information **45-39**
 - using Auto-RP and BSR **45-37**
- stacking
 - stack master functions **45-9**
 - stack member functions **45-9**
- statistics, displaying system and network **45-67**
- See also CGMP
- See also DVMRP
- See also IGMP
- See also PIM
- IP phones
 - and QoS **15-1**
 - automatic classification and queueing **37-21**
 - configuring **15-4**
 - ensuring port security with QoS **37-44**
 - trusted boundary for QoS **37-44**
- IP Port Security for Static Hosts
 - on a Layer 2 access port **22-21**
 - on a PVLAN host port **22-24**
- IP precedence **37-2**

- IP-precedence-to-DSCP map for QoS **37-75**
- IP protocols
- in ACLs **35-12**
 - routing **1-14**
- IP protocols in ACLs **35-12**
- IP routes, monitoring **39-113**
- IP routing
- connecting interfaces with **11-8**
 - disabling **39-20**
 - enabling **39-20**
- IP Service Level Agreements
- See IP SLAs
- IP service levels, analyzing **42-1**
- IP services feature set **1-2**
- IP SLAs
- benefits **42-2**
 - configuration guidelines **42-6**
 - configuring object tracking **43-8**
 - Control Protocol **42-4**
 - default configuration **42-6**
 - definition **42-1**
 - ICMP echo operation **42-11**
 - measuring network performance **42-3**
 - monitoring **42-13**
 - multioperations scheduling **42-5**
 - object tracking **43-8**
 - operation **42-3**
 - reachability tracking **43-8**
 - responder
 - described **42-4**
 - enabling **42-7** - response time **42-4**
 - scheduling **42-5**
 - SNMP support **42-2**
 - supported metrics **42-2**
 - threshold monitoring **42-6**
 - track state **43-8**
 - UDP jitter operation **42-8**
- IP source guard
- and DHCP snooping **22-16**
 - and EtherChannels **22-19**
 - and IEEE 802.1x **22-19**
 - and port security **22-19**
 - and private VLANs **22-19**
 - and routed ports **22-18**
 - and TCAM entries **22-19**
 - and trunk interfaces **22-19**
 - and VRF **22-19**
 - binding configuration
 - automatic **22-16**
 - manual **22-16**
 - binding table **22-16**
 - configuration guidelines **22-18**
 - default configuration **22-18**
 - described **22-16**
 - disabling **22-20**
 - displaying
 - bindings **22-26**
 - configuration **22-26**
 - enabling **22-19, 22-21**
 - filtering
 - source IP address **22-17**
 - source IP and MAC address **22-17**
 - source IP address filtering **22-17**
 - source IP and MAC address filtering **22-17**
 - static bindings
 - adding **22-19, 22-21**
 - deleting **22-20**
 - static hosts **22-21**
- IP traceroute
- executing **48-14**
 - overview **48-13**
- IP unicast routing
- address resolution **39-10**
 - administrative distances **39-100, 39-111**
 - ARP **39-11**
 - assigning IP addresses to Layer 3 interfaces **39-8**
 - authentication keys **39-111**

- broadcast
 - address **39-17**
 - flooding **39-18**
 - packets **39-15**
 - storms **39-15**
- classless routing **39-9**
- configuring static routes **39-99**
- default
 - addressing configuration **39-7**
 - gateways **39-13**
 - networks **39-101**
 - routes **39-101**
 - routing **39-4**
- directed broadcasts **39-16**
- disabling **39-20**
- dynamic routing **39-4**
- enabling **39-20**
- EtherChannel Layer 3 interface **39-6**
- IGP **39-31**
- inter-VLAN **39-3**
- IP addressing
 - classes **39-8**
 - configuring **39-6**
- IPv6 **40-4**
- IRDP **39-14**
- Layer 3 interfaces **39-6**
- MAC address and IP address **39-10**
- passive interfaces **39-109**
- protocols
 - distance-vector **39-4**
 - dynamic **39-4**
 - link-state **39-4**
- proxy ARP **39-11**
- redistribution **39-101**
- reverse address resolution **39-10**
- routed ports **39-6**
- static routing **39-4**
- steps to configure **39-6**
- subnet mask **39-8**
- subnet zero **39-8**
- supernet **39-9**
- UDP **39-17**
- unicast reverse path forwarding **1-15**
- with SVIs **39-6**
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP
- IPv4 ACLs
 - applying to interfaces **35-20**
 - extended, creating **35-11**
 - named **35-15**
 - standard, creating **35-10**
- IPv6
 - ACLs
 - displaying **36-9**
 - limitations **36-3**
 - matching criteria **36-3**
 - port **36-2**
 - precedence **36-3**
 - router **36-2**
 - addresses **40-3**
 - address formats **40-3**
 - and switch stacks **40-11**
 - applications **40-6**
 - assigning address **40-13**
 - autoconfiguration **40-6**
 - CEFv6 **40-21**
 - configuring static routes **40-22**
 - default configuration **40-13**
 - default router preference (DRP) **40-6**
 - defined **40-1, 40-3**
 - Enhanced Interior Gateway Routing Protocol (EIGRP) **40-8**
 - IPv6 **40-8**
 - EIGRP IPv6 Commands **40-8**
 - Router ID **40-8**
 - feature limitations **40-10**
 - features not supported **40-10**

forwarding **40-13**
 ICMP **40-5**
 monitoring **40-29**
 neighbor discovery **40-5**
 OSPF **40-8**
 path MTU discovery **40-5**
 SDM templates **8-2, 25-1, 36-1**
 stack master functions **40-11**
 supported features **40-4**
 switch limitations **40-10**
 understanding static routes **40-8**
 IPv6 traffic, filtering **36-4**
IRDP
 configuring **39-14**
 definition **39-14**
 support for **1-15**
IS-IS
 addresses **39-71**
 area routing **39-71**
 default configuration **39-73**
 monitoring **39-81**
 show commands **39-81**
 system routing **39-71**
ISO CLNS
 clear commands **39-81**
 dynamic routing protocols **39-71**
 monitoring **39-81**
 NETs **39-71**
 NSAPs **39-71**
 OSI standard **39-71**
ISO IGRP
 area routing **39-71**
 system routing **39-71**
isolated port **16-2**
isolated VLANs **16-2, 16-3**

J

join messages, IGMP **24-3**

K

KDC
 described **6-41**
 See also Kerberos
 keepalive messages **18-2**
Kerberos
 authenticating to
 boundary switch **6-43**
 KDC **6-43**
 network services **6-44**
 configuration examples **6-40**
 configuring **6-44**
 credentials **6-41**
 cryptographic software image **6-40**
 described **6-41**
 KDC **6-41**
 operation **6-43**
 realm **6-42**
 server **6-42**
 support for **1-12**
 switch as trusted third party **6-40**
 terms **6-41**
 TGT **6-42**
 tickets **6-41**
 key distribution center
 See KDC

L

l2protocol-tunnel command **17-13**
LACP
 Layer 2 protocol tunneling **17-9**
 See EtherChannel
 Layer 2 frames, classification with CoS **37-2**
 Layer 2 interfaces, default configuration **11-17**
 Layer 2 protocol tunneling
 configuring **17-10**
 configuring for EtherChannels **17-14**

- default configuration **17-11**
- defined **17-8**
- guidelines **17-12**
- Layer 2 traceroute
 - and ARP **48-12**
 - and CDP **48-12**
 - broadcast traffic **48-11**
 - described **48-11**
 - IP addresses and subnets **48-12**
 - MAC addresses and VLANs **48-12**
 - multicast traffic **48-12**
 - multiple devices on a port **48-12**
 - unicast traffic **48-11**
 - usage guidelines **48-12**
- Layer 3 features **1-14**
- Layer 3 interfaces
 - assigning IP addresses to **39-8**
 - assigning IPv4 and IPv6 addresses to **40-16**
 - assigning IPv6 addresses to **40-14**
 - changing from Layer 2 mode **39-8, 39-88**
 - types of **39-6**
- Layer 3 packets, classification methods **37-2**
- LDAP **4-2**
- Leaking IGMP Reports **21-4**
- LEDs, switch
 - See hardware installation guide
- Lightweight Directory Access Protocol
 - See LDAP
- line configuration mode **2-2**
- Link Aggregation Control Protocol
 - See EtherChannel
- Link Failure, detecting unidirectional **19-8**
- Link Layer Discovery Protocol
 - See CDP
- link local unicast addresses **40-5**
- link redundancy
 - See Flex Links
- links, unidirectional **29-1**
- link state advertisements (LSAs) **39-37**
- link-state protocols **39-4**
- link-state tracking
 - configuring **38-25**
 - described **38-23**
- LLDP
 - configuring **28-4**
 - characteristics **28-6**
 - default configuration **28-4**
 - enabling **28-5**
 - monitoring and maintaining **28-10**
 - overview **28-1**
 - supported TLVs **28-2**
 - switch stack considerations **28-2**
 - transmission timer and holdtime, setting **28-6**
- LLDP-MED
 - configuring
 - procedures **28-4**
 - TLVs **28-6**
 - monitoring and maintaining **28-10**
 - overview **28-1, 28-2**
 - supported TLVs **28-2**
- LLDP Media Endpoint Discovery
 - See LLDP-MED
- load balancing **41-4**
- local SPAN **30-2**
- location TLV **28-3, 28-7**
- logging messages, ACL **35-9**
- login authentication
 - with RADIUS **6-30**
 - with TACACS+ **6-14**
- login banners **5-17**
- log messages
 - See system message logging
- Long-Reach Ethernet (LRE) technology **1-21**
- loop guard
 - described **20-11**
 - enabling **20-18**
 - support for **1-8**

M

MAC/PHY configuration status TLV **28-2**

MAC addresses

aging time **5-21**

and VLAN association **5-20**

building the address table **5-20**

default configuration **5-21**

disabling learning on a VLAN **5-30**

discovering **5-31**

displaying **5-31**

displaying in the IP source binding table **22-26**

dynamic

learning **5-20**

removing **5-22**

in ACLs **35-28**

IP address association **39-10**

manually assigning IP address **3-16**

static

adding **5-28**

allowing **5-29, 5-30**

characteristics of **5-27**

dropping **5-29**

removing **5-28**

MAC address learning **1-6**

MAC address learning, disabling on a VLAN **5-30**

MAC address notification, support for **1-16**

MAC address-table move update

configuration guidelines **21-8**

configuring **21-12**

default configuration **21-8**

description **21-6**

monitoring **21-14**

MAC address-to-VLAN mapping **13-26**

MAC authentication bypass **9-16**

MAC extended access lists

applying to Layer 2 interfaces **35-29**

configuring for QoS **37-53**

creating **35-28**

defined **35-28**

for QoS classification **37-5**

macros

See Smartports macros

magic packet **9-27**

manageability features **1-6**

management access

in-band

browser session **1-7**

CLI session **1-7**

device manager **1-7**

SNMP **1-7**

out-of-band console port connection **1-7**

management address TLV **28-2**

management options

CLI **2-1**

CNS **4-1**

Network Assistant **1-3**

overview **1-5**

switch stacks **1-3**

mapping tables for QoS

configuring

CoS-to-DSCP **37-74**

DSCP **37-74**

DSCP-to-CoS **37-77**

DSCP-to-DSCP-mutation **37-78**

IP-precedence-to-DSCP **37-75**

policed-DSCP **37-76**

described **37-13**

marking

action in policy map **37-59**

action with aggregate policers **37-72**

described **37-4, 37-9**

matching IPv4 ACLs **35-8**

maximum aging time

MSTP **19-25**

STP **18-23**

maximum hop count, MSTP **19-25**

- maximum number of allowed devices, port-based authentication **9-38**
- maximum-paths command **39-58, 39-99**
- MDA
- configuration guidelines **9-30 to 9-31**
 - described **1-11, 9-30**
 - exceptions with authentication process **9-4**
- membership mode, VLAN port **13-3**
- messages, to users through banners **5-17**
- metrics, in BGP **39-58**
- metric translations, between routing protocols **39-105**
- metro tags **17-2**
- MHSRP **41-4**
- MIBs
- accessing files with FTP **A-4**
 - location of files **A-4**
 - overview **33-1**
 - SNMP interaction with **33-4**
 - supported **A-1**
- mirroring traffic for analysis **30-1**
- mismatches, autonegotiation **48-9**
- module number **11-8**
- monitoring
- access groups **35-40**
 - BGP **39-70**
 - cables for unidirectional links **29-1**
 - CDP **27-5**
 - CEF **39-98**
 - EIGRP **39-49**
 - fallback bridging **47-11**
 - features **1-16**
 - Flex Links **21-14**
 - HSRP **41-12**
 - IEEE 802.1Q tunneling **17-18**
 - IGMP
 - filters **24-29**
 - snooping **24-16, 25-12**
 - interfaces **11-28**
 - IP
- address tables **39-19**
- multicast routing **45-66**
- routes **39-113**
- IP SLAs operations **42-13**
- IPv4 ACL configuration **35-40**
- IPv6 **40-29**
- IPv6 ACL configuration **36-9**
- IS-IS **39-81**
- ISO CLNS **39-81**
- Layer 2 protocol tunneling **17-18**
- MAC address-table move update **21-14**
- MSDP peers **46-18**
- multicast router interfaces **24-17, 25-12**
- multi-VRF CE **39-96**
- MVR **24-24**
- network traffic for analysis with probe **30-2**
- object tracking **43-9**
- OSPF **39-41**
- port
- blocking **26-19**
 - protection **26-19**
- private VLANs **16-15**
- RP mapping information **45-39**
- source-active messages **46-18**
- speed and duplex mode **11-19**
- traffic flowing among switches **31-1**
- traffic suppression **26-19**
- tunneling **17-18**
- VLAN
- filters **35-41**
 - maps **35-41**
- VLANs **13-14**
- VMPS **13-30**
- VTP **14-18**
- mrouter Port **21-3**
- mrouter port **21-5**
- MSDP
- benefits of **46-3**
 - clearing MSDP connections and statistics **46-18**

- controlling source information
 - forwarded by switch **46-11**
 - originated by switch **46-8**
 - received by switch **46-14**
- default configuration **46-4**
- dense-mode regions
 - sending SA messages to **46-16**
 - specifying the originating address **46-17**
- filtering
 - incoming SA messages **46-14**
 - SA messages to a peer **46-12**
 - SA requests from a peer **46-10**
- join latency, defined **46-6**
- meshed groups
 - configuring **46-15**
 - defined **46-15**
- originating address, changing **46-17**
- overview **46-1**
- peer-RPF flooding **46-2**
- peers
 - configuring a default **46-4**
 - monitoring **46-18**
 - peering relationship, overview **46-1**
 - requesting source information from **46-8**
 - shutting down **46-16**
- source-active messages
 - caching **46-6**
 - clearing cache entries **46-18**
 - defined **46-2**
 - filtering from a peer **46-10**
 - filtering incoming **46-14**
 - filtering to a peer **46-12**
 - limiting data with TTL **46-13**
 - monitoring **46-18**
 - restricting advertised sources **46-9**
- support for **1-15**
- MSTP
 - boundary ports
 - configuration guidelines **19-16**
- described **19-6**
- BPDU filtering
 - described **20-3**
 - enabling **20-14**
- BPDU guard
 - described **20-2**
 - enabling **20-13**
- CIST, described **19-3**
- CIST regional root **19-3**
- CIST root **19-5**
- configuration guidelines **19-15, 20-12**
- configuring
 - forward-delay time **19-24**
 - hello time **19-23**
 - link type for rapid convergence **19-26**
 - maximum aging time **19-25**
 - maximum hop count **19-25**
 - MST region **19-17**
 - neighbor type **19-26**
 - path cost **19-22**
 - port priority **19-20**
 - root switch **19-18**
 - secondary root switch **19-19**
 - switch priority **19-23**
- CST
 - defined **19-3**
 - operations between regions **19-4**
- default configuration **19-15**
- default optional feature configuration **20-12**
- displaying status **19-27**
- enabling the mode **19-17**
- EtherChannel guard
 - described **20-10**
 - enabling **20-17**
- extended system ID
 - effects on root switch **19-18**
 - effects on secondary root switch **19-19**
 - unexpected behavior **19-18**
- IEEE 802.1s

- implementation **19-6**
- port role naming change **19-7**
- terminology **19-5**
- instances supported **18-10**
- interface state, blocking to forwarding **20-2**
- interoperability and compatibility among modes **18-11**
- interoperability with IEEE 802.1D
 - described **19-9**
 - restarting migration process **19-27**
- IST
 - defined **19-3**
 - master **19-3**
 - operations within a region **19-3**
- loop guard
 - described **20-11**
 - enabling **20-18**
- mapping VLANs to MST instance **19-17**
- MST region
 - CIST **19-3**
 - configuring **19-17**
 - described **19-2**
 - hop-count mechanism **19-5**
 - IST **19-3**
 - supported spanning-tree instances **19-2**
 - optional features supported **1-8**
 - overview **19-2**
- Port Fast
 - described **20-2**
 - enabling **20-12**
- preventing root switch selection **20-10**
- root guard
 - described **20-10**
 - enabling **20-18**
- root switch
 - configuring **19-18**
 - effects of extended system ID **19-18**
 - unexpected behavior **19-18**
- shutdown Port Fast-enabled port **20-2**
- stack changes, effects of **19-8**
- status, displaying **19-27**
- MTU
 - system **11-26**
 - system jumbo **11-26**
 - system routing **11-26**
- multiauth
 - support for inaccessible authentication bypass **9-24**
- multiauth mode
 - See multiple-authentication mode
- multicast groups
 - Immediate Leave **24-6**
 - joining **24-3**
 - leaving **24-5**
 - static joins **24-10, 25-8**
- multicast packets
 - ACLs on **35-39**
 - blocking **26-8**
- multicast router interfaces, monitoring **24-17, 25-12**
- multicast router ports, adding **24-10, 25-9**
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm **26-1**
- multicast storm-control command **26-4**
- multicast television application **24-19**
- multicast VLAN **24-18**
- Multicast VLAN Registration
 - See MVR
- multidomain authentication
 - See MDA
- multioperations scheduling, IP SLAs **42-5**
- multiple authentication **9-13**
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE
- multi-VRF CE
 - configuration example **39-92**

configuration guidelines **39-84**
 configuring **39-84**
 default configuration **39-84**
 defined **39-82**
 displaying **39-96**
 monitoring **39-96**
 network components **39-84**
 packet-forwarding process **39-84**
 support for **1-14**

MVR

and address aliasing **24-21**
 and IGMPv3 **24-21**
 configuration guidelines **24-21**
 configuring interfaces **24-22**
 default configuration **24-20**
 described **24-18**
 example application **24-19**
 in the switch stack **24-20**
 modes **24-22**
 monitoring **24-24**
 multicast television application **24-19**
 setting global parameters **24-21**
 support for **1-5**

N**NAC**

AAA down policy **1-12**
 critical authentication **9-23, 9-55**
 IEEE 802.1x authentication using a RADIUS server **9-60**
 IEEE 802.1x validation using RADIUS server **9-60**
 inaccessible authentication bypass **1-12, 9-55**
 Layer 2 IEEE 802.1x validation **1-11, 9-60**
 Layer 2 IP validation **1-11**
 named IPv4 ACLs **35-15**
 named IPv6 ACLs **36-3**
 NameSpace Mapper
 See NSM

native VLAN
 and IEEE 802.1Q tunneling **17-4**
 configuring **13-22**
 default **13-22**
NEAT
 configuring **9-61**
 overview **9-32**
 neighbor discovery, IPv6 **40-5**
 neighbor discovery/recovery, EIGRP **39-43**
 neighbors, BGP **39-65**

Network Admission Control
 See NAC
Network Assistant
 benefits **1-3**
 described **1-5**
 downloading image files **1-3**
 guide mode **1-3**
 management options **1-3**
 managing switch stacks **7-2, 7-18**
 upgrading a switch **B-24**
 wizards **1-3**

network configuration examples
 data center **1-21**
 expanded data center **1-21**
 increasing network performance **1-20**
 providing network services **1-20**
 small to medium-sized network **1-22**

network design
 performance **1-20**
 services **1-20**
Network Edge Access Topology

See NEAT

network management

CDP **27-1**
 RMON **31-1**
 SNMP **33-1**

network performance, measuring with IP SLAs **42-3**
 network policy TLV **28-2, 28-7**
 Network Time Protocol

- See NTP
- no commands **2-4**
- nonhierarchical policy maps
- configuration guidelines **37-39**
 - configuring **37-59**
 - described **37-10**
- non-IP traffic filtering **35-28**
- nontrunking mode **13-16**
- normal-range VLANs **13-4**
- configuration guidelines **13-6**
 - configuring **13-4**
 - defined **13-1**
- no switchport command **11-4**
- not-so-stubby areas
- See NSSA
- NSAPs, as ISO IGRP addresses **39-71**
- NSF Awareness
- IS-IS **39-74**
 - NSM **4-3**
 - NSSA, OSPF **39-37**
- NTP
- associations
 - authenticating **5-4**
 - defined **5-2**
 - enabling broadcast messages **5-6**
 - peer **5-5**
 - server **5-5**
 - default configuration **5-4**
 - displaying the configuration **5-11**
 - overview **5-2**
 - restricting access
 - creating an access group **5-8**
 - disabling NTP services per interface **5-10**
 - source IP address, configuring **5-10**
 - stratum **5-2**
 - support for **1-6**
 - synchronizing devices **5-5**
 - time
 - services **5-2**
- synchronizing **5-2**
-
- O**
- OBFL
- configuring **48-22**
 - described **48-21**
 - displaying **48-22**
- object tracking
- HSRP **43-6**
 - IP SLAs **43-8**
 - IP SLAs, configuring **43-8**
 - monitoring **43-9**
- offline configuration for switch stacks **7-9**
- off mode, VTP **14-3**
- on-board failure logging
- See OBFL
- online diagnostics
- described **49-1**
 - overview **49-1**
 - running tests **49-5**
- open1x
- configuring **9-66**
- open1x authentication
- overview **9-30**
- Open Shortest Path First
- See OSPF
- optimizing system resources **8-1**
- options, management **1-5**
- OSPF
- area parameters, configuring **39-37**
 - configuring **39-35**
 - default configuration
 - metrics **39-39**
 - route **39-39**
 - settings **39-32**
 - described **39-31**
 - for IPv6 **40-8**
 - interface parameters, configuring **39-36**

- LSA group pacing **39-40**
 monitoring **39-41**
 router IDs **39-41**
 route summarization **39-38**
 support for **1-14**
 virtual links **39-39**
- out-of-profile markdown **1-13**
-
- P**
- packet modification, with QoS **37-20**
- PAgP
 Layer 2 protocol tunneling **17-9**
 See EtherChannel
- parallel paths, in routing tables **39-99**
- passive interfaces
 configuring **39-109**
 OSPF **39-39**
- passwords
 default configuration **6-2**
 disabling recovery of **6-5**
 encrypting **6-3**
 for security **1-10**
 overview **6-1**
 recovery of **48-3**
 setting
 enable **6-3**
 enable secret **6-3**
 Telnet **6-6**
 with usernames **6-6**
- VTP domain **14-10**
- path cost
 MSTP **19-22**
 STP **18-20**
- path MTU discovery **40-5**
- PBR
 defined **39-105**
 enabling **39-107**
 fast-switched policy-based routing **39-108**
- local policy-based routing **39-108**
 peers, BGP **39-65**
 percentage thresholds in tracked lists **43-5**
 performance, network design **1-20**
 performance features **1-4**
 persistent self-signed certificate **6-51**
 per-user ACLs and Filter-Ids **9-9**
 per-VLAN spanning-tree plus
 See PVST+
- PE to CE routing, configuring **39-92**
- physical ports **11-2**
- PIM
 default configuration **45-10**
 dense mode
 overview **45-4**
 rendezvous point (RP), described **45-5**
 RPF lookups **45-8**
 displaying neighbors **45-67**
 enabling a mode **45-13**
 overview **45-3**
 router-query message interval, modifying **45-42**
 shared tree and source tree, overview **45-39**
 shortest path tree, delaying the use of **45-41**
 sparse mode
 join messages and shared tree **45-5**
 overview **45-5**
 prune messages **45-5**
 RPF lookups **45-8**
- stub routing
 configuration guidelines **39-28**
 enabling **39-28, 45-26**
 overview **45-5**
 understanding **39-27**
- support for **1-15**
- versions
 interoperability **45-11**
 troubleshooting interoperability problems **45-39**
 v2 improvements **45-4**
- PIM-DVMRP, as snooping method **24-9**

- ping
- character output description **48-11**
 - executing **48-10**
 - overview **48-10**
- policed-DSCP map for QoS **37-76**
- policers
- configuring
 - for each matched traffic class **37-59**
 - for more than one traffic class **37-72**
 - described **37-4**
 - displaying **37-92**
 - number of **37-40**
 - types of **37-10**
- policing
- described **37-4**
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm **37-10**
- policy-based routing
- See PBR
- policy maps for QoS
- characteristics of **37-59**
 - described **37-8**
 - displaying **37-93**
 - hierarchical **37-9**
 - hierarchical on SVIs
 - configuration guidelines **37-39**
 - configuring **37-64**
 - described **37-12**
 - nonhierarchical on physical ports
 - configuration guidelines **37-39**
 - configuring **37-59**
 - described **37-10**
- port ACLs
- defined **35-2**
 - types of **35-3**
- Port Aggregation Protocol
- See EtherChannel
- port-based authentication
- accounting **9-15**
 - authentication server
 - defined **9-3, 10-2**
 - RADIUS server **9-3**
 - client, defined **9-3, 10-2**
 - configuration guidelines **9-36, 10-9**
 - configuring
 - 802.1x authentication **9-39**
 - guest VLAN **9-52**
 - host mode **9-44**
 - inaccessible authentication bypass **9-55**
 - manual re-authentication of a client **9-47**
 - periodic re-authentication **9-45**
 - quiet period **9-47**
 - RADIUS server **9-44, 10-12**
 - RADIUS server parameters on the switch **9-43, 10-11**
 - restricted VLAN **9-53**
 - switch-to-client frame-retransmission number **9-48, 9-49**
 - switch-to-client retransmission time **9-48**
 - violation mode **9-26**
 - violation modes **9-38 to 9-39**
 - default configuration **9-35, 10-9**
 - described **9-2**
 - device roles **9-3, 10-2**
 - displaying statistics **9-68, 10-17**
 - downloadable ACLs and redirect URLs
 - configuring **9-63**
 - overview **9-19 to 9-21**
 - EAPOL-start frame **9-6**
 - EAP-request/identity frame **9-6**
 - EAP-response/identity frame **9-6**
 - enabling
 - 802.1X authentication **10-11**
 - encapsulation **9-4**
 - flexible authentication ordering
 - configuring **9-66**
 - overview **9-30**

guest VLAN
 configuration guidelines **9-22, 9-23**
 described **9-21**

host mode **9-12**
 inaccessible authentication bypass
 configuring **9-55**
 described **9-23**
 guidelines **9-37**
 initiation and message exchange **9-6**
 magic packet **9-27**
 maximum number of allowed devices per port **9-38**
 method lists **9-39**
 multiple authentication **9-13**
 multiple-hosts mode, described **9-12**
 per-user ACLs
 AAA authorization **9-39**
 configuration tasks **9-19**
 described **9-18**
 RADIUS server attributes **9-18**
 ports
 authorization state and dot1x port-control command **9-11**
 authorized and unauthorized **9-11**
 voice VLAN **9-25**
 port security
 and voice VLAN **9-26**
 described **9-26**
 interactions **9-26**
 multiple-hosts mode **9-12**
 readiness check
 configuring **9-41**
 described **9-16, 9-41**
 resetting to default values **9-67**
 stack changes, effects of **9-12**
 statistics, displaying **9-68**
 switch
 as proxy **9-3, 10-2**
 RADIUS client **9-3**
 switch supplicant

configuring **9-61**
 overview **9-32**

user distribution
 guidelines **9-28**
 overview **9-27**

VLAN assignment
 AAA authorization **9-39**
 characteristics **9-17**
 configuration tasks **9-17**
 described **9-16**
 voice aware 802.1x security
 configuring **9-42**
 described **9-31, 9-42**

voice VLAN
 described **9-25**
 PVID **9-25**
 VVID **9-25**
 wake-on-LAN, described **9-27**

port-based authentication methods, supported **9-8**
 port blocking **1-4, 26-7**
 port-channel
 See EtherChannel

port description TLV **28-2**

Port Fast
 described **20-2**
 enabling **20-12**
 mode, spanning tree **13-28**
 support for **1-8**

port membership modes, VLAN **13-3**

port priority
 MSTP **19-20**
 STP **18-18**

ports
 10-Gigabit Ethernet **11-6**
 access **11-3**
 blocking **26-7**
 dynamic access **13-3**
 IEEE 802.1Q tunnel **13-4**
 protected **26-6**

- routed **11-4**
- secure **26-9**
- static-access **13-3, 13-10**
- switch **11-2**
- trunks **13-3, 13-15**
- VLAN assignments **13-10**
- port security
 - aging **26-17**
 - and private VLANs **26-18**
 - and QoS trusted boundary **37-44**
 - and stacking **26-18**
 - configuring **26-13**
 - default configuration **26-11**
 - described **26-8**
 - displaying **26-19**
 - enabling **26-18**
 - on trunk ports **26-14**
 - sticky learning **26-9**
 - violations **26-10**
 - with other features **26-11**
- port-shutdown response, VMPS **13-26**
- port VLAN ID TLV **28-2**
- power management TLV **28-2, 28-7**
- preemption, default configuration **21-8**
- preemption delay, default configuration **21-8**
- preferential treatment of traffic
 - See QoS
- prefix lists, BGP **39-62**
- preventing unauthorized access **6-1**
- primary links **21-2**
- primary VLANs **16-1, 16-3**
- priority
 - HSRP **41-8**
 - overriding CoS **15-6**
 - trusting CoS **15-6**
- private VLAN edge ports
 - See protected ports
- private VLANs
 - across multiple switches **16-4**
 - and SDM template **16-4**
 - and SVIs **16-5**
 - and switch stacks **16-6**
 - benefits of **16-1**
 - community ports **16-2**
 - community VLANs **16-2, 16-3**
 - configuration guidelines **16-7, 16-9**
 - configuration tasks **16-6**
 - configuring **16-10**
 - default configuration **16-7**
 - end station access to **16-3**
 - IP addressing **16-3**
 - isolated port **16-2**
 - isolated VLANs **16-2, 16-3**
 - mapping **16-14**
 - monitoring **16-15**
 - ports
 - community **16-2**
 - configuration guidelines **16-9**
 - configuring host ports **16-12**
 - configuring promiscuous ports **16-13**
 - described **13-4**
 - isolated **16-2**
 - promiscuous **16-2**
 - primary VLANs **16-1, 16-3**
 - promiscuous ports **16-2**
 - secondary VLANs **16-2**
 - subdomains **16-1**
 - traffic in **16-5**
- privileged EXEC mode **2-2**
- privilege levels
 - changing the default for lines **6-9**
 - exiting **6-9**
 - logging into **6-9**
 - overview **6-2, 6-7**
 - setting a command with **6-8**
- promiscuous ports
 - configuring **16-13**
 - defined **16-2**

- protected mode
 described [3-17](#)
 disabling [3-18](#)
 enabling [3-18](#)
 guidelines and restrictions [3-18](#)
- protected ports [1-10, 26-6](#)
- protocol-dependent modules, EIGRP [39-43](#)
- Protocol-Independent Multicast Protocol
 See PIM
- provider edge devices [39-82](#)
- provisioning new members for a switch stack [7-9](#)
- proxy ARP
 configuring [39-13](#)
 definition [39-11](#)
 with IP routing disabled [39-13](#)
- proxy reports [21-4](#)
- pruning, VTP
 disabling
 in VTP domain [14-16](#)
 on a port [13-21](#)
 enabling
 in VTP domain [14-16](#)
 on a port [13-21](#)
 examples [14-7](#)
 overview [14-6](#)
- pruning-eligible list
 changing [13-21](#)
 for VTP pruning [14-6](#)
 VLANs [14-16](#)
- PVST+
 described [18-10](#)
 IEEE 802.1Q trunking interoperability [18-11](#)
 instances supported [18-10](#)
-
- Q**
- QoS
 and MQC commands [37-2](#)
 auto-QoS
 categorizing traffic [37-22](#)
 configuration and defaults display [37-35](#)
 configuration guidelines [37-32](#)
 described [37-21](#)
 disabling [37-34](#)
 displaying generated commands [37-34](#)
 displaying the initial configuration [37-35](#)
 effects on running configuration [37-32](#)
 list of generated commands [37-25](#)
 basic model [37-4](#)
 classification
 class maps, described [37-8](#)
 defined [37-4](#)
 DSCP transparency, described [37-45](#)
 flowchart [37-7](#)
 forwarding treatment [37-3](#)
 in frames and packets [37-3](#)
 IP ACLs, described [37-6, 37-8](#)
 MAC ACLs, described [37-5, 37-8](#)
 options for IP traffic [37-6](#)
 options for non-IP traffic [37-5](#)
 policy maps, described [37-8](#)
 trust DSCP, described [37-5](#)
 trusted CoS, described [37-5](#)
 trust IP precedence, described [37-5](#)
 class maps
 configuring [37-54](#)
 displaying [37-92](#)
 configuration guidelines
 auto-QoS [37-32](#)
 standard QoS [37-38](#)
 configuring
 aggregate policers [37-72](#)
 auto-QoS [37-21](#)
 default port CoS value [37-43](#)
 DSCP maps [37-74](#)
 DSCP transparency [37-45](#)
 DSCP trust states bordering another domain [37-46](#)

- egress queue characteristics [37-84](#)
- ingress queue characteristics [37-80](#)
- IP extended ACLs [37-50](#)
- IP standard ACLs [37-49](#)
- MAC ACLs [37-53](#)
- policy maps, hierarchical [37-64](#)
- policy maps on physical ports [37-59](#)
- port trust states within the domain [37-42](#)
- trusted boundary [37-44](#)
- default auto configuration [37-22](#)
- default standard configuration [37-36](#)
- displaying statistics [37-92](#)
- DSCP transparency [37-45](#)
- egress queues
 - allocating buffer space [37-85](#)
 - buffer allocation scheme, described [37-19](#)
 - configuring shaped weights for SRR [37-89](#)
 - configuring shared weights for SRR [37-90](#)
 - described [37-4](#)
 - displaying the threshold map [37-88](#)
 - flowchart [37-18](#)
 - mapping DSCP or CoS values [37-87](#)
 - scheduling, described [37-4](#)
 - setting WTD thresholds [37-85](#)
 - WTD, described [37-20](#)
- enabling globally [37-41](#)
- flowcharts
 - classification [37-7](#)
 - egress queueing and scheduling [37-18](#)
 - ingress queueing and scheduling [37-16](#)
 - policing and marking [37-11](#)
- implicit deny [37-8](#)
- ingress queues
 - allocating bandwidth [37-82](#)
 - allocating buffer space [37-82](#)
 - buffer and bandwidth allocation, described [37-17](#)
 - configuring shared weights for SRR [37-82](#)
 - configuring the priority queue [37-83](#)
 - described [37-4](#)
- displaying the threshold map [37-81](#)
- flowchart [37-16](#)
- mapping DSCP or CoS values [37-81](#)
- priority queue, described [37-17](#)
- scheduling, described [37-4](#)
- setting WTD thresholds [37-81](#)
- WTD, described [37-17](#)
- IP phones
 - automatic classification and queueing [37-21](#)
 - detection and trusted settings [37-21, 37-44](#)
 - limiting bandwidth on egress interface [37-91](#)
- mapping tables
 - CoS-to-DSCP [37-74](#)
 - displaying [37-93](#)
 - DSCP-to-CoS [37-77](#)
 - DSCP-to-DSCP-mutation [37-78](#)
 - IP-precedence-to-DSCP [37-75](#)
 - policed-DSCP [37-76](#)
 - types of [37-13](#)
- marked-down actions [37-62, 37-68](#)
- marking, described [37-4, 37-9](#)
- overview [37-2](#)
- packet modification [37-20](#)
- policers
 - configuring [37-62, 37-68, 37-72](#)
 - described [37-9](#)
 - displaying [37-92](#)
 - number of [37-40](#)
 - types of [37-10](#)
- policies, attaching to an interface [37-9](#)
- policing
 - described [37-4, 37-9](#)
 - token bucket algorithm [37-10](#)
- policy maps
 - characteristics of [37-59](#)
 - displaying [37-93](#)
 - hierarchical [37-9](#)
 - hierarchical on SVIs [37-64](#)
 - nonhierarchical on physical ports [37-59](#)

- QoS label, defined **37-4**
- queues
 - configuring egress characteristics **37-84**
 - configuring ingress characteristics **37-80**
 - high priority (expedite) **37-20, 37-91**
 - location of **37-14**
 - SRR, described **37-15**
 - WTD, described **37-14**
 - rewrites **37-20**
 - support for **1-13**
 - trust states
 - bordering another domain **37-46**
 - described **37-5**
 - trusted device **37-44**
 - within the domain **37-42**
- quality of service
 - See QoS
- queries, IGMP **24-4**
- query solicitation, IGMP **24-13**

R

- RADIUS
 - attributes
 - vendor-proprietary **6-38**
 - vendor-specific **6-36**
 - configuring
 - accounting **6-35**
 - authentication **6-30**
 - authorization **6-34**
 - communication, global **6-28, 6-36**
 - communication, per-server **6-27, 6-28**
 - multiple UDP ports **6-28**
 - default configuration **6-27**
 - defining AAA server groups **6-32**
 - displaying the configuration **6-40**
 - identifying the server **6-27**
 - limiting the services to the user **6-34**
 - method list, defined **6-27**
- operation of **6-19**
- overview **6-18**
- server load balancing **6-40**
- suggested network environments **6-18**
- support for **1-12**
- tracking services accessed by user **6-35**
- RADIUS Change of Authorization **6-20**
- range
 - macro **11-12**
 - of interfaces **11-10**
- rapid convergence **19-10**
- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - described **18-10**
 - IEEE 802.1Q trunking interoperability **18-11**
 - instances supported **18-10**
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP **39-11**
- RCP
 - configuration files
 - downloading **B-18**
 - overview **B-16**
 - preparing the server **B-17**
 - uploading **B-19**
 - image files
 - deleting old image **B-38**
 - downloading **B-36**
 - preparing the server **B-35**
 - uploading **B-38**
 - reachability, tracking IP SLAs IP host **43-8**
 - readiness check
 - port-based authentication
 - configuring **9-41**
 - described **9-16, 9-41**
 - reconfirmation interval, VMPS, changing **13-30**
 - reconfirming dynamic VLAN membership **13-29**
 - recovery procedures **48-1**

- redirect URL **9-19, 9-20, 9-63**
- redundancy
- EtherChannel **38-2**
 - HSRP **41-1**
 - STP
 - backbone **18-8**
 - multidrop backbone **20-5**
 - path cost **13-24**
 - port priority **13-23**
 - redundant links and UplinkFast **20-15**
 - reliable transport protocol, EIGRP **39-43**
 - reloading software **3-26**
 - Remote Authentication Dial-In User Service
 - See RADIUS
 - Remote Copy Protocol
 - See RCP
 - Remote Network Monitoring
 - See RMON
 - Remote SPAN
 - See RSPAN
 - remote SPAN **30-3**
 - report suppression, IGMP
 - described **24-6**
 - disabling **24-16, 25-11**
 - resequencing ACL entries **35-15**
 - reserved addresses in DHCP pools **22-28**
 - resets, in BGP **39-57**
 - resetting a UDLD-shutdown interface **29-6**
 - responder, IP SLAs
 - described **42-4**
 - enabling **42-7**
 - response time, measuring with IP SLAs **42-4**
 - restricted VLAN
 - configuring **9-53**
 - described **9-22**
 - using with IEEE 802.1x **9-22**
 - restricting access
 - NTP services **5-8**
 - overview **6-1**
 - passwords and privilege levels **6-2**
 - RADIUS **6-18**
 - TACACS+ **6-10**
 - retry count, VMPS, changing **13-30**
 - reverse address resolution **39-10**
 - Reverse Address Resolution Protocol
 - See RARP
 - RFC
 - 1112, IP multicast and IGMP **24-2**
 - 1157, SNMPv1 **33-2**
 - 1166, IP addresses **39-8**
 - 1305, NTP **5-2**
 - 1587, NSSAs **39-31**
 - 1757, RMON **31-2**
 - 1901, SNMPv2C **33-2**
 - 1902 to 1907, SNMPv2 **33-2**
 - 2236, IP multicast and IGMP **24-2**
 - 2273-2275, SNMPv3 **33-2**
 - RFC 5176 Compliance **6-21**
 - RIP
 - advertisements **39-21**
 - authentication **39-24**
 - configuring **39-22**
 - default configuration **39-22**
 - described **39-21**
 - for IPv6 **40-8**
 - hop counts **39-21**
 - split horizon **39-25**
 - summary addresses **39-25**
 - support for **1-14**
 - RMON
 - default configuration **31-3**
 - displaying status **31-6**
 - enabling alarms and events **31-3**
 - groups supported **31-2**
 - overview **31-1**
 - statistics
 - collecting group Ethernet **31-6**
 - collecting group history **31-5**

- support for **1-16**
- root guard
 - described **20-10**
 - enabling **20-18**
 - support for **1-8**
- root switch
 - MSTP **19-18**
 - STP **18-16**
- route calculation timers, OSPF **39-39**
- route dampening, BGP **39-69**
- routed packets, ACLs on **35-39**
- routed ports
 - configuring **39-6**
 - defined **11-4**
 - IP addresses on **11-24, 39-6**
- route-map command **39-108**
- route maps
 - BGP **39-60**
 - policy-based routing **39-106**
- router ACLs
 - defined **35-2**
 - types of **35-4**
- route reflectors, BGP **39-68**
- router ID, OSPF **39-41**
- route selection, BGP **39-58**
- route summarization, OSPF **39-38**
- route targets, VPN **39-84**
- routing
 - default **39-4**
 - dynamic **39-4**
 - redistribution of information **39-101**
 - static **39-4**
- routing domain confederation, BGP **39-67**
- Routing Information Protocol
 - See RIP
- routing protocol administrative distances **39-100**
- RSPAN **30-3**
 - and stack changes **30-10**
 - characteristics **30-9**
- configuration guidelines **30-18**
- default configuration **30-11**
- destination ports **30-8**
- displaying status **30-29**
- in a switch stack **30-2**
- interaction with other features **30-9**
- monitored ports **30-6**
- monitoring ports **30-8**
- overview **1-16, 30-1**
- received traffic **30-5**
- session limits **30-12**
- sessions
 - creating **30-18**
 - defined **30-4**
 - limiting source traffic to specific VLANs **30-21**
 - specifying monitored ports **30-18**
 - with ingress traffic enabled **30-23**
- source ports **30-6**
- transmitted traffic **30-6**
- VLAN-based **30-7**
- RSTP
 - active topology **19-10**
 - BPDU
 - format **19-13**
 - processing **19-13**
 - designated port, defined **19-9**
 - designated switch, defined **19-9**
 - interoperability with IEEE 802.1D
 - described **19-9**
 - restarting migration process **19-27**
 - topology changes **19-14**
 - overview **19-9**
 - port roles
 - described **19-9**
 - synchronized **19-12**
 - proposal-agreement handshake process **19-10**
 - rapid convergence
 - cross-stack rapid convergence **19-11**
 - described **19-10**

- edge ports and Port Fast **19-10**
 - point-to-point links **19-10, 19-26**
 - root ports **19-10**
 - root port, defined **19-9**
See also MSTP
 - running configuration
replacing **B-20, B-21**
rolling back **B-20, B-21**
saving **3-19**

 - S**
 - scheduled reloads **3-26**
 - scheduling, IP SLAs operations **42-5**
 - SDM
described **8-1**
switch stack consideration **7-12**
templates

configuring **8-5**
number of **8-1**
 - SDM template
configuring **8-4**
dual IPv4 and IPv6 **8-2**
types of **8-1**
 - secondary VLANs **16-2**
 - secure HTTP client
configuring **6-55**
displaying **6-56**
 - secure HTTP server
configuring **6-54**
displaying **6-56**
 - secure MAC addresses
and switch stacks **26-18**
deleting **26-16**
maximum number of **26-10**
types of **26-9**
 - secure ports
and switch stacks **26-18**
configuring **26-9**
- secure remote connections **6-46**
- Secure Shell
See SSH
- Secure Socket Layer
See SSL
- security, port **26-8**
- security features **1-10**
- sequence numbers in log messages **32-8**
- server mode, VTP **14-3**
- service-provider network, MSTP and RSTP **19-1**
- service-provider networks
and customer VLANs **17-2**
and IEEE 802.1Q tunneling **17-1**
Layer 2 protocols across **17-8**
Layer 2 protocol tunneling for EtherChannels **17-9**
- set-request operation **33-4**
- severity levels, defining in system messages **32-9**
- shaped round robin
See SRR
- show access-lists hw-summary command **35-22**
- show and more command output, filtering **2-9**
- show cdp traffic command **27-5**
- show configuration command **11-23**
- show forward command **48-18**
- show interfaces command **11-19, 11-23**
- show interfaces switchport **21-4**
- show l2protocol command **17-13, 17-15, 17-16**
- showlldp traffic command **28-11**
- show platform forward command **48-18**
- show running-config command
displaying ACLs **35-20, 35-21, 35-32, 35-35**
interface description in **11-23**
- shutdown command on interfaces **11-29**
- shutdown threshold for Layer 2 protocol packets **17-11**
- Simple Network Management Protocol
See SNMP
- single session ID **9-33**
- small-frame arrival rate, configuring **26-5**
- Smartports macros

- applying Cisco-default macros **12-6**
- applying global parameter values **12-5, 12-6**
- applying macros **12-5**
- applying parameter values **12-5, 12-7**
- configuration guidelines **12-2**
- creating **12-4**
- default configuration **12-2**
- defined **12-1**
- displaying **12-8**
- tracing **12-3**
- SNAP** **27-1**
- SNMP**
 - accessing MIB variables with **33-4**
 - agent
 - described **33-4**
 - disabling **33-7**
 - and IP SLAs **42-2**
 - authentication level **33-10**
 - community strings
 - configuring **33-8**
 - overview **33-4**
 - configuration examples **33-18**
 - default configuration **33-6**
 - engine ID **33-7**
 - groups **33-6, 33-9**
 - host **33-6**
 - ifIndex values **33-5**
 - in-band management **1-7**
 - informs
 - and trap keyword **33-12**
 - described **33-5**
 - differences from traps **33-5**
 - disabling **33-15**
 - enabling **33-15**
 - limiting access by TFTP servers **33-17**
 - limiting system log messages to NMS **32-10**
 - manager functions **1-6, 33-3**
 - MIBs
 - location of **A-4**
 - supported **A-1**
 - notifications **33-5**
 - overview **33-1, 33-4**
 - security levels **33-3**
 - setting CPU threshold notification **33-16**
 - status, displaying **33-19**
 - system contact and location **33-16**
 - trap manager, configuring **33-14**
 - traps
 - described **33-3, 33-5**
 - differences from informs **33-5**
 - disabling **33-15**
 - enabling **33-12**
 - enabling MAC address notification **5-22, 5-24, 5-26**
 - overview **33-1, 33-4**
 - types of **33-12**
 - users **33-6, 33-9**
 - versions supported **33-2**
 - SNMP and Syslog Over IPv6 **40-9**
 - SNMPv1 **33-2**
 - SNMPv2C **33-2**
 - SNMPv3 **33-2**
 - snooping, IGMP **24-2**
 - software compatibility
 - See stacks, switch
 - software images
 - location in flash **B-25**
 - recovery procedures **48-2**
 - scheduling reloads **3-26**
 - tar file format, described **B-25**
 - See also downloading and uploading
 - source addresses
 - in IPv4 ACLs **35-12**
 - in IPv6 ACLs **36-6**
 - source-and-destination-IP address based forwarding, EtherChannel **38-8**
 - source-and-destination MAC address forwarding, EtherChannel **38-8**
 - source-IP address based forwarding, EtherChannel **38-8**

- source-MAC address forwarding, EtherChannel **38-8**
- Source-specific multicast
See SSM
- SPAN
and stack changes **30-10**
configuration guidelines **30-12**
default configuration **30-11**
destination ports **30-8**
displaying status **30-29**
interaction with other features **30-9**
monitored ports **30-6**
monitoring ports **30-8**
overview **1-16, 30-1**
ports, restrictions **26-12**
received traffic **30-5**
session limits **30-12**
sessions
 configuring ingress forwarding **30-16, 30-24**
 creating **30-13, 30-25**
 defined **30-4**
 limiting source traffic to specific VLANs **30-16**
 removing destination (monitoring) ports **30-14**
 specifying monitored ports **30-13, 30-25**
 with ingress traffic enabled **30-15**
source ports **30-6**
transmitted traffic **30-6**
VLAN-based **30-7**
spanning tree and native VLANs **13-17**
Spanning Tree Protocol
 See STP
- SPAN traffic **30-5**
- split horizon, RIP **39-25**
- SRR
configuring
 shaped weights on egress queues **37-89**
 shared weights on egress queues **37-90**
 shared weights on ingress queues **37-82**
- described **37-15**
- shaped mode **37-15**
- shared mode **37-15**
- support for **1-13**
- SSH
configuring **6-47**
described **1-7, 6-46**
encryption methods **6-46**
switch stack considerations **6-46, 7-18**
user authentication methods, supported **6-46**
- SSL
configuration guidelines **6-52**
configuring a secure HTTP client **6-55**
configuring a secure HTTP server **6-53**
cryptographic software image **6-50**
described **6-50**
monitoring **6-56**
- SSM
address management restrictions **45-25**
CGMP limitations **45-25**
configuration guidelines **45-25**
configuring **45-26**
differs from Internet standard multicast **45-23**
IGMP snooping **45-25**
IGMPv3 **45-14, 45-23**
IGMPv3 Host Signalling **45-25**
IP address range **45-24**
monitoring **45-26**
operations **45-24**
PIM **45-14, 45-23**
state maintenance limitations **45-25**
- stack changes
 effects on
 IPv6 routing **40-11**
- stack changes, effects on
 ACL configuration **35-7**
 CDP **27-2**
 cross-stack EtherChannel **38-12**
 EtherChannel **38-9**
 fallback bridging **47-3**
 HSRP **41-5**

- IEEE 802.1x port-based authentication **9-12**
- IGMP snooping **24-7**
- IP routing **39-5**
- IPv6 ACLs **36-4**
- MAC address tables **5-21**
- MSTP **19-8**
- multicast routing **45-10**
- MVR **24-18**
- port security **26-18**
- SDM template selection **8-3**
- SNMP **33-1**
- SPAN and RSPAN **30-10**
- STP **18-12**
- system message log **32-2**
- VLANs **13-7**
- VTP **14-8**
- stack master
 - bridge ID (MAC address) **7-8**
 - defined **7-1**
 - election **7-6**
 - IPv6 **40-11**
 - re-election **7-6**
 - See also stacks, switch
- stack member
 - accessing CLI of specific member **7-26**
 - configuring
 - member number **7-24**
 - priority value **7-25**
 - defined **7-1**
 - displaying information of **7-27**
 - IPv6 **40-12**
 - number **7-8**
 - priority value **7-9**
 - provisioning a new member **7-25**
 - replacing **7-17**
 - See also stacks, switch
- stack member number **11-8**
- stack protocol version **7-12**
- stacks, switch
 - accessing CLI of specific member **7-26**
 - assigning information
 - member number **7-24**
 - priority value **7-25**
 - provisioning a new member **7-25**
 - auto-advise **7-14**
 - auto-copy **7-13**
 - auto-extract **7-13**
 - auto-upgrade **7-13**
 - bridge ID **7-8**
 - CDP considerations **27-2**
 - compatibility, software **7-12**
 - configuration file **7-16**
 - configuration guidelines **7-22**
 - configuration scenarios **7-19**
 - copying an image file from one member to another **B-39**
 - default configuration **7-21**
 - description of **7-1**
 - displaying information of **7-27**
 - enabling persistent MAC address timer **7-22**
 - hardware compatibility and SDM mismatch mode **7-12**
 - HSRP considerations **41-5**
 - incompatible software and image upgrades **7-16, B-39**
 - IPv6 on **40-11**
 - MAC address considerations **5-21**
 - MAC address of **7-22**
 - management connectivity **7-18**
 - managing **7-1**
 - membership **7-3**
 - merged **7-3**
 - MSTP instances supported **18-10**
 - multicast routing, stack master and member roles **45-9**
 - offline configuration
 - described **7-9**
 - effects of adding a provisioned switch **7-10**
 - effects of removing a provisioned switch **7-11**
 - effects of replacing a provisioned switch **7-11**

- provisioned configuration, defined **7-9**
- provisioned switch, defined **7-9**
- provisioning a new member **7-25**
- partitioned **7-3, 48-9**
- provisioned switch
 - adding **7-10**
 - removing **7-11**
 - replacing **7-11**
- replacing a failed member **7-17**
- software compatibility **7-12**
- software image version **7-12**
- stack protocol version **7-12**
- STP
 - bridge ID **18-3**
 - instances supported **18-10**
 - root port selection **18-3**
 - stack root switch election **18-3**
- system messages
 - hostnames in the display **32-1**
 - remotely monitoring **32-2**
- system prompt consideration **5-14**
- system-wide configuration considerations **7-17**
- upgrading **B-39**
- version-mismatch (VM) mode
 - automatic upgrades with auto-upgrade **7-13**
 - described **7-13**
 - examples **7-14**
 - manual upgrades with auto-advise **7-14**
 - upgrades with auto-extract **7-13**
- See also stack master and stack member
- StackWise Plus technology, Cisco **1-3**
 - See also stacks, switch
- standby ip command **41-7**
- standby links **21-2**
- standby router **41-1**
- standby timers, HSRP **41-11**
- startup configuration
 - booting
 - manually **3-22**
- specific image **3-23**
- clearing **B-20**
- configuration file
 - automatically downloading **3-21**
 - specifying the filename **3-22**
 - default boot configuration **3-21**
- static access ports
 - assigning to VLAN **13-10**
 - defined **11-3, 13-3**
- static addresses
 - See addresses
- static IP routing **1-14**
- static MAC addressing **1-10**
- static routes
 - configuring **39-99**
 - configuring for IPv6 **40-22**
 - understanding **40-8**
- static routing **39-4**
- static VLAN membership **13-2**
- statistics
 - 802.1X **10-17**
 - CDP **27-5**
 - IEEE 802.1x **9-68**
 - interface **11-28**
 - IP multicast routing **45-67**
 - LLDP **28-10**
 - LLDP-MED **28-10**
 - NMSP **28-10**
 - OSPF **39-41**
 - QoS ingress and egress **37-92**
 - RMON group Ethernet **31-6**
 - RMON group history **31-5**
 - SNMP input and output **33-19**
 - VTP **14-18**
- sticky learning **26-9**
- storm control
 - configuring **26-3**
 - described **26-1**
 - disabling **26-5**

- displaying **26-19**
- support for **1-4**
- thresholds **26-1**
- STP
 - accelerating root port selection **20-4**
 - BackboneFast
 - described **20-7**
 - disabling **20-17**
 - enabling **20-16**
 - BPDUs filtering
 - described **20-3**
 - disabling **20-15**
 - enabling **20-14**
 - BPDUs guard
 - described **20-2**
 - disabling **20-14**
 - enabling **20-13**
 - BPDUs message exchange **18-3**
 - configuration guidelines **18-14, 20-12**
 - configuring
 - forward-delay time **18-23**
 - hello time **18-22**
 - maximum aging time **18-23**
 - path cost **18-20**
 - port priority **18-18**
 - root switch **18-16**
 - secondary root switch **18-18**
 - spanning-tree mode **18-15**
 - switch priority **18-21**
 - transmit hold-count **18-24**
 - counters, clearing **18-24**
 - cross-stack UplinkFast
 - described **20-5**
 - enabling **20-16**
 - default configuration **18-13**
 - default optional feature configuration **20-12**
 - designated port, defined **18-4**
 - designated switch, defined **18-4**
 - detecting indirect link failures **20-8**
 - disabling **18-16**
 - displaying status **18-24**
 - EtherChannel guard
 - described **20-10**
 - disabling **20-17**
 - enabling **20-17**
 - extended system ID
 - effects on root switch **18-16**
 - effects on the secondary root switch **18-18**
 - overview **18-4**
 - unexpected behavior **18-16**
 - features supported **1-8**
 - IEEE 802.1D and bridge ID **18-4**
 - IEEE 802.1D and multicast addresses **18-9**
 - IEEE 802.1t and VLAN identifier **18-4**
 - inferior BPDUs **18-3**
 - instances supported **18-10**
 - interface state, blocking to forwarding **20-2**
 - interface states
 - blocking **18-6**
 - disabled **18-7**
 - forwarding **18-6, 18-7**
 - learning **18-7**
 - listening **18-7**
 - overview **18-5**
 - interoperability and compatibility among modes **18-11**
 - keepalive messages **18-2**
 - Layer 2 protocol tunneling **17-8**
 - limitations with IEEE 802.1Q trunks **18-11**
 - load sharing
 - overview **13-22**
 - using path costs **13-24**
 - using port priorities **13-23**
 - loop guard
 - described **20-11**
 - enabling **20-18**
 - modes supported **18-10**
 - multicast addresses, effect of **18-9**

- optional features supported **1-8**
- overview **18-2**
- path costs **13-24, 13-25**
- Port Fast
 - described **20-2**
 - enabling **20-12**
- port priorities **13-23**
- preventing root switch selection **20-10**
- protocols supported **18-10**
- redundant connectivity **18-8**
- root guard
 - described **20-10**
 - enabling **20-18**
- root port, defined **18-3**
- root port selection on a switch stack **18-3**
- root switch
 - configuring **18-16**
 - effects of extended system ID **18-4, 18-16**
 - election **18-3**
 - unexpected behavior **18-16**
- shutdown Port Fast-enabled port **20-2**
- stack changes, effects of **18-12**
- status, displaying **18-24**
- superior BPDU **18-3**
- timers, described **18-22**
- UplinkFast
 - described **20-3**
 - enabling **20-15**
- VLAN-bridge **18-12**
- stratum, NTP **5-2**
- stub areas, OSPF **39-37**
- stub routing
 - EIGRP **39-29**
 - PIM **39-27**
- subdomains, private VLAN **16-1**
- subnet mask **39-8**
- subnet zero **39-8**
- success response, VMPS **13-27**
- summer time **5-13**
- SunNet Manager **1-6**
- supernet **39-9**
- supported port-based authentication methods **9-8**
- SVI autostate exclude
 - configuring **11-25**
 - defined **11-6**
- SVI link state **11-6**
- SVIs
 - and IP unicast routing **39-6**
 - and router ACLs **35-4**
 - connecting VLANs **11-7**
 - defined **11-5**
 - routing between VLANs **13-2**
- switch **40-3**
- switch console port **1-7**
- Switch Database Management
 - See SDM
- switched packets, ACLs on **35-37**
- Switched Port Analyzer
 - See SPAN
- switched ports **11-2**
- switchport backup interface **21-4, 21-5**
- switchport block multicast command **26-8**
- switchport block unicast command **26-8**
- switchport command **11-17**
- switchport mode dot1q-tunnel command **17-6**
- switchport protected command **26-7**
- switch priority
 - MSTP **19-23**
 - STP **18-21**
- switch software features **1-1**
- switch virtual interface
 - See SVI
- synchronization, BGP **39-54**
- syslog
 - See system message logging
- system capabilities TLV **28-2**
- system clock
 - configuring

- daylight saving time **5-13**
 manually **5-11**
 summer time **5-13**
 time zones **5-12**
- displaying the time and date **5-12**
 overview **5-2**
- See also NTP
- system description TLV **28-2**
- system message logging
 default configuration **32-4**
 defining error message severity levels **32-9**
 disabling **32-4**
 displaying the configuration **32-14**
 enabling **32-5**
 facility keywords, described **32-14**
 level keywords, described **32-10**
 limiting messages **32-10**
 message format **32-2**
 overview **32-1**
 sequence numbers, enabling and disabling **32-8**
 setting the display destination device **32-5**
 stack changes, effects of **32-2**
 synchronizing log messages **32-6**
 syslog facility **1-16**
 time stamps, enabling and disabling **32-8**
 UNIX syslog servers
 configuring the daemon **32-13**
 configuring the logging facility **32-13**
 facilities supported **32-14**
- system MTU
 and IS-IS LSPs **39-76**
- system MTU and IEEE 802.1Q tunneling **17-5**
- system name
 default configuration **5-15**
 default setting **5-15**
 manual configuration **5-15**
- See also DNS
- system name TLV **28-2**
- system prompt, default setting **5-14, 5-15**
- system resources, optimizing **8-1**
 system routing
 IS-IS **39-71**
 ISO IGRP **39-71**
-
- T**
- TACACS+
 accounting, defined **6-11**
 authentication, defined **6-11**
 authorization, defined **6-11**
 configuring
 accounting **6-17**
 authentication key **6-13**
 authorization **6-16**
 login authentication **6-14**
 default configuration **6-13**
 displaying the configuration **6-17**
 identifying the server **6-13**
 limiting the services to the user **6-16**
 operation of **6-12**
 overview **6-10**
 support for **1-12**
 tracking services accessed by user **6-17**
- tagged packets
 IEEE 802.1Q **17-3**
 Layer 2 protocol **17-8**
- tar files
 creating **B-7**
 displaying the contents of **B-7**
 extracting **B-8**
 image file format **B-25**
- TCL script, registering and defining with embedded event manager **34-7**
- TDR **1-16**
- Telnet
 accessing management interfaces **2-10**
 number of connections **1-7**
 setting a password **6-6**

- templates, SDM **8-2**
- temporary self-signed certificate **6-51**
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password **6-6**
- TFTP
 - configuration files
 - downloading **B-12**
 - preparing the server **B-11**
 - uploading **B-13**
 - configuration files in base directory **3-8**
 - configuring for autoconfiguration **3-7**
 - image files
 - deleting **B-29**
 - downloading **B-27**
 - preparing the server **B-27**
 - uploading **B-29**
 - limiting access by servers **33-17**
- TFTP server **1-6**
- threshold, traffic level **26-2**
- threshold monitoring, IP SLAs **42-6**
- time
 - See NTP and system clock
- Time Domain Reflector
 - See TDR
- time-range command **35-17**
- time ranges in ACLs **35-17**
- time stamps in log messages **32-8**
- time zones **5-12**
- TLVs
 - defined **28-1**
 - LLDP **28-2**
 - LLDP-MED **28-2**
- Token Ring VLANs
 - support for **13-6**
 - VTP support **14-4**
- ToS **1-13**
- traceroute, Layer 2
 - and ARP **48-12**
 - and CDP **48-12**
 - broadcast traffic **48-11**
 - described **48-11**
 - IP addresses and subnets **48-12**
 - MAC addresses and VLANs **48-12**
 - multicast traffic **48-12**
 - multiple devices on a port **48-12**
 - unicast traffic **48-11**
 - usage guidelines **48-12**
- traceroute command **48-14**
 - See also IP traceroute
- tracked lists
 - configuring **43-3**
 - types **43-3**
- tracked objects
 - by Boolean expression **43-3**
 - by threshold percentage **43-5**
 - by threshold weight **43-4**
- tracking interface line-protocol state **43-2**
- tracking IP routing state **43-2**
- tracking objects **43-1**
- tracking process **43-1**
- track state, tracking IP SLAs **43-8**
- traffic
 - blocking flooded **26-8**
 - fragmented **35-5**
 - fragmented IPv6 **36-2**
 - unfragmented **35-5**
- traffic policing **1-13**
- traffic suppression **26-1**
- transmit hold-count
 - see STP
- transparent mode, VTP **14-3**
- trap-door mechanism **3-2**
- traps
 - configuring MAC address notification **5-22, 5-24, 5-26**
 - configuring managers **33-12**
 - defined **33-3**
 - enabling **5-22, 5-24, 5-26, 33-12**

- notification types **33-12**
 - overview **33-1, 33-4**
 - troubleshooting**
 - connectivity problems **48-10, 48-11, 48-13**
 - CPU utilization **48-23**
 - detecting unidirectional links **29-1**
 - displaying crash information **48-20**
 - PIMv1 and PIMv2 interoperability problems **45-39**
 - setting packet forwarding **48-18**
 - show forward command **48-18**
 - with CiscoWorks **33-4**
 - with debug commands **48-16**
 - with ping **48-10**
 - with system message logging **32-1**
 - with traceroute **48-13**
 - trunk failover**
 - See link-state tracking
 - trunking encapsulation** **1-9**
 - trunk ports**
 - configuring **13-19**
 - defined **11-3, 13-3**
 - encapsulation **13-19, 13-24, 13-25**
 - trunks**
 - allowed-VLAN list **13-20**
 - configuring **13-19, 13-24, 13-25**
 - load sharing
 - setting STP path costs **13-24**
 - using STP port priorities **13-23**
 - native VLAN for untagged traffic **13-22**
 - parallel **13-24**
 - pruning-eligible list **13-21**
 - to non-DTP device **13-16**
 - trusted boundary for QoS** **37-44**
 - trusted port states**
 - between QoS domains **37-46**
 - classification options **37-5**
 - ensuring port security for IP phones **37-44**
 - support for **1-13**
 - within a QoS domain **37-42**
 - trustpoints, CA **6-50**
 - tunneling**
 - defined **17-1**
 - IEEE 802.1Q **17-1**
 - Layer 2 protocol **17-8**
 - tunnel ports**
 - defined **13-4**
 - described **11-4, 17-1**
 - IEEE 802.1Q, configuring **17-6**
 - incompatibilities with other features **17-6**
 - twisted-pair Ethernet, detecting unidirectional links** **29-1**
 - type of service**
 - See ToS
-
- U**
- UDLD**
 - configuration guidelines **29-4**
 - default configuration **29-4**
 - disabling
 - globally **29-5**
 - on fiber-optic interfaces **29-5**
 - per interface **29-6**
 - echoing detection mechanism **29-2**
 - enabling
 - globally **29-5**
 - per interface **29-6**
 - Layer 2 protocol tunneling **17-10**
 - link-detection mechanism **29-1**
 - neighbor database **29-2**
 - overview **29-1**
 - resetting an interface **29-6**
 - status, displaying **29-7**
 - support for **1-8**
 - UDP, configuring **39-17**
 - UDP jitter, configuring **42-9**
 - UDP jitter operation, IP SLAs **42-8**
 - unauthorized ports with IEEE 802.1x **9-11**
 - unicast MAC address filtering **1-6**

- and adding static addresses **5-29**
 - and broadcast MAC addresses **5-28**
 - and CPU packets **5-28**
 - and multicast addresses **5-28**
 - and router MAC addresses **5-28**
 - configuration guidelines **5-28**
 - described **5-28**
 - unicast storm **26-1**
 - unicast storm control command **26-4**
 - unicast traffic, blocking **26-8**
 - UniDirectional Link Detection protocol
 - See UDLD
 - universal software image
 - cryptographic **1-1**
 - feature set
 - IP base **1-2**
 - IP services **1-2**
 - noncryptographic **1-1**
 - UNIX syslog servers
 - daemon configuration **32-13**
 - facilities supported **32-14**
 - message logging configuration **32-13**
 - unrecognized Type-Length-Value (TLV) support **14-4**
 - upgrading software images
 - See downloading
 - UplinkFast
 - described **20-3**
 - disabling **20-16**
 - enabling **20-15**
 - support for **1-8**
 - uploading
 - configuration files
 - preparing **B-11, B-14, B-17**
 - reasons for **B-9**
 - using FTP **B-15**
 - using RCP **B-19**
 - using TFTP **B-13**
 - image files
 - preparing **B-27, B-30, B-35**
 - reasons for **B-24**
 - using FTP **B-33**
 - using RCP **B-38**
 - using TFTP **B-29**
 - User Datagram Protocol
 - See UDP
 - user EXEC mode **2-2**
 - username-based authentication **6-6**
-
- V**
- version-dependent transparent mode **14-5**
 - version-mismatch (VM) mode
 - automatic upgrades with auto-upgrade **7-13**
 - described **7-13**
 - displaying **7-13**
 - manual upgrades with auto-advise **7-14**
 - upgrades with auto-extract **7-13**
 - Virtual Private Network
 - See VPN
 - virtual router **41-1, 41-2**
 - virtual switches and PAgP **38-6**
 - vlan.dat file **13-5**
 - VLAN 1
 - disabling on a trunk port **13-20**
 - minimization **13-20**
 - VLAN ACLs
 - See VLAN maps
 - vlan-assignment response, VMPS **13-26**
 - VLAN configuration
 - at bootup **13-7**
 - saving **13-7**
 - VLAN configuration mode **2-2**
 - VLAN database
 - and startup configuration file **13-7**
 - and VTP **14-1, 34-1**
 - VLAN configuration saved in **13-7**
 - VLANS saved in **13-4**
 - vlan dot1q tag native command **17-5**

- VLAN filtering and SPAN **30-7**
- vlan global configuration command **13-7**
- VLAN ID, discovering **5-31**
- VLAN link state **11-6**
- VLAN load balancing on flex links
- configuration guidelines **21-8**
 - described **21-3**
- VLAN management domain **14-2**
- VLAN Management Policy Server
- See VMPS
- VLAN map entries, order of **35-31**
- VLAN maps
- applying **35-35**
 - common uses for **35-35**
 - configuration guidelines **35-31**
 - configuring **35-30**
 - creating **35-32**
 - defined **35-2**
 - denying access to a server example **35-35**
 - denying and permitting packets **35-33**
 - displaying **35-41**
 - examples of ACLs and VLAN maps **35-33**
 - removing **35-35**
 - support for **1-10**
- VLAN membership
- confirming **13-29**
 - modes **13-3**
- VLAN Query Protocol
- See VQP
- VLANs
- adding **13-8**
 - adding to VLAN database **13-8**
 - aging dynamic addresses **18-9**
 - allowed on trunk **13-20**
 - and spanning-tree instances **13-3, 13-6, 13-11**
 - configuration guidelines, extended-range VLANs **13-11**
 - configuration guidelines, normal-range VLANs **13-6**
 - configuring **13-1**
 - configuring IDs 1006 to 4094 **13-11**
 - connecting through SVIs **11-7**
 - customer numbering in service-provider networks **17-3**
 - default configuration **13-8**
 - deleting **13-9**
 - described **11-2, 13-1**
 - displaying **13-14**
 - extended-range **13-1, 13-11**
 - features **1-9**
 - illustrated **13-2**
 - internal **13-12**
 - in the switch stack **13-7**
 - limiting source traffic with RSPAN **30-21**
 - limiting source traffic with SPAN **30-16**
 - modifying **13-8**
 - multicast **24-18**
 - native, configuring **13-22**
 - normal-range **13-1, 13-4**
 - number supported **1-9**
 - parameters **13-5**
 - port membership modes **13-3**
 - static-access ports **13-10**
 - STP and IEEE 802.1Q trunks **18-11**
 - supported **13-2**
 - Token Ring **13-6**
 - traffic between **13-2**
 - VLAN-bridge STP **18-12, 47-2**
 - VTP modes **14-3**
 - VLAN Trunking Protocol
 - See VTP - VLAN trunks **13-15**
 - VMPS
 - administering **13-30**
 - configuration example **13-31**
 - configuration guidelines **13-28**
 - default configuration **13-27**
 - description **13-26**
 - dynamic port membership

- described **13-27**
- reconfirming **13-30**
- troubleshooting **13-31**
- mapping MAC addresses to VLANs **13-26**
- monitoring **13-30**
- reconfirmation interval, changing **13-30**
- reconfirming membership **13-29**
- retry count, changing **13-30**
- voice aware 802.1x security
 - port-based authentication
 - configuring **9-42**
 - described **9-31, 9-42**
- voice-over-IP **15-1**
 - Cisco 7960 phone, port connections **15-1**
 - configuration guidelines **15-3**
 - configuring IP phones for data traffic
 - override CoS of incoming frame **15-6**
 - trust CoS priority of incoming frame **15-6**
 - configuring ports for voice traffic in
 - IEEE 802.1p priority tagged frames **15-5**
 - IEEE 802.1Q frames **15-5**
 - connecting to an IP phone **15-4**
 - default configuration **15-3**
 - described **15-1**
 - displaying **15-7**
 - IP phone data traffic, described **15-2**
 - IP phone voice traffic, described **15-2**
- VPN
 - configuring routing in **39-91**
 - forwarding **39-84**
 - in service provider networks **39-82**
 - routes **39-83**
- VPN routing and forwarding table
 - See VRF
- VQP **1-9, 13-26**
- VRF
 - defining **39-84**
 - tables **39-82**
 - VRF-aware services
 - ARP **39-87**
 - configuring **39-86**
 - ftp **39-89**
 - HSRP **39-88**
 - ping **39-87**
 - RADIUS **39-90**
 - SNMP **39-87**
 - syslog **39-89**
 - tftp **39-89**
 - traceroute **39-89**
 - VRFs, configuring multicast **39-90**
 - VTP
 - adding a client to a domain **14-17**
 - advertisements **13-18, 14-4**
 - and extended-range VLANs **13-3, 14-2**
 - and normal-range VLANs **13-2, 14-2**
 - client mode, configuring **14-13**
 - configuration
 - guidelines **14-9**
 - requirements **14-11**
 - saving **14-9**
 - configuration requirements **14-11**
 - configuration revision number
 - guideline **14-17**
 - resetting **14-17**
 - consistency checks **14-5**
 - default configuration **14-8**
 - described **14-1**
 - domain names **14-9**
 - domains **14-2**
 - Layer 2 protocol tunneling **17-8**
 - modes
 - client **14-3**
 - off **14-3**
 - server **14-3**
 - transitions **14-3**
 - transparent **14-3**
 - monitoring **14-18**

passwords **14-10**
 pruning
 disabling **14-16**
 enabling **14-16**
 examples **14-7**
 overview **14-6**
 support for **1-9**
 pruning-eligible list, changing **13-21**
 server mode, configuring **14-14**
 statistics **14-18**
 support for **1-9**
 Token Ring support **14-4**
 transparent mode, configuring **14-11**
 using **14-1**
 Version
 enabling **14-15**
 version, guidelines **14-10**
 Version 1 **14-5**
 Version 2
 configuration guidelines **14-10**
 overview **14-4**
 Version 3
 overview **14-5**

W

WCCP
 authentication **44-4**
 configuration guidelines **44-6**
 default configuration **44-6**
 described **44-2**
 displaying **44-10**
 dynamic service groups **44-4**
 enabling **44-6**
 features unsupported **44-5**
 forwarding method **44-3**
 Layer-2 header rewrite **44-3**
 MD5 security **44-4**
 message exchange **44-3**

monitoring and maintaining **44-10**
 negotiation **44-3**
 packet redirection **44-4**
 packet-return method **44-3**
 redirecting traffic received from a client **44-6**
 setting the password **44-7**
 unsupported WCCPv2 features **44-5**
 web authentication **9-16**
 configuring **10-16**
 described **1-10**
 web-based authentication
 customizable web pages **10-6**
 description **10-1**
 web-based authentication, interactions with other features **10-7**
 Web Cache Communication Protocol
 See WCCP
 weighted tail drop
 See WTD
 weight thresholds in tracked lists **43-4**
 wired location service
 configuring **28-9**
 displaying **28-10**
 location TLV **28-3**
 understanding **28-3**
 wizards **1-3**
 WTD
 described **37-14**
 setting thresholds
 egress queue-sets **37-85**
 ingress queues **37-81**
 support for **1-13**

