



## INDEX

### A

- aaa accounting dot1x command [2-1](#)
- aaa authentication dot1x command [2-3](#)
- aaa authorization network command [2-5, 2-24, 2-30, 2-32, 2-34, 2-36, 2-38, 2-145, 2-313, B-7, B-31](#)
- AAA methods [2-3](#)
- access control entries
  - See ACEs
- access control lists
  - See ACLs
- access groups
  - IP [2-196](#)
- access list, IPv6 [2-270](#)
- access map configuration mode [2-339](#)
- access mode [2-779](#)
- access ports [2-779](#)
- ACEs [2-129, 2-416](#)
- ACLs
  - deny [2-127](#)
  - for non-IP protocols [2-317](#)
  - IP [2-196](#)
  - matching [2-339](#)
  - on Layer 2 interfaces [2-196](#)
  - permit [2-414](#)
- action command [2-6](#)
- aggregate-port learner [2-403](#)
- allowed VLANs [2-799](#)
- archive copy-sw command [2-8](#)
- archive download-sw command [2-11](#)
- archive tar command [2-15](#)
- archive upload-sw command [2-18](#)
- arp (boot loader) command [A-2](#)
- arp access-list command [2-20](#)
- authentication command disable-port ignore [2-23](#)
- authentication control-direction command [2-24](#)
- authentication event command [2-26](#)
- authentication failed VLAN
  - See dot1x auth-fail vlan
- authentication fallback command [2-30](#)
- authentication host-mode command [2-32](#)
- authentication mac-move permit command [2-34](#)
- authentication open command [2-36](#)
- authentication order command [2-38](#)
- authentication periodic command [2-40](#)
- authentication port-control command [2-42](#)
- authentication priority command [2-44](#)
- authentication timer command [2-46](#)
- authentication violation command [2-48](#)
- auth-fail max-attempts
  - See dot1x auth-fail max-attempts
- auth-fail vlan
  - See dot1x auth-fail vlan
- auth open command [2-36](#)
- auth order command [2-38](#)
- authorization state of controlled port [2-162](#)
- auth timer command [2-46](#)
- autonegotiation of duplex mode [2-173](#)
- auto qos classify command [2-50](#)
- auto qos trust command [2-53](#)
- auto qos video command [2-56](#)
- auto qos voip command [2-59](#)

**B**

BackboneFast, for STP [2-701](#)

backup interfaces

    configuring [2-773](#)

boot (boot loader) command [A-3](#)

boot auto-copy-sw command [2-66](#)

boot auto-download-sw command [2-68](#)

boot config-file command [2-71](#)

boot enable-break command [2-72](#)

boot helper command [2-73](#)

boot helper-config file command [2-74](#)

booting

    Cisco IOS image [2-77](#)

    interrupting [2-72](#)

    manually [2-75](#)

boot loader

    accessing [A-1](#)

    booting

        Cisco IOS image [A-3](#)

        helper image [2-73](#)

    directories

        creating [A-19](#)

        displaying a list of [A-8](#)

        removing [A-23](#)

    displaying

        available commands [A-13](#)

        memory heap utilization [A-14](#)

        version [A-30](#)

    environment variables

        described [A-24](#)

        displaying settings [A-24](#)

        location of [A-25](#)

        setting [A-24](#)

        unsetting [A-28](#)

    files

        copying [A-6](#)

        deleting [A-7](#)

        displaying a list of [A-8](#)

        displaying the contents of [A-5, A-20, A-27](#)

        renaming [A-21](#)

    file system

        formatting [A-11](#)

        initializing flash [A-10](#)

        running a consistency check [A-12](#)

    prompt [A-1](#)

    resetting the system [A-22](#)

boot manual command [2-75](#)

boot private-config-file command [2-76](#)

boot system command [2-77](#)

BPDU filtering, for spanning tree [2-702, 2-736](#)

BPDU guard, for spanning tree [2-704, 2-736](#)

broadcast storm control [2-757](#)

**C**

cat (boot loader) command [A-5](#)

CDP, enabling protocol tunneling for [2-296](#)

channel-group command [2-79](#)

channel-protocol command [2-83](#)

Cisco IP camera

    auto-QoS configuration [2-56](#)

Cisco SoftPhone

    auto-QoS configuration [2-59](#)

    trusting packets sent from [2-380](#)

Cisco Telepresence System

    auto-QoS configuration [2-56](#)

CISP

    See Client Information Signalling Protocol

cisp

    debug platform cisp command [B-31](#)

cisp enable command [2-84](#)

class command [2-85](#)

class-map command [2-88](#)

class maps

    creating [2-88](#)

    defining the match criteria [2-341](#)

class of service  
     See CoS

clear dot1x command [2-90](#)

clear eap command [2-91](#)

clear errdisable interface [2-92](#)

clear ip arp inspection log command [2-93](#)

clear ip arp inspection statistics command [2-94](#)

clear ipc command [2-99](#)

clear ip dhcp snooping database command [2-95, 2-97](#)

clear ipv6 dhcp conflict command [2-100](#)

clear l2protocol-tunnel counters command [2-101](#)

clear lacp command [2-102](#)

clear logging command [2-103](#)

clear mac address-table command [2-104, 2-105](#)

clear nmsp statistics command [2-106](#)

clear pagp command [2-107](#)

clear port-security command [2-108](#)

clear psp counter [2-110](#)

clear psp counter command [2-110](#)

clear spanning-tree counters command [2-111](#)

clear spanning-tree detected-protocols command [2-112](#)

clear vmpls statistics command [2-113](#)

clear vtp counters command [2-114](#)

Client Information Signalling Protocol [2-84, 2-145, B-7, B-31](#)

command modes defined [1-2](#)

configuration files  
     password recovery disable considerations [A-1](#)  
     specifying the name [2-71, 2-76](#)

configuring multiple interfaces [2-192](#)

config-vlan mode  
     commands [2-823](#)  
     entering [2-822](#)

copy (boot loader) command [A-6](#)

copy logging onboard command [2-115](#)

CoS  
     assigning default value to incoming packets [2-350](#)  
     assigning to Layer 2 protocol packets [2-299](#)  
     overriding the incoming value [2-350](#)

CoS-to-DSCP map [2-354](#)

crashinfo files [2-183](#)

critical VLAN [2-27](#)

---

## D

debug authentication [B-2](#)

debug auto qos command [B-4](#)

debug backup command [B-6](#)

debug cisp command [B-7](#)

debug dot1x command [B-8](#)

debug dtp command [B-9](#)

debug eap command [B-10](#)

debug etherchannel command [B-11](#)

debug fastethernet command [B-12](#)

debug interface command [B-15](#)

debug ip dhcp snooping command [B-13](#)

debug ip igmp filter command [B-16](#)

debug ip igmp max-groups command [B-17](#)

debug ip igmp snooping command [B-18](#)

debug ip verify source packet command [B-14](#)

debug lacp command [B-19](#)

debug lldp packets command [B-20](#)

debug mac-notification command [B-21](#)

debug matm command [B-22](#)

debug matm move update command [B-23](#)

debug monitor command [B-24](#)

debug mvrdbg command [B-25](#)

debug nmsp command [B-26](#)

debug nvram command [B-27](#)

debug pagp command [B-28](#)

debug platform acl command [B-29](#)

debug platform backup interface command [B-30](#)

debug platform cisp command [B-31](#)

debug platform cli-redirection main command [B-32](#)

debug platform configuration command [B-33](#)

debug platform cpu-queues command [B-34](#)

debug platform device-manager command [B-36](#)

debug platform dot1x command [B-37](#)

- debug platform etherchannel command [B-38](#)
- debug platform fallback-bridging command [B-39](#)
- debug platform ip arp inspection command [B-40](#)
- debug platform ipc command [B-49](#)
- debug platform ip dhcp command [B-41](#)
- debug platform ip igmp snooping command [B-42](#)
- debug platform ip multicast command [B-44](#)
- debug platform ip unicast command [B-46](#)
- debug platform ip wccp command [B-48](#)
- debug platform led command [B-50](#)
- debug platform matm command [B-51](#)
- debug platform messaging application command [B-52](#)
- debug platform phy command [B-53](#)
- debug platform pm command [B-55](#)
- debug platform port-asic command [B-57](#)
- debug platform port-security command [B-58](#)
- debug platform qos-acl-tcam command [B-59](#)
- debug platform remote-commands command [B-60](#)
- debug platform resource-manager command [B-61](#)
- debug platform snmp command [B-62](#)
- debug platform span command [B-63](#)
- debug platform stack-manager command [B-64](#)
- debug platform supervisor-asic command [B-65](#)
- debug platform sw-bridge command [B-66](#)
- debug platform team command [B-67](#)
- debug platform udd command [B-70](#)
- debug platform vlan command [B-71](#)
- debug pm command [B-72](#)
- debug port-security command [B-74](#)
- debug qos-manager command [B-75](#)
- debug spanning-tree backbonefast command [B-78](#)
- debug spanning-tree bpdu command [B-79](#)
- debug spanning-tree bpdu-opt command [B-80](#)
- debug spanning-tree command [B-76](#)
- debug spanning-tree mstp command [B-81](#)
- debug spanning-tree switch command [B-83](#)
- debug spanning-tree uplinkfast command [B-85](#)
- debug sw-vlan command [B-86](#)
- debug sw-vlan ifs command [B-88](#)
- debug sw-vlan notification command [B-89](#)
- debug sw-vlan vtp command [B-91](#)
- debug udd command [B-93](#)
- debug vqpc command [B-95](#)
- define interface-range command [2-117](#)
- delete (boot loader) command [A-7](#)
- delete command [2-119](#)
- deny (ARP access-list configuration) command [2-120](#)
- deny (IPv6) command [2-122](#)
- deny command [2-127](#)
- detect mechanism, causes [2-175](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-228](#)
  - enabling
    - on a VLAN [2-234](#)
    - option 82 [2-226, 2-228](#)
    - trust on an interface [2-232](#)
  - error recovery timer [2-179](#)
  - rate limiting [2-231](#)
- DHCP snooping binding database
  - binding file, configuring [2-224](#)
  - bindings
    - adding [2-222](#)
    - deleting [2-222](#)
  - clearing database agent statistics [2-95, 2-97](#)
  - database agent, configuring [2-224](#)
  - renewing [2-445](#)
- dir (boot loader) command [A-8](#)
- directories, deleting [2-119](#)
- domain name, VTP [2-838](#)
- dot1x auth-fail max-attempts [2-139](#)
- dot1x auth-fail vlan [2-141](#)
- dot1x command [2-137](#)
- dot1x control-direction command [2-143](#)
- dot1x credentials (global configuration) command [2-145](#)
- dot1x critical global configuration command [2-146](#)
- dot1x critical interface configuration command [2-148](#)
- dot1x default command [2-150](#)
- dot1x fallback command [2-151](#)

- dot1x guest-vlan command [2-152](#)
- dot1x host-mode command [2-154](#)
- dot1x initialize command [2-155](#)
- dot1x mac-auth-bypass command [2-156](#)
- dot1x max-reauth-req command [2-158](#)
- dot1x max-req command [2-160](#)
- dot1x pae command [2-161](#)
- dot1x port-control command [2-162](#)
- dot1x re-authenticate command [2-164](#)
- dot1x reauthentication command [2-165](#)
- dot1x supplicant force-multicast command [2-166](#)
- dot1x timeout command [2-167](#)
- dot1x violation-mode command [2-170](#)
- dropping packets, with ACL matches [2-6](#)
- drop threshold, Layer 2 protocol tunneling [2-296](#)
- DSCP-to-CoS map [2-354](#)
- DSCP-to-DSCP-mutation map [2-354](#)
- DTP [2-780](#)
- DTP flap
  - error detection for [2-175](#)
  - error recovery timer [2-179](#)
- DTP negotiation [2-784](#)
- dual IPv4 and IPv6 templates [2-409](#)
- duplex command [2-172](#)
- dynamic-access ports
  - configuring [2-769](#)
  - restrictions [2-770](#)
- dynamic ARP inspection
  - ARP ACLs
    - apply to a VLAN [2-204](#)
    - define [2-20](#)
    - deny packets [2-120](#)
    - permit packets [2-407](#)
  - clear
    - log buffer [2-93](#)
    - statistics [2-94](#)
  - enable per VLAN [2-214](#)
  - error detection for [2-175](#)
  - error recovery timer [2-179](#)

- log buffer
  - clear [2-93](#)
  - configure [2-208](#)
- rate-limit incoming ARP packets [2-206](#)
- statistics
  - clear [2-94](#)
- trusted interface state [2-210](#)
- type of packet logged [2-215](#)
- validation checks [2-212](#)
- dynamic auto VLAN membership mode [2-779](#)
- dynamic desirable VLAN membership mode [2-779](#)
- Dynamic Host Configuration Protocol (DHCP)
  - See DHCP snooping
- Dynamic Trunking Protocol
  - See DTP

---

## E

- EAP-request/identity frame
  - maximum number to send [2-160](#)
  - response time before retransmitting [2-167](#)
- encapsulation methods [2-799](#)
- epm access-control open [2-174](#)
- errdisable detect cause command [2-175](#)
- errdisable detect cause small-frame comand [2-177](#)
- errdisable recovery cause small-frame [2-182](#)
- errdisable recovery command [2-179](#)
- error disable detection [2-175](#)
- EtherChannel
  - assigning Ethernet interface to channel group [2-79](#)
  - creating port-channel logical interface [2-190](#)
  - debug EtherChannel/PAGP, display [B-11](#)
  - debug platform-specific events, display [B-38](#)
  - enabling Layer 2 protocol tunneling for
    - LACP [2-297](#)
    - PAGP [2-297](#)
    - UDLD [2-297](#)

## EtherChannel (continued)

## LACP

- clearing channel-group information [2-102, 2-103](#)
- debug messages, display [B-19](#)
- modes [2-79](#)
- port priority for hot-standby ports [2-300](#)
- restricting a protocol [2-83](#)
- system priority [2-302](#)

load-distribution methods [2-424](#)

## PAgP

- aggregate-port learner [2-403](#)
- clearing channel-group information [2-107](#)
- debug messages, display [B-28](#)
- error detection for [2-175](#)
- error recovery timer [2-179](#)
- learn method [2-403](#)
- modes [2-79](#)
- physical-port learner [2-403](#)
- priority of interface for transmitted traffic [2-405](#)

Ethernet Management port, debugging [B-12](#)exception crashinfo command [2-183, 2-188](#)

## extended-range VLANs

- and allowed VLAN list [2-799](#)
- and pruning-eligible list [2-799](#)
- configuring [2-822](#)

extended system ID for STP [2-710](#)**F**fallback profile command [2-184](#)fan information, displaying [2-516](#)file name, VTP [2-838](#)files, deleting [2-119](#)flash\_init (boot loader) command [A-10](#)flexible authentication ordering [2-38](#)

## Flex Links

- configuring [2-773](#)

flowcontrol command [2-186](#)format (boot loader) command [A-11](#)forwarding packets, with ACL matches [2-6](#)forwarding results, display [C-7](#)frame forwarding information, displaying [C-7](#)front-end controller counter and status information [C-9](#)fsck (boot loader) command [A-12](#)**G**global configuration mode [1-2, 1-4](#)**H**health monitoring diagnostic tests [2-130](#)help (boot loader) command [A-13](#)hierarchical policy maps [2-422](#)host connection, port configuration [2-778](#)host ports, private VLANs [2-782](#)**I**IEEE 802.1Q trunk ports and native VLANs [2-829](#)

## IEEE 802.1Q tunnel ports

- configuring [2-779](#)
- limitations [2-780](#)

## IEEE 802.1x

- and switchport modes [2-780](#)
- violation error recovery [2-179](#)
- See also port-based authentication

## IGMP filters

- applying [2-237](#)
- debug messages, display [B-16](#)

IGMP groups, setting maximum [2-239](#)IGMP maximum groups, debugging [B-17](#)

## IGMP profiles

- creating [2-241](#)

- IGMP snooping
  - adding ports as a static member of a group [2-257](#)
  - enabling [2-243](#)
  - enabling the configurable-leave timer [2-245](#)
  - enabling the Immediate-Leave feature [2-254](#)
  - flooding query count [2-251](#)
  - interface topology change notification behavior [2-253](#)
  - querier [2-247](#)
  - query solicitation [2-251](#)
  - report suppression [2-249](#)
  - switch topology change notification behavior [2-251](#)
- images
  - See software images
- Immediate-Leave processing
  - IGMP [2-254](#)
  - IPv6 [2-292](#)
  - MVR [2-390](#)
- interface configuration mode [1-2, 1-4](#)
- interface port-channel command [2-190](#)
- interface range command [2-192](#)
- interface-range macros [2-117](#)
- interfaces
  - assigning Ethernet interface to channel group [2-79](#)
  - configuring [2-172](#)
  - configuring multiple [2-192](#)
  - creating port-channel logical [2-190](#)
  - debug messages, display [B-15](#)
  - disabling [2-687](#)
  - restarting [2-687](#)
- interface speed, configuring [2-747](#)
- interface vlan command [2-194](#)
- Internet Group Management Protocol
  - See IGMP
- invalid GBIC
  - error detection for [2-175](#)
  - error recovery timer [2-179](#)
- ip access-group command [2-196](#)
- ip address command [2-199](#)
- IP addresses, setting [2-199](#)
- IP address matching [2-339](#)
- ip admission command [2-201](#)
- ip admission name proxy http command [2-202](#)
- ip arp inspection filter vlan command [2-204](#)
- ip arp inspection limit command [2-206](#)
- ip arp inspection log-buffer command [2-208](#)
- ip arp inspection trust command [2-210](#)
- ip arp inspection validate command [2-212](#)
- ip arp inspection vlan command [2-214](#)
- ip arp inspection vlan logging command [2-215](#)
- ip device tracking command [2-217](#)
- ip device tracking probe command [2-219](#)
- IP DHCP snooping
  - See DHCP snooping
- ip dhcp snooping binding command [2-222](#)
- ip dhcp snooping command [2-221](#)
- ip dhcp snooping database command [2-224](#)
- ip dhcp snooping information option allow-untrusted command [2-228](#)
- ip dhcp snooping information option command [2-226](#)
- ip dhcp snooping information option format remote-id command [2-230](#)
- ip dhcp snooping limit rate command [2-231](#)
- ip dhcp snooping trust command [2-232](#)
- ip dhcp snooping verify command [2-233](#)
- ip dhcp snooping vlan command [2-234](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [2-235](#)
- ip igmp filter command [2-237](#)
- ip igmp max-groups command [2-239, 2-264, 2-266](#)
- ip igmp profile command [2-241](#)
- ip igmp snooping command [2-243](#)
- ip igmp snooping last-member-query-interval command [2-245](#)
- ip igmp snooping querier command [2-247](#)
- ip igmp snooping report-suppression command [2-249](#)
- ip igmp snooping tcn command [2-251](#)
- ip igmp snooping tcn flood command [2-253](#)
- ip igmp snooping vlan immediate-leave command [2-254](#)
- ip igmp snooping vlan mrouter command [2-255](#)

- ip igmp snooping vlan static command [2-257](#)
- IP multicast addresses [2-387](#)
- IP phones
  - auto-QoS configuration [2-59](#)
  - trusting packets sent from [2-380](#)
- IP-precedence-to-DSCP map [2-354](#)
- ip snap forwarding command [2-259](#)
- ip source binding command [2-260](#)
- IP source guard
  - disabling [2-268](#)
  - enabling [2-268](#)
  - static IP source bindings [2-260](#)
- ip ssh command [2-262](#)
- IPv6 access list, deny conditions [2-122](#)
- ipv6 access-list command [2-270](#)
- ipv6 address dhcp command [2-272](#)
- ipv6 dhcp client request vendor command [2-273](#)
- ipv6 dhcp ping packets command [2-274](#)
- ipv6 dhcp pool command [2-276](#)
- ipv6 dhcp server command [2-278](#)
- ipv6 mld snooping command [2-280](#)
- ipv6 mld snooping last-listener-query count command [2-282](#)
- ipv6 mld snooping last-listener-query-interval command [2-284](#)
- ipv6 mld snooping listener-message-suppression command [2-286](#)
- ipv6 mld snooping robustness-variable command [2-288](#)
- ipv6 mld snooping tcn command [2-290](#)
- ipv6 mld snooping vlan command [2-292](#)
- ipv6 traffic-filter command [2-294](#)
- ip verify source command [2-268](#)
- lacp port-priority command [2-300](#)
- lacp system-priority command [2-302](#)
- Layer 2 mode, enabling [2-767](#)
- Layer 2 protocol-tunnel
  - error detection for [2-175](#)
  - error recovery timer [2-179](#)
- Layer 2 protocol tunnel counters [2-101](#)
- Layer 2 protocol tunneling error recovery [2-297](#)
- Layer 2 traceroute
  - IP addresses [2-813](#)
  - MAC addresses [2-810](#)
- Layer 3 mode, enabling [2-767](#)
- line configuration mode [1-3, 1-5](#)
- Link Aggregation Control Protocol
  - See EtherChannel
- link flap
  - error detection for [2-175](#)
  - error recovery timer [2-179](#)
- link state group command [2-304](#)
- link state track command [2-306](#)
- load-distribution methods for EtherChannel [2-424](#)
- location (global configuration) command [2-307](#)
- location (interface configuration) command [2-309](#)
- logging file command [2-311](#)
- logical interface [2-190](#)
- loopback error
  - detection for [2-175](#)
  - recovery timer [2-179](#)
- loop guard, for spanning tree [2-712, 2-716](#)

---

## L

- l2protocol-tunnel command [2-296](#)
- l2protocol-tunnel cos command [2-299](#)
- LACP
  - See EtherChannel

---

## M

- mab request format attribute 32 command [2-313](#)
- mac access-group command [2-315](#)
- MAC access list configuration mode [2-317](#)
- mac access-list extended command [2-317](#)
- MAC access lists [2-127](#)



- MAC addresses
  - disabling MAC address learning per VLAN [2-320](#)
  - dynamic
    - aging time [2-319](#)
    - deleting [2-104](#)
  - enabling MAC address notification [2-324](#)
  - enabling MAC address-table move update [2-322](#)
  - matching [2-339](#)
  - persistent stack [2-755](#)
  - static
    - adding and removing [2-326](#)
    - dropping on an interface [2-327](#)
- MAC address notification, debugging [B-21](#)
- mac address-table aging-time [2-315, 2-339](#)
- mac address-table aging-time command [2-319](#)
- mac address-table learning command [2-320](#)
- mac address-table move update command [2-322](#)
- mac address-table notification command [2-324](#)
- mac address-table static command [2-326](#)
- mac address-table static drop command [2-327](#)
- macro apply command [2-329](#)
- macro description command [2-332](#)
- macro global command [2-333](#)
- macro global description command [2-336](#)
- macro name command [2-337](#)
- macros
  - adding a description [2-332](#)
  - adding a global description [2-336](#)
  - applying [2-333](#)
  - creating [2-337](#)
  - interface range [2-117, 2-192](#)
  - specifying parameter values [2-333](#)
  - tracing [2-333](#)
- maps
  - QoS
    - defining [2-354](#)
  - VLAN
    - creating [2-827](#)
    - defining [2-339](#)
- match (access-map configuration) command [2-339](#)
- match (class-map configuration) command [2-341](#)
- maximum transmission unit
  - See MTU
- mdix auto command [2-344](#)
- memory (boot loader) command [A-14](#)
- mgmt\_clr (boot loader) command [A-16](#)
- mgmt\_init (boot loader) command [A-17, A-18](#)
- mkdir (boot loader) command [A-19](#)
- MLD snooping
  - configuring [2-286, 2-288](#)
  - configuring queries [2-282, 2-284](#)
  - configuring topology change notification [2-290](#)
  - enabling [2-280](#)
  - enabling on a VLAN [2-292](#)
- mls qos aggregate-policer command [2-348](#)
- mls qos command [2-346](#)
- mls qos cos command [2-350](#)
- mls qos dscp-mutation command [2-352](#)
- mls qos map command [2-354](#)
- mls qos queue-set output buffers command [2-358](#)
- mls qos queue-set output threshold command [2-360](#)
- mls qos rewrite ip dscp command [2-362](#)
- mls qos srr-queue input bandwidth command [2-364](#)
- mls qos srr-queue input buffers command [2-366](#)
- mls qos srr-queue input cos-map command [2-368](#)
- mls qos srr-queue input dscp-map command [2-370](#)
- mls qos srr-queue input priority-queue command [2-372](#)
- mls qos srr-queue input threshold command [2-374](#)
- mls qos srr-queue output cos-map command [2-376](#)
- mls qos srr-queue output dscp-map command [2-378](#)
- mls qos trust command [2-380](#)
- mls qos vlan-based command [2-382](#)
- mode, MVR [2-387](#)
- modes, commands [1-2](#)
- monitor session command [2-383](#)
- more (boot loader) command [A-20](#)

## MSTP

- interoperability [2-112](#)
- link type [2-714](#)
- MST region
  - aborting changes [2-720](#)
  - applying changes [2-720](#)
  - configuration name [2-720](#)
  - configuration revision number [2-720](#)
  - current or pending display [2-720](#)
  - MST configuration mode [2-720](#)
  - VLANs-to-instance mapping [2-720](#)
- path cost [2-722](#)
- protocol mode [2-718](#)
- restart protocol migration process [2-112](#)
- root port
  - loop guard [2-712](#)
  - preventing from becoming designated [2-712](#)
  - restricting which can be root [2-712](#)
  - root guard [2-712](#)
- root switch
  - affects of extended system ID [2-710](#)
  - hello-time [2-725, 2-732](#)
  - interval between BDPUs messages [2-726](#)
  - interval between hello BPDUs messages [2-725, 2-732](#)
  - max-age [2-726](#)
  - maximum hop count before discarding BPDUs [2-727](#)
  - port priority for selection of [2-728](#)
  - primary or secondary [2-732](#)
  - switch priority [2-731](#)
- state changes
  - blocking to forwarding state [2-739](#)
  - enabling BPDUs filtering [2-702, 2-736](#)
  - enabling BPDUs guard [2-704, 2-736](#)
  - enabling Port Fast [2-736, 2-739](#)
  - forward-delay time [2-724](#)

- length of listening and learning states [2-724](#)
- rapid transition to forwarding [2-714](#)
- shutting down Port Fast-enabled ports [2-736](#)

## MTU

- configuring size [2-807](#)

## Multicast Listener Discovery

- See MLD

- multicast group address, MVR [2-390](#)
- multicast groups, MVR [2-388](#)
- multicast router learning method [2-255](#)
- multicast router ports, configuring [2-255](#)
- multicast router ports, IPv6 [2-292](#)
- multicast storm control [2-757](#)
- multicast VLAN, MVR [2-387](#)
- multicast VLAN registration

- See MVR

- multiple hosts on authorized port [2-154](#)

## Multiple Spanning Tree Protocol

- See MSTP

## MVR

- configuring [2-387](#)
- configuring interfaces [2-390](#)
- debug messages, display [B-25](#)
- mvr (global configuration) command [2-387](#)
- mvr (interface configuration) command [2-390](#)
- mvr vlan group command [2-391](#)

---

**N**

- native VLANs [2-799](#)
- native VLAN tagging [2-829](#)
- network-policy (global configuration) command [2-393](#)
- network-policy command [2-392](#)
- network-policy profile (network-policy configuration) command [2-394](#)
- nmosp attachment suppress command [2-397](#)
- nmosp command [2-396](#)

no authentication logging verbose [2-398](#)  
 no dot1x logging verbose [2-399](#)  
 no mab logging verbose [2-400](#)  
 nonegotiate  
   DTP messaging [2-784](#)  
   speed [2-747](#)  
 non-IP protocols  
   denying [2-127](#)  
   forwarding [2-414](#)  
 non-IP traffic access lists [2-317](#)  
 non-IP traffic forwarding  
   denying [2-127](#)  
   permitting [2-414](#)  
 non-stop forwarding [2-401](#)  
 normal-range VLANs [2-822](#)  
 no vlan command [2-822](#)  
 nsf command [2-401](#)

## O

online diagnostics  
   configuring health monitoring diagnostic tests [2-130](#)  
   enabling  
     scheduling [2-132](#)  
     syslog messages [2-130](#)  
   global configuration mode  
     clearing health monitoring diagnostic test  
     schedule [2-130](#)  
     clearing test-based testing schedule [2-132](#)  
     setting health monitoring diagnostic  
     testing [2-130](#)  
     setting test-based testing [2-132](#)  
     setting up health monitoring diagnostic test  
     schedule [2-130](#)  
     setting up test-based testing [2-132](#)  
   removing scheduling [2-132](#)  
   scheduled switchover  
     disabling [2-132](#)  
     enabling [2-132](#)

setting test interval [2-132](#)  
 specifying health monitoring diagnostic tests [2-130](#)  
 starting testing [2-134](#)

## P

PAgP  
   See EtherChannel  
 pagp learn-method command [2-403](#)  
 pagp port-priority command [2-405](#)  
 password, VTP [2-839](#)  
 permit (ARP access-list configuration) command [2-407](#)  
 permit (IPv6) command [2-409](#)  
 permit (MAC access-list configuration) command [2-414](#)  
 per-VLAN spanning-tree plus  
   See STP  
 physical-port learner [2-403](#)  
 PIM-DVMRP, as multicast router learning method [2-255](#)  
 police aggregate command [2-419](#)  
 police command [2-417](#)  
 policed-DSCP map [2-354](#)  
 policy-map command [2-421](#)  
 policy maps  
   creating [2-421](#)  
   hierarchical [2-422](#)  
   policers  
     for a single class [2-417](#)  
     for multiple classes [2-348, 2-419](#)  
     policed-DSCP map [2-354](#)  
   traffic classification  
     defining the class [2-85](#)  
     defining trust states [2-815](#)  
 Port Aggregation Protocol  
   See EtherChannel  
 port-based authentication  
   AAA method list [2-3](#)  
   configuring violation modes [2-170](#)  
   debug messages, display [B-8](#)  
   enabling guest VLAN supplicant [2-140, 2-151](#)

port-based authentication (continued)

- enabling IEEE 802.1x
  - globally [2-137](#)
  - per interface [2-162](#)
- guest VLAN [2-152](#)
- host modes [2-154](#)
- IEEE 802.1x AAA accounting methods [2-1](#)
- initialize an interface [2-155](#)
- MAC authentication bypass [2-156](#)
- manual control of authorization state [2-162](#)
- multiple hosts on authorized port [2-154](#)
- PAE as authenticator [2-161](#)
- periodic re-authentication
  - enabling [2-165](#)
  - time between attempts [2-167](#)
- quiet period between failed authentication exchanges [2-167](#)
- re-authenticating IEEE 802.1x-enabled ports [2-164](#)
- resetting configurable IEEE 802.1x parameters [2-150](#)
- switch-to-authentication server retransmission time [2-167](#)
- switch-to-client frame-retransmission number [2-158 to 2-160](#)
- switch-to-client retransmission time [2-167](#)

port-channel load-balance command [2-424](#)

Port Fast, for spanning tree [2-739](#)

port ranges, defining [2-115, 2-117](#)

ports, debugging [B-72](#)

ports, protected [2-797](#)

port security
 

- aging [2-791](#)
- debug messages, display [B-74](#)
- enabling [2-786](#)
- violation error recovery [2-179](#)

port trust states for QoS [2-380](#)

port types, MVR [2-390](#)

power information, displaying [2-516](#)

priority-queue command [2-426](#)

priority value, stack member [2-762](#)

private-vlan command [2-428](#)

private-vlan mapping command [2-431](#)

private VLANs
 

- association [2-795](#)
- configuring [2-428](#)
- configuring ports [2-782](#)
- host ports [2-782](#)
- mapping
  - configuring [2-795](#)
  - promiscuous ports [2-782](#)

privileged EXEC mode [1-2, 1-3](#)

promiscuous ports, private VLANs [2-782](#)

pruning
 

- VLANs [2-799](#)
- VTP
  - enabling [2-839](#)

pruning-eligible VLAN list [2-801](#)

psp [2-433](#)

psp command [2-433](#)

PVST+
 

- See STP

---

## Q

QoS
 

- auto-QoS
  - configuring [2-59](#)
  - debug messages, display [B-4](#)
- auto-QoS trust
  - configuring [2-53](#)
- auto-QoS video
  - configuring [2-56](#)
- class maps
  - creating [2-88](#)
  - defining the match criteria [2-341](#)
- defining the CoS value for an incoming packet [2-350](#)
- DSCP transparency [2-362](#)
- DSCP trusted ports
  - applying DSCP-to-DSCP-mutation map to [2-352](#)
  - defining DSCP-to-DSCP-mutation map [2-354](#)

## QoS (continued)

## egress queues

- allocating buffers [2-358](#)
- defining the CoS output queue threshold map [2-376](#)
- defining the DSCP output queue threshold map [2-378](#)
- enabling bandwidth shaping and scheduling [2-751](#)
- enabling bandwidth sharing and scheduling [2-753](#)
- limiting the maximum output on a port [2-749](#)
- mapping a port to a queue-set [2-434](#)
- mapping CoS values to a queue and threshold [2-376](#)
- mapping DSCP values to a queue and threshold [2-378](#)
- setting maximum and reserved memory allocations [2-360](#)
- setting WTD thresholds [2-360](#)

enabling [2-346](#)

## ingress queues

- allocating buffers [2-366](#)
- assigning SRR scheduling weights [2-364](#)
- defining the CoS input queue threshold map [2-368](#)
- defining the DSCP input queue threshold map [2-370](#)
- enabling the priority queue [2-372](#)
- mapping CoS values to a queue and threshold [2-368](#)
- mapping DSCP values to a queue and threshold [2-370](#)
- setting WTD thresholds [2-374](#)

## maps

- defining [2-354](#), [2-368](#), [2-370](#), [2-376](#), [2-378](#)

## policy maps

- applying an aggregate policer [2-419](#)
- creating [2-421](#)
- defining policers [2-348](#), [2-417](#)
- hierarchical [2-422](#)
- policed-DSCP map [2-354](#)

traffic classifications [2-85](#)

trust states [2-815](#)

port trust states [2-380](#)

queues, enabling the expedite [2-426](#)

trusted boundary for IP phones [2-380](#)

VLAN-based [2-382](#)

## quality of service

See QoS

querytime, MVR [2-387](#)

queue-set command [2-434](#)

---

**R**

radius-server dead-criteria command [2-435](#)

radius-server host command [2-437](#)

rapid per-VLAN spanning-tree plus

See STP

rapid PVST+

See STP

re-authenticating IEEE 802.1x-enabled ports [2-164](#)

re-authentication

periodic [2-165](#)

time between attempts [2-167](#)

receiver ports, MVR [2-390](#)

receiving flow-control packets [2-186](#)

recovery mechanism

causes [2-179](#)

display [2-92](#)

timer interval [2-180](#)

reload command [2-439](#)

remote command [2-441](#)

remote-span command [2-443](#)

Remote Switched Port Analyzer

See RSPAN

rename (boot loader) command [A-21](#)

renew ip dhcp snooping database command [2-445](#)

reset (boot loader) command [A-22](#)

restricted VLAN

See dot1x auth-fail vlan

rmdir (boot loader) command [A-23](#)  
 rmon collection stats command [2-449](#)  
 root guard, for spanning tree [2-712](#)  
 routed ports  
   IP addresses on [2-200](#)  
   number supported [2-200](#)  
 RSPAN  
   configuring [2-383](#)  
   filter RSPAN traffic [2-383](#)  
   remote-span command [2-443](#)  
   sessions  
     add interfaces to [2-383](#)  
     start new [2-383](#)

## S

scheduled switchover  
   disabling [2-132](#)  
   enabling [2-132](#)  
 sdm prefer command [2-450](#)  
 SDM templates  
   displaying [2-650](#)  
 secure ports, limitations [2-788](#)  
 sending flow-control packets [2-186](#)  
 service password-recovery command [2-454](#)  
 service-policy command [2-456](#)  
 set (boot loader) command [A-24](#)  
 set command [2-460](#)  
 setup command [2-462](#)  
 setup express command [2-465](#)  
 show access-lists command [2-467](#)  
 show archive status command [2-470](#)  
 show arp access-list command [2-471](#)  
 show authentication command [2-472](#)  
 show auto qos command [2-476](#)  
 show boot command [2-480](#)  
 show cable-diagnostics tdr command [2-483](#)  
 show cisp command [2-485](#)  
 show class-map command [2-486](#)  
 show controllers cpu-interface command [2-487](#)  
 show controllers ethernet-controller command [2-489](#)  
 show controllers ethernet-controller fastethernet command [2-496](#)  
 show controllers team command [2-499](#)  
 show controller utilization command [2-501](#)  
 show dot1q-tunnel command [2-507](#)  
 show dot1x command [2-508](#)  
 show dtp [2-512](#)  
 show eap command [2-514](#)  
 show env command [2-516](#)  
 show errdisable detect command [2-518](#)  
 show errdisable flap-values command [2-520](#)  
 show errdisable recovery command [2-521](#)  
 show etherchannel command [2-523](#)  
 show fallback profile command [2-526](#)  
 show flowcontrol command [2-527](#)  
 show idprom command [2-529](#)  
 show interfaces command [2-531](#)  
 show interfaces counters command [2-543](#)  
 show inventory command [2-545](#)  
 show ip arp inspection command [2-546](#)  
 show ipc command [2-570](#)  
 show ip dhcp snooping binding command [2-551](#)  
 show ip dhcp snooping command [2-550](#)  
 show ip dhcp snooping database command [2-553, 2-555](#)  
 show ip igmp profile command [2-558](#)  
 show ip igmp snooping address command [2-578](#)  
 show ip igmp snooping command [2-559, 2-576](#)  
 show ip igmp snooping groups command [2-562](#)  
 show ip igmp snooping mrouter command [2-564, 2-580](#)  
 show ip igmp snooping querier command [2-565](#)  
 show ip source binding command [2-567](#)  
 show ipv6 access-list command [2-573](#)  
 show ipv6 dhcp conflict command [2-575](#)  
 show ipv6 route updated [2-584](#)  
 show ip verify source command [2-568](#)  
 show l2protocol-tunnel command [2-586](#)  
 show lacp command [2-588](#)

- show link state group command [2-592](#)
- show location command [2-594](#)
- show logging command [2-596](#)
- show mac address-table address command [2-603](#)
- show mac address-table command [2-601](#)
- show mac address-table count command [2-606](#)
- show mac address-table dynamic command [2-607](#)
- show mac address-table interface command [2-609](#)
- show mac address-table learning command [2-610](#)
- show mac address-table move update command [2-611](#)
- show mac address-table notification command [2-105](#),  
[2-612](#), [B-23](#)
- show mac address-table vlan command [2-616](#)
- show mls qos aggregate-policer command [2-619](#)
- show mls qos command [2-618](#)
- show mls qos input-queue command [2-620](#)
- show mls qos interface command [2-621](#)
- show mls qos maps command [2-624](#)
- show mls qos queue-set command [2-627](#)
- show mls qos vlan command [2-628](#)
- show monitor command [2-629](#)
- show network-policy profile command [2-636](#)
- show nmsp command [2-637](#)
- show pagp command [2-640](#)
- show parser macro command [2-642](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform dl command [C-5](#)
- show platform etherchannel command [C-6](#)
- show platform forward command [C-7](#)
- show platform frontend-controller command [C-9](#)
- show platform igmp snooping command [C-10](#)
- show platform ipc trace command [C-17](#)
- show platform ip multicast command [C-11](#)
- show platform ip unicast command [C-12](#)
- show platform ipv6 unicast command [C-18](#)
- show platform ip wccp command [C-16](#)
- show platform layer4op command [C-20](#)
- show platform mac-address-table command [C-21](#)
- show platform messaging command [C-22](#)
- show platform monitor command [C-23](#)
- show platform mvr table command [C-24](#)
- show platform pm command [C-25](#)
- show platform port-asic command [C-26](#)
- show platform port-security command [C-31](#)
- show platform qos command [C-32](#)
- show platform resource-manager command [C-33](#)
- show platform snmp counters command [C-35](#)
- show platform spanning-tree command [C-36](#)
- show platform stack-manager command [C-38](#)
- show platform stp-instance command [C-37](#)
- show platform tb command [C-42](#)
- show platform team command [C-44](#)
- show platform vlan command [C-47](#)
- show policy-map command [2-645](#)
- show port security command [2-646](#)
- show psp config [2-648](#)
- show psp config command [2-648](#)
- show psp statistics [2-649](#)
- show psp statistics command [2-649](#)
- show sdm prefer command [2-650](#)
- show setup express command [2-653](#)
- show spanning-tree command [2-654](#)
- show storm-control command [2-660](#)
- show switch command [2-662](#)
- show system mtu command [2-667](#)
- show trust command [2-815](#)
- show uddl command [2-668](#)
- show version command [2-671](#)
- show vlan access-map command [2-677](#)
- show vlan command [2-673](#)
- show vlan filter command [2-678](#)
- show vmmps command [2-679](#)
- show vtp command [2-681](#)
- shutdown command [2-687](#)
- shutdown threshold, Layer 2 protocol tunneling [2-296](#)
- shutdown vlan command [2-688](#)

- small violation-rate command [2-689](#)
- Smartports macros
  - See macros
- SNMP host, specifying [2-695](#)
- SNMP informs, enabling the sending of [2-691](#)
- snmp-server enable traps command [2-691](#)
- snmp-server host command [2-695](#)
- snmp trap mac-notification command [2-699](#)
- SNMP traps
  - enabling MAC address notification trap [2-699](#)
  - enabling the MAC address notification feature [2-324](#)
  - enabling the sending of [2-691](#)
- SoftPhone
  - See Cisco SoftPhone
- software images
  - copying [2-8](#)
  - deleting [2-119](#)
  - downloading [2-11](#)
  - upgrading [2-8, 2-11](#)
  - uploading [2-18](#)
- source ports, MVR [2-390](#)
- SPAN
  - configuring [2-383](#)
  - debug messages, display [B-24](#)
  - filter SPAN traffic [2-383](#)
  - sessions
    - add interfaces to [2-383](#)
    - start new [2-383](#)
- spanning-tree backbonefast command [2-701](#)
- spanning-tree bpduguard command [2-702](#)
- spanning-tree bpduguard command [2-704](#)
- spanning-tree cost command [2-706](#)
- spanning-tree etherchannel command [2-708](#)
- spanning-tree extend system-id command [2-710](#)
- spanning-tree guard command [2-712](#)
- spanning-tree link-type command [2-714](#)
- spanning-tree loopguard default command [2-716](#)
- spanning-tree mode command [2-718](#)
- spanning-tree mst configuration command [2-720](#)
- spanning-tree mst cost command [2-722](#)
- spanning-tree mst forward-time command [2-724](#)
- spanning-tree mst hello-time command [2-725](#)
- spanning-tree mst max-age command [2-726](#)
- spanning-tree mst max-hops command [2-727](#)
- spanning-tree mst port-priority command [2-728](#)
- spanning-tree mst pre-standard command [2-730](#)
- spanning-tree mst priority command [2-731](#)
- spanning-tree mst root command [2-732](#)
- spanning-tree portfast (global configuration) command [2-736](#)
- spanning-tree portfast (interface configuration) command [2-739](#)
- spanning-tree port-priority command [2-734](#)
- Spanning Tree Protocol
  - See STP
- spanning-tree transmit hold-count command [2-741](#)
- spanning-tree uplinkfast command [2-742](#)
- spanning-tree vlan command [2-744](#)
- speed command [2-747](#)
- srr-queue bandwidth limit command [2-749](#)
- srr-queue bandwidth shape command [2-751](#)
- srr-queue bandwidth share command [2-753](#)
- SSH, configuring version [2-262](#)
- stack-mac persistent timer command [2-755](#)
- stack member
  - number [2-765](#)
  - priority value [2-762](#)
  - provisioning [2-763](#)
  - reloading [2-439](#)
- stacks, switch
  - disabling a member [2-760](#)
  - enabling a member [2-760](#)
  - MAC address [2-755](#)
  - provisioning a new member [2-763](#)
  - reloading [2-439](#)
  - stack member number [2-765](#)
  - stack member priority value [2-762](#)
- static-access ports, configuring [2-769](#)



- sticky learning, enabling [2-786](#)
- storm-control command [2-757](#)
- STP
  - BackboneFast [2-701](#)
  - counters, clearing [2-111](#)
  - debug messages, display
    - BackboneFast events [B-78](#)
    - MSTP [B-81](#)
    - optimized BPDUs handling [B-80](#)
    - spanning-tree activity [B-76](#)
    - switch shim [B-83](#)
    - transmitted and received BPDUs [B-79](#)
    - UplinkFast [B-85](#)
  - detection of indirect link failures [2-701](#)
  - enabling protocol tunneling for [2-296](#)
  - EtherChannel misconfiguration [2-708](#)
  - extended system ID [2-710](#)
  - path cost [2-706](#)
  - protocol modes [2-718](#)
  - root port
    - accelerating choice of new [2-742](#)
    - loop guard [2-712](#)
    - preventing from becoming designated [2-712](#)
    - restricting which can be root [2-712](#)
    - root guard [2-712](#)
    - UplinkFast [2-742](#)
  - root switch
    - affects of extended system ID [2-710, 2-745](#)
    - hello-time [2-744](#)
    - interval between BDPU messages [2-744](#)
    - interval between hello BPDU messages [2-744](#)
    - max-age [2-744](#)
    - port priority for selection of [2-734](#)
    - primary or secondary [2-744](#)
    - switch priority [2-744](#)
  - state changes
    - blocking to forwarding state [2-739](#)
    - enabling BPDU filtering [2-702, 2-736](#)
    - enabling BPDU guard [2-704, 2-736](#)
    - enabling Port Fast [2-736, 2-739](#)
    - enabling timer to recover from error state [2-179](#)
    - forward-delay time [2-744](#)
    - length of listening and learning states [2-744](#)
    - shutting down Port Fast-enabled ports [2-736](#)
    - VLAN options [2-731, 2-744](#)
  - SVIs, creating [2-194](#)
  - SVI status calculation [2-771](#)
  - Switched Port Analyzer
    - See SPAN
  - switching characteristics
    - modifying [2-767](#)
    - returning to interfaces [2-767](#)
  - switchport access command [2-769](#)
  - switchport autostate exclude command [2-771](#)
  - switchport backup interface command [2-773](#)
  - switchport block command [2-776](#)
  - switchport command [2-767](#)
  - switchport host command [2-778](#)
  - switchport mode command [2-779](#)
  - switchport mode private-vlan command [2-782](#)
  - switchport nonegotiate command [2-784](#)
  - switchport port-security aging command [2-791](#)
  - switchport port-security command [2-786](#)
  - switchport priority extend command [2-793](#)
  - switchport private-vlan command [2-795](#)
  - switchport protected command [2-797](#)
  - switchport trunk command [2-799](#)
  - switchport voice detect [2-802](#)
  - switchport voice vlan command [2-803](#)
  - switch priority command [2-760, 2-762](#)
  - switch provision command [2-763](#)
  - switch renumber command [2-765](#)
  - system env temperature threshold yellow command [2-805](#)
  - system message logging, save message to flash [2-311](#)
  - system mtu command [2-807](#)
  - system resource templates [2-450](#)

**T**

tar files, creating, listing, and extracting [2-15](#)  
 TDR, running [2-809](#)  
 temperature information, displaying [2-516](#)  
 templates, system resources [2-450](#)  
 test cable-diagnostics tdr command [2-809](#)  
 traceroute mac command [2-810](#)  
 traceroute mac ip command [2-813](#)  
 trunking, VLAN mode [2-779](#)  
 trunk mode [2-779](#)  
 trunk ports [2-779](#)  
 trunks, to non-DTP device [2-780](#)  
 trusted boundary for QoS [2-380](#)  
 trusted port states for QoS [2-380](#)  
 type (boot loader) command [A-27](#)

**U**

UDLD  
   aggressive mode [2-817, 2-819](#)  
   debug messages, display [B-93](#)  
   enable globally [2-817](#)  
   enable per interface [2-819](#)  
   error recovery timer [2-179](#)  
   message timer [2-817](#)  
   normal mode [2-817, 2-819](#)  
   reset a shutdown interface [2-821](#)  
 uddl command [2-817](#)  
 uddl port command [2-819](#)  
 uddl reset command [2-821](#)  
 unicast storm control [2-757](#)  
 UniDirectional Link Detection  
   See UDLD  
 unknown multicast traffic, preventing [2-776](#)  
 unknown unicast traffic, preventing [2-776](#)  
 unset (boot loader) command [A-28](#)

upgrading  
   copying software images [2-8](#)  
   downloading software images [2-11](#)  
 UplinkFast, for STP [2-742](#)  
 user EXEC mode [1-2, 1-3](#)

**V**

version (boot loader) command [A-30](#)  
 version mismatch mode [C-39](#)  
 vlan (global configuration) command [2-822](#)  
 vlan access-map command [2-827](#)  
 VLAN access map configuration mode [2-827](#)  
 VLAN access maps  
   actions [2-6](#)  
 VLAN-based QoS [2-382](#)  
 VLAN configuration  
   rules [2-825](#)  
   saving [2-822](#)  
 VLAN configuration mode  
   description [1-4](#)  
   summary [1-3](#)  
 vlan dot1q tag native command [2-829](#)  
 vlan filter command [2-831](#)  
 VLAN ID range [2-822](#)  
 VLAN maps  
   applying [2-831](#)  
   creating [2-827](#)  
   defining [2-339](#)  
 VLAN Query Protocol  
   See VQP  
 VLANs  
   adding [2-822](#)  
   configuring [2-822](#)  
   debug messages, display  
     ISL [B-89](#)  
     VLAN IOS file system error tests [B-88](#)  
     VLAN manager activity [B-86](#)  
     VTP [B-91](#)

## VLANs (continued)

- extended-range [2-822](#)

- media types [2-825](#)

- normal-range [2-822](#)

- private [2-782](#)

- configuring [2-428](#)

- See also private VLANs

- restarting [2-688](#)

- saving the configuration [2-822](#)

- shutting down [2-688](#)

- SNMP traps for VTP [2-693, 2-696](#)

- suspending [2-688](#)

## VLAN Trunking Protocol

- See VTP

VM mode [C-39](#)

## VMPS

- configuring servers [2-836](#)

- error recovery timer [2-180](#)

- reconfirming dynamic VLAN assignments [2-833](#)

- vmps reconfirm (global configuration) command [2-834](#)

- vmps reconfirm (privileged EXEC) command [2-833](#)

- vmps retry command [2-835](#)

- vmps server command [2-836](#)

## voice VLAN

- configuring [2-802, 2-803](#)

- setting port priority [2-793](#)

## VQP

- and dynamic-access ports [2-770](#)

- clearing client statistics [2-113](#)

- per-server retry count [2-835](#)

- reconfirmation interval [2-834](#)

- reconfirming dynamic VLAN assignments [2-833](#)

## VTP

- changing characteristics [2-838](#)

- clearing pruning counters [2-114](#)

- configuring

- domain name [2-838](#)

- file name [2-838](#)

- mode [2-838](#)

- password [2-839](#)

- enabling

- pruning [2-839](#)

- tunneling for [2-296](#)

- Version 2 [2-839](#)

- enabling per port [2-843](#)

- mode [2-838](#)

- pruning [2-839](#)

- saving the configuration [2-822](#)

- vtp (global configuration) command [2-838](#)

- vtp interface configuration) command [2-843](#)

- vtp primary command [2-844](#)

