



W Commands

- [webtoken-timeout-seconds, on page 2](#)
- [weight, on page 3](#)
- [where, on page 4](#)
- [where detail, on page 5](#)
- [whitelist-blacklist-mix, on page 6](#)
- [window-size, on page 7](#)
- [winservers, on page 8](#)

webtoken-timeout-seconds

webtoken-timeout-seconds

webtoken-timeout-seconds <NUMBER>**Description:** Set The web token timeout interval**Syntax:**

<300-9600>	Set The web token timeout interval. Number range from=300 to=9600
------------	---

Command Mode: crypto webtoken : The cryptographic data used for generating and verifying web tokens.**Command Path:**

```
# configure [['terminal', 't']]  
(config)# crypto webtoken  
(config-webtoken)# webtoken-timeout-seconds <NUMBER>
```

weight

weight <NUMBER>

Description: Weight attribute that is local to a router.

Syntax:

<0-65535>	Assigns a weight to all routes learned through the neighbor. Number range from=0 to=65535
-----------	---

Command Mode: address-family : Configure an address-family for peer

Command Path:

```
# configure [['terminal', 't']]
(config)# leaf <101-4000>
(config-leaf)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out <WORD>]
(config-leaf-bgp-vrf-neighbor)# address-family ipv4|ipv6|l2vpn unicast|evpn
(config-leaf-bgp-vrf-neighbor-af)# weight <NUMBER>
```

weight <NUMBER>

Description: Weight attribute that is local to a router.

Syntax:

<0-65535>	Assigns a weight to all routes learned through the neighbor. Number range from=0 to=65535
-----------	---

Command Mode: address-family : Configure an address-family for peer

Command Path:

```
# configure [['terminal', 't']]
(config)# spine <101-4000>
(config-spine)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out <WORD>]
(config-leaf-bgp-vrf-neighbor)# address-family ipv4|ipv6|l2vpn unicast|evpn
(config-leaf-bgp-vrf-neighbor-af)# weight <NUMBER>
```

where

where

Description: Show the current mode

Command Mode: exec : Exec Mode

Command Path:

```
# where
```

where detail

where detail

Description: Show detailed mode information

Command Mode: exec : Exec Mode

Command Path:

```
# where detail
```

whitelist-blacklist-mix

whitelist-blacklist-mix

Description: WhiteList/BlackList mode coexistance

Command Mode: vrf : Configuration for vrf

Command Path:

```
# configure [['terminal', 't']]  
(config)# tenant <WORD>  
(config-tenant)# vrf context <WORD>  
(config-tenant-vrf)# whitelist-blacklist-mix
```

window-size

window-size <NUMBER>

Description: Configure the replay protection window size

Syntax:

<0-4294967295>	window size. Number range from=0 to=4294967295
----------------	--

Command Mode: template macsec access|fabric security-policy : Configure MAC security policy parameters

Command Path:

```
# configure [['terminal', 't']]  
(config)# template macsec access|fabric security-policy <WORD>  
(config-macsec-param)# window-size <NUMBER>
```

winservers

winservers <windows server ip>

Description: Add windows server

Syntax:

<i>windows server ip</i>	windows server ip
--------------------------	-------------------

Command Mode: microsoft : Configure static IP pool

Command Path:

```
# configure [['terminal', 't']]  
(config)# tenant <WORD>  
(config-tenant)# application <WORD>  
(config-tenant-app)# epg <WORD> [type <WORD>]  
(config-tenant-app-epg)# microsoft static-ip-pool <name> gateway <gwAddress>  
(config-tenant-app-epg-ms-ip-pool)# winservers <windows server ip>
```