



New and Changed Information

This chapter contains the following sections:

- [New and Changed Information, on page 1](#)

New and Changed Information

The following table provides an overview of the significant changes to this guide for this current release. The table does not provide an exhaustive list of all changes made to the guide or of the new features in this release.

Feature	Description	Where Documented
Cisco ACI with Cisco UCSM Integration	Beginning in Cisco APIC Release 4.1(1), you can automate networking policies on Cisco UCS devices. To do so, you integrate Cisco UCSM into the Cisco Application Centric Infrastructure (ACI) fabric. Cisco APIC takes hypervisor NIC information from the Cisco UCSM and a virtual machine manager (VMM). The automation applies to all the devices that the Cisco UCSM manages.	<ul style="list-style-type: none"> • The section "Cisco ACI VM Networking Support for Virtual Machine Managers" in this guide. • The chapter "Cisco ACI with Cisco UCSM Integration" in the Cisco ACI Virtualization Guide, Release 4.1(1)
ACI IP SLAs	Support for IP SLAs in static routes	<ul style="list-style-type: none"> • The section "ACI IP SLAs" in this guide. • The chapter "IP SLAs" in the Cisco Layer 3 Networking Configuration Guide, Release 4.1(x)

Feature	Description	Where Documented
Multi-Tier Architecture (Tier-2 Leaf)	Cisco APIC now supports a 3-tier core-aggregation-access topology.	<ul style="list-style-type: none">• The section "Multi-Tier Architecture" in this guide.• The chapter "Fabric Initialization and Switch Discovery" in the <i>Cisco APIC Getting Started Guide, Release 4.1(x)</i>