



Cisco CSP 2100 X2 Power Cord Specifications

This appendix provides supported power cable specifications for Cisco CSP 2100 X2.

Supported Power Cords and Plugs

Each power supply has a separate power cord. Standard power cords or jumper power cords are available for connection to the Cisco CSP 2100 X2. The jumper power cords, for use in racks, are available as an optional alternative to the standard power cords.



Note

Only the approved power cords or jumper power cords provided with the Cisco CSP 2100 X2 are supported.

[Table 10-1](#) lists the power cords for the Cisco CSP 2100 X2 power supplies.

Table 10-1 Supported Power Cords for the Cisco CSP 2100 X2

Description	Length	
	Feet	Meters
CAB-9K10A-AU AC power cord, 250 V, 10 A, 3112 plug, Australia	8.2	2.5
CAB-JPN-3PIN AC Power Cord, 3-pin Japan	6.6	2.0
CAB-C13-C14-2M AC cabinet jumper power cord, 250 V, 10 A, C13 to C14	6.6	2.0
CAB-9K10A-EU AC Power Cord, 250 V, 10 A; CEE 7/7 Plug Europe	8.2	2.5
CAB-N5K6A-NA AC power cord, 200/240 V, 6 A, North America	8.2	2.5

Table 10-1 Supported Power Cords for the Cisco CSP 2100 X2

Description	Length	
	Feet	Meters
CAB-250V-10A-ID AC power Cord, 250 V, 10 A, India	8.2	2.5
CAB-250V-10A-BR AC power Cord, 250 V, 10 A Brazil	8.2	2.5
CAB-9K10A-UK AC power cord, 250 V, 10 A (13 A fuse), BS1363 plug United Kingdom	8.2	2.5
CAB-C13-CBN AC cabinet jumper power cord, 250, 10 A, C13 to C14	2.2	0.68
CAB-9K10A-SW AC power cord, 250 V, 10 A, MP232 plug Switzerland	8.2	2.5
CAB-250V-10A-CN AC power cord, 250 V, 10 A PR China	8.2	2.5
CAB-250V-10A-AR AC power cord, 250 V, 10 A Argentina	8.2	2.5
CAB-C13-C14-AC AC power cord, 10 A; C13 to C14, recessed receptacle	9.8	3.0
R2XX-DMYMPWRCORD No power cord; PID option for ordering Cisco CSP 2100 X2 with no power cord	NA	NA
CAB-AC-L620-C13 AC power cord, NEMA L6-20 to C13 connectors	6.6	2.0
CAB-48DC-40A-8AWG DC power cord, -48 VDC, 40 A, 8 AWG Three-socket Mini-Fit connector to three-wire	11.7	3.5
CAB-9K10A-IT AC power cord, 250 V, 10 A, CEI 23-16/VII plug Italy	8.2	2.5
CAB-9K12A-NA AC power cord, 125 V, 13 A, NEMA 5-15 plug North America	8.2	2.5

Table 10-1 Supported Power Cords for the Cisco CSP 2100 X2

Description	Length	
	Feet	Meters
CAB-C13-C14-2M-JP AC Power Cord, C13 to C14 Japan PSE Mark	6.6	2.0
CAB-250V-10A-IS AC Power Cord, 250 V, 10 A Israel	8.2	2.5

