



## B Commands

---

- [show background](#), on page 3
- [show banner motd](#), on page 4
- [show bash-shell](#), on page 5
- [show bfd-app session status](#), on page 6
- [show bfd addrmap](#), on page 7
- [show bfd clients](#), on page 8
- [show bfd discrmap](#), on page 9
- [show bfd intfipmap](#), on page 10
- [show bfd neighbors](#), on page 11
- [show bfd scalar](#), on page 15
- [show bfd session](#), on page 16
- [show bgp](#), on page 19
- [show bgp](#), on page 25
- [show bgp](#), on page 28
- [show bgp](#), on page 36
- [show bgp](#), on page 42
- [show bgp](#), on page 43
- [show bgp](#), on page 46
- [show bgp bmp server](#), on page 48
- [show bgp community](#), on page 51
- [show bgp convergence](#), on page 57
- [show bgp convergence private](#), on page 59
- [show bgp dampening dampened](#), on page 60
- [show bgp dampening flap-statistics](#), on page 66
- [show bgp dampening parameters](#), on page 69
- [show bgp default-info](#), on page 72
- [show bgp event-history](#), on page 73
- [show bgp extcommunity](#), on page 74
- [show bgp l3vpn](#), on page 80
- [show bgp neighbors](#), on page 82
- [show bgp neighbors](#), on page 91
- [show bgp neighbors commands](#), on page 97
- [show bgp neighbors flap-statistics](#), on page 99

- [show bgp neighbors paths](#), on page 101
- [show bgp paths](#), on page 103
- [show bgp peer-template](#), on page 104
- [show bgp peer](#), on page 108
- [show bgp prefix-list](#), on page 110
- [show bgp private](#), on page 115
- [show bgp private attr](#), on page 116
- [show bgp private damp](#), on page 117
- [show bgp private debug history](#), on page 118
- [show bgp process](#), on page 119
- [show bgp received-paths](#), on page 124
- [show bgp regexp](#), on page 130
- [show bgp self-originated](#), on page 135
- [show bgp sessions](#), on page 140
- [show bgp statistics](#), on page 142
- [show bgp summary](#), on page 143
- [show bgp summary](#), on page 147
- [show boot](#), on page 151
- [show boot auto-copy](#), on page 152
- [show boot auto-copy list](#), on page 153
- [show boot autocopy-status](#), on page 154
- [show boot current](#), on page 155
- [show boot mode](#), on page 156
- [show boot order](#), on page 157
- [show boot sup-1](#), on page 158
- [show boot sup-2](#), on page 159
- [show boot timings](#), on page 160
- [show boot variables](#), on page 161
- [show bootmode](#), on page 162
- [show buffers ip](#), on page 163

# show background

show background

## Syntax Description

show	Show running system information
background	show background processes (started with 'source background <file>' command)

## Command Mode

- /exec

# show banner motd

```
show banner motd [ __readonly__ { banner_msg <b_msg> } ]
```

## Syntax Description

show	Show running system information
banner	Show current motd banner message
motd	Show current motd banner message
__readonly__	(Optional)
banner_msg	(Optional) The banner message
<i>b_msg</i>	(Optional) The banner message

## Command Mode

- /exec

# show bash-shell

```
show bash-shell [ __readonly__ { operation_status <o_status> } ]
```

## Syntax Description

show	Show running system information
bash-shell	Show bash shell status
<i>__readonly__</i>	(Optional)
<i>operation_status</i>	(Optional) Bash shell status
<i>o_status</i>	(Optional) operational status of bash shell

## Command Mode

- /exec

## show bfd-app session status

```
show bfd-app session status { src-ip { <src_ip> dest-ip <dest_ip> | <src_ipv6> dest-ip <dest_ipv6> } { iod
<iod_id> | intf <intf_id> } | <all> }
```

### Syntax Description

show	Show running system information
bfd-app	BFD application commands
session	session operation
src-ip	Source ip
<i>src_ip</i>	Source ip value
dest-ip	Destination ip
<i>dest_ip</i>	Destination ip value
iod	interface iod
<i>iod_id</i>	Interface iod in hex
intf	interface
<i>intf_id</i>	Interface Id
status	status of sessions
<i>all</i>	All sessions

### Command Mode

- /exec

# show bfd addrmap

```
show bfd addrmap [ application <appid> discriminator <discr> address-type <addrtype> address <addr> ] [
__readonly__ TABLE_bfdSessMapTable <ciscoBfdSessApplicationId> <ciscoBfdSessDiscriminator>
<ciscoBfdSessAddrType> <ciscoBfdSessAddr> <ciscoBfdSessMapBfdIndex> ]
```

## Syntax Description

show	Show running system information
bfd	BFD commands
addrmap	Session
application	(Optional)
discriminator	(Optional)
address-type	(Optional)
address	(Optional)
<i>appid</i>	(Optional)
<i>discr</i>	(Optional)
<i>addrtype</i>	(Optional)
<i>addr</i>	(Optional)
<i>__readonly__</i>	(Optional)
TABLE_bfdSessMapTable	(Optional) Address Map table
<i>ciscoBfdSessApplicationId</i>	(Optional)
<i>ciscoBfdSessDiscriminator</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessMapBfdIndex</i>	(Optional)

## Command Mode

- /exec

## show bfd clients

show bfd clients [ *\_\_readonly\_\_* <header> TABLE-bfdClients <client\_name> <num\_sess> ]

### Syntax Description

show	Show running system information
bfd	BFD commands
clients	bfd client list
<i>__readonly__</i>	(Optional)
<i>header</i>	(Optional) print header
TABLE-bfdClients	(Optional) BFD Client table
<i>client_name</i>	(Optional) client name
<i>num_sess</i>	(Optional) Number of sessions

### Command Mode

- /exec

# show bfd discrmap

```
show bfd discrmap [ <discr> ] [ __readonly__ TABLE_bfdDiscMapTable <ciscoBfdSessDiscMapIndex> ]
```

## Syntax Description

show	Show running system information
bfd	BFD commands
discrmap	Session
<i>discr</i>	(Optional)
<i>__readonly__</i>	(Optional)
<i>TABLE_bfdDiscMapTable</i>	(Optional) Discriminator map table
<i>ciscoBfdSessDiscMapIndex</i>	(Optional)

## Command Mode

- /exec

# show bfd intfipmap

```
show bfd intfipmap [ interface <intf> address-type <addrtype> address <addr> ] [ __readonly__
TABLE_ipMapTable <ciscoBfdSessInterface> <ciscoBfdSessAddrType> <ciscoBfdSessAddr>
<ciscoBfdSessIpMapIndex> ]
```

## Syntax Description

show	Show running system information
bfd	BFD commands
intfipmap	Session
interface	(Optional)
address-type	(Optional)
address	(Optional)
<i>intf</i>	(Optional)
<i>addrtype</i>	(Optional)
<i>addr</i>	(Optional)
<i>__readonly__</i>	(Optional)
TABLE_ipMapTable	(Optional) ip map table
<i>ciscoBfdSessInterface</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessIpMapIndex</i>	(Optional)

## Command Mode

- /exec

## show bfd neighbors

```
show bfd { [ vrf { <vrf-name> | <vrf-known-name> | all } ] } { [ <ip_type> ] } neighbors { [ module
<module_no> ] [ interface <intf_id> ] [ application <bfd_cli_client_names> ] [ { src-ip <src_ip> | src-ipv6
<src_ipv6> } ] [ { dest-ip <dest_ip> | dest-ipv6 <dest_ipv6> } ] [ vrf { <vrf-name> | <vrf-known-name> |
all } ] } + [ details ] [ __readonly__ TABLE_bfdNeighbor <local_disc> [ <header> ] [ <vrf_name> ] [
<src_ip_addr> ] [ <src_ipv6_addr> ] [ <dest_ip_addr> ] [ <dest_ipv6_addr> ] [ <remote_disc> ] [ <local_state>
] [ <remote_state> ] [ <holddown> ] [ <cur_detect_mult> ] [ <intf> ] [ <echo> ] [ <echo_tx> ] [ <local_diag>
] [ <demand> ] [ <poll> ] [ <min_tx> ] [ <min_rx> ] [ <local_multi> ] [ <dectect_timer> ] [ <down_count>
] [ <tx_interval> ] [ <rx_count> ] [ <rx_avg> ] [ <rx_min> ] [ <rx_max> ] [ <last_rx> ] [ <tx_count> ] [
<tx_avg> ] [ <tx_min> ] [ <tx_max> ] [ <last_tx> ] [ <app> ] [ <up_time> ] [ <version> ] [ <diag> ] [
<state_bit> ] [ <demand_bit> ] [ <poll_bit> ] [ <final_bit> ] [ <multiplier> ] [ <length> ] [ <my_disc> ] [
<your_disc> ] [ <min_tx_interval> ] [ <req_min_rx> ] [ <min_echo_interval> ] [ <out_str> ] [ <host_lc> ] [
<down_reason> ] [ <no_host_reason> ] [ <parent> ] [ <per_link_str> ] [ <auth> ] [ <auth_bit> ] [ <print_details>
] ]
```

### Syntax Description

show	Show running system information
bfd	BFD commands
<i>ip_type</i>	(Optional) ipv4 or ipv6
neighbors	neighbors
module	(Optional) module
<i>module_no</i>	(Optional) module number
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>bfd_cli_client_names</i>	(Optional) __nil__ Clients need to register with bfd for this list
src-ip	(Optional) Source ip
src-ipv6	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
dest-ipv6	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name

<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
details	(Optional) details
<i>__readonly__</i>	(Optional)
TABLE_bfdNeighbor	(Optional) BFD Neighbor table
<i>header</i>	(Optional) Header
<i>vrf_name</i>	(Optional) vrf name
<i>src_ip_addr</i>	(Optional) Source IPV4 address
<i>dest_ip_addr</i>	(Optional) Destination IPV4 address
<i>local_disc</i>	(Optional) Local Discriminator
<i>remote_disc</i>	(Optional) Remote Discriminator
<i>local_state</i>	(Optional) Local State
<i>remote_state</i>	(Optional) Remote State
<i>holddown</i>	(Optional) Hold Down Time
<i>cur_detect_mult</i>	(Optional) Current Detection Multiplier
<i>intf</i>	(Optional) Interface
<i>echo</i>	(Optional) Echo enabled
<i>echo_tx</i>	(Optional) Echo Tx Interval
<i>local_diag</i>	(Optional) Local Diag
<i>demand</i>	(Optional) Demand Mode
<i>poll</i>	(Optional) Poll Bit
<i>min_tx</i>	(Optional) Local Min Tx Interval
<i>min_rx</i>	(Optional) Local Min Rx Interval
<i>local_multi</i>	(Optional) Local Detection Multiplier
<i>dectect_timer</i>	(Optional) Current Detection Timer
<i>down_count</i>	(Optional) Session Down Count
<i>tx_interval</i>	(Optional) Tx Interval
<i>rx_count</i>	(Optional) Tx Count
<i>rx_avg</i>	(Optional) Rx Interval Avg

<i>rx_min</i>	(Optional) Rx Interval Min
<i>rx_max</i>	(Optional) Rx Interval Max
<i>last_rx</i>	(Optional) Last Rx time
<i>tx_count</i>	(Optional) Tx Count
<i>tx_avg</i>	(Optional) Tx Interval Avg
<i>tx_min</i>	(Optional) Tx Interval Min
<i>tx_max</i>	(Optional) Tx Interval Max
<i>last_tx</i>	(Optional) Last Tx time
<i>app</i>	(Optional) App name
<i>up_time</i>	(Optional) Up time
<i>version</i>	(Optional) Version in Last Packet
<i>diag</i>	(Optional) diag in Last Packet
<i>state_bit</i>	(Optional) State Bit in Last Packet
<i>demand_bit</i>	(Optional) Demand Bit in Last Packet
<i>poll_bit</i>	(Optional) Poll Bit in Last Packet
<i>final_bit</i>	(Optional) Final Bit in Last Packet
<i>multiplier</i>	(Optional) Detection Multiplier in Last Packet
<i>length</i>	(Optional) Length in Last Packet
<i>my_disc</i>	(Optional) My Discriminator in Last Packet
<i>your_disc</i>	(Optional) Your Discriminator in Last Packet
<i>min_tx_interval</i>	(Optional) Min Tx Interval in Last Packet
<i>req_min_rx</i>	(Optional) Required Rx Interval in Last Packet
<i>min_echo_interval</i>	(Optional) Min Echo Interval in Last Packet
<i>out_str</i>	(Optional) No Host LC string
<i>parent</i>	(Optional) Parent Session
<i>per_link_str</i>	(Optional) Per Link string
<i>host_lc</i>	(Optional) Host LC
<i>down_reason</i>	(Optional) Session Down Reason
<i>no_host_reason</i>	(Optional) Not Hosted Reason

<i>auth</i>	(Optional) Authentication Mode
<i>auth_bit</i>	(Optional) Auth Bit in Last Packet
<i>print_details</i>	(Optional) print details

**Command Mode**

- /exec

# show bfd scalar

show bfd scalar [ \_\_readonly\_\_ <adminStatus> <version> <notifEnable> ]

## Syntax Description

show	Show running system information
bfd	BFD commands
scalar	bfd mib scalars
__readonly__	(Optional)
<i>adminStatus</i>	(Optional) bfd admin status
<i>version</i>	(Optional) bfd version number
<i>notifEnable</i>	(Optional) Enable bfd traps

## Command Mode

- /exec

## show bfd session

```
show bfd session { [ discriminator <sessionIndex> ] | [ interface <intf_id> ] | [ application <app_name> ] | [ src-ip <src_ip> ] | [ dest-ip <dest_ip> ] | [ vrf { <vrf-name> | <vrf-known-name> | all } ] } + [ __readonly__ <vrf_name_header> TABLE_bfdSessTable <ciscoBfdSessIndex> <isMember> <ciscoBfdSessApplicationId> <ciscoBfdSessDiscriminator> <ciscoBfdSessRemoteDiscr> <ciscoBfdSessUdpPort> <ciscoBfdSessState> <remoteBfdSessState> <ciscoBfdSessRemoteHeardFlag> <ciscoBfdSessDiag> <remoteBfdSessDiag> <ciscoBfdSessOperMode> <ciscoBfdSessDemandModeDesiredFlag> <ciscoBfdSessEchoFuncModeDesiredFlag> <ciscoBfdSessControlPlanIndepFlag> <ciscoBfdSessAddrType> <ciscoBfdSessAddr> <localBfdSessAddr> <ciscoBfdSessDesiredMinTxInterval> <ciscoBfdSessReqMinRxInterval> <ciscoBfdSessReqMinEchoRxInterval> <ciscoBfdSessDetectMult> <remoteBfdSessDesiredMinTxInterval> <remoteBfdSessReqMinRxInterval> <remoteBfdSessReqMinEchoRxInterval> <remoteBfdSessDetectMult> <ciscoBfdSessStorType> <ciscoBfdSessRowStatus> <ciscoBfdSessAuthPresFlag> <ciscoBfdSessAuthenticationType> <ciscoBfdSessVersionNumber> <ciscoBfdSessType> <ciscoBfdSessInterface> <ciscoBfdSessPerfPktIn> <ciscoBfdSessPerfPktOut> <ciscoBfdSessUpTime> <ciscoBfdSessPerfLastSessDownTime> <ciscoBfdSessPerfLastCommLostDiag> <ciscoBfdSessPerfSessUpCount> <ciscoBfdSessPerfDiscTime> <ciscoBfdSessPerfPktInHC> <ciscoBfdSessPerfPktOutHC> <effasyncdt> <effechothd> ]
```

### Syntax Description

show	Show running system information
bfd	BFD commands
session	Session
discriminator	(Optional) Session local discriminator
<i>sessionIndex</i>	(Optional)
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>app_name</i>	(Optional) show bfd session based on application name
src-ip	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

<i>__readonly__</i>	(Optional)
<i>vrf_name_header</i>	(Optional)
TABLE_bfdSessTable	(Optional) BFD Session table
<i>ciscoBfdSessIndex</i>	(Optional)
<i>isMember</i>	(Optional)
<i>ciscoBfdSessApplicationId</i>	(Optional)
<i>ciscoBfdSessDiscriminator</i>	(Optional)
<i>ciscoBfdSessRemoteDiscr</i>	(Optional)
<i>ciscoBfdSessUdpPort</i>	(Optional)
<i>ciscoBfdSessState</i>	(Optional) Session state
<i>remoteBfdSessState</i>	(Optional) Session state
<i>ciscoBfdSessRemoteHeardFlag</i>	(Optional)
<i>ciscoBfdSessDiag</i>	(Optional) Session diagnostic code
<i>remoteBfdSessDiag</i>	(Optional) Session diagnostic code
<i>ciscoBfdSessOperMode</i>	(Optional) ciscoBfdSessOperMode
<i>ciscoBfdSessDemandModeDesiredFlag</i>	(Optional)
<i>ciscoBfdSessEchoFuncModeDesiredFlag</i>	(Optional)
<i>ciscoBfdSessControlPlanIndepFlag</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional) ciscoBfdSessAddrType
<i>localBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessDesiredMinTxInterval</i>	(Optional)
<i>ciscoBfdSessReqMinRxInterval</i>	(Optional)
<i>ciscoBfdSessReqMinEchoRxInterval</i>	(Optional)
<i>ciscoBfdSessDetectMult</i>	(Optional)
<i>remoteBfdSessDesiredMinTxInterval</i>	(Optional)
<i>remoteBfdSessReqMinRxInterval</i>	(Optional)
<i>remoteBfdSessReqMinEchoRxInterval</i>	(Optional)
<i>remoteBfdSessDetectMult</i>	(Optional)

<i>ciscoBfdSessStorType</i>	(Optional) ciscoBfdSessStorType
<i>ciscoBfdSessRowStatus</i>	(Optional)
<i>ciscoBfdSessAuthPresFlag</i>	(Optional)
<i>ciscoBfdSessAuthenticationType</i>	(Optional) ciscoBfdSessAuthenticationType
<i>ciscoBfdSessVersionNumber</i>	(Optional)
<i>ciscoBfdSessType</i>	(Optional) ciscoBfdSessType
<i>ciscoBfdSessInterface</i>	(Optional)
<i>ciscoBfdSessPerfPktIn</i>	(Optional)
<i>ciscoBfdSessPerfPktOut</i>	(Optional)
<i>ciscoBfdSessUpTime</i>	(Optional)
<i>ciscoBfdSessPerfLastSessDownTime</i>	(Optional)
<i>ciscoBfdSessPerfLastCommLostDiag</i>	(Optional)
<i>ciscoBfdSessPerfSessUpCount</i>	(Optional)
<i>ciscoBfdSessPerfDiscTime</i>	(Optional)
<i>ciscoBfdSessPerfPktInHC</i>	(Optional)
<i>ciscoBfdSessPerfPktOutHC</i>	(Optional)
<i>effasyncdt</i>	(Optional)
<i>effechodt</i>	(Optional)

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ipv4 { unicast |
multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4
mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast } nexthop <ipnexthop>
| { ipv6 { unicast | multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] |
ipv6 labeled-unicast | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } nexthop
<ipv6nexthop> } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ _readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> }
<ipnexthop> | <ipv6nexthop> } { { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath>
<origin> [ <metric> ] [ <localpref> ] } } } | { [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabelednrh> ] [ <importsource>
[ <originalimportsource> ] ] [ <importdestscount> ] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> |
<ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ]
<localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalf-life> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid>
] [ <psid_origsr-gb_len> <psid_origsr-gb_flag> <psid_origsr-gb_base> <psid_origsr-gb_end> ] ] [ <remoten-h>
<remoten-h_encap> <remoten-h_vnid> <remoten-h_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr>
<link-state-attr-len> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop	Display routes matching the nexthop
<i>ipnexthop</i>	Nexthop address

ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
evpn	Display BGP information for L2VPN EVPN address family
mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)

<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_ <i>advertisedto</i>	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_ <i>scheduledto</i>	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_ <i>path</i>	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)

<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)

<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)

<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } policy statistics { { redistribute [ { { eigrp | isis | ospf | rip } <tag> } | static | direct | amt | lisp |
hmm | am ] } | { neighbor <neighbor-id> [ default-originate | { route-map | filter-list | prefix-list } { in | out }
] } | { dampening } | { network { <ip-addr> mask <ip-mask> | <ip-prefix> } } | { aggregate-address { <ip-addr>
<ip-mask> | <ip-prefix> } { suppress-map | advertise-map } } } | vpnv4 unicast policy statistics { neighbor
<neighbor-id> [ { route-map | filter-list | prefix-list } { in | out } ] } | ipv6 { unicast | multicast } policy statistics
{ { redistribute [ { { eigrp | isis | ospfv3 | rip } <tag> } | static | direct | amt | lisp | hmm | am ] } | { neighbor
{ <neighbor-id> | <ipv6-neighbor-id> } [ default-originate | { route-map | filter-list | prefix-list } { in | out }
] } | { dampening } | { network <ipv6-prefix> } | { aggregate-address <ipv6-prefix> { suppress-map |
advertise-map } } } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-polstats> [ <rpm-handle-count> ] [ { TABLE_rmap <name> <action>
<seqnum> [ { TABLE_cmd <command> <comparecount> <matchcount> } ] [ <totalacceptcount> ] [
<totalrejectcount> ] } ] ] ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
policy	Display policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	(Optional) ISO IS-IS
ospf	(Optional) Open Shortest Path First
ospfv3	(Optional) Open Shortest Path First v3
rip	(Optional) Routing Information Protocol
eigrp	(Optional) Enhanced Interior Gateway Protocol

static	(Optional) Static routes
direct	(Optional) Directly connected
amt	(Optional) AMT anycast prefix
lisp	(Optional) LISP EID-prefixes in the non-default VRF
hmm	(Optional) HMM prefix
am	(Optional) AM routes (learned via ARP)
<i>tag</i>	(Optional) Source protocol tag
neighbor	Show neighbor specific counters
<i>neighbor-id</i>	Neighbor IPv4 address
route-map	(Optional) Neighbor route-map
prefix-list	(Optional) Neighbor prefix-list
filter-list	(Optional) Neighbor filter-list
out	(Optional) Outbound policy
in	(Optional) Inbound policy
default-originate	(Optional) Default-originate policy
dampening	Show dampening info
network	Configured IP prefix to advertise
mask	Configured mask of the IP prefix advertised
aggregate-address	Configured BGP aggregate prefixes
suppress-map	Statistics of suppress policy
advertise-map	Statistics of advertise policy
<i>ip-addr</i>	IP network advertised
<i>ip-mask</i>	Dotted 4-octet mask
<i>ip-prefix</i>	IP prefix in CIDR format
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-polstats</i>	(Optional)
<i>rpm-handle-count</i>	(Optional)
TABLE_rmap	(Optional)

<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seqnum</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>comparecount</i>	(Optional)
<i>matchcount</i>	(Optional)
<i>totalacceptcount</i>	(Optional)
<i>totalrejectcount</i>	(Optional)

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ipv4 { unicast |
multicast } | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast
} [ <ip-addr> [ <ip-mask> [ longer-prefixes ] ] [ detail ] | <ip-prefix> [ longer-prefixes ] [ detail ] | labels |
exported | imported | detail ] } | ipv6 { unicast | multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast } [ <ipv6-prefix> [ longer-prefixes ] [ detail ] | labels |
exported | imported | detail ] } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } [
<ip-addr> [ <ip-mask> ] | <ip-prefix> | labels | mdt-group <mdt-group> ] | { ipv4 | ipv6 } unicast [
injected-routes ] | link-state [ route-type <rt-type> | <ipv4-ls-rt> | <ipv6-ls-rt> ] | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ { <ip-addr> [ <ip-mask> ] | <ip-prefix> } ] | { ve-id
<ve-id> block-offset <ve-bs> } ] ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [
join <v4src-addr> <v4grp-addr> <src-asn> | rp <v4src-addr> <grp-v4prefix> <pe-addr> <rp-flags> <rp-priority>
<hashlen> | sa <grp-v4prefix> | sa-ad <v4src-addr> <v4grp-addr> | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail
] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] | join [ detail ] | sa-ad [ detail ] | i-pmsi [ detail ] ] | ipv6 mvpn
[ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v6src-addr> <v6grp-addr> <src-asn> | rp
<v6src-addr> <grp-v6prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v6prefix> | sa-ad
<v6src-addr> <v6grp-addr> | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7
} [ detail ] | join [ detail ] | sa-ad [ detail ] | i-pmsi [ detail ] ] | l2vpn evpn [ route-type <rtype> [ etid <et> ] |
rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ route-type <rtype> [ etid <et> ] | <ipv4-evpn-rt> |
<ipv6-evpn-rt> | <mac-address> ] | vni-id <vni_id> [ route-type <rtype> ] | es <es-id> [ route-type <rtype> [
etid <et> ] ] | <ipv4-evpn-rt> | <ipv6-evpn-rt> | <mac-address> ] | all [ detail ] ] [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } ] [ <prefixversion>
<totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [
<export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path
<pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop>
} } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref>
] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory>
<pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <importsource> [ <originalimportsource> ]
] [ <importdestscount> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop> }
<nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community
<community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist
<clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife>
<flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [
<psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context

<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ip-addr</i>	(Optional) Display one particular network from the BRIB in detail
<i>ip-mask</i>	(Optional) Mask for one particular prefix in the BRIB
<i>ip-prefix</i>	(Optional) Display one particular prefix from the BRIB in detail
longer-prefixes	(Optional) Display route and more specific routes
labels	(Optional) Display BGP labels for prefixes
exported	(Optional) Display only exported prefixes
imported	(Optional) Display only imported prefixes
injected-routes	(Optional) Display only injected prefixes
mdt-group	(Optional) Display prefixes with MDT group address
<i>mdt-group</i>	(Optional) MDT group address
rd	(Optional) Display information for a route distinguisher
ve-id	(Optional) VPLS VE ID
<i>ve-id</i>	(Optional) VPLS VE ID
route-type	(Optional) EVPN Route Type number
<i>rtype</i>	(Optional) EVPN route type number
1	(Optional) Inter-AS PMSI AD
2	(Optional) Intra-AS PMSI AD
3	(Optional) SPMSI AD
4	(Optional) LEAF AD
5	(Optional) Source-Active AD
6	(Optional) Shared C-Multicast
7	(Optional) Source C-Multicast
vni-id	(Optional) EVPN VNI ID number
<i>vni_id</i>	(Optional) EVPN VNI ID number
<i>rt-type</i>	(Optional) Link-State route-type
es	(Optional) Ethernet Segment
<i>es-id</i>	(Optional) ESID

<i>etid</i>	(Optional) Ethernet Tag-ID for L2VPN EVPN route
<i>et</i>	(Optional) Ethernet Tag-ID
<i>ipv4-evpn-rt</i>	(Optional) EVPN IPv4 address
<i>ipv4-ls-rt</i>	(Optional) Link-State NLRI with descriptor including IPv4 address
<i>mac-address</i>	(Optional) MAC address
<i>block-offset</i>	(Optional) VPLS VE Block offset
<i>ve-bs</i>	(Optional) VPLS VE Block offset
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
<i>ipv4</i>	Display BGP information for IPv4 address family
<i>vpn4</i>	Display BGP information for VPNv4 address family
<i>vpn6</i>	Display BGP information for VPNv6 address family
<i>ipv6</i>	Display BGP information for IPv6 address family
<i>unicast</i>	Display BGP information for unicast address family
<i>multicast</i>	Display BGP information for multicast address family
<i>mdt</i>	Display BGP information for multicast distribution tree
<i>link-state</i>	Display BGP information for link-state address family
<i>l2vpn</i>	Display BGP information for L2VPN address family
<i>vpls</i>	Display BGP information for L2VPN VPLS address family
<i>labeled-unicast</i>	Display BGP information for labeled-unicast address family
<i>mvpn</i>	Display BGP information for MVPN address family
<i>evpn</i>	Display BGP information for L2VPN EVPN address family
<i>all</i>	Display BGP information for all address families
<i>join</i>	(Optional) Display Multicast Join route
<i>detail</i>	(Optional) Display detailed path info for routes
<i>sa</i>	(Optional) Display Multicast Source Active AD route
<i>sa-ad</i>	(Optional) Display Multicast Source Active AD route
<i>i-pmsi</i>	(Optional) Display Multicast Intra-AS I-PMSI route
<i>rp</i>	(Optional) Display Multicast Group to RP route

<i>v4src-addr</i>	(Optional) Source IP Address
<i>src-asn</i>	(Optional) Source ASN
<i>v4grp-addr</i>	(Optional) Group IP Address
<i>grp-v4prefix</i>	(Optional) Group IP prefix
<i>pe-addr</i>	(Optional) PE IP Address
<i>rp-flags</i>	(Optional) Flags
<i>rp-priority</i>	(Optional) RP Priority
<i>hashlen</i>	(Optional) Hash mask length
<i>l</i>	(Optional) vrf
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)

TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)

<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)

<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)

<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

## show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } { route-map {
<rmap-name> | <rmap-name> } | filter-list { <fltrlist-name> | <test_pol_name> } | community-list {
<commlist-name> | <test_pol_name> } | extcommunity-list { <extcommlist-name> | <test_pol_name> } } [
exact-match ] ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> {
<ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel> <vpn> <hold_down> } } { <weight> <aspath>
<origin> [ <metric> ] [ <localpref> ] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <importsourc>
[ <originalimportsourc> ] ] [ <importdestscout> ] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> |
<ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ]
<localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalflife> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid>
] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh>
<remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr>
<link-state-attr-len> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
route-map	Display routes matching the route-map
<i>rmap-name</i>	Route-map name
<i>rmap-name</i>	Known route-map name
filter-list	Display routes matching the filter-list

<i>fltrlist-name</i>	Name of filter-list
community-list	Display routes matching the community-list
<i>commlist-name</i>	Name of community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>extcommlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
exact-match	(Optional) Exact match of the communities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)

TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)

TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)

<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalf-life</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)

<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } { rib-install | rib-uninstall | rib-pending } [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
rib-install	Routes installed in RIB
rib-uninstall	Routes not installed in RIB
rib-pending	Routes not acknowledged by RIB

## Command Mode

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { { ipv4 { unicast
| multicast } | vpnv4 unicast | ipv4 mdt | link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn } nexthop-database
[ <ipnexthop> ] } | { { ipv6 { unicast | multicast } | vpnv6 unicast | ipv6 mvpn } nexthop-database [
<ipv6nexthop> ] } | { all nexthop-database } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_nhvrfrf <nhvrfrf-name-out> TABLE_nhafi <nhafi>
TABLE_nhsafi <nhsafi> <af-name> <nhcriticaldelay> <nhnnoncriticaldelay> [ { TABLE_nexthop {
<ipnexthop-out> | <ipv6nexthop-out> } <refcount> <igpmetric> <igptype> <igppref> [ { TABLE_attachedhops
{ <attachedhop> | <ipv6attachedhop> } <interface> [ { TABLE_labels <index> <label> } ] } ] <attached>
<local> <reachable> <labeled> <filtered> <resolvetime> { <ribroute> | <ipv6ribroute> } { <pendingupdate>
| <pendingtime> } <nextadvertise> <rnhepoch> [ <pendingrnhepoch> ] } ] ] ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
nexthop-database	Display nexthop database
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
mdt	Display BGP information for multicast distribution tree
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
<i>ipnexthop</i>	(Optional) Nexthop address

<code>__readonly__</code>	(Optional)
<code>TABLE_nhvr</code>	(Optional)
<code>nhvr-name-out</code>	(Optional)
<code>TABLE_nhafi</code>	(Optional)
<code>nhafi</code>	(Optional)
<code>TABLE_nhsafi</code>	(Optional)
<code>nhsafi</code>	(Optional)
<code>af-name</code>	(Optional)
<code>nhcriticaldelay</code>	(Optional)
<code>nhnoncriticaldelay</code>	(Optional)
<code>TABLE_nexthop</code>	(Optional)
<code>ipnexthop-out</code>	(Optional)
<code>refcount</code>	(Optional)
<code>igpmetric</code>	(Optional)
<code>igptype</code>	(Optional)
<code>igppref</code>	(Optional)
<code>TABLE_attachedhops</code>	(Optional)
<code>attachedhop</code>	(Optional)
<code>interface</code>	(Optional)
<code>TABLE_labels</code>	(Optional)
<code>index</code>	(Optional)
<code>label</code>	(Optional)
<code>attached</code>	(Optional)
<code>local</code>	(Optional)
<code>reachable</code>	(Optional)
<code>labeled</code>	(Optional)
<code>filtered</code>	(Optional)
<code>resolvetime</code>	(Optional)
<code>pendingupdate</code>	(Optional)

<i>pendingtime</i>	(Optional)
<i>ribroute</i>	(Optional)
<i>nextadvertise</i>	(Optional)
<i>rnhepoch</i>	(Optional)
<i>pendingrnhepoch</i>	(Optional)

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] | ipv6 { unicast | multicast } flap-statistics
[ <ipv6-prefix> ] | all flap-statistics } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234
} ] [ __readonly__ TABLE_vrf <vrf-name-out> [ TABLE_afi <afi> TABLE_safi <safi> <af-name> [
TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ <dampening> <historypaths> <dampenedpaths> ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <status> ] [ <pathtype> ] [ <peer> | <ipv6peer>
] [ <flapcount> ] [ <duration> ] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [ <best> ] ] ] ]
]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
<i>ip-prefix</i>	(Optional) Display flap statistics for one prefix
<i>ip-addr</i>	(Optional) Display flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)

<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

**Command Mode**

- /exec



<i>refresh_interval</i>	(Optional) refresh delay for bmp server
<i>stats_interval</i>	(Optional) frequency of stat updates
<i>initiation</i>	(Optional) number of initiation messages
<i>termination</i>	(Optional) number of termination messages
<i>peer_up</i>	(Optional) number of peer up messages
<i>peer_down</i>	(Optional) number of peer down messages
<i>route_monitor</i>	(Optional) number of route monitor messages
<i>route_mirror</i>	(Optional) number of route mirror messages
<i>stats</i>	(Optional) number of stats messages
<i>messages_dropped</i>	(Optional) number of dropped messages
<i>monitored_peers</i>	(Optional) number of monitored peers for the bmp server
TABLE_peer	(Optional) monitored peer for the bmp server
<i>peer_addr</i>	(Optional) ip address of the peer
<i>refresh_interval</i>	(Optional) refresh delay for the peer
<i>peer_up</i>	(Optional) number of peer up messages for the peer
<i>peer_down</i>	(Optional) number of peer down messages for the peer
<i>route_monitor</i>	(Optional) number of route monitor messages for the peer
<i>route_mirror</i>	(Optional) number of route mirror messages for the peer
<i>stats</i>	(Optional) number of stats messages for the peer
<i>messages_dropped</i>	(Optional) number of dropped messages for the peer
<i>prefixes_denied</i>	(Optional) prefixes denied for the peer
<i>dup_pfx_advmnt</i>	(Optional) dup pfx advmnt for the peer
<i>pfx_dup_wdr_count</i>	(Optional) pfx dup wdr count for the peer
<i>cluster_list_loops</i>	(Optional) cluster list loops for the peer
<i>as_path_loops</i>	(Optional) as path loops for the peer
<i>as_confed_loops</i>	(Optional) as confed loops for the peer
<i>invalid_originator</i>	(Optional) invalid originator for the peer
<i>adj_rib_in</i>	(Optional) adj-rib-in for the peer
<i>loc-rib</i>	(Optional) loc-rib for the peer

**Command Mode**

- /exec

## show bgp community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } community {
<regexp-str> | { <comm-id> | <wellknown-id> } + [ exact-match ] } [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths>
<bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel>
<vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] } } } | { [
<policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabelednrh> ] [ <importsource> [ <originalimportsource> ] ] [ <importdestscount>
] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> |
<ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> } } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family

vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
community	Display routes matching the BGP communities
<i>regexp-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)

<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)

<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)

<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)

<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec



<i>updatedelay</i>	(Optional)
<i>firstpeerup</i>	(Optional)
<i>timerrunning</i>	(Optional)
<i>timerexpires</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>firstbestpathsignalled</i>	(Optional)
<i>firstbestpathsignalledtime</i>	(Optional)
<i>firstbestpathdone</i>	(Optional)
<i>firstbestpathdonetime</i>	(Optional)
<i>lastbestpathsignalledtime</i>	(Optional)
<i>lastbestpathdonetime</i>	(Optional)
<i>ribbibconvergencesent</i>	(Optional)
<i>importtimerrunning</i>	(Optional)
<i>importtimerexpires</i>	(Optional)
TABLE_rcvdpeers	(Optional)
<i>peer</i>	(Optional)
<i>signalledtimepeer</i>	(Optional)
TABLE_notrcvdpeers	(Optional)
<i>notpeer</i>	(Optional)
<i>nokeepalive</i>	(Optional)
<i>notsignalledtime</i>	(Optional)

**Command Mode**

- /exec

# show bgp convergence private

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] convergence private  
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
convergence	Display information about convergence
private	Display private information about convergence

## Command Mode

- /exec

## show bgp dampening dampened

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening {
dampened-paths [ regexp <regexp-str> ] | history-paths [ regexp <regexp-str> ] } [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ _readonly_ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } ] [ <prefixversion>
<totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [
<export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path
<pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop>
} { { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref>
] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory>
<pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <importsource> [ <originalimportsource> ]
] [ <importdestscount> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop> }
<nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community
<community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist
<clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife>
<flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [
<psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmssi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampened-paths	Display all dampened paths
history-paths	Display all history paths
dampening	Display dampening info
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format

<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)

<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)

<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)

<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)

<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec



<code>l2vpn</code>	Display BGP information for L2VPN address family
<code>vpls</code>	Display BGP information for L2VPN VPLS address family
<code>mvpn</code>	Display BGP information for MVPN address family
<code>evpn</code>	Display BGP information for L2VPN EVPN address family
<code>all</code>	Display BGP information for all address families
<code>__readonly__</code>	(Optional)
<code>TABLE_vrf</code>	(Optional)
<code>vrf-name-out</code>	(Optional)
<code>TABLE_afi</code>	(Optional)
<code>afi</code>	(Optional)
<code>TABLE_safi</code>	(Optional)
<code>safi</code>	(Optional)
<code>af-name</code>	(Optional)
<code>TABLE_rd</code>	(Optional)
<code>rd_val</code>	(Optional)
<code>rd_vrf</code>	(Optional)
<code>rd_vniid</code>	(Optional)
<code>dampening</code>	(Optional)
<code>historypaths</code>	(Optional)
<code>dampenedpaths</code>	(Optional)
<code>TABLE_prefix</code>	(Optional)
<code>ipprefix</code>	(Optional)
<code>nonipprefix</code>	(Optional)
<code>status</code>	(Optional)
<code>best</code>	(Optional)
<code>pathtype</code>	(Optional)
<code>peer</code>	(Optional)
<code>flapcount</code>	(Optional)
<code>duration</code>	(Optional)

<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

**Command Mode**

- /exec

## show bgp dampening parameters

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening
parameters [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> ] [
<rd_vrf> ] [ <rd_vniid> ] [ <rpmname> ] [ TABLE_rpm <rpmindex> <rpmdamphalflife> <rpm dampsuppress>
<rpm dampreuse> <rpm dampsuppress> <rpm dampmaxpenalty> ] [ <dampconfigured> <damp halflife>
<damp suppress> <damp reuse> <damp suppress> <damp maxpenalty> ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
parameters	Display dampening parameters
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpv4	Display BGP information for VPNv4 address family
vpv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family

l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional) VRF RD
<i>rd_vniid</i>	(Optional)
TABLE_rpm	(Optional)
<i>rpmname</i>	(Optional)
<i>rpmindex</i>	(Optional)
<i>rpmdamphalflife</i>	(Optional)
<i>rpmdampsuppress</i>	(Optional)
<i>rpmdampreuse</i>	(Optional)
<i>rpmdampsuppresstime</i>	(Optional)
<i>rpmdampmaxpenalty</i>	(Optional)
<i>dampconfigured</i>	(Optional)
<i>damphalflife</i>	(Optional)
<i>dampsuppress</i>	(Optional)
<i>dampreuse</i>	(Optional)

<i>dampsuppresstime</i>	(Optional)
<i>dampmaxpenalty</i>	(Optional)

**Command Mode**

- /exec

## show bgp default-info

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } default-info [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
default-info	Display information about default routes
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families

### Command Mode

- /exec

# show bgp event-history

```
show bgp [ internal ] event-history { <bgp-event-hist> | events | errors | msgs | detail | periodic | objstore |
developer }
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
internal	(Optional) Commands for internal use
event-history	Show various event logs of BGP
<i>bgp-event-hist</i>	Show BGP event log
detail	Show detailed event logs
events	Show event logs of BGP
errors	Show error logs of BGP
msgs	Show various message logs of BGP
objstore	Show objstore logs of BGP
developer	Show developer logs of BGP
periodic	Show periodic logs of BGP

## Command Mode

- /exec

## show bgp extcommunity

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } extcommunity
{ <regex-str> | { { 4byteas-generic { transitive <ext-comm-gen-trans> | non-transitive
<ext-comm-gen-nontrans> } } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [
<on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel>
<vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] } } } | { {
<policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabeledrn> ] [ <importsourc> [ <originalimportsourc> ] ] [ <importdestscount>
] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> |
<ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmssi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family

ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
labeled-unicast	Display BGP information for labeled-unicast address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
<i>regexp-str</i>	Regular expression to match the extcommunities
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)

<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)

<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)

<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

### Command Mode

- /exec

## show bgp l3vpn

```
show bgp l3vpn [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-rd> ] [ <vrf-state> ] [ <vrf-state-rsn> ] [
<vrf-pending-rd> ] [ { TABLE_af <af-id> [ <af-name> ] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [
<af-num-peers> ] [ <af-num-active-peers> ] [ <af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ]
[ <af-peer-aggregates> ] [ <af-export-rmap> ] [ <af-import-rmap> ] [ <af-retain-rt> ] [ TABLE_export_rt
<export-rt> ] [ TABLE_import_rt <import-rt> ] [ TABLE_evpn_export_rt <evpn-export-rt> ] [
TABLE_evpn_import_rt <evpn-import-rt> ] [ TABLE_mvpn_export_rt <mvpn-export-rt> ] [
TABLE_mvpn_import_rt <mvpn-import-rt> ] [ <af-label-mode> ] [ <af-aggregate-label> ] } ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
l3vpn	BGP l3vpn information
vrf	(Optional) Virtual Router Context
detail	(Optional) Detailed information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason

<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route-target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route-target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route-target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route-target
TABLE_mvpn_export_rt	(Optional)
<i>mvpn-export-rt</i>	(Optional) Export MVPN route-target
TABLE_mvpn_import_rt	(Optional)
<i>mvpn-import-rt</i>	(Optional) Import MVPN route-target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label

**Command Mode**

- /exec

## show bgp neighbors

```
show bgp { { vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } } { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast |
link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn | ipv6 mvpn | ipv4 labeled-unicast } neighbors [ { <neighbor-id>
| <ipv6-neighbor-id> | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id> } ] [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ TABLE_neighbor { <neighbor>
| <ipv6neighbor> | <templatepeer> | <ipv4prefixneighbor> | <ipv6prefixneighbor> } ] [ <remoteas> ] [ <localas>
] [ <link> ] [ <peertype> ] [ <index> ] [ TABLE_peer <peer> ] [ <maxprefixpeers> ] [ <configpeer> ] [
<inherit-template> ] [ <inherit-session-template> ] [ { <prefix-parent> | <ipv6prefix-parent> } ] [ <description>
] [ <version> <remote-id> <state> <up> [ <elapsedtime> ] [ <restarttime> ] ] [ <sourcecif> ] [ <connectedif>
] [ <connectedcheck> ] [ <lowmemexempt> ] [ <bfd> ] [ <ttlsecurity> ] [ <ttllimit> ] [ <password> ] [
<passiveonly> ] [ <activepeers> <closingpeers> <maxconcurrentpeers> ] [ <allocatedpeers> ] [
<totalpeersaccepted> ] [ <localas-inactive> ] <remove-privateas> { { [ <lastread> ] <holdtime> <keepalivetime>
[ <lastwrite> ] [ <keepalive> ] <msgrecvd> <notificationsrcvd> <rcvbufbytesinq> <msgsent>
<notificationssent> <sentbytesoutstanding> <sentbytespacked> <connsestablished> <connsdropped> [
<connattempts> ] } { [ <peerresettime> ] <peerresetreason> [ <resettime> ] <resetreason> } } [ <resetime>
] <resetreason> [ <peerresettime> ] <peerresetreason> } } [ <capsnegotiated> <capmpadvertised> [
<caprefreshadvertised> <capgrdynamicadvertised> ] [ <capmprecvd> <caprefreshrecvd> <capgrdynamicrecvd>
] [ <capolddynamicadvertised> <capolddynamicrecvd> <caprradvertised> <caprrrecvd> <capoldrradvertised>
<capoldrrrecvd> <capas4advertised> <capas4recvd> ] [ { TABLE_af <af-afi> TABLE_saf <af-safi>
<af-advertised> <af-recvd> <af-name> } ] [ <capgradvertised> <capgrrecvd> ] [ { TABLE_graf <gr-afi>
TABLE_grsaf <gr-safi> <gr-af-name> <gr-adv> <gr-recv> <gr-fwd> } ] [ <grrestarttime> <grstaletime> ] [
<grrecvrestarttime> ] [ [ { TABLE_addpathscapaf <addpathscap-afi> TABLE_addpathscapsaf
<addpathscap-safi> <addpathscap-af-name> <addpathssendcap-adv> <addpathsrecvcap-adv>
<addpathssendcap-recv> <addpathsrecvcap-recv> } ] [ <capaddpathsadvertised> <capaddpathsrecvd> ] ] [
<capextendednhadvertised> <capextendednhrecvd> ] [ { TABLE_capextendednhaf <capextendednh-afi>
TABLE_capextendednhsaf <capextendednh-safi> <capextendednh-af-name> } ] ] } [ <configholdtime>
<configkeepalivetime> ] } ] [ <epe> ] [ <epe-adj-sids> ] [ <epe-peer-rpc-set> ] [ <epe-peer-sid> ] [
<epe-peer-set-name> ] [ <epe-peer-set-rpc-set> ] [ <epe-peer-set-sid> ] [ { TABLE_epe-adj { {
<epe-adj-ip-local> <epe-adj-ip-remote> } | { <epe-adj-ipv6-local> <epe-adj-ipv6-remote> } } ] [
<epe-adj-ifindex> <epe-adj-rpc-set> <epe-adj-sid> } ] [ <grstate> <grexpiry> ] [ <firstkeepalive> ] [
<openssent> <opensrecvd> <updatesent> <updatesrecvd> <keepalivesent> <keepaliverecvd> <rtrefreshsent>
<rtrefreshrecvd> <capabilitiesent> <capabilitiesrecvd> <bytesent> <bytesrecvd> ] [ TABLE_peraf <per-afi>
TABLE_persaf <per-safi> <per-af-name> [ <tableversion> ] [ <neighborstableversion> ] [ <pfxcrcvd> ] [
<pfxbytes> ] [ <pfxsent> ] [ <conditionmap> <advertisemap> <advertisemapstatus> ] [ <insoftreconfigallowed>
[ <insoftreconfigallowedalways> ] [ <sendcommunity> ] [ <sendextcommunity> ] [ { <localnexthop> |
<ipv6localnexthop> } ] [ <thirdpartynexthop> ] [ <maxpfx> ] [ <maxpfx_threshold> ] [ <soo> ] [ <weight>
] [ <allowasin> ] <asoverride> <peerascheckdisabled> [ <vplsissignalingprotocol> ] [ { TABLE_inpolicy
<inpolicynr> <inpolicytype> <inpolicyname> [ <inpolicyhandle> } } ] [ { TABLE_outpolicy <outpolicynr>
<outpolicytype> <outpolicyname> [ <outpolicyhandle> } } ] <rrconfigured> <defaultoriginate> [
<defaultoriginatormap> ] [ <defaultsent> ] [ <grpathsaved> ] [ <firsteorrecvd> ] [ <firsteortime> ] [
<pathsflushed> ] [ <lasteorrecvtime> ] [ <lasteorsenttime> ] [ <firstconvgtime> ] [ <pfxsentfirsteor> ] [
<unsuppress-map> ] [ { TABLE_policy_template <preference> <inherit-policy-template> } } ] [ [ <threadid>
] [ <passivethreadid> <passivefd> ] [ { <localaddr> | <ipv6localaddr> } <localport> { <remoteaddr> |
<ipv6remoteaddr> } <remoteport> <fd> } ] ] ] ]
```

### Syntax Description

show	Show running system information
------	---------------------------------

bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	(Optional) Display details for a prefix peering
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
<i>__readonly__</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor</i>	(Optional)
<i>templatepeer</i>	(Optional)
<i>ipv4prefixneighbor</i>	(Optional)
<i>remoteas</i>	(Optional)
<i>localas</i>	(Optional)
<i>link</i>	(Optional)
<i>index</i>	(Optional)

TABLE_peer	(Optional)
<i>peer</i>	(Optional)
<i>maxprefixpeers</i>	(Optional)
<i>configpeer</i>	(Optional)
<i>inherit-template</i>	(Optional)
<i>inherit-session-template</i>	(Optional)
<i>prefix-parent</i>	(Optional)
<i>description</i>	(Optional)
<i>version</i>	(Optional)
<i>remote-id</i>	(Optional)
<i>state</i>	(Optional)
<i>up</i>	(Optional)
<i>elapsedtime</i>	(Optional)
<i>restarttime</i>	(Optional)
<i>peertype</i>	(Optional)
<i>sourceif</i>	(Optional)
<i>connectedif</i>	(Optional)
<i>connectedcheck</i>	(Optional)
<i>lowmemexempt</i>	(Optional)
<i>bfd</i>	(Optional)
<i>ttlsecurity</i>	(Optional)
<i>tllimit</i>	(Optional)
<i>localas-inactive</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>activepeers</i>	(Optional)
<i>closingpeers</i>	(Optional)
<i>maxconcurrentpeers</i>	(Optional)
<i>allocatedpeers</i>	(Optional)
<i>totalpeersaccepted</i>	(Optional)

<i>password</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>lastread</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalivetime</i>	(Optional)
<i>lastwrite</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>notificationsrcvd</i>	(Optional)
<i>rcvbufbytesinq</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>notificationssent</i>	(Optional)
<i>sentbytesoutstanding</i>	(Optional)
<i>sentbytespacked</i>	(Optional)
<i>connsestablished</i>	(Optional)
<i>connsdropped</i>	(Optional)
<i>connattempts</i>	(Optional)
<i>peerresetime</i>	(Optional)
<i>peerresetreason</i>	(Optional)
<i>resetime</i>	(Optional)
<i>resetreason</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
<i>grstate</i>	(Optional)
<i>gexpiry</i>	(Optional)
<i>firstkeepalive</i>	(Optional)
<i>epe</i>	(Optional)
<i>epe-adj-sids</i>	(Optional)
<i>epe-peer-rpc-set</i>	(Optional)

<i>epe-peer-sid</i>	(Optional)
<i>epe-peer-set-name</i>	(Optional)
<i>epe-peer-set-rpc-set</i>	(Optional)
<i>epe-peer-set-sid</i>	(Optional)
TABLE_ <i>epe-adj</i>	(Optional)
<i>epe-adj-ip-local</i>	(Optional)
<i>epe-adj-ip-remote</i>	(Optional)
<i>epe-adj-ifindex</i>	(Optional)
<i>epe-adj-rpc-set</i>	(Optional)
<i>epe-adj-sid</i>	(Optional)
<i>openssent</i>	(Optional)
<i>opensrecvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updatesrecvd</i>	(Optional)
<i>keepalivesent</i>	(Optional)
<i>keepaliverecvd</i>	(Optional)
<i>rtrefreshsent</i>	(Optional)
<i>rtrefreshrecvd</i>	(Optional)
<i>capabilitiesent</i>	(Optional)
<i>capabilitiesrecvd</i>	(Optional)
<i>bytessent</i>	(Optional)
<i>bytesrecvd</i>	(Optional)
<i>threadid</i>	(Optional)
<i>fd</i>	(Optional)
<i>passivethreadid</i>	(Optional)
<i>passivefd</i>	(Optional)
<i>localaddr</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteaddr</i>	(Optional)

<i>remoteport</i>	(Optional)
<i>capsnegotiated</i>	(Optional)
<i>capmpadvertised</i>	(Optional)
<i>capgrdynamicadvertised</i>	(Optional)
<i>capaddpathsadvertised</i>	(Optional)
<i>caprefreshadvertised</i>	(Optional)
<i>capmprecvd</i>	(Optional)
<i>capgrdynamicrecvd</i>	(Optional)
<i>capaddpathsrecvd</i>	(Optional)
<i>caprefreshrecvd</i>	(Optional)
<i>capolddynamicadvertised</i>	(Optional)
<i>capolddynamicrecvd</i>	(Optional)
<i>caprradvertised</i>	(Optional)
<i>caprrrecvd</i>	(Optional)
<i>capoldrradvertised</i>	(Optional)
<i>capoldrrrecvd</i>	(Optional)
<i>capas4advertised</i>	(Optional)
<i>capas4recvd</i>	(Optional)
TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-advertised</i>	(Optional)
<i>af-recvd</i>	(Optional)
<i>af-name</i>	(Optional)
<i>capgradvertised</i>	(Optional)
<i>capgrrecvd</i>	(Optional)
TABLE_graf	(Optional)
<i>gr-afi</i>	(Optional)

TABLE_grsaf	(Optional)
<i>gr-safi</i>	(Optional)
<i>gr-af-name</i>	(Optional)
<i>gr-adv</i>	(Optional)
<i>gr-recv</i>	(Optional)
<i>gr-fwd</i>	(Optional)
<i>grrestarttime</i>	(Optional)
<i>grstaletime</i>	(Optional)
<i>grrecvdrestarttime</i>	(Optional)
TABLE_addpathscapaf	(Optional)
<i>addpathscap-afi</i>	(Optional)
TABLE_addpathscapsaf	(Optional)
<i>addpathscap-safi</i>	(Optional)
<i>addpathscap-af-name</i>	(Optional)
<i>addpathssendcap-adv</i>	(Optional)
<i>addpathsrecvcap-adv</i>	(Optional)
<i>addpathssendcap-recv</i>	(Optional)
<i>addpathsrecvcap-recv</i>	(Optional)
<i>capextendednhadvertised</i>	(Optional)
<i>capextendednhrecvd</i>	(Optional)
TABLE_capextendednhaf	(Optional)
<i>capextendednh-afi</i>	(Optional)
TABLE_capextendednhsaf	(Optional)
<i>capextendednh-safi</i>	(Optional)
<i>capextendednh-af-name</i>	(Optional)
TABLE_peraf	(Optional)
<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)

<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pxrcvd</i>	(Optional)
<i>pxbytes</i>	(Optional)
<i>pxsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)
<i>maxpx</i>	(Optional)
<i>maxpx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
TABLE_inpolicy	(Optional)
<i>inpolicynr</i>	(Optional)
<i>inpolicytype</i>	(Optional)
<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
TABLE_outpolicy	(Optional)
<i>outpolicynr</i>	(Optional)
<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)
<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatermap</i>	(Optional)

<i>defaultsent</i>	(Optional)
<i>grpathssaved</i>	(Optional)
<i>firsteorrecvd</i>	(Optional)
<i>firsteortime</i>	(Optional)
<i>pathsflushed</i>	(Optional)
<i>lasteorrecvtime</i>	(Optional)
<i>lasteorsenttime</i>	(Optional)
<i>firstconvgttime</i>	(Optional)
<i>pxsentfirsteor</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)
<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vpls signalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)

**Command Mode**

- /exec

## show bgp neighbors

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] } { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv4 labeled-unicast | ipv4
labeled-unicast | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } { routes [ advertised | received
| dampened ] | advertised-routes | received-routes } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [
<on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { { <inlabel> <outlabel>
<vpn> <hold_down> } } { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] } } } | { [
<policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabelednrh> ] [ <importsource> [ <originalimportsource> ] ] [ <importdstscount>
] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> |
<ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> } } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
labeled-unicast	Display BGP information for labeled-unicast address family
ipv6	Display BGP information for IPv6 address family

unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
routes	Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
advertised-routes	Display all the routes advertised to this peer
received-routes	Display all the routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional)
TABLE_afi	(Optional)
afi	(Optional)
TABLE_safi	(Optional)
safi	(Optional)
af-name	(Optional)
table-version	(Optional)
router-id	(Optional)
TABLE_rd	(Optional)
rd_val	(Optional)
rd_vrf	(Optional)
rd_vniid	(Optional)
TABLE_prefix	(Optional)
ipprefix	(Optional)
nonipprefix	(Optional)
totalpaths	(Optional)

<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_ <i>advertisedto</i>	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_ <i>scheduledto</i>	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_ <i>path</i>	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)

<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)

<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)

<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

## show bgp neighbors commands

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | l2vpn evpn } neighbors {
<neighbor-id> | <ipv6-neighbor-id> } commands [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ [ { TABLE_sesscmd <sessioncmd> <sessioncmdstatus>
[ <sessioncmdtemplate> ] } ] [ TABLE_af <af-afi> TABLE_saf <af-safi> <af-name> [ { TABLE_polcmd
<polycmd> <polycmdstatus> [ <polycmdtemplate> ] } ] ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
neighbors	Display all configured BGP neighbors
commands	Display details on commands
<i>__readonly__</i>	(Optional)
TABLE_sesscmd	(Optional)
<i>sessioncmd</i>	(Optional)
<i>sessioncmdstatus</i>	(Optional)
<i>sessioncmdtemplate</i>	(Optional)

TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_polcmd	(Optional)
<i>polycmd</i>	(Optional)
<i>polycmdstatus</i>	(Optional)
<i>polycmdtemplate</i>	(Optional)

**Command Mode**

- /exec

## show bgp neighbors flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } neighbors { <neighbor-id> | <ipv6-neighbor-id> } flap-statistics
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf
<vrf-name-out> [ TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] ] [ <dampening> <historypaths> <dampenedpaths> ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } ] [ <status> ] [ <pathtype> ] [ <peer> | <ipv6peer> ] [ <flapcount> ] [ <duration> ] [ <reuse>
] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [ <best> ] ] ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
flap-statistics	Display flap statistics for routes received from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_rd	(Optional)

<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

**Command Mode**

- /exec

## show bgp neighbors paths

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] } { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | ipv4
labeled-unicast | link-state | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } paths [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf
<vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_id <id> <hashvalue> <refcount>
<metric> <aspath> ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
paths	Display AS paths learned from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)

TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)

**Command Mode**

- /exec

# show bgp paths

```
show [ ip ] bgp paths [ __readonly__ TABLE_id <id> <hashvalue> <refcount> <metric> <aspath> <origin> ]
```

## Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
paths	Display Path information
__readonly__	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)

## Command Mode

- /exec



<i>ttlsecurity</i>	(Optional)
<i>tllimit</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>password</i>	(Optional)
<i>localas-inactive</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_inheritingpeer	(Optional)
<i>inheritingpeer</i>	(Optional)
TABLE_peraf	(Optional)
<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)
<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pfxrcvd</i>	(Optional)
<i>pfxbytes</i>	(Optional)
<i>pfxsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)

<i>maxpfx</i>	(Optional)
<i>maxpfx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
TABLE_inpolicy	(Optional)
<i>inpolicynr</i>	(Optional)
<i>inpolicytype</i>	(Optional)
<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
TABLE_outpolicy	(Optional)
<i>outpolicynr</i>	(Optional)
<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)
<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatemap</i>	(Optional)
<i>defaultsent</i>	(Optional)
<i>grpathssaved</i>	(Optional)
<i>firsteorrecvd</i>	(Optional)
<i>firsteortime</i>	(Optional)
<i>pathsflushed</i>	(Optional)
<i>lasteorrecvtime</i>	(Optional)
<i>lasteorsenttime</i>	(Optional)
<i>firstconvtime</i>	(Optional)
<i>pfxsentfirsteor</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)

<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vplssignalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)

**Command Mode**

- /exec

## show bgp peer

```
show [ ip ] bgp { peer-session [ <session-template-name> ] | peer-policy [ <policy-template-name> ] } [
__readonly__ TABLE_template <template> <present> [ { TABLE_command <command> [ <polarity> ] [
<updatesource> ] [ <description> ] [ <multihop> ] [ <holdtime> ] [ <keepalive> ] [ <routemapin> ] [
<routemapout> ] [ <filterlistin> ] [ <filterlistout> ] [ <prefixlistin> ] [ <prefixlistout> ] [ <maxprefixlimit> ]
[ <defaultorigin> ] } ] [ { TABLE_vrf <vrf-name> { TABLE_peer <inheritingpeer> } } ] ] ]
```

### Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-session	Display information about a peer-session
peer-policy	Display information about a peer-policy
<i>session-template-name</i>	(Optional) Peer-session name
<i>policy-template-name</i>	(Optional) Peer-policy name
<i>__readonly__</i>	(Optional)
TABLE_template	(Optional)
<i>template</i>	(Optional)
<i>present</i>	(Optional)
TABLE_command	(Optional)
<i>command</i>	(Optional)
<i>polarity</i>	(Optional)
<i>updatesource</i>	(Optional)
<i>description</i>	(Optional)
<i>multihop</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>routemapin</i>	(Optional)
<i>routemapout</i>	(Optional)
<i>filterlistin</i>	(Optional)
<i>filterlistout</i>	(Optional)

<i>prefixlistin</i>	(Optional)
<i>prefixlistout</i>	(Optional)
<i>maxprefixlimit</i>	(Optional)
<i>defaultorigin</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_peer	(Optional)
<i>inheritingpeer</i>	(Optional)

**Command Mode**

- /exec

## show bgp prefix-list

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } } prefix-list { <prfxlist-name> | <test_pol_name> } [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion>
<totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [
<export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path
<pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop>
} { { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref>
] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory>
<pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <importsource> [ <originalimportsource> ]
] [ <importdstscount> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop> }
<nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community
<community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist
<clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife>
<flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [
<psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origrsgb_len>
<psid_origrsgb_flag> <psid_origrsgb_base> <psid_origrsgb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmssi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
<i>test_pol_name</i>	An existing test-list policy
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
__readonly__	(Optional)

TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)

<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)

<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)

<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

# show bgp private

```
show bgp private [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { all_private
| session | ipc | rnh | lists | rpm-info [ route-map <rpm-name> { <ip-prefix> | <ipv6-prefix> } ] | attr [ {
<ip-prefix> } ] | rpm-attribute-cache | rpm-comm-attr-cache | virtual [ summary ] } [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
all_private	Show all info
session	Show session info
lists	Show BGP internal lists
route-map	(Optional) Show information for route-map
rpm-info	Show BGP policy outbound info
<i>ip-prefix</i>	(Optional) Show attribute for a prefix
<i>rpm-name</i>	(Optional) Route-map name
attr	Show attribute information
ipc	Show ipc information
rnh	Show recursive next hops
rpm-attribute-cache	Show rpm attribute cache statistics
rpm-comm-attr-cache	Show rpm community attribute cache statistics
summary	(Optional) Summary only
virtual	Virtualization related
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

## Command Mode

- /exec

## show bgp private attr

```
show bgp private attr [ remote-nh ] [ [ [ ipv4 { unicast | multicast } <ip-prefix> ] ] [ ipv6 { unicast | multicast } <ipv6-prefix> ] ] [ detail ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
attr	Show BGP attributes
remote-nh	(Optional) Show Remote NH Attr
ipv4	(Optional) Display BGP information for IPv4 address family
ipv6	(Optional) Display BGP information for IPv6 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
detail	(Optional) Show detailed info
<i>ip-prefix</i>	(Optional) Show attribute for a prefix

### Command Mode

- /exec

## show bgp private damp

```
show bgp private [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 {
unicast | multicast } | ipv6 { unicast | multicast } | all } damp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
damp	Show dampening info

### Command Mode

- /exec

# show bgp private debug history

show bgp private debug history { all | ead-es | es | mac }

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
debug	Debug
history	history
all	all
ead-es	ead-es
es	es
mac	mac

## Command Mode

- /exec

## show bgp process

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] process [ detail ] [
vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ <processid>
<protocolstartedreason> <protocoltag> <protocolstate> [ <isolatemode> ] <mmode> <memorystate> [
<mallocmemorystate> ] [ <platformmemorystate> ] [ <lowmemorytimer> ] [ <issu> ] <forwardingstatesaved>
<asformat> [ <fabricsoo> ] [ <srgbmin> <srgbmax> ] [ <epeconfiguredpeers> <epeactivepeers> ]
<attributeentries> <hwmattributeentries> <bytesused> <entriespendingdelete> <hwmentriespendingdelete>
<pathsperattribute> <aspathentries> <aspathbytes> ] TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-state>
] [ <vrf-state-rsn> ] [ <vrf-delete-pending> ] [ <vrf-vni-id> ] [ <vrf-vni-id-valid> ] [ <vrf-encap-type> ] [
<vrf-vtep-ip> ] [ <vrf-vtep-virtual-ip> ] [ <vrf-vtep-vipr> ] [ <vrf-router-mac> ] [ <vrf-vip-router-mac> ] [
<vrf-router-id> ] [ <vrf-cfgd-id> ] [ <vrf-local-as> ] [ <vrf-confed-id> ] [ <vrf-cluster-id> ] [
<vrf-reconnect-interval> ] [ <vrf-peers> ] [ <vrf-pending-peers> ] [ <vrf-est-peers> ] [ <vrf-cfgd-max-as-limit>
] [ <vrf-max-as-limit> ] [ <vrf-rd> ] [ <vrf-pending-rd> ] { TABLE_af <af-id> [ <af-name> ] [ <af-table-id>
] [ <af-state> ] [ <af-state-rsn> ] [ <af-num-peers> ] [ <af-num-active-peers> ] [ <af-peer-routes> ] [
<af-peer-paths> ] [ <af-peer-networks> ] [ <af-peer-aggregates> ] [ <af-export-rmap> ] [ <af-import-rmap>
] [ <af-retain-rt> ] [ { TABLE_redist <protocol> <route-map> } ] [ { TABLE_add_paths_selection <route-map>
} ] [ TABLE_export_rt <export-rt> ] [ TABLE_import_rt <import-rt> ] [ TABLE_evpn_export_rt
<evpn-export-rt> ] [ TABLE_evpn_import_rt <evpn-import-rt> ] [ TABLE_mvpn_export_rt <mvpn-export-rt>
] [ TABLE_mvpn_import_rt <mvpn-import-rt> ] [ <af-label-mode> ] [ <af-aggregate-label> ] [
<importdefault_prefixlimit> <importdefault_prefixcount> <importdefault_map> ] [ <exportdefault_prefixlimit>
<exportdefault_prefixcount> <exportdefault_map> ] <af-rt> <default-information-enabled> [
<default-information-rd> <default-information-rt> ] <nexthop-trigger-delay-critical>
<nexthop-trigger-delay-non-critical> [ <nexthop-route-map> ] } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
process	BGP global information
detail	(Optional) Detailed information
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only
<i>processid</i>	(Optional)
<i>protocolstartedreason</i>	(Optional)
<i>protocoltag</i>	(Optional)
<i>protocolstate</i>	(Optional)
<i>isolatemode</i>	(Optional)

<i>mmode</i>	(Optional)
<i>memorystate</i>	(Optional)
<i>mallocmemorystate</i>	(Optional)
<i>platformmemorystate</i>	(Optional)
<i>lowmemorytimer</i>	(Optional)
<i>issu</i>	(Optional)
<i>forwardingstatesaved</i>	(Optional)
<i>asformat</i>	(Optional)
<i>attributeentries</i>	(Optional)
<i>fabricsoo</i>	(Optional)
<i>srgbmin</i>	(Optional)
<i>srgbmax</i>	(Optional)
<i>epeconfiguredpeers</i>	(Optional)
<i>epeactivepeers</i>	(Optional)
<i>hwmattributeentries</i>	(Optional)
<i>bytesused</i>	(Optional)
<i>entriespendingdelete</i>	(Optional)
<i>hwmentriespendingdelete</i>	(Optional)
<i>pathsperattribute</i>	(Optional)
<i>aspathentries</i>	(Optional)
<i>aspathbytes</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity

<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-vtep-vipr</i>	(Optional) VRF VTEP Virtual IP for Re-origination
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-vip-router-mac</i>	(Optional) VRF VIP Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths

<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_redist	(Optional)
<i>protocol</i>	(Optional) Protocol
<i>route-map</i>	(Optional) Route Map
TABLE_add_paths_selection	(Optional)
<i>route-map</i>	(Optional) Route Map
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route-target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route-target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route-target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route-target
TABLE_mvpn_export_rt	(Optional)
<i>mvpn-export-rt</i>	(Optional) Export MVPN route-target
TABLE_mvpn_import_rt	(Optional)
<i>mvpn-import-rt</i>	(Optional) Import MVPN route-target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label
<i>importdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>importdefault_prefixcount</i>	(Optional) Current number of prefixes
<i>importdefault_map</i>	(Optional) Configured route-map
<i>exportdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>exportdefault_prefixcount</i>	(Optional) Current number of prefixes

<i>exportdefault_map</i>	(Optional) Configured route-map
<i>af-rr</i>	(Optional) Is a Route-reflector
<i>default-information-enabled</i>	(Optional) Default-information originate is enabled
<i>default-information-rd</i>	(Optional) Default-information originate RD
<i>default-information-rt</i>	(Optional) Default-information originate RT
<i>nexthop-trigger-delay-critical</i>	(Optional)
<i>nexthop-trigger-delay-non-critical</i>	(Optional)
<i>nexthop-route-map</i>	(Optional)

**Command Mode**

- /exec

## show bgp received-paths

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } received-paths
[ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> <statuscode> <bestcode> <typecode> {
<ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel> <vpn> <hold_down> } } { <weight> <aspath>
<origin> [ <metric> ] [ <localpref> ] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabelednrh> ] [ <importsourc>
[ <originalimportsourc> ] ] [ <importdestscout> ] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> |
<ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ]
<localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalflife> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid>
] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh>
<remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr>
<link-state-attr-len> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family

ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
private	(Optional) private
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)

<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)

<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)

<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)

<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

**Command Mode**

- /exec

## show bgp regexp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } regexp <regexp-str> [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths>
<bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel>
<vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] } } } | { [
<policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabeledrn> ] [ <importsourc> [ <originalimportsourc> ] ] [ <importdestscount>
] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> |
<ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
regexp	Display routes matching the AS path regular expression
<i>regexp-str</i>	Regular expression to match the AS paths
__readonly__	(Optional)

TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)

<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)

<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)

<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

### Command Mode

- /exec

## show bgp self-originated

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } self-originated [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [
<on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { { <inlabel> <outlabel>
<vpn> <hold_down> } } { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] } } } | { [
<policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabelednrh> ] [ <importsource> [ <originalimportsource> ] ] [ <importdestscount>
] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> |
<ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<mdt_grp_addr> } } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ]
]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
self-originated	Self originated routes
__readonly__	(Optional)
TABLE_vrf	(Optional)

<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)

<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)

<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)

<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_origsrgrb_len</i>	(Optional)
<i>psid_origsrgrb_flag</i>	(Optional)
<i>psid_origsrgrb_base</i>	(Optional)
<i>psid_origsrgrb_end</i>	(Optional)

**Command Mode**

- /exec

## show bgp sessions

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] sessions [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ <totalpeers>
<totalestablishedpeers> <localas> TABLE_vrf <vrf-name-out> <local-as> <vrfpeers> <vrfestablishedpeers>
<router-id> [ TABLE_neighbor <neighbor-id> <connectionsdropped> <remotear> [ <lastflap> ] [ <lastread>
] [ <lastwrite> ] <state> <localport> <remoteport> <notificationssent> <notificationsreceived> ] ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
sessions	Display session information for all peers
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>local-as</i>	(Optional)
<i>totalpeers</i>	(Optional)
<i>totalestablishedpeers</i>	(Optional)
<i>router-id</i>	(Optional)
<i>localas</i>	(Optional)
<i>vrfpeers</i>	(Optional)
<i>vrfestablishedpeers</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor-id</i>	(Optional)
<i>connectionsdropped</i>	(Optional)
<i>remotear</i>	(Optional)
<i>lastflap</i>	(Optional)
<i>lastread</i>	(Optional)
<i>lastwrite</i>	(Optional)

<i>state</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteport</i>	(Optional)
<i>notificationssent</i>	(Optional)
<i>notificationsreceived</i>	(Optional)

**Command Mode**

- /exec

# show bgp statistics

```
show bgp statistics [ __readonly__ <msgsent> <msgrcvd> <bytesent> <bytercvd> <opensent> <openrcvd>
<updatesent> <updaterecvd> <kasent> <karecvd> <notifsent> <notifrcvd> <rrefreshsent> <rrefreshrcvd>
<capsent> <caprcvd> ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
statistics	BGP global statistics
<i>__readonly__</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>msgrcvd</i>	(Optional)
<i>bytesent</i>	(Optional)
<i>bytercvd</i>	(Optional)
<i>opensent</i>	(Optional)
<i>openrcvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updaterecvd</i>	(Optional)
<i>kasent</i>	(Optional)
<i>karecvd</i>	(Optional)
<i>notifsent</i>	(Optional)
<i>notifrcvd</i>	(Optional)
<i>rrefreshsent</i>	(Optional)
<i>rrefreshrcvd</i>	(Optional)
<i>capsent</i>	(Optional)
<i>caprcvd</i>	(Optional)

## Command Mode

- /exec



<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-vtep-vipr</i>	(Optional) VRF VTEP Virtual IP for Re-origination
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-vip-router-mac</i>	(Optional) VRF VIP Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason

<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)
<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)

<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)
<i>softreconfigcombopaths</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighboras</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)

**Command Mode**

- /exec



l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-vtep-vipr</i>	(Optional) VRF VTEP Virtual IP for Re-origination
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-vip-router-mac</i>	(Optional) VRF VIP Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers

<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)

<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)
<i>softreconfigcombopaths</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighboras</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)

**Command Mode**

- /exec

# show boot

```
show boot [ __readonly__ { [ TABLE_bootvar_show <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_show	(Optional) Bootvar table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot auto-copy

```
show boot auto-copy [ __readonly__ { [ TABLE_auto_copy <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autcopy is turned on
__readonly__	(Optional)
TABLE_auto_copy	(Optional) Auto copy table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot auto-copy list

```
show boot auto-copy list [ __readonly__ { [ TABLE_auto_copy_list <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autocopy is turned on
list	Show the list of files to be auto-copied
__readonly__	(Optional)
TABLE_auto_copy_list	(Optional) Auto copy table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot autocopy-status

show boot autocopy-status

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
autocopy-status	Display the standby autocopy status

## Command Mode

- /exec

# show boot current

```
show boot current [ __readonly__ { [ TABLE_bootvar_current <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
current	Show Current Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_current	(Optional) Bootvar current table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot mode

```
show boot mode [ __readonly__ { [ TABLE_mode <Str1> ] } ]
```

## Syntax Description

show	Show boot mode information
boot	Show boot mode
mode	See if lxc boot is turned on
__readonly__	(Optional)
TABLE_mode	(Optional) boot mode table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot order

```
show boot order [ __readonly__ { [ TABLE_bootvar_order <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
order	Show Boot Order
__readonly__	(Optional)
TABLE_bootvar_order	(Optional) Boot order table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show boot sup-1

```
show boot sup-1 [ __readonly__ { [ TABLE_show_sup1 <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
sup-1	Enter sup-1 to show the 1st sup config
__readonly__	(Optional)
TABLE_show_sup1	(Optional) Show Sup-1 bootvar table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

## show boot sup-2

```
show boot sup-2 [ __readonly__ { [ TABLE_show_sup2 <Str1> ] } ]
```

### Syntax Description

show	Show running system information
boot	Show Bootvar Variables
sup-2	Enter sup-2 to show the 2nd sup config
__readonly__	(Optional)
TABLE_show_sup2	(Optional) Show Sup-22 bootvar table
<i>Str1</i>	(Optional)

### Command Mode

- /exec

# show boot timings

show boot timings

## Syntax Description

show	Show running system information
boot	show boot information
timings	show boot timings

## Command Mode

- /exec

# show boot variables

```
show boot variables [ __readonly__ { [ TABLE_boot_vars <Str1> ] } ]
```

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
variables	Display the list of boot variables
__readonly__	(Optional)
TABLE_boot_vars	(Optional) Show boot variables table
<i>Str1</i>	(Optional)

## Command Mode

- /exec

# show bootmode

```
show bootmode [ module <module> ] [ __readonly__ { TABLE_bootmode_info <mod_num> <bootmode>
} ]
```

## Syntax Description

show	Show running system information
bootmode	show bootmode of the all linecard modules
module	(Optional) show bootmode of a specific linecard module
<i>module</i>	(Optional) please enter module number
__readonly__	(Optional)
TABLE_bootmode_info	(Optional)
<i>mod_num</i>	(Optional)
<i>bootmode</i>	(Optional)

## Command Mode

- /exec

# show buffers ip

```
show buffers ip [ { [ all <count> ] [ free <count> ] } ]
```

## Syntax Description

show	Show running system information
buffers	Display detailed buffer statistics
ip	Display IP buffer information
all	(Optional) Dump buffers from ALL list
free	(Optional) Dump buffers from FREE list
<i>count</i>	(Optional) Number of buffers to dump

## Command Mode

- /exec

■ show buffers ip