



## K Commands

---

- [key-chain macsec-psk no-show](#), on page 2
- [key-octet-string 7 cryptographic-algorithm AES\\_128\\_CMAC](#), on page 3
- [key-octet-string 7 cryptographic-algorithm AES\\_256\\_CMAC](#), on page 4
- [key-octet-string cryptographic-algorithm AES\\_128\\_CMAC](#), on page 5
- [key-octet-string cryptographic-algorithm AES\\_256\\_CMAC](#), on page 6
- [key-server-priority](#), on page 7
- [key-string](#), on page 8
- [key-string 7](#), on page 9
- [key](#), on page 10
- [key](#), on page 11
- [key chain](#), on page 12
- [key chain macsec](#), on page 13
- [kill background](#), on page 14
- [kubernetes server ip-address port](#), on page 15

# key-chain macsec-psk no-show

[no] key-chain macsec-psk no-show

Syntax Description

no	(Optional) Negate a command or set its defaults
key-chain	Keychain Management
macsec-psk	Macsec Pre-shared key
no-show	do not show

Command Mode

- /exec/configure

# key-octet-string 7 cryptographic-algorithm AES\_128\_CMAC

```
{ key-octet-string 7 <keystring> cryptographic-algorithm AES_128_CMAC }
```

## Syntax Description

key-octet-string	Set key octet string
7	Encryption Type - Proprietary
keystring	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_128_CMAC	cryptographic-algorithm AES-128-CMAC

## Command Mode

- /exec/configure/macseckeychain-key

## key-octet-string 7 cryptographic-algorithm AES\_256\_CMAC

```
{ key-octet-string 7 <keystring> cryptographic-algorithm AES_256_CMAC }
```

### Syntax Description

key-octet-string	Set key octet string
7	Encryption Type - Proprietary
keystring	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_256_CMAC	cryptographic-algorithm AES-256-CMAC

### Command Mode

- /exec/configure/macseckeychain-key

# key-octet-string cryptographic-algorithm AES\_128\_CMAC

```
{ key-octet-string [ 0 ] <keystring> cryptographic-algorithm AES_128_CMAC | no key-octet-string [ 0 ]  
<keystring> cryptographic-algorithm AES_128_CMAC }
```

## Syntax Description

no	Negate a command or set its defaults
key-octet-string	Set key octet string
0	(Optional) Encryption Type - No Encryption(default)
keystring	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_128_CMAC	cryptographic-algorithm AES-128-CMAC

## Command Mode

- /exec/configure/macseckeychain-key

## key-octet-string cryptographic-algorithm AES\_256\_CMAC

```
{ key-octet-string [ 0 ] <keystring> cryptographic-algorithm AES_256_CMAC | no key-octet-string [ 0 ]
<keystring> cryptographic-algorithm AES_256_CMAC }
```

### Syntax Description

no	Negate a command or set its defaults
key-octet-string	Set key octet string
0	(Optional) Encryption Type - No Encryption(default)
keystring	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_256_CMAC	cryptographic-algorithm AES-256-CMAC

### Command Mode

- /exec/configure/macseckeychain-key

# key-server-priority

[no] key-server-priority <pri>

Syntax Description

key-server-priority	Configure Key-Server priority
pri	key-server priority value

Command Mode

- /exec/configure/macsec-policy

# key-string

```
{ key-string [ 0 ] <keystring> | no key-string }
```

## Syntax Description

no	Negate a command or set its defaults
key-string	Set key string
0	(Optional) Encryption Type - No Encryption(default)
keystring	key string

## Command Mode

- /exec/configure/keychain-key



# key-string 7

```
{ key-string 7 <keystring> }
```

## Syntax Description

key-string	Set key string
7	Encryption Type - Proprietary
keystring	key string

## Command Mode

- /exec/configure/keychain-key

# key

[no] key <macsec\_keyid>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Configure a macsec key
macsec_keyid	MACsec Key identifier ranging from 1 octet to 32

Command Mode

- /exec/configure/macseckeychain

# key

[no] key <keyid>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Configure a key
keyid	Key identifier

Command Mode

- /exec/configure/keychain

# key chain

[no] key chain <keychain>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Key Management
chain	Keychain Management
keychain	key-chain name

Command Mode

- /exec/configure

# key chain macsec

[no] key chain <keychain> macsec

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Key Management
chain	Keychain Management
keychain	macsec key-chain name
macsec	Macsec Keychain

Command Mode

- /exec/configure

# kill background

kill background <pid>

Syntax Description

kill	terminate processes
background	kill background processes (started with 'source background <file>' command)
pid	background script to terminate, by process-id or just a regex matching any line from 'show background' command

Command Mode

- /exec

## kubernetes server ip-address port

[no] kubernetes server ip-address <ip-addr> port <s0> [ vrf <vrf-name> ] | no kubernetes server

### Syntax Description

no	(Optional) Negate a command or set its defaults
kubernetes	kubernetes
server	kubernetes server
ip-address	IP address of the kubernetes host
ip-addr	ip address of kubernetes Host
port	Port number of the host
s0	port number
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name

### Command Mode

- /exec/configure

