



New and Changed Information

This chapter provides release-specific information for each new and changed feature in the *Cisco Nexus 3000 Series NX-OS Unicast Routing Configuration Guide, Release 5.0(3)U2(2)*. The latest version of this document is available at the following Cisco website:

http://www.cisco.com/en/US/products/ps11541/products_installation_and_configuration_guides_list.html

To check for additional information, see the *Cisco Nexus 7000 Series NX-OS Release Notes, Release 5.x* available at the following Cisco website:

http://www.cisco.com/en/US/products/ps11541/prod_release_notes_list.html

Table 1 summarizes the new and changed features for the *Cisco Nexus 3000 Series NX-OS Unicast Routing Configuration Guide, Release 5.0(3)U2(2)*, and tells you where they are documented.

Table 1 ***New and Changed Features for 5.0(3)***

Feature	Description	Changed in Release	Where Documented
IPv4	Added information to configure the glean throttling feature.	5.0(3)U2(1)	Chapter 2, “Configuring IPv4”
Bidirectional forwarding detection (BFD) for BGP	Added information on how to configure BFD for BGP.	5.0(3)U2(2)	Chapter 7, “Configuring Bidirectional Forwarding Detection for BGP”
Equal-cost multipathing (ECMP) protocol for host routes	Added information on how to configure ECMP for host routes.	5.0(3)U2(2)	Chapter 8, “Configuring ECMP for Host Routes”
BGP	Added support for Local AS.	5.0(3)U2(2a)	Configuring Local AS Support, page 6-24
BFD for BGP	Added guidelines and limitations for LACP configuration, and for BFD echo and URFP.	5.0(3)U2(2a)	Guidelines and Limitations, page 7-3

Send document comments to nexus3k-docfeedback@cisco.com.