



New and Changed Information

This chapter provides release-specific information for new and changed feature in the Cisco Nexus 3600 NX-OS Unicast Routing Configuration Guide, Release 7.x. The latest version of this document is available at the following Cisco website:

<https://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-installation-and-configuration-guides-list.html>

To check for additional information, see the Cisco Nexus 3600 NX-OS Release Notes, Release 7.x available at the following Cisco website:

<https://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-release-notes-list.html>

- [New and Changed Information, on page 1](#)

New and Changed Information

This table provides an overview of the significant changes made to this configuration guide. The table does not provide an exhaustive list of all changes to this guide or all new features in a particular release

Table 1: New and Changed Feature Information

Feature	Description	Changed in Release	Where Documented
BGP Routing	For next-hop-self , added the optional all argument which controls whether reflected routes have their next hops changed.	7.0(3)I7(6)	Controlling Reflected Routes Through Next Hop Self
HSRP	Added the ability to configure an HSRP subnet virtual IP address in a different subnet than that of the SVI IP address.	7.0(3)F3(3)	Configuring HSRP
Policy-based routing (PBR)	Introduced this feature.	7.0(3)F3(3)	Configuring Policy-Based Routing
Unicast routing	First release.	7.0(3)F3(1)	

