



Cisco Nexus 3164Q NX-OS Verified Scalability Guide, Release 7.0(3)I4(1)

[Verified Scalability Limits](#) 2

Verified Scalability Limits

This chapter describes the Cisco NX-OS configuration limits for the Cisco Nexus 3164Q switch.

Introduction

The values provided in this guide should not be interpreted as theoretical system limits for Cisco Nexus 3164Q hardware or Cisco NX-OS software. These limits refer to values that have been validated by Cisco. They can increase over time as more testing and validation is done.

Verified Scalability Limits (Unidimensional)

The tables in this section list the unidimensional verified scalability limits for Cisco NX-OS Release 7.0(3)I4(1) on the Cisco Nexus 3164Q switch. The values provided in these tables focus on the scalability of one particular feature at a time.

Each number is the absolute maximum currently supported by this Cisco NX-OS release for the corresponding feature. If the hardware is capable of a higher scale, future software releases might increase this verified maximum limit. Results might differ from the values listed here when trying to achieve maximum scalability with multiple features enabled.

Table 1: Interfaces Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
DHCP clients per switch	10 (IPv4) + 10 (IPv6)
BFD sessions	128 (IPv4) + 128 (IPv6)
Generic routing encapsulation (GRE) tunnels	8
Port channel links	32
SVIs	250
vPCs	60

Table 2: Label Switching Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
Forwarding Equivalence Classes (FECs)	128
Equal-cost multipaths (ECMPs)	16
FECs * ECMPs	1000
Flex counters for static MPLS in egress direction	4000
Flex counters per adjacency	2
Adjacencies	1024



Note The maximum number of FECs and ECMPs cannot be configured at the same time. For example, if you have 128 FECs and all of those FECs have 8 ECMPs, you will have $128 * 8 = 1024$ adjacencies, so egress statistics will be supported for all. In contrast, if you have 100 FECs and all of those FECs have 16 ECMPs, you will have $100 * 16 = 1600$ adjacencies. Because a maximum of 1024 adjacencies are supported, the statistics might not work as expected.

Table 3: Layer 2 Switching Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
MST instances	64
MST virtual ports	48,000
RPVST virtual ports	12,000
VLANs	3900
VLANs in RPVST mode	500
Total number of VLANs × ports with switchport isolated (3967 VLANs x 48 ports)	190,000



Note The number of supported VLANs per vPC should be within the MST or RPVST virtual port count specified in this table, depending on the topology.

Table 4: Multicast Routing Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
IPv4 multicast routes	8000 (Layer 2 + Layer 3)
Outgoing interfaces (OIFs)	40 (SVI + physical Layer 3)
IGMP snooping groups	8000
PIM neighbors	250



Note The IPv4 multicast routes and the IPv4/IPv6 host routes share the same hardware table. Limits are provided for both the default line card mode and the max host line card mode.



Note High availability (graceful restart and stateful switchover) is not supported when unicast or multicast aggressive timers are configured at any scale.

Table 5: Security Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
DHCP snooping bindings	2048
IPv4 ingress ACLs	3070 (per network forwarding engine)
IPv4 egress ACLs	765 (per network forwarding engine)
IPv6 ingress ACLs	1530 (per network forwarding engine)
IPv6 egress ACLs	250 (per network forwarding engine)



Note The ACL scalability limits also apply to policy-based ACLs (PBACLs).

Table 6: System Management Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
MPLS Stripping	
Labels	12,000
Ingress interfaces	48
Egress interfaces	16
PTP	
10G physical ports enabled for PTP	44
sFlow	
sFlow ports	64
SPAN and ERSPAN	
Configurable SPAN or ERSPAN sessions	32
Active SPAN or ERSPAN sessions ¹	4
Active localized SPAN or ERSPAN sessions per line card ²	4
Source interfaces per SPAN or ERSPAN session (Rx and Tx, Rx, or Tx)	48
Destination interfaces per SPAN session	1 (physical interface)
Source VLANs per SPAN or ERSPAN session	32
TAP Aggregation	

Feature	3164Q Verified Limit
Redirect interfaces in the redirect port list	12
Redirect port lists (or fan outs) per system	100

¹ A single forwarding engine instance supports four SPAN or ERSPAN sessions. If the first three sessions have bidirectional sources, the fourth session might have hardware resources only for Rx sources, depending on the SPAN or ERSPAN source's forwarding engine instance mappings.

² The number of SPAN or ERSPAN sessions per line card reduces to two if the same interface is configured as the bidirectional source in more than one session.

Table 7: Unicast Routing Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
Unicast Routing	
BGP neighbors	512 (IPv4 only) 512 (IPv6 only) 256 (IPv4) + 256 (IPv6)
EIGRP neighbors	128 (IPv4), 128 (IPv6)
EIGRP routes	20,000
HSRP groups	250
IPv4 ARP	48,000
IPv4 host routes	208,000
IPv6 host routes	40,000
IPv6 ND	40,000
IPv4 unicast routes (LPM)	128,000 (default system routing mode) 128,000 with no IPv6 routes (64-bit ALPM routing mode)
IPv6 unicast routes (LPM)	20,000 (default system routing mode) 80,000 with no IPv4 routes (64-bit ALPM routing mode)
IPv4 and IPv6 unicast routes (LPM) in 64-bit ALPM routing mode	x IPv6 routes and y IPv4 routes, where $2x + y \leq 128,000$
MAC addresses	80,000
OSPFv2 neighbors	256
OSPFv3 neighbors	256
VRFs	1000

Feature	3164Q Verified Limit
VRRP groups per interface or I/O module	250
Policy-Based Routing (PBR)	
Configured sequences per policy	256
Next-hop addresses per policy	32
IPv4 ACEs (unidimensional)	3072 (per network forwarding engine)
IPv6 ACEs (unidimensional)	1536 (per network forwarding engine)
IPv4 and IPv6s ACEs	2048 IPv4 + 256 IPv6
Interfaces with PBR policy	512
VRRPv3	
VRRPv3 groups per interface	255
VRRPv3 groups with default timers	490
Pathways with one VRRPv3 group with default timer	489
VRRPv3 groups and pathways combined	490



Note The IPv4 and IPv6 unicast routes share the same hardware table. Limits are provided for both the default line card mode and the max host line card mode.



Note The IPv4/IPv6 host routes and the IPv4 multicast routes share the same hardware table. Limits are provided for both the default line card mode and the max host line card mode.



Note High availability (graceful restart and stateful switchover) is not supported when unicast or multicast aggressive timers are configured at any scale.

Guidelines and Limitations for OSPF Verified Scalability Limits

- To achieve the highest scale, we recommend that you use a single OSPF instance instead of multiple instances.
- Each OSPFv2 and OSPFv3 scale value might vary when combined with other parameters.
- The graceful restart timeout value might need to be increased in multidimensional scenarios.

Table 8: VXLAN Verified Scalability Limits (Unidimensional)

Feature	3164Q Verified Limit
VXLAN Flood and Learn	
Virtual network identifiers (VNIs) or VXLAN-mapped VLANs	1000
Underlay multicast groups	128
Overlay MAC addresses	64,000
Remote VXLAN tunnel endpoints (VTEPs)	256
Ingress replication peers	256
Ingress replication Layer 2 VNIs	1000
MAC addresses for ingress replication	64,000
VXLAN VLAN logical port VP count	6000
VXLAN BGP eVPN	
Layer 2 VNI	1000
Underlay multicast groups	128
VTEPs	256
BGP VTEP peers	256
MAC addresses	64,000
VXLAN VLAN logical port VP count	6000

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS REFERENCED IN THIS DOCUMENTATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. EXCEPT AS MAY OTHERWISE BE AGREED BY CISCO IN WRITING, ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS DOCUMENTATION ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

The Cisco End User License Agreement and any supplemental license terms govern your use of any Cisco software, including this product documentation, and are located at: <http://www.cisco.com/go/softwareterms>. Cisco product warranty information is available at <http://www.cisco.com/go/warranty>. US Federal Communications Commission Notices are found here <http://www.cisco.com/c/en/us/products/us-fcc-notice.html>.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any products and features described herein as in development or available at a future date remain in varying stages of development and will be offered on a when-and if-available basis. Any such product or feature roadmaps are subject to change at the sole discretion of Cisco and Cisco will have no liability for delay in the delivery or failure to deliver any products or feature roadmap items that may be set forth in this document.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

The documentation set for this product strives to use bias-free language. For the purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com go trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2016 Cisco Systems, Inc. All rights reserved.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA 95134-1706
USA

Asia Pacific Headquarters
CiscoSystems(USA)Pte.Ltd.
Singapore

Europe Headquarters
CiscoSystemsInternationalBV
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.