



New and Changed Information

This chapter provides release-specific information for each new and changed feature in the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide, Release 6.x. The latest version of this document is available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-installation-and-configuration-guides-list.html>

To check for additional information, see the Cisco Nexus 3548 Switch NX-OS Release Notes, Release 6.x available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-release-notes-list.html>

- [New and Changed Information, on page 1](#)

New and Changed Information

This table summarizes the new and changed features for the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide, Release 7.x and indicates where they are documented.

Table 1: New and Changed Features

Feature	Description	Changed in Release	Where Documented
IP Routing	Added a command that sets the logging conditions for IP packets that the NX-OS software forwards.	7.0(3)I7(7)	Configuring Logging for Software Forwarding of IP Packets
BGP Routing	For next-hop-self , added the optional all argument which controls whether reflected routes have their next hops changed.	7.0(3)I7(6)	Controlling Reflected Routes Through Next Hop Self
Unicast Routing	No updates since Cisco NX-OS Release 6.x	7.0(3)I7(3)	

