



## New and Changed Information

This chapter provides release-specific information for each new and changed feature in this release of the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide. The latest version of this document is available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-installation-and-configuration-guides-list.html>

To check for additional information, see the Cisco Nexus 3548 Switch NX-OS Release Notes for this release, which are available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-release-notes-list.html>

- [New and Changed Information](#), on page 1

## New and Changed Information

This table summarizes the new and changed features for the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide, Release 9.2(x) and tells you where they are documented.

**Table 1: New and Changed Feature Information**

Feature	Description	Changed in Release	Where Documented
	Changed the document title from 9.x to 9.2(x)		Title page
BGP best-path algorithm	Added the option to ignore the Interior Gateway Protocol (IGP) metric for next hop during best-path selection.	9.2(2)	<a href="#">Tuning BGP</a>
Unicast routing	No updates since Cisco NX-OS Release 7.x	9.2(1)	

