



I Show Commands

- [show icam entries acl module inst](#), on page 11
- [show icam entries multicast module](#), on page 13
- [show icam prediction entries acl module inst](#), on page 15
- [show icam prediction entries multicast module](#), on page 17
- [show icam prediction resource acl_tcam module inst trend](#), on page 19
- [show icam prediction resource module inst](#), on page 21
- [show icam resource module inst](#), on page 23
- [show icam scale](#), on page 26
- [show ieth-header-decode](#), on page 29
- [show imp client](#), on page 30
- [show imp client sa](#), on page 31
- [show incompatibility-all system](#), on page 32
- [show incompatibility system](#), on page 33
- [show install](#), on page 34
- [show install all failed-standby](#), on page 35
- [show install all failure-reason](#), on page 36
- [show install all impact](#), on page 37
- [show install all status](#), on page 38
- [show install all time-stats](#), on page 39
- [show install impact](#), on page 40
- [show install impact](#), on page 41
- [show install impact detail](#), on page 42
- [show install log](#), on page 43
- [show install packages](#), on page 44
- [show install patches](#), on page 45
- [show interface](#), on page 46
- [show interface](#), on page 48
- [show interface](#), on page 56
- [show interface](#), on page 60
- [show interface](#), on page 72
- [show interface](#), on page 76
- [show interface](#), on page 82
- [show interface](#), on page 84

- [show interface brief, on page 88](#)
- [show interface brief, on page 89](#)
- [show interface brief, on page 90](#)
- [show interface brief, on page 92](#)
- [show interface brief, on page 93](#)
- [show interface brief, on page 95](#)
- [show interface brief, on page 96](#)
- [show interface brief, on page 97](#)
- [show interface cable-diagnostics-tdr, on page 98](#)
- [show interface capabilities, on page 99](#)
- [show interface capabilities, on page 101](#)
- [show interface counters, on page 103](#)
- [show interface counters, on page 105](#)
- [show interface counters, on page 106](#)
- [show interface counters, on page 108](#)
- [show interface counters, on page 110](#)
- [show interface counters, on page 112](#)
- [show interface counters brief, on page 113](#)
- [show interface counters brief, on page 115](#)
- [show interface counters detailed, on page 117](#)
- [show interface counters detailed, on page 127](#)
- [show interface counters detailed, on page 130](#)
- [show interface counters detailed, on page 132](#)
- [show interface counters detailed all, on page 139](#)
- [show interface counters detailed all, on page 140](#)
- [show interface counters detailed all, on page 143](#)
- [show interface counters detailed all, on page 145](#)
- [show interface counters detailed all, on page 146](#)
- [show interface counters detailed cached, on page 154](#)
- [show interface counters errors, on page 162](#)
- [show interface counters errors, on page 164](#)
- [show interface counters errors, on page 166](#)
- [show interface counters snmp, on page 167](#)
- [show interface counters storm-control, on page 169](#)
- [show interface counters storm-control, on page 170](#)
- [show interface counters table, on page 171](#)
- [show interface counters trunk, on page 172](#)
- [show interface dampening, on page 173](#)
- [show interface debounce, on page 174](#)
- [show interface debounce, on page 175](#)
- [show interface description, on page 176](#)
- [show interface description, on page 177](#)
- [show interface description, on page 178](#)
- [show interface description, on page 179](#)
- [show interface description, on page 180](#)
- [show interface description, on page 181](#)

- [show interface description](#), on page 182
- [show interface fcoe](#), on page 183
- [show interface flowcontrol](#), on page 184
- [show interface flowcontrol](#), on page 185
- [show interface mac-address](#), on page 186
- [show interface mac-address](#), on page 187
- [show interface private-vlan mapping](#), on page 188
- [show interface pruning](#), on page 189
- [show interface snmp-ifindex](#), on page 190
- [show interface status](#), on page 191
- [show interface status](#), on page 192
- [show interface status](#), on page 194
- [show interface status](#), on page 195
- [show interface status](#), on page 196
- [show interface status](#), on page 197
- [show interface status](#), on page 198
- [show interface status err-disabled](#), on page 199
- [show interface status err-disabled](#), on page 200
- [show interface status err-vlans](#), on page 201
- [show interface status err-vlans](#), on page 202
- [show interface switchport](#), on page 203
- [show interface switchport](#), on page 205
- [show interface transceiver](#), on page 207
- [show interface transceiver](#), on page 216
- [show interface trunk](#), on page 223
- [show interface trunk](#), on page 225
- [show interface untagged-cos](#), on page 227
- [show inventory](#), on page 228
- [show ip adjacency](#), on page 229
- [show ip amt relay](#), on page 232
- [show ip amt route](#), on page 233
- [show ip amt tunnel](#), on page 234
- [show ip arp](#), on page 236
- [show ip arp anycast topo-info](#), on page 238
- [show ip arp cache](#), on page 239
- [show ip arp client](#), on page 240
- [show ip arp controller-statistics](#), on page 241
- [show ip arp esi](#), on page 242
- [show ip arp multihoming-statistics](#), on page 243
- [show ip arp off-list](#), on page 245
- [show ip arp open-flow error-statistics](#), on page 246
- [show ip arp snmp ptree](#), on page 248
- [show ip arp statistics](#), on page 249
- [show ip arp suppression-cache](#), on page 253
- [show ip arp suppression topo-info](#), on page 256
- [show ip arp tunnel-statistics](#), on page 257

- [show ip arp unnum-svi-adj](#), on page 259
- [show ip arp vaddr](#), on page 260
- [show ip arp vpc-statistics](#), on page 261
- [show ip as-path-access-list](#), on page 264
- [show ip bgp](#), on page 265
- [show ip cache](#), on page 266
- [show ip client](#), on page 267
- [show ip community-list](#), on page 268
- [show ip debug](#), on page 269
- [show ip dhcp global statistics](#), on page 270
- [show ip dhcp option82 suboption info interface](#), on page 272
- [show ip dhcp relay](#), on page 273
- [show ip dhcp relay address](#), on page 275
- [show ip dhcp relay information trusted-sources](#), on page 276
- [show ip dhcp relay statistics](#), on page 277
- [show ip dhcp snooping](#), on page 281
- [show ip dhcp snooping binding](#), on page 282
- [show ip dhcp snooping statistics](#), on page 283
- [show ip dhcp status](#), on page 284
- [show ip dns source-interface](#), on page 285
- [show ip dns source-interface vrf all](#), on page 286
- [show ip eigrp route-map statistics](#), on page 287
- [show ip extcommunity-list](#), on page 289
- [show ip fib adjacency](#), on page 290
- [show ip fib interfaces](#), on page 291
- [show ip fib mroute](#), on page 292
- [show ip fib mroute](#), on page 294
- [show ip fib mroute txlist](#), on page 296
- [show ip fib route](#), on page 297
- [show ip fib route](#), on page 300
- [show ip fib route recovered](#), on page 302
- [show ip ftm statistics](#), on page 303
- [show ip ftp source-interface](#), on page 304
- [show ip ftp source-interface vrf all](#), on page 305
- [show ip http source-interface](#), on page 306
- [show ip http source-interface vrf all](#), on page 307
- [show ip igmp event-history](#), on page 308
- [show ip igmp groups](#), on page 309
- [show ip igmp interface](#), on page 311
- [show ip igmp local-groups](#), on page 315
- [show ip igmp policy statistics reports](#), on page 317
- [show ip igmp snooping](#), on page 318
- [show ip igmp snooping event-history](#), on page 320
- [show ip igmp snooping explicit-tracking](#), on page 321
- [show ip igmp snooping filter details](#), on page 323
- [show ip igmp snooping groups](#), on page 324

- [show ip igmp snooping lookup-mode](#), on page 327
- [show ip igmp snooping mac-oif](#), on page 328
- [show ip igmp snooping mrouter](#), on page 329
- [show ip igmp snooping pw vlan brief](#), on page 331
- [show ip igmp snooping querier](#), on page 332
- [show ip igmp snooping report statistics](#), on page 334
- [show ip igmp snooping snmp mib adminMode](#), on page 335
- [show ip igmp snooping snmp mib aliasingMode](#), on page 336
- [show ip igmp snooping snmp mib cisV3ProcessEnableOperStatus](#), on page 337
- [show ip igmp snooping snmp mib explicitTrackingTable](#), on page 338
- [show ip igmp snooping snmp mib fallBackTime](#), on page 339
- [show ip igmp snooping snmp mib fastBlockEnabled](#), on page 340
- [show ip igmp snooping snmp mib fastleaveenabled](#), on page 341
- [show ip igmp snooping snmp mib filterStatsTable](#), on page 342
- [show ip igmp snooping snmp mib ifAccessGroupTable](#), on page 343
- [show ip igmp snooping snmp mib ifConfigTable](#), on page 344
- [show ip igmp snooping snmp mib ifLimitTable](#), on page 345
- [show ip igmp snooping snmp mib ifLimitTotalTable](#), on page 346
- [show ip igmp snooping snmp mib igmpsnoopingenabled](#), on page 347
- [show ip igmp snooping snmp mib interfaceStatsTable](#), on page 348
- [show ip igmp snooping snmp mib lastMemeberQueryCount](#), on page 350
- [show ip igmp snooping snmp mib lastMemeberQueryInterval](#), on page 351
- [show ip igmp snooping snmp mib leaveQueryType](#), on page 352
- [show ip igmp snooping snmp mib mcastGroupTable](#), on page 353
- [show ip igmp snooping snmp mib mcastRouterCfgTable](#), on page 354
- [show ip igmp snooping snmp mib mcastRouterConfigTable](#), on page 355
- [show ip igmp snooping snmp mib multicastGroupConfigTable](#), on page 356
- [show ip igmp snooping snmp mib multicastGroupPortListTable](#), on page 358
- [show ip igmp snooping snmp mib multicastGroupTable](#), on page 360
- [show ip igmp snooping snmp mib operMode](#), on page 362
- [show ip igmp snooping snmp mib querierTable](#), on page 363
- [show ip igmp snooping snmp mib reportsuppressionenabled](#), on page 365
- [show ip igmp snooping snmp mib robustnessVariable](#), on page 366
- [show ip igmp snooping snmp mib routerAlertCheckEnabled](#), on page 367
- [show ip igmp snooping snmp mib sourceOnlyEntryAgingTime](#), on page 368
- [show ip igmp snooping snmp mib sourceOnlyLearningEnabled](#), on page 369
- [show ip igmp snooping snmp mib tcxFloodQueryCount](#), on page 370
- [show ip igmp snooping snmp mib timeToLiveCheckEnabled](#), on page 371
- [show ip igmp snooping snmp mib topoChanageQuerySolicitEnabled](#), on page 372
- [show ip igmp snooping snmp mib v3ProcessEnabledAdminStatus](#), on page 373
- [show ip igmp snooping snmp mib v3SnoopingSupport](#), on page 374
- [show ip igmp snooping snmp mib vlanFilterConfigTable](#), on page 375
- [show ip igmp snooping snmp mib vlanconfigtable](#), on page 376
- [show ip igmp snooping statistics](#), on page 378
- [show ip igmp vrf all](#), on page 381
- [show ip interface](#), on page 382

- [show ip lisp](#), on page 386
- [show ip lisp data-cache](#), on page 387
- [show ip lisp locator-hash](#), on page 388
- [show ip lisp map-cache](#), on page 389
- [show ip lisp statistics](#), on page 390
- [show ip lisp translate-cache](#), on page 391
- [show ip lisp version-hash](#), on page 392
- [show ip load-sharing](#), on page 393
- [show ip local-pt](#), on page 394
- [show ip local policy](#), on page 395
- [show ip logging](#), on page 396
- [show ip mbgp](#), on page 397
- [show ip mbgp](#), on page 399
- [show ip mbgp community](#), on page 400
- [show ip mbgp dampening](#), on page 401
- [show ip mbgp extcommunity](#), on page 402
- [show ip mbgp flap-statistics](#), on page 403
- [show ip mbgp neighbors](#), on page 404
- [show ip mbgp nexthop-database](#), on page 406
- [show ip mbgp nexthop](#), on page 407
- [show ip mbgp prefix-list](#), on page 408
- [show ip mbgp received-paths](#), on page 409
- [show ip msdp count](#), on page 410
- [show ip msdp event-history](#), on page 411
- [show ip msdp mesh-group](#), on page 412
- [show ip msdp peer](#), on page 413
- [show ip msdp policy statistics sa-policy in](#), on page 416
- [show ip msdp rpf](#), on page 418
- [show ip msdp sa](#), on page 419
- [show ip msdp sources](#), on page 421
- [show ip msdp statistics](#), on page 422
- [show ip msdp summary](#), on page 424
- [show ip nat-alias](#), on page 426
- [show ip nat max](#), on page 427
- [show ip nat statistics](#), on page 428
- [show ip nat timeout](#), on page 430
- [show ip nat translations](#), on page 431
- [show ip ospf](#), on page 433
- [show ip ospf border-routers](#), on page 438
- [show ip ospf database](#), on page 440
- [show ip ospf database database-summary](#), on page 442
- [show ip ospf database detail](#), on page 444
- [show ip ospf event-history](#), on page 449
- [show ip ospf event-history detail](#), on page 451
- [show ip ospf ha](#), on page 452
- [show ip ospf interface](#), on page 453

- [show ip ospf interface brief](#), on page 456
- [show ip ospf lsa-content-changed-list](#), on page 458
- [show ip ospf memory](#), on page 460
- [show ip ospf neighbors](#), on page 462
- [show ip ospf neighbors detail](#), on page 464
- [show ip ospf neighbors summary](#), on page 467
- [show ip ospf policy statistics](#), on page 469
- [show ip ospf request-list](#), on page 471
- [show ip ospf retransmission-list](#), on page 473
- [show ip ospf route](#), on page 475
- [show ip ospf route summary](#), on page 477
- [show ip ospf sham-links](#), on page 479
- [show ip ospf statistics](#), on page 483
- [show ip ospf summary-address](#), on page 487
- [show ip ospf traffic](#), on page 488
- [show ip ospf traps-queue](#), on page 492
- [show ip ospf virtual-links](#), on page 493
- [show ip ospf virtual-links brief](#), on page 497
- [show ip overlay-traffic](#), on page 498
- [show ip pim bitfield](#), on page 499
- [show ip pim config-sanity](#), on page 500
- [show ip pim df](#), on page 502
- [show ip pim event-history](#), on page 504
- [show ip pim fabric info](#), on page 505
- [show ip pim fabric legacy-vlans](#), on page 506
- [show ip pim group-range](#), on page 507
- [show ip pim host-proxy](#), on page 508
- [show ip pim interface](#), on page 509
- [show ip pim mdt](#), on page 513
- [show ip pim mdt bgp](#), on page 515
- [show ip pim mdt history interval](#), on page 516
- [show ip pim mdt receive](#), on page 517
- [show ip pim mdt send](#), on page 518
- [show ip pim neighbor](#), on page 519
- [show ip pim oif-list](#), on page 520
- [show ip pim policy statistics](#), on page 522
- [show ip pim policy statistics jp](#), on page 524
- [show ip pim route](#), on page 525
- [show ip pim rp-hash](#), on page 529
- [show ip pim rp](#), on page 530
- [show ip pim statistics](#), on page 533
- [show ip pim vrf](#), on page 535
- [show ip ping source-interface](#), on page 536
- [show ip ping source-interface vrf all](#), on page 537
- [show ip policy](#), on page 538
- [show ip prefix-list](#), on page 539

- [show ip process](#), on page 540
- [show ip rip policy statistics redistribute](#), on page 542
- [show ip route](#), on page 544
- [show ip router-id](#), on page 547
- [show ip rsvp](#), on page 548
- [show ip sla application](#), on page 550
- [show ip sla configuration](#), on page 551
- [show ip sla enhanced-history collection-statistics](#), on page 554
- [show ip sla enhanced-history distribution-statistics](#), on page 558
- [show ip sla group schedule](#), on page 559
- [show ip sla history](#), on page 560
- [show ip sla reaction-configuration](#), on page 562
- [show ip sla reaction-trigger](#), on page 563
- [show ip sla responder](#), on page 564
- [show ip sla statistics](#), on page 566
- [show ip ssh source-interface](#), on page 572
- [show ip ssh source-interface vrf all](#), on page 573
- [show ip static-route](#), on page 574
- [show ip stats](#), on page 576
- [show ip telnet source-interface](#), on page 577
- [show ip telnet source-interface vrf all](#), on page 578
- [show ip tftp source-interface](#), on page 579
- [show ip tftp source-interface vrf all](#), on page 580
- [show ip traceroute source-interface](#), on page 581
- [show ip traceroute source-interface vrf all](#), on page 582
- [show ip traffic](#), on page 583
- [show ip txlist list](#), on page 590
- [show ip udp relay](#), on page 591
- [show ip udp relay interface](#), on page 592
- [show ip udp relay object-group](#), on page 593
- [show ip verify source](#), on page 594
- [show ipv6 amt tunnel](#), on page 595
- [show ipv6 bgp](#), on page 597
- [show ipv6 bgp](#), on page 598
- [show ipv6 bgp](#), on page 599
- [show ipv6 bgp community](#), on page 600
- [show ipv6 bgp dampening](#), on page 601
- [show ipv6 bgp extcommunity](#), on page 602
- [show ipv6 bgp flap-statistics](#), on page 603
- [show ipv6 bgp neighbors](#), on page 604
- [show ipv6 bgp nexthop-database](#), on page 605
- [show ipv6 bgp nexthop](#), on page 606
- [show ipv6 bgp received-paths](#), on page 607
- [show ipv6 bgp regexp](#), on page 608
- [show ipv6 bgp summary](#), on page 609
- [show ipv6 dhcp-ldra](#), on page 610

- [show ipv6 dhcp-ldra statistics](#), on page 611
- [show ipv6 dhcp guard policy](#), on page 613
- [show ipv6 dhcp relay](#), on page 614
- [show ipv6 dhcp relay statistics](#), on page 615
- [show ipv6 local policy](#), on page 619
- [show ipv6 nd rguard policy](#), on page 620
- [show ipv6 neighbor binding](#), on page 621
- [show ipv6 neighbor binding mac](#), on page 622
- [show ipv6 pim bitfield](#), on page 623
- [show ipv6 pim df](#), on page 624
- [show ipv6 pim embed-rp](#), on page 626
- [show ipv6 pim event-history](#), on page 627
- [show ipv6 pim fabric info](#), on page 628
- [show ipv6 pim fabric legacy-vlans](#), on page 629
- [show ipv6 pim group-range](#), on page 630
- [show ipv6 pim interface show ipv6 pim interface](#), on page 631
- [show ipv6 pim neighbor](#), on page 634
- [show ipv6 pim oif-list](#), on page 635
- [show ipv6 pim policy statistics jp](#), on page 637
- [show ipv6 pim route](#), on page 638
- [show ipv6 pim rp-hash](#), on page 640
- [show ipv6 pim rp](#), on page 641
- [show ipv6 pim statistics](#), on page 644
- [show ipv6 pim vrf](#), on page 646
- [show ipv6 policy](#), on page 647
- [show ipv6 prefix-list](#), on page 648
- [show ipv6 route](#), on page 649
- [show ipv6 snooping capture-policy](#), on page 652
- [show ipv6 snooping counters vlan](#), on page 653
- [show ipv6 snooping events](#), on page 655
- [show ipv6 snooping features](#), on page 656
- [show ipv6 snooping messages](#), on page 657
- [show ipv6 snooping policies](#), on page 658
- [show ipv6 snooping policy](#), on page 659
- [show ipv6 snooping pss database](#), on page 661
- [show isis](#), on page 662
- [show isis adjacency](#), on page 666
- [show isis csnp](#), on page 669
- [show isis database](#), on page 671
- [show isis distribute-ls](#), on page 676
- [show isis event-history](#), on page 680
- [show isis hostname](#), on page 681
- [show isis interface](#), on page 682
- [show isis ipv6 redistribute route](#), on page 687
- [show isis ipv6 route-map statistics](#), on page 689
- [show isis ipv6 route](#), on page 691

- [show isis lslib](#), on page 695
- [show isis lsp free-list](#), on page 697
- [show isis mesh-group](#), on page 698
- [show isis non tlv overflow-list](#), on page 699
- [show isis redistribute route](#), on page 700
- [show isis route-map statistics](#), on page 702
- [show isis route](#), on page 704
- [show isis route is](#), on page 708
- [show isis rrm](#), on page 709
- [show isis segment-routing local-mapcache](#), on page 711
- [show isis segment-routing mapcache](#), on page 712
- [show isis segment-routing remote-srgb](#), on page 714
- [show isis segment-routing sids](#), on page 716
- [show isis spf-adjacency](#), on page 717
- [show isis spf-log](#), on page 719
- [show isis srm](#), on page 721
- [show isis ssn](#), on page 722
- [show isis statistics](#), on page 723
- [show isis summary-address show isis ipv6 summary-address](#), on page 724
- [show isis topology](#), on page 726
- [show isis traffic](#), on page 728
- [show itd](#), on page 730
- [show itd](#), on page 734
- [show itd session device-group](#), on page 738
- [show itd statistics](#), on page 739
- [show itd vrf](#), on page 741

show icam entries acl module inst

```
show icam entries acl module <module> inst <inst> [ history <num_intervals> ] [ sort { top <top_x> | sort-order
{ ascending | descending } | filter <f_f> [ exact ] | top <top_x> sort-order { ascending | descending } | top
<top_x> filter <f_f> [ exact ] | top <top_x> sort-order { ascending | descending } filter <f_f> [ exact ] | top
<top_x> filter <f_f> [ exact ] sort-order { ascending | descending } | sort-order { ascending | descending } top
<top_x> | sort-order { ascending | descending } filter <f_f> [ exact ] | sort-order { ascending | descending }
filter <f_f> [ exact ] top <top_x> | sort-order { ascending | descending } top <top_x> filter <f_f> [ exact ] |
filter <f_f> [ exact ] top <top_x> | filter <f_f> [ exact ] sort-order { ascending | descending } | filter <f_f> [
exact ] top <top_x> sort-order { ascending | descending } | filter <f_f> [ exact ] sort-order { ascending |
descending } top <top_x> } ] [ __readonly__ <module> <instance> [ <num_intervals> ] [ {
TABLE_ACL_entries <Feature> <Pkt_Type> <SourceIP_Mask_DestIP_Mask> <Action> <Intf_name>
<Stats> [ <Rate> ] } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
entries	TCAM Entries with result and stats
acl	ACL entries
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number
sort	(Optional) Sorted display
top	(Optional) Show top x% entries (Default:100%)
<i>top_x</i>	(Optional) x% of entries to be displayed
sort-order	(Optional) Choose the order of displaying sorted entries (Default:descending)
ascending	(Optional) Sort in Ascending order of Stats
descending	(Optional) Sort in Descending order of Stats
filter	(Optional) Feature to be filtered (Default:All)
<i>f_f</i>	(Optional) Enter feature to be filtered
exact	(Optional) Exact match for feature filter
history	(Optional) Show entries history
<i>num_intervals</i>	(Optional) Number of intervals to display

<i>__readonly__</i>	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>instance</i>	(Optional) Instance number
<i>num_intervals</i>	(Optional) Number of intervals displayed
TABLE_ACL_entries	(Optional) Table for ACL entries
<i>Feature</i>	(Optional) Feature name
<i>Pkt_Type</i>	(Optional) Packet type
<i>SourceIP_Mask_DestIP_Mask</i>	(Optional) IP addresses
<i>Action</i>	(Optional) Action
<i>Intf_name</i>	(Optional) Interface name
<i>Stats</i>	(Optional) Total stats
<i>Rate</i>	(Optional) Rate packets/sec

Command Mode

- /exec

show icam entries multicast module

```
show icam entries multicast module <module> [ history <num_intervals> ] [ sort { top <top_x> | sort-order { ascending | descending } | top <top_x> sort-order { ascending | descending } | sort-order { ascending | descending } top <top_x> } ] [ __readonly__ <module> [ <num_intervals> ] [ { TABLE_MULTICAST_entries <Vdc> <Table_Id> <Source_Mask> <Group_Mask> <Rpf> <Stats> [ <Rate> ] } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
entries	TCAM Entries with result and stats
multicast	Multicast entries
module	Module Number
<i>module</i>	Enter Module Number
sort	(Optional) Sorted display
top	(Optional) Show top x% entries (Default:100%)
<i>top_x</i>	(Optional) x% of entries to be displayed
sort-order	(Optional) Choose the order of displaying sorted entries (Default:Descending)
ascending	(Optional) Sort in Ascending order of Stats
descending	(Optional) Sort in Descending order of Stats
history	(Optional) Show entries history
<i>num_intervals</i>	(Optional) Number of intervals to display
<i>__readonly__</i>	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>num_intervals</i>	(Optional) Number of intervals displayed
TABLE_MULTICAST_entries	(Optional) Table for Multicast entries
<i>Vdc</i>	(Optional) VDC id
<i>Table_Id</i>	(Optional) Table id
<i>Source_Mask</i>	(Optional) Source address
<i>Group_Mask</i>	(Optional) Group address
<i>Rpf</i>	(Optional) RPF/Ordinal

<i>Stats</i>	(Optional) Total stats
<i>Rate</i>	(Optional) Rate packets/sec

Command Mode

- /exec

show icam prediction entries acl module inst

```
show icam prediction entries acl module <module> inst <inst> <YYYY> <Month> <Date> <Time> [ top
<top_x> ] [ __readonly__ <module> <instance> [ { TABLE_PREDICTION_ACL_entries <Feature>
<Pkt_Type> <Value_Mask> <Action> <Intf_name> <Stats> <Prediction> } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
prediction	Machine learning prediction
entries	TCAM Entries with result and stats
acl	ACL entries
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number
<i>YYYY</i>	Enter year in YYYY format
<i>Month</i>	Enter Month as Jan, Feb, Mar, ..., Oct, Nov, or Dec
<i>Date</i>	Enter day of month in dd format
<i>Time</i>	Enter hour, minutes, seconds as HH:MM:SS
top	(Optional) Show top x% entries (Default:1%)
<i>top_x</i>	(Optional) x% of entries to be displayed
__readonly__	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>instance</i>	(Optional) Instance number
TABLE_PREDICTION_ACL_entries	(Optional) Table for ACL entries prediction
<i>Feature</i>	(Optional) Feature name
<i>Pkt_Type</i>	(Optional) Packet type
<i>Value_Mask</i>	(Optional) Value mask
<i>Action</i>	(Optional) Action
<i>Intf_name</i>	(Optional) Interface name

<i>Stats</i>	(Optional) Current stats
<i>Prediction</i>	(Optional) Prediction

Command Mode

- /exec

show icam prediction entries multicast module

```
show icam prediction entries multicast module <module> <YYYY> <Month> <Date> <Time> [ top <top_x>
] [ __readonly__ <module> [ { TABLE_PREDICTION_MULTICAST_entries <Vdc> <Table_Id>
<Source_Mask> <Group_Mask> <Rpf> <Stats> <Prediction> } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
prediction	Machine learning prediction
entries	TCAM Entries with result and stats
multicast	Multicast entries
module	Module Number
<i>module</i>	Enter Module Number
<i>YYYY</i>	Enter year in YYYY format
<i>Month</i>	Enter Month as Jan, Feb, Mar, ..., Oct, Nov, or Dec
<i>Date</i>	Enter day of month in dd format
<i>Time</i>	Enter hour, minutes, seconds as HH:MM:SS
top	(Optional) Show top x% entries (Default:1%)
<i>top_x</i>	(Optional) x% of entries to be displayed
__readonly__	(Optional) Read Only
<i>module</i>	(Optional) Module number
TABLE_PREDICTION_MULTICAST_entries	(Optional) Table for multicast entries prediction
<i>Vdc</i>	(Optional) VDC id
<i>Table_Id</i>	(Optional) Table id
<i>Source_Mask</i>	(Optional) Source address
<i>Group_Mask</i>	(Optional) Group address
<i>Rpf</i>	(Optional) RPF/Ordinal
<i>Stats</i>	(Optional) Current stats
<i>Prediction</i>	(Optional) Prediction

Command Mode

- /exec

show icam prediction resource acl_tcam module inst trend

```
show icam prediction resource acl_tcam module <module> inst <inst> trend [ __readonly__ <module>
<instance> [ { TABLE_PREDICTION_ACL_feature <Feature> <Dir> <TCAM> <BANK> <Feature_Entries1>
<Free_Entries1> <Percent_Util1> <Feature_Entries2> <Free_Entries2> <Percent_Util2> <Feature_Entries3>
<Free_Entries3> <Percent_Util3> } ] [ <mod> <inst> { TABLE_PREDICTION_ACL_tcam <Tcam_no>
<Bank_no> <Used1> <Free1> <Util1> <Used2> <Free2> <Util2> <Used3> <Free3> <Util3> } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
prediction	Machine learning prediction
resource	TCAM Resource utilization
acl_tcam	ACL TCAM resource
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number
trend	ACL Prediction Trend
__readonly__	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>instance</i>	(Optional) Instance number
TABLE_PREDICTION_ACL_feature	(Optional) ACL Feature utilization predictions
<i>Feature</i>	(Optional) Feature name
<i>Dir</i>	(Optional) Direction
<i>TCAM</i>	(Optional) TCAM entry
<i>BANK</i>	(Optional) BANK entry
<i>Feature_Entries1</i>	(Optional) +24Hr Feature_Entries
<i>Free_Entries1</i>	(Optional) +24Hr Free_Entries
<i>Percent_Util1</i>	(Optional) +24Hr Percent_Util
<i>Feature_Entries2</i>	(Optional) +48Hr Feature_Entries
<i>Free_Entries2</i>	(Optional) +48Hr Free_Entries

<i>Percent_Util2</i>	(Optional) +48Hr Percent_Util
<i>Feature_Entries3</i>	(Optional) +1wk Feature_Entries
<i>Free_Entries3</i>	(Optional) +1wk Free_Entries
<i>Percent_Util3</i>	(Optional) +1wk Percent_Util
<i>mod</i>	(Optional) Module number
<i>inst</i>	(Optional) Instance number
TABLE_PREDICTION_ACL_tcam	(Optional) ACL TCAM utilization predictions
<i>Tcam_no</i>	(Optional) Tcam number
<i>Bank_no</i>	(Optional) Bank number
<i>Used1</i>	(Optional) +24Hr Used
<i>Free1</i>	(Optional) +24Hr Free
<i>Util1</i>	(Optional) +24Hr Percent_Util
<i>Used2</i>	(Optional) +48Hr Used
<i>Free2</i>	(Optional) +48Hr Free
<i>Util2</i>	(Optional) +48Hr Percent_Util
<i>Used3</i>	(Optional) +1wk Used
<i>Free3</i>	(Optional) +1wk Free
<i>Util3</i>	(Optional) +1wk Percent_Util

Command Mode

- /exec

show icam prediction resource module inst

```
show icam prediction resource { acl_tcam | fib_tcam | l2_table } module <module> inst <inst> <YYYY>
<Month> <Date> <Time> [ __readonly__ <module> <instance> [ { TABLE_PREDICTION_ACL_feature
<Feature> <Dir> <TCAM> <BANK> <Feature_Entries> <Free_Entries> <Percent_Util> } ] [ <mod> <inst>
{ TABLE_PREDICTION_ACL_tcam <Tcam_no> <Bank_no> <Used> <Free> <Percent_Util> } ] [ {
TABLE_PREDICTION_FIB_tcam <Class> <Used_Entries> <Max_Entries> <Percent_Util> } ] [ {
TABLE_PREDICTION_L2_TABLE <Used_Entries> <Free_Entries> <Percent_Util> } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
prediction	Machine learning prediction
resource	TCAM Resource utilization
acl_tcam	ACL TCAM resource
fib_tcam	FIB TCAM resource
l2_table	L2 TABLE resource
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number
YYYY	Enter year in YYYY format
<i>Month</i>	Enter Month as Jan, Feb, Mar, ..., Oct, Nov, or Dec
<i>Date</i>	Enter day of month in dd format
<i>Time</i>	Enter hour, minutes, seconds as HH:MM:SS
__readonly__	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>instance</i>	(Optional) Instance number
TABLE_PREDICTION_ACL_feature	(Optional) ACL Feature utilization predictions
<i>Feature</i>	(Optional) Feature name
<i>Dir</i>	(Optional) Direction
<i>TCAM</i>	(Optional) TCAM entry

<i>BANK</i>	(Optional) BANK entry
<i>Feature_Entries</i>	(Optional) Feature_Entries
<i>Free_Entries</i>	(Optional) Free_Entries
<i>Percent_Util</i>	(Optional) Percent_Util
<i>mod</i>	(Optional) Module number
<i>inst</i>	(Optional) Instance number
TABLE_PREDICTION_ACL_tcam	(Optional) ACL TCAM utilization predictions
<i>Tcam_no</i>	(Optional) Tcam number
<i>Bank_no</i>	(Optional) Bank number
<i>Used</i>	(Optional) Used
<i>Free</i>	(Optional) Free
<i>Percent_Util</i>	(Optional) Percent_Util
TABLE_PREDICTION_FIB_tcam	(Optional) FIB TCAM utilization predictions
<i>Class</i>	(Optional) FIB class
<i>Used_Entries</i>	(Optional) Used entries
<i>Max_Entries</i>	(Optional) Max entries
<i>Percent_Util</i>	(Optional) Percent_Util
TABLE_PREDICTION_L2_TABLE	(Optional) L2 TABLE Util prediction
<i>Used_Entries</i>	(Optional) Used
<i>Free_Entries</i>	(Optional) Free
<i>Percent_Util</i>	(Optional) Percent_Util

Command Mode

- /exec

show icam resource module inst

```
show icam resource { acl_tcam | fib_tcam | l2_table } module <module> inst <inst> [ history <num_intervals> ] [ __readonly__ <module> <instance> [ { TABLE_feature_resource <Feature> <TCAM> <BANK> [ { TABLE_ingress_stats <Feature_Entries> <Free_Entries> <Percent_Util> <Timestamp> } ] } ] [ { TABLE_egress_feature_resource <Feature> <TCAM> <BANK> [ { TABLE_egress_stats <Feature_Entries> <Free_Entries> <Percent_Util> <Timestamp> } ] } ] [ <mod> <inst> { TABLE_tcam_bank_utilization <Tcam_no> <Bank_no> [ { TABLE_tcam_bank_stats <Used> <Free> <Percent_Util> <Timestamp> } ] } ] [ { TABLE_global_configs <Atomic_Update> <Bank_Chain_Mode> <Dynamic_Bank_Mapping> <LOU_Threshold_Value> } ] [ { TABLE_fib_resource <Class> [ { TABLE_fib_stats <Used_Entries> <Max_Entries> <Percent_Util> <Timestamp> } ] } ] [ { TABLE_l2_table_resource <Total_Entries> <Used_Entries> <Percent_Util> <Timestamp> } ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
resource	TCAM Resource utilization
acl_tcam	ACL TCAM resource
fib_tcam	FIB TCAM resource
l2_table	L2 TABLE resource
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number
history	(Optional) Show resource history
<i>num_intervals</i>	(Optional) Number of intervals in history
<i>__readonly__</i>	(Optional) Read Only
<i>module</i>	(Optional) Module number
<i>instance</i>	(Optional) Instance number
TABLE_feature_resource	(Optional) Table for ingress feature resources
<i>Feature</i>	(Optional) Feature name
<i>TCAM</i>	(Optional) TCAM entry
<i>BANK</i>	(Optional) BANK entry
TABLE_ingress_stats	(Optional) Table for ingress feature stats

<i>Feature_Entries</i>	(Optional) Feature_Entries
<i>Free_Entries</i>	(Optional) Free_Entries
<i>Percent_Util</i>	(Optional) Percent_Util
<i>Timestamp</i>	(Optional) Timestamp
TABLE_egress_feature_resource	(Optional) Table for egress feature resources
<i>Feature</i>	(Optional) Feature name
<i>TCAM</i>	(Optional) TCAM entry
<i>BANK</i>	(Optional) BANK entry
TABLE_egress_stats	(Optional) Table for egress feature stats
<i>Feature_Entries</i>	(Optional) Feature_Entries
<i>Free_Entries</i>	(Optional) Free_Entries
<i>Percent_Util</i>	(Optional) Percent_Util
<i>Timestamp</i>	(Optional) Timestamp
<i>mod</i>	(Optional) Module number
<i>inst</i>	(Optional) Instance number
TABLE_tcam_bank_utilization	(Optional) Table for tcam and bank utilization
<i>Tcam_no</i>	(Optional) Tcam number
<i>Bank_no</i>	(Optional) Bank number
TABLE_tcam_bank_stats	(Optional) Table for tcam and bank stats
<i>Used</i>	(Optional) Used
<i>Free</i>	(Optional) Free
<i>Percent_Util</i>	(Optional) Percent_Util
<i>Timestamp</i>	(Optional) Timestamp
TABLE_global_configs	(Optional) TABLE_global_configs
<i>Atomic_Update</i>	(Optional) Atomic_Update
<i>Bank_Chain_Mode</i>	(Optional) Bank_Chain_Mode
<i>Dynamic_Bank_Mapping</i>	(Optional) Dynamic_Bank_Mapping
<i>LOU_Threshold_Value</i>	(Optional) LOU_Threshold_Value
TABLE_fib_resource	(Optional) Table for fib resources

<i>Class</i>	(Optional) FIB class
TABLE_fib_stats	(Optional) Table for fib resource stats
<i>Used_Entries</i>	(Optional) Used entries
<i>Max_Entries</i>	(Optional) Max entries
<i>Percent_Util</i>	(Optional) Percent_Util
<i>Timestamp</i>	(Optional) Timestamp
TABLE_l2_table_resource	(Optional) Table for L2 Resources
<i>Total_Entries</i>	(Optional) Total L2 entries
<i>Used_Entries</i>	(Optional) Used L2 entries
<i>Percent_Util</i>	(Optional) Percent_Util
<i>Timestamp</i>	(Optional) Timestamp

Command Mode

- /exec

show icam scale

```
show icam scale [ { { l2-switching [ mac-addresses | mst-instances | mst-vports | rpvt-vports | rpvt-vlans | vlans ] } | { multicast-routing [ multicast-routes | igmp-groups | pim-neighbors | outgoing-interfaces ] } | { unicast-routing [ bfd-sessions | eigrp-routes | ipv4-arp | ipv4-host-routes | ipv6-host-routes | ipv4-isis-routes | ospf-size ] } | { vxlan [ test ] } } ] [ history <num_intervals> | utilization | thresholds ] [ __readonly__ [ <Info_Thres> <Warn_Thres> <Crit_Thres> ] [ { TABLE_technology <Technology> [ { TABLE_feature <Feature> <Verified_Scale> <Config_Scale> [ { TABLE_feature_stats <Used_Entries> <Cur_Util> [ <Thres_Exceeded> <Polled_TS> ] [ <Avg_Util> ] [ <Week_Util> <Week_TS> ] [ <Peak_Util> <Peak_TS> ] [ <Info_Thres_Exceed> <Info_Thres_Exceed_TS> <Warn_Thres_Exceed> <Warn_Thres_Exceed_TS> <Crit_Thres_Exceed> <Crit_Thres_Exceed_TS> ] } ] } ] ] ] ] ] ] ]
```

Syntax Description

show	Show running system information
icam	intelligent CAM
scale	Verified scale
l2-switching	(Optional) Layer 2 switching
multicast-routing	(Optional) Multicast routing
unicast-routing	(Optional) Unicast routing
vxlan	(Optional) VxLAN
mac-addresses	(Optional) MAC addresses
mst-instances	(Optional) MST instances
mst-vports	(Optional) MST virtual ports
rpvst-vports	(Optional) RPVST virtual ports
rpvst-vlans	(Optional) RPVST VLANs
vlans	(Optional) VLANs
multicast-routes	(Optional) Multicast routes
igmp-groups	(Optional) IGMP groups
pim-neighbors	(Optional) PIM neighbors
outgoing-interfaces	(Optional) Outgoing interfaces
bfd-sessions	(Optional) BFD sessions
eigrp-routes	(Optional) EIGRP routes
ipv4-arp	(Optional) IPv4 ARP
ipv4-host-routes	(Optional) IPv4 host routes

ipv6-host-routes	(Optional) IPv6 host routes
ipv4-isis-routes	(Optional) IPv4 IS-IS routes
ospf-size	(Optional) OSPF size
test	(Optional) VxLAN test
history	(Optional) Show scale history
<i>num_intervals</i>	(Optional) Number of intervals in history
utilization	(Optional) Show utilization statistics
thresholds	(Optional) Show thresholds statistics
__readonly__	(Optional) Read Only
<i>Info_Thres</i>	(Optional) Configured info threshold percent
<i>Warn_Thres</i>	(Optional) Configured warning threshold percent
<i>Crit_Thres</i>	(Optional) Configured critical threshold percent
TABLE_technology	(Optional) Table technology
<i>Technology</i>	(Optional) Technology name
TABLE_feature	(Optional) Table feature
<i>Feature</i>	(Optional) Feature name
<i>Verified_Scale</i>	(Optional) Verified scale
<i>Config_Scale</i>	(Optional) Configured scale
TABLE_feature_stats	(Optional) Table feature stats
<i>Used_Entries</i>	(Optional) Used entries
<i>Cur_Util</i>	(Optional) Current utilization
<i>Thres_Exceeded</i>	(Optional) Threshold type exceeded
<i>Polled_TS</i>	(Optional) Polled timestamp
<i>Avg_Util</i>	(Optional) Average utilization
<i>Week_Util</i>	(Optional) 1 week utilization
<i>Week_TS</i>	(Optional) 1 week peak utilization timestamp
<i>Peak_Util</i>	(Optional) Peak utilization
<i>Peak_TS</i>	(Optional) Peak utilization timestamp
<i>Info_Thres_Exceed</i>	(Optional) Number of times info threshold exceeded

<i>Info_Thres_Exceed_TS</i>	(Optional) Last info threshold exceeded timestamp
<i>Warn_Thres_Exceed</i>	(Optional) Number of times warning threshold exceeded
<i>Warn_Thres_Exceed_TS</i>	(Optional) Last warning threshold exceeded timestamp
<i>Crit_Thres_Exceed</i>	(Optional) Number of times critical threshold exceeded
<i>Crit_Thres_Exceed_TS</i>	(Optional) Last critical threshold exceeded timestamp

Command Mode

- /exec

show ieth-header-decode

show ieth-header-decode <ieth>

Syntax Description

show	Show running system information
ieth-header-decode	Show decode of ieth header
<i>ieth</i>	ieth header in hex (0xFF...) or string (FF..) form

Command Mode

- /exec

show imp client

show imp client

Syntax Description

show	Show running system information
imp	ipsec management process
client	Show ipsec clients name

Command Mode

- /exec

show imp client sa

show imp client sa

Syntax Description

show	Show running system information
imp	IPSec management process
client	IMP client
sa	Display all SAs

Command Mode

- /exec

show incompatibility-all system

```
show incompatibility-all { system <uri0> | nxos <uri1> } [ __readonly__ { [ TABLE_incompat_all <Str1> [
<Serv> ] [ <Cap> ] [ <Desc> ] [ <Req> ] [ <Enable> ] [ <Dynamic> ] } ]
```

Syntax Description

show	Show running system information
incompatibility-all	Show incompatible configurations for the entire system
system	show incompatibilities with an image
<i>uri0</i>	Enter image uri
nxos	show incompatibilities with an image
<i>uri1</i>	Enter image uri
<i>__readonly__</i>	(Optional)
TABLE_incompat_all	(Optional) Show incompatibility system table
<i>Str1</i>	(Optional)
<i>Serv</i>	(Optional)
<i>Cap</i>	(Optional)
<i>Desc</i>	(Optional)
<i>Req</i>	(Optional)
<i>Enable</i>	(Optional)
<i>Dynamic</i>	(Optional)

Command Mode

- /exec

show incompatibility system

```
show incompatibility { system <uri0> | nxos <uri1> } [ __readonly__ { [ TABLE_incompat <Str1> [ <Serv>
] [ <Cap> ] [ <Desc> ] [ <Req> ] [ <Enable> ] ] [ <Dynamic> ] } ]
```

Syntax Description

show	Show running system information
incompatibility	Show incompatible configurations
system	show incompatibilities with an image
<i>uri0</i>	Enter image uri
nxos	show incompatibilities with an image
<i>uri1</i>	Enter image uri
<i>__readonly__</i>	(Optional)
TABLE_incompat	(Optional) Show incompatibility system table
<i>Str1</i>	(Optional)
<i>Serv</i>	(Optional)
<i>Cap</i>	(Optional)
<i>Desc</i>	(Optional)
<i>Req</i>	(Optional)
<i>Enable</i>	(Optional)
<i>Dynamic</i>	(Optional)

Command Mode

- /exec

show install

```
show install { inactive | active [ brief ] | committed } [ __readonly__ { <curr_nxos_image> [ TABLE_smu_list  
<install_smu_id> + ] [ TABLE_package_list <package_id> ] } ]
```

Syntax Description

show	Show running system information
install	Install related show commands
inactive	Inactive packages
active	Active packages
brief	(Optional) Brief
committed	Committed packages
__readonly__	(Optional)
<i>curr_nxos_image</i>	(Optional) NXOS image
TABLE_smu_list	(Optional)
<i>install_smu_id</i>	(Optional) install operation smu identifier
TABLE_package_list	(Optional)
<i>package_id</i>	(Optional) Package name

Command Mode

- /exec

show install all failed-standby

show install all failed-standby [__readonly__ { [TABLE_installFailStandby <Str1>] }]

Syntax Description

show	Show running system information
install	Show the software install impact between two images
all	Show install all information
failed-standby	show log from failed standby
__readonly__	(Optional)
TABLE_installFailStandby	(Optional) Install failed-standby table
Str1	(Optional)

Command Mode

- /exec

show install all failure-reason

```
show install all failure-reason [ __readonly__ { [ TABLE_installFailReason <installFailReasonStr> ] } ]
```

Syntax Description

show	Show running system information
install	Show the software install impact between two images
all	show install all information
failure-reason	Show failure reason for the last install all
__readonly__	(Optional)
TABLE_installFailReason	(Optional) Install failure-reason table
<i>installFailReasonStr</i>	(Optional)

Command Mode

- /exec

show install all impact

show install all impact [nxos <uri>] + [non-disruptive]

Syntax Description

show	Show running system information
install	Show the software install impact between two images
all	show install all information
impact	show impact of the install all command
nxos	(Optional) boot-variable name
<i>uri</i>	(Optional) Enter image uri
non-disruptive	(Optional) non-disruptive show install

Command Mode

- /exec

show install all status

show install all status

Syntax Description

show	Show running system information
install	Show the software install impact between two images
all	show install all information
status	show status of the current or last install all

Command Mode

- /exec

show install all time-stats

show install all time-stats [detail | handshake]

Syntax Description

show	Show running system information
install	Show the software install impact between two images
all	show install all information
time-stats	show overall time statistics of the last install all
detail	(Optional) show detailed time statistics of the last install all
handshake	(Optional) show handshake time statistics for sysmgr and lc processes of the last install all

Command Mode

- /exec

show install impact

show install impact <uri0> <uri1>

Syntax Description

show	Show running system information
install	Show the software install impact between two images
impact	impact system_uri {active_system_uri/active_kickstart_uri}
<i>uri0</i>	Enter system URI
<i>uri1</i>	Enter active URI

Command Mode

- /exec

show install impact

show install impact <uri0>

Syntax Description

show	Show running system information
install	Show the software install impact between two images
impact	impact system_uri {active_system_uri/active_kickstart_uri}
<i>uri0</i>	Enter system URI

Command Mode

- /exec

show install impact detail

show install impact <uri0> detail

Syntax Description

show	Show running system information
install	Show the software install impact between two images
impact	impact system_uri {active_system_uri/active_kickstart_uri}
<i>uri0</i>	Enter system URI
detail	Show detailed install impact of given system image

Command Mode

- /exec

show install log

```
show install log { [ <id> | from <id1> ] [ detail ] [ reverse ] [ last ] } [ __readonly__ { current_time <curr_time>
[ TABLE_show_log_output <install_id> <install_log_entry> + ] } ]
```

Syntax Description

show	Show running system information
install	Install related show commands
log	log
<i>id</i>	(Optional) Install Identifies
from	(Optional) Starting at this install identifier
<i>id1</i>	(Optional) Install Identifier
detail	(Optional) Detailed information including impacted processes
reverse	(Optional) Displays the logs in reverse order
last	(Optional) Display the logs for last install operation
__readonly__	(Optional)
current_time	(Optional) current time
<i>curr_time</i>	(Optional) current time
TABLE_show_log_output	(Optional)
<i>install_id</i>	(Optional) install operation id
<i>install_log_entry</i>	(Optional) install log entry

Command Mode

- /exec

show install packages

```
show install packages [ __readonly__ { <curr_nxos_image> [ TABLE_package_list <package_name>  
<version> <state> ] } ]
```

Syntax Description

show	Show running system information
install	Install related show commands
packages	All packages
__readonly__	(Optional)
<i>curr_nxos_image</i>	(Optional) NXOS image
TABLE_package_list	(Optional)
<i>package_name</i>	(Optional) Package name
<i>version</i>	(Optional) Package version
<i>state</i>	(Optional) package state

Command Mode

- /exec

show install patches

```
show install patches [ __readonly__ { <curr_nxos_image> [ TABLE_smu_list <install_smu_id>
<install_smu_state> [ TABLE_module_list <install_modno> <install_mod_smu_state> ] ] } ]
```

Syntax Description

show	Show running system information
install	Install related show commands
patches	All Patches
__readonly__	(Optional)
TABLE_smu_list	(Optional)
<i>curr_nxos_image</i>	(Optional) NXOS image
<i>install_smu_id</i>	(Optional) install operation smu identifier
<i>install_smu_state</i>	(Optional) install operation smu state
TABLE_module_list	(Optional)
<i>install_modno</i>	(Optional) install operation module number
<i>install_mod_smu_state</i>	(Optional) install operation module state

Command Mode

- /exec

show interface

```
show interface <iftun_desc> [ __readonly__ TABLE_interface <interface> <state> [ <state_rsn_desc> ] [
<desc> ] <admin-state> { <tunnel-ipv4> | <tunnel-ipv6> } <mtu> <bandwidth> <encap-type>
<keepalive-period> <keepalive-retries> { <src-ipv4> | <src-ipv6> } <src-intf> { <dest-ipv4> | <dest-ipv6> }
<dest-hostname> <vrf_name> <wccp_header> <ttl_val> <tunnel_pmtud_age_time> <tunnel_pmtud_min_mtu>
<tunnel_pmtud> <tunnel_pgm_mtu> <tunnel_rx_pkt_count> <tunnel_rx_byte_count> <tunnel_rx_rate>
<tunnel_tx_pkt_count> <tunnel_tx_byte_count> <tunnel_tx_rate> <tunnel_clear_counter> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>iftun_desc</i>	Enter tunnel interface number
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>desc</i>	(Optional) Interface description
<i>admin-state</i>	(Optional)
<i>tunnel-ipv4</i>	(Optional) interface IPv4 address
<i>mtu</i>	(Optional) interface Maximum Transmission Unit
<i>bandwidth</i>	(Optional) interface Bandwidth in kilobits
<i>encap-type</i>	(Optional)
<i>keepalive-period</i>	(Optional) keealive period
<i>keepalive-retries</i>	(Optional) number of retries
<i>src-ipv4</i>	(Optional) tunnel source IPv4 address
<i>src-intf</i>	(Optional) tunnel source interface
<i>dest-ipv4</i>	(Optional) tunnel destination IPv4 address
<i>dest-hostname</i>	(Optional) tunnel destination hostname
<i>vrf_name</i>	(Optional) transport VRF name
<i>wccp_header</i>	(Optional) wccp header

<i>ttl_val</i>	(Optional) tunnel time to live value
<i>tunnel_pmtud_age_time</i>	(Optional) tunnel path MTU discovery age time
<i>tunnel_pmtud_min_mtu</i>	(Optional) tunnel path MTU discovery min mtu
<i>tunnel_pmtud</i>	(Optional) tunnel path MTU discovered
<i>tunnel_pgm_mtu</i>	(Optional) tunnel actual programmed MTU
<i>tunnel_rx_pkt_count</i>	(Optional) total number of packets received
<i>tunnel_rx_byte_count</i>	(Optional) total number of bytes received
<i>tunnel_rx_rate</i>	(Optional) packets input rate per 5 minutes
<i>tunnel_tx_pkt_count</i>	(Optional) total number of packets transmitted
<i>tunnel_tx_byte_count</i>	(Optional) total number of bytes transmitted
<i>tunnel_tx_rate</i>	(Optional) packets transmitted per 5 minutes
<i>tunnel_clear_counter</i>	(Optional) Last clearing of show interface counters

Command Mode

- /exec

show interface

```

show interface <ifid> [ brief | quick ] [ __readonly__ TABLE interface <interface> [ <desc> ] [ [ <svi_if_index>
] [ <svi_admin_state> ] [ <svi_rsn_desc> ] [ <svi_line_proto> ] [ <svi_hw> ] [ <svi_mac> ] [ <svi_desc> ] [
<svi_ip_addr> ] [ <svi_ip_mask> ] [ <svi_mtu> ] [ <svi_bw> ] [ <svi_delay> ] [ [ <svi_tx_load> ] [
<svi_rx_load> ] ] [ [ <svi_carrier_delay_sec> ] [ <svi_carrier_delay_msec> ] [ <svi_arp_type> ] [
<svi_arp_timeout> ] ] [ [ <svi_time_last_cleared> ] ] [ { [ TABLE_sec_vlan ] [ <sec_vlan> ] [ <sec_vlan_type>
] } ] [ [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [ <eth_load_interval1_tx> ]
[ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [ <eth_inrate2_bits> ] [
<eth_inrate2_pkts> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [ <eth_load_interval3> ] [
<eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [ <eth_outrate3_bits> ] [ <eth_outrate3_pkts> ] [ <eth_l2_ucastpkts>
] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [ <eth_l2_mcastbytes> ] [ <eth_l2_bcastpkts> ] [
<eth_l2_bcastbytes> ] [ <eth_l3in_ucastpkts> ] [ <eth_l3in_ucastbytes> ] [ <eth_l3in_mcastpkts> ] [
<eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [ <eth_l3in_bcastbytes> ] [ <eth_l3out_ucastpkts> ] [
<eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_mcastbytes> ] [ <eth_l3out_bcastpkts> ] [
<eth_l3out_bcastbytes> ] [ <eth_l3in_routed_pkts> ] [ <eth_l3in_routed_bytes> ] [ <eth_l3out_routed_pkts>
] [ <eth_l3out_routed_bytes> ] [ <eth_l3avg1_inbytes> ] [ <eth_l3avg1_inpkts> ] [ <eth_l3avg1_outbytes>
] [ <eth_l3avg1_outpkts> ] [ <eth_l3avg2_inbytes> ] [ <eth_l3avg2_inpkts> ] [ <eth_l3avg2_outbytes> ] [
<eth_l3avg2_outpkts> ] [ <eth_l3avg3_inbytes> ] [ <eth_l3avg3_inpkts> ] [ <eth_l3avg3_outbytes> ] [
<eth_l3avg3_outpkts> ] [ <eth_inpkts> ] [ <eth_inbytes> ] [ <eth_nobuf> ] [ <eth_inbcast> ] [ <eth_inmcast>
] [ <eth_inucast> ] [ <eth_ingiants> ] [ <eth_ipmcast> ] [ <eth_inhw_switched> ] [ <eth_insw_switched> ] [
<eth_runts> ] [ <eth_storm_supp> ] [ <eth_throtles> ] [ <eth_inerr> ] [ <eth_crc> ] [ <eth_ecc> ] [ <eth_frame>
] [ <eth_overrun> ] [ <eth_ignored> ] [ <eth_watchdog> ] [ <eth_outbcast> ] [ <eth_outmcast> ] [
<eth_outucast> ] [ <eth_outgiants> ] [ <eth_inpause> ] [ <eth_dribble> ] [ <eth_in_ifdown_drops> ] [
<eth_bad_eth> ] [ <eth_bad_proto> ] [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_underrun> ] [
<eth_outhw_switched> ] [ <eth_outsw_switched> ] [ <eth_outerr> ] [ <eth_coll> ] [ <eth_resets> ] [
<eth_babbles> ] [ <eth_latecoll> ] [ <eth_deferred> ] [ <eth_lostcarrier> ] [ <eth_nocarrier> ] [ <eth_outpause>
] [ <eth_buffail> ] [ <eth_bufswapped> ] [ <eth_arpdrops> ] [ <eth_out_ifdown_drops> ] [ <eth_single_coll>
] [ <eth_multi_coll> ] [ <eth_excess_coll> ] [ <eth_jabbers> ] [ <eth_shortframe> ] [ <eth_indiscard> ] [
<eth_bad_encap> ] [ <eth_outcrc> ] [ <eth_symbol> ] [ <eth_out_drops> ] [ <eth_sqetest> ] [ <eth_inb64>
] [ <eth_inb65_127> ] [ <eth_inb128_255> ] [ <eth_inb256_511> ] [ <eth_inb512_1023> ] [
<eth_inb1024_1518> ] [ <eth_inb1519_1548> ] [ <eth_intrunk> ] [ <eth_outb64> ] [ <eth_outb65_127> ] [
<eth_outb128_255> ] [ <eth_outb256_511> ] [ <eth_outb512_1023> ] [ <eth_outb1024_1518> ] [
<eth_outb1519_1548> ] [ <eth_outtrunk> ] [ <eth_bpdu_outlost> ] [ <eth_cos0_outlost> ] [ <eth_cos1_outlost>
] [ <eth_cos2_outlost> ] [ <eth_cos3_outlost> ] [ <eth_cos4_outlost> ] [ <eth_cos5_outlost> ] [
<eth_cos6_outlost> ] [ <eth_cos7_outlost> ] [ <eth_fcoe_in_pkts> ] [ <eth_fcoe_in_octets> ] [
<eth_fcoe_out_pkts> ] [ <eth_fcoe_out_octets> ] [ <eth_nfcoe_in_pkts> ] [ <eth_nfcoe_in_octets> ] [
<eth_nfcoe_out_pkts> ] [ <eth_nfcoe_out_octets> ] [ <eth_eee_atx_lpi_msec> ] [ <eth_eee_arcv_lpi_msec>
] [ <eth_eee_atx_lpi_transitions> ] [ <eth_eee_arcv_lpi_transitions> ] [ <eth_phy_ber_count> ] [
<eth_phy_errblks_count> ] ] [ [ <svi_routed_pkts_in> ] [ <svi_routed_bytes_in> ] [ <svi_routed_pkts_out>
] [ <svi_routed_bytes_out> ] [ <svi_ucast_pkts_in> ] [ <svi_ucast_bytes_in> ] [ <svi_mcast_pkts_in> ] [
<svi_mcast_bytes_in> ] [ <svi_ucast_pkts_out> ] [ <svi_ucast_bytes_out> ] [ <svi_mcast_pkts_out> ] [
<svi_mcast_bytes_out> ] [ <svi_ipv4_ucast_pkts_in> ] [ <svi_ipv4_ucast_bytes_in> ] [
<svi_ipv4_ucast_pkts_out> ] [ <svi_ipv4_ucast_bytes_out> ] [ <svi_ipv4_mcast_pkts_in> ] [
<svi_ipv4_mcast_bytes_in> ] [ <svi_ipv4_mcast_pkts_out> ] [ <svi_ipv4_mcast_bytes_out> ] [
<svi_ipv6_ucast_pkts_in> ] [ <svi_ipv6_ucast_bytes_in> ] [ <svi_ipv6_ucast_pkts_out> ] [
<svi_ipv6_ucast_bytes_out> ] [ <svi_ipv6_mcast_pkts_in> ] [ <svi_ipv6_mcast_bytes_in> ] [
<svi_ipv6_mcast_pkts_out> ] [ <svi_ipv6_mcast_bytes_out> ] [ <svi_average_input_bits> ] [
<svi_average_input_packets> ] [ <svi_average_output_bits> ] [ <svi_average_output_packets> ] [
<svi_rate_in_mins> ] ] [ [ <svi_reliability> ] ] [ <switchport> ] ]

```


Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid</i>	Enter interface type and number in module/slot format
brief	(Optional) Show brief info of interface
quick	(Optional) Show info of interface skipping stats
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>desc</i>	(Optional) Interface description
<i>svi_if_index</i>	(Optional) Interface
<i>svi_admin_state</i>	(Optional)
<i>svi_rsn_desc</i>	(Optional) Interface state reason detailed
<i>svi_line_proto</i>	(Optional)
<i>svi_hw</i>	(Optional) Hardware
<i>svi_mac</i>	(Optional) Address
<i>svi_desc</i>	(Optional) Interface Description
<i>svi_ip_addr</i>	(Optional) IP Address
<i>svi_ip_mask</i>	(Optional) IP address mask
<i>svi_mtu</i>	(Optional) MTU size in bytes
<i>svi_bw</i>	(Optional) Bandwidth in kilobits
<i>svi_delay</i>	(Optional) Throughput delay (tens of microseconds)
<i>svi_tx_load</i>	(Optional) Tx Load
<i>svi_rx_load</i>	(Optional) Rx Load
<i>svi_carrier_delay_sec</i>	(Optional) carrier delay value in seconds
<i>svi_carrier_delay_msec</i>	(Optional) carrier delay value in milli-seconds
<i>svi_arp_type</i>	(Optional) ARP type
<i>svi_arp_timeout</i>	(Optional) ARP timeout value
<i>svi_time_last_cleared</i>	(Optional) Time last cleared

<i>TABLE_sec_vlan</i>	(Optional) secondary vlans
<i>sec_vlan</i>	(Optional) vlan id
<i>sec_vlan_type</i>	(Optional) secondary vlan type
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec
<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) IPv4 L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) IPv4 L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) IPv4 L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) IPv4 L3 in switched mcast bytes

<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcst pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcst bytes
<i>eth_l3out_ucastpkts</i>	(Optional) IPv4 L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) IPv4 L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) IPv4 L3 out switched mcast pkts
<i>eth_l3out_mcastbytes</i>	(Optional) IPv4 L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcst pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcst bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_l3avg2_inbytes</i>	(Optional) Load interval 2 L3 average in switched bytes
<i>eth_l3avg2_inpkts</i>	(Optional) Load interval 2 L3 average in switched pkts
<i>eth_l3avg2_outbytes</i>	(Optional) Load interval 2 L3 average out switched bytes
<i>eth_l3avg2_outpkts</i>	(Optional) Load interval 2 L3 average out switched pkts
<i>eth_l3avg3_inbytes</i>	(Optional) Load interval 3 L3 average in switched bytes
<i>eth_l3avg3_inpkts</i>	(Optional) Load interval 3 L3 average in switched pkts
<i>eth_l3avg3_outbytes</i>	(Optional) Load interval 3 L3 average out switched bytes
<i>eth_l3avg3_outpkts</i>	(Optional) Load interval 3 L3 average out switched pkts
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_inbcst</i>	(Optional) Broadcasts
<i>eth_inmcast</i>	(Optional) Multicasts

<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_ingiants</i>	(Optional) giants
<i>eth_ipmcast</i>	(Optional) IP multicast
<i>eth_inhw_switched</i>	(Optional) Input H/W Switched
<i>eth_insw_switched</i>	(Optional) Input S/W Switched
<i>eth_runts</i>	(Optional) runts
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_throtles</i>	(Optional) throttles
<i>eth_inerr</i>	(Optional) input errors
<i>eth_crc</i>	(Optional) CRC
<i>eth_ecc</i>	(Optional) ECC
<i>eth_frame</i>	(Optional) frame
<i>eth_overrun</i>	(Optional) overrun
<i>eth_ignored</i>	(Optional) ignored
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outgiants</i>	(Optional) giants
<i>eth_inpause</i>	(Optional) pause input
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_underrun</i>	(Optional) underruns
<i>eth_outhw_switched</i>	(Optional) Out H/W Switched
<i>eth_outsw_switched</i>	(Optional) Out S/W Switched

<i>eth_outerr</i>	(Optional) output errors
<i>eth_coll</i>	(Optional) collisions
<i>eth_resets</i>	(Optional) interface resets
<i>eth_babbles</i>	(Optional) babbles
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_deferred</i>	(Optional) deferred
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_outpause</i>	(Optional) PAUSE output
<i>eth_buffail</i>	(Optional) output buffer failures
<i>eth_bufswapped</i>	(Optional) output buffers swapped out
<i>eth_arpdrops</i>	(Optional) arp drops
<i>eth_out_ifdown_drops</i>	(Optional) Output if-down drops
<i>eth_single_coll</i>	(Optional) single collisions
<i>eth_multi_coll</i>	(Optional) multi collisions
<i>eth_excess_coll</i>	(Optional) excessive collisions
<i>eth_jabbers</i>	(Optional) jabbers
<i>eth_shortframe</i>	(Optional) short frames
<i>eth_indiscard</i>	(Optional) discards
<i>eth_bad_encap</i>	(Optional) bad encapsulation
<i>eth_outcrc</i>	(Optional) Output CRC
<i>eth_symbol</i>	(Optional) symbol errors
<i>eth_out_drops</i>	(Optional) output drops
<i>eth_sqetest</i>	(Optional) SQE test
<i>eth_inb64</i>	(Optional) input pkts between 0 and 64 bytes
<i>eth_inb65_127</i>	(Optional) input pkts between 65 and 127 bytes
<i>eth_inb128_255</i>	(Optional) input pkts between 128 and 255 bytes
<i>eth_inb256_511</i>	(Optional) input pkts between 256 and 511 bytes
<i>eth_inb512_1023</i>	(Optional) input pkts between 512 and 1023 bytes

<i>eth_inb1024_1518</i>	(Optional) input pkts between 1024 and 1518 bytes
<i>eth_inb1519_1548</i>	(Optional) input pkts between 1519 and 1548 bytes
<i>eth_intrunk</i>	(Optional) input trunk pkts
<i>eth_outb64</i>	(Optional) output pkts between 0 and 64 bytes
<i>eth_outb65_127</i>	(Optional) output pkts between 65 and 127 bytes
<i>eth_outb128_255</i>	(Optional) output pkts between 128 and 255 bytes
<i>eth_outb256_511</i>	(Optional) output pkts between 256 and 511 bytes
<i>eth_outb512_1023</i>	(Optional) output pkts between 512 and 1023 bytes
<i>eth_outb1024_1518</i>	(Optional) output pkts between 1024 and 1518 bytes
<i>eth_outb1519_1548</i>	(Optional) output pkts between 1519 and 1548 bytes
<i>eth_outtrunk</i>	(Optional) output trunk pkts
<i>eth_bpdu_outlost</i>	(Optional) BPDU output lost
<i>eth_cos0_outlost</i>	(Optional) output pkts
<i>eth_cos1_outlost</i>	(Optional) output pkts
<i>eth_cos2_outlost</i>	(Optional) output pkts
<i>eth_cos3_outlost</i>	(Optional) output pkts
<i>eth_cos4_outlost</i>	(Optional) output pkts
<i>eth_cos5_outlost</i>	(Optional) output pkts
<i>eth_cos6_outlost</i>	(Optional) output pkts
<i>eth_cos7_outlost</i>	(Optional) output pkts
<i>eth_fcoe_in_pkts</i>	(Optional) fcoe in pkts
<i>eth_fcoe_in_octets</i>	(Optional) fcoe in octets
<i>eth_fcoe_out_pkts</i>	(Optional) fcoe out pkts
<i>eth_fcoe_out_octets</i>	(Optional) fcoe out octets
<i>eth_nfcoe_in_pkts</i>	(Optional) nfcoe in pkts
<i>eth_nfcoe_in_octets</i>	(Optional) nfcoe in octets
<i>eth_nfcoe_out_pkts</i>	(Optional) nfcoe out pkts
<i>eth_nfcoe_out_octets</i>	(Optional) nfcoe out octets
<i>eth_eee_atx_lpi_msec</i>	(Optional) Tx Lpi usec

<i>eth_eee_arcv_lpi_msec</i>	(Optional) Rx Lpi usec
<i>eth_eee_atx_lpi_transitions</i>	(Optional) Tx Lpi requests
<i>eth_eee_arcv_lpi_transitions</i>	(Optional) Rx Lpi indications
<i>eth_phy_ber_count</i>	(Optional) Bit error rate counter
<i>eth_phy_errblks_count</i>	(Optional) Errored blocks counter
<i>svi_reliability</i>	(Optional) Reliability
<i>switchport</i>	(Optional) Switchport enabled

Command Mode

- /exec

show interface

```
show interface <ifmgmt> [ __readonly__ TABLE_interface <interface> <state> [ <state_rsn_desc> ] [
<state_rsn> ] [ <eth_rsn_fac> ] [ <eth_rsn_code> ] [ <share_state> ] [ <eth_bundle> ] [ <eth_dce_mode> ] [
<vpc_status> ] [ <eth_hw_desc> ] [ <eth_hw_addr> ] [ <eth_bia_addr> ] [ <desc> ] [ <eth_ip_addr> ] [
<eth_ip_mask> ] [ <eth_ip_prefix> ] [ <eth_mtu> ] [ <eth_bw> ] [ <eth_encap_vlan> ] [ <eth_dly> ] [
<eth_reliability> ] [ <eth_txload> ] [ <eth_rxload> ] [ <eth_loopback> ] [ <eth_keepalive> ] [ <eth_duplex>
] [ <eth_speed> ] [ <eth_mode> ] [ <eth_ratemode> ] [ <eth_autoneg> ] [ <eth_beacon> ] [ <eth_media> ] [
<eth_in_flowctrl> ] [ <eth_out_flowctrl> ] [ <eth_mdix> ] [ <eth_swt_monitor> ] [ <eth_ether_type> ] [
<eth_members> ] [ <eth_clk_mode> ] [ <eth_arp_type> ] [ <eth_arp_timeout> ] [ <eth_last_in> ] [
<eth_last_out> ] [ <eth_out_hang> ] [ <eth_clear_counters> ] [ <eth_link_flapped> ] [ <eth_inq_size> ] [
<eth_inq_max> ] [ <eth_inq_drops> ] [ <eth_inq_flush> ] [ <eth_out_drop> ] [ <eth_q_strategy> ] [
<eth_outq_size> ] [ <eth_outq_max> ] [ <eth_reset_cnt> ] [ <mgmt_hw_desc> ] [ <mgmt_hw_addr> ] [
<mgmt_ip_addr> ] [ <mgmt_ip_mask> ] [ <mgmt_mtu> ] [ <mgmt_speed> ] [ <mgmt_duplex> ] [
<vdc_lvl_in_avg_bits> ] [ <vdc_lvl_in_avg_pkts> ] [ <vdc_lvl_out_avg_bits> ] [ <vdc_lvl_out_avg_pkts>
] [ <vdc_lvl_in_pkts> ] [ <vdc_lvl_in_ucast> ] [ <vdc_lvl_in_mcast> ] [ <vdc_lvl_in_bcast> ] [
<vdc_lvl_in_bytes> ] [ <vdc_lvl_in_bps> ] [ <vdc_lvl_in_pps> ] [ <vdc_lvl_out_pkts> ] [ <vdc_lvl_out_ucast>
] [ <vdc_lvl_out_mcast> ] [ <vdc_lvl_out_bcast> ] [ <vdc_lvl_out_bytes> ] [ <vdc_lvl_out_bps> ] [
<vdc_lvl_out_pps> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifmgmt</i>	Enter interface type and number in module/slot format
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>state_rsn</i>	(Optional) Interface state reason
<i>eth_rsn_fac</i>	(Optional) State reason facility
<i>eth_rsn_code</i>	(Optional) State reason code
<i>share_state</i>	(Optional) Interface ownership
<i>eth_bundle</i>	(Optional) Belongs to bundle
<i>eth_dce_mode</i>	(Optional) DCE mode description
<i>vpc_status</i>	(Optional) VPC status
<i>eth_hw_desc</i>	(Optional) HW description

<i>eth_hw_addr</i>	(Optional) HW address
<i>eth_bia_addr</i>	(Optional) bia address
<i>desc</i>	(Optional) Interface description
<i>eth_ip_addr</i>	(Optional) IP Address
<i>eth_ip_mask</i>	(Optional) IP address mask
<i>eth_ip_prefix</i>	(Optional) IP address prefix
<i>eth_mtu</i>	(Optional) MTU
<i>eth_bw</i>	(Optional) Bandwidth
<i>eth_encap_vlan</i>	(Optional) Encapsulation Vlan
<i>eth_dly</i>	(Optional) Delay
<i>eth_reliability</i>	(Optional) Reliability
<i>eth_txload</i>	(Optional) Tx load
<i>eth_rxload</i>	(Optional) Rx load
<i>eth_loopback</i>	(Optional) Loopback
<i>eth_keepalive</i>	(Optional) Keepalive
<i>eth_duplex</i>	(Optional) Duplex
<i>eth_speed</i>	(Optional) Speed
<i>eth_mode</i>	(Optional) Port mode
<i>eth_ratemode</i>	(Optional) Rate mode
<i>eth_autoneg</i>	(Optional) Autonegotiation
<i>eth_beacon</i>	(Optional) Beacon
<i>eth_media</i>	(Optional) Media type
<i>eth_in_flowctrl</i>	(Optional) Input flowcontrol
<i>eth_out_flowctrl</i>	(Optional) Output flowcontrol
<i>eth_mdix</i>	(Optional) Mdix
<i>eth_swt_monitor</i>	(Optional) Switchport Monitor
<i>eth_etherType</i>	(Optional) EtherType
<i>eth_members</i>	(Optional) Members in this channel
<i>eth_clk_mode</i>	(Optional) Clock mode

<i>eth_arp_type</i>	(Optional) ARP type
<i>eth_arp_timeout</i>	(Optional) ARP timeout
<i>eth_last_in</i>	(Optional) Last input
<i>eth_last_out</i>	(Optional) Last output
<i>eth_out_hang</i>	(Optional) Last output hang
<i>eth_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>eth_link_flapped</i>	(Optional) Last link flapped
<i>eth_inq_size</i>	(Optional) Input queue size
<i>eth_inq_max</i>	(Optional) Input queue max
<i>eth_inq_drops</i>	(Optional) Input queue drops
<i>eth_inq_flush</i>	(Optional) Input queue flushes
<i>eth_out_drop</i>	(Optional) Output drops
<i>eth_q_strategy</i>	(Optional) Queueing strategy
<i>eth_outq_size</i>	(Optional) Output queue size
<i>eth_outq_max</i>	(Optional) Output queue max
<i>eth_reset_cnr</i>	(Optional) Interface resets
<i>mgmt_hw_desc</i>	(Optional) HW description
<i>mgmt_hw_addr</i>	(Optional) HW address
<i>mgmt_ip_addr</i>	(Optional) IP address
<i>mgmt_ip_mask</i>	(Optional) IP address mask
<i>mgmt_mtu</i>	(Optional) MTU
<i>mgmt_speed</i>	(Optional) Speed
<i>mgmt_duplex</i>	(Optional) Duplex
<i>vdc_lvl_in_avg_bits</i>	(Optional) VDC level average input bits
<i>vdc_lvl_in_avg_pkts</i>	(Optional) VDC level average input packets
<i>vdc_lvl_out_avg_bits</i>	(Optional) VDC level average output bits
<i>vdc_lvl_out_avg_pkts</i>	(Optional) VDC level average output packets
<i>vdc_lvl_in_pkts</i>	(Optional) VDC level input packets
<i>vdc_lvl_in_ucast</i>	(Optional) VDC level input unicast packets

<i>vdc_lvl_in_mcast</i>	(Optional) VDC level input multicast packets
<i>vdc_lvl_in_bcast</i>	(Optional) VDC level input broadcast packets
<i>vdc_lvl_in_bytes</i>	(Optional) VDC level input bytes
<i>vdc_lvl_in_bps</i>	(Optional) VDC level input bytes per second
<i>vdc_lvl_in_pps</i>	(Optional) VDC level input packets per second
<i>vdc_lvl_out_pkts</i>	(Optional) VDC level output packets
<i>vdc_lvl_out_ucast</i>	(Optional) VDC level output unicast packets
<i>vdc_lvl_out_mcast</i>	(Optional) VDC level output multicast packets
<i>vdc_lvl_out_bcast</i>	(Optional) VDC level output broadcast packets
<i>vdc_lvl_out_bytes</i>	(Optional) VDC level output bytes
<i>vdc_lvl_out_bps</i>	(Optional) VDC level output bytes per second
<i>vdc_lvl_out_pps</i>	(Optional) VDC level output packets per second

Command Mode

- /exec

show interface

```

show interface [ controller | quick ] [ __readonly__ TABLE interface <interface> [ <state> ] [ <state_rsn_desc>
] [ <state_rsn> ] [ <eth_rsn_fac> ] [ <eth_rsn_code> ] [ <admin_state> ] [ <share_state> ] [ <parent_interface>
] [ <vpc_status> ] [ <eth_bundle> ] [ <eth_hw_desc> ] [ <eth_hw_addr> ] [ <eth_bia_addr> ] [ <desc> ] [
<eth_ip_addr> ] [ <eth_ip_mask> ] [ <eth_ip_prefix> ] [ <eth_mtu> ] + [ <eth_bw> ] [ <eth_dly> ] [
<eth_reliability> ] [ <eth_txload> ] [ <eth_rxload> ] [ <eth_encap_vlan> ] [ <medium> ] [ <eth_mode> ] [
<eth_duplex> ] [ <eth_speed> ] [ <eth_media> ] [ <eth_beacon> ] [ <eth_autoneg> ] [ <eth_in_flowctrl> ] [
<eth_out_flowctrl> ] [ <eth_mdix> ] [ <eth_ratemode> ] [ <eth_swt_monitor> ] [ <eth_ethertype> ] [
<eth_eee_state> ] [ <eth_members> ] [ <eth_link_flapped> ] [ <eth_clear_counters> ] [ <eth_reset_cntr> ] [
<eth_load_interval1> ] [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [
<eth_load_interval1_tx> ] [ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [
<eth_inrate1_summary_bits> ] [ <eth_inrate1_summary_pkts> ] [ <eth_outrate1_summary_bits> ] [
<eth_outrate1_summary_pkts> ] [ <eth_load_interval2_rx> ] [ <eth_inrate2_bits> ] [ <eth_inrate2_pkts> ] [
<eth_load_interval2_tx> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [ <eth_load_interval3> ] [
<eth_inrate2_summary_bits> ] [ <eth_inrate2_summary_pkts> ] [ <eth_outrate2_summary_bits> ] [
<eth_outrate2_summary_pkts> ] [ <eth_load_interval3_rx> ] [ <eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [
<eth_load_interval3_tx> ] [ <eth_outrate3_bits> ] [ <eth_outrate3_pkts> ] [ <eth_inrate3_summary_bits> ]
[ <eth_inrate3_summary_pkts> ] [ <eth_outrate3_summary_bits> ] [ <eth_outrate3_summary_pkts> ] [
<eth_l2_ucastpkts> ] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [ <eth_l2_mcastbytes> ] [
<eth_l2_bcastpkts> ] [ <eth_l2_bcastbytes> ] [ <eth_l3in_routed_pkts> ] [ <eth_l3in_routed_bytes> ] [
<eth_l3out_routed_pkts> ] [ <eth_l3out_routed_bytes> ] [ <eth_l3in_ucastpkts> ] [ <eth_l3in_ucastbytes> ]
[ <eth_l3in_mcastpkts> ] [ <eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [ <eth_l3in_bcastbytes> ] [
<eth_l3out_ucastpkts> ] [ <eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_mcastbytes> ] [
<eth_l3out_bcastpkts> ] [ <eth_l3out_bcastbytes> ] [ <eth_l3avg1_inbytes> ] [ <eth_l3avg1_inpkts> ] [
<eth_l3avg1_outbytes> ] [ <eth_l3avg1_outpkts> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [
<eth_inpkts> ] [ <eth_inbytes> ] [ <eth_jumbo_inpkts> ] [ <eth_storm_supp> ] [ <eth_runts> ] [ <eth_giants>
] [ <eth_crc> ] [ <eth_nobuf> ] [ <eth_inerr> ] [ <eth_frame> ] [ <eth_overrun> ] [ <eth_underrun> ] [
<eth_ignored> ] [ <eth_watchdog> ] [ <eth_bad_eth> ] [ <eth_bad_proto> ] [ <eth_in_ifdown_drops> ] [
<eth_dribble> ] [ <eth_indiscard> ] [ <eth_inpause> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_jumbo_outpkts> ] [ <eth_outerr> ] [ <eth_coll> ] [ <eth_deferred>
] [ <eth_latecoll> ] [ <eth_lostcarrier> ] [ <eth_nocarrier> ] [ <eth_babbles> ] [ <eth_outdiscard> ] [
<eth_outpause> ] [ <mgmt_hw_desc> ] [ <mgmt_hw_addr> ] [ <mgmt_ip_addr> ] [ <mgmt_ip_mask> ] [
<mgmt_mtu> ] [ <mgmt_speed> ] [ <mgmt_duplex> ] [ <vdc_lvl_in_avg_bits> ] [ <vdc_lvl_in_avg_pkts>
] [ <vdc_lvl_out_avg_bits> ] [ <vdc_lvl_out_avg_pkts> ] [ <vdc_lvl_in_pkts> ] [ <vdc_lvl_in_ucast> ] [
<vdc_lvl_in_mcast> ] [ <vdc_lvl_in_bcast> ] [ <vdc_lvl_in_bytes> ] [ <vdc_lvl_in_bps> ] [ <vdc_lvl_in_pps>
] [ <vdc_lvl_out_pkts> ] [ <vdc_lvl_out_ucast> ] [ <vdc_lvl_out_mcast> ] [ <vdc_lvl_out_bcast> ] [
<vdc_lvl_out_bytes> ] [ <vdc_lvl_out_bps> ] [ <vdc_lvl_out_pps> ] [ <mgmt_in_pkts> ] [ <mgmt_in_bytes>
] [ <mgmt_in_mcast> ] [ <mgmt_in_compressed> ] [ <mgmt_in_errors> ] [ <mgmt_in_frame> ] [
<mgmt_in_overrun> ] [ <mgmt_in_fifo> ] [ <mgmt_out_pkts> ] [ <mgmt_out_bytes> ] [
<mgmt_out_underruns> ] [ <mgmt_out_errors> ] [ <mgmt_out_collisions> ] [ <mgmt_out_fifo> ] [
<mgmt_out_carrier> ] [ <mgmt_align_err> ] [ <mgmt_fcs_err> ] [ <mgmt_xmit_err> ] [ <mgmt_rcv_err> ]
[ <mgmt_undersize> ] [ <mgmt_outdisc> ] [ <mgmt_single_col> ] [ <mgmt_multi_col> ] [ <mgmt_late_col>
] [ <mgmt_excess_col> ] [ <mgmt_carri_sen> ] [ <mgmt_runts> ] [ <mgmt_giants> ] [ <mgmt_sqetest_err>
] [ <mgmt_deferred_tx> ] [ <mgmt_inmactx_err> ] [ <mgmt_inmacrx_err> ] [ <mgmt_symbol_err> ] [
<loop_in_pkts> ] [ <loop_in_bytes> ] [ <loop_in_mcast> ] [ <loop_in_compressed> ] [ <loop_in_errors> ]
[ <loop_in_frame> ] [ <loop_in_overrun> ] [ <loop_in_fifo> ] [ <loop_out_pkts> ] [ <loop_out_bytes> ] [
<loop_out_underruns> ] [ <loop_out_errors> ] [ <loop_out_collisions> ] [ <loop_out_fifo> ] [
<loop_out_carriers> ] <admin-state> { <tunnel-ipv4> | <tunnel-ipv6> } <mtu> <bandwidth> <encap-type>
<keepalive-period> <keepalive-retries> { <src-ipv4> | <src-ipv6> } <src-intf> { <dest-ipv4> | <dest-ipv6> }

```

```

<dest-hostname> <vrf_name> <wccp_header> <ttl_val> <tunnel_pmtud_age_time> <tunnel_pmtud_min_mtu>
<tunnel_pmtud> <tunnel_pgm_mtu> <tunnel_rx_pkt_count> <tunnel_rx_byte_count> <tunnel_rx_rate>
<tunnel_tx_pkt_count> <tunnel_tx_byte_count> <tunnel_tx_rate> <tunnel_clear_counter> [ <svi_if_index>
] [ <svi_admin_state> ] [ <svi_rsn_desc> ] [ <svi_line_proto> ] [ <svi_hw> ] [ <svi_mac> ] [ <svi_desc> ] [
<svi_ip_addr> ] [ <svi_ip_mask> ] [ <svi_mtu> ] [ <svi_bw> ] [ <svi_delay> ] [ <svi_tx_load> ] [
<svi_rx_load> ] [ <svi_carrier_delay_sec> ] [ <svi_carrier_delay_msec> ] [ <svi_arp_type> ] [
<svi_arp_timeout> ] [ <svi_time_last_cleared> ] { [ TABLE_sec_vlan ] [ <sec_vlan> ] [ <sec_vlan_type> ]
} [ <svi_routed_pkts_in> ] [ <svi_routed_bytes_in> ] [ <svi_routed_pkts_out> ] [ <svi_routed_bytes_out> ]
[ <svi_ucast_pkts_in> ] [ <svi_ucast_bytes_in> ] [ <svi_mcast_pkts_in> ] [ <svi_mcast_bytes_in> ] [
<svi_ucast_pkts_out> ] [ <svi_ucast_bytes_out> ] [ <svi_mcast_pkts_out> ] [ <svi_mcast_bytes_out> ] [
<svi_ipv4_ucast_pkts_in> ] [ <svi_ipv4_ucast_bytes_in> ] [ <svi_ipv4_ucast_pkts_out> ] [
<svi_ipv4_ucast_bytes_out> ] [ <svi_ipv4_mcast_pkts_in> ] [ <svi_ipv4_mcast_bytes_in> ] [
<svi_ipv4_mcast_pkts_out> ] [ <svi_ipv4_mcast_bytes_out> ] [ <svi_ipv6_ucast_pkts_in> ] [
<svi_ipv6_ucast_bytes_in> ] [ <svi_ipv6_ucast_pkts_out> ] [ <svi_ipv6_ucast_bytes_out> ] [
<svi_ipv6_mcast_pkts_in> ] [ <svi_ipv6_mcast_bytes_in> ] [ <svi_ipv6_mcast_pkts_out> ] [
<svi_ipv6_mcast_bytes_out> ] [ <svi_average_input_bits> ] [ <svi_average_input_packets> ] [
<svi_average_output_bits> ] [ <svi_average_output_packets> ] [ <svi_rate_in_mins> ] [ <svi_reliability> ]
[ <overlay_addr> ] [ <overlay_addr_mask> ] [ <overlay_mtu> ] [ <overlay_bandwidth> ] [ <overlay_encap_str>
] [ <overlay_vrf> ] [ <overlay_src_addr> ] [ <overlay_dst_addr> ] [ <overlay_last_link_flap> ] [
<overlay_clear_counters> ] [ <overlay_load_interval> ] [ <overlay_rx_ucastpkts> ] [ <overlay_rx_ucastbytes>
] [ <overlay_rx_mcastpkts> ] [ <overlay_rx_mcastbytes> ] [ <overlay_rx_pkts> ] [ <overlay_rx_bytes> ] [
<overlay_rx_bcastpkts> ] [ <overlay_rx_bcastbytes> ] [ <overlay_rx_bitrate> ] [ <overlay_rx_pktrate> ] [
<overlay_tx_ucastpkts> ] [ <overlay_tx_ucastbytes> ] [ <overlay_tx_mcastpkts> ] [ <overlay_tx_mcastbytes>
] [ <overlay_tx_bcastpkts> ] [ <overlay_tx_bcastbytes> ] [ <overlay_tx_pkts> ] [ <overlay_tx_bytes> ] [
<overlay_tx_bitrate> ] [ <overlay_tx_pktrate> ] <switchport> ]

```

Syntax Description

show	Show running system information
interface	Show interface status and information
controller	(Optional) Show controller configured interfaces
quick	(Optional) Show info of interface skipping stats
__readonly__	(Optional) Read Only
interface	(Optional) Interface index
TABLE_interface	(Optional) show interface
state	(Optional) Interface state
state_rsn_desc	(Optional) Interface state reason detailed
state_rsn	(Optional) Interface state reason
switchport	(Optional) Switchport enabled
eth_rsn_fac	(Optional) State reason facility
eth_rsn_code	(Optional) State reason code
admin_state	(Optional) admin state

<i>share_state</i>	(Optional) Interface ownership
<i>parent_interface</i>	(Optional) parent interface
<i>vpc_status</i>	(Optional) VPC status
<i>eth_bundle</i>	(Optional) Belongs to bundle
<i>eth_hw_desc</i>	(Optional) HW description
<i>eth_hw_addr</i>	(Optional) HW address
<i>eth_bia_addr</i>	(Optional) bia address
<i>desc</i>	(Optional) Interface description
<i>eth_ip_addr</i>	(Optional) IP Address
<i>eth_ip_mask</i>	(Optional) IP address mask
<i>eth_ip_prefix</i>	(Optional) IP address prefix
<i>eth_mtu</i>	(Optional) MTU
<i>eth_bw</i>	(Optional) Bandwidth
<i>eth_dly</i>	(Optional) Delay
<i>eth_reliability</i>	(Optional) Reliability
<i>eth_txload</i>	(Optional) Tx load
<i>eth_rxload</i>	(Optional) Rx load
<i>eth_encap_vlan</i>	(Optional) Encapsulation Vlan
<i>medium</i>	(Optional) medium type
<i>eth_mode</i>	(Optional) Port mode
<i>eth_duplex</i>	(Optional) Duplex
<i>eth_speed</i>	(Optional) Speed
<i>eth_media</i>	(Optional) Media type
<i>eth_beacon</i>	(Optional) Beacon
<i>eth_autoneg</i>	(Optional) Autonegotiation
<i>eth_in_flowctrl</i>	(Optional) Input flowcontrol
<i>eth_out_flowctrl</i>	(Optional) Output flowcontrol
<i>eth_mdix</i>	(Optional) Mdx
<i>eth_ratemode</i>	(Optional) Rate mode

<i>eth_swt_monitor</i>	(Optional) Switchport Monitor
<i>eth_etherstype</i>	(Optional) EtherType
<i>eth_eee_state</i>	(Optional) EEE state
<i>eth_members</i>	(Optional) Members in this channel
<i>eth_link_flapped</i>	(Optional) Last link flapped
<i>eth_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>eth_reset_cntr</i>	(Optional) Interface resets
<i>eth_load_interval1</i>	(Optional) interval 1 timer value in sec
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec
<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate1_summary_bits</i>	(Optional) interval 1 input rate bit summary
<i>eth_inrate1_summary_pkts</i>	(Optional) interval 1 input rate pkt summary
<i>eth_outrate1_summary_bits</i>	(Optional) interval 1 output rate bit summary
<i>eth_outrate1_summary_pkts</i>	(Optional) interval 1 output rate pkt summary
<i>eth_load_interval2_rx</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_load_interval2_tx</i>	(Optional) interval 2 timer value in sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate2_summary_bits</i>	(Optional) interval 2 input rate bit summary
<i>eth_inrate2_summary_pkts</i>	(Optional) interval 2 input rate pkt summary
<i>eth_outrate2_summary_bits</i>	(Optional) interval 2 output rate bit summary

<i>eth_outrate2_summary_pkts</i>	(Optional) interval 2 output rate pkt summary
<i>eth_load_interval3_rx</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_load_interval3_tx</i>	(Optional) interval 3 timer value in sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_inrate3_summary_bits</i>	(Optional) interval 3 input rate bit summary
<i>eth_inrate3_summary_pkts</i>	(Optional) interval 3 input rate pkt summary
<i>eth_outrate3_summary_bits</i>	(Optional) interval 3 output rate bit summary
<i>eth_outrate3_summary_pkts</i>	(Optional) interval 3 output rate pkt summary
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) L3 out switched mcast pkts
<i>eth_l3out_mcastbytes</i>	(Optional) L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes

<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_jumbo_inpkts</i>	(Optional) Incoming jumbo pkts
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_runts</i>	(Optional) runts
<i>eth_giants</i>	(Optional) giants
<i>eth_crc</i>	(Optional) CRC
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_inerr</i>	(Optional) input errors
<i>eth_frame</i>	(Optional) frame
<i>eth_overrun</i>	(Optional) overrun
<i>eth_underrun</i>	(Optional) underruns
<i>eth_ignored</i>	(Optional) ignored
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_dribble</i>	(Optional) input packets with dribble condition

<i>eth_indiscard</i>	(Optional) discards
<i>eth_inpause</i>	(Optional) pause input
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_jumbo_outpkts</i>	(Optional) Outgoing jumbo pkts
<i>eth_outerr</i>	(Optional) output errors
<i>eth_coll</i>	(Optional) collisions
<i>eth_deferred</i>	(Optional) deferred
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_babbles</i>	(Optional) babbles
<i>eth_outdiscard</i>	(Optional) output discard
<i>eth_outpause</i>	(Optional) PAUSE output
<i>mgmt_hw_desc</i>	(Optional) HW description
<i>mgmt_hw_addr</i>	(Optional) HW address
<i>mgmt_ip_addr</i>	(Optional) IP address
<i>mgmt_ip_mask</i>	(Optional) IP address mask
<i>mgmt_mtu</i>	(Optional) MTU
<i>mgmt_speed</i>	(Optional) Speed
<i>mgmt_duplex</i>	(Optional) Duplex
<i>vdc_lvl_in_avg_bits</i>	(Optional) VDC level average input bits
<i>vdc_lvl_in_avg_pkts</i>	(Optional) VDC level average input packets
<i>vdc_lvl_out_avg_bits</i>	(Optional) VDC level average output bits
<i>vdc_lvl_out_avg_pkts</i>	(Optional) VDC level average output packets
<i>vdc_lvl_in_pkts</i>	(Optional) VDC level input packets

<i>vdc_lvl_in_ucast</i>	(Optional) VDC level input unicast packets
<i>vdc_lvl_in_mcast</i>	(Optional) VDC level input multicast packets
<i>vdc_lvl_in_bcast</i>	(Optional) VDC level input broadcast packets
<i>vdc_lvl_in_bytes</i>	(Optional) VDC level input bytes
<i>vdc_lvl_in_bps</i>	(Optional) VDC level input bytes per second
<i>vdc_lvl_in_pps</i>	(Optional) VDC level input packets per second
<i>vdc_lvl_out_pkts</i>	(Optional) VDC level output packets
<i>vdc_lvl_out_ucast</i>	(Optional) VDC level output unicast packets
<i>vdc_lvl_out_mcast</i>	(Optional) VDC level output multicast packets
<i>vdc_lvl_out_bcast</i>	(Optional) VDC level output broadcast packets
<i>vdc_lvl_out_bytes</i>	(Optional) VDC level output bytes
<i>vdc_lvl_out_bps</i>	(Optional) VDC level output bytes per second
<i>vdc_lvl_out_pps</i>	(Optional) VDC level output packets per second
<i>mgmt_in_pkts</i>	(Optional) Input packets
<i>mgmt_in_bytes</i>	(Optional) Input bytes
<i>mgmt_in_mcast</i>	(Optional) Input multicast frames
<i>mgmt_in_compressed</i>	(Optional) Input compressed
<i>mgmt_in_errors</i>	(Optional) Input errors
<i>mgmt_in_frame</i>	(Optional) Input frame errors
<i>mgmt_in_overrun</i>	(Optional) Input overrun
<i>mgmt_in_fifo</i>	(Optional) Input fifo
<i>mgmt_out_pkts</i>	(Optional) Output packets
<i>mgmt_out_bytes</i>	(Optional) Output bytes
<i>mgmt_out_underruns</i>	(Optional) Output overruns
<i>mgmt_out_errors</i>	(Optional) Output errors
<i>mgmt_out_collisions</i>	(Optional) Output collisions
<i>mgmt_out_fifo</i>	(Optional) Output fifo
<i>mgmt_out_carrier</i>	(Optional) Output carrier errors
<i>mgmt_align_err</i>	(Optional) Align error

<i>mgmt_fcs_err</i>	(Optional) FCS error
<i>mgmt_xmit_err</i>	(Optional) Transmit error
<i>mgmt_rcv_err</i>	(Optional) Receive error
<i>mgmt_undersize</i>	(Optional) Undersize
<i>mgmt_outdisc</i>	(Optional) Out discard
<i>mgmt_single_col</i>	(Optional) Single collision
<i>mgmt_multi_col</i>	(Optional) Multiple collision
<i>mgmt_late_col</i>	(Optional) Late collision
<i>mgmt_excess_col</i>	(Optional) Excess collision
<i>mgmt_carri_sen</i>	(Optional) Carrier sense
<i>mgmt_runts</i>	(Optional) Runts
<i>mgmt_giants</i>	(Optional) Giants
<i>mgmt_sqetest_err</i>	(Optional) SQETest error
<i>mgmt_deferred_tx</i>	(Optional) Deferred tx
<i>mgmt_inmactx_err</i>	(Optional) In MAC tx
<i>mgmt_inmacrx_err</i>	(Optional) In MAC rx
<i>mgmt_symbol_err</i>	(Optional) Symbol error
<i>loop_in_pkts</i>	(Optional) Input packets
<i>loop_in_bytes</i>	(Optional) Input bytes
<i>loop_in_mcast</i>	(Optional) Input multicast
<i>loop_in_compressed</i>	(Optional) Input compressed
<i>loop_in_errors</i>	(Optional) Input errors
<i>loop_in_frame</i>	(Optional) Input frame errors
<i>loop_in_overrun</i>	(Optional) Input overrun
<i>loop_in_fifo</i>	(Optional) Input fifo
<i>loop_out_pkts</i>	(Optional) Output packets
<i>loop_out_bytes</i>	(Optional) Output bytes
<i>loop_out_underruns</i>	(Optional) Output underruns
<i>loop_out_errors</i>	(Optional) Output errors

<i>loop_out_collisions</i>	(Optional) Output collisions
<i>loop_out_fifo</i>	(Optional) Output fifo
<i>loop_out_carriers</i>	(Optional) Output carrier errors
<i>admin-state</i>	(Optional)
<i>tunnel-ipv4</i>	(Optional) interface IPv4 address
<i>mtu</i>	(Optional) interface Maximum Transmission Unit
<i>bandwidth</i>	(Optional) interface Bandwidth in kilobits
<i>encap-type</i>	(Optional)
<i>keepalive-period</i>	(Optional) keealive period
<i>keepalive-retries</i>	(Optional) number of retries
<i>src-ipv4</i>	(Optional) tunnel source IPv4 address
<i>src-intf</i>	(Optional) tunnel source interface
<i>dest-ipv4</i>	(Optional) tunnel destination IPv4 address
<i>dest-hostname</i>	(Optional) tunnel destination hostname
<i>vrf_name</i>	(Optional) transport VRF name
<i>wccp_header</i>	(Optional) wccp header
<i>ttl_val</i>	(Optional) tunnel time to live value
<i>tunnel_pmtud_age_time</i>	(Optional) tunnel path MTU discovery age time
<i>tunnel_pmtud_min_mtu</i>	(Optional) tunnel path MTU discovery min mtu
<i>tunnel_pmtud</i>	(Optional) tunnel path MTU discovered
<i>tunnel_pgm_mtu</i>	(Optional) tunnel actual programmed MTU
<i>tunnel_rx_pkt_count</i>	(Optional) total number of packets received
<i>tunnel_rx_byte_count</i>	(Optional) total number of bytes received
<i>tunnel_rx_rate</i>	(Optional) packets input rate per 5 minutes
<i>tunnel_tx_pkt_count</i>	(Optional) total number of packets transmitted
<i>tunnel_tx_byte_count</i>	(Optional) total number of bytes transmitted
<i>tunnel_tx_rate</i>	(Optional) packets transmitted per 5 minutes
<i>tunnel_clear_counter</i>	(Optional) Last clearing of show interface counters
<i>svi_if_index</i>	(Optional) Interface

<i>svi_admin_state</i>	(Optional)
<i>svi_rsn_desc</i>	(Optional) Interface state reason detailed
<i>svi_line_proto</i>	(Optional)
<i>svi_hw</i>	(Optional) Hardware
<i>svi_mac</i>	(Optional) Address
<i>svi_desc</i>	(Optional) Interface Description
<i>svi_ip_addr</i>	(Optional) IP Address
<i>svi_ip_mask</i>	(Optional) IP address mask
<i>svi_mtu</i>	(Optional) MTU size in bytes
<i>svi_bw</i>	(Optional) Bandwidth in kilobits
<i>svi_delay</i>	(Optional) Throughput delay (tens of microseconds)
<i>svi_tx_load</i>	(Optional) Tx Load
<i>svi_rx_load</i>	(Optional) Rx Load
<i>svi_carrier_delay_sec</i>	(Optional) carrier delay value in seconds
<i>svi_carrier_delay_msec</i>	(Optional) carrier delay value in milli-seconds
<i>svi_arp_type</i>	(Optional) ARP type
<i>svi_arp_timeout</i>	(Optional) ARP timeout value
<i>svi_time_last_cleared</i>	(Optional) Time last cleared
TABLE_sec_vlan	(Optional) secondary vlans
<i>sec_vlan</i>	(Optional) vlan id
<i>sec_vlan_type</i>	(Optional) secondary vlan type
<i>svi_reliability</i>	(Optional) Reliability
<i>overlay_addr</i>	(Optional) Overlay address
<i>overlay_addr_mask</i>	(Optional) Overlay address mask
<i>overlay_mtu</i>	(Optional) MTU
<i>overlay_bandwidth</i>	(Optional) Bandwidth
<i>overlay_encap_str</i>	(Optional) Encap type
<i>overlay_vrf</i>	(Optional) VRF
<i>overlay_src_addr</i>	(Optional) Source address

<i>overlay_dst_addr</i>	(Optional) Destination address
<i>overlay_last_link_flap</i>	(Optional) Last link flap
<i>overlay_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>overlay_load_interval</i>	(Optional) Load interval
<i>overlay_rx_ucastpkts</i>	(Optional) Received ucast pkts
<i>overlay_rx_ucastbytes</i>	(Optional) Received ucast bytes
<i>overlay_rx_mcastpkts</i>	(Optional) Received mcast pkts
<i>overlay_rx_mcastbytes</i>	(Optional) Received mcast bytes
<i>overlay_rx_bcastpkts</i>	(Optional) Received bcast pkts
<i>overlay_rx_bcastbytes</i>	(Optional) Received bcast bytes
<i>overlay_rx_pkts</i>	(Optional) Total received pkts
<i>overlay_rx_bytes</i>	(Optional) Total received bytes
<i>overlay_rx_bitrate</i>	(Optional) Receive bit rate
<i>overlay_rx_pktrate</i>	(Optional) Receive pkt rate
<i>overlay_tx_ucastpkts</i>	(Optional) Trasnmitted ucast pkts
<i>overlay_tx_ucastbytes</i>	(Optional) Trasnmitted ucast bytes
<i>overlay_tx_mcastpkts</i>	(Optional) Trasnmitted mcast pkts
<i>overlay_tx_mcastbytes</i>	(Optional) Trasnmitted mcast bytes
<i>overlay_tx_bcastpkts</i>	(Optional) Trasnmitted bcast pkts
<i>overlay_tx_bcastbytes</i>	(Optional) Trasnmitted bcast bytes
<i>overlay_tx_pkts</i>	(Optional) Total transmitted pkts
<i>overlay_tx_bytes</i>	(Optional) Total transmitted bytes
<i>overlay_tx_bitrate</i>	(Optional) Transmit bit rate
<i>overlay_tx_pktrate</i>	(Optional) Transmit pkt rate

Command Mode

- /exec

show interface

```
show interface <ifloop> [ __readonly__ TABLE_interface <interface> [ <state> ] [ <admin_state> ] [
<share_state> ] [ <state_rsn> ] [ <state_rsn_desc> ] [ <desc> ] [ <eth_bundle> ] [ <mgmt_sfp> ] [ <mgmt_type>
] [ <eth_eee_state> ] [ <eth_dce_mode> ] [ <vpc_status> ] [ <eth_rsn_fac> ] [ <eth_rsn_code> ] [
<eth_hw_desc> ] [ <eth_hw_addr> ] [ <eth_bia_addr> ] [ <eth_ip_addr> ] [ <eth_ip_mask> ] [ <eth_ip_prefix>
] [ <eth_mtu> ] [ <eth_bw> ] [ <eth_encap_vlan> ] [ <eth_dly> ] [ <eth_reliability> ] [ <eth_txload> ] [
<eth_rxload> ] [ <eth_loopback> ] [ <eth_keepalive> ] [ <eth_duplex> ] [ <eth_speed> ] [ <eth_mode> ] [
<eth_ratemode> ] [ <eth_autoneg> ] [ <eth_beacon> ] [ <eth_media> ] [ <eth_in_flowctrl> ] [
<eth_out_flowctrl> ] [ <eth_mdix> ] [ <eth_swt_monitor> ] [ <eth_ether_type> ] [ <eth_members> ] [
<eth_clk_mode> ] [ <eth_arp_type> ] [ <eth_arp_timeout> ] [ <eth_last_in> ] [ <eth_last_out> ] [
<eth_out_hang> ] [ <eth_clear_counters> ] [ <eth_link_flapped> ] [ <eth_inq_size> ] [ <eth_inq_max> ] [
<eth_inq_drops> ] [ <eth_inq_flush> ] [ <eth_out_drop> ] [ <eth_q_strategy> ] [ <eth_outq_size> ] [
<eth_outq_max> ] [ <eth_reset_cntr> ] [ <loop_in_pkts> ] [ <loop_in_bytes> ] [ <loop_in_mcast> ] [
<loop_in_compressed> ] [ <loop_in_errors> ] [ <loop_in_frame> ] [ <loop_in_overrun> ] [ <loop_in_fifo>
] [ <loop_out_pkts> ] [ <loop_out_bytes> ] [ <loop_out_underruns> ] [ <loop_out_errors> ] [
<loop_out_collisions> ] [ <loop_out_fifo> ] [ <loop_out_carriers> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifloop</i>	Enter interface type and number in module/slot format
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>admin_state</i>	(Optional) Interface admin state
<i>share_state</i>	(Optional) Interface ownership
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>desc</i>	(Optional) Interface description
<i>mgmt_sfp</i>	(Optional) mgmt sfp
<i>mgmt_type</i>	(Optional) mgmt type
<i>eth_bundle</i>	(Optional) Belongs to bundle
<i>eth_eee_state</i>	(Optional) EEE state
<i>eth_dce_mode</i>	(Optional) DCE mode description

<i>vpc_status</i>	(Optional) VPC status
<i>eth_rsn_fac</i>	(Optional) State reason facility
<i>eth_rsn_code</i>	(Optional) State reason code
<i>eth_hw_desc</i>	(Optional) HW description
<i>eth_hw_addr</i>	(Optional) HW address
<i>eth_bia_addr</i>	(Optional) bia address
<i>eth_ip_addr</i>	(Optional) IP Address
<i>eth_ip_mask</i>	(Optional) IP address mask
<i>eth_ip_prefix</i>	(Optional) IP Prefix
<i>eth_mtu</i>	(Optional) MTU
<i>eth_bw</i>	(Optional) Bandwidth
<i>eth_encap_vlan</i>	(Optional) Encapsulation Vlan
<i>eth_dly</i>	(Optional) Delay
<i>eth_reliability</i>	(Optional) Reliability
<i>eth_txload</i>	(Optional) Tx load
<i>eth_rxload</i>	(Optional) Rx load
<i>eth_loopback</i>	(Optional) Loopback
<i>eth_keepalive</i>	(Optional) Keepalive
<i>eth_duplex</i>	(Optional) Duplex
<i>eth_speed</i>	(Optional) Speed
<i>eth_mode</i>	(Optional) Port mode
<i>eth_ratemode</i>	(Optional) Rate mode
<i>eth_autoneg</i>	(Optional) Autonegotiation
<i>eth_beacon</i>	(Optional) Beacon
<i>eth_media</i>	(Optional) Media type
<i>eth_in_flowctrl</i>	(Optional) Input flowcontrol
<i>eth_out_flowctrl</i>	(Optional) Output flowcontrol
<i>eth_mdix</i>	(Optional) Mdx
<i>eth_swt_monitor</i>	(Optional) Switchport Monitor

<i>eth_etherType</i>	(Optional) EtherType
<i>eth_members</i>	(Optional) Members in this channel
<i>eth_clk_mode</i>	(Optional) Clock mode
<i>eth_arp_type</i>	(Optional) ARP type
<i>eth_arp_timeout</i>	(Optional) ARP timeout
<i>eth_last_in</i>	(Optional) Last input
<i>eth_last_out</i>	(Optional) Last output
<i>eth_out_hang</i>	(Optional) Last output hang
<i>eth_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>eth_link_flapped</i>	(Optional) Last link flapped
<i>eth_inq_size</i>	(Optional) Input queue size
<i>eth_inq_max</i>	(Optional) Input queue max
<i>eth_inq_drops</i>	(Optional) Input queue drops
<i>eth_inq_flush</i>	(Optional) Input queue flushes
<i>eth_out_drop</i>	(Optional) Output drops
<i>eth_q_strategy</i>	(Optional) Queueing strategy
<i>eth_outq_size</i>	(Optional) Output queue size
<i>eth_outq_max</i>	(Optional) Output queue max
<i>eth_reset_cntr</i>	(Optional) Interface resets
<i>loop_in_pkts</i>	(Optional) Input packets
<i>loop_in_bytes</i>	(Optional) Input bytes
<i>loop_in_mcast</i>	(Optional) Input multicast
<i>loop_in_compressed</i>	(Optional) Input compressed
<i>loop_in_errors</i>	(Optional) Input errors
<i>loop_in_frame</i>	(Optional) Input frame errors
<i>loop_in_overrun</i>	(Optional) Input overrun
<i>loop_in_fifo</i>	(Optional) Input fifo
<i>loop_out_pkts</i>	(Optional) Output packets
<i>loop_out_bytes</i>	(Optional) Output bytes

<i>loop_out_underruns</i>	(Optional) Output underruns
<i>loop_out_errors</i>	(Optional) Output errors
<i>loop_out_collisions</i>	(Optional) Output collisions
<i>loop_out_fifo</i>	(Optional) Output fifo
<i>loop_out_carriers</i>	(Optional) Output carrier errors

Command Mode

- /exec

show interface

```
show interface <ifeth> [ quick ] [ __readonly__ TABLE_interface <interface> <state> [ <state_rsn_desc> ]
[ <state_rsn> ] [ <eth_rsn_fac> ] [ <eth_rsn_code> ] [ <admin_state> ] [ <share_state> ] [ <parent_interface>
] [ <vpc_status> ] [ <eth_bundle> ] [ <eth_hw_desc> ] [ <eth_hw_addr> ] [ <eth_bia_addr> ] [ <desc> ] [
<eth_ip_addr> ] [ <eth_ip_mask> ] [ <eth_ip_prefix> ] [ <eth_mtu> ] + [ <eth_bw> ] [ <eth_dly> ] [
<eth_reliability> ] [ <eth_txload> ] [ <eth_rxload> ] [ <eth_encap_vlan> ] [ <medium> ] [ <eth_mode> ] [
<eth_duplex> ] [ <eth_speed> ] [ <eth_media> ] [ <eth_beacon> ] [ <eth_autoneg> ] [ <eth_in_flowctrl> ] [
<eth_out_flowctrl> ] [ <eth_mdix> ] [ <eth_ratemode> ] [ <eth_swt_monitor> ] [ <eth_ethertype> ] [
<eth_eee_state> ] [ <eth_members> ] [ <eth_link_flapped> ] [ <eth_clear_counters> ] [ <eth_reset_cntr> ] [
<eth_load_interval1> ] [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [
<eth_load_interval1_tx> ] [ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [
<eth_inrate1_summary_bits> ] [ <eth_inrate1_summary_pkts> ] [ <eth_outrate1_summary_bits> ] [
<eth_outrate1_summary_pkts> ] [ <eth_load_interval2_rx> ] [ <eth_inrate2_bits> ] [ <eth_inrate2_pkts> ] [
<eth_load_interval2_tx> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [ <eth_load_interval3> ] [
<eth_inrate2_summary_bits> ] [ <eth_inrate2_summary_pkts> ] [ <eth_outrate2_summary_bits> ] [
<eth_outrate2_summary_pkts> ] [ <eth_load_interval3_rx> ] [ <eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [
<eth_load_interval3_tx> ] [ <eth_outrate3_bits> ] [ <eth_outrate3_pkts> ] [ <eth_inrate3_summary_bits> ]
[ <eth_inrate3_summary_pkts> ] [ <eth_outrate3_summary_bits> ] [ <eth_outrate3_summary_pkts> ] [
<eth_l2_ucastpkts> ] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [ <eth_l2_mcastbytes> ] [
<eth_l2_bcastpkts> ] [ <eth_l2_bcastbytes> ] [ <eth_l3in_routed_pkts> ] [ <eth_l3in_routed_bytes> ] [
<eth_l3out_routed_pkts> ] [ <eth_l3out_routed_bytes> ] [ <eth_l3in_ucastpkts> ] [ <eth_l3in_ucastbytes> ]
[ <eth_l3in_mcastpkts> ] [ <eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [ <eth_l3in_bcastbytes> ] [
<eth_l3out_ucastpkts> ] [ <eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_mcastbytes> ] [
<eth_l3out_bcastpkts> ] [ <eth_l3out_bcastbytes> ] [ <eth_l3avg1_inbytes> ] [ <eth_l3avg1_inpkts> ] [
<eth_l3avg1_outbytes> ] [ <eth_l3avg1_outpkts> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [
<eth_inpkts> ] [ <eth_inbytes> ] [ <eth_jumbo_inpkts> ] [ <eth_storm_supp> ] [ <eth_runts> ] [ <eth_giants>
] [ <eth_crc> ] [ <eth_nobuf> ] [ <eth_inerr> ] [ <eth_frame> ] [ <eth_overrun> ] [ <eth_underrun> ] [
<eth_ignored> ] [ <eth_watchdog> ] [ <eth_bad_eth> ] [ <eth_bad_proto> ] [ <eth_in_ifdown_drops> ] [
<eth_dribble> ] [ <eth_indiscard> ] [ <eth_inpause> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_jumbo_outpkts> ] [ <eth_outerr> ] [ <eth_coll> ] [ <eth_deferred>
] [ <eth_latecoll> ] [ <eth_lostcarrier> ] [ <eth_nocarrier> ] [ <eth_babbles> ] [ <eth_outdiscard> ] [
<eth_outpause> ] [ <switchport> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth</i>	Enter interface type and number in module/slot format
quick	(Optional) Show info of interface skipping stats
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state

<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>state_rsn</i>	(Optional) Interface state reason
<i>eth_rsn_fac</i>	(Optional) State reason facility
<i>eth_rsn_code</i>	(Optional) State reason code
<i>admin_state</i>	(Optional) admin state
<i>share_state</i>	(Optional) Interface ownership
<i>parent_interface</i>	(Optional) parent interface
<i>vpc_status</i>	(Optional) VPC status
<i>eth_bundle</i>	(Optional) Belongs to bundle
<i>eth_hw_desc</i>	(Optional) HW description
<i>eth_hw_addr</i>	(Optional) HW address
<i>eth_bia_addr</i>	(Optional) bia address
<i>desc</i>	(Optional) Interface description
<i>eth_ip_addr</i>	(Optional) IP Address
<i>eth_ip_mask</i>	(Optional) IP address mask
<i>eth_ip_prefix</i>	(Optional) IP address prefix
<i>eth_mtu</i>	(Optional) MTU
<i>eth_bw</i>	(Optional) Bandwidth
<i>eth_dly</i>	(Optional) Delay
<i>eth_reliability</i>	(Optional) Reliability
<i>eth_txload</i>	(Optional) Tx load
<i>eth_rxload</i>	(Optional) Rx load
<i>eth_encap_vlan</i>	(Optional) Encapsulation Vlan
<i>medium</i>	(Optional) medium type
<i>eth_mode</i>	(Optional) Port mode
<i>eth_duplex</i>	(Optional) Duplex
<i>eth_speed</i>	(Optional) Speed
<i>eth_media</i>	(Optional) Media type
<i>eth_beacon</i>	(Optional) Beacon

<i>eth_autoneg</i>	(Optional) Autonegotiation
<i>eth_in_flowctrl</i>	(Optional) Input flowcontrol
<i>eth_out_flowctrl</i>	(Optional) Output flowcontrol
<i>eth_mdix</i>	(Optional) Mdix
<i>eth_ratemode</i>	(Optional) Rate mode
<i>eth_swt_monitor</i>	(Optional) Switchport Monitor
<i>eth_ethertype</i>	(Optional) EtherType
<i>eth_eee_state</i>	(Optional) EEE state
<i>eth_members</i>	(Optional) Members in this channel
<i>eth_link_flapped</i>	(Optional) Last link flapped
<i>eth_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>eth_reset_cntr</i>	(Optional) Interface resets
<i>eth_load_interval1</i>	(Optional) interval 1 timer value in sec
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec
<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate1_summary_bits</i>	(Optional) interval 1 input rate bit summary
<i>eth_inrate1_summary_pkts</i>	(Optional) interval 1 input rate pkt summary
<i>eth_outrate1_summary_bits</i>	(Optional) interval 1 output rate bit summary
<i>eth_outrate1_summary_pkts</i>	(Optional) interval 1 output rate pkt summary
<i>eth_load_interval2_rx</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_load_interval2_tx</i>	(Optional) interval 2 timer value in sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec

<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate2_summary_bits</i>	(Optional) interval 2 input rate bit summary
<i>eth_inrate2_summary_pkts</i>	(Optional) interval 2 input rate pkt summary
<i>eth_outrate2_summary_bits</i>	(Optional) interval 2 output rate bit summary
<i>eth_outrate2_summary_pkts</i>	(Optional) interval 2 output rate pkt summary
<i>eth_load_interval3_rx</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_load_interval3_tx</i>	(Optional) interval 3 timer value in sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_inrate3_summary_bits</i>	(Optional) interval 3 input rate bit summary
<i>eth_inrate3_summary_pkts</i>	(Optional) interval 3 input rate pkt summary
<i>eth_outrate3_summary_bits</i>	(Optional) interval 3 output rate bit summary
<i>eth_outrate3_summary_pkts</i>	(Optional) interval 3 output rate pkt summary
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 out switched ucast pkts

<i>eth_l3out_ucastbytes</i>	(Optional) L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) L3 out switched mcast pkts
<i>eth_l3out_mcastbytes</i>	(Optional) L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_jumbo_inpkts</i>	(Optional) Incoming jumbo pkts
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_runts</i>	(Optional) runts
<i>eth_giants</i>	(Optional) giants
<i>eth_crc</i>	(Optional) CRC
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_inerr</i>	(Optional) input errors
<i>eth_frame</i>	(Optional) frame
<i>eth_overnrun</i>	(Optional) overrun
<i>eth_underrun</i>	(Optional) underruns
<i>eth_ignored</i>	(Optional) ignored

<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_indiscard</i>	(Optional) discards
<i>eth_inpause</i>	(Optional) pause input
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_jumbo_outpkts</i>	(Optional) Outgoing jumbo pkts
<i>eth_outerr</i>	(Optional) output errors
<i>eth_coll</i>	(Optional) collisions
<i>eth_deferred</i>	(Optional) deferred
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_babbles</i>	(Optional) babbles
<i>eth_outdiscard</i>	(Optional) output discard
<i>eth_outpause</i>	(Optional) PAUSE output
<i>switchport</i>	(Optional) Switchport enabled

Command Mode

- /exec

show interface

```
show interface <ifrange> [ __readonly__ TABLE_interface <interface> <state> <state_rsn> <state_rsn_desc>
<desc> [ <overlay_addr> ] [ <overlay_addr_mask> ] [ <overlay_mtu> ] [ <overlay_bandwidth> ] [
<overlay_encap_str> ] [ <overlay_vrf> ] [ <overlay_src_addr> ] [ <overlay_dst_addr> ] [
<overlay_last_link_flap> ] [ <overlay_clear_counters> ] [ <overlay_load_interval> ] [ <overlay_rx_ucastpkts>
] [ <overlay_rx_ucastbytes> ] [ <overlay_rx_mcastpkts> ] [ <overlay_rx_mcastbytes> ] [ <overlay_rx_pkts>
] [ <overlay_rx_bytes> ] [ <overlay_rx_bcastpkts> ] [ <overlay_rx_bcastbytes> ] [ <overlay_rx_bitrate> ] [
<overlay_rx_pktrate> ] [ <overlay_tx_ucastpkts> ] [ <overlay_tx_ucastbytes> ] [ <overlay_tx_mcastpkts> ]
[ <overlay_tx_mcastbytes> ] [ <overlay_tx_bcastpkts> ] [ <overlay_tx_bcastbytes> ] [ <overlay_tx_pkts> ]
[ <overlay_tx_bytes> ] [ <overlay_tx_bitrate> ] [ <overlay_tx_pktrate> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>desc</i>	(Optional) Interface description
<i>overlay_addr</i>	(Optional) Overlay address
<i>overlay_addr_mask</i>	(Optional) Overlay address mask
<i>overlay_mtu</i>	(Optional) MTU
<i>overlay_bandwidth</i>	(Optional) Bandwidth
<i>overlay_encap_str</i>	(Optional) Encap type
<i>overlay_vrf</i>	(Optional) VRF
<i>overlay_src_addr</i>	(Optional) Source address
<i>overlay_dst_addr</i>	(Optional) Destination address
<i>overlay_last_link_flap</i>	(Optional) Last link flap
<i>overlay_clear_counters</i>	(Optional) Last clearing of show interface counters

<i>overlay_load_interval</i>	(Optional) Load interval
<i>overlay_rx_ucastpkts</i>	(Optional) Received ucast pkts
<i>overlay_rx_ucastbytes</i>	(Optional) Received ucast bytes
<i>overlay_rx_mcastpkts</i>	(Optional) Received mcast pkts
<i>overlay_rx_mcastbytes</i>	(Optional) Received mcast bytes
<i>overlay_rx_bcastpkts</i>	(Optional) Received bcast pkts
<i>overlay_rx_bcastbytes</i>	(Optional) Received bcast bytes
<i>overlay_rx_pkts</i>	(Optional) Total received pkts
<i>overlay_rx_bytes</i>	(Optional) Total received bytes
<i>overlay_rx_bitrate</i>	(Optional) Receive bit rate
<i>overlay_rx_pktrate</i>	(Optional) Receive pkt rate
<i>overlay_tx_ucastpkts</i>	(Optional) Trasnmitted ucast pkts
<i>overlay_tx_ucastbytes</i>	(Optional) Trasnmitted ucast bytes
<i>overlay_tx_mcastpkts</i>	(Optional) Trasnmitted mcast pkts
<i>overlay_tx_mcastbytes</i>	(Optional) Trasnmitted mcast bytes
<i>overlay_tx_bcastpkts</i>	(Optional) Trasnmitted bcast pkts
<i>overlay_tx_bcastbytes</i>	(Optional) Trasnmitted bcast bytes
<i>overlay_tx_pkts</i>	(Optional) Total transmitted pkts
<i>overlay_tx_bytes</i>	(Optional) Total transmitted bytes
<i>overlay_tx_bitrate</i>	(Optional) Transmit bit rate
<i>overlay_tx_pktrate</i>	(Optional) Transmit pkt rate

Command Mode

- /exec

show interface

```
show interface <ifrange> [ __readonly__ TABLE interface <interface> <state> [ <state_rsn_desc> ] [
<state_rsn> ] [ <admin_state> ] [ <eth_rsn_fac> ] [ <eth_rsn_code> ] [ <share_state> ] [ <vpc_status> ] [
<eth_bundle> ] [ <eth_hw_desc> ] [ <eth_hw_addr> ] [ <eth_bia_addr> ] [ <desc> ] [ <eth_ip_addr> ] [
<eth_ip_mask> ] [ <eth_mtu> ] [ <eth_bw> ] [ <eth_dly> ] [ <eth_reliability> ] [ <eth_txload> ] [ <eth_rxload>
] [ <eth_encap_vlan> ] [ <eth_mode> ] [ <eth_duplex> ] [ <eth_speed> ] [ <eth_media> ] [ <eth_beacon> ]
[ <eth_autoneg> ] [ <eth_in_flowctrl> ] [ <eth_out_flowctrl> ] [ <eth_mdix> ] [ <eth_ratemode> ] [
<eth_swt_monitor> ] [ <eth_etherthtype> ] [ <eth_members> ] [ <eth_link_flapped> ] [ <eth_clear_counters>
] [ <eth_reset_cntr> ] [ <nve_addr> ] [ <nve_addr_mask> ] [ <nve_vcid> ] [ <nve_mtu> ] [ <nve_bandwidth>
] [ <nve_encap_str> ] [ <nve_vrf> ] [ <nve_src_addr> ] [ <nve_dst_addr> ] [ <nve_last_link_flap> ] [
<nve_clear_counters> ] [ <nve_load_interval> ] [ <nve_rx_ucastpkts> ] [ <nve_rx_ucastbytes> ] [
<nve_rx_mcastpkts> ] [ <nve_rx_mcastbytes> ] [ <nve_rx_pkts> ] [ <nve_rx_bytes> ] [ <nve_rx_bcastpkts>
] [ <nve_rx_bcastbytes> ] [ <nve_rx_bitrate> ] [ <nve_rx_pktrate> ] [ <nve_tx_ucastpkts> ] [
<nve_tx_ucastbytes> ] [ <nve_tx_mcastpkts> ] [ <nve_tx_mcastbytes> ] [ <nve_tx_bcastpkts> ] [
<nve_tx_bcastbytes> ] [ <nve_tx_pkts> ] [ <nve_tx_bytes> ] [ <nve_tx_bitrate> ] [ <nve_tx_pktrate> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>state_rsn</i>	(Optional) Interface state reason
<i>admin_state</i>	(Optional) admin state
<i>eth_rsn_fac</i>	(Optional) State reason facility
<i>eth_rsn_code</i>	(Optional) State reason code
<i>share_state</i>	(Optional) Interface ownership
<i>vpc_status</i>	(Optional) VPC status
<i>eth_bundle</i>	(Optional) Belongs to bundle
<i>eth_hw_desc</i>	(Optional) HW description
<i>eth_hw_addr</i>	(Optional) HW address
<i>eth_bia_addr</i>	(Optional) bia address

<i>desc</i>	(Optional) Interface description
<i>eth_ip_addr</i>	(Optional) IP Address
<i>eth_ip_mask</i>	(Optional) IP address mask
<i>eth_mtu</i>	(Optional) MTU
<i>eth_bw</i>	(Optional) Bandwidth
<i>eth_dly</i>	(Optional) Delay
<i>eth_reliability</i>	(Optional) Reliability
<i>eth_txload</i>	(Optional) Tx load
<i>eth_rxload</i>	(Optional) Rx load
<i>eth_encap_vlan</i>	(Optional) Encapsulation Vlan
<i>eth_mode</i>	(Optional) Port mode
<i>eth_duplex</i>	(Optional) Duplex
<i>eth_speed</i>	(Optional) Speed
<i>eth_media</i>	(Optional) Media type
<i>eth_beacon</i>	(Optional) Beacon
<i>eth_autoneg</i>	(Optional) Autonegotiation
<i>eth_in_flowctrl</i>	(Optional) Input flowcontrol
<i>eth_out_flowctrl</i>	(Optional) Output flowcontrol
<i>eth_mdix</i>	(Optional) Mdx
<i>eth_ratemode</i>	(Optional) Rate mode
<i>eth_swt_monitor</i>	(Optional) Switchport Monitor
<i>eth_ethertype</i>	(Optional) EtherType
<i>eth_members</i>	(Optional) Members in this channel
<i>eth_link_flapped</i>	(Optional) Last link flapped
<i>eth_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>eth_reset_cntr</i>	(Optional) Interface resets
<i>nve_addr</i>	(Optional) Peer address
<i>nve_addr_mask</i>	(Optional) Peer address mask
<i>nve_vcid</i>	(Optional) VCID

<i>nve_mtu</i>	(Optional) MTU
<i>nve_bandwidth</i>	(Optional) Bandwidth
<i>nve_encap_str</i>	(Optional) Encap type
<i>nve_vrf</i>	(Optional) VRF
<i>nve_src_addr</i>	(Optional) Source address
<i>nve_dst_addr</i>	(Optional) Destination address
<i>nve_last_link_flap</i>	(Optional) Last link flap
<i>nve_clear_counters</i>	(Optional) Last clearing of show interface counters
<i>nve_load_interval</i>	(Optional) Load interval
<i>nve_rx_ucastpkts</i>	(Optional) Received ucast pkts
<i>nve_rx_ucastbytes</i>	(Optional) Received ucast bytes
<i>nve_rx_mcastpkts</i>	(Optional) Received mcast pkts
<i>nve_rx_mcastbytes</i>	(Optional) Received mcast bytes
<i>nve_rx_bcastpkts</i>	(Optional) Received bcast pkts
<i>nve_rx_bcastbytes</i>	(Optional) Received bcast bytes
<i>nve_rx_pkts</i>	(Optional) Total received pkts
<i>nve_rx_bytes</i>	(Optional) Total received bytes
<i>nve_rx_bitrate</i>	(Optional) Receive bit rate
<i>nve_rx_pktrate</i>	(Optional) Receive pkt rate
<i>nve_tx_ucastpkts</i>	(Optional) Trasnmitted ucast pkts
<i>nve_tx_ucastbytes</i>	(Optional) Trasnmitted ucast bytes
<i>nve_tx_mcastpkts</i>	(Optional) Trasnmitted mcast pkts
<i>nve_tx_mcastbytes</i>	(Optional) Trasnmitted mcast bytes
<i>nve_tx_bcastpkts</i>	(Optional) Trasnmitted bcast pkts
<i>nve_tx_bcastbytes</i>	(Optional) Trasnmitted bcast bytes
<i>nve_tx_pkts</i>	(Optional) Total transmitted pkts
<i>nve_tx_bytes</i>	(Optional) Total transmitted bytes
<i>nve_tx_bitrate</i>	(Optional) Transmit bit rate
<i>nve_tx_pktrate</i>	(Optional) Transmit pkt rate

Command Mode

- /exec

show interface brief

```
show interface <ifrange> brief [ __readonly__ TABLE_interface <interface> <state> [ <state_rsn> ] [
<state_rsn_desc> ] [ <overlay_mtu> ] [ <overlay_bandwidth> ] [ <overlay_vrf> ] [ <overlay_src_addr> ] [
<overlay_dst_addr> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
brief	Show brief info of interface
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>overlay_mtu</i>	(Optional) MTU
<i>overlay_bandwidth</i>	(Optional) Bandwidth
<i>overlay_vrf</i>	(Optional) VRF
<i>overlay_src_addr</i>	(Optional) Source address
<i>overlay_dst_addr</i>	(Optional) Destination address

Command Mode

- /exec

show interface brief

```
show interface <ifpch_brf> brief [ __readonly__ TABLE_interface <interface> [ <vlan> ] <type> <portmode>
<state> <state_rsn_desc> <speed> <ratemode> [ <proto> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifpch_brf</i>	Enter interface type and number in module/slot format
brief	Show brief info of interface
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>vlan</i>	(Optional) Vlan
<i>type</i>	(Optional) Type
<i>portmode</i>	(Optional) Port mode
<i>state</i>	(Optional) Interface state
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>speed</i>	(Optional) Speed
<i>ratemode</i>	(Optional) Interface port speed
<i>proto</i>	(Optional) Port Channel Protocol

Command Mode

- /exec

show interface brief

```
show interface brief [ controller | cli ] [ __readonly__ TABLE_interface [ <interface> ] [ <vlan> ] [ <type> ]
[ <portmode> ] [ <state> ] [ <state_rsn> ] [ <state_rsn_desc> ] [ <desc> ] [ <vrf> ] [ <ipv6_addr> ] [ <ip_addr>
] [ <speed> ] [ <mtu> ] [ <ratemode> ] [ <portchan> ] [ <proto> ] [ <interface_vfc> ] [ <vsan_brief> ] [
<admin_mode> ] [ <admin_trunk_mode> ] [ <status> ] [ <fcot_info> ] [ <bind_info> ] [ <bind_type> ] [
<port_rate_mode> ] [ <oper_speed> ] [ <port_channel> ] [ <ip_addr1> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
brief	Show brief info of interface
controller	(Optional) Show controller configured interfaces
cli	(Optional) Show CLI configured interfaces
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>desc</i>	(Optional) Interface description
<i>vrf</i>	(Optional) Vrf membership
<i>ip_addr</i>	(Optional) IP address
<i>mtu</i>	(Optional) MTU
<i>speed</i>	(Optional) Speed
<i>vlan</i>	(Optional) Vlan
<i>type</i>	(Optional) Type
<i>portmode</i>	(Optional) Port mode
<i>ratemode</i>	(Optional) Interface port speed
<i>portchan</i>	(Optional) Port Channel Membership
<i>proto</i>	(Optional) Port Channel Protocol
<i>interface_vfc</i>	(Optional) Interface index

<i>vsan_brief</i>	(Optional) vsan brief
<i>admin_mode</i>	(Optional) admin mode
<i>admin_trunk_mode</i>	(Optional) admin trunk mode
<i>status</i>	(Optional) status
<i>fcot_info</i>	(Optional) fcot info
<i>bind_info</i>	(Optional) bind interface
<i>bind_type</i>	(Optional) bind type
<i>port_rate_mode</i>	(Optional) rate mode
<i>oper_speed</i>	(Optional) speed
<i>port_channel</i>	(Optional) port channel number
<i>ip_addr1</i>	(Optional) IP address

Command Mode

- /exec

show interface brief

show interface <ifloop_brf> brief [__readonly__ TABLE_interface <interface> <state> [<desc>]]

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifloop_brf</i>	Enter interface type and number in module/slot format
brief	Show brief info of interface
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>desc</i>	(Optional) Interface description

Command Mode

- /exec

show interface brief

```
show interface <iftunnel_brf> brief [ __readonly__ TABLE_interface <interface> <state> <admin-state> {
<tunnel-ipv4> | <tunnel-ipv6> } <mtu> <bandwidth> <encap-type> <keepalive-period> <keepalive-retries>
{ <src-ipv4> | <src-ipv6> } <src-intf> { <dest-ipv4> | <dest-ipv6> } <dest-hostname> <vrf_name>
<wccp_header> <ttl_val> <tunnel_pmtud_age_time> <tunnel_pmtud_min_mtu> <tunnel_pmtud>
<tunnel_pgm_mtu> <tunnel_rx_pkt_count> <tunnel_rx_byte_count> <tunnel_rx_rate> <tunnel_tx_pkt_count>
<tunnel_tx_byte_count> <tunnel_tx_rate> <tunnel_clear_counter> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>iftunnel_brf</i>	Enter interface type and number in module/slot format
brief	Show brief info of interface
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>admin-state</i>	(Optional)
<i>tunnel-ipv4</i>	(Optional) interface IPv4 address
<i>mtu</i>	(Optional) interface Maximum Transmission Unit
<i>bandwidth</i>	(Optional) interface Bandwidth in kilobits
<i>encap-type</i>	(Optional)
<i>keepalive-period</i>	(Optional) keealive period
<i>keepalive-retries</i>	(Optional) number of retries
<i>src-ipv4</i>	(Optional) tunnel source IPv4 address
<i>src-intf</i>	(Optional) tunnel source interface
<i>dest-ipv4</i>	(Optional) tunnel destination IPv4 address
<i>dest-hostname</i>	(Optional) tunnel destination hostname
<i>vrf_name</i>	(Optional) transport VRF name
<i>wccp_header</i>	(Optional) wccp header
<i>ttl_val</i>	(Optional) tunnel time to live value

<i>tunnel_pmtud_age_time</i>	(Optional) tunnel path MTU discovery age time
<i>tunnel_pmtud_min_mtu</i>	(Optional) tunnel path MTU discovery min mtu
<i>tunnel_pmtud</i>	(Optional) tunnel path MTU discovered
<i>tunnel_pgm_mtu</i>	(Optional) tunnel actual programmed MTU
<i>tunnel_rx_pkt_count</i>	(Optional) total number of packets received
<i>tunnel_rx_byte_count</i>	(Optional) total number of bytes received
<i>tunnel_rx_rate</i>	(Optional) packets input rate per 5 minutes
<i>tunnel_tx_pkt_count</i>	(Optional) total number of packets transmitted
<i>tunnel_tx_byte_count</i>	(Optional) total number of bytes transmitted
<i>tunnel_tx_rate</i>	(Optional) packets transmitted per 5 minutes
<i>tunnel_clear_counter</i>	(Optional) Last clearing of show interface counters

Command Mode

- /exec

show interface brief

```
show interface <ifmgmt_brf> brief [ __readonly__ TABLE_interface <interface> [ <vrf> ] <state> [
<ipv6_addr> ] [ <ip_addr> ] <mtu> <speed> [ <duplex> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifmgmt_brf</i>	Enter interface type and number in module/slot format
brief	Show brief info of interface
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>vrf</i>	(Optional) Vrf membership
<i>state</i>	(Optional) Interface state
<i>ip_addr</i>	(Optional) IP address
<i>mtu</i>	(Optional) MTU
<i>speed</i>	(Optional) Speed
<i>duplex</i>	(Optional) Duplex

Command Mode

- /exec

show interface brief

```
show interface <ifeth_brf> brief [ __readonly__ TABLE_interface <interface> [ <vlan> ] <type> <portmode>
<state> <state_rsn_desc> <speed> <ratemode> [ <portchan> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_brf</i>	Enter interface type and number in module/slot format
brief	Show brief info of interface
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>vlan</i>	(Optional) Vlan
<i>type</i>	(Optional) Type
<i>portmode</i>	(Optional) Port mode
<i>state</i>	(Optional) Interface state
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>speed</i>	(Optional) Speed
<i>ratemode</i>	(Optional) Interface port speed
<i>portchan</i>	(Optional) Port Channel Membership

Command Mode

- /exec

show interface brief

```
show interface <ifrange> brief [ __readonly__ TABLE interface <interface> <state> [ <state_rsn> ] [
<state_rsn_desc> ] [ <admin_state> ] [ <nve_addr> ] [ <nve_vcid> ] [ <nve_mtu> ] [ <nve_bandwidth> ] [
<nve_vrf> ] [ <nve_src_addr> ] [ <nve_dst_addr> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
brief	Show brief info of interface
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>admin_state</i>	(Optional) admin state
<i>nve_addr</i>	(Optional) Peer address
<i>nve_vcid</i>	(Optional) VCID
<i>nve_mtu</i>	(Optional) MTU
<i>nve_bandwidth</i>	(Optional) Bandwidth
<i>nve_vrf</i>	(Optional) VRF
<i>nve_src_addr</i>	(Optional) Source address
<i>nve_dst_addr</i>	(Optional) Destination address

Command Mode

- /exec

show interface cable-diagnostics-tdr

```
show interface <ifid_tdr> cable-diagnostics-tdr [ __readonly__ TABLE_interface <interface> <speed>
<distance1> <pair1_status> <distance2> <pair2_status> <distance3> <pair3_status> <distance4> <pair4_status>
]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifid_tdr</i>	Enter interface type and number in module/slot format
<code>cable-diagnostics-tdr</code>	Show interface tdr test information
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>speed</i>	(Optional) Speed
<i>distance1</i>	(Optional) Distance to fault for pair 1
<i>distance2</i>	(Optional) Distance to fault for pair 2
<i>distance3</i>	(Optional) Distance to fault for pair 3
<i>distance4</i>	(Optional) Distance to fault for pair 4
<i>pair1_status</i>	(Optional) Pair1 status
<i>pair2_status</i>	(Optional) Pair2 status
<i>pair3_status</i>	(Optional) Pair3 status
<i>pair4_status</i>	(Optional) Pair4 status

Command Mode

- /exec

show interface capabilities

```
show interface capabilities [ __readonly__ TABLE_interface <interface> <model> <type> <speed> <duplex>
<trunk_encap> [ <dce_capable> ] <channel> <bcast_supp> <flo_ctrl> <rate_mode> <port_mode> [ <fast_start>
] <qos_scheduling> <cos_rewrite> <tos_rewrite> [ <inline_power> ] <span> <udld> [ <mdix> ] [ <tdr> ]
<lnk_debounce> <lnk_debounce_time> <fex_fabric> <dot1q_tunnel> [ <pvlan_trunk_mode> ] [ <port_group>
] [ <port_group_members> ] <eee_capable> <pfc_capable> [ <speed_group_capable> ] <buffer_boost_capable>
[ <bkout_capable> ] [ <macsec_capable> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<code>capabilities</code>	Show interface capabilities information
<code>__readonly__</code>	(Optional) Read Only
<code>interface</code>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<code>model</code>	(Optional) Model
<code>type</code>	(Optional) Type
<code>speed</code>	(Optional) Speed
<code>duplex</code>	(Optional) Duplex
<code>trunk_encap</code>	(Optional) Trunk encap. type
<code>dce_capable</code>	(Optional) DCE mode capable
<code>channel</code>	(Optional) Channel
<code>bcast_supp</code>	(Optional) Broadcast suppression
<code>flo_ctrl</code>	(Optional) Flowcontrol
<code>rate_mode</code>	(Optional) Rate mode
<code>port_mode</code>	(Optional) Port mode
<code>fast_start</code>	(Optional) Fast start
<code>qos_scheduling</code>	(Optional) QOS scheduling
<code>cos_rewrite</code>	(Optional) CoS rewrite
<code>tos_rewrite</code>	(Optional) ToS rewrite
<code>inline_power</code>	(Optional) Inline power

<i>span</i>	(Optional) SPAN
<i>udld</i>	(Optional) UDLD
<i>mdix</i>	(Optional) MDIX
<i>tdr</i>	(Optional) TDR
<i>lnk_debounce</i>	(Optional) Link debounce
<i>lnk_debounce_time</i>	(Optional) Link debounce time
<i>fex_fabric</i>	(Optional) FEX Fabric
<i>dot1q_tunnel</i>	(Optional) dot1q-tunnel
<i>pvlan_trunk_mode</i>	(Optional) Private-vlan trunk mode
<i>port_group</i>	(Optional) Port Group
<i>port_group_members</i>	(Optional) Port Group Members
<i>eee_capable</i>	(Optional) EEE (efficient-eth)
<i>pfc_capable</i>	(Optional) PFC Capable:
<i>bkout_capable</i>	(Optional) Breakout Capable:
<i>buffer_boost_capable</i>	(Optional) Buffer Boost Capable:
<i>speed_group_capable</i>	(Optional) Speed group capable
<i>macsec_capable</i>	(Optional) MACSEC capable

Command Mode

- /exec

show interface capabilities

```
show interface <ifid_eth_cap> capabilities [ __readonly__ TABLE_interface <interface> <model> <type>
<speed> <duplex> <trunk_encap> [ <dce_capable> ] <channel> <bcast_supp> <flo_ctrl> <rate_mode>
<port_mode> [ <fast_start> ] <qos_scheduling> <cos_rewrite> <tos_rewrite> [ <inline_power> ] <span>
<udld> [ <mdix> ] [ <tdr> ] <lnk_debounce> <lnk_debounce_time> <fex_fabric> <dot1q_tunnel> [
<pvlan_trunk_mode> ] [ <port_group> ] [ <port_group_members> ] <eee_capable> <pfc_capable> [
<speed_group_capable> ] <buffer_boost_capable> [ <bkout_capable> ] [ <macsec_capable> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_eth_cap</i>	Enter interface type and number in module/slot format
capabilities	Show interface capabilities information
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>model</i>	(Optional) Model
<i>type</i>	(Optional) Type
<i>speed</i>	(Optional) Speed
<i>duplex</i>	(Optional) Duplex
<i>trunk_encap</i>	(Optional) Trunk encap. type
<i>dce_capable</i>	(Optional) DCE mode capable
<i>channel</i>	(Optional) Channel
<i>bcast_supp</i>	(Optional) Broadcast suppression
<i>flo_ctrl</i>	(Optional) Flowcontrol
<i>rate_mode</i>	(Optional) Rate mode
<i>port_mode</i>	(Optional) Port mode
<i>fast_start</i>	(Optional) Fast start
<i>qos_scheduling</i>	(Optional) QOS scheduling
<i>cos_rewrite</i>	(Optional) CoS rewrite
<i>tos_rewrite</i>	(Optional) ToS rewrite

<i>inline_power</i>	(Optional) Inline power
<i>span</i>	(Optional) SPAN
<i>udld</i>	(Optional) UDLD
<i>mdix</i>	(Optional) MDIX
<i>tdr</i>	(Optional) TDR
<i>lnk_debounce</i>	(Optional) Link debounce
<i>lnk_debounce_time</i>	(Optional) Link debounce time
<i>fex_fabric</i>	(Optional) FEX Fabric
<i>dot1q_tunnel</i>	(Optional) dot1q-tunnel
<i>pvlan_trunk_mode</i>	(Optional) Private-vlan trunk mode
<i>port_group</i>	(Optional) Port Group
<i>port_group_members</i>	(Optional) Port Group Members
<i>eee_capable</i>	(Optional) EEE (efficient-eth)
<i>pfc_capable</i>	(Optional) PFC Capable:
<i>bkout_capable</i>	(Optional) Breakout Capable:
<i>buffer_boost_capable</i>	(Optional) Buffer Boost Capable:
<i>speed_group_capable</i>	(Optional) Speed group capable
<i>macsec_capable</i>	(Optional) MACSEC capable

Command Mode

- /exec

show interface counters

```
show interface <ifrange> counters [ __readonly__ TABLE_interface <interface> [ <overlay_load_interval>
] [ <overlay_rx_ucastpkts> ] [ <overlay_rx_ucastbytes> ] [ <overlay_rx_mcastpkts> ] [
<overlay_rx_mcastbytes> ] [ <overlay_rx_pkts> ] [ <overlay_rx_bytes> ] [ <overlay_rx_bcastpkts> ] [
<overlay_rx_bcastbytes> ] [ <overlay_rx_bitrate> ] [ <overlay_rx_pktrate> ] [ <overlay_tx_ucastpkts> ] [
<overlay_tx_ucastbytes> ] [ <overlay_tx_mcastpkts> ] [ <overlay_tx_mcastbytes> ] [ <overlay_tx_bcastpkts>
] [ <overlay_tx_bcastbytes> ] [ <overlay_tx_pkts> ] [ <overlay_tx_bytes> ] [ <overlay_tx_bitrate> ] [
<overlay_tx_pktrate> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
counters	Show interface counters
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>overlay_load_interval</i>	(Optional) Load interval
<i>overlay_rx_ucastpkts</i>	(Optional) Received ucast pkts
<i>overlay_rx_ucastbytes</i>	(Optional) Received ucast bytes
<i>overlay_rx_mcastpkts</i>	(Optional) Received mcast pkts
<i>overlay_rx_mcastbytes</i>	(Optional) Received mcast bytes
<i>overlay_rx_bcastpkts</i>	(Optional) Received bcast pkts
<i>overlay_rx_bcastbytes</i>	(Optional) Received bcast bytes
<i>overlay_rx_pkts</i>	(Optional) Total received pkts
<i>overlay_rx_bytes</i>	(Optional) Total received bytes
<i>overlay_rx_bitrate</i>	(Optional) Receive bit rate
<i>overlay_rx_pktrate</i>	(Optional) Receive pkt rate
<i>overlay_tx_ucastpkts</i>	(Optional) Trasnmitted ucast pkts
<i>overlay_tx_ucastbytes</i>	(Optional) Trasnmitted ucast bytes
<i>overlay_tx_mcastpkts</i>	(Optional) Trasnmitted mcast pkts
<i>overlay_tx_mcastbytes</i>	(Optional) Trasnmitted mcast bytes

<i>overlay_tx_bcastpkts</i>	(Optional) Trasnmitted bcast pkts
<i>overlay_tx_bcastbytes</i>	(Optional) Trasnmitted bcast bytes
<i>overlay_tx_pkts</i>	(Optional) Total transmitted pkts
<i>overlay_tx_bytes</i>	(Optional) Total transmitted bytes
<i>overlay_tx_bitrate</i>	(Optional) Transmit bit rate
<i>overlay_tx_pktrate</i>	(Optional) Transmit pkt rate

Command Mode

- /exec

show interface counters

```
show interface <ifid_ctr> counters [ snmp ] [ __readonly__ { TABLE_rx_counters <interface_rx> [
<eth_inpkts> ] [ <eth_inbytes> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] } { TABLE_tx_counters
<interface_tx> [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_ctr</i>	Enter interface type and number in module/slot format
counters	Show interface counters
snmp	(Optional) Show SNMP MIB values
<i>__readonly__</i>	(Optional) Read Only
<i>interface_rx</i>	(Optional) Interface index rx
<i>interface_tx</i>	(Optional) Interface index tx
TABLE_rx_counters	(Optional) show Rx counters
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
TABLE_tx_counters	(Optional) show Tx counters
<i>eth_outpkts</i>	(Optional) Packets output
<i>eth_outbytes</i>	(Optional) Bytes output
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts

Command Mode

- /exec

show interface counters

```
show interface counters [ module <module> ] [ __readonly__ { TABLE_rx_counters <interface_rx> [
<eth_inpkts> ] [ <eth_inbytes> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_l3in_bytes> ]
[ <eth_l3in_ucastpkts> ] [ <eth_l3in_mcastpkts> ] [ <eth_l3in_bcastpkts> ] } } { TABLE_tx_counters
<interface_tx> [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] [ <eth_l3out_bytes> ] [ <eth_l3out_ucastpkts> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_bcastpkts> ] } }
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
<i>__readonly__</i>	(Optional) Read Only
<i>interface_rx</i>	(Optional) Interface index rx
<i>interface_tx</i>	(Optional) Interface index tx
TABLE_rx_counters	(Optional) show Rx counters
TABLE_tx_counters	(Optional) show Tx counters
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_outpkts</i>	(Optional) Packets output
<i>eth_outbytes</i>	(Optional) Bytes output
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_l3in_bytes</i>	(Optional) L3 Rx bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 Rx Unicast pkts
<i>eth_l3in_mcastpkts</i>	(Optional) L3 Rx Multicast pkts

<i>eth_l3in_bcastpkts</i>	(Optional) L3 Rx Broadcast pkts
<i>eth_l3out_bytes</i>	(Optional) L3 Tx bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 Tx Unicast pkts
<i>eth_l3out_mcastpkts</i>	(Optional) L3 Tx Multicast pkts
<i>eth_l3out_bcastpkts</i>	(Optional) L3 Tx Broadcast pkts

Command Mode

- /exec

show interface counters

```
show interface counters [ non-zero ] [ __readonly__ { TABLE_rx_counters <interface_rx> [ <eth_inpkts> ]
[ <eth_inbytes> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_l3in_bytes> ] [
<eth_l3in_ucastpkts> ] [ <eth_l3in_mcastpkts> ] [ <eth_l3in_bcastpkts> ] } { TABLE_tx_counters
<interface_tx> [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] [ <eth_l3out_bytes> ] [ <eth_l3out_ucastpkts> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_bcastpkts> ] } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
non-zero	(Optional) To display only the non-zero counter values
__readonly__	(Optional) Read Only
<i>interface_rx</i>	(Optional) Interface index rx
<i>interface_tx</i>	(Optional) Interface index tx
TABLE_rx_counters	(Optional) show Rx counters
TABLE_tx_counters	(Optional) show Tx counters
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_outpkts</i>	(Optional) Packets output
<i>eth_outbytes</i>	(Optional) Bytes output
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_l3in_bytes</i>	(Optional) L3 Rx bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 Rx Unicast pkts
<i>eth_l3in_mcastpkts</i>	(Optional) L3 Rx Multicast pkts
<i>eth_l3in_bcastpkts</i>	(Optional) L3 Rx Broadcast pkts

<i>eth_l3out_bytes</i>	(Optional) L3 Tx bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 Tx Unicast pkts
<i>eth_l3out_mcastpkts</i>	(Optional) L3 Tx Multicast pkts
<i>eth_l3out_bcastpkts</i>	(Optional) L3 Tx Broadcast pkts

Command Mode

- /exec

show interface counters

```
show interface <ifeth_ctr> counters [ snmp ] [ __readonly__ { TABLE_rx_counters <interface_rx> [
<eth_inbytes> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_l3in_bytes> ] [
<eth_l3in_ucastpkts> ] [ <eth_l3in_mcastpkts> ] [ <eth_l3in_bcastpkts> ] } { TABLE_tx_counters
<interface_tx> [ <eth_outbytes> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast> ] [ <eth_l3out_bytes>
] [ <eth_l3out_ucastpkts> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_bcastpkts> ] } }
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr</i>	Enter interface type and number in module/slot format
counters	Show interface counters
snmp	(Optional) Show SNMP MIB values
__readonly__	(Optional) Read Only
TABLE_rx_counters	(Optional) show Rx counters
<i>interface_rx</i>	(Optional) Interface index rx
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_inucast</i>	(Optional) Unicasts input
<i>eth_inmcast</i>	(Optional) Multicasts input
<i>eth_inbcast</i>	(Optional) Broadcasts input
<i>eth_l3in_bytes</i>	(Optional) L3 Rx bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 Rx Unicast pkts
<i>eth_l3in_mcastpkts</i>	(Optional) L3 Rx Multicast pkts
<i>eth_l3in_bcastpkts</i>	(Optional) L3 Rx Broadcast pkts
TABLE_tx_counters	(Optional) show Tx counters
<i>interface_tx</i>	(Optional) Interface index tx
<i>eth_outbytes</i>	(Optional) Bytes output
<i>eth_outucast</i>	(Optional) Unicasts output
<i>eth_outmcast</i>	(Optional) Multicasts output
<i>eth_outbcast</i>	(Optional) Broadcasts output
<i>eth_l3out_bytes</i>	(Optional) L3 Tx bytes

<i>eth_l3out_ucastpkts</i>	(Optional) L3 Tx Unicast pkts
<i>eth_l3out_mcastpkts</i>	(Optional) L3 Tx Multicast pkts
<i>eth_l3out_bcastpkts</i>	(Optional) L3 Tx Broadcast pkts

Command Mode

- /exec

show interface counters

```
show interface <ifrange> counters [ __readonly__ { TABLE_nve_counters <interface> [ <ucast_inbytes> ]
[ <ucast_inpkts> ] [ <ucast_outbytes> ] [ <ucast_outpkts> ] [ <mcast_inbytes> ] [ <mcast_inpkts> ] [
<mcast_outbytes> ] [ <mcast_outpkts> ] } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number
counters	Show interface counters
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_nve_counters	(Optional) show interface
<i>ucast_inbytes</i>	(Optional) ucast bytes input
<i>ucast_inpkts</i>	(Optional) ucast packets input
<i>ucast_outbytes</i>	(Optional) ucast bytes output
<i>ucast_outpkts</i>	(Optional) ucast packets output
<i>mcast_inbytes</i>	(Optional) mcast bytes input
<i>mcast_inpkts</i>	(Optional) mcast packets input
<i>mcast_outbytes</i>	(Optional) mcast bytes output
<i>mcast_outpkts</i>	(Optional) mcast packets output

Command Mode

- /exec

show interface counters brief

```
show interface <ifeth_ctr_brf> counters brief [ <counter_val> ] [ __readonly__ TABLE_interface <interface>
<eth_inrate1> <eth_inframes1> <eth_outrate1> <eth_outframes1> <eth_load_intv1> <eth_inrate2>
<eth_inframes2> <eth_outrate2> <eth_outframes2> <eth_load_intv2> [ <eth_inrate3> <eth_inframes3>
<eth_outrate3> <eth_outframes3> <eth_load_intv3> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_brf</i>	Enter interface type and number in module/slot format
counters	Show interface counters
brief	Show interface counters in brief
<i>counter_val</i>	(Optional) Specify a single load interval id to show the rates
<i>__readonly__</i>	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>eth_inrate1</i>	(Optional) interval 1 input rate in mbps
<i>eth_inframes1</i>	(Optional) interval 1 input rate in frames (pkts)
<i>eth_outrate1</i>	(Optional) interval 1 output rate in mbps
<i>eth_outframes1</i>	(Optional) interval 1 output rate in output frames (pkts)
<i>eth_load_intv1</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate2</i>	(Optional) interval 2 input rate in mbps
<i>eth_inframes2</i>	(Optional) interval 2 input rate in frames (pkts)
<i>eth_outrate2</i>	(Optional) interval 2 output rate in mbps
<i>eth_outframes2</i>	(Optional) interval 2 output rate in output frames (pkts)
<i>eth_load_intv2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate3</i>	(Optional) interval 3 input rate in mbps
<i>eth_inframes3</i>	(Optional) interval 3 input rate in frames (pkts)
<i>eth_outrate3</i>	(Optional) interval 3 output rate in mbps
<i>eth_outframes3</i>	(Optional) interval 3 output rate in output frames (pkts)

<i>eth_load_intv3</i>	(Optional) interval 3 timer value in sec
-----------------------	--

Command Mode

- /exec

show interface counters brief

```
show interface counters brief [ <counter_val> ] [ __readonly__ TABLE_interface <interface> <eth_inrate1>
<eth_inframes1> <eth_outrate1> <eth_outframes1> <eth_load_intv1> <eth_inrate2> <eth_inframes2>
<eth_outrate2> <eth_outframes2> <eth_load_intv2> [ <eth_inrate3> <eth_inframes3> <eth_outrate3>
<eth_outframes3> <eth_load_intv3> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
brief	Show interface counters in brief
<i>counter_val</i>	(Optional) Specify a single load interval id to show the rates
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_inrate1</i>	(Optional) interval 1 input rate in mbps
<i>eth_inframes1</i>	(Optional) interval 1 input rate in frames (pkts)
<i>eth_outrate1</i>	(Optional) interval 1 output rate in mbps
<i>eth_outframes1</i>	(Optional) interval 1 output rate in output frames (pkts)
<i>eth_load_intv1</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate2</i>	(Optional) interval 2 input rate in mbps
<i>eth_inframes2</i>	(Optional) interval 2 input rate in frames (pkts)
<i>eth_outrate2</i>	(Optional) interval 2 output rate in mbps
<i>eth_outframes2</i>	(Optional) interval 2 output rate in output frames (pkts)
<i>eth_load_intv2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate3</i>	(Optional) interval 3 input rate in mbps
<i>eth_inframes3</i>	(Optional) interval 3 input rate in frames (pkts)
<i>eth_outrate3</i>	(Optional) interval 3 output rate in mbps
<i>eth_outframes3</i>	(Optional) interval 3 output rate in output frames (pkts)
<i>eth_load_intv3</i>	(Optional) interval 3 timer value in sec

Command Mode

- /exec

show interface counters detailed

```
show interface counters detailed [ snmp ] [ __readonly__ TABLE_interface <interface> [ <vdc_lvl_in_pkts>
] [ <vdc_lvl_in_bytes> ] [ <vdc_lvl_in_ucast> ] [ <vdc_lvl_in_mcast> ] [ <vdc_lvl_in_bcast> ] [
<vdc_lvl_in_bps> ] [ <vdc_lvl_in_pps> ] [ <vdc_lvl_in_avg_pkts> ] [ <vdc_lvl_in_avg_bytes> ] [
<vdc_lvl_out_pkts> ] [ <vdc_lvl_out_bytes> ] [ <vdc_lvl_out_ucast> ] [ <vdc_lvl_out_mcast> ] [
<vdc_lvl_out_bcast> ] [ <vdc_lvl_out_bps> ] [ <vdc_lvl_out_pps> ] [ <vdc_lvl_out_avg_pkts> ] [
<vdc_lvl_out_avg_bytes> ] [ <mgmt_in_pkts> ] [ <mgmt_in_bytes> ] [ <mgmt_in_mcast> ] [
<mgmt_in_compressed> ] [ <mgmt_in_errors> ] [ <mgmt_in_frame> ] [ <mgmt_in_overrun> ] [
<mgmt_in_fifo> ] [ <mgmt_out_pkts> ] [ <mgmt_out_bytes> ] [ <mgmt_out_underruns> ] [
<mgmt_out_errors> ] [ <mgmt_out_collisions> ] [ <mgmt_out_fifo> ] [ <mgmt_out_carrier> ] [
<mgmt_align_err> ] [ <mgmt_fcs_err> ] [ <mgmt_xmit_err> ] [ <mgmt_rcv_err> ] [ <mgmt_undersize> ] [
<mgmt_outdisc> ] [ <mgmt_single_coll> ] [ <mgmt_multi_coll> ] [ <mgmt_late_coll> ] [ <mgmt_excess_coll>
] [ <mgmt_carri_sen> ] [ <mgmt_runs> ] [ <mgmt_giants> ] [ <mgmt_sqetest_err> ] [ <mgmt_deferred_tx>
] [ <mgmt_inmactx_err> ] [ <mgmt_inmacrx_err> ] [ <mgmt_symbol_err> ] [ <loop_in_pkts> ] [
<loop_in_bytes> ] [ <loop_in_mcast> ] [ <loop_in_compressed> ] [ <loop_in_errors> ] [ <loop_in_frame>
] [ <loop_in_overrun> ] [ <loop_in_fifo> ] [ <loop_out_pkts> ] [ <loop_out_bytes> ] [ <loop_out_underruns>
] [ <loop_out_errors> ] [ <loop_out_collisions> ] [ <loop_out_fifo> ] [ <loop_out_carriers> ] [
<eth_load_interval1> ] [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [
<eth_load_interval1_tx> ] [ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [
<eth_inrate1_summary_bits> ] [ <eth_inrate1_summary_pkts> ] [ <eth_outrate1_summary_bits> ] [
<eth_outrate1_summary_pkts> ] [ <eth_load_interval2_rx> ] [ <eth_inrate2_bits> ] [ <eth_inrate2_pkts> ] [
<eth_load_interval2_tx> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [ <eth_load_interval3> ] [
<eth_inrate2_summary_bits> ] [ <eth_inrate2_summary_pkts> ] [ <eth_outrate2_summary_bits> ] [
<eth_outrate2_summary_pkts> ] [ <eth_load_interval3_rx> ] [ <eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [
<eth_load_interval3_tx> ] [ <eth_outrate3_bits> ] [ <eth_outrate3_pkts> ] [ <eth_inrate3_summary_bits> ]
[ <eth_inrate3_summary_pkts> ] [ <eth_outrate3_summary_bits> ] [ <eth_outrate3_summary_pkts> ] [
<eth_inpkts> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_ingiants> ] [ <eth_inbytes> ] [
<eth_storm_supp> ] [ <eth_inb64> ] [ <eth_inb65_127> ] [ <eth_inb128_255> ] [ <eth_inb256_511> ] [
<eth_inb512_1023> ] [ <eth_inb1024_1518> ] [ <eth_inb1519_1548> ] [ <eth_intrunk> ] [ <eth_outpkts> ]
[ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast> ] [ <eth_outgiants> ] [ <eth_outbytes> ] [ <eth_outb64>
] [ <eth_outb65_127> ] [ <eth_outb128_255> ] [ <eth_outb256_511> ] [ <eth_outb512_1023> ] [
<eth_outb1024_1518> ] [ <eth_outb1519_1548> ] [ <eth_outtrunk> ] [ <eth_nobuf> ] [ <eth_runs> ] [
<eth_crc> ] [ <eth_ecc> ] [ <eth_overrun> ] [ <eth_underrun> ] [ <eth_ignored> ] [ <eth_bad_eth> ] [
<eth_bad_proto> ] [ <eth_in_ifdown_drops> ] [ <eth_coll> ] [ <eth_latecoll> ] [ <eth_lostcarrier> ] [
<eth_nocarrier> ] [ <eth_babbles> ] [ <eth_watchdog> ] [ <eth_dribble> ] [ <eth_inerr> ] [ <eth_outerr> ] [
<eth_deferred> ] [ <eth_jabbers> ] [ <eth_shortframe> ] [ <eth_single_coll> ] [ <eth_multi_coll> ] [
<eth_excess_coll> ] [ <eth_indiscard> ] [ <eth_bad_encap> ] [ <eth_outcrc> ] [ <eth_symbol> ] [
<eth_out_drops> ] [ <eth_bpdu_outlost> ] [ <eth_cos0_outlost> ] [ <eth_cos1_outlost> ] [ <eth_cos2_outlost>
] [ <eth_cos3_outlost> ] [ <eth_cos4_outlost> ] [ <eth_cos5_outlost> ] [ <eth_cos6_outlost> ] [
<eth_cos7_outlost> ] [ <eth_inpause> ] [ <eth_outpause> ] [ <eth_resets> ] [ <eth_sqetest> ] [
<eth_l2_ucastpkts> ] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [ <eth_l2_mcastbytes> ] [
<eth_l2_bcastpkts> ] [ <eth_l2_bcastbytes> ] [ <eth_l3in_routed_pkts> ] [ <eth_l3in_routed_bytes> ] [
<eth_l3out_routed_pkts> ] [ <eth_l3out_routed_bytes> ] [ <eth_l3in_ucastpkts> ] [ <eth_l3in_ucastbytes> ]
[ <eth_l3in_mcastpkts> ] [ <eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [ <eth_l3in_bcastbytes> ] [
<eth_l3out_ucastpkts> ] [ <eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_mcastbytes> ] [
<eth_l3out_bcastpkts> ] [ <eth_l3out_bcastbytes> ] [ <eth_l3avg1_inbytes> ] [ <eth_l3avg1_inpkts> ] [
<eth_l3avg1_outbytes> ] [ <eth_l3avg1_outpkts> ] [ <eth_ipmcast> ] [ <eth_inhw_switched> ] [
<eth_insw_switched> ] [ <eth_throtles> ] [ <eth_frame> ] [ <eth_outhw_switched> ] [ <eth_outsw_switched>
] [ <eth_buffail> ] [ <eth_bufswapped> ] [ <eth_arpdrops> ] [ <eth_out_ifdown_drops> ] [ <eth_fcce_in_pkts>
```

```

] [ <eth_fcoe_in_octets> ] [ <eth_fcoe_out_pkts> ] [ <eth_fcoe_out_octets> ] [ <eth_nfcoe_in_pkts> ] [
<eth_nfcoe_in_octets> ] [ <eth_nfcoe_out_pkts> ] [ <eth_nfcoe_out_octets> ] [ <svi_routed_pkts_in> ] [
<svi_routed_bytes_in> ] [ <svi_routed_pkts_out> ] [ <svi_routed_bytes_out> ] [ <svi_ucast_pkts_in> ] [
<svi_ucast_bytes_in> ] [ <svi_mcast_pkts_in> ] [ <svi_mcast_bytes_in> ] [ <svi_ucast_pkts_out> ] [
<svi_ucast_bytes_out> ] [ <svi_mcast_pkts_out> ] [ <svi_mcast_bytes_out> ] [ <svi_ipv4_ucast_pkts_in> ]
[ <svi_ipv4_ucast_bytes_in> ] [ <svi_ipv4_ucast_pkts_out> ] [ <svi_ipv4_ucast_bytes_out> ] [
<svi_ipv4_mcast_pkts_in> ] [ <svi_ipv4_mcast_bytes_in> ] [ <svi_ipv4_mcast_pkts_out> ] [
<svi_ipv4_mcast_bytes_out> ] [ <svi_ipv6_ucast_pkts_in> ] [ <svi_ipv6_ucast_bytes_in> ] [
<svi_ipv6_ucast_pkts_out> ] [ <svi_ipv6_ucast_bytes_out> ] [ <svi_ipv6_mcast_pkts_in> ] [
<svi_ipv6_mcast_bytes_in> ] [ <svi_ipv6_mcast_pkts_out> ] [ <svi_ipv6_mcast_bytes_out> ] [
<svi_average_input_bits> ] [ <svi_average_input_packets> ] [ <svi_average_output_bits> ] [
<svi_average_output_packets> ] [ <svi_rate_in_mins> ] [ <svi_time_last_cleared> ] [ <svi_tx_load> ] [
<svi_rx_load> ] [ <svi_reliability> ] ]

```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
detailed	Show only non-zero counters
snmp	(Optional) Show SNMP MIB values
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>vdc_lvl_in_pkts</i>	(Optional) VDC level input packets
<i>vdc_lvl_in_bytes</i>	(Optional) VDC level input bytes
<i>vdc_lvl_in_ucast</i>	(Optional) VDC level input unicast packets
<i>vdc_lvl_in_mcast</i>	(Optional) VDC level input multicast packets
<i>vdc_lvl_in_bcast</i>	(Optional) VDC level input broadcast packets
<i>vdc_lvl_in_bps</i>	(Optional) VDC level input bytes per second
<i>vdc_lvl_in_pps</i>	(Optional) VDC level input packets per second
<i>vdc_lvl_in_avg_pkts</i>	(Optional) VDC level average input packets
<i>vdc_lvl_in_avg_bytes</i>	(Optional) VDC level average input bytes
<i>vdc_lvl_out_pkts</i>	(Optional) VDC level output packets
<i>vdc_lvl_out_bytes</i>	(Optional) VDC level output bytes
<i>vdc_lvl_out_ucast</i>	(Optional) VDC level output unicast packets

<i>vdc_lvl_out_mcast</i>	(Optional) VDC level output multicast packets
<i>vdc_lvl_out_bcast</i>	(Optional) VDC level output broadcast packets
<i>vdc_lvl_out_bps</i>	(Optional) VDC level output bytes per second
<i>vdc_lvl_out_pps</i>	(Optional) VDC level output packets per second
<i>vdc_lvl_out_avg_pkts</i>	(Optional) VDC level average output packets
<i>vdc_lvl_out_avg_bytes</i>	(Optional) VDC level average output bytes
<i>mgmt_in_pkts</i>	(Optional) Input packets
<i>mgmt_in_bytes</i>	(Optional) Input bytes
<i>mgmt_in_mcast</i>	(Optional) Input multicast frames
<i>mgmt_in_compressed</i>	(Optional) Input compressed
<i>mgmt_in_errors</i>	(Optional) Input errors
<i>mgmt_in_frame</i>	(Optional) Input frame errors
<i>mgmt_in_overrun</i>	(Optional) Input overrun
<i>mgmt_in_fifo</i>	(Optional) Input fifo
<i>mgmt_out_pkts</i>	(Optional) Output packets
<i>mgmt_out_bytes</i>	(Optional) Output bytes
<i>mgmt_out_underruns</i>	(Optional) Output overruns
<i>mgmt_out_errors</i>	(Optional) Output errors
<i>mgmt_out_collisions</i>	(Optional) Output collisions
<i>mgmt_out_fifo</i>	(Optional) Output fifo
<i>mgmt_out_carrier</i>	(Optional) Output carrier errors
<i>mgmt_align_err</i>	(Optional) Align error
<i>mgmt_fcs_err</i>	(Optional) FCS error
<i>mgmt_xmit_err</i>	(Optional) Transmit error
<i>mgmt_rcv_err</i>	(Optional) Receive error
<i>mgmt_undersize</i>	(Optional) Undersize
<i>mgmt_outdisc</i>	(Optional) Out discard
<i>mgmt_single_col</i>	(Optional) Single collision
<i>mgmt_multi_col</i>	(Optional) Multiple collision

<i>mgmt_late_col</i>	(Optional) Late collision
<i>mgmt_excess_col</i>	(Optional) Excess collision
<i>mgmt_carri_sen</i>	(Optional) Carrier sense
<i>mgmt_runts</i>	(Optional) Runts
<i>mgmt_giants</i>	(Optional) Giants
<i>mgmt_sqetest_err</i>	(Optional) SQETest error
<i>mgmt_deferred_tx</i>	(Optional) Deferred tx
<i>mgmt_inmactx_err</i>	(Optional) In MAC tx
<i>mgmt_inmacrx_err</i>	(Optional) In MAC rx
<i>mgmt_symbol_err</i>	(Optional) Symbol error
<i>loop_in_pkts</i>	(Optional) Input packets
<i>loop_in_bytes</i>	(Optional) Input bytes
<i>loop_in_mcast</i>	(Optional) Input multicast
<i>loop_in_compressed</i>	(Optional) Input compressed
<i>loop_in_errors</i>	(Optional) Input errors
<i>loop_in_frame</i>	(Optional) Input frame errors
<i>loop_in_overrun</i>	(Optional) Input overrun
<i>loop_in_fifo</i>	(Optional) Input fifo
<i>loop_out_pkts</i>	(Optional) Output packets
<i>loop_out_bytes</i>	(Optional) Output bytes
<i>loop_out_underruns</i>	(Optional) Output underruns
<i>loop_out_errors</i>	(Optional) Output errors
<i>loop_out_collisions</i>	(Optional) Output collisions
<i>loop_out_fifo</i>	(Optional) Output fifo
<i>loop_out_carriers</i>	(Optional) Output carrier errors
<i>eth_load_intervall</i>	(Optional) interval 1 timer value in sec
<i>eth_load_intervall_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec

<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate1_summary_bits</i>	(Optional) interval 1 input rate bit summary
<i>eth_inrate1_summary_pkts</i>	(Optional) interval 1 input rate pkt summary
<i>eth_outrate1_summary_bits</i>	(Optional) interval 1 output rate bit summary
<i>eth_outrate1_summary_pkts</i>	(Optional) interval 1 output rate pkt summary
<i>eth_load_interval2_rx</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_load_interval2_tx</i>	(Optional) interval 2 timer value in sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate2_summary_bits</i>	(Optional) interval 2 input rate bit summary
<i>eth_inrate2_summary_pkts</i>	(Optional) interval 2 input rate pkt summary
<i>eth_outrate2_summary_bits</i>	(Optional) interval 2 output rate bit summary
<i>eth_outrate2_summary_pkts</i>	(Optional) interval 2 output rate pkt summary
<i>eth_load_interval3_rx</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_load_interval3_tx</i>	(Optional) interval 3 timer value in sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_inrate3_summary_bits</i>	(Optional) interval 3 input rate bit summary
<i>eth_inrate3_summary_pkts</i>	(Optional) interval 3 input rate pkt summary
<i>eth_outrate3_summary_bits</i>	(Optional) interval 3 output rate bit summary
<i>eth_outrate3_summary_pkts</i>	(Optional) interval 3 output rate pkt summary

<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_ingiants</i>	(Optional) giants
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_inb64</i>	(Optional) input pkts between 0 and 64 bytes
<i>eth_inb65_127</i>	(Optional) input pkts between 65 and 127 bytes
<i>eth_inb128_255</i>	(Optional) input pkts between 128 and 255 bytes
<i>eth_inb256_511</i>	(Optional) input pkts between 256 and 511 bytes
<i>eth_inb512_1023</i>	(Optional) input pkts between 512 and 1023 bytes
<i>eth_inb1024_1518</i>	(Optional) input pkts between 1024 and 1518 bytes
<i>eth_inb1519_1548</i>	(Optional) input pkts between 1519 and 1548 bytes
<i>eth_intrunk</i>	(Optional) input trunk pkts
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outgiants</i>	(Optional) giants
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_outb64</i>	(Optional) output pkts between 0 and 64 bytes
<i>eth_outb65_127</i>	(Optional) output pkts between 65 and 127 bytes
<i>eth_outb128_255</i>	(Optional) output pkts between 128 and 255 bytes
<i>eth_outb256_511</i>	(Optional) output pkts between 256 and 511 bytes
<i>eth_outb512_1023</i>	(Optional) output pkts between 512 and 1023 bytes
<i>eth_outb1024_1518</i>	(Optional) output pkts between 1024 and 1518 bytes
<i>eth_outb1519_1548</i>	(Optional) output pkts between 1519 and 1548 bytes
<i>eth_outtrunk</i>	(Optional) output trunk pkts

<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_runts</i>	(Optional) runts
<i>eth_crc</i>	(Optional) CRC
<i>eth_ecc</i>	(Optional) ECC
<i>eth_overrun</i>	(Optional) overrun
<i>eth_underrun</i>	(Optional) underruns
<i>eth_ignored</i>	(Optional) ignored
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_coll</i>	(Optional) collisions
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_babbles</i>	(Optional) babbles
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_inerr</i>	(Optional) input errors
<i>eth_outerr</i>	(Optional) output errors
<i>eth_deferred</i>	(Optional) deferred
<i>eth_jabbers</i>	(Optional) jabbers
<i>eth_shortframe</i>	(Optional) short frames
<i>eth_single_coll</i>	(Optional) single collisions
<i>eth_multi_coll</i>	(Optional) multi collisions
<i>eth_excess_coll</i>	(Optional) excessive collisions
<i>eth_indiscard</i>	(Optional) discards
<i>eth_bad_encap</i>	(Optional) bad encapsulation
<i>eth_outcrc</i>	(Optional) Output CRC
<i>eth_symbol</i>	(Optional) symbol errors

<i>eth_out_drops</i>	(Optional) output drops
<i>eth_bpdu_outlost</i>	(Optional) BPDU output lost
<i>eth_cos0_outlost</i>	(Optional) output pkts
<i>eth_cos1_outlost</i>	(Optional) output pkts
<i>eth_cos2_outlost</i>	(Optional) output pkts
<i>eth_cos3_outlost</i>	(Optional) output pkts
<i>eth_cos4_outlost</i>	(Optional) output pkts
<i>eth_cos5_outlost</i>	(Optional) output pkts
<i>eth_cos6_outlost</i>	(Optional) output pkts
<i>eth_cos7_outlost</i>	(Optional) output pkts
<i>eth_inpause</i>	(Optional) pause input
<i>eth_outpause</i>	(Optional) PAUSE output
<i>eth_resets</i>	(Optional) interface resets
<i>eth_sqetest</i>	(Optional) SQE test
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) L3 out switched mcast pkts

<i>eth_l3out_mcastbytes</i>	(Optional) L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_ipmcast</i>	(Optional) IP multicast
<i>eth_inhw_switched</i>	(Optional) Input H/W Switched
<i>eth_insw_switched</i>	(Optional) Input S/W Switched
<i>eth_throtles</i>	(Optional) throttles
<i>eth_frame</i>	(Optional) frame
<i>eth_outhw_switched</i>	(Optional) Out H/W Switched
<i>eth_outsw_switched</i>	(Optional) Out S/W Switched
<i>eth_buffail</i>	(Optional) output buffer failures
<i>eth_bufswapped</i>	(Optional) output buffers swapped out
<i>eth_arpdrops</i>	(Optional) arp drops
<i>eth_out_ifdown_drops</i>	(Optional) Output if-down drops
<i>eth_fcoe_in_pkts</i>	(Optional) fcoe in pkts
<i>eth_fcoe_in_octets</i>	(Optional) fcoe in octets
<i>eth_fcoe_out_pkts</i>	(Optional) fcoe out pkts
<i>eth_fcoe_out_octets</i>	(Optional) fcoe out octets
<i>eth_nfcoe_in_pkts</i>	(Optional) nfcoe in pkts
<i>eth_nfcoe_in_octets</i>	(Optional) nfcoe in octets
<i>eth_nfcoe_out_pkts</i>	(Optional) nfcoe out pkts

<i>eth_nfcoc_out_octets</i>	(Optional) nfcoc out octets
<i>svi_time_last_cleared</i>	(Optional) Time last cleared
<i>svi_tx_load</i>	(Optional) Tx Load
<i>svi_rx_load</i>	(Optional) Rx Load
<i>svi_reliability</i>	(Optional) Reliability

Command Mode

- /exec

show interface counters detailed

```
show interface <ifmgmt_ctr_dtl> counters detailed [ __readonly__ TABLE_interface <interface> [
<vdc_lvl_in_pkts> ] [ <vdc_lvl_in_bytes> ] [ <vdc_lvl_in_ucast> ] [ <vdc_lvl_in_mcast> ] [
<vdc_lvl_in_bcast> ] [ <vdc_lvl_in_bps> ] [ <vdc_lvl_in_pps> ] [ <vdc_lvl_in_avg_pkts> ] [
<vdc_lvl_in_avg_bytes> ] [ <vdc_lvl_out_pkts> ] [ <vdc_lvl_out_bytes> ] [ <vdc_lvl_out_ucast> ] [
<vdc_lvl_out_mcast> ] [ <vdc_lvl_out_bcast> ] [ <vdc_lvl_out_bps> ] [ <vdc_lvl_out_pps> ] [
<vdc_lvl_out_avg_pkts> ] [ <vdc_lvl_out_avg_bytes> ] [ <mgmt_in_pkts> ] [ <mgmt_in_bytes> ] [
<mgmt_in_mcast> ] [ <mgmt_in_compressed> ] [ <mgmt_in_errors> ] [ <mgmt_in_frame> ] [
<mgmt_in_overnun> ] [ <mgmt_in_fifo> ] [ <mgmt_out_pkts> ] [ <mgmt_out_bytes> ] [
<mgmt_out_underruns> ] [ <mgmt_out_errors> ] [ <mgmt_out_collisions> ] [ <mgmt_out_fifo> ] [
<mgmt_out_carrier> ] [ <mgmt_align_err> ] [ <mgmt_fcs_err> ] [ <mgmt_xmit_err> ] [ <mgmt_rcv_err> ]
] [ <mgmt_undersize> ] [ <mgmt_outdisc> ] [ <mgmt_single_col> ] [ <mgmt_multi_col> ] [ <mgmt_late_col>
] [ <mgmt_excess_col> ] [ <mgmt_carri_sen> ] [ <mgmt_runs> ] [ <mgmt_giants> ] [ <mgmt_sqetest_err>
] [ <mgmt_deferred_tx> ] [ <mgmt_inmactx_err> ] [ <mgmt_inmacrx_err> ] [ <mgmt_symbol_err> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifmgmt_ctr_dtl</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>vdc_lvl_in_pkts</i>	(Optional) VDC level input packets
<i>vdc_lvl_in_bytes</i>	(Optional) VDC level input bytes
<i>vdc_lvl_in_ucast</i>	(Optional) VDC level input unicast packets
<i>vdc_lvl_in_mcast</i>	(Optional) VDC level input multicast packets
<i>vdc_lvl_in_bcast</i>	(Optional) VDC level input broadcast packets
<i>vdc_lvl_in_bps</i>	(Optional) VDC level input bytes per second
<i>vdc_lvl_in_pps</i>	(Optional) VDC level input packets per second
<i>vdc_lvl_in_avg_pkts</i>	(Optional) VDC level average input packets
<i>vdc_lvl_in_avg_bytes</i>	(Optional) VDC level average input bytes
<i>vdc_lvl_out_pkts</i>	(Optional) VDC level output packets

<i>vdc_lvl_out_bytes</i>	(Optional) VDC level output bytes
<i>vdc_lvl_out_ucast</i>	(Optional) VDC level output unicast packets
<i>vdc_lvl_out_mcast</i>	(Optional) VDC level output multicast packets
<i>vdc_lvl_out_bcast</i>	(Optional) VDC level output broadcast packets
<i>vdc_lvl_out_bps</i>	(Optional) VDC level output bytes per second
<i>vdc_lvl_out_pps</i>	(Optional) VDC level output packets per second
<i>vdc_lvl_out_avg_pkts</i>	(Optional) VDC level average output packets
<i>vdc_lvl_out_avg_bytes</i>	(Optional) VDC level average output bytes
<i>mgmt_in_pkts</i>	(Optional) Input packets
<i>mgmt_in_bytes</i>	(Optional) Input bytes
<i>mgmt_in_mcast</i>	(Optional) Input multicast frames
<i>mgmt_in_compressed</i>	(Optional) Input compressed
<i>mgmt_in_errors</i>	(Optional) Input errors
<i>mgmt_in_frame</i>	(Optional) Input frame errors
<i>mgmt_in_overrun</i>	(Optional) Input overrun
<i>mgmt_in_fifo</i>	(Optional) Input fifo
<i>mgmt_out_pkts</i>	(Optional) Output packets
<i>mgmt_out_bytes</i>	(Optional) Output bytes
<i>mgmt_out_underruns</i>	(Optional) Output overruns
<i>mgmt_out_errors</i>	(Optional) Output errors
<i>mgmt_out_collisions</i>	(Optional) Output collisions
<i>mgmt_out_fifo</i>	(Optional) Output fifo
<i>mgmt_out_carrier</i>	(Optional) Output carrier errors
<i>mgmt_align_err</i>	(Optional) Align error
<i>mgmt_fcs_err</i>	(Optional) FCS error
<i>mgmt_xmit_err</i>	(Optional) Transmit error
<i>mgmt_rcv_err</i>	(Optional) Receive error
<i>mgmt_undersize</i>	(Optional) Undersize
<i>mgmt_outdisc</i>	(Optional) Out discard

<i>mgmt_single_col</i>	(Optional) Single collision
<i>mgmt_multi_col</i>	(Optional) Multiple collision
<i>mgmt_late_col</i>	(Optional) Late collision
<i>mgmt_excess_col</i>	(Optional) Excess collision
<i>mgmt_carri_sen</i>	(Optional) Carrier sense
<i>mgmt_runts</i>	(Optional) Runts
<i>mgmt_giants</i>	(Optional) Giants
<i>mgmt_sgetest_err</i>	(Optional) SQETest error
<i>mgmt_deferred_tx</i>	(Optional) Deferred tx
<i>mgmt_inmactx_err</i>	(Optional) In MAC tx
<i>mgmt_inmacrx_err</i>	(Optional) In MAC rx
<i>mgmt_symbol_err</i>	(Optional) Symbol error

Command Mode

- /exec

show interface counters detailed

```
show interface <ifloop_ctr_dtl> counters detailed [ __readonly__ TABLE_interface <interface> [
<loop_in_pkts> ] [ <loop_in_bytes> ] [ <loop_in_mcast> ] [ <loop_in_compressed> ] [ <loop_in_errors> ]
[ <loop_in_frame> ] [ <loop_in_overrun> ] [ <loop_in_fifo> ] [ <loop_out_pkts> ] [ <loop_out_bytes> ] [
<loop_out_underruns> ] [ <loop_out_errors> ] [ <loop_out_collisions> ] [ <loop_out_fifo> ] [
<loop_out_carriers> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifloop_ctr_dtl</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>loop_in_pkts</i>	(Optional) Input packets
<i>loop_in_bytes</i>	(Optional) Input bytes
<i>loop_in_mcast</i>	(Optional) Input multicast
<i>loop_in_compressed</i>	(Optional) Input compressed
<i>loop_in_errors</i>	(Optional) Input errors
<i>loop_in_frame</i>	(Optional) Input frame errors
<i>loop_in_overrun</i>	(Optional) Input overrun
<i>loop_in_fifo</i>	(Optional) Input fifo
<i>loop_out_pkts</i>	(Optional) Output packets
<i>loop_out_bytes</i>	(Optional) Output bytes
<i>loop_out_underruns</i>	(Optional) Output underruns
<i>loop_out_errors</i>	(Optional) Output errors
<i>loop_out_collisions</i>	(Optional) Output collisions
<i>loop_out_fifo</i>	(Optional) Output fifo
<i>loop_out_carriers</i>	(Optional) Output carrier errors

Command Mode

- /exec

show interface counters detailed

```
show interface <ifeth_ctr_dtl> counters detailed [ snmp ] [ __readonly__ TABLE interface <interface> [
<eth_load_interval1> ] [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [
<eth_load_interval1_tx> ] [ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [
<eth_inrate1_summary_bits> ] [ <eth_inrate1_summary_pkts> ] [ <eth_outrate1_summary_bits> ] [
<eth_outrate1_summary_pkts> ] [ <eth_load_interval2_rx> ] [ <eth_inrate2_bits> ] [ <eth_inrate2_pkts> ] [
<eth_load_interval2_tx> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [ <eth_load_interval3> ] [
<eth_inrate2_summary_bits> ] [ <eth_inrate2_summary_pkts> ] [ <eth_outrate2_summary_bits> ] [
<eth_outrate2_summary_pkts> ] [ <eth_load_interval3_rx> ] [ <eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [
<eth_load_interval3_tx> ] [ <eth_outrate3_bits> ] [ <eth_outrate3_pkts> ] [ <eth_inrate3_summary_bits> ]
[ <eth_inrate3_summary_pkts> ] [ <eth_outrate3_summary_bits> ] [ <eth_outrate3_summary_pkts> ] [
<eth_inpkts> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_ingiants> ] [ <eth_inbytes> ] [
<eth_storm_supp> ] [ <eth_inb64> ] [ <eth_inb65_127> ] [ <eth_inb128_255> ] [ <eth_inb256_511> ] [
<eth_inb512_1023> ] [ <eth_inb1024_1518> ] [ <eth_inb1519_1548> ] [ <eth_intrunk> ] [ <eth_outpkts> ]
[ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast> ] [ <eth_outgiants> ] [ <eth_outbytes> ] [ <eth_outb64>
] [ <eth_outb65_127> ] [ <eth_outb128_255> ] [ <eth_outb256_511> ] [ <eth_outb512_1023> ] [
<eth_outb1024_1518> ] [ <eth_outb1519_1548> ] [ <eth_outtrunk> ] [ <eth_nobuf> ] [ <eth_runs> ] [
<eth_crc> ] [ <eth_ecc> ] [ <eth_overnun> ] [ <eth_underrun> ] [ <eth_ignored> ] [ <eth_bad_eth> ] [
<eth_bad_proto> ] [ <eth_in_ifdown_drops> ] [ <eth_coll> ] [ <eth_latecoll> ] [ <eth_lostcarrier> ] [
<eth_nocarrier> ] [ <eth_babbles> ] [ <eth_watchdog> ] [ <eth_dribble> ] [ <eth_inerr> ] [ <eth_outerr> ] [
<eth_deferred> ] [ <eth_jabbers> ] [ <eth_shortframe> ] [ <eth_single_coll> ] [ <eth_multi_coll> ] [
<eth_excess_coll> ] [ <eth_indiscard> ] [ <eth_bad_encap> ] [ <eth_outcrc> ] [ <eth_symbol> ] [
<eth_out_drops> ] [ <eth_bpdu_outlost> ] [ <eth_cos0_outlost> ] [ <eth_cos1_outlost> ] [ <eth_cos2_outlost>
] [ <eth_cos3_outlost> ] [ <eth_cos4_outlost> ] [ <eth_cos5_outlost> ] [ <eth_cos6_outlost> ] [
<eth_cos7_outlost> ] [ <eth_inpause> ] [ <eth_outpause> ] [ <eth_resets> ] [ <eth_sqetest> ] [
<eth_l2_ucastpkts> ] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [ <eth_l2_mcastbytes> ] [
<eth_l2_bcastpkts> ] [ <eth_l2_bcastbytes> ] [ <eth_l3in_routed_pkts> ] [ <eth_l3in_routed_bytes> ] [
<eth_l3out_routed_pkts> ] [ <eth_l3out_routed_bytes> ] [ <eth_l3in_ucastpkts> ] [ <eth_l3in_ucastbytes> ]
[ <eth_l3in_mcastpkts> ] [ <eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [ <eth_l3in_bcastbytes> ] [
<eth_l3out_ucastpkts> ] [ <eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_mcastbytes> ] [
<eth_l3out_bcastpkts> ] [ <eth_l3out_bcastbytes> ] [ <eth_l3avg1_inbytes> ] [ <eth_l3avg1_inpkts> ] [
<eth_l3avg1_outbytes> ] [ <eth_l3avg1_outpkts> ] [ <eth_ipmcast> ] [ <eth_inhw_switched> ] [
<eth_insw_switched> ] [ <eth_throtles> ] [ <eth_frame> ] [ <eth_outhw_switched> ] [ <eth_outsw_switched>
] [ <eth_buffail> ] [ <eth_bufswapped> ] [ <eth_arpdrops> ] [ <eth_out_ifdown_drops> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_dtl</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
snmp	(Optional) Show SNMP MIB values
__readonly__	(Optional) Read Only

<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_load_interval1</i>	(Optional) interval 1 timer value in sec
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec
<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate1_summary_bits</i>	(Optional) interval 1 input rate bit summary
<i>eth_inrate1_summary_pkts</i>	(Optional) interval 1 input rate pkt summary
<i>eth_outrate1_summary_bits</i>	(Optional) interval 1 output rate bit summary
<i>eth_outrate1_summary_pkts</i>	(Optional) interval 1 output rate pkt summary
<i>eth_load_interval2_rx</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_load_interval2_tx</i>	(Optional) interval 2 timer value in sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate2_summary_bits</i>	(Optional) interval 2 input rate bit summary
<i>eth_inrate2_summary_pkts</i>	(Optional) interval 2 input rate pkt summary
<i>eth_outrate2_summary_bits</i>	(Optional) interval 2 output rate bit summary
<i>eth_outrate2_summary_pkts</i>	(Optional) interval 2 output rate pkt summary
<i>eth_load_interval3_rx</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_load_interval3_tx</i>	(Optional) interval 3 timer value in sec

<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_inrate3_summary_bits</i>	(Optional) interval 3 input rate bit summary
<i>eth_inrate3_summary_pkts</i>	(Optional) interval 3 input rate pkt summary
<i>eth_outrate3_summary_bits</i>	(Optional) interval 3 output rate bit summary
<i>eth_outrate3_summary_pkts</i>	(Optional) interval 3 output rate pkt summary
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_ingiants</i>	(Optional) giants
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_inb64</i>	(Optional) input pkts between 0 and 64 bytes
<i>eth_inb65_127</i>	(Optional) input pkts between 65 and 127 bytes
<i>eth_inb128_255</i>	(Optional) input pkts between 128 and 255 bytes
<i>eth_inb256_511</i>	(Optional) input pkts between 256 and 511 bytes
<i>eth_inb512_1023</i>	(Optional) input pkts between 512 and 1023 bytes
<i>eth_inb1024_1518</i>	(Optional) input pkts between 1024 and 1518 bytes
<i>eth_inb1519_1548</i>	(Optional) input pkts between 1519 and 1548 bytes
<i>eth_intrunk</i>	(Optional) input trunk pkts
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outgiants</i>	(Optional) giants
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_outb64</i>	(Optional) output pkts between 0 and 64 bytes
<i>eth_outb65_127</i>	(Optional) output pkts between 65 and 127 bytes

<i>eth_outb128_255</i>	(Optional) output pkts between 128 and 255 bytes
<i>eth_outb256_511</i>	(Optional) output pkts between 256 and 511 bytes
<i>eth_outb512_1023</i>	(Optional) output pkts between 512 and 1023 bytes
<i>eth_outb1024_1518</i>	(Optional) output pkts between 1024 and 1518 bytes
<i>eth_outb1519_1548</i>	(Optional) output pkts between 1519 and 1548 bytes
<i>eth_outtrunk</i>	(Optional) output trunk pkts
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_runts</i>	(Optional) runts
<i>eth_crc</i>	(Optional) CRC
<i>eth_ecc</i>	(Optional) ECC
<i>eth_overnrun</i>	(Optional) overrun
<i>eth_underrun</i>	(Optional) underruns
<i>eth_ignored</i>	(Optional) ignored
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_coll</i>	(Optional) collisions
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_babbles</i>	(Optional) babbles
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_inerr</i>	(Optional) input errors
<i>eth_outerr</i>	(Optional) output errors
<i>eth_deferred</i>	(Optional) deferred
<i>eth_jabbers</i>	(Optional) jabbers
<i>eth_shortframe</i>	(Optional) short frames
<i>eth_single_coll</i>	(Optional) single collisions

<i>eth_multi_coll</i>	(Optional) multi collisions
<i>eth_excess_coll</i>	(Optional) excessive collisions
<i>eth_indiscard</i>	(Optional) discards
<i>eth_bad_encap</i>	(Optional) bad encapsulation
<i>eth_outcrc</i>	(Optional) Output CRC
<i>eth_symbol</i>	(Optional) symbol errors
<i>eth_out_drops</i>	(Optional) output drops
<i>eth_bpdu_outlost</i>	(Optional) BPDU output lost
<i>eth_cos0_outlost</i>	(Optional) output pkts
<i>eth_cos1_outlost</i>	(Optional) output pkts
<i>eth_cos2_outlost</i>	(Optional) output pkts
<i>eth_cos3_outlost</i>	(Optional) output pkts
<i>eth_cos4_outlost</i>	(Optional) output pkts
<i>eth_cos5_outlost</i>	(Optional) output pkts
<i>eth_cos6_outlost</i>	(Optional) output pkts
<i>eth_cos7_outlost</i>	(Optional) output pkts
<i>eth_inpause</i>	(Optional) pause input
<i>eth_outpause</i>	(Optional) PAUSE output
<i>eth_resets</i>	(Optional) interface resets
<i>eth_sgetest</i>	(Optional) SQE test
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) L3 in switched mcast pkts

<i>eth_l3in_mcastbytes</i>	(Optional) L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) L3 out switched mcast pkts
<i>eth_l3out_mcastbytes</i>	(Optional) L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_ipmcast</i>	(Optional) IP multicast
<i>eth_inhw_switched</i>	(Optional) Input H/W Switched
<i>eth_insw_switched</i>	(Optional) Input S/W Switched
<i>eth_throtles</i>	(Optional) throttles
<i>eth_frame</i>	(Optional) frame
<i>eth_outhw_switched</i>	(Optional) Out H/W Switched
<i>eth_outsw_switched</i>	(Optional) Out S/W Switched
<i>eth_buffail</i>	(Optional) output buffer failures
<i>eth_bufswapped</i>	(Optional) output buffers swapped out
<i>eth_arpdrops</i>	(Optional) arp drops
<i>eth_out_ifdown_drops</i>	(Optional) Output if-down drops

Command Mode

- /exec

show interface counters detailed all

show interface <ifid_ctr_dtl_all> counters detailed all [snmp]

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_ctr_dtl_all</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
all	Show every interface counter
snmp	(Optional) Show SNMP MIB values

Command Mode

- /exec

show interface counters detailed all

```
show interface <ifmgmt_ctr_dtl_all> counters detailed all [ __readonly__ TABLE_interface <interface> [
<vdc_lvl_in_pkts> ][ <vdc_lvl_in_bytes> ][ <vdc_lvl_in_ucast> ][ <vdc_lvl_in_mcast> ][
<vdc_lvl_in_bcast> ][ <vdc_lvl_in_bps> ][ <vdc_lvl_in_pps> ][ <vdc_lvl_in_avg_pkts> ][
<vdc_lvl_in_avg_bytes> ][ <vdc_lvl_out_pkts> ][ <vdc_lvl_out_bytes> ][ <vdc_lvl_out_ucast> ][
<vdc_lvl_out_mcast> ][ <vdc_lvl_out_bcast> ][ <vdc_lvl_out_bps> ][ <vdc_lvl_out_pps> ][
<vdc_lvl_out_avg_pkts> ][ <vdc_lvl_out_avg_bytes> ][ <mgmt_in_pkts> ][ <mgmt_in_bytes> ][
<mgmt_in_mcast> ][ <mgmt_out_pkts> ][ <mgmt_out_bytes> ][ <mgmt_in_errors> ][ <mgmt_out_errors>
][ <mgmt_in_fifo> ][ <mgmt_out_fifo> ][ <mgmt_in_compressed> ][ <mgmt_in_frame> ][
<mgmt_in_overrun> ][ <mgmt_out_underruns> ][ <mgmt_out_collisions> ][ <mgmt_out_carrier> ][
<mgmt_align_err> ][ <mgmt_fcs_err> ][ <mgmt_xmit_err> ][ <mgmt_rcv_err> ][ <mgmt_undersize> ][
<mgmt_outdisc> ][ <mgmt_single_col> ][ <mgmt_multi_col> ][ <mgmt_late_col> ][ <mgmt_excess_col>
][ <mgmt_carri_sen> ][ <mgmt_runts> ][ <mgmt_giants> ][ <mgmt_sqetest_err> ][ <mgmt_deferred_tx>
][ <mgmt_inmactx_err> ][ <mgmt_inmacrx_err> ][ <mgmt_symbol_err> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifmgmt_ctr_dtl_all</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
all	Show every interface counter
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>vdc_lvl_in_pkts</i>	(Optional) VDC level input packets
<i>vdc_lvl_in_bytes</i>	(Optional) VDC level input bytes
<i>vdc_lvl_in_ucast</i>	(Optional) VDC level input unicast packets
<i>vdc_lvl_in_mcast</i>	(Optional) VDC level input multicast packets
<i>vdc_lvl_in_bcast</i>	(Optional) VDC level input broadcast packets
<i>vdc_lvl_in_bps</i>	(Optional) VDC level input bytes per second
<i>vdc_lvl_in_pps</i>	(Optional) VDC level input packets per second
<i>vdc_lvl_in_avg_pkts</i>	(Optional) VDC level average input packets
<i>vdc_lvl_in_avg_bytes</i>	(Optional) VDC level average input bytes

<i>vdc_lvl_out_pkts</i>	(Optional) VDC level output packets
<i>vdc_lvl_out_bytes</i>	(Optional) VDC level output bytes
<i>vdc_lvl_out_ucast</i>	(Optional) VDC level output unicast packets
<i>vdc_lvl_out_mcast</i>	(Optional) VDC level output multicast packets
<i>vdc_lvl_out_bcast</i>	(Optional) VDC level output broadcast packets
<i>vdc_lvl_out_bps</i>	(Optional) VDC level output bytes per second
<i>vdc_lvl_out_pps</i>	(Optional) VDC level output packets per second
<i>vdc_lvl_out_avg_pkts</i>	(Optional) VDC level average output packets
<i>vdc_lvl_out_avg_bytes</i>	(Optional) VDC level average output bytes
<i>mgmt_in_pkts</i>	(Optional) Input packets
<i>mgmt_in_bytes</i>	(Optional) Input bytes
<i>mgmt_in_mcast</i>	(Optional) Input multicast frames
<i>mgmt_out_pkts</i>	(Optional) Output packets
<i>mgmt_out_bytes</i>	(Optional) Output bytes
<i>mgmt_in_errors</i>	(Optional) Input errors
<i>mgmt_out_errors</i>	(Optional) Output errors
<i>mgmt_in_fifo</i>	(Optional) Input fifo
<i>mgmt_out_fifo</i>	(Optional) Output fifo
<i>mgmt_in_compressed</i>	(Optional) Input compressed
<i>mgmt_in_frame</i>	(Optional) Input frame errors
<i>mgmt_in_overnrun</i>	(Optional) Input overrun
<i>mgmt_out_underruns</i>	(Optional) Output overruns
<i>mgmt_out_collisions</i>	(Optional) Output collisions
<i>mgmt_out_carrier</i>	(Optional) Output carrier errors
<i>mgmt_align_err</i>	(Optional) Align error
<i>mgmt_fcs_err</i>	(Optional) FCS error
<i>mgmt_xmit_err</i>	(Optional) Transmit error
<i>mgmt_rcv_err</i>	(Optional) Receive error
<i>mgmt_undersize</i>	(Optional) Undersize

<i>mgmt_outdisc</i>	(Optional) Out discard
<i>mgmt_single_col</i>	(Optional) Single collision
<i>mgmt_multi_col</i>	(Optional) Multiple collision
<i>mgmt_late_col</i>	(Optional) Late collision
<i>mgmt_excess_col</i>	(Optional) Excess collision
<i>mgmt_carri_sen</i>	(Optional) Carrier sense
<i>mgmt_runs</i>	(Optional) Runts
<i>mgmt_giants</i>	(Optional) Giants
<i>mgmt_sqetest_err</i>	(Optional) SQETest error
<i>mgmt_deferred_tx</i>	(Optional) Deferred tx
<i>mgmt_inmactx_err</i>	(Optional) In MAC tx
<i>mgmt_inmacrx_err</i>	(Optional) In MAC rx
<i>mgmt_symbol_err</i>	(Optional) Symbol error

Command Mode

- /exec

show interface counters detailed all

```
show interface <ifloop_ctr_dtl_all> counters detailed all [ __readonly__ TABLE_interface <interface> [
<rx_total_pkts> ] [ <tx_total_pkts> ] [ <rx_mcast_pkts> ] [ <rx_octets> ] [ <tx_octets> ] [ <loop_in_pkts> ]
[ <loop_in_bytes> ] [ <loop_in_mcast> ] [ <loop_in_compressed> ] [ <loop_in_errors> ] [ <loop_in_frame> ]
[ <loop_in_overrun> ] [ <loop_in_fifo> ] [ <loop_out_pkts> ] [ <loop_out_bytes> ] [ <loop_out_underruns> ]
[ <loop_out_errors> ] [ <loop_out_collisions> ] [ <loop_out_fifo> ] [ <loop_out_carriers> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifloop_ctr_dtl_all</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
all	Show every interface counter
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>rx_total_pkts</i>	(Optional) total input packets
<i>tx_total_pkts</i>	(Optional) total output packets
<i>rx_mcast_pkts</i>	(Optional) input multicasts
<i>rx_octets</i>	(Optional) input bytes
<i>tx_octets</i>	(Optional) output bytes
<i>loop_in_pkts</i>	(Optional) Input packets
<i>loop_in_bytes</i>	(Optional) Input bytes
<i>loop_in_mcast</i>	(Optional) Input multicast
<i>loop_in_compressed</i>	(Optional) Input compressed
<i>loop_in_errors</i>	(Optional) Input errors
<i>loop_in_frame</i>	(Optional) Input frame errors
<i>loop_in_overrun</i>	(Optional) Input overrun
<i>loop_in_fifo</i>	(Optional) Input fifo
<i>loop_out_pkts</i>	(Optional) Output packets

<i>loop_out_bytes</i>	(Optional) Output bytes
<i>loop_out_underruns</i>	(Optional) Output underruns
<i>loop_out_errors</i>	(Optional) Output errors
<i>loop_out_collisions</i>	(Optional) Output collisions
<i>loop_out_fifo</i>	(Optional) Output fifo
<i>loop_out_carriers</i>	(Optional) Output carrier errors

Command Mode

- /exec

show interface counters detailed all

```
show interface <ifrange> counters detailed all [ snmp ] [ __readonly__ TABLE interface <interface> [
<svi_routed_pkts_in> ] [ <svi_routed_bytes_in> ] [ <svi_routed_pkts_out> ] [ <svi_routed_bytes_out> ] [
<svi_ucast_pkts_in> ] [ <svi_ucast_bytes_in> ] [ <svi_mcast_pkts_in> ] [ <svi_mcast_bytes_in> ] [
<svi_ucast_pkts_out> ] [ <svi_ucast_bytes_out> ] [ <svi_mcast_pkts_out> ] [ <svi_mcast_bytes_out> ] [
<svi_ipv4_ucast_pkts_in> ] [ <svi_ipv4_ucast_bytes_in> ] [ <svi_ipv4_ucast_pkts_out> ] [
<svi_ipv4_ucast_bytes_out> ] [ <svi_ipv4_mcast_pkts_in> ] [ <svi_ipv4_mcast_bytes_in> ] [
<svi_ipv4_mcast_pkts_out> ] [ <svi_ipv4_mcast_bytes_out> ] [ <svi_ipv6_ucast_pkts_in> ] [
<svi_ipv6_ucast_bytes_in> ] [ <svi_ipv6_ucast_pkts_out> ] [ <svi_ipv6_ucast_bytes_out> ] [
<svi_ipv6_mcast_pkts_in> ] [ <svi_ipv6_mcast_bytes_in> ] [ <svi_ipv6_mcast_pkts_out> ] [
<svi_ipv6_mcast_bytes_out> ] [ <svi_average_input_bits> ] [ <svi_average_input_packets> ] [
<svi_average_output_bits> ] [ <svi_average_output_packets> ] [ <svi_rate_in_mins> ] [
<svi_time_last_cleared> ] [ <svi_tx_load> ] [ <svi_rx_load> ] [ <svi_reliability> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter interface type and number in module/slot format
counters	Show interface counters
detailed	Show only non-zero counters
all	everything
snmp	(Optional) Show SNMP MIB values
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>svi_time_last_cleared</i>	(Optional) Time last cleared
<i>svi_tx_load</i>	(Optional) Tx Load
<i>svi_rx_load</i>	(Optional) Rx Load
<i>svi_reliability</i>	(Optional) Reliability

Command Mode

- /exec

show interface counters detailed all

```
show interface <ifeth_ctr_dtl_all> counters detailed all [ snmp ] [ __readonly__ TABLE interface <interface>
[ <rx_total_pkts> ] [ <tx_total_pkts> ] [ <rx_ucast_pkts> ] [ <rx_mcast_pkts> ] [ <rx_bcast_pkts> ] [
<rx_octets> ] [ <tx_ucast_pkts> ] [ <tx_mcast_pkts> ] [ <tx_bcast_pkts> ] [ <tx_octets> ] [
<rxtx_pkts_64octets> ] [ <rxtx_pkts_65_127octets> ] [ <rxtx_pkts_128_255octets> ] [
<rxtx_pkts_256_511octets> ] [ <rxtx_pkts_512_1023octets> ] [ <rxtx_pkts_1024_1518octets> ] [
<rxtx_pkts_1519_1548octets> ] [ <rx_trunk_frames> ] [ <tx_trunk_frames> ] [ <rx_drop_events> ] [
<rxtx_giants> ] [ <eth_load_interval1_rx> ] [ <eth_inrate1_bits> ] [ <eth_inrate1_pkts> ] [
<eth_load_interval1_tx> ] [ <eth_outrate1_bits> ] [ <eth_outrate1_pkts> ] [ <eth_load_interval2> ] [
<eth_inrate2_bits> ] [ <eth_inrate2_pkts> ] [ <eth_outrate2_bits> ] [ <eth_outrate2_pkts> ] [
<eth_load_interval3> ] [ <eth_inrate3_bits> ] [ <eth_inrate3_pkts> ] [ <eth_outrate3_bits> ] [
<eth_outrate3_pkts> ] [ <eth_l2_ucastpkts> ] [ <eth_l2_ucastbytes> ] [ <eth_l2_mcastpkts> ] [
<eth_l2_mcastbytes> ] [ <eth_l2_bcastpkts> ] [ <eth_l2_bcastbytes> ] [ <eth_l3in_ucastpkts> ] [
<eth_l3in_ucastbytes> ] [ <eth_l3in_mcastpkts> ] [ <eth_l3in_mcastbytes> ] [ <eth_l3in_bcastpkts> ] [
<eth_l3in_bcastbytes> ] [ <eth_l3out_ucastpkts> ] [ <eth_l3out_ucastbytes> ] [ <eth_l3out_mcastpkts> ] [
<eth_l3out_mcastbytes> ] [ <eth_l3out_bcastpkts> ] [ <eth_l3out_bcastbytes> ] [ <eth_l3in_routed_pkts> ]
[ <eth_l3in_routed_bytes> ] [ <eth_l3out_routed_pkts> ] [ <eth_l3out_routed_bytes> ] [ <eth_l3avg1_inbytes> ]
[ <eth_l3avg1_inpkts> ] [ <eth_l3avg1_outbytes> ] [ <eth_l3avg1_outpkts> ] [ <eth_l3avg2_inbytes> ] [
<eth_l3avg2_inpkts> ] [ <eth_l3avg2_outbytes> ] [ <eth_l3avg2_outpkts> ] [ <eth_l3avg3_inbytes> ] [
<eth_l3avg3_inpkts> ] [ <eth_l3avg3_outbytes> ] [ <eth_l3avg3_outpkts> ] [ <eth_inpkts> ] [ <eth_inbytes> ]
[ <eth_nobuf> ] [ <eth_inbcast> ] [ <eth_inmcast> ] [ <eth_inucast> ] [ <eth_ingiants> ] [ <eth_ipmcast> ]
[ <eth_inhw_switched> ] [ <eth_insw_switched> ] [ <eth_runs> ] [ <eth_storm_supp> ] [ <eth_throtles> ] [
<eth_inerr> ] [ <eth_crc> ] [ <eth_ecc> ] [ <eth_frame> ] [ <eth_outrun> ] [ <eth_ignored> ] [ <eth_watchdog> ]
[ <eth_outbcast> ] [ <eth_outmcast> ] [ <eth_outucast> ] [ <eth_outgiants> ] [ <eth_inpause> ] [ <eth_dribble> ]
[ <eth_in_ifdown_drops> ] [ <eth_bad_eth> ] [ <eth_bad_proto> ] [ <eth_outpkts> ] [ <eth_outbytes> ] [
<eth_underrun> ] [ <eth_outhw_switched> ] [ <eth_outsw_switched> ] [ <eth_outerr> ] [ <eth_coll> ] [
<eth_resets> ] [ <eth_babbles> ] [ <eth_latecoll> ] [ <eth_deferred> ] [ <eth_lostcarrier> ] [ <eth_nocarrier> ]
[ <eth_outpause> ] [ <eth_buffail> ] [ <eth_bufswapped> ] [ <eth_arpdrops> ] [ <eth_out_ifdown_drops> ]
[ <eth_single_coll> ] [ <eth_multi_coll> ] [ <eth_excess_coll> ] [ <eth_jabbers> ] [ <eth_shortframe> ] [
<eth_indiscard> ] [ <eth_bad_encap> ] [ <eth_outcrc> ] [ <eth_symbol> ] [ <eth_out_drops> ] [ <eth_ssetest> ]
[ <eth_inb64> ] [ <eth_inb65_127> ] [ <eth_inb128_255> ] [ <eth_inb256_511> ] [ <eth_inb512_1023> ]
[ <eth_inb1024_1518> ] [ <eth_inb1519_1548> ] [ <eth_intrunk> ] [ <eth_outb64> ] [ <eth_outb65_127> ]
[ <eth_outb128_255> ] [ <eth_outb256_511> ] [ <eth_outb512_1023> ] [ <eth_outb1024_1518> ] [
<eth_outb1519_1548> ] [ <eth_outtrunk> ] [ <eth_bpdu_outlost> ] [ <eth_cos0_outlost> ] [ <eth_cos1_outlost> ]
[ <eth_cos2_outlost> ] [ <eth_cos3_outlost> ] [ <eth_cos4_outlost> ] [ <eth_cos5_outlost> ] [
<eth_cos6_outlost> ] [ <eth_cos7_outlost> ] [ <eth_fcove_in_pkts> ] [ <eth_fcove_in_octets> ] [
<eth_fcove_out_pkts> ] [ <eth_fcove_out_octets> ] [ <eth_nfcove_in_pkts> ] [ <eth_nfcove_in_octets> ] [
<eth_nfcove_out_pkts> ] [ <eth_nfcove_out_octets> ] [ <eth_eee_atx_lpi_msec> ] [ <eth_eee_arcv_lpi_msec> ]
[ <eth_eee_atx_lpi_transitions> ] [ <eth_eee_arcv_lpi_transitions> ] [ <eth_phy_ber_count> ] [
<eth_phy_errblks_count> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_dtl_all</i>	Enter interface type and number in module/slot format
counters	Show interface counters

<i>detailed</i>	Show only non-zero counters
<i>all</i>	everything
<i>snmp</i>	(Optional) Show SNMP MIB values
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<i>TABLE_interface</i>	(Optional) show interface
<i>rx_total_pkts</i>	(Optional) total input packets
<i>tx_total_pkts</i>	(Optional) total output packets
<i>rx_ucast_pkts</i>	(Optional) input unicasts
<i>rx_mcast_pkts</i>	(Optional) input multicasts
<i>rx_bcast_pkts</i>	(Optional) input broadcasts
<i>rx_octets</i>	(Optional) input bytes
<i>tx_ucast_pkts</i>	(Optional) output unicasts
<i>tx_mcast_pkts</i>	(Optional) output multicasts
<i>tx_bcast_pkts</i>	(Optional) output broadcasts
<i>tx_octets</i>	(Optional) output bytes
<i>rxtx_pkts_64octets</i>	(Optional) all pkts between 0 and 64 bytes
<i>rxtx_pkts_65_127octets</i>	(Optional) all pkts between 65 and 127 bytes
<i>rxtx_pkts_128_255octets</i>	(Optional) all pkts between 128 and 255 bytes
<i>rxtx_pkts_256_511octets</i>	(Optional) all pkts between 256 and 511 bytes
<i>rxtx_pkts_512_1023octets</i>	(Optional) all pkts between 512 and 1023 bytes
<i>rxtx_pkts_1024_1518octets</i>	(Optional) all pkts between 1024 and 1518 bytes
<i>rxtx_pkts_1519_1548octets</i>	(Optional) all pkts between 1519 and 1548 bytes
<i>rx_trunk_frames</i>	(Optional) input trunk pkts
<i>tx_trunk_frames</i>	(Optional) output trunk pkts
<i>rx_drop_events</i>	(Optional) dropped pkts
<i>rxtx_giants</i>	(Optional) giants
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec

<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec
<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) IPv4 L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) IPv4 L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) IPv4 L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) IPv4 L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) IPv4 L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) IPv4 L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) IPv4 L3 out switched mcast pkts

<i>eth_l3out_mcastbytes</i>	(Optional) IPv4 L3 out switched mcast bytes
<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_l3avg2_inbytes</i>	(Optional) Load interval 2 L3 average in switched bytes
<i>eth_l3avg2_inpkts</i>	(Optional) Load interval 2 L3 average in switched pkts
<i>eth_l3avg2_outbytes</i>	(Optional) Load interval 2 L3 average out switched bytes
<i>eth_l3avg2_outpkts</i>	(Optional) Load interval 2 L3 average out switched pkts
<i>eth_l3avg3_inbytes</i>	(Optional) Load interval 3 L3 average in switched bytes
<i>eth_l3avg3_inpkts</i>	(Optional) Load interval 3 L3 average in switched pkts
<i>eth_l3avg3_outbytes</i>	(Optional) Load interval 3 L3 average out switched bytes
<i>eth_l3avg3_outpkts</i>	(Optional) Load interval 3 L3 average out switched pkts
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_ingiants</i>	(Optional) giants
<i>eth_ipmcast</i>	(Optional) IP multicast
<i>eth_inhw_switched</i>	(Optional) Input H/W Switched
<i>eth_insw_switched</i>	(Optional) Input S/W Switched

<i>eth_runts</i>	(Optional) runts
<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_throtles</i>	(Optional) throttles
<i>eth_inerr</i>	(Optional) input errors
<i>eth_crc</i>	(Optional) CRC
<i>eth_ecc</i>	(Optional) ECC
<i>eth_frame</i>	(Optional) frame
<i>eth_overrun</i>	(Optional) overrun
<i>eth_ignored</i>	(Optional) ignored
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outgiants</i>	(Optional) giants
<i>eth_inpause</i>	(Optional) pause input
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_underrun</i>	(Optional) underruns
<i>eth_outhw_switched</i>	(Optional) Out H/W Switched
<i>eth_outsw_switched</i>	(Optional) Out S/W Switched
<i>eth_outerr</i>	(Optional) output errors
<i>eth_coll</i>	(Optional) collisions
<i>eth_resets</i>	(Optional) interface resets
<i>eth_babbles</i>	(Optional) babbles
<i>eth_latecoll</i>	(Optional) late collision

<i>eth_deferred</i>	(Optional) deferred
<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_outpause</i>	(Optional) PAUSE output
<i>eth_buffail</i>	(Optional) output buffer failures
<i>eth_bufswapped</i>	(Optional) output buffers swapped out
<i>eth_arpdrops</i>	(Optional) arp drops
<i>eth_out_ifdown_drops</i>	(Optional) Output if-down drops
<i>eth_single_coll</i>	(Optional) single collisions
<i>eth_multi_coll</i>	(Optional) multi collisions
<i>eth_excess_coll</i>	(Optional) excessive collisions
<i>eth_jabbers</i>	(Optional) jabbers
<i>eth_shortframe</i>	(Optional) short frames
<i>eth_indiscard</i>	(Optional) discards
<i>eth_bad_encap</i>	(Optional) bad encapsulation
<i>eth_outcrc</i>	(Optional) Output CRC
<i>eth_symbol</i>	(Optional) symbol errors
<i>eth_out_drops</i>	(Optional) output drops
<i>eth_sqetest</i>	(Optional) SQE test
<i>eth_inb64</i>	(Optional) input pkts between 0 and 64 bytes
<i>eth_inb65_127</i>	(Optional) input pkts between 65 and 127 bytes
<i>eth_inb128_255</i>	(Optional) input pkts between 128 and 255 bytes
<i>eth_inb256_511</i>	(Optional) input pkts between 256 and 511 bytes
<i>eth_inb512_1023</i>	(Optional) input pkts between 512 and 1023 bytes
<i>eth_inb1024_1518</i>	(Optional) input pkts between 1024 and 1518 bytes
<i>eth_inb1519_1548</i>	(Optional) input pkts between 1519 and 1548 bytes
<i>eth_intrunk</i>	(Optional) input trunk pkts
<i>eth_outb64</i>	(Optional) output pkts between 0 and 64 bytes
<i>eth_outb65_127</i>	(Optional) output pkts between 65 and 127 bytes

<i>eth_outb128_255</i>	(Optional) output pkts between 128 and 255 bytes
<i>eth_outb256_511</i>	(Optional) output pkts between 256 and 511 bytes
<i>eth_outb512_1023</i>	(Optional) output pkts between 512 and 1023 bytes
<i>eth_outb1024_1518</i>	(Optional) output pkts between 1024 and 1518 bytes
<i>eth_outb1519_1548</i>	(Optional) output pkts between 1519 and 1548 bytes
<i>eth_outtrunk</i>	(Optional) output trunk pkts
<i>eth_bpdu_outlost</i>	(Optional) BPDU output lost
<i>eth_cos0_outlost</i>	(Optional) output pkts
<i>eth_cos1_outlost</i>	(Optional) output pkts
<i>eth_cos2_outlost</i>	(Optional) output pkts
<i>eth_cos3_outlost</i>	(Optional) output pkts
<i>eth_cos4_outlost</i>	(Optional) output pkts
<i>eth_cos5_outlost</i>	(Optional) output pkts
<i>eth_cos6_outlost</i>	(Optional) output pkts
<i>eth_cos7_outlost</i>	(Optional) output pkts
<i>eth_fcoe_in_pkts</i>	(Optional) fcoe in pkts
<i>eth_fcoe_in_octets</i>	(Optional) fcoe in octets
<i>eth_fcoe_out_pkts</i>	(Optional) fcoe out pkts
<i>eth_fcoe_out_octets</i>	(Optional) fcoe out octets
<i>eth_nfcoe_in_pkts</i>	(Optional) nfcoe in pkts
<i>eth_nfcoe_in_octets</i>	(Optional) nfcoe in octets
<i>eth_nfcoe_out_pkts</i>	(Optional) nfcoe out pkts
<i>eth_nfcoe_out_octets</i>	(Optional) nfcoe out octets
<i>eth_eee_atx_lpi_msec</i>	(Optional) Tx Lpi usec
<i>eth_eee_arcv_lpi_msec</i>	(Optional) Rx Lpi usec
<i>eth_eee_atx_lpi_transitions</i>	(Optional) Tx Lpi requests
<i>eth_eee_arcv_lpi_transitions</i>	(Optional) Rx Lpi indications
<i>eth_phy_ber_count</i>	(Optional) Bit error rate counter
<i>eth_phy_errblks_count</i>	(Optional) Errorred blocks counter

Command Mode

- /exec

show interface counters detailed cached

```
show interface <ifeth_ctr_dtl_all> counters detailed cached [ __readonly__ TABLE_interface <interface> [
<rx_total_pkts> ][ <tx_total_pkts> ][ <rx_ucast_pkts> ][ <rx_mcast_pkts> ][ <rx_bcast_pkts> ][ <rx_octets> ]
][ <tx_ucast_pkts> ][ <tx_mcast_pkts> ][ <tx_bcast_pkts> ][ <tx_octets> ][ <rxtx_pkts_64octets> ][
<rxtx_pkts_65_127octets> ][ <rxtx_pkts_128_255octets> ][ <rxtx_pkts_256_511octets> ][
<rxtx_pkts_512_1023octets> ][ <rxtx_pkts_1024_1518octets> ][ <rxtx_pkts_1519_1548octets> ][
<rx_trunk_frames> ][ <tx_trunk_frames> ][ <rx_drop_events> ][ <rxtx_giants> ][ <eth_load_interval1_rx>
][ <eth_inrate1_bits> ][ <eth_inrate1_pkts> ][ <eth_load_interval1_tx> ][ <eth_outrate1_bits> ][
<eth_outrate1_pkts> ][ <eth_load_interval2> ][ <eth_inrate2_bits> ][ <eth_inrate2_pkts> ][
<eth_outrate2_bits> ][ <eth_outrate2_pkts> ][ <eth_load_interval3> ][ <eth_inrate3_bits> ][
<eth_inrate3_pkts> ][ <eth_outrate3_bits> ][ <eth_outrate3_pkts> ][ <eth_l2_ucastpkts> ][
<eth_l2_ucastbytes> ][ <eth_l2_mcastpkts> ][ <eth_l2_mcastbytes> ][ <eth_l2_bcastpkts> ][
<eth_l2_bcastbytes> ][ <eth_l3in_ucastpkts> ][ <eth_l3in_ucastbytes> ][ <eth_l3in_mcastpkts> ][
<eth_l3in_mcastbytes> ][ <eth_l3in_bcastpkts> ][ <eth_l3in_bcastbytes> ][ <eth_l3out_ucastpkts> ][
<eth_l3out_ucastbytes> ][ <eth_l3out_mcastpkts> ][ <eth_l3out_mcastbytes> ][ <eth_l3out_bcastpkts> ][
<eth_l3out_bcastbytes> ][ <eth_l3in_routed_pkts> ][ <eth_l3in_routed_bytes> ][ <eth_l3out_routed_pkts>
][ <eth_l3out_routed_bytes> ][ <eth_l3avg1_inbytes> ][ <eth_l3avg1_inpkts> ][ <eth_l3avg1_outbytes>
][ <eth_l3avg1_outpkts> ][ <eth_l3avg2_inbytes> ][ <eth_l3avg2_inpkts> ][ <eth_l3avg2_outbytes> ][
<eth_l3avg2_outpkts> ][ <eth_l3avg3_inbytes> ][ <eth_l3avg3_inpkts> ][ <eth_l3avg3_outbytes> ][
<eth_l3avg3_outpkts> ][ <eth_inpkts> ][ <eth_inbytes> ][ <eth_nobuf> ][ <eth_inbcast> ][ <eth_inmcast>
][ <eth_inucast> ][ <eth_ingiants> ][ <eth_ipmcast> ][ <eth_inhw_switched> ][ <eth_insw_switched> ][
<eth_runs> ][ <eth_storm_supp> ][ <eth_throtles> ][ <eth_inerr> ][ <eth_crc> ][ <eth_ecc> ][ <eth_frame>
][ <eth_overrun> ][ <eth_ignored> ][ <eth_watchdog> ][ <eth_outbcast> ][ <eth_outmcast> ][
<eth_outucast> ][ <eth_outgiants> ][ <eth_inpause> ][ <eth_dribble> ][ <eth_in_ifdown_drops> ][
<eth_bad_eth> ][ <eth_bad_proto> ][ <eth_outpkts> ][ <eth_outbytes> ][ <eth_underrun> ][
<eth_outhw_switched> ][ <eth_outsw_switched> ][ <eth_outerr> ][ <eth_coll> ][ <eth_resets> ][
<eth_babbles> ][ <eth_latecoll> ][ <eth_deferred> ][ <eth_lostcarrier> ][ <eth_nocarrier> ][ <eth_outpause>
][ <eth_buffail> ][ <eth_bufswapped> ][ <eth_arpdrops> ][ <eth_out_ifdown_drops> ][ <eth_single_coll>
][ <eth_multi_coll> ][ <eth_excess_coll> ][ <eth_jabbers> ][ <eth_shortframe> ][ <eth_indiscard> ][
<eth_bad_encap> ][ <eth_outcrc> ][ <eth_symbol> ][ <eth_out_drops> ][ <eth_sqetest> ][ <eth_inb64>
][ <eth_inb65_127> ][ <eth_inb128_255> ][ <eth_inb256_511> ][ <eth_inb512_1023> ][
<eth_inb1024_1518> ][ <eth_inb1519_1548> ][ <eth_intrunk> ][ <eth_outb64> ][ <eth_outb65_127> ][
<eth_outb128_255> ][ <eth_outb256_511> ][ <eth_outb512_1023> ][ <eth_outb1024_1518> ][
<eth_outb1519_1548> ][ <eth_outtrunk> ][ <eth_bpdu_outlost> ][ <eth_cos0_outlost> ][ <eth_cos1_outlost>
][ <eth_cos2_outlost> ][ <eth_cos3_outlost> ][ <eth_cos4_outlost> ][ <eth_cos5_outlost> ][
<eth_cos6_outlost> ][ <eth_cos7_outlost> ][ <eth_fcoe_in_pkts> ][ <eth_fcoe_in_octets> ][
<eth_fcoe_out_pkts> ][ <eth_fcoe_out_octets> ][ <eth_nfcoe_in_pkts> ][ <eth_nfcoe_in_octets> ][
<eth_nfcoe_out_pkts> ][ <eth_nfcoe_out_octets> ][ <eth_eee_atx_lpi_msec> ][ <eth_eee_arcv_lpi_msec>
][ <eth_eee_atx_lpi_transitions> ][ <eth_eee_arcv_lpi_transitions> ][ <eth_phy_ber_count> ][
<eth_phy_errblks_count> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_dtl_all</i>	Enter interface type and number in module/slot format
counters	Show interface counters

<i>detailed</i>	Show only non-zero counters
<i>cached</i>	everything cached
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<i>TABLE_interface</i>	(Optional) show interface
<i>rx_total_pkts</i>	(Optional) total input packets
<i>tx_total_pkts</i>	(Optional) total output packets
<i>rx_ucast_pkts</i>	(Optional) input unicasts
<i>rx_mcast_pkts</i>	(Optional) input multicasts
<i>rx_bcast_pkts</i>	(Optional) input broadcasts
<i>rx_octets</i>	(Optional) input bytes
<i>tx_ucast_pkts</i>	(Optional) output unicasts
<i>tx_mcast_pkts</i>	(Optional) output multicasts
<i>tx_bcast_pkts</i>	(Optional) output broadcasts
<i>tx_octets</i>	(Optional) output bytes
<i>rxtx_pkts_64octets</i>	(Optional) all pkts between 0 and 64 bytes
<i>rxtx_pkts_65_127octets</i>	(Optional) all pkts between 65 and 127 bytes
<i>rxtx_pkts_128_255octets</i>	(Optional) all pkts between 128 and 255 bytes
<i>rxtx_pkts_256_511octets</i>	(Optional) all pkts between 256 and 511 bytes
<i>rxtx_pkts_512_1023octets</i>	(Optional) all pkts between 512 and 1023 bytes
<i>rxtx_pkts_1024_1518octets</i>	(Optional) all pkts between 1024 and 1518 bytes
<i>rxtx_pkts_1519_1548octets</i>	(Optional) all pkts between 1519 and 1548 bytes
<i>rx_trunk_frames</i>	(Optional) input trunk pkts
<i>tx_trunk_frames</i>	(Optional) output trunk pkts
<i>rx_drop_events</i>	(Optional) dropped pkts
<i>rxtx_giants</i>	(Optional) giants
<i>eth_load_interval1_rx</i>	(Optional) interval 1 timer value in sec
<i>eth_inrate1_bits</i>	(Optional) interval 1 input rate bits/sec
<i>eth_inrate1_pkts</i>	(Optional) interval 1 input rate pkts/sec

<i>eth_load_interval1_tx</i>	(Optional) interval 1 timer value in sec
<i>eth_outrate1_bits</i>	(Optional) interval 1 output rate bits/sec
<i>eth_outrate1_pkts</i>	(Optional) interval 1 output rate pkts/sec
<i>eth_load_interval2</i>	(Optional) interval 2 timer value in sec
<i>eth_inrate2_bits</i>	(Optional) interval 2 input rate bits/sec
<i>eth_inrate2_pkts</i>	(Optional) interval 2 input rate pkts/sec
<i>eth_outrate2_bits</i>	(Optional) interval 2 output rate bits/sec
<i>eth_outrate2_pkts</i>	(Optional) interval 2 output rate pkts/sec
<i>eth_load_interval3</i>	(Optional) interval 3 timer value in sec
<i>eth_inrate3_bits</i>	(Optional) interval 3 input rate bits/sec
<i>eth_inrate3_pkts</i>	(Optional) interval 3 input rate pkts/sec
<i>eth_outrate3_bits</i>	(Optional) interval 3 output rate bits/sec
<i>eth_outrate3_pkts</i>	(Optional) interval 3 output rate pkts/sec
<i>eth_l2_ucastpkts</i>	(Optional) L2 switched ucast pkts
<i>eth_l2_ucastbytes</i>	(Optional) L2 switched ucast bytes
<i>eth_l2_mcastpkts</i>	(Optional) L2 switched mcast pkts
<i>eth_l2_mcastbytes</i>	(Optional) L2 switched mcast bytes
<i>eth_l2_bcastpkts</i>	(Optional) L2 switched bcast pkts
<i>eth_l2_bcastbytes</i>	(Optional) L2 switched bcast bytes
<i>eth_l3in_ucastpkts</i>	(Optional) IPv4 L3 in switched ucast pkts
<i>eth_l3in_ucastbytes</i>	(Optional) IPv4 L3 in switched ucast bytes
<i>eth_l3in_mcastpkts</i>	(Optional) IPv4 L3 in switched mcast pkts
<i>eth_l3in_mcastbytes</i>	(Optional) IPv4 L3 in switched mcast bytes
<i>eth_l3in_bcastpkts</i>	(Optional) L3 in switched bcast pkts
<i>eth_l3in_bcastbytes</i>	(Optional) L3 in switched bcast bytes
<i>eth_l3out_ucastpkts</i>	(Optional) IPv4 L3 out switched ucast pkts
<i>eth_l3out_ucastbytes</i>	(Optional) IPv4 L3 out switched ucast bytes
<i>eth_l3out_mcastpkts</i>	(Optional) IPv4 L3 out switched mcast pkts
<i>eth_l3out_mcastbytes</i>	(Optional) IPv4 L3 out switched mcast bytes

<i>eth_l3out_bcastpkts</i>	(Optional) L3 out switched bcast pkts
<i>eth_l3out_bcastbytes</i>	(Optional) L3 out switched bcast bytes
<i>eth_l3in_routed_pkts</i>	(Optional) L3 in routed pkts
<i>eth_l3in_routed_bytes</i>	(Optional) L3 in routed bytes
<i>eth_l3out_routed_pkts</i>	(Optional) L3 out routed pkts
<i>eth_l3out_routed_bytes</i>	(Optional) L3 out routed bytes
<i>eth_l3avg1_inbytes</i>	(Optional) Load interval 1 L3 average in switched bytes
<i>eth_l3avg1_inpkts</i>	(Optional) Load interval 1 L3 average in switched pkts
<i>eth_l3avg1_outbytes</i>	(Optional) Load interval 1 L3 average out switched bytes
<i>eth_l3avg1_outpkts</i>	(Optional) Load interval 1 L3 average out switched pkts
<i>eth_l3avg2_inbytes</i>	(Optional) Load interval 2 L3 average in switched bytes
<i>eth_l3avg2_inpkts</i>	(Optional) Load interval 2 L3 average in switched pkts
<i>eth_l3avg2_outbytes</i>	(Optional) Load interval 2 L3 average out switched bytes
<i>eth_l3avg2_outpkts</i>	(Optional) Load interval 2 L3 average out switched pkts
<i>eth_l3avg3_inbytes</i>	(Optional) Load interval 3 L3 average in switched bytes
<i>eth_l3avg3_inpkts</i>	(Optional) Load interval 3 L3 average in switched pkts
<i>eth_l3avg3_outbytes</i>	(Optional) Load interval 3 L3 average out switched bytes
<i>eth_l3avg3_outpkts</i>	(Optional) Load interval 3 L3 average out switched pkts
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_nobuf</i>	(Optional) No buffer received
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_ingiants</i>	(Optional) giants
<i>eth_ipmcast</i>	(Optional) IP multicast
<i>eth_inhw_switched</i>	(Optional) Input H/W Switched
<i>eth_insw_switched</i>	(Optional) Input S/W Switched
<i>eth_runs</i>	(Optional) runs

<i>eth_storm_supp</i>	(Optional) storm suppression
<i>eth_throtles</i>	(Optional) throttles
<i>eth_inerr</i>	(Optional) input errors
<i>eth_crc</i>	(Optional) CRC
<i>eth_ecc</i>	(Optional) ECC
<i>eth_frame</i>	(Optional) frame
<i>eth_overrun</i>	(Optional) overrun
<i>eth_ignored</i>	(Optional) ignored
<i>eth_watchdog</i>	(Optional) watchdog
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outucast</i>	(Optional) Unicasts
<i>eth_outgiants</i>	(Optional) giants
<i>eth_inpause</i>	(Optional) pause input
<i>eth_dribble</i>	(Optional) input packets with dribble condition
<i>eth_in_ifdown_drops</i>	(Optional) Input if-down drops
<i>eth_bad_eth</i>	(Optional) bad ether type drop
<i>eth_bad_proto</i>	(Optional) bad protocol drops
<i>eth_outpkts</i>	(Optional) packets output
<i>eth_outbytes</i>	(Optional) bytes output
<i>eth_underrun</i>	(Optional) underruns
<i>eth_outhw_switched</i>	(Optional) Out H/W Switched
<i>eth_outsw_switched</i>	(Optional) Out S/W Switched
<i>eth_outerr</i>	(Optional) output errors
<i>eth_coll</i>	(Optional) collisions
<i>eth_resets</i>	(Optional) interface resets
<i>eth_babbles</i>	(Optional) babbles
<i>eth_latecoll</i>	(Optional) late collision
<i>eth_deferred</i>	(Optional) deferred

<i>eth_lostcarrier</i>	(Optional) lost carrier
<i>eth_nocarrier</i>	(Optional) no carrier
<i>eth_outpause</i>	(Optional) PAUSE output
<i>eth_buffail</i>	(Optional) output buffer failures
<i>eth_bufswapped</i>	(Optional) output buffers swapped out
<i>eth_arpdrops</i>	(Optional) arp drops
<i>eth_out_ifdown_drops</i>	(Optional) Output if-down drops
<i>eth_single_coll</i>	(Optional) single collisions
<i>eth_multi_coll</i>	(Optional) multi collisions
<i>eth_excess_coll</i>	(Optional) excessive collisions
<i>eth_jabbers</i>	(Optional) jabbers
<i>eth_shortframe</i>	(Optional) short frames
<i>eth_indiscard</i>	(Optional) discards
<i>eth_bad_encap</i>	(Optional) bad encapsulation
<i>eth_outcrc</i>	(Optional) Output CRC
<i>eth_symbol</i>	(Optional) symbol errors
<i>eth_out_drops</i>	(Optional) output drops
<i>eth_sqetest</i>	(Optional) SQE test
<i>eth_inb64</i>	(Optional) input pkts between 0 and 64 bytes
<i>eth_inb65_127</i>	(Optional) input pkts between 65 and 127 bytes
<i>eth_inb128_255</i>	(Optional) input pkts between 128 and 255 bytes
<i>eth_inb256_511</i>	(Optional) input pkts between 256 and 511 bytes
<i>eth_inb512_1023</i>	(Optional) input pkts between 512 and 1023 bytes
<i>eth_inb1024_1518</i>	(Optional) input pkts between 1024 and 1518 bytes
<i>eth_inb1519_1548</i>	(Optional) input pkts between 1519 and 1548 bytes
<i>eth_intrunk</i>	(Optional) input trunk pkts
<i>eth_outb64</i>	(Optional) output pkts between 0 and 64 bytes
<i>eth_outb65_127</i>	(Optional) output pkts between 65 and 127 bytes
<i>eth_outb128_255</i>	(Optional) output pkts between 128 and 255 bytes

<i>eth_outb256_511</i>	(Optional) output pkts between 256 and 511 bytes
<i>eth_outb512_1023</i>	(Optional) output pkts between 512 and 1023 bytes
<i>eth_outb1024_1518</i>	(Optional) output pkts between 1024 and 1518 bytes
<i>eth_outb1519_1548</i>	(Optional) output pkts between 1519 and 1548 bytes
<i>eth_outtrunk</i>	(Optional) output trunk pkts
<i>eth_bpdu_outlost</i>	(Optional) BPDU output lost
<i>eth_cos0_outlost</i>	(Optional) output pkts
<i>eth_cos1_outlost</i>	(Optional) output pkts
<i>eth_cos2_outlost</i>	(Optional) output pkts
<i>eth_cos3_outlost</i>	(Optional) output pkts
<i>eth_cos4_outlost</i>	(Optional) output pkts
<i>eth_cos5_outlost</i>	(Optional) output pkts
<i>eth_cos6_outlost</i>	(Optional) output pkts
<i>eth_cos7_outlost</i>	(Optional) output pkts
<i>eth_fcoe_in_pkts</i>	(Optional) fcoe in pkts
<i>eth_fcoe_in_octets</i>	(Optional) fcoe in octets
<i>eth_fcoe_out_pkts</i>	(Optional) fcoe out pkts
<i>eth_fcoe_out_octets</i>	(Optional) fcoe out octets
<i>eth_nfcoe_in_pkts</i>	(Optional) nfcoe in pkts
<i>eth_nfcoe_in_octets</i>	(Optional) nfcoe in octets
<i>eth_nfcoe_out_pkts</i>	(Optional) nfcoe out pkts
<i>eth_nfcoe_out_octets</i>	(Optional) nfcoe out octets
<i>eth_eee_atx_lpi_msec</i>	(Optional) Tx Lpi usec
<i>eth_eee_arcv_lpi_msec</i>	(Optional) Rx Lpi usec
<i>eth_eee_atx_lpi_transitions</i>	(Optional) Tx Lpi requests
<i>eth_eee_arcv_lpi_transitions</i>	(Optional) Rx Lpi indications
<i>eth_phy_ber_count</i>	(Optional) Bit error rate counter
<i>eth_phy_errblks_count</i>	(Optional) Errored blocks counter

Command Mode

- /exec

show interface counters errors

```
show interface <ifeth_ctr_errs> counters errors [ snmp ] [ __readonly__ TABLE_interface <interface> [
<eth_align_err> ] [ <eth_fcs_err> ] [ <eth_xmit_err> ] [ <eth_rcv_err> ] [ <eth_undersize> ] [ <eth_outdisc>
] [ <eth_single_col> ] [ <eth_multi_col> ] [ <eth_late_col> ] [ <eth_excess_col> ] [ <eth_carri_sen> ] [
<eth_runs> ] [ <eth_giants> ] [ <eth_sqetest_err> ] [ <eth_deferred_tx> ] [ <eth_inmactx_err> ] [
<eth_inmacrx_err> ] [ <eth_symbol_err> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_errs</i>	Enter interface type and number in module/slot format
counters	Show interface counters
errors	Show interface error counters
snmp	(Optional) Show SNMP MIB values
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_align_err</i>	(Optional) Align error
<i>eth_fcs_err</i>	(Optional) FCS error
<i>eth_xmit_err</i>	(Optional) Transmit error
<i>eth_rcv_err</i>	(Optional) Receive error
<i>eth_undersize</i>	(Optional) Undersize
<i>eth_outdisc</i>	(Optional) Out discard
<i>eth_single_col</i>	(Optional) Single collision
<i>eth_multi_col</i>	(Optional) Multiple collision
<i>eth_late_col</i>	(Optional) Late collision
<i>eth_excess_col</i>	(Optional) Excess collision
<i>eth_carri_sen</i>	(Optional) Carrier sense
<i>eth_runs</i>	(Optional) Runts
<i>eth_giants</i>	(Optional) Giants
<i>eth_sqetest_err</i>	(Optional) SQETest error

<i>eth_deferred_tx</i>	(Optional) Deferred tx
<i>eth_inmactx_err</i>	(Optional) In MAC tx
<i>eth_inmacrx_err</i>	(Optional) In MAC rx
<i>eth_symbol_err</i>	(Optional) Symbol error

Command Mode

- /exec

show interface counters errors

```
show interface counters errors [ module <module> ] [ non-zero ] [ __readonly__ TABLE_interface <interface>
[ <eth_align_err> ] [ <eth_fcs_err> ] [ <eth_xmit_err> ] [ <eth_rcv_err> ] [ <eth_undersize> ] [ <eth_outdisc>
] [ <eth_single_col> ] [ <eth_multi_col> ] [ <eth_late_col> ] [ <eth_excess_col> ] [ <eth_carri_sen> ] [
<eth_runs> ] [ <eth_giants> ] [ <eth_sqetest_err> ] [ <eth_deferred_tx> ] [ <eth_inmacrx_err> ] [
<eth_inmactx_err> ] [ <eth_symbol_err> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
errors	Show interface error counters
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
non-zero	(Optional) Display only the non-zero error values
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_align_err</i>	(Optional) Align error
<i>eth_fcs_err</i>	(Optional) FCS error
<i>eth_xmit_err</i>	(Optional) Transmit error
<i>eth_rcv_err</i>	(Optional) Receive error
<i>eth_undersize</i>	(Optional) Undersize
<i>eth_outdisc</i>	(Optional) Out discard
<i>eth_single_col</i>	(Optional) Single collision
<i>eth_multi_col</i>	(Optional) Multiple collision
<i>eth_late_col</i>	(Optional) Late collision
<i>eth_excess_col</i>	(Optional) Excess collision
<i>eth_carri_sen</i>	(Optional) Carrier sense
<i>eth_runs</i>	(Optional) Runt
<i>eth_giants</i>	(Optional) Giants

<i>eth_sqetest_err</i>	(Optional) SQETest error
<i>eth_deferred_tx</i>	(Optional) Deferred tx
<i>eth_inmacrx_err</i>	(Optional) In MAC rx
<i>eth_inmactx_err</i>	(Optional) In MAC tx
<i>eth_symbol_err</i>	(Optional) Symbol error

Command Mode

- /exec

show interface counters errors

show interface <loop_ctr_errs> counters errors

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>loop_ctr_errs</i>	Enter interface type and number in module/slot format
counters	Show interface counters
errors	Show interface error counters

Command Mode

- /exec

show interface counters snmp

```
show interface counters snmp [ module <module> ] [ __readonly__ { TABLE_rx_counters <interface_rx> [
<eth_inpkts> ] [ <eth_inbytes> ] [ <eth_inucast> ] [ <eth_inmcast> ] [ <eth_inbcast> ] [ <eth_l3in_bytes> ]
[ <eth_l3in_ucastpkts> ] [ <eth_l3in_mcastpkts> ] [ <eth_l3in_bcastpkts> ] } { TABLE_tx_counters
<interface_tx> [ <eth_outpkts> ] [ <eth_outbytes> ] [ <eth_outucast> ] [ <eth_outmcast> ] [ <eth_outbcast>
] [ <eth_l3out_bytes> ] [ <eth_l3out_ucastpkts> ] [ <eth_l3out_mcastpkts> ] [ <eth_l3out_bcastpkts> ] } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
snmp	Show SNMP MIB values
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
__readonly__	(Optional) Read Only
TABLE_rx_counters	(Optional) show Rx counters
<i>interface_rx</i>	(Optional) Interface index
<i>eth_inpkts</i>	(Optional) Packets input
<i>eth_inbytes</i>	(Optional) Bytes input
<i>eth_inucast</i>	(Optional) Unicasts
<i>eth_inmcast</i>	(Optional) Multicasts
<i>eth_inbcast</i>	(Optional) Broadcasts
<i>eth_l3in_bytes</i>	(Optional) L3 Rx bytes
<i>eth_l3in_ucastpkts</i>	(Optional) L3 Rx Unicast pkts
<i>eth_l3in_mcastpkts</i>	(Optional) L3 Rx Multicast pkts
<i>eth_l3in_bcastpkts</i>	(Optional) L3 Rx Broadcast pkts
TABLE_tx_counters	(Optional) show Tx counters
<i>interface_tx</i>	(Optional) Interface index
<i>eth_outpkts</i>	(Optional) Packets output
<i>eth_outbytes</i>	(Optional) Bytes output
<i>eth_outucast</i>	(Optional) Unicasts

<i>eth_outmcast</i>	(Optional) Multicasts
<i>eth_outbcast</i>	(Optional) Broadcasts
<i>eth_l3out_bytes</i>	(Optional) L3 Tx bytes
<i>eth_l3out_ucastpkts</i>	(Optional) L3 Tx Unicast pkts
<i>eth_l3out_mcastpkts</i>	(Optional) L3 Tx Multicast pkts
<i>eth_l3out_bcastpkts</i>	(Optional) L3 Tx Broadcast pkts

Command Mode

- /exec

show interface counters storm-control

```
show interface <ifeth_ctr_stm_ctrl> counters storm-control [ __readonly__ TABLE_interface <interface>
<eth_ucast_supp> <eth_mcast_supp> <eth_bcast_supp> <eth_total_supp> <supp_action> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_stm_ctrl</i>	Enter interface type and number in module/slot format
counters	Show interface counters
storm-control	Show interface storm-control counters
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_ucast_supp</i>	(Optional) Unicast suppression percentage
<i>eth_mcast_supp</i>	(Optional) Multicast suppression percentage
<i>eth_bcast_supp</i>	(Optional) Broadcast suppression percentage
<i>eth_total_supp</i>	(Optional) Total discarded due to suppression
<i>supp_action</i>	(Optional) Action to be taken on suppression

Command Mode

- /exec

show interface counters storm-control

```
show interface counters storm-control [ module <module> ] [ __readonly__ TABLE_interface <interface>
<eth_ucast_supp> <eth_mcast_supp> <eth_bcast_supp> <eth_total_supp> <supp_action> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
storm-control	Show interface storm-control counters
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_ucast_supp</i>	(Optional) Unicast suppression percentage
<i>eth_mcast_supp</i>	(Optional) Multicast suppression percentage
<i>eth_bcast_supp</i>	(Optional) Broadcast suppression percentage
<i>eth_total_supp</i>	(Optional) Total discarded due to suppression
<i>supp_action</i>	(Optional) Action to be taken on suppression

Command Mode

- /exec

show interface counters table

show interface counters table [verbose]

Syntax Description

show	Show running system information
interface	Show interface status and information
counters	Show interface counters
table	format counters in a table
verbose	(Optional) show errors counts after counters

Command Mode

- /exec

show interface counters trunk

```
show interface <ifeth_ctr_trnk> counters trunk [ __readonly__ TABLE_interface <interface> [
<eth_trunk_frames_tx> ] [ <eth_trunk_frames_rx> ] [ <eth_wrong_encap> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_ctr_trnk</i>	Enter interface type and number in module/slot format
counters	Show interface counters
trunk	Show interface trunk counters
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>eth_trunk_frames_tx</i>	(Optional) Trunk frame transmitted
<i>eth_trunk_frames_rx</i>	(Optional) Trunk frames received
<i>eth_wrong_encap</i>	(Optional) Wrong encapsulation

Command Mode

- /exec

show interface dampening

show interface dampening

Syntax Description

show	Show running system information
interface	Show interface status and information
dampening	Show interface dampening info

Command Mode

- /exec

show interface debounce

show interface debounce [__readonly__ TABLE_interface <interface> <debounce> <debounce_val>]

Syntax Description

show	Show running system information
interface	Show interface status and information
debounce	Show interface debounce time information
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>debounce</i>	(Optional) Debounce time
<i>debounce_val</i>	(Optional) Value(ms)

Command Mode

- /exec

show interface debounce

```
show interface <ifeth_dbnc> debounce [ __readonly__ TABLE_interface <interface> <debounce>  
<debounce_val> ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifeth_dbnc</i>	Enter interface type and number in module/slot format
<code>debounce</code>	Show interface debounce time information
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>debounce</i>	(Optional) Debounce time
<i>debounce_val</i>	(Optional) Value(ms)

Command Mode

- /exec

show interface description

show interface <ifid> description [__readonly__ <start> <if_index> <LINE>]

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
description	Interface specific description
__readonly__	(Optional) Read Only
<i>start</i>	(Optional) Start
<i>if_index</i>	(Optional) Interface
<i>LINE</i>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface description [ __readonly__ TABLE_interface <interface> [ <state> ] [ <type> ] [ <speed> ] [
<protocol> ] [ <desc> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<code>description</code>	Show interface description
<code>__readonly__</code>	(Optional) Read Only
<code>interface</code>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<code>state</code>	(Optional) Interface state
<code>type</code>	(Optional) Type
<code>speed</code>	(Optional) Speed
<code>protocol</code>	(Optional) Protocol
<code>desc</code>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface <ifid_mgmt_loop> description [ __readonly__ TABLE_interface <interface> [ <state> ] [
<protocol> ] [ <desc> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_mgmt_loop</i>	Enter interface type and number in module/slot format
description	Show interface description
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>protocol</i>	(Optional) Protocol
<i>desc</i>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface <ifid_eth> description [ __readonly__ TABLE_interface <interface> [ <state> ] [ <type> ] [ <speed> ] [ <protocol> ] [ <desc> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<code>ifid_eth</code>	Enter interface type and number in module/slot format
<code>description</code>	Show interface description
<code>__readonly__</code>	(Optional) Read Only
<code>interface</code>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<code>state</code>	(Optional) Interface state
<code>type</code>	(Optional) Type
<code>speed</code>	(Optional) Speed
<code>protocol</code>	(Optional) Protocol
<code>desc</code>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface <iftun_desc> description [ __readonly__ TABLE_interface <interface> <state> <protocol>
<desc> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>iftun_desc</i>	Enter tunnel interface number
description	Show interface description
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>protocol</i>	(Optional) Protocol
<i>desc</i>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface <ifrange> description [ __readonly__ TABLE_interface <interface> <state> <protocol> <desc> ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifrange</i>	Enter tunnel interface number
<code>description</code>	Show interface description
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>protocol</i>	(Optional) Protocol
<i>desc</i>	(Optional) Description

Command Mode

- /exec

show interface description

```
show interface <ifrange> description [ __readonly__ TABLE_interface <interface> <state> <protocol> <desc> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter tunnel interface number
description	Show interface description
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>state</i>	(Optional) Interface state
<i>protocol</i>	(Optional) Protocol
<i>desc</i>	(Optional) Description

Command Mode

- /exec

show interface fcoe

```
show interface <ifeth_fcoe> fcoe [ __readonly__ TABLE_interface <interface> [ <state> ] [ <vfc> ] [ <vfc_bound> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_fcoe</i>	Enter interface type and number in module/slot format
fcoe	Show interface fcoe information
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>state</i>	(Optional) State of interface
<i>vfc</i>	(Optional) VFC
<i>vfc_bound</i>	(Optional) Binding information

Command Mode

- /exec

show interface flowcontrol

```
show interface <ifeth_fl_ctrl> flowcontrol [ __readonly__ TABLE_interface <interface> <send_admin>
<send_oper> <recv_admin> <recv_oper> <rxpause> <txpause> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_fl_ctrl</i>	Enter interface type and number in module/slot format
flowcontrol	Show interface flowcontrol information
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>send_admin</i>	(Optional) Send flowcontrol admin
<i>send_oper</i>	(Optional) Send flowcontrol oper
<i>recv_admin</i>	(Optional) Receive flowcontrol admin
<i>recv_oper</i>	(Optional) Receive flowcontrol oper
<i>rxpause</i>	(Optional) RxPause
<i>txpause</i>	(Optional) TxPause

Command Mode

- /exec

show interface flowcontrol

```
show interface flowcontrol [ module <module> ] [ __readonly__ TABLE_interface <interface> <send_admin>
<send_oper> <recv_admin> <recv_oper> <rxpause> <txpause> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
flowcontrol	Show interface flowcontrol information
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>send_admin</i>	(Optional) Send flowcontrol admin
<i>send_oper</i>	(Optional) Send flowcontrol oper
<i>recv_admin</i>	(Optional) Receive flowcontrol admin
<i>recv_oper</i>	(Optional) Receive flowcontrol oper
<i>rxpause</i>	(Optional) RxPause
<i>txpause</i>	(Optional) TxPause

Command Mode

- /exec

show interface mac-address

show interface <ifid_macaddr> mac-address [__readonly__ TABLE_interface <interface> <address> <bia_address>]

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_macaddr</i>	Enter interface type and number in module/slot format
mac-address	Show interface MAC address
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>address</i>	(Optional) MAC Address
<i>bia_address</i>	(Optional) Burn-In MAC Address

Command Mode

- /exec

show interface mac-address

show interface mac-address [__readonly__ TABLE_interface <interface> <address> <bia_address>]

Syntax Description

show	Show running system information
interface	Show interface status and information
mac-address	Show interface MAC address
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>address</i>	(Optional) MAC Address
<i>bia_address</i>	(Optional) Burn-In MAC Address

Command Mode

- /exec

show interface private-vlan mapping

```
show interface [ <if> ] private-vlan mapping [ __readonly__ [ <output-filtered> ] [ { TABLE_interf_mapp  
<interface-id> [ <secondary-vlan> + ] [ <pvlan-type> ] } ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>if</i>	(Optional) Vlan Interface number
private-vlan	Show interface private vlan information
mapping	Show interface private vlan information
<i>__readonly__</i>	(Optional) Read Only
<i>output-filtered</i>	(Optional) the output is filtered for specified ifs
TABLE_interf_mapp	(Optional) Pvlan interface mapping table
<i>interface-id</i>	(Optional) Interface
<i>secondary-vlan</i>	(Optional) Secondary Vlan
<i>pvlan-type</i>	(Optional) PVLAN Type

Command Mode

- /exec

show interface pruning

```
show interface pruning [ __readonly__ <start> { TABLE_interface_pruning1 <if_index1> <rx_join> } {  
TABLE_interface_pruning2 <if_index2> <cur_join> } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
pruning	Show interface trunk VTP pruning information
__readonly__	(Optional) Read Only
start	(Optional) Start
TABLE_interface_pruning1	(Optional) Interface pruning information in table format
if_index1	(Optional) Trunk
rx_join	(Optional) Vlan pruning for lack of request by neighbor
TABLE_interface_pruning2	(Optional) Interface pruning information in table format
if_index2	(Optional) Trunk
cur_join	(Optional) Vlan traffic requested of neighbor

Command Mode

- /exec

show interface snmp-ifindex

```
show interface snmp-ifindex [ __readonly__ TABLE_interface <interface> <snmp-ifindex> [ <ifindex-hex> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
snmp-ifindex	Show snmp ifindex list
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>ifindex-hex</i>	(Optional) If Index in Hex
<i>snmp-ifindex</i>	(Optional) If Index in Dec

Command Mode

- /exec

show interface status

```
show interface <iftun_status> status [ err-disabled ] [ __readonly__ TABLE_interface <interface> <name>  
<state> <state_rsn> <state_rsn_desc> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>iftun_status</i>	Enter tunnel interface number
status	Show interface line status
err-disabled	(Optional) Show interface error disabled state
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed

Command Mode

- /exec

show interface status

```
show interface status [ down | inactive | module <module> | up | auto-column ] [ __readonly__ TABLE_interface
<interface> [ <name> ] [ <state> ] [ <state_san> ] [ <state_rsn> ] [ <vlan> ] [ <duplex> ] [ <speed> ] [ <type>
] [ <admin_mode> ] [ <vsan> ] [ <bind_info> ] [ <bind_type> ] [ <bind_mac> ] [ <oper_speed> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
status	Show interface line status
down	(Optional) Show interface down state
inactive	(Optional) Show interface inactive state
auto-column	(Optional) Show interface status auto-column adjusted
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
up	(Optional) Show interface up state
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>state_san</i>	(Optional) SAN Port State
<i>vlan</i>	(Optional) Vlan
<i>vsan</i>	(Optional) Vsan
<i>duplex</i>	(Optional) Duplex
<i>speed</i>	(Optional) Speed
<i>type</i>	(Optional) Type
<i>state_rsn</i>	(Optional) Port State Reason
<i>bind_info</i>	(Optional) bind interface
<i>bind_type</i>	(Optional) bind type
<i>bind_mac</i>	(Optional) bind mac

<i>oper_speed</i>	(Optional) speed
<i>admin_mode</i>	(Optional) admin mode

Command Mode

- /exec

show interface status

```
show interface <ifid_status> status [ __readonly__ TABLE_interface <interface> [ <name> ] [ <state> ] [ <vlan> ] [ <duplex> ] [ <speed> ] [ <type> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifid_status</i>	Enter interface type and number in module/slot format
<code>status</code>	Show interface line status
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>vlan</i>	(Optional) Vlan
<i>duplex</i>	(Optional) Duplex
<i>speed</i>	(Optional) Speed
<i>type</i>	(Optional) Type

Command Mode

- /exec

show interface status

```
show interface <ifeth_status> status [ __readonly__ TABLE_interface <interface> [ <name> ] [ <state> ] [ <vlan> ] <duplex> <speed> [ <type> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifeth_status</i>	Enter interface type and number in module/slot format
<code>status</code>	Show interface line status
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>vlan</i>	(Optional) Vlan
<i>duplex</i>	(Optional) Duplex
<i>speed</i>	(Optional) Speed
<i>type</i>	(Optional) Type

Command Mode

- /exec

show interface status

```
show interface <ifrange> status [ err-disabled ] [ __readonly__ TABLE_interface <interface> <name> <state>
<state_rsn> <state_rsn_desc> ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifrange</i>	Enter tunnel interface number
status	Show interface line status
err-disabled	(Optional) Show interface error disabled state
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed

Command Mode

- /exec

show interface status

```
show interface <ifrange> status [ err-disabled ] [ __readonly__ TABLE_interface <interface> <name> <state>
<state_rsn> <state_rsn_desc> <admin_state> ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<i>ifrange</i>	Enter tunnel interface number
<code>status</code>	Show interface line status
<code>err-disabled</code>	(Optional) Show interface error disabled state
<code>__readonly__</code>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed
<i>admin_state</i>	(Optional) admin state

Command Mode

- /exec

show interface status

show interface <ifid> status [__readonly__ <start> <if_index> <admin-state> <line-proto>]

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
status	Interface status
__readonly__	(Optional) Read Only
<i>start</i>	(Optional) Start
<i>if_index</i>	(Optional) Interface
<i>admin-state</i>	(Optional)
<i>line-proto</i>	(Optional)

Command Mode

- /exec

show interface status err-disabled

```
show interface <ifeth_errdis> status err-disabled [ __readonly__ TABLE_interface <interface> [ <name> ]
<state> [ <state_rsn> ] [ <state_rsn_desc> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>interface</code>	Show interface status and information
<code>status</code>	Show interface line status
<code>ifeth_errdis</code>	Enter interface type and number in module/slot format
<code>err-disabled</code>	Show interface error disabled state
<code>__readonly__</code>	(Optional) Read Only
<code>interface</code>	(Optional) Interface index
<code>TABLE_interface</code>	(Optional) show interface
<code>name</code>	(Optional) Name
<code>state</code>	(Optional) Interface state
<code>state_rsn</code>	(Optional) Interface state reason
<code>state_rsn_desc</code>	(Optional) Interface state reason detailed

Command Mode

- /exec

show interface status err-disabled

```
show interface status err-disabled [ __readonly__ TABLE_interface <interface> [ <name> ] <state> [ <state_rsn> ] [ <state_rsn_desc> ] ]
```

Syntax Description

<i>show</i>	Show running system information
<i>interface</i>	Show interface status and information
<i>status</i>	Show interface line status
<i>err-disabled</i>	Show interface error disabled state
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<i>TABLE_interface</i>	(Optional) show interface
<i>name</i>	(Optional) Name
<i>state</i>	(Optional) Interface state
<i>state_rsn</i>	(Optional) Interface state reason
<i>state_rsn_desc</i>	(Optional) Interface state reason detailed

Command Mode

- /exec

show interface status err-vlans

```
show interface status err-vlans [ __readonly__ TABLE_interface <interface> [ <name> ] { TABLE_vlan  
<err_vlan> <err_vlan_status> <err_vlan_syserr> } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
status	Show interface line status
err-vlans	Show errored vlans
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>name</i>	(Optional) Name
TABLE_vlan	(Optional) show vlan
<i>err_vlan</i>	(Optional) Errored vlan
<i>err_vlan_status</i>	(Optional) Errored vlan status
<i>err_vlan_syserr</i>	(Optional) Errored vlan syserr name

Command Mode

- /exec

show interface status err-vlans

```
show interface <ifeth_errvlans> status err-vlans [ __readonly__ TABLE_interface <interface> [ <name> ] [
{ TABLE_vlan [ <err_vlan> ] [ <err_vlan_status> ] [ <err_vlan_syserr> } } ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_errvlans</i>	Enter interface type and number in module/slot format
status	Show interface line status
err-vlans	Show errored vlans
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>name</i>	(Optional) Name
TABLE_vlan	(Optional) show vlan
<i>err_vlan</i>	(Optional) Errored vlan
<i>err_vlan_status</i>	(Optional) Errored vlan status
<i>err_vlan_syserr</i>	(Optional) Errored vlan syserr name

Command Mode

- /exec

show interface switchport

```
show interface <ifeth_swth> switchport [ __readonly__ TABLE_interface <interface> <switchport> [
<switchport_monitor> ] [ <switchport_isolated> ] [ <switchport_block_multicast> ] [
<switchport_block_unicast> ] [ <oper_mode> ] [ <access_vlan> ] [ <access_vlan_name> ] [ <native_vlan>
] [ <native_vlan_name> ] [ <trunk_vlans> ] [ <fabricpath_topologies> ] [ <pruning_vlans> ] [ <voice_vlan>
] [ <voice_vlan_name> ] [ <extended_trust> ] [ <extended_trust_name> ] [ <admin_pvlan_pri_assoc> ] [
<admin_pvlan_sec_assoc> ] [ <admin_pvlan_pri_mapping> ] [ <admin_pvlan_sec_mapping> ] [
<admin_pvlan_trunk_native> ] [ <admin_pvlan_trunk_encap> ] [ <admin_pvlan_trunk_normal> ] [
<admin_pvlan_trunk_private> ] [ <oper_pvlan> ] [ <autostate_mode> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_swth</i>	Enter interface type and number in module/slot format
switchport	Show interface switchport information
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>switchport</i>	(Optional) Switchport enabled
<i>switchport_monitor</i>	(Optional) Switchport monitor enabled
<i>switchport_isolated</i>	(Optional) Switchport isolated enabled
<i>switchport_block_multicast</i>	(Optional) Switchport monitor enabled
<i>switchport_block_unicast</i>	(Optional) Switchport monitor enabled
<i>oper_mode</i>	(Optional) Operational mode
<i>access_vlan</i>	(Optional) Access mode VLAN
<i>access_vlan_name</i>	(Optional) Access mode VLAN name
<i>native_vlan</i>	(Optional) Trunking native mode VLAN
<i>native_vlan_name</i>	(Optional) Trunking native mode VLAN name
<i>trunk_vlans</i>	(Optional) Trunking VLANs Allowed
<i>fabricpath_topologies</i>	(Optional) FabricPath Topologies Allowed
<i>pruning_vlans</i>	(Optional) Pruning eligible VLANs
<i>voice_vlan</i>	(Optional) Voice VLAN

<i>voice_vlan_name</i>	(Optional) Voice VLAN name
<i>extended_trust</i>	(Optional) Extended Trust
<i>extended_trust_name</i>	(Optional) Extended Trust name
<i>admin_pvlan_pri_assoc</i>	(Optional) Administrative private-vlan primary host-association
<i>admin_pvlan_sec_assoc</i>	(Optional) Administrative private-vlan secondary host-association
<i>admin_pvlan_pri_mapping</i>	(Optional) Administrative private-vlan primary mapping
<i>admin_pvlan_sec_mapping</i>	(Optional) Administrative private-vlan secondary mapping
<i>admin_pvlan_trunk_native</i>	(Optional) Administrative private-vlan trunk native VLAN
<i>admin_pvlan_trunk_encap</i>	(Optional) Administrative private-vlan trunk encapsulation
<i>admin_pvlan_trunk_normal</i>	(Optional) Administrative private-vlan trunk normal VLANs
<i>admin_pvlan_trunk_private</i>	(Optional) Administrative private-vlan trunk private VLANs
<i>oper_pvlan</i>	(Optional) Operational private-vlan
<i>autostate_mode</i>	(Optional) SVI Autostate Exclude Info

Command Mode

- /exec

show interface switchport

```
show interface switchport [ __readonly__ TABLE_interface <interface> <switchport> [ <switchport_monitor>
] [ <switchport_isolated> ] [ <switchport_block_multicast> ] [ <switchport_block_unicast> ] [ <oper_mode>
] [ <access_vlan> ] [ <access_vlan_name> ] [ <native_vlan> ] [ <native_vlan_name> ] [ <trunk_vlans> ] [
<fabricpath_topologies> ] [ <pruning_vlans> ] [ <voice_vlan> ] [ <voice_vlan_name> ] [ <extended_trust>
] [ <extended_trust_name> ] [ <admin_pvlan_pri_assoc> ] [ <admin_pvlan_sec_assoc> ] [
<admin_pvlan_pri_mapping> ] [ <admin_pvlan_sec_mapping> ] [ <admin_pvlan_trunk_native> ] [
<admin_pvlan_trunk_encap> ] [ <admin_pvlan_trunk_normal> ] [ <admin_pvlan_trunk_private> ] [
<oper_pvlan> ] [ <autostate_mode> ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
switchport	Show interface switchport information
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>switchport</i>	(Optional) Switchport enabled
<i>switchport_monitor</i>	(Optional) Switchport monitor enabled
<i>switchport_isolated</i>	(Optional) Switchport isolated enabled
<i>switchport_block_multicast</i>	(Optional) Switchport monitor enabled
<i>switchport_block_unicast</i>	(Optional) Switchport monitor enabled
<i>oper_mode</i>	(Optional) Operational mode
<i>access_vlan</i>	(Optional) Access mode VLAN
<i>access_vlan_name</i>	(Optional) Access mode VLAN name
<i>native_vlan</i>	(Optional) Trunking native mode VLAN
<i>native_vlan_name</i>	(Optional) Trunking native mode VLAN name
<i>trunk_vlans</i>	(Optional) Trunking VLANs Allowed
<i>fabricpath_topologies</i>	(Optional) FabricPath Topologies Allowed
<i>pruning_vlans</i>	(Optional) Pruning eligible VLANs
<i>voice_vlan</i>	(Optional) Voice VLAN
<i>voice_vlan_name</i>	(Optional) Voice VLAN name

<i>extended_trust</i>	(Optional) Extended Trust
<i>extended_trust_name</i>	(Optional) Extended Trust name
<i>admin_pvlan_pri_assoc</i>	(Optional) Administrative private-vlan primary host-association
<i>admin_pvlan_sec_assoc</i>	(Optional) Administrative private-vlan secondary host-association
<i>admin_pvlan_pri_mapping</i>	(Optional) Administrative private-vlan primary mapping
<i>admin_pvlan_sec_mapping</i>	(Optional) Administrative private-vlan secondary mapping
<i>admin_pvlan_trunk_native</i>	(Optional) Administrative private-vlan trunk native VLAN
<i>admin_pvlan_trunk_encap</i>	(Optional) Administrative private-vlan trunk encapsulation
<i>admin_pvlan_trunk_normal</i>	(Optional) Administrative private-vlan trunk normal VLANs
<i>admin_pvlan_trunk_private</i>	(Optional) Administrative private-vlan trunk private VLANs
<i>oper_pvlan</i>	(Optional) Operational private-vlan
<i>autostate_mode</i>	(Optional) SVI Autostate Exclude Info

Command Mode

- /exec

show interface transceiver

```
show interface <ifid_transceiver> transceiver [ calibrations | details | sprom ] [ __readonly__ TABLE_interface
<interface> [ <sfp> ] [ <qsfp_or_cfp> ] [ <type> ] [ <name> ] [ <partnum> ] [ <rev> ] [ <serialnum> ] [
<nom_bitrate> ] [ <len_9> ] [ <len_9_2> ] [ <len_50> ] [ <len_625> ] [ <len_cu> ] [ <len_50_OM3> ] [
<txcvr_type> ] [ <connector_type> ] [ <bit_encoding> ] [ <protocol_type> ] [ <10gbe_code> ] [
<fiber_type_byte0> ] [ <fiber_type_byte1> ] [ <tx_range> ] [ <ciscoid> ] [ <ciscoid_1> ] [ <cisco_part_number>
] [ <cisco_product_id> ] [ <cisco_vendor_id> ] [ <firmware_version> ] [ <identifier> ] [ <ext_identifier> ] [
<connector> ] [ <infiniband_compliance_code> ] [ <sonet_compliance_code> ] [
<gigabit_ethernet_compliance_code> ] [ <fibre_chan_link_length> ] [ <fibre_chan_trans_technology> ] [
<fibre_chan_trans_tech_reserved> ] [ <fibre_chan_transmission_media> ] [ <fibre_chan_speed> ] [ <encoding>
] [ <br_nominal> ] [ <reserved1> ] [ <length_smf> ] [ <length_om3> ] [ <length_om2> ] [ <length_om1> ]
[ <length_copper> ] [ <length_9u_1> ] [ <length_9u_2> ] [ <length_50u> ] [ <length_60u> ] [ <length_copper>
] [ <reserved3> ] [ <vendor_oui> ] [ <vendor_part_no> ] [ <vendor_revision> ] [ <reserved4> ] [
<check_code_id> ] [ <options> ] [ <br_max> ] [ <br_min> ] [ <vendor_serial_no> ] [ <data_code> ] [
<diagnostic_monitoring_type> ] [ <enhanced_options> ] [ <sff8472compliance> ] [ <check_code_ext> ] [
<vendor_specific_data_id_data> ] [ <temp_slope> ] [ <temp_offset> ] [ <volt_slope> ] [ <volt_offset> ] [
<curr_slope> ] [ <curr_offset> ] [ <tx_pwr_slope> ] [ <tx_pwr_offset> ] [ <rx_pwr_4> ] [ <rx_pwr_3> ] [
<rx_pwr_2> ] [ <rx_pwr_1> ] [ <rx_pwr_0> ] [ TABLE_lane [ <lane_number> ] [ <temperature> ] [
<temp_flag> ] [ <temp_alm_hi> ] [ <temp_alm_lo> ] [ <temp_warn_hi> ] [ <temp_warn_lo> ] [ <voltage>
] [ <volt_flag> ] [ <volt_alm_hi> ] [ <volt_alm_lo> ] [ <volt_warn_hi> ] [ <volt_warn_lo> ] [ <current> ]
[ <current_flag> ] [ <current_alm_hi> ] [ <current_alm_lo> ] [ <current_warn_hi> ] [ <current_warn_lo>
] [ <tx_pwr> ] [ <tx_pwr_flag> ] [ <tx_pwr_alm_hi> ] [ <tx_pwr_alm_lo> ] [ <tx_pwr_warn_hi> ] [
<tx_pwr_warn_lo> ] [ <rx_pwr> ] [ <rx_pwr_flag> ] [ <rx_pwr_alm_hi> ] [ <rx_pwr_alm_lo> ] [
<rx_pwr_warn_hi> ] [ <rx_pwr_warn_lo> ] [ <xmit_faults> ] [ <snr> ] [ <snr_flag> ] [ <snr_alm_hi> ] [
<snr_alm_lo> ] [ <snr_warn_hi> ] [ <snr_warn_lo> ] [ <isi> ] [ <isi_flag> ] [ <isi_alm_hi> ] [ <isi_alm_lo>
] [ <isi_warn_hi> ] [ <isi_warn_lo> ] [ <pam> ] [ <pam_flag> ] [ <pam_alm_hi> ] [ <pam_alm_lo> ] [
<pam_warn_hi> ] [ <pam_warn_lo> ] [ <pre_fec_ber> ] [ <pre_fec_ber_flag> ] [ <pre_fec_ber_alm_hi> ] [
<pre_fec_ber_alm_lo> ] [ <pre_fec_ber_warn_hi> ] [ <pre_fec_ber_warn_lo> ] [ <uncorrect_ber> ] [
<uncorrect_ber_flag> ] [ <uncorrect_ber_alm_hi> ] [ <uncorrect_ber_alm_lo> ] [ <uncorrect_ber_warn_hi>
] [ <uncorrect_ber_warn_lo> ] [ <tec_current> ] [ <tec_current_flag> ] [ <tec_current_alm_hi> ] [
<tec_current_alm_lo> ] [ <tec_current_warn_hi> ] [ <tec_current_warn_lo> ] [ <laser_freq> ] [
<laser_freq_flag> ] [ <laser_freq_alm_hi> ] [ <laser_freq_alm_lo> ] [ <laser_freq_warn_hi> ] [
<laser_freq_warn_lo> ] [ <laser_temp> ] [ <laser_temp_flag> ] [ <laser_temp_alm_hi> ] [
<laser_temp_alm_lo> ] [ <laser_temp_warn_hi> ] [ <laser_temp_warn_lo> ] [ <pre_fec_ber_acc> ] [
<pre_fec_ber_acc_flag> ] [ <pre_fec_ber_acc_alm_hi> ] [ <pre_fec_ber_acc_alm_lo> ] [
<pre_fec_ber_acc_warn_hi> ] [ <pre_fec_ber_acc_warn_lo> ] [ <pre_fec_ber_min> ] [ <pre_fec_ber_min_flag>
] [ <pre_fec_ber_min_alm_hi> ] [ <pre_fec_ber_min_alm_lo> ] [ <pre_fec_ber_min_warn_hi> ] [
<pre_fec_ber_min_warn_lo> ] [ <pre_fec_ber_max> ] [ <pre_fec_ber_max_flag> ] [
<pre_fec_ber_max_alm_hi> ] [ <pre_fec_ber_max_alm_lo> ] [ <pre_fec_ber_max_warn_hi> ] [
<pre_fec_ber_max_warn_lo> ] [ <pre_fec_ber_cur> ] [ <pre_fec_ber_cur_flag> ] [ <pre_fec_ber_cur_alm_hi>
] [ <pre_fec_ber_cur_alm_lo> ] [ <pre_fec_ber_cur_warn_hi> ] [ <pre_fec_ber_cur_warn_lo> ] [
<uncorrect_ber_acc> ] [ <uncorrect_ber_acc_flag> ] [ <uncorrect_ber_acc_alm_hi> ] [
<uncorrect_ber_acc_alm_lo> ] [ <uncorrect_ber_acc_warn_hi> ] [ <uncorrect_ber_acc_warn_lo> ] [
<uncorrect_ber_min> ] [ <uncorrect_ber_min_flag> ] [ <uncorrect_ber_min_alm_hi> ] [
<uncorrect_ber_min_alm_lo> ] [ <uncorrect_ber_min_warn_hi> ] [ <uncorrect_ber_min_warn_lo> ] [
<uncorrect_ber_max> ] [ <uncorrect_ber_max_flag> ] [ <uncorrect_ber_max_alm_hi> ] [
<uncorrect_ber_max_alm_lo> ] [ <uncorrect_ber_max_warn_hi> ] [ <uncorrect_ber_max_warn_lo> ] [
<uncorrect_ber_cur> ] [ <uncorrect_ber_cur_flag> ] [ <uncorrect_ber_cur_alm_hi> ] [
<uncorrect_ber_cur_alm_lo> ] [ <uncorrect_ber_cur_warn_hi> ] [ <uncorrect_ber_cur_warn_lo> ] ] ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifid_transceiver</i>	Enter interface type and number in module/slot format
transceiver	Show interface transceiver information
calibrations	(Optional) Show interface transceiver calibration information
details	(Optional) Show interface transceiver detail information
sprom	(Optional) Show interface transceiver sprom information
__readonly__	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
TABLE_interface	(Optional) show interface
<i>sfp</i>	(Optional) sfp
<i>qsfp_or_cfp</i>	(Optional) qsfp_or_cfp
<i>type</i>	(Optional) type
<i>name</i>	(Optional) Name
<i>partnum</i>	(Optional) part number
<i>rev</i>	(Optional) revision
<i>serialnum</i>	(Optional) serial number
<i>nom_bitrate</i>	(Optional) Nominal bit rate in MBits/sec
<i>len_9</i>	(Optional) Link length supported for 9/125um fiber in Km
<i>len_9_2</i>	(Optional) Link length supported for 9/125um fiber in m
<i>len_50</i>	(Optional) Link length supported for 50/125um fiber in m
<i>len_625</i>	(Optional) Link length supported for 62.5/125um fiber in m
<i>len_cu</i>	(Optional) Link length supported for copper sfp in m
<i>len_50_OM3</i>	(Optional) Link length supported for 50/125um fiber in m
<i>txcvr_type</i>	(Optional)
<i>connector_type</i>	(Optional)
<i>bit_encoding</i>	(Optional)
<i>protocol_type</i>	(Optional)

<i>l0gbe_code</i>	(Optional)
<i>fiber_type_byte0</i>	(Optional)
<i>fiber_type_byte1</i>	(Optional)
<i>tx_range</i>	(Optional)
<i>ciscoid</i>	(Optional) Cisco extended id
<i>ciscoid_1</i>	(Optional) Cisco extended id number
<i>cisco_part_number</i>	(Optional) Cisco part number
<i>cisco_product_id</i>	(Optional) Cisco product identifier
<i>cisco_vendor_id</i>	(Optional) Cisco vendor identifier
<i>firmware_version</i>	(Optional) Firmware version
<i>identifier</i>	(Optional) SFP Identifier
<i>ext_identifier</i>	(Optional) SFP Ext Identifier
<i>connector</i>	(Optional) SFP connector
<i>infiniband_compliance_code</i>	(Optional) SFP Infiniband Compliance Code
<i>sonet_compliance_code</i>	(Optional) Sonet Compliance Code
<i>gigabit_ethernet_compliance_code</i>	(Optional) Gigabit Ethernet Compliance Code
<i>fibre_chan_link_length</i>	(Optional) Fibre Chan Link Length
<i>fibre_chan_trans_technology</i>	(Optional) Fibre Chan Trans Technology
<i>fibre_chan_trans_tech_reserved</i>	(Optional) Fibre Chan Trans Tech Reserved
<i>fibre_chan_transmission_media</i>	(Optional) Fibre Chan Transmission Media
<i>fibre_chan_speed</i>	(Optional) Fibre Chan Speed
<i>encoding</i>	(Optional) Encoding
<i>br_nominal</i>	(Optional) BR Nominal
<i>reserved1</i>	(Optional) Reserved1
<i>length_smf</i>	(Optional) Length_SMF
<i>length_om3</i>	(Optional) Length_OM3
<i>length_om2</i>	(Optional) Length_OM2
<i>length_om1</i>	(Optional) Length_OM1
<i>length_copper</i>	(Optional) Length_Copper

<i>length_9u_1</i>	(Optional) Length 9u 1
<i>length_9u_2</i>	(Optional) Length 9u 2
<i>length_50u</i>	(Optional) Length 50u
<i>length_60u</i>	(Optional) Length 60u
<i>length_copper</i>	(Optional) Length Copper
<i>reserved3</i>	(Optional) Reserved3
<i>vendor_oui</i>	(Optional) Vendor OUI
<i>vendor_part_no</i>	(Optional) Vendor Part No
<i>vendor_revision</i>	(Optional) Vendor Revision
<i>reserved4</i>	(Optional) Reserved4
<i>check_code_id</i>	(Optional) Check Code ID
<i>options</i>	(Optional) Options
<i>br_max</i>	(Optional) BR max
<i>br_min</i>	(Optional) BR min
<i>vendor_serial_no</i>	(Optional) Vendor Serial No
<i>data_code</i>	(Optional) Data code
<i>diagnostic_monitoring_type</i>	(Optional) Diagnostic Monitoring Type
<i>enhanced_options</i>	(Optional) Enhanced Options
<i>sff8472compliance</i>	(Optional) SFF8472Compliance
<i>check_code_ext</i>	(Optional) Check code ext
<i>vendor_specific_data_id_data</i>	(Optional) Vendor Specific Data Id Data
<i>temp_slope</i>	(Optional) Temperature slope
<i>temp_offset</i>	(Optional) Temperature offset
<i>volt_slope</i>	(Optional) Voltage slope
<i>volt_offset</i>	(Optional) Voltage offset
<i>curr_slope</i>	(Optional) Current slope
<i>curr_offset</i>	(Optional) Current offset
<i>tx_pwr_slope</i>	(Optional) Tx power slope
<i>tx_pwr_offset</i>	(Optional) Tx power offset

<i>rx_pwr_4</i>	(Optional) Rx power 4
<i>rx_pwr_3</i>	(Optional) Rx power 3
<i>rx_pwr_2</i>	(Optional) Rx power 2
<i>rx_pwr_1</i>	(Optional) Rx power 1
<i>rx_pwr_0</i>	(Optional) Rx power 0
TABLE_lane	(Optional) show lane
<i>lane_number</i>	(Optional) Lane number
<i>temperature</i>	(Optional) Temperature
<i>temp_flag</i>	(Optional) Temperature Flag
<i>temp_alrm_hi</i>	(Optional) Temperature Alarm High
<i>temp_alrm_lo</i>	(Optional) Temperature Alarm Low
<i>temp_warn_hi</i>	(Optional) Temperature Warning High
<i>temp_warn_lo</i>	(Optional) Temperature Warning Low
<i>voltage</i>	(Optional) Voltage
<i>volt_flag</i>	(Optional) Voltage Flag
<i>volt_alrm_hi</i>	(Optional) Voltage Alarm High
<i>volt_alrm_lo</i>	(Optional) Voltage Alarm Low
<i>volt_warn_hi</i>	(Optional) Voltage Warning High
<i>volt_warn_lo</i>	(Optional) Voltage Warning Low
<i>current</i>	(Optional) Current
<i>current_flag</i>	(Optional) Current Flag
<i>current_alrm_hi</i>	(Optional) Current Alarm High
<i>current_alrm_lo</i>	(Optional) Current Alarm Low
<i>current_warn_hi</i>	(Optional) Current Warning High
<i>current_warn_lo</i>	(Optional) Current Warning Low
<i>tx_pwr</i>	(Optional) Tx Power
<i>tx_pwr_flag</i>	(Optional) Tx Power Flag
<i>tx_pwr_alrm_hi</i>	(Optional) Tx Power Alarm High
<i>tx_pwr_alrm_lo</i>	(Optional) Tx Power Alarm Low

<i>tx_pwr_warn_hi</i>	(Optional) Tx Power Warning High
<i>tx_pwr_warn_lo</i>	(Optional) Tx Power Warning Low
<i>rx_pwr</i>	(Optional) Rx Power
<i>rx_pwr_flag</i>	(Optional) Rx Power Flag
<i>rx_pwr_alrm_hi</i>	(Optional) Rx Power Alarm High
<i>rx_pwr_alrm_lo</i>	(Optional) Rx Power Alarm Low
<i>rx_pwr_warn_hi</i>	(Optional) Rx Power Warning High
<i>rx_pwr_warn_lo</i>	(Optional) Rx Power Warning Low
<i>xmit_faults</i>	(Optional) Transmit Fault Count
<i>snr</i>	(Optional) RX Signal-to-Noise Ratio (SNR)
<i>snr_flag</i>	(Optional) SNR Flag
<i>snr_alrm_hi</i>	(Optional) SNR Alarm High
<i>snr_alrm_lo</i>	(Optional) SNR Alarm Low
<i>snr_warn_hi</i>	(Optional) SNR Warning High
<i>snr_warn_lo</i>	(Optional) SNR Warning Low
<i>isi</i>	(Optional) Residual-Dispersion(ISI)
<i>isi_flag</i>	(Optional) ISI Flag
<i>isi_alrm_hi</i>	(Optional) ISI alarm high
<i>isi_alrm_lo</i>	(Optional) ISI alarm low
<i>isi_warn_hi</i>	(Optional) ISI warning high
<i>isi_warn_lo</i>	(Optional) ISI warning low
<i>pam</i>	(Optional) PAM Transition
<i>pam_flag</i>	(Optional) PAM Flag
<i>pam_alrm_hi</i>	(Optional) PAM alarm high
<i>pam_alrm_lo</i>	(Optional) PAM alarm low
<i>pam_warn_hi</i>	(Optional) PAM warning high
<i>pam_warn_lo</i>	(Optional) PAM warning low
<i>pre_fec_ber</i>	(Optional) Pre-FEC BER
<i>pre_fec_ber_flag</i>	(Optional) Pre-FEC BER flag

<i>pre_fec_ber_alm_hi</i>	(Optional) Pre-FEC BER alarm high
<i>pre_fec_ber_alm_lo</i>	(Optional) Pre-FEC BER alarm low
<i>pre_fec_ber_warn_hi</i>	(Optional) Pre-FEC BER warning high
<i>pre_fec_ber_warn_lo</i>	(Optional) Pre-FEC BER warning low
<i>uncorrect_ber</i>	(Optional) Uncorrected BER
<i>uncorrect_ber_flag</i>	(Optional) Uncorrected BER flag
<i>uncorrect_ber_alm_hi</i>	(Optional) Uncorrected BER alarm high
<i>uncorrect_ber_alm_lo</i>	(Optional) Uncorrected BER alarm low
<i>uncorrect_ber_warn_hi</i>	(Optional) Uncorrected BER warning high
<i>uncorrect_ber_warn_lo</i>	(Optional) Uncorrected BER warning low
<i>tec_current</i>	(Optional) TEC Current
<i>tec_current_flag</i>	(Optional) TEC Current flag
<i>tec_current_alm_hi</i>	(Optional) TEC Current Alarm High
<i>tec_current_alm_lo</i>	(Optional) TEC Current Alarm Low
<i>tec_current_warn_hi</i>	(Optional) TEC Current Warning High
<i>tec_current_warn_lo</i>	(Optional) TEC Current Warning Low
<i>laser_freq</i>	(Optional) Laser Frequency
<i>laser_freq_flag</i>	(Optional) Laser Frequency flag
<i>laser_freq_alm_hi</i>	(Optional) Laser Frequency Alarm High
<i>laser_freq_alm_lo</i>	(Optional) Laser Frequency Alarm Low
<i>laser_freq_warn_hi</i>	(Optional) Laser Frequency Warning High
<i>laser_freq_warn_lo</i>	(Optional) Laser Frequency Warning Low
<i>laser_temp</i>	(Optional) Laser Temperature
<i>laser_temp_flag</i>	(Optional) Laser Temperature flag
<i>laser_temp_alm_hi</i>	(Optional) Laser Temperature Alarm High
<i>laser_temp_alm_lo</i>	(Optional) Laser Temperature Alarm Low
<i>laser_temp_warn_hi</i>	(Optional) Laser Temperature Warning High
<i>laser_temp_warn_lo</i>	(Optional) Laser Temperature Warning Low
<i>pre_fec_ber_acc</i>	(Optional) Pre-FEC BER Acc

<i>pre_fec_ber_acc_flag</i>	(Optional) Pre-FEC BER Acc flag
<i>pre_fec_ber_acc_alrm_hi</i>	(Optional) Pre-FEC BER Acc alarm high
<i>pre_fec_ber_acc_alrm_lo</i>	(Optional) Pre-FEC BER Acc alarm low
<i>pre_fec_ber_acc_warn_hi</i>	(Optional) Pre-FEC BER Acc warning high
<i>pre_fec_ber_acc_warn_lo</i>	(Optional) Pre-FEC BER Acc warning low
<i>pre_fec_ber_min</i>	(Optional) Pre-FEC BER Min
<i>pre_fec_ber_min_flag</i>	(Optional) Pre-FEC BER Min flag
<i>pre_fec_ber_min_alrm_hi</i>	(Optional) Pre-FEC BER Min alarm high
<i>pre_fec_ber_min_alrm_lo</i>	(Optional) Pre-FEC BER Min alarm low
<i>pre_fec_ber_min_warn_hi</i>	(Optional) Pre-FEC BER Min warning high
<i>pre_fec_ber_min_warn_lo</i>	(Optional) Pre-FEC BER Min warning low
<i>pre_fec_ber_max</i>	(Optional) Pre-FEC BER Max
<i>pre_fec_ber_max_flag</i>	(Optional) Pre-FEC BER Max flag
<i>pre_fec_ber_max_alrm_hi</i>	(Optional) Pre-FEC BER Max alarm high
<i>pre_fec_ber_max_alrm_lo</i>	(Optional) Pre-FEC BER Max alarm low
<i>pre_fec_ber_max_warn_hi</i>	(Optional) Pre-FEC BER Max warning high
<i>pre_fec_ber_max_warn_lo</i>	(Optional) Pre-FEC BER Max warning low
<i>pre_fec_ber_cur</i>	(Optional) Pre-FEC BER Cur
<i>pre_fec_ber_cur_flag</i>	(Optional) Pre-FEC BER Cur flag
<i>pre_fec_ber_cur_alrm_hi</i>	(Optional) Pre-FEC BER Cur alarm high
<i>pre_fec_ber_cur_alrm_lo</i>	(Optional) Pre-FEC BER Cur alarm low
<i>pre_fec_ber_cur_warn_hi</i>	(Optional) Pre-FEC BER Cur warning high
<i>pre_fec_ber_cur_warn_lo</i>	(Optional) Pre-FEC BER Cur warning low
<i>uncorrect_ber_acc</i>	(Optional) Uncorrected BER Acc
<i>uncorrect_ber_acc_flag</i>	(Optional) Uncorrected BER Acc flag
<i>uncorrect_ber_acc_alrm_hi</i>	(Optional) Uncorrected BER Acc alarm high
<i>uncorrect_ber_acc_alrm_lo</i>	(Optional) Uncorrected BER Acc alarm low
<i>uncorrect_ber_acc_warn_hi</i>	(Optional) Uncorrected BER Acc warning high
<i>uncorrect_ber_acc_warn_lo</i>	(Optional) Uncorrected BER Acc warning low

<i>uncorrect_ber_min</i>	(Optional) Uncorrected BER Min
<i>uncorrect_ber_min_flag</i>	(Optional) Uncorrected BER Min flag
<i>uncorrect_ber_min_alrm_hi</i>	(Optional) Uncorrected BER Min alarm high
<i>uncorrect_ber_min_alrm_lo</i>	(Optional) Uncorrected BER Min alarm low
<i>uncorrect_ber_min_warn_hi</i>	(Optional) Uncorrected BER Min warning high
<i>uncorrect_ber_min_warn_lo</i>	(Optional) Uncorrected BER Min warning low
<i>uncorrect_ber_max</i>	(Optional) Uncorrected BER Max
<i>uncorrect_ber_max_flag</i>	(Optional) Uncorrected BER Max flag
<i>uncorrect_ber_max_alrm_hi</i>	(Optional) Uncorrected BER Max alarm high
<i>uncorrect_ber_max_alrm_lo</i>	(Optional) Uncorrected BER Max alarm low
<i>uncorrect_ber_max_warn_hi</i>	(Optional) Uncorrected BER Max warning high
<i>uncorrect_ber_max_warn_lo</i>	(Optional) Uncorrected BER Max warning low
<i>uncorrect_ber_cur</i>	(Optional) Uncorrected BER Cur
<i>uncorrect_ber_cur_flag</i>	(Optional) Uncorrected BER Cur flag
<i>uncorrect_ber_cur_alrm_hi</i>	(Optional) Uncorrected BER Cur alarm high
<i>uncorrect_ber_cur_alrm_lo</i>	(Optional) Uncorrected BER Cur alarm low
<i>uncorrect_ber_cur_warn_hi</i>	(Optional) Uncorrected BER Cur warning high
<i>uncorrect_ber_cur_warn_lo</i>	(Optional) Uncorrected BER Cur warning low

Command Mode

- /exec

show interface transceiver

```
show interface transceiver [ calibrations | details | inventory ] [ __readonly__ TABLE_interface <interface>
[ <sfp> ] [ <type> ] [ <name> ] [ <partnum> ] [ <rev> ] [ <serialnum> ] [ <nom_bitrate> ] [ <len_9> ] [
<len_50> ] [ <len_625> ] [ <len_cu> ] [ <len_50_OM3> ] [ <txcvr_type> ] [ <connector_type> ] [
<bit_encoding> ] [ <protocol_type> ] [ <10gbe_code> ] [ <fiber_type_byte0> ] [ <fiber_type_byte1> ] [
<tx_range> ] [ <ciscoid> ] [ <ciscoid_1> ] [ <cisco_part_number> ] [ <cisco_product_id> ] [ <cisco_vendor_id> ]
] [ <temp_slope> ] [ <temp_offset> ] [ <volt_slope> ] [ <volt_offset> ] [ <curr_slope> ] [ <curr_offset> ] [
<tx_pwr_slope> ] [ <tx_pwr_offset> ] [ <rx_pwr_4> ] [ <rx_pwr_3> ] [ <rx_pwr_2> ] [ <rx_pwr_1> ] [
<rx_pwr_0> ] [ TABLE_lane [ <lane_number> ] [ <temperature> ] [ <temp_flag> ] [ <temp_alm_hi> ] [
<temp_alm_lo> ] [ <temp_warn_hi> ] [ <temp_warn_lo> ] [ <voltage> ] [ <volt_flag> ] [ <volt_alm_hi> ] [
<volt_alm_lo> ] [ <volt_warn_hi> ] [ <volt_warn_lo> ] [ <current> ] [ <current_flag> ] [ <current_alm_hi> ]
] [ <current_alm_lo> ] [ <current_warn_hi> ] [ <current_warn_lo> ] [ <tx_pwr> ] [ <tx_pwr_flag> ] [
<tx_pwr_alm_hi> ] [ <tx_pwr_alm_lo> ] [ <tx_pwr_warn_hi> ] [ <tx_pwr_warn_lo> ] [ <rx_pwr> ] [
<rx_pwr_flag> ] [ <rx_pwr_alm_hi> ] [ <rx_pwr_alm_lo> ] [ <rx_pwr_warn_hi> ] [ <rx_pwr_warn_lo> ]
] [ <xmit_faults> ] [ <snr> ] [ <snr_flag> ] [ <snr_alm_hi> ] [ <snr_alm_lo> ] [ <snr_warn_hi> ] [
<snr_warn_lo> ] [ <isi> ] [ <isi_flag> ] [ <isi_alm_hi> ] [ <isi_alm_lo> ] [ <isi_warn_hi> ] [ <isi_warn_lo> ]
] [ <pam> ] [ <pam_flag> ] [ <pam_alm_hi> ] [ <pam_alm_lo> ] [ <pam_warn_hi> ] [ <pam_warn_lo> ] [
<pre_fec_ber> ] [ <pre_fec_ber_flag> ] [ <pre_fec_ber_alm_hi> ] [ <pre_fec_ber_alm_lo> ] [
<pre_fec_ber_warn_hi> ] [ <pre_fec_ber_warn_lo> ] [ <uncorrect_ber> ] [ <uncorrect_ber_flag> ] [
<uncorrect_ber_alm_hi> ] [ <uncorrect_ber_alm_lo> ] [ <uncorrect_ber_warn_hi> ] [
<uncorrect_ber_warn_lo> ] [ <tec_current> ] [ <tec_current_flag> ] [ <tec_current_alm_hi> ] [
<tec_current_alm_lo> ] [ <tec_current_warn_hi> ] [ <tec_current_warn_lo> ] [ <laser_freq> ] [
<laser_freq_flag> ] [ <laser_freq_alm_hi> ] [ <laser_freq_alm_lo> ] [ <laser_freq_warn_hi> ] [
<laser_freq_warn_lo> ] [ <laser_temp> ] [ <laser_temp_flag> ] [ <laser_temp_alm_hi> ] [
<laser_temp_alm_lo> ] [ <laser_temp_warn_hi> ] [ <laser_temp_warn_lo> ] [ <pre_fec_ber_acc> ] [
<pre_fec_ber_acc_flag> ] [ <pre_fec_ber_acc_alm_hi> ] [ <pre_fec_ber_acc_alm_lo> ] [
<pre_fec_ber_acc_warn_hi> ] [ <pre_fec_ber_acc_warn_lo> ] [ <pre_fec_ber_min> ] [ <pre_fec_ber_min_flag> ]
] [ <pre_fec_ber_min_alm_hi> ] [ <pre_fec_ber_min_alm_lo> ] [ <pre_fec_ber_min_warn_hi> ] [
<pre_fec_ber_min_warn_lo> ] [ <pre_fec_ber_max> ] [ <pre_fec_ber_max_flag> ] [
<pre_fec_ber_max_alm_hi> ] [ <pre_fec_ber_max_alm_lo> ] [ <pre_fec_ber_max_warn_hi> ] [
<pre_fec_ber_max_warn_lo> ] [ <pre_fec_ber_cur> ] [ <pre_fec_ber_cur_flag> ] [ <pre_fec_ber_cur_alm_hi> ]
] [ <pre_fec_ber_cur_alm_lo> ] [ <pre_fec_ber_cur_warn_hi> ] [ <pre_fec_ber_cur_warn_lo> ] [
<uncorrect_ber_acc> ] [ <uncorrect_ber_acc_flag> ] [ <uncorrect_ber_acc_alm_hi> ] [
<uncorrect_ber_acc_alm_lo> ] [ <uncorrect_ber_acc_warn_hi> ] [ <uncorrect_ber_acc_warn_lo> ] [
<uncorrect_ber_min> ] [ <uncorrect_ber_min_flag> ] [ <uncorrect_ber_min_alm_hi> ] [
<uncorrect_ber_min_alm_lo> ] [ <uncorrect_ber_min_warn_hi> ] [ <uncorrect_ber_min_warn_lo> ] [
<uncorrect_ber_max> ] [ <uncorrect_ber_max_flag> ] [ <uncorrect_ber_max_alm_hi> ] [
<uncorrect_ber_max_alm_lo> ] [ <uncorrect_ber_max_warn_hi> ] [ <uncorrect_ber_max_warn_lo> ] [
<uncorrect_ber_cur> ] [ <uncorrect_ber_cur_flag> ] [ <uncorrect_ber_cur_alm_hi> ] [
<uncorrect_ber_cur_alm_lo> ] [ <uncorrect_ber_cur_warn_hi> ] [ <uncorrect_ber_cur_warn_lo> ] ] ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
transceiver	Show interface transceiver information
calibrations	(Optional) Show interface transceiver calibration information

<i>details</i>	(Optional) Show interface transceiver detail information
<i>inventory</i>	(Optional) Show interface transceiver inventory
<i>__readonly__</i>	(Optional) Read Only
<i>interface</i>	(Optional) Interface index
<i>TABLE_interface</i>	(Optional) show interface
<i>sfp</i>	(Optional) sfp
<i>type</i>	(Optional) type
<i>name</i>	(Optional) Name
<i>partnum</i>	(Optional) part number
<i>rev</i>	(Optional) revision
<i>serialnum</i>	(Optional) serial number
<i>nom_bitrate</i>	(Optional) Nominal bit rate in MBits/sec
<i>len_9</i>	(Optional) Link length supported for 9/125um fiber
<i>len_50</i>	(Optional) Link length supported for 50/125um fiber
<i>len_625</i>	(Optional) Link length supported for 62.5/125um fiber
<i>len_cu</i>	(Optional) Link length supported for copper
<i>len_50_OM3</i>	(Optional) Link length supported for 50/125um fiber in m
<i>txcvr_type</i>	(Optional)
<i>connector_type</i>	(Optional)
<i>bit_encoding</i>	(Optional)
<i>protocol_type</i>	(Optional)
<i>10gbe_code</i>	(Optional)
<i>fiber_type_byte0</i>	(Optional)
<i>fiber_type_byte1</i>	(Optional)
<i>tx_range</i>	(Optional)
<i>ciscoid</i>	(Optional) Cisco extended id
<i>ciscoid_1</i>	(Optional) Cisco extended id number
<i>cisco_part_number</i>	(Optional) Cisco part number
<i>cisco_product_id</i>	(Optional) Cisco product identifier

<i>cisco_vendor_id</i>	(Optional) Cisco vendor identifier
<i>temp_slope</i>	(Optional) Temperature slope
<i>temp_offset</i>	(Optional) Temperature offset
<i>volt_slope</i>	(Optional) Voltage slope
<i>volt_offset</i>	(Optional) Voltage offset
<i>curr_slope</i>	(Optional) Current slope
<i>curr_offset</i>	(Optional) Current offset
<i>tx_pwr_slope</i>	(Optional) Tx power slope
<i>tx_pwr_offset</i>	(Optional) Tx power offset
<i>rx_pwr_4</i>	(Optional) Rx power 4
<i>rx_pwr_3</i>	(Optional) Rx power 3
<i>rx_pwr_2</i>	(Optional) Rx power 2
<i>rx_pwr_1</i>	(Optional) Rx power 1
<i>rx_pwr_0</i>	(Optional) Rx power 0
TABLE_lane	(Optional) show lane
<i>lane_number</i>	(Optional) Lane number
<i>temperature</i>	(Optional) Temperature
<i>temp_flag</i>	(Optional) Temperature Flag
<i>temp_alrm_hi</i>	(Optional) Temperature Alarm High
<i>temp_alrm_lo</i>	(Optional) Temperature Alarm Low
<i>temp_warn_hi</i>	(Optional) Temperature Warning High
<i>temp_warn_lo</i>	(Optional) Temperature Warning Low
<i>voltage</i>	(Optional) Voltage
<i>volt_flag</i>	(Optional) Voltage Flag
<i>volt_alrm_hi</i>	(Optional) Voltage Alarm High
<i>volt_alrm_lo</i>	(Optional) Voltage Alarm Low
<i>volt_warn_hi</i>	(Optional) Voltage Warning High
<i>volt_warn_lo</i>	(Optional) Voltage Warning Low
<i>current</i>	(Optional) Current

<i>current_flag</i>	(Optional) Current Flag
<i>current_alm_hi</i>	(Optional) Current Alarm High
<i>current_alm_lo</i>	(Optional) Current Alarm Low
<i>current_warn_hi</i>	(Optional) Current Warning High
<i>current_warn_lo</i>	(Optional) Current Warning Low
<i>tx_pwr</i>	(Optional) Tx Power
<i>tx_pwr_flag</i>	(Optional) Tx Power Flag
<i>tx_pwr_alm_hi</i>	(Optional) Tx Power Alarm High
<i>tx_pwr_alm_lo</i>	(Optional) Tx Power Alarm Low
<i>tx_pwr_warn_hi</i>	(Optional) Tx Power Warning High
<i>tx_pwr_warn_lo</i>	(Optional) Tx Power Warning Low
<i>rx_pwr</i>	(Optional) Rx Power
<i>rx_pwr_flag</i>	(Optional) Rx Power Flag
<i>rx_pwr_alm_hi</i>	(Optional) Rx Power Alarm High
<i>rx_pwr_alm_lo</i>	(Optional) Rx Power Alarm Low
<i>rx_pwr_warn_hi</i>	(Optional) Rx Power Warning High
<i>rx_pwr_warn_lo</i>	(Optional) Rx Power Warning Low
<i>xmit_faults</i>	(Optional) Transmit Fault Count
<i>snr</i>	(Optional) RX Signal-to-Noise Ratio (SNR)
<i>snr_flag</i>	(Optional) SNR Flag
<i>snr_alm_hi</i>	(Optional) SNR Alarm High
<i>snr_alm_lo</i>	(Optional) SNR Alarm Low
<i>snr_warn_hi</i>	(Optional) SNR Warning High
<i>snr_warn_lo</i>	(Optional) SNR Warning Low
<i>isi</i>	(Optional) Residual-Dispersion(ISI)
<i>isi_flag</i>	(Optional) ISI Flag
<i>isi_alm_hi</i>	(Optional) ISI alarm high
<i>isi_alm_lo</i>	(Optional) ISI alarm low
<i>isi_warn_hi</i>	(Optional) ISI warning high

<i>isi_warn_lo</i>	(Optional) ISI warning low
<i>pam</i>	(Optional) PAM Transition
<i>pam_flag</i>	(Optional) PAM Flag
<i>pam_alrm_hi</i>	(Optional) PAM alarm high
<i>pam_alrm_lo</i>	(Optional) PAM alarm low
<i>pam_warn_hi</i>	(Optional) PAM warning high
<i>pam_warn_lo</i>	(Optional) PAM warning low
<i>pre_fec_ber</i>	(Optional) Pre-FEC BER
<i>pre_fec_ber_flag</i>	(Optional) Pre-FEC BER flag
<i>pre_fec_ber_alrm_hi</i>	(Optional) Pre-FEC BER alarm high
<i>pre_fec_ber_alrm_lo</i>	(Optional) Pre-FEC BER alarm low
<i>pre_fec_ber_warn_hi</i>	(Optional) Pre-FEC BER warning high
<i>pre_fec_ber_warn_lo</i>	(Optional) Pre-FEC BER warning low
<i>uncorrect_ber</i>	(Optional) Uncorrected BER
<i>uncorrect_ber_flag</i>	(Optional) Uncorrected BER flag
<i>uncorrect_ber_alrm_hi</i>	(Optional) Uncorrected BER alarm high
<i>uncorrect_ber_alrm_lo</i>	(Optional) Uncorrected BER alarm low
<i>uncorrect_ber_warn_hi</i>	(Optional) Uncorrected BER warning high
<i>uncorrect_ber_warn_lo</i>	(Optional) Uncorrected BER warning low
<i>tec_current</i>	(Optional) TEC Current
<i>tec_current_flag</i>	(Optional) TEC Current flag
<i>tec_current_alrm_hi</i>	(Optional) TEC Current Alarm High
<i>tec_current_alrm_lo</i>	(Optional) TEC Current Alarm Low
<i>tec_current_warn_hi</i>	(Optional) TEC Current Warning High
<i>tec_current_warn_lo</i>	(Optional) TEC Current Warning Low
<i>laser_freq</i>	(Optional) Laser Frequency
<i>laser_freq_flag</i>	(Optional) Laser Frequency flag
<i>laser_freq_alrm_hi</i>	(Optional) Laser Frequency Alarm High
<i>laser_freq_alrm_lo</i>	(Optional) Laser Frequency Alarm Low

<i>laser_freq_warn_hi</i>	(Optional) Laser Frequency Warning High
<i>laser_freq_warn_lo</i>	(Optional) Laser Frequency Warning Low
<i>laser_temp</i>	(Optional) Laser Temperature
<i>laser_temp_flag</i>	(Optional) Laser Temperature flag
<i>laser_temp_alrm_hi</i>	(Optional) Laser Temperature Alarm High
<i>laser_temp_alrm_lo</i>	(Optional) Laser Temperature Alarm Low
<i>laser_temp_warn_hi</i>	(Optional) Laser Temperature Warning High
<i>laser_temp_warn_lo</i>	(Optional) Laser Temperature Warning Low
<i>pre_fec_ber_acc</i>	(Optional) Pre-FEC BER Acc
<i>pre_fec_ber_acc_flag</i>	(Optional) Pre-FEC BER Acc flag
<i>pre_fec_ber_acc_alrm_hi</i>	(Optional) Pre-FEC BER Acc alarm high
<i>pre_fec_ber_acc_alrm_lo</i>	(Optional) Pre-FEC BER Acc alarm low
<i>pre_fec_ber_acc_warn_hi</i>	(Optional) Pre-FEC BER Acc warning high
<i>pre_fec_ber_acc_warn_lo</i>	(Optional) Pre-FEC BER Acc warning low
<i>pre_fec_ber_min</i>	(Optional) Pre-FEC BER Min
<i>pre_fec_ber_min_flag</i>	(Optional) Pre-FEC BER Min flag
<i>pre_fec_ber_min_alrm_hi</i>	(Optional) Pre-FEC BER Min alarm high
<i>pre_fec_ber_min_alrm_lo</i>	(Optional) Pre-FEC BER Min alarm low
<i>pre_fec_ber_min_warn_hi</i>	(Optional) Pre-FEC BER Min warning high
<i>pre_fec_ber_min_warn_lo</i>	(Optional) Pre-FEC BER Min warning low
<i>pre_fec_ber_max</i>	(Optional) Pre-FEC BER Max
<i>pre_fec_ber_max_flag</i>	(Optional) Pre-FEC BER Max flag
<i>pre_fec_ber_max_alrm_hi</i>	(Optional) Pre-FEC BER Max alarm high
<i>pre_fec_ber_max_alrm_lo</i>	(Optional) Pre-FEC BER Max alarm low
<i>pre_fec_ber_max_warn_hi</i>	(Optional) Pre-FEC BER Max warning high
<i>pre_fec_ber_max_warn_lo</i>	(Optional) Pre-FEC BER Max warning low
<i>pre_fec_ber_cur</i>	(Optional) Pre-FEC BER Cur
<i>pre_fec_ber_cur_flag</i>	(Optional) Pre-FEC BER Cur flag
<i>pre_fec_ber_cur_alrm_hi</i>	(Optional) Pre-FEC BER Cur alarm high

<i>pre_fec_ber_cur_alrm_lo</i>	(Optional) Pre-FEC BER Cur alarm low
<i>pre_fec_ber_cur_warn_hi</i>	(Optional) Pre-FEC BER Cur warning high
<i>pre_fec_ber_cur_warn_lo</i>	(Optional) Pre-FEC BER Cur warning low
<i>uncorrect_ber_acc</i>	(Optional) Uncorrected BER Acc
<i>uncorrect_ber_acc_flag</i>	(Optional) Uncorrected BER Acc flag
<i>uncorrect_ber_acc_alrm_hi</i>	(Optional) Uncorrected BER Acc alarm high
<i>uncorrect_ber_acc_alrm_lo</i>	(Optional) Uncorrected BER Acc alarm low
<i>uncorrect_ber_acc_warn_hi</i>	(Optional) Uncorrected BER Acc warning high
<i>uncorrect_ber_acc_warn_lo</i>	(Optional) Uncorrected BER Acc warning low
<i>uncorrect_ber_min</i>	(Optional) Uncorrected BER Min
<i>uncorrect_ber_min_flag</i>	(Optional) Uncorrected BER Min flag
<i>uncorrect_ber_min_alrm_hi</i>	(Optional) Uncorrected BER Min alarm high
<i>uncorrect_ber_min_alrm_lo</i>	(Optional) Uncorrected BER Min alarm low
<i>uncorrect_ber_min_warn_hi</i>	(Optional) Uncorrected BER Min warning high
<i>uncorrect_ber_min_warn_lo</i>	(Optional) Uncorrected BER Min warning low
<i>uncorrect_ber_max</i>	(Optional) Uncorrected BER Max
<i>uncorrect_ber_max_flag</i>	(Optional) Uncorrected BER Max flag
<i>uncorrect_ber_max_alrm_hi</i>	(Optional) Uncorrected BER Max alarm high
<i>uncorrect_ber_max_alrm_lo</i>	(Optional) Uncorrected BER Max alarm low
<i>uncorrect_ber_max_warn_hi</i>	(Optional) Uncorrected BER Max warning high
<i>uncorrect_ber_max_warn_lo</i>	(Optional) Uncorrected BER Max warning low
<i>uncorrect_ber_cur</i>	(Optional) Uncorrected BER Cur
<i>uncorrect_ber_cur_flag</i>	(Optional) Uncorrected BER Cur flag
<i>uncorrect_ber_cur_alrm_hi</i>	(Optional) Uncorrected BER Cur alarm high
<i>uncorrect_ber_cur_alrm_lo</i>	(Optional) Uncorrected BER Cur alarm low
<i>uncorrect_ber_cur_warn_hi</i>	(Optional) Uncorrected BER Cur warning high
<i>uncorrect_ber_cur_warn_lo</i>	(Optional) Uncorrected BER Cur warning low

Command Mode

- /exec

show interface trunk

```
show interface trunk [ module <module> | vlan <vlan_id> | fex <fex_num> ] [ __readonly__ { TABLE_interface
<interface> <native> <status> <portchannel> } { TABLE_allowed_vlans <interface> <allowedvlans> } {
TABLE_errored_vlans <interface> <erroredvlans> } { TABLE_stp_forward <interface> <stpfdw_vlans> }
[ { TABLE_fabricpath_vlans <interface> <fabricpath_vlans> } ] { TABLE_vtp_pruning <interface>
<vtp pruning_vlans> } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
trunk	Show interface trunk information
module	(Optional) Limit display to interfaces on module
<i>module</i>	(Optional) Enter module number
fex	(Optional) Limit display to interfaces on a FEX
<i>fex_num</i>	(Optional) Enter FEX number
vlan	(Optional) Show per vlan information for trunk
<i>vlan_id</i>	(Optional) Enter vlan range
<i>interface</i>	(Optional) Interface index
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>native</i>	(Optional) Native VLAN
<i>status</i>	(Optional) Status
<i>portchannel</i>	(Optional) Port Channel
TABLE_allowed_vlans	(Optional) show allowed vlans
<i>interface</i>	(Optional) Interface index
<i>allowedvlans</i>	(Optional) VLANs allowed and active in management domain
TABLE_errored_vlans	(Optional) show errored vlans
<i>interface</i>	(Optional) Interface index
<i>erroredvlans</i>	(Optional) Errored VLANs
TABLE_stp_forward	(Optional) show STP forwarding VLANs

<i>interface</i>	(Optional) Interface index
<i>stp fwd_vlans</i>	(Optional) STP Forwarding VLANs
TABLE_fabricpath_vlans	(Optional) show fabricpath VLANs
<i>interface</i>	(Optional) Interface index
<i>fabricpath_vlans</i>	(Optional) FabricPath VLANs
TABLE_vtp_pruning	(Optional) show VTP pruning VLANs
<i>vtp pruning_vlans</i>	(Optional) VTP Pruning VLANs

Command Mode

- /exec

show interface trunk

```
show interface <ifeth_trnk> trunk [ __readonly__ { TABLE_interface <interface> <native> <status>
<portchannel> } { TABLE_allowed_vlans <interface> <allowedvlans> } { TABLE_errored_vlans <interface>
<erroredvlans> } { TABLE_stp_forward <interface> <stp fwd_vlans> } [ { TABLE_fabricpath_vlans
<interface> <fabricpath_vlans> } ] { TABLE_vtp_pruning <interface> <vtp pruning_vlans> } ]
```

Syntax Description

show	Show running system information
interface	Show interface status and information
<i>ifeth_trnk</i>	Enter interface type and number in module/slot format
trunk	Show interface trunk information
__readonly__	(Optional) Read Only
TABLE_interface	(Optional) show interface
<i>interface</i>	(Optional) Interface index
<i>native</i>	(Optional) Native VLAN
<i>status</i>	(Optional) Status
<i>portchannel</i>	(Optional) Port Channel
TABLE_allowed_vlans	(Optional) show allowed vlans
<i>interface</i>	(Optional) Interface index
<i>allowedvlans</i>	(Optional) VLANs allowed and active in management domain
TABLE_errored_vlans	(Optional) show errored vlans
<i>interface</i>	(Optional) Interface index
<i>erroredvlans</i>	(Optional) Errored VLANs
TABLE_stp_forward	(Optional) show STP forwarding VLANs
<i>interface</i>	(Optional) Interface index
<i>stp fwd_vlans</i>	(Optional) STP Forwarding VLANs
TABLE_fabricpath_vlans	(Optional) show fabricpath VLANs
<i>interface</i>	(Optional) Interface index
<i>fabricpath_vlans</i>	(Optional) FabricPath VLANs
TABLE_vtp_pruning	(Optional) show VTP pruning VLANs

<i>interface</i>	(Optional) Interface index
<i>vtppruning_vlans</i>	(Optional) VTP Pruning VLANs

Command Mode

- /exec

show interface untagged-cos

show interface untagged-cos [module <mod_num>] [__readonly__ <interface> <ucos-value>]

Syntax Description

show	Show running system information
interface	Show interface status and information
untagged-cos	Show interface untagged CoS information
module	(Optional) Limit display to interfaces on module
<i>mod_num</i>	(Optional) Enter module number
<i>__readonly__</i>	(Optional)
<i>interface</i>	(Optional) Interface index
<i>ucos-value</i>	(Optional) COS value

Command Mode

- /exec

show inventory

```
show inventory [ chassis | fans | power_supply | module [ <module> ] | <s0> [ <santa-cruz-range> ] | all ] [
__readonly__ TABLE_inv <name> <desc> <productid> <vendorid> <serialnum> ]
```

Syntax Description

show	Show running system information
inventory	system inventory information
chassis	(Optional) system inventory chassis information
fans	(Optional) system inventory fan information
power_supply	(Optional) system inventory power supply information
module	(Optional) system inventory module information
<i>module</i>	(Optional) please enter the module number
<i>s0</i>	(Optional) please enter the module number
<i>santa-cruz-range</i>	(Optional) please enter the xbar number
all	(Optional) system and transceiver inventory information
__readonly__	(Optional)
TABLE_inv	(Optional) Inventory table
<i>name</i>	(Optional) Name of inventory
<i>desc</i>	(Optional) Description of inventory
<i>productid</i>	(Optional) Product ID
<i>vendorid</i>	(Optional) Vendor ID
<i>serialnum</i>	(Optional) Serial Number

Command Mode

- /exec

```
show ip adjacency [ <interface> [ summary ] | <ip-addr> [ non-best | detail ] | detail | summary | non-best | [ throttle ] statistics ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ <invalid_pkt_cnt> ] [ <invalid_byte_cnt> ] [ <global_drop_pkt_cnt> ] [ <global_drop_byte_cnt> ] [ <global_punt_pkt_cnt> ] [ <global_punt_byte_cnt> ] [ <global_glean_pkt_cnt> ] [ <global_glean_byte_cnt> ] [ <glean_pkt_cnt> ] [ <glean_byte_cnt> ] [ <normal_pkt_cnt> ] [ <normal_byte_cnt> ] [ <last_updated> ] [ <count-static> ] [ <count-dynamic> ] [ <count-others> ] [ <count-throttle> ] [ <count-total> ] [ TABLE_vrf <vrf-name-out> [ TABLE_afi <afi> <count> [ TABLE_adj [ <intf-out> ] [ <ip-addr-out> ] [ <phy-intf> ] [ <mac> ] [ <pref> ] [ <owner> ] [ <pkt-count> ] [ <byte-count> ] [ <is-best> ] [ <is-thrld> ] ] ] ] ] }
```

<i>global_punt_pkt_cnt</i>	(Optional) Global packet punt count
<i>global_punt_byte_cnt</i>	(Optional) Global byte punt count
<i>global_glean_pkt_cnt</i>	(Optional) Global glean packet count
<i>global_glean_byte_cnt</i>	(Optional) Global glean byte count
<i>glean_pkt_cnt</i>	(Optional) Glean packet count
<i>glean_byte_cnt</i>	(Optional) Glean byte count
<i>normal_pkt_cnt</i>	(Optional) Packet count
<i>normal_byte_cnt</i>	(Optional) Byte count
<i>last_updated</i>	(Optional) Last updated
<i>count-static</i>	(Optional) Count static
<i>count-dynamic</i>	(Optional) Count dynamic
<i>count-others</i>	(Optional) Count others
<i>count-throttle</i>	(Optional) Count throttle
<i>count-total</i>	(Optional) Count total
TABLE_afi	(Optional) TABLR afi
afi	(Optional) afi
count	(Optional) count
TABLE_adj	(Optional) Adjacency table
intf-out	(Optional) Interface
phy-intf	(Optional) Physical interface
ip-addr-out	(Optional) IP address
mac	(Optional) MAC address
pref	(Optional) Preference
owner	(Optional) Owner
pkt-count	(Optional) Packet count
byte-count	(Optional) Byte count
is-best	(Optional) Best
is-thrtld	(Optional) Throttled

Command Mode

- /exec

show ip amt relay

```
show { ip | ipv6 } amt relay [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ TABLE_vrf <vrf>
<tut> <ra> <nds> <ldn> <nts> <lrn> <lra> <lq> <uc> <rc4> <rc6> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
vrf	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
amt	AMT show commands
relay	Display status information about the AMT Relay
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>tut</i>	(Optional)
<i>ra</i>	(Optional)
<i>vrf</i>	(Optional)
<i>nds</i>	(Optional)
<i>ldn</i>	(Optional)
<i>nts</i>	(Optional)
<i>lrn</i>	(Optional)
<i>lra</i>	(Optional)
<i>lq</i>	(Optional)
<i>uc</i>	(Optional)
<i>rc4</i>	(Optional)
<i>rc6</i>	(Optional)

Command Mode

- /exec

show ip amt route

```
show { ip | ipv6 } amt route [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ TABLE_vrf <vrf>
<rc4> <rc6> { TABLE_route <addrs> <if> <nbr> <gwa> <gw_exp> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
vrf	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
amt	AMT show commands
route	Display multicast routes learned via AMT
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf</i>	(Optional)
<i>rc4</i>	(Optional)
<i>rc6</i>	(Optional)
TABLE_route	(Optional)
<i>addrs</i>	(Optional)
<i>if</i>	(Optional)
<i>nbr</i>	(Optional)
<i>gwa</i>	(Optional)
<i>gw_exp</i>	(Optional)

Command Mode

- /exec

show ip amt tunnel

```
show ip amt tunnel [ <address4> <port> ] [ detail ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__
TABLE_vrf <vrf> <tc4> { TABLE_tunnel <gwa> <gwp> <ut> <ld> <lr> <rc> <exp> { TABLE_route
<source> <group> <rexp> } } ]
```

Syntax Description

show	Show running system information
amt	AMT show commands
ip	Display IP information
tunnel	Display tunnel information
vrf	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>address4</i>	(Optional) IP address of tunnel endpoint
<i>port</i>	(Optional) UDP port number of gateway
detail	(Optional) Display routes joined by tunnel endpoint
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf</i>	(Optional)
<i>tc4</i>	(Optional)
TABLE_tunnel	(Optional)
<i>gwa</i>	(Optional)
<i>gwp</i>	(Optional)
<i>ut</i>	(Optional)
<i>ld</i>	(Optional)
<i>lr</i>	(Optional)
<i>rc</i>	(Optional)
<i>exp</i>	(Optional)
TABLE_route	(Optional)
<i>source</i>	(Optional)

<i>group</i>	(Optional)
<i>rexp</i>	(Optional)

Command Mode

- /exec

show ip arp

```
show ip arp [ [ [ <ip-address> ] [ sync-entries | fhrp-non-active-learn ] [ detail ] | static | summary | [ summary
] <interface> ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ] [ __readonly__ TABLE_vrf <vrf-name-out>
[ <cnt-resolved> ] [ <cnt-incomplete> ] [ <cnt-thrtld-incomplete> ] [ <cnt-unknown> ] [ <cnt-total> ] [
TABLE_adj <intf-out> <ip-addr-out> [ <time-stamp> ] <mac> [ <phy-intf> ] [ <unknown> ] [ <incomplete>
] [ <flags> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
summary	(Optional) Display ARP adjacency summary
detail	(Optional) Display detailed information
sync-entries	(Optional) Display ARP table learnt only due to arp table sync
fhrp-non-active-learn	(Optional) Display ARP table learnt only due to request for non-active FHRP address
<i>interface</i>	(Optional) ARP interface
<i>ip-address</i>	(Optional) IP address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display ARP entries for all vrfs
static	(Optional) Display Static ARP entries
__readonly__	(Optional)
TABLE_vrf	(Optional) Show VRF table
<i>vrf-name-out</i>	(Optional) Show VRF name
<i>cnt-resolved</i>	(Optional) Show total resolved ARP entries
<i>cnt-incomplete</i>	(Optional) Show total incomplete ARP entreis
<i>cnt-thrtld-incomplete</i>	(Optional) Show total incomplete throttled entries
<i>cnt-unknown</i>	(Optional) Show total unknow entris
<i>cnt-total</i>	(Optional) Show total

<i>TABLE_adj</i>	(Optional) Show IP ARP
<i>intf-out</i>	(Optional) Show interface
<i>ip-addr-out</i>	(Optional) Show ip address
<i>time-stamp</i>	(Optional) Show age of adjacency
<i>mac</i>	(Optional) Show mac
<i>phy-intf</i>	(Optional) Show physical interface
<i>unknown</i>	(Optional) Show unknown entry
<i>incomplete</i>	(Optional) Show incomplete entry
<i>flags</i>	(Optional) Show flags

Command Mode

- /exec

show ip arp anycast topo-info

```
show ip arp anycast topo-info [ <topo-id> ] [ __readonly__ { TABLE_ip_arp_anycast_topo_info [ <ip_arp_anycat_topo_id> ] [ <ip_arp_anycast_feature> ] [ <ip_arp_anycast_mode> ] } ]
```

Syntax Description

show	Show running system information
ip	Configure IP features
arp	Configure ARP parameters
anycast	anycast feature info
topo-info	Per topology specific information
<i>topo-id</i>	(Optional) Topology ID (VLAN-ID or BD-ID)
<i>__readonly__</i>	(Optional)
<i>TABLE_ip_arp_anycast_topo_info</i>	(Optional) Show ip arp anycast topo-info
<i>ip_arp_anycat_topo_id</i>	(Optional) Show ARP anycast topo-id
<i>ip_arp_anycast_feature</i>	(Optional) Show ARP anycast feature
<i>ip_arp_anycast_mode</i>	(Optional) Show ARP anycast mode

Command Mode

- /exec

show ip arp cache

show ip arp cache { { brief | detail } | { interface [<intf>] } } [operational]

Syntax Description

show	Show running system information
ip	Display IP information
arp	arp
cache	Display ip arp cache
interface	Display ip arp related interface information
brief	Display summary of arp interface status and configuration
detail	Display detailed information of arp interface status and configuration
operational	(Optional) Display only interfaces that are administratively enabled
<i>intf</i>	(Optional) Interface name to display

Command Mode

- /exec

show ip arp client

```
show ip arp client [ __readonly__ { <arp-clients> } [ TABLE_arp_client_list { <arp-cli-uuid> <l2-client-type>
<client-flg> <mts-addr-sap> <cli-msg-cnt> [ <l2-cli-func-name> ] [ <l2-cli-dbg-func> ] [
<l2-cli-dbg-un-init-func> ] } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
client	Display ARP Client table
<i>__readonly__</i>	(Optional)
<i>arp-clients</i>	(Optional) Number of ARP Clients
<i>TABLE_arp_client_list</i>	(Optional) Show ip arp client
<i>arp-cli-uuid</i>	(Optional) Protocol uuid
<i>l2-client-type</i>	(Optional) Client type
<i>client-flg</i>	(Optional) Flags
<i>mts-addr-sap</i>	(Optional) SAP
<i>cli-msg-cnt</i>	(Optional) Client message count
<i>l2-cli-func-name</i>	(Optional) Received function
<i>l2-cli-dbg-func</i>	(Optional) Debug init function
<i>l2-cli-dbg-un-init-func</i>	(Optional) Debug Un-init function

Command Mode

- /exec

show ip arp controller-statistics

```
show ip arp controller-statistics [ __readonly__ { TABLE_ip_arp_controller_statistics [
<arp_adj_controller_add_count> ][ <arp_adj_controller_del_count> ][ <arp_adj_controller_add_err_count>
][ <arp_adj_controller_del_err> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
controller-statistics	Controller statistics
__readonly__	(Optional)
TABLE_ip_arp_controller_statistics	(Optional) Show controller-statistics
<i>arp_adj_controller_add_count</i>	(Optional)
<i>arp_adj_controller_del_count</i>	(Optional)
<i>arp_adj_controller_add_err_count</i>	(Optional)
<i>arp_adj_controller_del_err</i>	(Optional)

Command Mode

- /exec

show ip arp esi

```
show ip arp esi [ __readonly__ { TABLE_ip_arp_esi [ <ip_arp_esi_interface> ] [ <ip_arp_esi_value> ] } ]
```

Syntax Description

show	Show running system information
ip	Configure IP features
arp	Configure ARP parameters
esi	ESI information
__readonly__	(Optional)
TABLE_ip_arp_esi	(Optional) Show ip arp esi
<i>ip_arp_esi_interface</i>	(Optional) Interface
<i>ip_arp_esi_value</i>	(Optional) Values

Command Mode

- /exec

show ip arp multihoming-statistics

```
show ip arp multihoming-statistics [ <interface> ] [ interface-all ] [ vrf { <vrf-name> | <vrf-known-name> |
all } ] [ __readonly__ TABLE_vrf <vrf-name-out2> TABLE_stat <ps-recv-add-l2rib> <ps-proc-add-l2rib>
<ps-recv-del-l2rib> <ps-proc-del-l2rib> <ps-recv-pc-shut-l2rib> <ps-proc-pc-shut-l2rib>
<ps-recv-remote-upd-l2rib> <ps-proc-remote-upd-l2rib> <ps-add-err-invalid-flags> <ps-del-err-invalid-flags>
<ps-add-err-invalid-curr-state> <ps-del-err-invalid-curr-state> <ps-del-err-mac-mismatch> <ps-del-err-sec-del>
<ps-del-err-tl-route> <tl-del-err-psro-route> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
multihoming-statistics	Display ARP Multihoming stats
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display ARP Multihoming statistics for all vrfs
interface-all	(Optional) Display ARP Multihoming statistics for all interface
<i>interface</i>	(Optional) ARP interface
__readonly__	(Optional)
TABLE_vrf	(Optional) VRF table
<i>vrf-name-out2</i>	(Optional) VRF name
TABLE_stat	(Optional) Show ip arp multihoming statistics
<i>ps-recv-add-l2rib</i>	(Optional) Receieved ADD from L2RIB
<i>ps-recv-del-l2rib</i>	(Optional) Receieved DEL from L2RIB
<i>ps-recv-remote-upd-l2rib</i>	(Optional) Receieved remote UPD from L2RIB
<i>ps-recv-pc-shut-l2rib</i>	(Optional) Receieved PC shut from L2RIB
<i>ps-proc-add-l2rib</i>	(Optional) Processed ADD from L2RIB
<i>ps-proc-del-l2rib</i>	(Optional) Processed DEL from L2RIB
<i>ps-proc-remote-upd-l2rib</i>	(Optional) Processed remote UPD from L2RIB
<i>ps-proc-pc-shut-l2rib</i>	(Optional) Processed PC shut from L2RIB

<i>ps-add-err-invalid-flags</i>	(Optional) Multihoming ADD error invalid flag
<i>ps-del-err-invalid-flags</i>	(Optional) Multihoming DEL error invalid flag
<i>ps-add-err-invalid-curr-state</i>	(Optional) Multihoming ADD error invalid current state
<i>ps-del-err-invalid-curr-state</i>	(Optional) Multihoming DEL error invalid current state
<i>ps-del-err-mac-mismatch</i>	(Optional) Peer sync DEL error MAC mismatch
<i>ps-del-err-tl-route</i>	(Optional) Peer sync DEL error second delete
<i>tl-del-err-psro-route</i>	(Optional) True local DEL error deleteing PS RO route
<i>ps-del-err-sec-del</i>	(Optional) Peer sync DEL error second delete

Command Mode

- /exec

show ip arp off-list

```
show ip arp off-list [ { vlan | bdi } <vlan-id> ] [ __readonly__ [ <offlist-vlan-id> <vlan-adj-cnt> ] [
<arp-sync-adj-cnt> ] { TABLE_arp_vlan_list <adj-vlan-id> <off-adj-ip-addr> <time-stamp> <arp-mac-addr>
<off-adj-flags> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
off-list	Show adjacencies in off-list arp database
vlan	(Optional) Vlan id
bdi	(Optional) Bridge Domain Name/Id
<i>vlan-id</i>	(Optional) Show information for specified vlan
<i>__readonly__</i>	(Optional)
<i>offlist-vlan-id</i>	(Optional) Show ip arp offlist vlan-id
<i>vlan-adj-cnt</i>	(Optional) Show ip arp vlan adjacency count
<i>arp-sync-adj-cnt</i>	(Optional) Show arp sync adjacency count
TABLE_arp_vlan_list	(Optional) Show ip arp vlan list
<i>adj-vlan-id</i>	(Optional) Show ip arp adjacency vlan id
<i>off-adj-ip-addr</i>	(Optional) Show arp offlist adjacency ip address
<i>time-stamp</i>	(Optional) Show duration
<i>arp-mac-addr</i>	(Optional) Show mac address
<i>off-adj-flags</i>	(Optional) show offlist adjacencyy flgs

Command Mode

- /exec

show ip arp open-flow error-statistics

```
show ip arp open-flow error-statistics [ __readonly__ { TABLE_ip_arp_open_flow_error_statistics [
<arp_ofa_total_err_cnt> ] [ <arp_ofa_dp_adj_err_on_del> ] [ <arp_ofa_cp_mac_mismatch_err_on_del> ] [
<arp_ofa_cp_null_mac_err_on_del> ] [ <arp_ofa_cp_no_adj_err_on_del_flag> ] [
<arp_ofa_cp_cp_nh_mismatch_err_on_del> ] [ <arp_ofa_cp_adj_del_failure_err> ] [
<arp_ofa_cp_null_mac_err_on_add> ] [ <arp_ofa_cp_dp_mac_mismatch_err_on_add> ] [
<arp_ofa_cp_cp_mac_mismatch_err_on_add> ] [ <arp_ofa_cp_added_first_err> ] [
<arp_ofa_dp_overwrite_cp_err> ] [ <arp_ofa_dp_cp_nh_mismatch_err_on_add> ] [
<arp_ofa_cp_cp_nh_mismatch_err_on_add> ] [ <arp_ofa_cp_dp_nh_mismatch_err_on_add> ] [
<arp_ofa_cp_adj_add_failure_err> ] [ <arp_ofa_barrier_response_err> ] } ]
```

Syntax Description

show	Show running system information
ip	Configure IP features
arp	Configure ARP parameters
open-flow	open flow
error-statistics	IR mode specific adjacency statistics
__readonly__	(Optional)
TABLE_ip_arp_open_flow_error_statistics	(Optional) ARP Open Flow Error Statistics
arp_ofa_total_err_cnt	(Optional) OFA total error count
arp_ofa_dp_adj_err_on_del	(Optional) Controller Deleting DP adjacency error
arp_ofa_cp_mac_mismatch_err_on_del	(Optional) CP adjacency MAC mismatch error while delete
arp_ofa_cp_null_mac_err_on_del	(Optional) CP adjacency NULL mac error while delete
arp_ofa_cp_no_adj_err_on_del_flag	(Optional) No adjacency found while delete
arp_ofa_cp_cp_nh_mismatch_err_on_del	(Optional) CP adjacency NH mismatch error while delete
arp_ofa_cp_adj_del_failure_err	(Optional) Other errors while deleting
arp_ofa_cp_null_mac_err_on_add	(Optional) CP adjacency NULL mac error while Adding
arp_ofa_cp_dp_mac_mismatch_err_on_add	(Optional) DP adjacency present with different mac
arp_ofa_cp_cp_mac_mismatch_err_on_add	(Optional) CP adjacency present with different mac
arp_ofa_cp_added_first_err	(Optional) CP adjacency added first
arp_ofa_dp_overwrite_cp_err	(Optional) Overwriting CP adjacency with DP
arp_ofa_dp_cp_nh_mismatch_err_on_add	(Optional) DP adjacency already present with different NH
arp_ofa_cp_cp_nh_mismatch_err_on_add	(Optional) CP adjacency already present with different NH

<i>arp_ofa_cp_dp_nh_mismatch_err_on_add</i>	(Optional) Overwriting CP adj with DP with different NH
<i>arp_ofa_cp_adj_add_failure_err</i>	(Optional) Other errors while adding
<i>arp_ofa_barrier_response_err</i>	(Optional) Barrier responses

Command Mode

- /exec

show ip arp snmp ptree

```
show ip arp snmp ptree { static | dynamic | virtual | typeall } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
snmp	Show only snmp ptree
ptree	Patricia tree
static	show only static adjacencies in pt tree
dynamic	show only dynamic adjacencies in pt tree
virtual	show only virtual adjacencies in pt tree
typeall	show all adjacencies in pt tree
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display ARP statistics for all vrfs

Command Mode

- /exec

show ip arp statistics

```
show ip arp statistics [ <interface> ] [ interface-all ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ TABLE_vrf <vrf-name-out1> [ TABLE_stat <tx-total> <tx-req> <tx-reply> <tx-req-l2>
<tx-reply-l2> <tx-grat> <tx-tunnel> <tx-drop> [ <tx-srvrport> ] [ <tx-fbrcport> ] [ <tx-fixup-core> ] [
<tx-fixup-server> ] [ <tx-fixup-rarp> ] [ <tx-anycast-glean> ] <tx-mbuf-fail> <tx-ctxt-not-crted> <tx-bad-ctxt-id>
<tx-invalid-ifindex> <tx-invalid-sip> <tx-invalid-dip> <tx-own-ip> <tx-unattached-ip> <tx-adj-create-fail>
<tx-null-sip> <tx-null-smac> <tx-client-enq-fail> <tx-dest-unreachable-proxy-arp>
<tx-dest-unreachable-enhanced-proxy> <tx-dest-l2port-track> <tx-invalid-local-proxy> <tx-invalid-proxy>
<tx-vip-not-active> <rx-total> <rx-req> <rx-reply> <rx-req-l2> <rx-reply-l2> <rx-proxy> <rx-local-proxy>
<rx-enhanced-proxy> <rx-enhanced-proxy-anycast> <rx-enhanced-proxy-l2port-track> <rx-tunnel>
<rx-fastpath> <rx-snoop> <rx-drop> <rx-srvrport> <bad-if> <bad-len> <invalid-prot> <invalid-hrd-type>
<invalid-ctxt> <ctxt-not-crted> <invalid-l2> <invalid-l3> <invalid-sip> <our-sip> <arp-if-no-mem>
<subnet-mismatch> <dir-bcast> <invalid-dip> <non-local-dst> <non-active-fhrp> <invalid-smac> <our-smac>
<not-init> <l2-prxy-en> <l2-port-untrusted> <stdby-fhrp-vip> <grat-prxy-en> <arp-req-ignore> <l2-intf>
<l2fm-query-fail> <tunnel_fail> [ <hsrp-active-vmac> ] [ <rx-intf-down> ] <refresh-req-from-clients>
<l2rib-signals> <adds> <dels> <timeouts> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
statistics	Display ARP statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display ARP statistics for all vrfs
interface-all	(Optional) Display ARP statistics for all interface
<i>interface</i>	(Optional) ARP interface
__readonly__	(Optional)
TABLE_vrf	(Optional) Table Vrf
<i>vrf-name-out1</i>	(Optional) Show VRF name
TABLE_stat	(Optional) Show IP ARP statistics
<i>tx-total</i>	(Optional) Sent: total
<i>tx-req</i>	(Optional) Sent: request
<i>tx-reply</i>	(Optional) Sent: reply

<i>tx-req-l2</i>	(Optional) Sent: request on L2
<i>tx-reply-l2</i>	(Optional) Sent: replay on L2
<i>tx-grat</i>	(Optional) Sent: gratuitous
<i>tx-tunnel</i>	(Optional) Sent: tunnel packet
<i>tx-drop</i>	(Optional) Sent:Dropped packet
<i>tx-srvrport</i>	(Optional) Sent from Server Port
<i>tx-fbrport</i>	(Optional) Sent from Fabric Port
<i>tx-fixup-core</i>	(Optional) Sent: fixup core
<i>tx-fixup-server</i>	(Optional) Sent: fixup server
<i>tx-fixup-rarp</i>	(Optional) Sent: fixup rarp
<i>tx-anycast-glean</i>	(Optional) Sent: modified anycast glean
<i>tx-mbuf-fail</i>	(Optional) Sent:MBUF operation failed
<i>tx-ctxt-not-crtd</i>	(Optional) Sent:Context not yet created
<i>tx-bad-ctxt-id</i>	(Optional) Sent:Invalid context
<i>tx-invalid-ifindex</i>	(Optional) Sent:Invalid ifindex
<i>tx-invalid-sip</i>	(Optional) Sent:Invalid SRC IP
<i>tx-invalid-dip</i>	(Optional) Sent:Invalid DEST IP
<i>tx-own-ip</i>	(Optional) Sent:Destination is our own IP
<i>tx-unattached-ip</i>	(Optional) Sent:Unattached IP
<i>tx-adj-create-fail</i>	(Optional) Sent:Adjacency Couldn't be added
<i>tx-null-sip</i>	(Optional) Sent:Null Source IP
<i>tx-null-smac</i>	(Optional) Sent: Null Source MAC
<i>tx-client-enq-fail</i>	(Optional) Sent: Client Enqueue Failed
<i>tx-dest-unreachable-proxy-arp</i>	(Optional) Sent: Dest. not reachable for proxy arp
<i>tx-dest-unreachable-enhanced-proxy</i>	(Optional) Sent:Dest. unreachable for enhanced proxy
<i>tx-dest-l2port-track</i>	(Optional) Sent:Dest. on L2 port being tracked
<i>tx-invalid-local-proxy</i>	(Optional) Sent:Invalid Local proxy arp
<i>tx-invalid-proxy</i>	(Optional) Sent:Invalid proxy arp
<i>tx-vip-not-active</i>	(Optional) Sent:VIP is not active

<i>rx-total</i>	(Optional) Received: total
<i>rx-req</i>	(Optional) Received: Requests
<i>rx-reply</i>	(Optional) Received: Replies
<i>rx-req-l2</i>	(Optional) Received: Requests on L2
<i>rx-reply-l2</i>	(Optional) Received: Replies on L2
<i>rx-proxy</i>	(Optional) Received: Proxy arp
<i>rx-local-proxy</i>	(Optional) Received: Local-Proxy arp
<i>rx-enhanced-proxy</i>	(Optional) Received: Enhanced Proxy arp
<i>rx-enhanced-proxy-anycast</i>	(Optional) Received: Anycast proxy Proxy arp
<i>rx-enhanced-proxy-l2port-track</i>	(Optional) Received: L2 Port-track Proxy arp
<i>rx-tunnel</i>	(Optional) Received: Tunneled
<i>rx-fastpath</i>	(Optional) Received: Fastpath
<i>rx-snoop</i>	(Optional) Received: Snooped
<i>rx-drop</i>	(Optional) Received: Dropped
<i>rx-srvrport</i>	(Optional) Received: on Server Port
<i>bad-if</i>	(Optional) Appeared on a wrong interface
<i>bad-len</i>	(Optional) Incorrect length
<i>invalid-prot</i>	(Optional) Invalid protocol packet
<i>invalid-hrd-type</i>	(Optional) Invalid Hardware type
<i>invalid-ctxt</i>	(Optional) Invalid context
<i>ctxt-not-crtd</i>	(Optional) Context not yet created
<i>invalid-l2</i>	(Optional) Invalid layer 2 address length
<i>invalid-l3</i>	(Optional) Invalid layer 3 address length
<i>invalid-sip</i>	(Optional) Invalid source IP address
<i>our-sip</i>	(Optional) Source IP address is our own
<i>arp-if-no-mem</i>	(Optional) No mem to create per intf structure
<i>subnet-mismatch</i>	(Optional) Source address mismatch with subnet
<i>dir-bcast</i>	(Optional) Directed broadcast source
<i>invalid-dip</i>	(Optional) Invalid destination IP address

<i>non-local-dst</i>	(Optional) Non-local destination IP address
<i>non-active-fhrp</i>	(Optional) Non-active FHRP dest IP address. Learn and drop
<i>invalid-smac</i>	(Optional) Invalid source MAC address
<i>our-smac</i>	(Optional) Source MAC address is our own
<i>not-init</i>	(Optional) Received before arp initialization
<i>l2-prxy-en</i>	(Optional) L2 packet on proxy-arp-enabled interface
<i>l2-port-untrusted</i>	(Optional) L2 packet on untrusted L2 port
<i>stdby-fhrp-vip</i>	(Optional) Packet with VIP on standby FHRP
<i>grat-prxy-en</i>	(Optional) Grat arp received on proxy-arp-enabled interface
<i>arp-req-ignore</i>	(Optional) Requests came for existing entries
<i>l2-intf</i>	(Optional) Requests came on a L2 interface
<i>l2fm-query-fail</i>	(Optional) L2FM query failed for a L2 Address
<i>tunnel_fail</i>	(Optional) Dropping due to tunneling failures
<i>hsrp-active-vmac</i>	(Optional) Dropping due to HSRP standby receiving HSRP active vmac
<i>rx-intf-down</i>	(Optional) Received Interface Down
<i>refresh-req-from-clients</i>	(Optional) Refresh requests received from clients
<i>l2rib-signals</i>	(Optional) Signals received from L2rib
<i>adds</i>	(Optional) Adds
<i>dels</i>	(Optional) Deletes
<i>timeouts</i>	(Optional) Timeouts

Command Mode

- /exec

show ip arp suppression-cache

```
show ip arp suppression-cache { detail [ vlan <vlan_id> ] | summary | statistics | vlan <vlan_id> | local [ vlan
<vlan_id> ] | remote [ vlan <vlan_id> ] } [ __readonly__ TABLE_arp-suppression [ TABLE_entries <ip-addr>
<age> <mac> <vlan> <physical-iod> <flag> ] [ TABLE_summary <remote-count> <local-count> <total-count>
] [ TABLE_stats TABLE_suppressed <total> <requests> <requests-on-l2> <gratuitous> <gratuitous-on-l2>
TABLE_forwarded <total-sent> <requests-sent> <replies-sent> <requests-on-core-l2> <replies-on-core-sent>
<dropped-sent> <requests-on-l2-sent> <replies-on-l2-sent> <requests-on-core-l2-sent>
<replies-on-core-l2-sent> <dropped-l2-sent> TABLE_received <total-recv> <requests-recv> <replies-recv>
<local-requests-recv> <local-replies-recv> <gratuitous-recv> <dropped-recv> <requests-on-l2-recv>
<replies-on-l2-recv> <gratuitous-l2-recv> <dropped-l2-recv> TABLE_entrystats <adds> <dels> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
suppression-cache	arp-suppression-cache
detail	show details
summary	show summary
statistics	show statistics
local	show local entries
remote	show remote entries
vlan	(Optional) L2vlan
<i>vlan_id</i>	(Optional) Vlan
__readonly__	(Optional)
TABLE_arp-suppression	(Optional) IP ARP suppression-cache
TABLE_entries	(Optional) IP ARP suppression entries
<i>ip-addr</i>	(Optional) IP address
<i>age</i>	(Optional) Age
<i>mac</i>	(Optional) MAC address
<i>vlan</i>	(Optional) vlan id
<i>physical-iod</i>	(Optional) Physical iod
<i>flag</i>	(Optional) Flags
TABLE_summary	(Optional) IP ARP suppression-cache Summary

<i>remote-count</i>	(Optional) Remote count
<i>local-count</i>	(Optional) Local count
<i>total-count</i>	(Optional) Total count
TABLE_stats	(Optional) Show IP ARP suppression statistics
TABLE_suppressed	(Optional) Suppressed table
<i>total</i>	(Optional) total
<i>requests</i>	(Optional) request
<i>requests-on-l2</i>	(Optional) requests-on-l2
<i>gratuitous</i>	(Optional) gratuitous
<i>gratuitous-on-l2</i>	(Optional) gratuitous-on-l2
TABLE_forwarded	(Optional) Forwarded table
<i>total-sent</i>	(Optional) total
<i>requests-sent</i>	(Optional) Requests sent on L3
<i>replies-sent</i>	(Optional) Replies sent on L3
<i>requests-on-core-sent</i>	(Optional) Request on core port
<i>replies-on-core-sent</i>	(Optional) Reply on core port
<i>dropped-sent</i>	(Optional) Dropped
<i>requests-on-l2-sent</i>	(Optional) Requests on L2
<i>replies-on-l2-sent</i>	(Optional) Replies on L2
<i>requests-on-core-l2-sent</i>	(Optional) Request on core port L2
<i>replies-on-core-l2-sent</i>	(Optional) Reply on core port L2
<i>dropped-l2-sent</i>	(Optional) Dropped on L2
TABLE_received	(Optional) Received
<i>total-recv</i>	(Optional) Total
<i>requests-recv</i>	(Optional) Requests on L3 mode
<i>replies-recv</i>	(Optional) Replies on L3 mode
<i>local-requests-recv</i>	(Optional) Local Request
<i>local-replies-recv</i>	(Optional) Local Responses
<i>gratuitous-recv</i>	(Optional) Gratuitous on L3 mode

<i>dropped-recv</i>	(Optional) Dropped on L3 mode
<i>requests-on-l2-recv</i>	(Optional) Requests on L2 mode
<i>replies-on-l2-recv</i>	(Optional) Replies on L2 mode
<i>gratuitous-l2-recv</i>	(Optional) Gratuitous on L2 mode
<i>dropped-l2-recv</i>	(Optional) Dropped on L2 mode
TABLE_entrystats	(Optional) ARP suppression-cache Local entry statistics
<i>adds</i>	(Optional) Adds
<i>dels</i>	(Optional) Deletes

Command Mode

- /exec

show ip arp suppression topo-info

```
show ip arp suppression topo-info [ <topo-id> ] [ __readonly__ { TABLE_ip_arp_suppression_topo_info [ <ip_arp_suppression_topo_id> ] [ <ip_arp_suppression_mode> ] } ]
```

Syntax Description

show	Show running system information
ip	Configure IP features
arp	Configure ARP parameters
suppression	ARP-suppression based event
topo-info	E-VPN identifier
<i>topo-id</i>	(Optional) E-VPN identifier (VLAN-ID or BD-ID)
<i>__readonly__</i>	(Optional)
<i>TABLE_ip_arp_suppression_topo_info</i>	(Optional) Show suppression topo-info
<i>ip_arp_suppression_topo_id</i>	(Optional) Show ARP suppression topo_id
<i>ip_arp_suppression_mode</i>	(Optional) Show ARP suppression mode

Command Mode

- /exec

show ip arp tunnel-statistics

```
show ip arp tunnel-statistics [ __readonly__ { TABLE_ip_arp_tunnel_stat [ <arp-tun-pkt-rcv-cnt> ] [
<arp-tun-pkt-rcv-ing-vpc> ] [ <arp-tun-pkt-rcv-ing-gpc> ] [ <arp-tun-pkt-rcv-ing-orp-vpc> ] [
<arp-tun-pkt-rcv-ing-orp-vpc-pl> ] [ <arp-tun-pkt-snd-cnt> ] [ <arp-tun-pkt-snd-snoop-cnt> ] [
<arp-tun-pkt-snd-non-local-vip-cnt> ] [ <arp-tun-pkt-snd-peer-gate-cnt> ] [ <arp-tun-pkt-snd-ing-vpc> ] [
<arp-tun-pkt-snd-ing-gpc> ] [ <arp-tun-pkt-snd-ing-orp-vpc> ] [ <arp-tun-pkt-snd-ing-orp-vpc-pl> ] [
<arp-tun-pkt-rcv-drp-cnt> ] [ <arp-tun-pkt-snd-drp-cnt> ] [ <arp-tun-pkt-snd-drp-snd-fail-cnt> ] [
<arp-tun-pkt-rcv-drp-ver-cnt> ] [ <arp-tun-pkt-rcv-drp-pl-cnt> ] [ <arp-tun-pkt-rcv-drp-ing-non-mct> ] [
<arp-tun-pkt-rcv-drp-inv-ing-intf> ] [ <arp-tun-pkt-snd-drp-inv-ing-intf> ] [
<arp-tun-pkt-rcvdrp-inv-gpc-core-sw> ] [ <arp-tun-pkt-rcvdrp-inv-gpc-peer-sw> ] [ <arp-tun-pkt-drp-inv-mcec>
] [ <arp-tun-pkt-im-api-fail> ] [ <arp-tun-pkt-drp-ctxt-inv> ] [ <arp-tun-pkt-drp-mct-dwn> ] [
<arp-tun-pkt-rcv-drp-mbuf-op-fail> ] [ <arp-tun-pkt-snd-drp-mbuf-op-fail> ] [ <arp-tun-pkt-snd-drp-tunnel>
] [ <arp-tun-pkt-snd-drp-ce> ] [ <arp-tun-pkt-snd-drp-inv-gpc> ] [ <arp-tun-pkt-rcv-drp-inv-gpc> ] [
<arp-tun-pkt-sys-mcecm-key-not-found> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
tunnel-statistics	Display ARP statistics for tunneled packets
__readonly__	(Optional)
TABLE_ip_arp_tunnel_stat	(Optional) ARP Tunnel statistics
<i>arp-tun-pkt-rcv-cnt</i>	(Optional) Total tunneled packets received
<i>arp-tun-pkt-rcv-ing-vpc</i>	(Optional) Tunneled packets rx for ingress vPC
<i>arp-tun-pkt-rcv-ing-gpc</i>	(Optional) Tunneled packets rx for ingress GPC
<i>arp-tun-pkt-rcv-ing-orp-vpc</i>	(Optional) Tunneled Packets rx for ingress orphan vPC
<i>arp-tun-pkt-rcv-ing-orp-vpc-pl</i>	(Optional) Tunneled Packets rx for ingress orphan vPC+
<i>arp-tun-pkt-snd-cnt</i>	(Optional) Total tunneled packets sent
<i>arp-tun-pkt-snd-snoop-cnt</i>	(Optional) Tunneled packets Sent for ARP Snoop
<i>arp-tun-pkt-snd-non-local-vip-cnt</i>	(Optional) Tunneled packets sent for Non-Local VIP
<i>arp-tun-pkt-snd-peer-gate-cnt</i>	(Optional) Tunneled Packets sent for Peer Gateway
<i>arp-tun-pkt-snd-ing-vpc</i>	(Optional) Tunneled packets tx for ingress vPC
<i>arp-tun-pkt-snd-ing-gpc</i>	(Optional) Tunneled packets tx for ingress GPC
<i>arp-tun-pkt-snd-ing-orp-vpc</i>	(Optional) Tunneled Packets tx for ingress orphan vPC

<i>arp-tun-pkt-snd-ing-orp-vpc-pl</i>	(Optional) Tunneled Packets tx for ingress orphan vPC+
<i>arp-tun-pkt-rcv-drp-cnt</i>	(Optional) Total tunnel packets rcv dropped
<i>arp-tun-pkt-snd-drp-cnt</i>	(Optional) Total tunnel packets send dropped
<i>arp-tun-pkt-snd-drp-snd-fail-cnt</i>	(Optional) Drops due to send failed
<i>arp-tun-pkt-rcv-drp-ver-cnt</i>	(Optional) Received packet with invalid version
<i>arp-tun-pkt-rcv-drp-pl-cnt</i>	(Optional) Received packet with invalid payload type
<i>arp-tun-pkt-rcv-drp-ing-non-mct</i>	(Optional) Received packet on non mct interface
<i>arp-tun-pkt-rcv-drp-inv-ing-intf</i>	(Optional) Received packet with invalid ingress port
<i>arp-tun-pkt-snd-drp-inv-ing-intf</i>	(Optional) Drop send packets for invalid ingress port
<i>arp-tun-pkt-rcvdrp-inv-gpc-core-sw</i>	(Optional) Drop rcv pkt, invalid GPC of core switch
<i>arp-tun-pkt-rcvdrp-inv-gpc-peer-sw</i>	(Optional) Drop rcv pkt, invalid GPC of peer switch
<i>arp-tun-pkt-drp-inv-mcec</i>	(Optional) Failed to retrieve vPC ID while processing
<i>arp-tun-pkt-im-api-fail</i>	(Optional) IM api failed while processing
<i>arp-tun-pkt-drp-ctxt-inv</i>	(Optional) Drop tunnel packet as context is invalid
<i>arp-tun-pkt-drp-mct-dwn</i>	(Optional) Drop tunnel packet as mct is down
<i>arp-tun-pkt-rcv-drp-mbuf-op-fail</i>	(Optional) Drop rcv packets as mbuf operation failed
<i>arp-tun-pkt-snd-drp-mbuf-op-fail</i>	(Optional) Drop send packets as mbuf operation failed
<i>arp-tun-pkt-snd-drp-tunnel</i>	(Optional) Cannot tunnel a incoming tunneled packet
<i>arp-tun-pkt-snd-drp-ce</i>	(Optional) Cannot tunnel in a CE network
<i>arp-tun-pkt-snd-drp-inv-gpc</i>	(Optional) Drop send pkt, failed in retrieving the GPC
<i>arp-tun-pkt-rcv-drp-inv-gpc</i>	(Optional) Drop rcv pkt, failed in retrieving the GPC
<i>arp-tun-pkt-sys-mcecm-key-not-found</i>	(Optional) MCEC_ID to PHY_IF_INDEX not found in DB

Command Mode

- /exec

show ip arp unnum-svi-adj

show ip arp unnum-svi-adj

Syntax Description

show	Show running system information
ip	Configure IP features
arp	Configure ARP parameters
unnum-svi-adj	Ip unnumbered SVI adjacency

Command Mode

- /exec

show ip arp vaddr

show ip arp vaddr

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
vaddr	Display VADDR ARP table

Command Mode

- /exec

show ip arp vpc-statistics

```
show ip arp vpc-statistics [ __readonly__ { TABLE_arp_vpc_stats [ <arp-pro-drp-pull-disable> ] [
<arp-pro-drp-push-msg-disable> ] [ <arp-pro-ign-snd-pull-disabe> ] [ <arp-ign-snd-push-disable> ] [
<arp-drp-im-fail> ] [ <arp-drp-mcecm-fail> ] [ <arp-drp-invalid-pc-iod> ] [ <arp-drp-pt-lookup-fail> ] [
<arp-drp-resp-fail-no-mct> ] [ <arp-drp-resp-fail> ] [ <arp-mcecm-ifidx-vpc-fail> ] [
<arp-mcecm-vpc-ifidx-fail> ] [ <arp-periodic-mcecm-ifidx-vpc-fail> ] [ <arp-resp-sent> ] [ <arp-resp-recvd>
] [ <arp-resp-recv-err> ] [ <arp-rcvd-msg> ] [ <arp-send-fail> ] [ <arp-cfs-rel-dlvry-fail> ] [
<arp-cfs-rel-dnvry-suc> ] [ <arp-drp-pt-add-fail> ] [ <arp-drp-no-mem> ] [ <arp-drp-tmr-cre-fail> ] [
<arp-drp-add-adj-fail> ] [ <arp-off-drp-pt-lookup-fail> ] [ <arp-dont-drp-vlan-mismat> ] [ <arp-drp-svi-invalid>
] [ <arp-dont-drop-sv-down> ] [ <arp-drp-mct-down> ] [ <arp-drp-ctxt-invalid> ] [ <arp-drp-vrf-invalid> ] [
<arp-drp-l3addr-invalid> ] [ <arp-drp-l3addr-sanity-fail> ] [ <arp-drp-mac-sanity-fail> ] [ <arp-own-rtr-mac>
] [ <arp-drp-own-ipaddr> ] [ <arp-drp-own-vipadd> ] [ <arp-drp-adj-fail> ] [ <arp-drp-subnet-mismatch> ] [
<arp-drp-adj-exist> ] [ <arp-dont-drp-ip-not-enable> ] [ <arp-drp-inval-phy-iod> ] [ <arp-drp-total-cnt> ] [
<arp-dont-drop-total-cnt> ] [ <arp-add-adj> ] [ <arp-del-adj> ] [ <arp-adj-already-exist> ] [
<arp-sync-recv-op-add-adj> ] [ <arp-sync-recv-op-del-adj> ] [ <arp-sync-push-msg-adj-cnt> ] [
<arp-sync-send-op-add-adj> ] [ <arp-sync-send-op-del-adj> ] [ <arp-sync-adj-cnt> ] [ <arp-sync-addadj-fail>
] [ <arp-sync-drp-svi-inv> ] [ <arp-sync-drp-svi-dwn> ] [ <arp-sync-drp-ctxt-inv> ] [ <arp-sync-null-adj> ]
[ <arp-sync-invalid-ip> ] [ <arp-periodic-sync-adj-l2-supp-cnt> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
arp	Display ARP table and statistics
vpc-statistics	Show vPC global statistics
__readonly__	(Optional)
TABLE_arp_vpc_stats	(Optional) Arp Vpc statistics
<i>arp-mcecm-ifidx-vpc-fail</i>	(Optional) Unable to retrieve VPC id from ifidx
<i>arp-mcecm-vpc-ifidx-fail</i>	(Optional) Unable to retrieve ifidx from VPC id
<i>arp-periodic-mcecm-ifidx-vpc-fail</i>	(Optional) Unable to retrieve ifidx from VPC id during periodic sync
<i>arp-sync-recv-op-add-adj</i>	(Optional) Total adjacencies recieved from peer to add
<i>arp-sync-recv-op-del-adj</i>	(Optional) Total adjacencies received from peer to delete
<i>arp-sync-push-msg-adj-cnt</i>	(Optional) Total gross adjacencies sent periodically
<i>arp-sync-send-op-add-adj</i>	(Optional) Total adjacencies sent to peer to add
<i>arp-sync-send-op-del-adj</i>	(Optional) Total adjacencies sent to peer to delete
<i>arp-sync-adj-cnt</i>	(Optional) Total periodic sync adjacencies
<i>arp-sync-addadj-fail</i>	(Optional) Failure in adding adjacencies while periodic sync send

<i>arp-sync-drp-svi-inv</i>	(Optional) Total drops during periodic sync because of invalid svi
<i>arp-sync-drp-svi-dwn</i>	(Optional) Total drops during periodic sync because of svi down
<i>arp-sync-drp-ctxt-inv</i>	(Optional) Total drops during periodic sync because of invalid context
<i>arp-sync-null-adj</i>	(Optional) Total drops while processsing syne of NULL Adjacencies
<i>arp-sync-invalid-ip</i>	(Optional) Total drops while processing sync because of NULL IP
<i>arp-periodic-sync-adj-l2-suppress-cnt</i>	(Optional) Total periodic sync adjacenciesadded for L2 suppression case
<i>arp-pro-drp-pull-disable</i>	(Optional) Drop the received CFS pull request
<i>arp-pro-drp-push-msg-disable</i>	(Optional) Drop the received CFS push message
<i>arp-pro-ign-snd-pull-disabe</i>	(Optional) Ignore to send pull request using CFSSoE
<i>arp-ign-snd-push-disable</i>	(Optional) Ignore to send push message using CFSSoE
<i>arp-drp-im-fail</i>	(Optional) IM api failed while processing CFS payload
<i>arp-drp-mcecm-fail</i>	(Optional) MCECM api failed while processing CFS payload
<i>arp-drp-invalid-pc-iod</i>	(Optional) Invalid MCT port-channel iod
<i>arp-drp-pt-lookup-fail</i>	(Optional) PT lookup failed while processing CFS payload
<i>arp-drp-resp-fail-no-mct</i>	(Optional) Sending CFS response failed due to invalid MCT iod
<i>arp-drp-resp-fail</i>	(Optional) Sending CFS response failed
<i>arp-resp-sent</i>	(Optional) Response sent via CFSSoE
<i>arp-resp-recvd</i>	(Optional) Response received via CFSSoE
<i>arp-resp-recv-err</i>	(Optional) Response received via CFSSoE with errors
<i>arp-rcvd-msg</i>	(Optional) Received message via CFSSoE
<i>arp-send-fail</i>	(Optional) Send message failed via CFSSoE
<i>arp-cfs-rel-dlvry-fail</i>	(Optional) MCECM send api failed via CFSSoE
<i>arp-cfs-rel-dnvry-suc</i>	(Optional) Send message succeeded via CFSSoE
<i>arp-drp-pt-add-fail</i>	(Optional) PT add failed while processing offlist
<i>arp-drp-no-mem</i>	(Optional) Memory alloc failed while processing offlist databse
<i>arp-drp-tmr-cre-fail</i>	(Optional) Timer create failed while processing offlist database
<i>arp-drp-add-adj-fail</i>	(Optional) Adjacency addition failed while processing offlist database
<i>arp-off-drp-pt-lookup-fail</i>	(Optional) PT lookup failed while processing offlist database

<i>arp-dont-drp-vlan-mismat</i>	(Optional) VLAN mismatch while processing offlist database
<i>arp-drp-svi-invalid</i>	(Optional) SVI is invalid while processing offlist database
<i>arp-dont-drop-sv-down</i>	(Optional) SVI is down while processing offlist database
<i>arp-drp-mct-down</i>	(Optional) MCT is down while processing offlist database
<i>arp-drp-ctxt-invalid</i>	(Optional) Ctxt_type is invalid while processing offlist database
<i>arp-drp-vrf-invalid</i>	(Optional) VRF is invalid while processing offlist database
<i>arp-drp-l3addr-invalid</i>	(Optional) VRF is invalid while processing offlist database
<i>arp-drp-l3addr-sanity-fail</i>	(Optional) IP address sanity failed
<i>arp-drp-mac-sanity-fail</i>	(Optional) MAC address sanity failed
<i>arp-own-rtr-mac</i>	(Optional) Our own router mac
<i>arp-drp-own-ipaddr</i>	(Optional) Our own ip address
<i>arp-drp-own-vipadd</i>	(Optional) Our own virtual ip address
<i>arp-drp-adj-fail</i>	(Optional) Create adjacency failed
<i>arp-drp-subnet-mismatch</i>	(Optional) Subnet mismatch
<i>arp-drp-adj-exist</i>	(Optional) Entry exists
<i>arp-dont-drp-ip-not-enable</i>	(Optional) IP not enabled on interface
<i>arp-drp-inval-phy-iod</i>	(Optional) Physical interface invalid
<i>arp-drp-total-cnt</i>	(Optional) Total drop count
<i>arp-dont-drop-total-cnt</i>	(Optional) Total don't drop count
<i>arp-add-adj</i>	(Optional) Total adjacency additions
<i>arp-del-adj</i>	(Optional) Total adjacency deletions
<i>arp-adj-already-exist</i>	(Optional) Total adjacencies ignored as already exist

Command Mode

- /exec

show ip as-path-access-list

```
show ip as-path-access-list [ <aspl-name> | <aspl-cfg-name> ] [ __readonly__ TABLE_aspl <name> <action>
<rule> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
as-path-access-list	List AS path access lists
<i>aspl-name</i>	(Optional) AS path access list name
<i>aspl-cfg-name</i>	(Optional) Known as-path access-list name
<i>__readonly__</i>	(Optional)
TABLE_aspl	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>rule</i>	(Optional)

Command Mode

- /exec

show ip bgp

```
show { ip mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | ip bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] all | ip bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ ipv4 { unicast | multicast } ] } { rib-install | rib-uninstall | rib-pending } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	Display BGP information for all address families
rib-install	Routes installed in RIB
rib-uninstall	Routes not installed in RIB
rib-pending	Routes not acknowledged by RIB

Command Mode

- /exec

show ip cache

show ip cache { { brief | detail } | { interface [<intf>] } } [operational]

Syntax Description

show	Show running system information
ip	Display IP information
cache	Display ip cache
brief	Display summary of ip interface status and configuration
detail	Display detailed information of ip interface status and configuration
operational	(Optional) Display only interfaces that are administratively enabled
interface	Display ip related interface information
<i>intf</i>	(Optional) Interface name to display

Command Mode

- /exec

show ip client

```
show ip client [ <client-name> ] [ __readonly__ [ TABLE_ip_clnt [ TABLE_clnt { <clnt-name> <clnt-uuid>
<clnt-pid> <clnt-ext-pid> [ <clnt-proto> ] <clnt-ind> <clnt-cntxt-id> <clnt-mts-sap> <clnt-flg>
<clnt-msg-succ-cnt> <clnt-msg-fail-cnt> [ <clnt-recv-fn-name> <clnt-recv-fn> ] } ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
client	Display clients registered with the IP process
<i>client-name</i>	(Optional) Display information for a single IP client
__readonly__	(Optional)
TABLE_ip_clnt	(Optional)
TABLE_clnt	(Optional)
<i>clnt-name</i>	(Optional)
<i>clnt-uuid</i>	(Optional)
<i>clnt-pid</i>	(Optional)
<i>clnt-ext-pid</i>	(Optional)
<i>clnt-proto</i>	(Optional)
<i>clnt-ind</i>	(Optional)
<i>clnt-cntxt-id</i>	(Optional)
<i>clnt-mts-sap</i>	(Optional)
<i>clnt-flg</i>	(Optional)
<i>clnt-msg-succ-cnt</i>	(Optional)
<i>clnt-msg-fail-cnt</i>	(Optional)
<i>clnt-recv-fn-name</i>	(Optional)
<i>clnt-recv-fn</i>	(Optional)

Command Mode

- /exec

show ip community-list

show ip community-list [<cl_name>] [__readonly__ TABLE_cl <name> <action> <rule>]

Syntax Description

show	Show running system information
ip	Display IP information
community-list	List community-list
<i>cl_name</i>	(Optional) Standard or expanded community-list name
<i>__readonly__</i>	(Optional)
<i>TABLE_cl</i>	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>rule</i>	(Optional)

Command Mode

- /exec

show ip debug

show ip debug

Syntax Description

show	Show running system information
ip	Display IP information
debug	Display IP debug-filter configuration

Command Mode

- /exec

show ip dhcp global statistics

```
show ip dhcp global statistics [ __readonly__ <pkts_processed> <pkts_rcvd_through_cfsoe> <pkts_fwded>
<pkts_cfsoe_fwded> <pkts_dropped> <pkts_dropped_from_untrusted_ports>
<pkts_dropped_src_mac_chk_fail> <pkts_dropped_opt82_ins_fail> <pkts_dropped_unknown_op_intf>
<pkts_dropped_unknown_pkt> <pkts_dropped_no_trust_inf> <pkts_dropped_unknown_pkt>
<pkts_dropped_relay_disable> <pkts_dropped_no_binding_entry> <pkts_dropped_interface_error>
<pkts_dropped_max_hops_exceeded> ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show information about DHCP
global	DHCP global stats
statistics	Statistics related to DHCP
<i>__readonly__</i>	(Optional) Read only
<i>pkts_processed</i>	(Optional) Packets processed
<i>pkts_rcvd_through_cfsoe</i>	(Optional) Packets received through cfsoe
<i>pkts_fwded</i>	(Optional) Packets forwarded
<i>pkts_cfsoe_fwded</i>	(Optional) Packets forwarded on cfsoe
<i>pkts_dropped</i>	(Optional) Total packets dropped
<i>pkts_dropped_from_untrusted_ports</i>	(Optional) Packets dropped from untrusted ports
<i>pkts_dropped_src_mac_chk_fail</i>	(Optional) Packets dropped due to MAC address check failure
<i>pkts_dropped_opt82_ins_fail</i>	(Optional) Packets dropped due to Option 82 insertion failure
<i>pkts_dropped_unknown_op_intf</i>	(Optional) Packets dropped due to o/p intf unknown
<i>pkts_dropped_unknown_pkt</i>	(Optional) Packets dropped which were unknown
<i>pkts_dropped_no_trust_inf</i>	(Optional) Packets dropped due to no trusted ports
<i>pkts_dropped_relay_disable</i>	(Optional) Packets dropped due to dhcp relay not enabled
<i>pkts_dropped_no_binding_entry</i>	(Optional) Packets dropped due to no binding entry
<i>pkts_dropped_interface_error</i>	(Optional) Packets dropped due to interface error/no interface
<i>pkts_dropped_max_hops_exceeded</i>	(Optional) Packets dropped due to max hops exceeded

Command Mode

- /exec

show ip dhcp option82 suboption info interface

show ip dhcp option82 suboption info interface [<intf>] [__readonly__ TABLE_intf_option82 <intf_header> <intf_name> <option82_status> <suboption_string> <tx_count>]

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show items in DHCP
option82	DHCP option82
suboption	DHCP option82 suboption
info	DHCP option82 suboption information
interface	DHCP option82 suboption information of all interfaces
<i>intf</i>	(Optional) interface
<i>__readonly__</i>	(Optional) Read only
<i>TABLE_intf_option82</i>	(Optional)
<i>intf_header</i>	(Optional)
<i>intf_name</i>	(Optional)
<i>option82_status</i>	(Optional)
<i>suboption_string</i>	(Optional)
<i>tx_count</i>	(Optional)

Command Mode

- /exec

show ip dhcp relay

```
show ip dhcp relay [ __readonly__ <relay_service_enable> <relay_opt82_enable> <relay_opt82_customize>
<relay_subopt_VPN_enable> <relay_subopt_type_cisco_enable> <global_smart-relay_enable>
<global_relay_trusted_enable> <relay_trusted_port_enable> <global_src_addr_hsrp_enable>
<smart_relay_intfs_hdr> [ TABLE_intf<smart_relay_enabled_intfs> ] <subnet_bcast_intfs_hdr> [ TABLE_intf
<subnet_bcast_enabled_intfs> ] <trusted_port_intfs_hdr> [ TABLE_intf<trusted_port_enabled_intfs> ]
<relay_src_addr_hsrp_hdr> [ TABLE_intf<src_addr_hsrp_enabled_intfs> ] <relay_address_hdr> [ TABLE_intf
<intf> <relay_address> <vrf_name> ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show items in DHCP
relay	DHCP relay
__readonly__	(Optional) Read only
<i>relay_service_enable</i>	(Optional)
<i>relay_opt82_enable</i>	(Optional)
<i>relay_opt82_customize</i>	(Optional)
<i>relay_subopt_VPN_enable</i>	(Optional)
<i>relay_subopt_type_cisco_enable</i>	(Optional)
<i>global_smart-relay_enable</i>	(Optional)
<i>global_relay_trusted_enable</i>	(Optional)
<i>relay_trusted_port_enable</i>	(Optional)
<i>global_src_addr_hsrp_enable</i>	(Optional) V4 Relay src-addr hsrp is globally enabled or not
<i>smart_relay_intfs_hdr</i>	(Optional) Smart relay interfaces header
TABLE_intf	(Optional)
<i>smart_relay_enabled_intfs</i>	(Optional) smart-relay enabled interfaces
<i>subnet_bcast_intfs_hdr</i>	(Optional) Subnet broadcast interfaces header
TABLE_intf	(Optional)
<i>subnet_bcast_enabled_intfs</i>	(Optional) subnet_bcast enabled interfaces
<i>trusted_port_intfs_hdr</i>	(Optional) Trusted port interfaces header
TABLE_intf	(Optional)

<i>trusted_port_enabled_intfs</i>	(Optional) trusted_port enabled interfaces
<i>relay_src_addr_hsrp_hdr</i>	(Optional) Header for V4 Relay src-addr enabled interfaces
TABLE_intf	(Optional)
<i>src_addr_hsrp_enabled_intfs</i>	(Optional) source-address hsrp enabled interfaces
<i>relay_address_hdr</i>	(Optional) relay address header
TABLE_intf	(Optional) Table for list of interfaces
<i>intf</i>	(Optional) interface name
<i>relay_address</i>	(Optional) helper address
<i>vrf_name</i>	(Optional) vrf name

Command Mode

- /exec

show ip dhcp relay address

```
show ip dhcp relay address [ interface <intf-range> ] [ __readonly__ <intf_header> [ TABLE_intf <intf2>  
<relay_address> <vrf_name> ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show DHCP
relay	relay address of the interface
address	DHCP relay address
interface	(Optional) DHCP relay address of the interface
<i>intf-range</i>	(Optional) interface
<i>__readonly__</i>	(Optional) Read only
<i>intf_header</i>	(Optional) interface header
TABLE_intf	(Optional)
<i>intf2</i>	(Optional) interface name
<i>relay_address</i>	(Optional) helper address
<i>vrf_name</i>	(Optional) VRF name

Command Mode

- /exec

show ip dhcp relay information trusted-sources

show ip dhcp relay information trusted-sources [__readonly__ <header> [TABLE_intf <intf>]]

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show DHCP
relay	DHCP Relay
information	Relay information
trusted-sources	Relay Trusted Sources
__readonly__	(Optional) Read only
TABLE_intf	(Optional) trusted interface table
<i>header</i>	(Optional) interface header
<i>intf</i>	(Optional) interface name

Command Mode

- /exec

show ip dhcp relay statistics

```
show ip dhcp relay statistics [ interface <intf> | { interface <intf> serverip <ip-addr-val> [ use-vrf <vrf-name>
] } ] [ __readonly__ [ <msg_stats_hdr> <msg_type_str> <tx_pkts> <rx_pkts> <drops> <msg_type_str_offer>
<offer_rx_pkts> <offer_tx_pkts> <offer_drops> <msg_type_str_request> <request_rx_pkts> <request_tx_pkts>
<request_drops> <msg_type_str_ack> <ack_rx_pkts> <ack_tx_pkts> <ack_drops> <msg_type_str_release>
<release_rx_pkts> <release_tx_pkts> <release_drops> <msg_type_str_decline> <decline_rx_pkts>
<decline_tx_pkts> <decline_drops> <msg_type_str_inform> <inform_rx_pkts> <inform_tx_pkts>
<inform_drops> <msg_type_str_nack> <nack_rx_pkts> <nack_tx_pkts> <nack_drops> <line>
<msg_type_str_total> <total_rx_pkts> <total_tx_pkts> <total_drops> <line_x> ] [ <server_consolidated_hdr>
[ TABLE_server_info <server_helper_addr> <server_vrf> <server_total_request> <server_total_response>
] <line_y> ] [ <l3_fwd_hdr> <l3_fwd_rx_pkts> <l3_fwd_tx_pkts> <l3_fwd_drops> <non_dhcp_hdr>
<non_dhcp_rx_pkts> <non_dhcp_tx_pkts> <non_dhcp_drops> <drop_hdr> <drop_validation_fail>
<drop_relay_disable> <drop_invalid_msg_type> <drop_intf_err> <drop_tx_sock_err>
<drop_tx_fail_client_intf> <drop_unknown_op_intf> <drop_l3_unknown_op_intf> <drop_max_hops>
<drop_opt82_insert_fail> <drop_malformed> <drop_mct_drop> <drop_untrusted_relay_intf> ] [
<server_discover> <server_request> <server_decline> <server_release> <server_inform> <server_ack>
<server_nack> <server_offer> <server_resp_hdr> <drop_unknown> <server_req_hdr> ] <footer> ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show information about DHCP
relay	DHCP Relay
statistics	Statistics related to DHCP
interface	(Optional) input interface
<i>intf</i>	(Optional) interface
serverip	(Optional) Helper address
<i>ip-addr-val</i>	(Optional) IP address
use-vrf	(Optional) helper address VRF membership
<i>vrf-name</i>	(Optional) VRF name
__readonly__	(Optional) Read only
<i>msg_stats_hdr</i>	(Optional) dhcp message statistics header
<i>msg_type_str</i>	(Optional) dhcp message type
<i>rx_pkts</i>	(Optional) received dhcp packets
<i>tx_pkts</i>	(Optional) forwarded dhcp packets
<i>drops</i>	(Optional) dhcp packet drops

<i>msg_type_str_offer</i>	(Optional) dhcp message type
<i>offer_rx_pkts</i>	(Optional) received dhcp packets
<i>offer_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>offer_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_request</i>	(Optional) dhcp message type
<i>request_rx_pkts</i>	(Optional) received dhcp packets
<i>request_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>request_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_ack</i>	(Optional) dhcp message type
<i>ack_rx_pkts</i>	(Optional) received dhcp packets
<i>ack_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>ack_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_release</i>	(Optional) dhcp message type
<i>release_rx_pkts</i>	(Optional) received dhcp packets
<i>release_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>release_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_decline</i>	(Optional) dhcp message type
<i>decline_rx_pkts</i>	(Optional) received dhcp packets
<i>decline_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>decline_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_inform</i>	(Optional) dhcp message type
<i>inform_rx_pkts</i>	(Optional) received dhcp packets
<i>inform_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>inform_drops</i>	(Optional) dhcp packet drops
<i>msg_type_str_nack</i>	(Optional) dhcp message type
<i>nack_rx_pkts</i>	(Optional) received dhcp packets
<i>nack_tx_pkts</i>	(Optional) forwarded dhcp packets
<i>nack_drops</i>	(Optional) dhcp packet drops
<i>line</i>	(Optional)

<i>msg_type_str_total</i>	(Optional) total dhcp packets of all message types
<i>total_rx_pkts</i>	(Optional) total forwarded dhcp packets
<i>total_tx_pkts</i>	(Optional) total forwarded dhcp packets
<i>total_drops</i>	(Optional) total dhcp drops
<i>line_x</i>	(Optional)
<i>server_consolidated_hdr</i>	(Optional) DHCP server stats
TABLE_server_info	(Optional)
<i>server_helper_addr</i>	(Optional) dhcp server address
<i>server_vrf</i>	(Optional) dhcp server vrf
<i>server_total_request</i>	(Optional) total dhcp requests to server
<i>server_total_response</i>	(Optional) total dhcp responses from server
<i>line_y</i>	(Optional)
<i>l3_fwd_hdr</i>	(Optional) DHCP l3 forward header
<i>l3_fwd_rx_pkts</i>	(Optional) DHCP l3 received packets
<i>l3_fwd_tx_pkts</i>	(Optional) DHCP l3 forwarded packets
<i>l3_fwd_drops</i>	(Optional) DHCP l3 forward drops
<i>non_dhcp_hdr</i>	(Optional) non dhcp packets header
<i>non_dhcp_rx_pkts</i>	(Optional) total non dhcp packets received
<i>non_dhcp_tx_pkts</i>	(Optional) total non dhcp packets forwarded
<i>non_dhcp_drops</i>	(Optional) total non dhcp drops
<i>drop_hdr</i>	(Optional) total dhcp drops in various scenarios
<i>drop_validation_fail</i>	(Optional) drops due to option 82 validation failed
<i>drop_relay_disable</i>	(Optional) drops due to dhcp relay not enabled
<i>drop_invalid_msg_type</i>	(Optional) drops due to invalid message type
<i>drop_intf_err</i>	(Optional) drops due to interface error
<i>drop_tx_sock_err</i>	(Optional) tx failure towards server
<i>drop_tx_fail_client_intf</i>	(Optional) drops due to Tx failure towards client
<i>drop_unknown_op_intf</i>	(Optional) Unknown output interface
<i>drop_l3_unknown_op_intf</i>	(Optional) unknown vrf interface for server

<i>drop_max_hops</i>	(Optional) drops due to max hop exceeded
<i>drop_opt82_insert_fail</i>	(Optional) Insertion of option 82 failed
<i>drop_malformed</i>	(Optional) drops due to packet malformed
<i>drop_mct_drop</i>	(Optional) drops through mct
<i>drop_untrusted_relay_intf</i>	(Optional) drops due to untrusted relay interface
<i>server_discover</i>	(Optional) DHCP discover messages relayed to server
<i>server_request</i>	(Optional) DHCP request messages relayed to server
<i>server_decline</i>	(Optional) DHCP decline messages relayed to server
<i>server_release</i>	(Optional) DHCP release messages relayed to server
<i>server_inform</i>	(Optional) DHCP inform messages relayed to server
<i>server_ack</i>	(Optional) DHCP ack messages relayed from server
<i>server_nack</i>	(Optional) DHCP nack messages relayed from server
<i>server_offer</i>	(Optional) DHCP offer messages relayed from server
<i>server_resp_hdr</i>	(Optional) DHCP server response header
<i>drop_unknown</i>	(Optional) drops due to Unknown Failure
<i>server_req_hdr</i>	(Optional) DHCP server request header
<i>footer</i>	(Optional) footer line

Command Mode

- /exec

show ip dhcp snooping

```
show ip dhcp snooping [ __readonly__ <snoop_service_enable> <snoop_gbl_enable> <snoop_vlan_enable>
<snoop_oper_vlan_enable> <snoop_opt82_enable> <snoop_hwaddr_verify_enable> <snoop_hdr> [ {
TABLE_intf_entry <intf_entry_if_index> <intf_entry_trust_dhcp> <intf_entry_pkt_limit> } ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show items in DHCP
snooping	DHCP snooping
__readonly__	(Optional) Read only
<i>snoop_service_enable</i>	(Optional)
<i>snoop_gbl_enable</i>	(Optional)
<i>snoop_vlan_enable</i>	(Optional)
<i>snoop_oper_vlan_enable</i>	(Optional)
<i>snoop_opt82_enable</i>	(Optional)
<i>snoop_hwaddr_verify_enable</i>	(Optional)
<i>snoop_hdr</i>	(Optional)
TABLE_intf_entry	(Optional)
<i>intf_entry_if_index</i>	(Optional)
<i>intf_entry_trust_dhcp</i>	(Optional) is DHCP snooping trusted on the interface
<i>intf_entry_pkt_limit</i>	(Optional) limit for DHCP packets per second on the interface

Command Mode

- /exec

show ip dhcp snooping binding

show ip dhcp snooping binding [<ip> | <mac> | vlan <vlan-range> |

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show items in DHCP
snooping	DHCP snooping
binding	DHCP snooping bindings
<i>ip</i>	(Optional) Binding entry IP address
<i>mac</i>	(Optional) Binding entry MAC address
vlan	(Optional) Binding entry VLAN
<i>vlan-range</i>	(Optional) VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec

show ip dhcp snooping statistics

show ip dhcp snooping statistics [{ vlan <vlan-id> interface <intf> } |

Syntax Description

<i>vlan-id</i>	(Optional)]
show	Show running system information
ip	Show the IP features of the system
dhcp	Show information about DHCP
snooping	DHCP snooping
statistics	Statistics related to DHCP
vlan	(Optional) VLAN
interface	(Optional) input interface
<i>intf</i>	(Optional) interface

Command Mode

- /exec

show ip dhcp status

```
show ip dhcp status [ __readonly__ [ <current_cli_op> ] [ <last_cli_op> <last_cli_stat> ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
dhcp	Show information about DHCP
status	Current CLI command and execution status of the last command
__readonly__	(Optional) Read only
<i>current_cli_op</i>	(Optional) current cli operation
<i>last_cli_op</i>	(Optional) last cli operation
<i>last_cli_stat</i>	(Optional) last cli status

Command Mode

- /exec

show ip dns source-interface

```
show ip dns source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_ipdnsvrf  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
dns	Display domain-lookup information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ipdnsvrf	(Optional) source interface of dns given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip dns source-interface vrf all

```
show ip dns source-interface vrf all [ __readonly__ [ { TABLE_ipdns <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
dns	Display domain-lookup information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ipdns	(Optional) source interface of dns
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip eigrp route-map statistics

```
show ip eigrp [ <eigrp-ptag> ] route-map statistics { { redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag>
| static | direct | amt | lisp } } | table-map } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_asn <asn> TABLE_vrf <vrf> { TABLE_rmap <name> <action> <seq_num> [ { TABLE_cmd
<command> <compare_count> <match_count> } ] } <total_accept_count> <total_reject_count> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
eigrp	Display EIGRP status and configuration
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
route-map	Route-map related information
statistics	Route-map statistics
redistribute	Redistribute information from another routing protocol
table-map	Tablemap information
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT Anycast prefix
lisp	LISP EID-prefixes

<i>__readonly__</i>	(Optional)
<i>TABLE_asn</i>	(Optional) AS number table
<i>asn</i>	(Optional) AS number
<i>TABLE_vrf</i>	(Optional) VRF table
<i>vrf</i>	(Optional) VRF name
<i>TABLE_rmap</i>	(Optional) Routemap table
<i>name</i>	(Optional) Route-map Name
<i>action</i>	(Optional) Route-map action
<i>seq_num</i>	(Optional) Sequence number of the rule in route-map
<i>TABLE_cmd</i>	(Optional) Route-map command table
<i>command</i>	(Optional) Route-map command
<i>compare_count</i>	(Optional) Number of comparisons
<i>match_count</i>	(Optional) Number of matches
<i>total_accept_count</i>	(Optional) Total number of packets accepted by the policy
<i>total_reject_count</i>	(Optional) Total number of packets rejected by the policy

Command Mode

- /exec

show ip extcommunity-list

show ip extcommunity-list [<extcl_name>] [__readonly__ TABLE_extcl <name> <action> <rule>]

Syntax Description

show	Show running system information
ip	Display IP information
extcommunity-list	List extcommunity-list
<i>extcl_name</i>	(Optional) Standard or expanded community-list name
<i>__readonly__</i>	(Optional)
TABLE_extcl	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>rule</i>	(Optional)

Command Mode

- /exec

show ip fib adjacency

```
show ip fib adjacency [ <aif> ] [ <anh> ] [ module <module> ] [ __readonly__ <adj-count> <nexthop>
<rewinfo> <interface> ]
```

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
adjacency	display adjacency information
<i>aif</i>	(Optional) adjacency output interface
<i>anh</i>	(Optional) adjacency next hop
module	(Optional) slot
<i>module</i>	(Optional) slot number
__readonly__	(Optional)
<i>adj-count</i>	(Optional) total adj count
<i>nexthop</i>	(Optional) next hop address
<i>rewinfo</i>	(Optional) rewrite information
<i>interface</i>	(Optional) output interface

Command Mode

- /exec

show ip fib interfaces

show ip fib interfaces [module <module>] [__readonly__ <intf> <v4adjcnt> <v6adjcnt> <rpfmode>]

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
interfaces	show fib interface info
__readonly__	(Optional)
<i>intf</i>	(Optional) interface name
module	(Optional) slot
<i>module</i>	(Optional) slot number
<i>v4adjcnt</i>	(Optional) count of v4 adjacencies
<i>v6adjcnt</i>	(Optional) count of v6 adjacencies
<i>rpfmode</i>	(Optional) uRPF mode

Command Mode

- /exec

show ip fib mroute

```
show ip fib mroute [ { <group> | <gprefix> } [ <source> ] ] [ table <table-id> ] [ module <module> ] [
__readonly__ <table_type> <num_groups> <num_sources> <src_len> <grp_len> <df_ordinal> <rpfiif>
<rpfiifindex> <flag> <flag_value> <route_pkts> <route_bytes> <oiflist_id> <platform_id> <oif_count>
<refcount> <oifname> <oifindex> <oif_pkts> <oif_bytes> ]
```

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
mroute	Multicast IPv4 routes
<i>group</i>	(Optional) Multicast IPv4 Group Address
<i>gprefix</i>	(Optional) Multicast IPv4 Group Prefix
<i>source</i>	(Optional) Multicast IPv4 Source Address
table	(Optional) display info per vpn-id
<i>table-id</i>	(Optional) table-id
module	(Optional) slot
<i>module</i>	(Optional) slot number
__readonly__	(Optional)
<i>table_type</i>	(Optional) Table Type
<i>num_groups</i>	(Optional) Number of group entries in the table
<i>num_sources</i>	(Optional) Number of (S, G) entries for the group address
<i>src_len</i>	(Optional) Source Address Mask
<i>grp_len</i>	(Optional) Group address Mask
<i>df_ordinal</i>	(Optional) DF ordinal
<i>rpfiif</i>	(Optional) RPF interface
<i>rpfiifindex</i>	(Optional) RPF Interface ifIndex
<i>flag</i>	(Optional) Route type flag
<i>flag_value</i>	(Optional) hex value of route flag
<i>route_pkts</i>	(Optional) Route packet count

<i>route_bytes</i>	(Optional) Route bytes
<i>oiflist_id</i>	(Optional) OIF list Identifier
<i>platform_id</i>	(Optional) Platform-index
<i>oif_count</i>	(Optional) Number of OIFs
<i>refcount</i>	(Optional) OIF list Reference Count
<i>oifname</i>	(Optional) OIF Interface name
<i>oifindex</i>	(Optional) OIF Interface ifIndex
<i>oif_pkts</i>	(Optional) OIF packets
<i>oif_bytes</i>	(Optional) OIF bytes

Command Mode

- /exec

show ip fib mroute

```
show ip fib mroute [ { <group> | <gprefix> } [ <source> ] ] [ table <table-id> ] [ module <module> ] [
__readonly__ <table_type> <num_groups> <num_sources> <src_len> <grp_len> <df_ordinal> <rpif>
<rpf_ifindex> <flag> <flag_value> <route_pkts> <route_bytes> <oiflist_id> <platform_id> <oif_count>
<refcount> <oifname> <oifindex> <oif_pkts> <oif_bytes> ]
```

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
mroute	Multicast IPv4 routes
<i>group</i>	(Optional) Multicast IPv4 Group Address
<i>gprefix</i>	(Optional) Multicast IPv4 Group Prefix
<i>source</i>	(Optional) Multicast IPv4 Source Address
table	(Optional) display info per vpn-id
<i>table-id</i>	(Optional) table-id
module	(Optional) slot
<i>module</i>	(Optional) slot number
__readonly__	(Optional)
<i>table_type</i>	(Optional) Table Type
<i>num_groups</i>	(Optional) Number of group entries in the table
<i>num_sources</i>	(Optional) Number of (S, G) entries for the group address
<i>src_len</i>	(Optional) Source Address Mask
<i>grp_len</i>	(Optional) Group address Mask
<i>df_ordinal</i>	(Optional) DF ordinal
<i>rpif</i>	(Optional) RPF interface
<i>rpf_ifindex</i>	(Optional) RPF Interface ifIndex
<i>flag</i>	(Optional) Route type flag
<i>flag_value</i>	(Optional) hex value of route flag
<i>route_pkts</i>	(Optional) Route packet count

<i>route_bytes</i>	(Optional) Route bytes
<i>oiflist_id</i>	(Optional) OIF list Identifier
<i>platform_id</i>	(Optional) Platform-index
<i>oif_count</i>	(Optional) Number of OIFs
<i>refcount</i>	(Optional) OIF list Reference Count
<i>oifname</i>	(Optional) OIF Interface name
<i>oifindex</i>	(Optional) OIF Interface ifIndex
<i>oif_pkts</i>	(Optional) OIF packets
<i>oif_bytes</i>	(Optional) OIF bytes

Command Mode

- /exec

show ip fib mroute txlist

show ip fib mroute txlist [module <module>]

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
mroute	display IP mcast routing table
txlist	display routes in the txlist
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

show ip fib route

```
show ip fib route [ vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } | table <table_id> ] [ summary | <prefix>
[ longer-prefixes ] | <address> | interface <interface> | next-hop <nh> | attached | unresolved | adjacency {
<aif> <anh> | drop | glean | punt } ] [ module <module> | vrf { <vrf-name> | <vrf-known-name> | <vrf-all>
} ] + [ __readonly__ [ <header> <vrfname> <tableid> <prefix-count> <pfx> { <nexthop> | <special> } <intf>
<route-count> <path-count> <mask-length> <routes-per-mask> ] [ TABLE_vrf { [ <vrf_name_out> ] [
<table_name> ] [ TABLE_prefix { [ <pfx> ] [ TABLE_path { [ <nexthop> | <special> ] [ <intf> ] } } ] } ] ] ] ] ]
```

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
route	display IP routing table
vrf	(Optional) display info per VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
table	(Optional) display info per vpn-id
<i>table_id</i>	(Optional) table number
summary	(Optional) display route counts
<i>prefix</i>	(Optional) display single exact match route
longer-prefixes	(Optional) display longer prefixes
<i>address</i>	(Optional) display single longest match route
interface	(Optional) display routes with this output i/f only
<i>interface</i>	(Optional) output interface
next-hop	(Optional) display routes with this next-hop only
<i>nh</i>	(Optional) next hop address
attached	(Optional) display directly connected routes
unresolved	(Optional) display unresolved routes
adjacency	(Optional) display routes via specified adjacency
<i>aif</i>	(Optional) adjacency output interface

<i>anh</i>	(Optional) adjacency next-hop address
<i>drop</i>	(Optional) display routes via drop adjacency
<i>glean</i>	(Optional) display routes via glean adjacency
<i>punt</i>	(Optional) display routes via punt adjacency
<i>module</i>	(Optional) slot
<i>module</i>	(Optional) slot number
<i>__readonly__</i>	(Optional)
<i>header</i>	(Optional) header string
<i>vrfname</i>	(Optional) VRF name
<i>tableid</i>	(Optional) table identifier
<i>prefix-count</i>	(Optional) total number of prefix in VRF
<i>px</i>	(Optional) ipv4 prefix
<i>nexthop</i>	(Optional) next hop address
<i>special</i>	(Optional) special adjacencies
<i>intf</i>	(Optional) output interface
<i>route-count</i>	(Optional) total number of routes in VRF
<i>path-count</i>	(Optional) total number of paths in VRF
<i>mask-length</i>	(Optional) length of mask
<i>routes-per-mask</i>	(Optional)
TABLE_vrf	(Optional) vrf table
<i>vrf_name_out</i>	(Optional) VRF name
<i>table_name</i>	(Optional) table name
TABLE_prefix	(Optional) all xml prefix entries
<i>px</i>	(Optional) ipv4 prefix
TABLE_path	(Optional) path table
<i>nexthop</i>	(Optional) next hop address
<i>special</i>	(Optional) special adjacencies
<i>intf</i>	(Optional) output interface

Command Mode

- /exec

show ip fib route

```
show ip fib route [ vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } ] [ table <table_id> ] [ summary | <prefix>
[ longer-prefixes ] | <address> | interface <interface> | next-hop <nh> | attached | unresolved | adjacency {
<aif> <anh> | drop | glean | punt } ] [ module <module> | vrf { <vrf-name> | <vrf-known-name> | <vrf-all>
} ] + [ __readonly__ <header> <vrfname> <tableid> <prefix-count> <pfx> { <nexthop> | <special> } <intf>
<route-count> <path-count> <mask-length> <routes-per-mask> ]
```

Syntax Description

show	
ip	Display IP information
fib	Forwarding information
route	display IP routing table
vrf	(Optional) display info per VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
table	(Optional) display info per vpn-id
<i>table_id</i>	(Optional) table number
summary	(Optional) display route counts
<i>prefix</i>	(Optional) display single exact match route
longer-prefixes	(Optional) display longer prefixes
<i>address</i>	(Optional) display single longest match route
interface	(Optional) display routes with this output i/f only
<i>interface</i>	(Optional) output interface
next-hop	(Optional) display routes with this next-hop only
<i>nh</i>	(Optional) next hop address
attached	(Optional) display directly connected routes
unresolved	(Optional) display unresolved routes
adjacency	(Optional) display routes via specified adjacency
<i>aif</i>	(Optional) adjacency output interface
<i>anh</i>	(Optional) adjacency next-hop address

<code>drop</code>	(Optional) display routes via drop adjacency
<code>glean</code>	(Optional) display routes via glean adjacency
<code>punt</code>	(Optional) display routes via punt adjacency
<code>module</code>	(Optional) slot
<i>module</i>	(Optional) slot number
<code>__readonly__</code>	(Optional)
<i>header</i>	(Optional) header string
<i>vrfname</i>	(Optional) VRF name
<i>tableid</i>	(Optional) table identifier
<i>prefix-count</i>	(Optional) total number of prefix in VRF
<i>pfx</i>	(Optional) ipv4 prefix
<i>nexthop</i>	(Optional) next hop address
<i>special</i>	(Optional) special adjacencies
<i>intf</i>	(Optional) output interface
<i>route-count</i>	(Optional) total number of routes in VRF
<i>path-count</i>	(Optional) total number of paths in VRF
<i>mask-length</i>	(Optional) length of mask
<i>routes-per-mask</i>	(Optional)

Command Mode

- /exec

show ip fib route recovered

show ip fib route recovered

Syntax Description

show	
ip	ipv4
fib	display fib information
route	display IP routing table
recovered	log of routes recovered after TCAM free condition

Command Mode

- /exec

show ip ftm statistics

show ip ftm statistics

Syntax Description

show	Show running system information
ip	Display IP information
ftm	FTM API
statistics	Statistics

Command Mode

- /exec

show ip ftp source-interface

```
show ip ftp source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_ipftpvrft  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ftp	Display FTP client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ipftpvrft	(Optional) source interface of ftp given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip ftp source-interface vrf all

show ip ftp source-interface vrf all [__readonly__ [{ TABLE_ipftp <vrfname> <ifname> }]]

Syntax Description

show	Show running system information
ip	Display IP information
ftp	Display FTP client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ipftp	(Optional) source interface of ftp
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip http source-interface

```
show ip http source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_iphttpvrf  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
http	Display HTTP client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_iphttpvrf	(Optional) source interface of http given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip http source-interface vrf all

```
show ip http source-interface vrf all [ __readonly__ [ { TABLE_iphttp <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
http	Display HTTP client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_iphttp	(Optional) source interface of http
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip igmp event-history

```
show ip igmp [ internal ] event-history { errors | msgs | <igmp-event-hist-buf-name> | statistics }
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
internal	(Optional) Commands for internal use
event-history	Show various event logs of IGMP
errors	Show error logs of IGMP
msgs	Show various message logs of IGMP
<i>igmp-event-hist-buf-name</i>	Show various logs of IGMP
statistics	Show state and size of buffer

Command Mode

- /exec

show ip igmp groups

```
show ip igmp { groups | route } [ <source> [ <group> ] | <group> [ <source> ] ] [ <interface> ] [ summary ]
[ vrf { <vrf-name> | <vrf-known-name> | all } ] [ summary-old ] [ __readonly__ ] [ TABLE_vrf [ <if-name>
] [ <vrfname> ] [ <entry-count> ] [ <group-addr> ] [ <sourceaddress> ] [ TABLE_group [ <group-addr> ] [
<group-type> ] [ <if-name> ] [ <uptime> ] [ <expires> ] [ <reporter> ] ] [ TABLE_source [ <source-addr> ]
[ <group-type> ] [ <translate> ] [ <if-name> ] [ <uptime> ] [ <expires> ] [ <reporter> ] ] [ <vrf-entxt> ] [
<g-count> ] [ <sg-count> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
groups	Display IGMP attached group membership information
route	Display IGMP attached group membership information
<i>group</i>	(Optional) Multicast IP address of single group to display
<i>source</i>	(Optional) Source IP address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>interface</i>	(Optional) Display group membership on single interface name
summary	(Optional) Display group summary
summary-old	(Optional) Display group summary
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrfname</i>	(Optional)
<i>if-name</i>	(Optional)
<i>group-addr</i>	(Optional)
<i>entry-count</i>	(Optional)
<i>sourceaddress</i>	(Optional)
TABLE_group	(Optional)

<i>group-addr</i>	(Optional)
<i>group-type</i>	(Optional)
<i>if-name</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expires</i>	(Optional)
<i>reporter</i>	(Optional)
TABLE_source	(Optional)
<i>source-addr</i>	(Optional)
<i>group-type</i>	(Optional)
<i>translate</i>	(Optional)
<i>if-name</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expires</i>	(Optional)
<i>reporter</i>	(Optional)
<i>vrf-cntxt</i>	(Optional)
<i>g-count</i>	(Optional)
<i>sg-count</i>	(Optional)

Command Mode

- /exec

show ip igmp interface

```
show ip igmp interface [ <interface> ] [ brief ] [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ TABLE_vrf <vrf> [ <entry-count> ] [ [ TABLE_brief [ <if-name> ] [ <addr> ] [ <querier> ] [
<mc> ] [ <ver> ] ] [ TABLE_if <if-name> [ <if-status> ] [ <ip-sum> ] [ <addr> ] [ <querier> ] [ <q-ver> ] [
<next-query> ] [ <expires> ] [ <mc> ] [ <ver> ] [ <host-ver> ] [ <qi> ] [ <cqi> ] [ <mrt> ] [ <cmrt> ] [ <sqi>
] [ <csqi> ] [ <sqc> ] [ <lmmt> ] [ <lmqc> ] [ <gt> ] [ <cgt> ] [ <qt> ] [ <cqt> ] [ <uri> ] [ <rv> ] [ <crv> ]
[ <rl> ] [ <rc> ] [ <il> ] [ <join-group-map> ] [ <static-group-map> ] [ <host-proxy> ] [
<host-proxy-group-map> ] [ <un-solicited> ] [ <unsoint> ] [ <v1rr> ] [ <v2qs> ] [ <v2qr> ] [ <v2rs> ] [ <v2rr>
] [ <v2ls> ] [ <v2lr> ] [ <v3qs> ] [ <v3qr> ] [ <v3rs> ] [ <v3rr> ] [ <v2gqdest> ] [ <v3gqdest> ] [ <cse> ] [
<ple> ] [ <lsip> ] [ <scf> ] [ <qnq> ] [ <rvm> ] [ <qvm> ] [ <uit> ] [ <v1gdam> ] [ <v2gdam> ] [ <v3dai> ]
[ <ra> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
interface	Display IGMP interface related information
<i>interface</i>	(Optional) Interface name of single interface to display
brief	(Optional) Display one line status per interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
detail	(Optional) Display detailed information
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf</i>	(Optional)
<i>entry-count</i>	(Optional)
TABLE_brief	(Optional)
<i>if-name</i>	(Optional)
<i>addr</i>	(Optional)
<i>querier</i>	(Optional)
<i>mc</i>	(Optional)

<i>ver</i>	(Optional)
TABLE_if	(Optional)
<i>if-name</i>	(Optional)
<i>if-status</i>	(Optional)
<i>ip-sum</i>	(Optional)
<i>addr</i>	(Optional)
<i>querier</i>	(Optional)
<i>q-ver</i>	(Optional)
<i>next-query</i>	(Optional)
<i>expires</i>	(Optional)
<i>mc</i>	(Optional)
<i>ver</i>	(Optional)
<i>host-ver</i>	(Optional)
<i>qi</i>	(Optional)
<i>cqi</i>	(Optional)
<i>mrt</i>	(Optional)
<i>cmrt</i>	(Optional)
<i>sqi</i>	(Optional)
<i>csqi</i>	(Optional)
<i>sqc</i>	(Optional)
<i>lmmrt</i>	(Optional)
<i>lmqc</i>	(Optional)
<i>gt</i>	(Optional)
<i>cgt</i>	(Optional)
<i>qt</i>	(Optional)
<i>cqt</i>	(Optional)
<i>uri</i>	(Optional)
<i>rv</i>	(Optional)
<i>crv</i>	(Optional)

<i>rll</i>	(Optional)
<i>rc</i>	(Optional)
<i>v1rr</i>	(Optional)
<i>v2qs</i>	(Optional)
<i>v2qr</i>	(Optional)
<i>v2rs</i>	(Optional)
<i>v2rr</i>	(Optional)
<i>v2ls</i>	(Optional)
<i>v2lr</i>	(Optional)
<i>v3qs</i>	(Optional)
<i>v3qr</i>	(Optional)
<i>v3rs</i>	(Optional)
<i>v3rr</i>	(Optional)
<i>v2ggdest</i>	(Optional)
<i>v3ggdest</i>	(Optional)
<i>cse</i>	(Optional)
<i>ple</i>	(Optional)
<i>lsip</i>	(Optional)
<i>scf</i>	(Optional)
<i>qnq</i>	(Optional)
<i>rvm</i>	(Optional)
<i>qvm</i>	(Optional)
<i>uit</i>	(Optional)
<i>v1gdam</i>	(Optional)
<i>v2gdam</i>	(Optional)
<i>v3dai</i>	(Optional)
<i>ra</i>	(Optional)
<i>static-group-map</i>	(Optional)
<i>join-group-map</i>	(Optional)

<i>host-proxy-group-map</i>	(Optional)
<i>il</i>	(Optional)
<i>host-proxy</i>	(Optional)
<i>un-solicited</i>	(Optional)
<i>unsoint</i>	(Optional)

Command Mode

- /exec

show ip igmp local-groups

```
show ip igmp local-groups [ <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [
TABLE_vrf [ <vrf-name> ] [ TABLE_if [ <if-name> ] [ TABLE_grp [ <group-addr> ] [ TABLE_src [
<source-addr> ] [ <last-reported> ] [ <local-group> ] [ <static-oif> ] [ <report-only> ] [ <host-proxy> ] ] ] ]
]]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
local-groups	Display IGMP local group membership information
<i>interface</i>	(Optional) Display group membership on single interface name
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_if	(Optional)
<i>if-name</i>	(Optional)
TABLE_grp	(Optional)
<i>group-addr</i>	(Optional)
TABLE_src	(Optional)
<i>source-addr</i>	(Optional)
<i>last-reported</i>	(Optional)
<i>local-group</i>	(Optional)
<i>static-oif</i>	(Optional)
<i>report-only</i>	(Optional)
<i>host-proxy</i>	(Optional)

Command Mode

- /exec

show ip igmp policy statistics reports

```
show ip igmp policy statistics reports [ <interface> ] [ __readonly__ [ TABLE_interface [ <if> ] [
TABLE_routemap [ <name> ] [ <action> ] [ <seq_num> ] [ TABLE_cmd [ <command> ] [ <match_count>
] [ <compare_count> ] ] ] [ <total_accept_count> ] [ <total_reject_count> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Show IGMP related information
policy	Policy related information
statistics	Policy statistics
reports	IGMP reports
<i>interface</i>	(Optional) Interface to display statistics for
<i>__readonly__</i>	(Optional)
TABLE_interface	(Optional)
<i>if</i>	(Optional)
TABLE_routemap	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seq_num</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>compare_count</i>	(Optional)
<i>match_count</i>	(Optional)
<i>total_accept_count</i>	(Optional)
<i>total_reject_count</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping

```
show ip igmp snooping [ { vlan <vlan> | bridge-domain <bdid> } ] [ __readonly__ [ <vdc> ] [ <enabled> ] [
<omf> ] [ <grepsup> ] [ <gv3repsup> ] [ <glinklocalgrpsup> ] { TABLE_vlan <vlan-id> [ <description> ] [
<snoop-on> ] [ <qa> ] [ <qv> ] [ <qi> ] [ <qlmqi> ] [ <rv> ] [ <sq> ] [ <sqr> ] [ <eht> ] [ <fl> ] [ <repsup> ]
[ <v3repsup> ] [ <vlinklocalgrpsup> ] [ <rpc> ] [ <gc> ] [ TABLE_active_ports [ <actvports> ] ] [ <lkupmode>
] [ <omf_enabled> ] [ <reportfloodenable> ] [ <reportfloodall> ] [ TABLE_intf <if-name> ] [
<leavegroupaddress> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
vlan	(Optional) Display VLAN IGMP snooping membership information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD IGMP snooping membership information
<i>bdid</i>	(Optional) Specify BD
__readonly__	(Optional)
<i>vdc</i>	(Optional)
<i>enabled</i>	(Optional)
<i>omf</i>	(Optional)
<i>grepsup</i>	(Optional)
<i>gv3repsup</i>	(Optional)
<i>glinklocalgrpsup</i>	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>description</i>	(Optional) description, if any
<i>snoop-on</i>	(Optional)
<i>qa</i>	(Optional)
<i>qv</i>	(Optional)
<i>qi</i>	(Optional)

<i>qlmqi</i>	(Optional)
<i>rv</i>	(Optional)
<i>sq</i>	(Optional)
<i>sqr</i>	(Optional)
<i>eht</i>	(Optional)
<i>fl</i>	(Optional)
<i>repsup</i>	(Optional)
<i>v3repsup</i>	(Optional)
<i>vlinklocalgrpsup</i>	(Optional)
<i>rpc</i>	(Optional)
<i>gc</i>	(Optional)
TABLE_active_ports	(Optional)
<i>actvports</i>	(Optional)
<i>lkupmode</i>	(Optional)
<i>omf_enabled</i>	(Optional)
<i>reportfloodenable</i>	(Optional)
<i>reportfloodall</i>	(Optional)
TABLE_intf	(Optional)
<i>if-name</i>	(Optional)
<i>leavegroupaddress</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping event-history

```
show ip igmp snooping [ internal ] event-history { statistics | <igmp-snoop-event-hist-buf-name> }
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
internal	(Optional) Display IGMP snooping internal information
event-history	Show various event logs of IGMP Snooping
statistics	Show state and size of the buffers
<i>igmp-snoop-event-hist-buf-name</i>	Show contents of event-history buffer

Command Mode

- /exec


```
show ip igmp snooping explicit-tracking [ vlan <vlan> | bridge-domain <bldid> ] [ detail ] [ __readonly__ [
TABLE_vlan [ <vlan-id> ] [ TABLE_gaddr [ <grp-addr> ] [ TABLE_if [ <if-name> ] [ TABLE_haddr [
<host-addr> ] [ TABLE_srcaddr [ <src-addr> ] [ <uptime> ] [ <last-join> ] [ <expires> ] [ <cfs-flag> ] [
<native-flag> ] [ <delete-pending> ] [ <cfs-update-pending> ] ] ] ] ] ]
```

<i>expires</i>	(Optional)
<i>cfs-flag</i>	(Optional)
<i>native-flag</i>	(Optional)
<i>delete-pending</i>	(Optional)
<i>cfs-update-pending</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping filter details

```
show ip igmp snooping filter [ vlan <vlan_id> ] details [ __readonly__ { TABLE_vlanid <vlan-id>
<access-group> <group-channels-limit> <igmp-min-ver> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
filter	Shows filter policy configuration
vlan	(Optional) Only for the specified VLAN
<i>vlan_id</i>	(Optional) VLAN ID
details	Shows different Filter configurations
<i>__readonly__</i>	(Optional)
TABLE_vlanid	(Optional)
<i>vlan-id</i>	(Optional)
<i>access-group</i>	(Optional)
<i>group-channels-limit</i>	(Optional)
<i>igmp-min-ver</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping groups

```
show ip igmp snooping [ otv | remote ] groups [ { <source> [ <group> ] } | { <group> [ <source> ] } ] [ vlan
<vlan> | bridge-domain <bdid> ] [ detail ] [ summary ] [ __readonly__ [ TABLE_vlan [ <vlan-id> ] [ <rports>
] [ <rtrPortFlag> ] [ TABLE_port <if-name> ] [ TABLE_rtrports <rport-if-name> ] [ <raddr> ] [ TABLE_source
<source> ] [ TABLE_group <addr> [ <g-mfdm> ] [ <ver> ] [ <old-host> ] [ <raddr> ] [ <static> ] [ <dynamic>
] [ TABLE_static_ports <static-if-name> ] [ TABLE_v2_ports <v2-if-name> [ <uptime> ] [ <expires> ] [
<gq-missed> ] ] [ TABLE_star_g_ports <star-g-if-name> [ <uptime> ] [ <expires> ] ] [ <g-vpc> ] [ <rsf> ] [
<js> ] [ TABLE_source <source> [ <srsf> ] [ <s-mfdm> ] [ <src-static> ] [ <src-dynamic> ] [
TABLE_src_static_ports <src-static-if-name> ] [ TABLE_src_dynamic [ <oifs> ] <dyn-if-name> [ <src-uptime>
] [ <src-expires> ] ] [ <s-vpc> ] ] ] [ <snoop-enabled> ] [ <omf-enabled> ] [ <group-count> ] [ <s-g-count>
] [ <total_star_g_count> ] [ <total_sg_count> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
otv	(Optional) IGMP Snooping OTV information
remote	(Optional) IGMP Snooping remote information
groups	Display snooping information for group address
summary	(Optional) Display snooping group summary
<i>group</i>	(Optional) Multicast IP address of single group to display
<i>source</i>	(Optional) Source IP address
vlan	(Optional) Display VLAN IGMP snooping membership information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD IGMP snooping membership information
<i>bdid</i>	(Optional) Specify BD
detail	(Optional) Display detailed information for the group
__readonly__	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>rports</i>	(Optional)
<i>rtrPortFlag</i>	(Optional)

<i>snoop-enabled</i>	(Optional)
<i>omf-enabled</i>	(Optional)
<i>group-count</i>	(Optional)
<i>s-g-count</i>	(Optional)
<i>total_star_g_count</i>	(Optional)
<i>total_sg_count</i>	(Optional)
TABLE_port	(Optional)
<i>if-name</i>	(Optional)
TABLE_rtrports	(Optional)
<i>rport-if-name</i>	(Optional)
<i>raddr</i>	(Optional)
TABLE_group	(Optional)
<i>addr</i>	(Optional)
<i>ver</i>	(Optional)
<i>raddr</i>	(Optional)
TABLE_source	(Optional)
<i>source</i>	(Optional)
<i>rsf</i>	(Optional)
<i>js</i>	(Optional)
<i>g-mfdm</i>	(Optional)
<i>old-host</i>	(Optional)
<i>g-vpc</i>	(Optional)
<i>static</i>	(Optional)
<i>dynamic</i>	(Optional)
TABLE_static_ports	(Optional)
<i>static-if-name</i>	(Optional)
TABLE_v2_ports	(Optional)
<i>v2-if-name</i>	(Optional)
<i>uptime</i>	(Optional)

<i>expires</i>	(Optional)
<i>gq-missed</i>	(Optional)
TABLE_star_g_ports	(Optional)
<i>star-g-if-name</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expires</i>	(Optional)
TABLE_source	(Optional)
<i>source</i>	(Optional)
<i>srsf</i>	(Optional)
<i>s-mfdm</i>	(Optional)
<i>s-vpc</i>	(Optional)
<i>src-static</i>	(Optional)
<i>src-dynamic</i>	(Optional)
TABLE_src_static_ports	(Optional)
<i>src-static-if-name</i>	(Optional)
TABLE_src_dynamic	(Optional)
<i>oifs</i>	(Optional)
<i>dyn-if-name</i>	(Optional)
<i>src-uptime</i>	(Optional)
<i>src-expires</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping lookup-mode

```
show ip igmp snooping lookup-mode [ vlan <vlan> | bridge-domain <bdid> ] [ __readonly__ [ <configured> ] [ <operational> ] [ TABLE_vlan [ <vlan-id> ] [ <lookup> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
lookup-mode	IGMP Snooping lkup mode information
vlan	(Optional) Display VLAN information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD information
<i>bdid</i>	(Optional) Specify BD
__readonly__	(Optional)
<i>configured</i>	(Optional)
<i>operational</i>	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>lookup</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping mac-oif

```
show ip igmp snooping mac-oif [ vlan <vlan> | bridge-domain <bdid> ] [ detail ] [ __readonly__ [ <totaloif> ] ] [ TABLE_vlan <vlan-id> <count> [ TABLE_mac <mac-addr> [ TABLE_oif <oifs> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
mac-oif	IGMP Snooping static mac oif information
vlan	(Optional) Display VLAN information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD information
<i>bdid</i>	(Optional) Specify BD
detail	(Optional) static mac oif detail, M2RIB oif info
__readonly__	(Optional)
<i>totaloif</i>	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>count</i>	(Optional)
TABLE_mac	(Optional)
<i>mac-addr</i>	(Optional)
TABLE_oif	(Optional)
<i>oifs</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping mrouter

```
show ip igmp snooping mrouter [ otv ] [ vlan <vlan> | bridge-domain <bdid> ] [ detail ] [ __readonly__
TABLE_vlan <vlan-id> TABLE_intf <if-name> <static> <dynamic> <vpc> <fabricpath-core-port>
<co-learned> <user-configured> <learnt-by-peer> <uptime> <expires> <internal> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
mrouter	Display multicast routers detected
otv	(Optional) IGMP Snooping OTV information
vlan	(Optional) Display VLAN multicast router information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD multicast router information
<i>bdid</i>	(Optional) Specify BD
detail	(Optional) Display detailed mrouter information
__readonly__	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
TABLE_intf	(Optional)
<i>if-name</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expires</i>	(Optional)
<i>static</i>	(Optional)
<i>dynamic</i>	(Optional)
<i>internal</i>	(Optional)
<i>vpc</i>	(Optional)
<i>fabricpath-core-port</i>	(Optional)
<i>co-learned</i>	(Optional)

<i>user-configured</i>	(Optional)
<i>learnt-by-peer</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping pw vlan brief

show ip igmp snooping pw vlan brief [__readonly__ <vlan-id>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
pw	IGMP Snooping PW information
vlan	Display VLAN/BD information
brief	Brief output
__readonly__	(Optional)
<i>vlan-id</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping querier

```
show ip igmp snooping querier [ vlan <vlan> | bridge-domain <bdid> ] [ detail ] [ __readonly__ [ TABLE_vlan
<vlan-id> <qa> <qv> [ <expires> ] <qiod> <qname> <int> [ <last_member_query_count> ] [
<config_last_member_query_count> ] [ <snooping_version> ] [ <config_qv> ] [ <robust> ] [ <config_robust>
] [ <startup_query_count> ] [ <config_startup_query_count> ] [ <startup_query_interval> ] [
<config_startup_query_interval> ] [ <mbr_query_interval> ] [ <config_mbr_query_interval> ] [
<snooping_query_intvl> ] [ <config_snooping_query_intvl> ] [ <gquery_response_time> ] [
<config_gquery_response_time> ] [ <querier_timeout> ] [ <querier_timeout_flag> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
querier	Display snooping querier information
vlan	(Optional) Display VLAN IGMP snooping querier information
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD IGMP snooping querier information
<i>bdid</i>	(Optional) Specify BD
detail	(Optional) Display detailed information
<i>__readonly__</i>	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>qa</i>	(Optional)
<i>expires</i>	(Optional)
<i>qv</i>	(Optional)
<i>qiod</i>	(Optional)
<i>qname</i>	(Optional)
<i>int</i>	(Optional)
<i>last_member_query_count</i>	(Optional)
<i>config_last_member_query_count</i>	(Optional)
<i>snooping_version</i>	(Optional)

<i>config_qv</i>	(Optional)
<i>robust</i>	(Optional)
<i>config_robust</i>	(Optional)
<i>startup_query_count</i>	(Optional)
<i>config_startup_query_count</i>	(Optional)
<i>startup_query_interval</i>	(Optional)
<i>config_startup_query_interval</i>	(Optional)
<i>mbr_query_interval</i>	(Optional)
<i>config_mbr_query_interval</i>	(Optional)
<i>snooping_query_intvl</i>	(Optional)
<i>config_snooping_query_intvl</i>	(Optional)
<i>gquery_response_time</i>	(Optional)
<i>config_gquery_response_time</i>	(Optional)
<i>querier_timeout</i>	(Optional)
<i>querier_timeout_flag</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping report statistics

```
show ip igmp snooping { report-policy | access-group } statistics [ vlan <vlan> ] [ __readonly__ [
TABLE_vlanid { <vlan-id> <rpm-type> <policy-name> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
report-policy	IGMP Report Policy
access-group	IGMP access-group
statistics	Policy statistics
vlan	(Optional) Display VLAN IGMP snooping policy statistics information
<i>vlan</i>	(Optional) Specify VLAN
__readonly__	(Optional)
TABLE_vlanid	(Optional)
<i>vlan-id</i>	(Optional)
<i>rpm-type</i>	(Optional)
<i>policy-name</i>	(Optional)

Command Mode

- /exec

show ip igmp snooping snmp mib adminMode

show ip igmp snooping snmp mib adminMode [__readonly__ <cisAdminMode>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
adminMode	Indicates the administrative snooping mode of IGMP Snooping feature
__readonly__	(Optional) Read Only
<i>cisAdminMode</i>	(Optional) mib object cisAdminMode

Command Mode

- /exec

show ip igmp snooping snmp mib aliasingMode

show ip igmp snooping snmp mib aliasingMode [__readonly__ <cisAddressAliasingMode>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
aliasingMode	Indicates the current IGMP Address Aliasing Mode of the device
__readonly__	(Optional) Read Only
<i>cisAddressAliasingMode</i>	(Optional) mib object cisAddressAliasingMode

Command Mode

- /exec

show ip igmp snooping snmp mib cisV3ProcessEnableOperStatus

```
show ip igmp snooping snmp mib cisV3ProcessEnableOperStatus [ __readonly__  
<cisV3ProcessEnabledOperStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
cisV3ProcessEnableOperStatus	Indicates the current operational status of IGMP v3 processing in the system
__readonly__	(Optional) Read Only
<i>cisV3ProcessEnabledOperStatus</i>	(Optional) mib object cisV3ProcessEnabledOperStatus

Command Mode

- /exec

show ip igmp snooping snmp mib explicitTrackingTable

```
show ip igmp snooping snmp mib explicitTrackingTable [ vlan <cisVlanIndex-in> ] [ __readonly__
TABLE_cisVlanExplicitTrackingTable <cisVlanIndex-out> <cisVlanExplicitTrackingEnabled>
<cisVlanExplicitTrackingLimit> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
explicitTrackingTable	Show mib table cisVlanExplicitTrackingTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>__readonly__</i>	(Optional)
<i>TABLE_cisVlanExplicitTrackingTable</i>	(Optional)
<i>cisVlanIndex-out</i>	(Optional) mib table index cisVlanIndex
<i>cisVlanExplicitTrackingEnabled</i>	(Optional) mib object cisVlanExplicitTrackingEnabled
<i>cisVlanExplicitTrackingLimit</i>	(Optional) mib object cisVlanExplicitTrackingLimit

Command Mode

- /exec

show ip igmp snooping snmp mib fallBackTime

show ip igmp snooping snmp mib fallBackTime [__readonly__ <cisFallbackTime>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
fallBackTime	Indicates the time the IGMP address aliasing mode is fallback
__readonly__	(Optional) Read Only
<i>cisFallbackTime</i>	(Optional) mib object cisFallbackTime

Command Mode

- /exec

show ip igmp snooping snmp mib fastBlockEnabled

show ip igmp snooping snmp mib fastBlockEnabled [__readonly__ <cisFastBlockEnabled>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
fastBlockEnabled	Indicates whether Fast-Block mechanism has been enabled for the system
__readonly__	(Optional) Read Only
<i>cisFastBlockEnabled</i>	(Optional) mib object cisFastBlockEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib fastleaveenabled

show ip igmp snooping snmp mib fastleaveenabled [__readonly__ <cisFastLeaveEnabled>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
fastleaveenabled	Check if fastleave is enabled
__readonly__	(Optional) Read Only
<i>cisFastLeaveEnabled</i>	(Optional) mib object cisFastLeaveEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib filterStatsTable

```
show ip igmp snooping snmp mib filterStatsTable [ interface <ifIndex-in> vlan <cisFilterStatsVlanNumber-in>
] [ __readonly__ TABLE_cisFilterStatsTable <ifIndex-out> <cisFilterStatsVlanNumber-out>
<cisFilterAccessGroupDenied> <cisFilterLimitDenied> <cisFilterTotalLimitDenied>
<cisFilterMinVersionDenied> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
filterStatsTable	Display VLAN/BD Filter Group
interface	(Optional) Display interface
<i>ifIndex-in</i>	(Optional) Interface Index
vlan	(Optional) Display Interface access group VLAN/BD information
<i>cisFilterStatsVlanNumber-in</i>	(Optional) Specify VLAN/BD
<i>__readonly__</i>	(Optional)
TABLE_cisFilterStatsTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisFilterStatsVlanNumber-out</i>	(Optional) mib table index cisFilterStatsVlanNumber
<i>cisFilterAccessGroupDenied</i>	(Optional) mib object cisFilterAccessGroupDenied
<i>cisFilterLimitDenied</i>	(Optional) mib object cisFilterLimitDenied
<i>cisFilterTotalLimitDenied</i>	(Optional) mib object cisFilterTotalLimitDenied
<i>cisFilterMinVersionDenied</i>	(Optional) mib object cisFilterMinVersionDenied

Command Mode

- /exec

show ip igmp snooping snmp mib ifAccessGroupTable

```
show ip igmp snooping snmp mib ifAccessGroupTable [ interface <ifIndex-in> vlan <cisIfAccessGroupVlan-in>
] [ __readonly__ TABLE_cisIfAccessGroupTable <ifIndex-out> <cisIfAccessGroupVlan-out>
<cisIfAccessGroupsChannelsAllowed> <cisIfAccessGroupStorageType> <cisIfAccessGroupRowStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
ifAccessGroupTable	Display interface access group
interface	(Optional) Display interface
<i>ifIndex-in</i>	(Optional) Interface Index
vlan	(Optional) Display Interface access group VLAN/BD information
<i>cisIfAccessGroupVlan-in</i>	(Optional) Specify VLAN/BD
__readonly__	(Optional)
TABLE_cisIfAccessGroupTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisIfAccessGroupVlan-out</i>	(Optional) mib table index cisIfAccessGroupVlan
<i>cisIfAccessGroupsChannelsAllowed</i>	(Optional) mib object cisIfAccessGroupsChannelsAllowed
<i>cisIfAccessGroupStorageType</i>	(Optional) mib object cisIfAccessGroupStorageType
<i>cisIfAccessGroupRowStatus</i>	(Optional) mib object cisIfAccessGroupRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib ifConfigTable

```
show ip igmp snooping snmp mib ifConfigTable [ interface <ifIndex-in> ] [ __readonly__  
TABLE_cisIfConfigTable <ifIndex-out> <cisIfTopoChangeFloodEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
ifConfigTable	Display interface configuration
interface	(Optional) Display interface
<i>ifIndex-in</i>	(Optional) Interface Index
<i>__readonly__</i>	(Optional)
TABLE_cisIfConfigTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisIfTopoChangeFloodEnabled</i>	(Optional) mib object cisIfTopoChangeFloodEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib ifLimitTable

```
show ip igmp snooping snmp mib ifLimitTable [ interface <ifIndex-in> vlan <cisIfLimitVlanNumber-in> ]
[ __readonly__ TABLE_cisIfLimitTable <ifIndex-out> <cisIfLimitVlanNumber-out> <cisIfLimitMax>
<cisIfLimitExcludeAccessGrp> <cisIfLimitStorageType> <cisIfLimitRowStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
ifLimitTable	Display interface configuration
interface	(Optional) Display interface
<i>ifIndex-in</i>	(Optional) Interface Index
vlan	(Optional) Display Interface Limit VLAN/BD information
<i>cisIfLimitVlanNumber-in</i>	(Optional) Specify VLAN/BD
__readonly__	(Optional)
TABLE_cisIfLimitTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisIfLimitVlanNumber-out</i>	(Optional) mib table index cisIfLimitVlanNumber
<i>cisIfLimitMax</i>	(Optional) mib object cisIfLimitMax
<i>cisIfLimitExcludeAccessGrp</i>	(Optional) mib object cisIfLimitExcludeAccessGrp
<i>cisIfLimitStorageType</i>	(Optional) mib object cisIfLimitStorageType
<i>cisIfLimitRowStatus</i>	(Optional) mib object cisIfLimitRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib ifLimitTotalTable

```
show ip igmp snooping snmp mib ifLimitTotalTable [ interface <ifIndex-in> ] [ __readonly__
TABLE_cisIfLimitTotalTable <ifIndex-out> <cisIfLimitTotalLimitMax> <cisIfLimitTotalExcludeAccessGrp>
<cisIfLimitTotalStorageType> <cisIfLimitTotalRowStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
ifLimitTotalTable	Display interface configuration
interface	(Optional) Display interface
<i>ifIndex-in</i>	(Optional) Interface Index
<i>__readonly__</i>	(Optional)
<i>TABLE_cisIfLimitTotalTable</i>	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisIfLimitTotalLimitMax</i>	(Optional) mib object cisIfLimitTotalLimitMax
<i>cisIfLimitTotalExcludeAccessGrp</i>	(Optional) mib object cisIfLimitTotalExcludeAccessGrp
<i>cisIfLimitTotalStorageType</i>	(Optional) mib object cisIfLimitTotalStorageType
<i>cisIfLimitTotalRowStatus</i>	(Optional) mib object cisIfLimitTotalRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib igmpsnoopingenabled

show ip igmp snooping snmp mib igmpsnoopingenabled [__readonly__ <cisIgmpSnoopingEnabled>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
igmpsnoopingenabled	Check if IGMP snooping is enabled
__readonly__	(Optional) Read Only
<i>cisIgmpSnoopingEnabled</i>	(Optional) mib object cisIgmpSnoopingEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib interfaceStatsTable

```
show ip igmp snooping snmp mib interfaceStatsTable [ interface <ifIndex-in> ] [ __readonly__
TABLE_cisInterfaceStatsTable <ifIndex-out> <cisTxGeneralQueries> <cisTxGroupSpecificQueries>
<cisTxReports> <cisTxLeaves> <cisRxGeneralQueries> <cisRxGroupSpecificQueries> <cisRxReports>
<cisRxLeaves> <cisRxValidPackets> <cisRxInvalidPackets> <cisRxOtherPackets>
<cisRxMACGeneralQueries> <cisRxTopoNotifications> <cisV3Allows> <cisV3Blocks> <cisV3IsIncluded>
<cisV3IsExcluded> <cisV3ToIncluded> <cisV3ToExcluded> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
interfaceStatsTable	Display interface stats
interface	(Optional) Display interface information
<i>ifIndex-in</i>	(Optional) Interface Index
<i>__readonly__</i>	(Optional)
TABLE_cisInterfaceStatsTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisTxGeneralQueries</i>	(Optional) mib object cisTxGeneralQueries
<i>cisTxGroupSpecificQueries</i>	(Optional) mib object cisTxGroupSpecificQueries
<i>cisTxReports</i>	(Optional) mib object cisTxReports
<i>cisTxLeaves</i>	(Optional) mib object cisTxLeaves
<i>cisRxGeneralQueries</i>	(Optional) mib object cisRxGeneralQueries
<i>cisRxGroupSpecificQueries</i>	(Optional) mib object cisRxGroupSpecificQueries
<i>cisRxReports</i>	(Optional) mib object cisRxReports
<i>cisRxLeaves</i>	(Optional) mib object cisRxLeaves
<i>cisRxValidPackets</i>	(Optional) mib object cisRxValidPackets
<i>cisRxInvalidPackets</i>	(Optional) mib object cisRxInvalidPackets

<i>cisRxOtherPackets</i>	(Optional) mib object cisRxOtherPackets
<i>cisRxMACGeneralQueries</i>	(Optional) mib object cisRxMACGeneralQueries
<i>cisRxTopoNotifications</i>	(Optional) mib object cisRxTopoNotifications
<i>cisV3Allows</i>	(Optional) mib object cisV3Allows
<i>cisV3Blocks</i>	(Optional) mib object cisV3Blocks
<i>cisV3IsIncluded</i>	(Optional) mib object cisV3IsIncluded
<i>cisV3IsExcluded</i>	(Optional) mib object cisV3IsExcluded
<i>cisV3ToIncluded</i>	(Optional) mib object cisV3ToIncluded
<i>cisV3ToExcluded</i>	(Optional) mib object cisV3ToExcluded

Command Mode

- /exec

show ip igmp snooping snmp mib lastMemeberQueryCount

```
show ip igmp snooping snmp mib lastMemeberQueryCount [ __readonly__ <cisLastMemberQueryCount> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
lastMemeberQueryCount	Specifies the Last Member Query Count value of this device
__readonly__	(Optional) Read Only
<i>cisLastMemberQueryCount</i>	(Optional) mib object cisLastMemberQueryCount

Command Mode

- /exec

show ip igmp snooping snmp mib lastMemeberQueryInterval

```
show ip igmp snooping snmp mib lastMemeberQueryInterval [ __readonly__ <cisLastMemberQueryInterval> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
lastMemeberQueryInterval	Specifies the IGMP Last Member Query Interval of this device
__readonly__	(Optional) Read Only
<i>cisLastMemberQueryInterval</i>	(Optional) mib object cisLastMemberQueryInterval

Command Mode

- /exec

show ip igmp snooping snmp mib leaveQueryType

show ip igmp snooping snmp mib leaveQueryType [__readonly__ <cisLeaveQueryType>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
leaveQueryType	Indicates type of leave query
__readonly__	(Optional) Read Only
<i>cisLeaveQueryType</i>	(Optional) mib object cisLeaveQueryType

Command Mode

- /exec

show ip igmp snooping snmp mib mcastGroupTable

```
show ip igmp snooping snmp mib mcastGroupTable [ vlan <cisMcastGroupVlanIndex-in>
<cisMcastGroupAddressType-in> <cisMcastGroupAddress-in> ][ __readonly__ TABLE_cisMcastGroupTable
<cisMcastGroupVlanIndex-out> <cisMcastGroupAddressType-out> <cisMcastGroupAddress-out>
<cisMcastGroupFilterMode> <cisMcastGroupIgmpVersion> <cisMcastGroupIncludeHostCount>
<cisMcastGroupExcludeHostCount> <cisMcastGroupPortList> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
mcastGroupTable	Show mib table cisMcastGroupTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMcastGroupVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>cisMcastGroupAddressType-in</i>	(Optional) Address type
<i>cisMcastGroupAddress-in</i>	(Optional) Group address
__readonly__	(Optional)
TABLE_cisMcastGroupTable	(Optional)
<i>cisMcastGroupVlanIndex-out</i>	(Optional) mib table index cisMcastGroupVlanIndex
<i>cisMcastGroupAddressType-out</i>	(Optional) mib table index cisMcastGroupAddressType
<i>cisMcastGroupAddress-out</i>	(Optional) mib table index cisMcastGroupAddress
<i>cisMcastGroupFilterMode</i>	(Optional) mib object cisMcastGroupFilterMode
<i>cisMcastGroupIgmpVersion</i>	(Optional) mib object cisMcastGroupIgmpVersion
<i>cisMcastGroupIncludeHostCount</i>	(Optional) mib object cisMcastGroupIncludeHostCount
<i>cisMcastGroupExcludeHostCount</i>	(Optional) mib object cisMcastGroupExcludeHostCount
<i>cisMcastGroupPortList</i>	(Optional) mib object cisMcastGroupPortList

Command Mode

- /exec

show ip igmp snooping snmp mib mcastRouterCfgTable

```
show ip igmp snooping snmp mib mcastRouterCfgTable [ interface <ifIndex-in> vlan
<cisMcastRouterVlanIndex-in> ] [ __readonly__ TABLE_cisMcastRouterCfgTable <ifIndex-out>
<cisMcastRouterVlanIndex-out> <cisMcastRouterType> <cisMcastRouterRowStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
mcastRouterCfgTable	show mib table cisMcastRouterCfgTable
interface	(Optional) Display Mcast Router Interface Information
<i>ifIndex-in</i>	(Optional) Specify the Mcast router interface
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMcastRouterVlanIndex-in</i>	(Optional) Specify VLAN/BD
__readonly__	(Optional)
TABLE_cisMcastRouterCfgTable	(Optional)
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisMcastRouterVlanIndex-out</i>	(Optional) mib table index cisMcastRouterVlanIndex
<i>cisMcastRouterType</i>	(Optional) mib object cisMcastRouterType
<i>cisMcastRouterRowStatus</i>	(Optional) mib object cisMcastRouterRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib mcastRouterConfigTable

```
show ip igmp snooping snmp mib mcastRouterConfigTable [ vlan <cisMcastRouterConfigVlanIndex-in>
interface <ifIndex-in> ] [ __readonly__ TABLE_cisMcastRouterConfigTable <ifIndex-out>
<cisMcastRouterConfigVlanIndex-out> <cisMcastRouterConfigRouterType>
<cisMcastRouterConfigStorageType> <cisMcastRouterConfigRowStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
mcastRouterConfigTable	show mib table cisMcastRouterConfigTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMcastRouterConfigVlanIndex-in</i>	(Optional) Specify VLAN/BD
interface	(Optional) Display Mcast Router Interface Information
<i>ifIndex-in</i>	(Optional) Specify the Mcast router interface index
__readonly__	(Optional)
TABLE_cisMcastRouterConfigTable	(Optional)
<i>cisMcastRouterConfigVlanIndex-out</i>	(Optional) mib table index cisMcastRouterConfigVlanIndex
<i>ifIndex-out</i>	(Optional) mib table index ifIndex
<i>cisMcastRouterConfigRouterType</i>	(Optional) mib object cisMcastRouterConfigRouterType
<i>cisMcastRouterConfigStorageType</i>	(Optional) mib object cisMcastRouterConfigStorageType
<i>cisMcastRouterConfigRowStatus</i>	(Optional) mib object cisMcastRouterConfigRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib multicastGroupConfigTable

```
show ip igmp snooping snmp mib multicastGroupConfigTable [ vlan <cisMulticastGroupConfVlanIndex-in>
<cisMulticastGroupConfCeVlanIndex-in> <cisMulticastGroupConfAddressType-in>
<cisMulticastGroupConfAddress-in> <cisMulticastGroupConfSourceAddress-in>
<cisMulticastGroupConfPortRange-in> ] [ __readonly__ TABLE_cisMulticastGroupConfigTable
<cisMulticastGroupConfVlanIndex-out> <cisMulticastGroupConfCeVlanIndex-out>
<cisMulticastGroupConfAddressType-out> <cisMulticastGroupConfAddress-out>
<cisMulticastGroupConfSourceAddress-out> <cisMulticastGroupConfPortRange-out>
<cisMulticastGroupConfPortList> <cisMulticastGroupConfStorageType> <cisMulticastGroupConfRowStatus>
]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
multicastGroupConfigTable	show mib table cisMulticastGroupConfigTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMulticastGroupConfVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>cisMulticastGroupConfCeVlanIndex-in</i>	(Optional) Specify consumer edge VLAN/BD
<i>cisMulticastGroupConfAddressType-in</i>	(Optional) Group Address Type
<i>cisMulticastGroupConfAddress-in</i>	(Optional) Group address
<i>cisMulticastGroupConfSourceAddress-in</i>	(Optional) source address
<i>cisMulticastGroupConfPortRange-in</i>	(Optional) port Range
__readonly__	(Optional)
TABLE_cisMulticastGroupConfigTable	(Optional)
<i>cisMulticastGroupConfVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupConfVlanIndex
<i>cisMulticastGroupConfCeVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupConfCeVlanIndex
<i>cisMulticastGroupConfAddressType-out</i>	(Optional) mib table index cisMulticastGroupConfAddressType
<i>cisMulticastGroupConfAddress-out</i>	(Optional) mib table index cisMulticastGroupConfAddress
<i>cisMulticastGroupConfSourceAddress-out</i>	(Optional) mib table index cisMulticastGroupConfSourceAddress

<i>cisMulticastGroupConfPortRange-out</i>	(Optional) mib table index cisMulticastGroupConfPortRange
<i>cisMulticastGroupConfPortList</i>	(Optional) mib object cisMulticastGroupConfPortList
<i>cisMulticastGroupConfStorageType</i>	(Optional) mib object cisMulticastGroupConfStorageType
<i>cisMulticastGroupConfRowStatus</i>	(Optional) mib object index cisMulticastGroupConfRowStatus

Command Mode

- /exec

show ip igmp snooping snmp mib multicastGroupPortListTable

```
show ip igmp snooping snmp mib multicastGroupPortListTable [ vlan <cisMulticastGroupVlanIndex-in>
<cisMulticastGroupCeVlanIndex-in> <cisMulticastGroupAddressType-in> <cisMulticastGroupAddress-in>
<cisMulticastGroupSourceAddress-in> <cisMulticastGroupPortRangeIndex-in> ] [ __readonly__
TABLE_ cisMulticastGroupPortListTable <cisMulticastGroupVlanIndex-out>
<cisMulticastGroupCeVlanIndex-out> <cisMulticastGroupAddressType-out> <cisMulticastGroupAddress-out>
<cisMulticastGroupSourceAddress-out> <cisMulticastGroupPortRangeIndex-out> <cisMulticastGroupPortList>
]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
multicastGroupPortListTable	show mib table multicastGroupPortListTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMulticastGroupVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>cisMulticastGroupCeVlanIndex-in</i>	(Optional) Specify consumer edge VLAN/BD
<i>cisMulticastGroupAddressType-in</i>	(Optional) Group Address Type
<i>cisMulticastGroupAddress-in</i>	(Optional) Group address
<i>cisMulticastGroupSourceAddress-in</i>	(Optional) source address
<i>cisMulticastGroupPortRangeIndex-in</i>	(Optional) port Range Index
<i>__readonly__</i>	(Optional)
TABLE_ <i>cisMulticastGroupPortListTable</i>	(Optional)
<i>cisMulticastGroupVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupVlanIndex
<i>cisMulticastGroupCeVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupCeVlanIndex
<i>cisMulticastGroupAddressType-out</i>	(Optional) mib table index cisMulticastGroupAddressType
<i>cisMulticastGroupAddress-out</i>	(Optional) mib table index cisMulticastGroupAddress
<i>cisMulticastGroupSourceAddress-out</i>	(Optional) mib table index cisMulticastGroupSourceAddress
<i>cisMulticastGroupPortRangeIndex-out</i>	(Optional) mib table index cisMulticastGroupPortRangeIndex

<i>cisMulticastGroupPortList</i>	(Optional) mib object cisMulticastGroupPortList
----------------------------------	---

Command Mode

- /exec

show ip igmp snooping snmp mib multicastGroupTable

```
show ip igmp snooping snmp mib multicastGroupTable [ vlan <cisMulticastGroupVlanIndex-in>
<cisMulticastGroupCeVlanIndex-in> <cisMulticastGroupAddressType-in> <cisMulticastGroupAddress-in>
<cisMulticastGroupSourceAddress-in> ] [ __readonly__ TABLE_cisMulticastGroupTable
<cisMulticastGroupVlanIndex-out> <cisMulticastGroupCeVlanIndex-out>
<cisMulticastGroupAddressType-out> <cisMulticastGroupAddress-out>
<cisMulticastGroupSourceAddress-out> <cisMulticastGroupGroupType> <cisMulticastGroupIgmpVersion>
<cisMulticastGroupSourceUpTime> <cisMulticastGroupSourceExpires> <cisMulticastGroupInclHostCount>
<cisMulticastGroupExclHostCount> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
multicastGroupTable	show mib table multicastGroupTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisMulticastGroupVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>cisMulticastGroupCeVlanIndex-in</i>	(Optional) Specify consumer edge VLAN/BD
<i>cisMulticastGroupAddressType-in</i>	(Optional) Group Address Type
<i>cisMulticastGroupAddress-in</i>	(Optional) Group address
<i>cisMulticastGroupSourceAddress-in</i>	(Optional) Source address
<i>__readonly__</i>	(Optional)
TABLE_cisMulticastGroupTable	(Optional)
<i>cisMulticastGroupVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupVlanIndex
<i>cisMulticastGroupCeVlanIndex-out</i>	(Optional) mib table index cisMulticastGroupCeVlanIndex
<i>cisMulticastGroupAddressType-out</i>	(Optional) mib table index cisMulticastGroupAddressType
<i>cisMulticastGroupAddress-out</i>	(Optional) mib table index cisMulticastGroupAddress
<i>cisMulticastGroupSourceAddress-out</i>	(Optional) mib table index cisMulticastGroupSourceAddress
<i>cisMulticastGroupGroupType</i>	(Optional) mib object cisMulticastGroupGroupType

<i>cisMulticastGroupIgmpVersion</i>	(Optional) mib object cisMulticastGroupIgmpVersion
<i>cisMulticastGroupSourceUpTime</i>	(Optional) mib object cisMulticastGroupSourceUpTime
<i>cisMulticastGroupSourceExpires</i>	(Optional) mib object cisMulticastGroupSourceExpires
<i>cisMulticastGroupInclHostCount</i>	(Optional) mib object cisMulticastGroupInclHostCount
<i>cisMulticastGroupExclHostCount</i>	(Optional) mib object cisMulticastGroupExclHostCount

Command Mode

- /exec

show ip igmp snooping snmp mib operMode

show ip igmp snooping snmp mib operMode [__readonly__ <cisOperMode>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
operMode	Indicates the operational snooping mode of the device
__readonly__	(Optional) Read Only
<i>cisOperMode</i>	(Optional) mib object cisOperMode

Command Mode

- /exec

show ip igmp snooping snmp mib querierTable

```
show ip igmp snooping snmp mib querierTable [ vlan <cisIgmpQuerierVlanIndex-in> ] [ __readonly__
TABLE_cisIgmpQuerierTable <cisIgmpQuerierVlanIndex-out> <cisIgmpQuerierEnabled>
<cisIgmpQuerierState> <cisIgmpQuerierVersion> <cisIgmpQuerierAddressType> <cisIgmpQuerierAddress>
<cisIgmpQuerierInterface> <cisIgmpQuerierTcnQueryCount> <cisIgmpQuerierTcnQueryInterval>
<cisIgmpQuerierTimerExpiry> <cisIgmpQuerierMaxResponseTime> <cisIgmpQuerierQueryInterval>
<cisIgmpQuerierAdminAddressType> <cisIgmpQuerierAdminAddress> <cisIgmpQuerierAdminVersion>
<cisIgmpQuerierTcnQueryPending> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
querierTable	Show mib table cisIgmpQuerierTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisIgmpQuerierVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>__readonly__</i>	(Optional)
<i>TABLE_cisIgmpQuerierTable</i>	(Optional)
<i>cisIgmpQuerierVlanIndex-out</i>	(Optional) mib table index cisIgmpQuerierVlanIndex
<i>cisIgmpQuerierEnabled</i>	(Optional) mib object cisIgmpQuerierEnabled
<i>cisIgmpQuerierState</i>	(Optional) mib object cisIgmpQuerierState
<i>cisIgmpQuerierVersion</i>	(Optional) mib object cisIgmpQuerierVersion
<i>cisIgmpQuerierAddressType</i>	(Optional) mib object cisIgmpQuerierAddressType
<i>cisIgmpQuerierAddress</i>	(Optional) mib object cisIgmpQuerierAddress
<i>cisIgmpQuerierInterface</i>	(Optional) mib object cisIgmpQuerierInterface
<i>cisIgmpQuerierTcnQueryCount</i>	(Optional) mib object cisIgmpQuerierTcnQueryCount
<i>cisIgmpQuerierTcnQueryInterval</i>	(Optional) mib object cisIgmpQuerierTcnQueryInterval
<i>cisIgmpQuerierTimerExpiry</i>	(Optional) mib object cisIgmpQuerierTimerExpiry
<i>cisIgmpQuerierMaxResponseTime</i>	(Optional) mib object cisIgmpQuerierMaxResponseTime

<i>cisIgmpQuerierQueryInterval</i>	(Optional) mib object cisIgmpQuerierQueryInterval
<i>cisIgmpQuerierAdminAddressType</i>	(Optional) mib object cisIgmpQuerierAdminAddressType
<i>cisIgmpQuerierAdminAddress</i>	(Optional) mib object cisIgmpQuerierAdminAddress
<i>cisIgmpQuerierAdminVersion</i>	(Optional) mib object cisIgmpQuerierAdminVersion
<i>cisIgmpQuerierTcnQueryPending</i>	(Optional) mib object cisIgmpQuerierTcnQueryPending

Command Mode

- /exec

show ip igmp snooping snmp mib reportsuppressionenabled

```
show ip igmp snooping snmp mib reportsuppressionenabled [ __readonly__ <cisReportSuppressionEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
reportsuppressionenabled	Check if reportsuppression is enabled
__readonly__	(Optional) Read Only
<i>cisReportSuppressionEnabled</i>	(Optional) mib object cisReportSuppressionEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib robustnessVariable

show ip igmp snooping snmp mib robustnessVariable [__readonly__ <cisRobustnessVariable>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
robustnessVariable	Specifies the Robustness Variable of this device
__readonly__	(Optional) Read Only
<i>cisRobustnessVariable</i>	(Optional) mib object cisRobustnessVariable

Command Mode

- /exec

show ip igmp snooping snmp mib routerAlertCheckEnabled

```
show ip igmp snooping snmp mib routerAlertCheckEnabled [ __readonly__ <cisLastMemberQueryCount> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
routerAlertCheckEnabled	Specifies whether checking of Router-Alert option is enabled for IGMP traffic in the system
__readonly__	(Optional) Read Only
<i>cisLastMemberQueryCount</i>	(Optional) mib object cisLastMemberQueryCount

Command Mode

- /exec

show ip igmp snooping snmp mib sourceOnlyEntryAgingTime

show ip igmp snooping snmp mib sourceOnlyEntryAgingTime [__readonly__
<cisSourceOnlyEntryAgingTime>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
sourceOnlyEntryAgingTime	Specifies the aging time in seconds for Source Only multicast entries
__readonly__	(Optional) Read Only
<i>cisSourceOnlyEntryAgingTime</i>	(Optional) mib object cisSourceOnlyEntryAgingTime

Command Mode

- /exec

show ip igmp snooping snmp mib sourceOnlyLearningEnabled

```
show ip igmp snooping snmp mib sourceOnlyLearningEnabled [ __readonly__  
<cisSourceOnlyLearningEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
sourceOnlyLearningEnabled	Specifies whether Source Only multicast entries are learned by IGMP Snooping or not
__readonly__	(Optional) Read Only
<i>cisSourceOnlyLearningEnabled</i>	(Optional) mib object cisSourceOnlyLearningEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib tcnFloodQueryCount

```
show ip igmp snooping snmp mib tcnFloodQueryCount [ __readonly__ <cisTopoChangeFloodQueryCount> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
tcnFloodQueryCount	Specifies the flooding period for multicast traffic upon receiving Topology Change Notifications
__readonly__	(Optional) Read Only
<i>cisTopoChangeFloodQueryCount</i>	(Optional) mib object cisTopoChangeFloodQueryCount

Command Mode

- /exec

show ip igmp snooping snmp mib timeToLiveCheckEnabled

```
show ip igmp snooping snmp mib timeToLiveCheckEnabled [ __readonly__ <cisTimeToLiveCheckEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
timeToLiveCheckEnabled	Specifies whether Time-To-Live (TTL) check is enabled when processing IGMP packets in the system
__readonly__	(Optional) Read Only
<i>cisTimeToLiveCheckEnabled</i>	(Optional) mib object cisTimeToLiveCheckEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib topoChanageQuerySolicitEnabled

```
show ip igmp snooping snmp mib topoChanageQuerySolicitEnabled [ __readonly__  
<cisTopoChangeQuerySolicitEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
topoChanageQuerySolicitEnabled	Specifies whether the device running IGMP Snooping will solicit IGMP General Queries from the Querier upon receiving a TCN
__readonly__	(Optional) Read Only
<i>cisTopoChangeQuerySolicitEnabled</i>	(Optional) mib object cisTopoChangeQuerySolicitEnabled

Command Mode

- /exec

show ip igmp snooping snmp mib v3ProcessEnabledAdminStatus

```
show ip igmp snooping snmp mib v3ProcessEnabledAdminStatus [ __readonly__  
<cisV3ProcessEnabledAdminStatus> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
v3ProcessEnabledAdminStatus	Indicates the administrative status of IGMP v3 processing in the system
__readonly__	(Optional) Read Only
<i>cisV3ProcessEnabledAdminStatus</i>	(Optional) mib object cisV3ProcessEnabledAdminStatus

Command Mode

- /exec

show ip igmp snooping snmp mib v3SnoopingSupport

show ip igmp snooping snmp mib v3SnoopingSupport [__readonly__ <cisV3SnoopingSupport>]

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
v3SnoopingSupport	Indicates IGMP Snooping support for IGMPv3
__readonly__	(Optional) Read Only
<i>cisV3SnoopingSupport</i>	(Optional) mib object cisV3SnoopingSupport

Command Mode

- /exec

show ip igmp snooping snmp mib vlanFilterConfigTable

```
show ip igmp snooping snmp mib vlanFilterConfigTable [ vlan <cisVlanIndex-in> ] [ __readonly__
TABLE_cisVlanFilterConfigTable <cisVlanIndex-out> <cisVlanFilterAccessGroup> <cisVlanFilterLimitMax>
<cisVlanFilterLimitExclAccessGrp> <cisVlanFilterMinVersionAllowed> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
vlanFilterConfigTable	Display VLAN/BD Filter Group
vlan	(Optional) Display Interface access group VLAN/BD information
<i>cisVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>__readonly__</i>	(Optional)
<i>TABLE_cisVlanFilterConfigTable</i>	(Optional)
<i>cisVlanIndex-out</i>	(Optional) mib talbe index cisVlanIndex>
<i>cisVlanFilterAccessGroup</i>	(Optional) mib table index cisVlanFilterAccessGroup
<i>cisVlanFilterLimitMax</i>	(Optional) mib object cisVlanFilterLimitMax
<i>cisVlanFilterLimitExclAccessGrp</i>	(Optional) mib object cisVlanFilterLimitExclAccessGrp
<i>cisVlanFilterMinVersionAllowed</i>	(Optional) mib object cisVlanFilterMinVersionAllowed

Command Mode

- /exec

show ip igmp snooping snmp mib vlanconfigtable

```
show ip igmp snooping snmp mib vlanconfigtable [ vlan <cisVlanIndex-in> ] [ __readonly__
TABLE_cisVlanConfigTable <cisVlanIndex-out> <cisVlanIgmpSnoopingEnabled>
<cisVlanFastLeaveEnabled> <cisVlanIgmpSnoopingOperMode> <cisVlanIgmpSnoopingLearningMode>
<cisVlanReportSuppressionEnabled> <cisVlanLeaveQueryInterval> <cisVlanLastMemberQueryCount>
<cisVlanRobustnessVariable> <cisVlanTimeToLiveCheckEnabled> <cisVlanRouterAlertCheckEnabled> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
snmp	Show SNMP
mib	Show MIB table
vlanconfigtable	Show mib table cisVlanConfigTable
vlan	(Optional) Display VLAN/BD IGMP snooping membership information
<i>cisVlanIndex-in</i>	(Optional) Specify VLAN/BD
<i>__readonly__</i>	(Optional)
TABLE_cisVlanConfigTable	(Optional)
<i>cisVlanIndex-out</i>	(Optional) mib table index cisVlanIndex
<i>cisVlanIgmpSnoopingEnabled</i>	(Optional) mib object cisVlanIgmpSnoopingEnabled
<i>cisVlanFastLeaveEnabled</i>	(Optional) mib object cisVlanFastLeaveEnabled
<i>cisVlanIgmpSnoopingOperMode</i>	(Optional) mib object cisVlanIgmpSnoopingOperMode
<i>cisVlanIgmpSnoopingLearningMode</i>	(Optional) mib object cisVlanIgmpSnoopingLearningMode
<i>cisVlanReportSuppressionEnabled</i>	(Optional) mib object cisVlanReportSuppressionEnabled
<i>cisVlanLeaveQueryInterval</i>	(Optional) mib object cisVlanLeaveQueryInterval
<i>cisVlanLastMemberQueryCount</i>	(Optional) mib object cisVlanLastMemberQueryCount
<i>cisVlanRobustnessVariable</i>	(Optional) mib object cisVlanRobustnessVariable
<i>cisVlanTimeToLiveCheckEnabled</i>	(Optional) mib object cisVlanTimeToLiveCheckEnabled
<i>cisVlanRouterAlertCheckEnabled</i>	(Optional) mib object cisVlanRouterAlertCheckEnabled

Command Mode

- /exec

show ip igmp snooping statistics

```
show ip igmp snooping statistics [ global | vlan <vlan> | bridge-domain <bdid> ] [ __readonly__ [ <pr> ] [
<inv_pkt> ] [ <pnv> ] [ <loopbkpkt> ] [ <mrdloopbk> ] [ <pf> ] [ <vpcdrqs> ] [ <vpcdrqr> ] [ <vpcdrqf> ] [
<vpcdrus> ] [ <vpcdrur> ] [ <vpcdruf> ] [ <vpccfssf> ] [ <vpccfsrs> ] [ <vpccfsrr> ] [ <vpccfsrf> ] [ <vpccfsrpf>
] [ <vpccfsurls> ] [ <vpccfsurlr> ] [ <vpccfsurlf> ] [ <vpccfsrls> ] [ <vpccfsrlr> ] [ <vpccfsrlf> ] [ <inv_iod>
] [ <stptcnr> ] [ <imapif> ] [ <mfreqr> ] [ <mfcmps> ] [ <mfdgcmps> ] [ <bufsnt> ] [ <bufackr> ] [
<vpcmismatch> ] [ { TABLE_vlan [ <vlan-id> ] [ <ut> ] [ <vpr> ] [ <v1rr> ] [ <v2rr> ] [ <v3rr> ] [ <v1qr>
] [ <v2qr> ] [ <v3qr> ] [ <v2lr> ] [ <phr> ] [ <irr> ] [ <iqr> ] [ <v1rs> ] [ <v2rs> ] [ <v2ls> ] [ <v3gs> ] [
<vmr> ] [ <upr> ] [ <qo> ] [ <v2ro> ] [ <v2lo> ] [ <v3ro> ] [ <vpsr> ] [ <str> ] [ <mps> ] [ <mpr> ] [ <mpe>
] [ <cps> ] [ <cpr> ] [ <cpe> ] [ <repflooded> ] [ <repfwded> ] } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
snooping	IGMP Snooping information
statistics	Display packet/error counter statistics
global	(Optional) Display global statistics
vlan	(Optional) Display VLAN statistics
<i>vlan</i>	(Optional) Specify VLAN
bridge-domain	(Optional) Display BD statistics
<i>bdid</i>	(Optional) Specify BD
__readonly__	(Optional)
<i>pr</i>	(Optional)
<i>inv_pkt</i>	(Optional)
<i>pnv</i>	(Optional)
<i>loopbkpkt</i>	(Optional)
<i>mrdloopbk</i>	(Optional)
<i>pf</i>	(Optional)
<i>vpcdrqs</i>	(Optional)
<i>vpcdrqr</i>	(Optional)
<i>vpcdrqf</i>	(Optional)
<i>vpcdrus</i>	(Optional)

<i>vpcdrur</i>	(Optional)
<i>vpcdruf</i>	(Optional)
<i>vpccfssf</i>	(Optional)
<i>vpccfsrs</i>	(Optional)
<i>vpccfsrr</i>	(Optional)
<i>vpccfsrf</i>	(Optional)
<i>vpccfsrfp</i>	(Optional)
<i>vpccfsurls</i>	(Optional)
<i>vpccfsurlr</i>	(Optional)
<i>vpccfsurlf</i>	(Optional)
<i>vpccfsrls</i>	(Optional)
<i>vpccfsrlr</i>	(Optional)
<i>vpccfsrlf</i>	(Optional)
<i>inv_iod</i>	(Optional)
<i>stptcnr</i>	(Optional)
<i>imapif</i>	(Optional)
<i>mfreqr</i>	(Optional)
<i>mfcmps</i>	(Optional)
<i>mfdgcmps</i>	(Optional)
<i>bufsnt</i>	(Optional)
<i>bufackr</i>	(Optional)
<i>vpcmismatch</i>	(Optional)
TABLE_vlan	(Optional)
<i>vlan-id</i>	(Optional)
<i>ut</i>	(Optional)
<i>vpr</i>	(Optional)
<i>v1rr</i>	(Optional)
<i>v2rr</i>	(Optional)
<i>v3rr</i>	(Optional)

<i>v1qr</i>	(Optional)
<i>v2qr</i>	(Optional)
<i>v3qr</i>	(Optional)
<i>v2lr</i>	(Optional)
<i>phr</i>	(Optional)
<i>irr</i>	(Optional)
<i>iqr</i>	(Optional)
<i>v1rs</i>	(Optional)
<i>v2rs</i>	(Optional)
<i>v2ls</i>	(Optional)
<i>v3gs</i>	(Optional)
<i>vmr</i>	(Optional)
<i>upr</i>	(Optional)
<i>qo</i>	(Optional)
<i>v2ro</i>	(Optional)
<i>v2lo</i>	(Optional)
<i>v3ro</i>	(Optional)
<i>vpsr</i>	(Optional)
<i>str</i>	(Optional)
<i>cps</i>	(Optional)
<i>cpr</i>	(Optional)
<i>cpe</i>	(Optional)
<i>mps</i>	(Optional)
<i>mpr</i>	(Optional)
<i>mpe</i>	(Optional)
<i>repflooded</i>	(Optional)
<i>repfwded</i>	(Optional)

Command Mode

- /exec

show ip igmp vrf all

```
show ip igmp vrf all [ __readonly__ { TABLE_vrfname <vrf-name> <vrf-id> <instance> <work-in-txlist> }
{ TABLE_vrfid <vrf-name-i> <vrf-id-i> <instance-i> <work-in-txlist-i> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
igmp	Display IGMP status and configuration
vrf	Display per-VRF information
all	Display information for all VRFs
__readonly__	(Optional)
TABLE_vrfname	(Optional)
<i>vrf-name</i>	(Optional)
<i>vrf-id</i>	(Optional)
<i>instance</i>	(Optional)
<i>work-in-txlist</i>	(Optional)
TABLE_vrfid	(Optional)
<i>vrf-name-i</i>	(Optional)
<i>vrf-id-i</i>	(Optional)
<i>instance-i</i>	(Optional)
<i>work-in-txlist-i</i>	(Optional)

Command Mode

- /exec

show ip interface

```
show ip interface { { { brief [ include-secondary ] } | [ <interface> ] | [ <ip-addr> ] } [ operational ] [ vaddr ]
[ vrf { <vrf-name> | <vrf-known-name> | all } } [ __readonly__ [ TABLE_vrf <vrf-name-out> ] [ TABLE_intf
<intf-name> <proto-state> <link-state> <admin-state> <iod> [ <first_unnum_iod> ] <prefix> <subnet>
<masklen> [ TABLE_unnuminf <unnum-child-inf> ] [ TABLE_secondary_address <prefix1> <subnet1>
<masklen1> ] [ <num-addr> ] [ <vaddr-client> ] [ <vaddr-prefix> ] [ <vaddr-subnet> ] [ <vaddr-masklen> ]
[ <num-vaddr> ] [ <unnum-intf> ] [ <ip-disabled> ] [ <bcast-addr> ] [ TABLE_maddr <maddr> ] [
<num-maddr> ] [ <mtu> ] [ <pref> ] [ <tag> ] [ <proxy-arp> ] [ <lcl-proxy-arp> ] [ <mrouting> ] [
<icmp-redirect> ] [ <dir-bcast> ] [ <ip-unreach> ] [ <port-unreach> ] [ <urpf-mode> ] [ <ip-ls-type> ] [
<urpf-acl> ] [ <pbr-in> ] [ <pbr-out> ] [ <acl-in> ] [ <acl-out> ] [ <stats-last-reset> ] [ <upkt-sent> ] [
<upkt-recv> ] [ <upkt-fwd> ] [ <upkt-orig> ] [ <upkt-consumed> ] [ <ubyte-sent> ] [ <ubyte-recv> ] [
<ubyte-fwd> ] [ <ubyte-orig> ] [ <ubyte-consumed> ] [ <mpkt-sent> ] [ <mpkt-recv> ] [ <mpkt-fwd> ] [
<mpkt-orig> ] [ <mpkt-consumed> ] [ <mbyte-sent> ] [ <mbyte-recv> ] [ <mbyte-fwd> ] [ <mbyte-orig> ] [
<mbyte-consumed> ] [ <bpkt-sent> ] [ <bpkt-recv> ] [ <bpkt-fwd> ] [ <bpkt-orig> ] [ <bpkt-consumed> ] [
<bbyte-sent> ] [ <bbyte-recv> ] [ <bbyte-fwd> ] [ <bbyte-orig> ] [ <bbyte-consumed> ] [ <lpkt-sent> ] [
<lpkt-recv> ] [ <lpkt-fwd> ] [ <lpkt-orig> ] [ <lpkt-consumed> ] [ <lbyte-sent> ] [ <lbyte-recv> ] [ <lbyte-fwd>
] [ <lbyte-orig> ] [ <lbyte-consumed> ] ] ] }
```

Syntax Description

show	Show running system information
ip	Display IP information
interface	Display IP related interface information
brief	Display summary of IP interface status and configuration
include-secondary	(Optional) Display summary of all IP addresses
operational	(Optional) Display only interfaces that are administratively enabled
<i>interface</i>	(Optional) Interface name to display
<i>ip-addr</i>	(Optional) Display interface for local IP address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display all VRFs
vaddr	(Optional) Display virtual IP addresses as well
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_intf	(Optional)

<i>intf-name</i>	(Optional)
<i>iod</i>	(Optional)
<i>first_unnum_iod</i>	(Optional)
<i>prefix</i>	(Optional)
<i>proto-state</i>	(Optional)
<i>link-state</i>	(Optional)
<i>admin-state</i>	(Optional)
<i>subnet</i>	(Optional)
<i>masklen</i>	(Optional)
TABLE_unnuminf	(Optional)
<i>unnum-child-inf</i>	(Optional)
TABLE_secondary_address	(Optional)
<i>prefix1</i>	(Optional)
<i>subnet1</i>	(Optional)
<i>masklen1</i>	(Optional)
<i>num-addr</i>	(Optional)
<i>vaddr-client</i>	(Optional)
<i>vaddr-prefix</i>	(Optional)
<i>vaddr-subnet</i>	(Optional)
<i>vaddr-masklen</i>	(Optional)
<i>num-vaddr</i>	(Optional)
<i>unnum-intf</i>	(Optional)
<i>ip-disabled</i>	(Optional)
<i>bcast-addr</i>	(Optional)
TABLE_maddr	(Optional)
<i>maddr</i>	(Optional)
<i>num-maddr</i>	(Optional)
<i>mtu</i>	(Optional)
<i>pref</i>	(Optional)

<i>tag</i>	(Optional)
<i>proxy-arp</i>	(Optional)
<i>lcl-proxy-arp</i>	(Optional)
<i>mrouting</i>	(Optional)
<i>icmp-redirect</i>	(Optional)
<i>dir-bcast</i>	(Optional)
<i>ip-unreach</i>	(Optional)
<i>port-unreach</i>	(Optional)
<i>urpf-mode</i>	(Optional)
<i>ip-ls-type</i>	(Optional)
<i>urpf-acl</i>	(Optional)
<i>pbr-in</i>	(Optional)
<i>pbr-out</i>	(Optional)
<i>acl-in</i>	(Optional)
<i>acl-out</i>	(Optional)
<i>stats-last-reset</i>	(Optional)
<i>upkt-sent</i>	(Optional)
<i>upkt-recv</i>	(Optional)
<i>upkt-fwd</i>	(Optional)
<i>upkt-orig</i>	(Optional)
<i>upkt-consumed</i>	(Optional)
<i>ubyte-sent</i>	(Optional)
<i>ubyte-recv</i>	(Optional)
<i>ubyte-fwd</i>	(Optional)
<i>ubyte-orig</i>	(Optional)
<i>ubyte-consumed</i>	(Optional)
<i>mpkt-sent</i>	(Optional)
<i>mpkt-recv</i>	(Optional)
<i>mpkt-fwd</i>	(Optional)

<i>mpkt-orig</i>	(Optional)
<i>mpkt-consumed</i>	(Optional)
<i>mbyte-sent</i>	(Optional)
<i>mbyte-recv</i>	(Optional)
<i>mbyte-fwd</i>	(Optional)
<i>mbyte-orig</i>	(Optional)
<i>mbyte-consumed</i>	(Optional)
<i>bpkt-sent</i>	(Optional)
<i>bpkt-recv</i>	(Optional)
<i>bpkt-fwd</i>	(Optional)
<i>bpkt-orig</i>	(Optional)
<i>bpkt-consumed</i>	(Optional)
<i>bbyte-sent</i>	(Optional)
<i>bbyte-recv</i>	(Optional)
<i>bbyte-fwd</i>	(Optional)
<i>bbyte-orig</i>	(Optional)
<i>bbyte-consumed</i>	(Optional)
<i>lpkt-sent</i>	(Optional)
<i>lpkt-recv</i>	(Optional)
<i>lpkt-fwd</i>	(Optional)
<i>lpkt-orig</i>	(Optional)
<i>lpkt-consumed</i>	(Optional)
<i>lbyte-sent</i>	(Optional)
<i>lbyte-recv</i>	(Optional)
<i>lbyte-fwd</i>	(Optional)
<i>lbyte-orig</i>	(Optional)
<i>lbyte-consumed</i>	(Optional)

Command Mode

- /exec

show ip lisp

```
show { ip | ipv6 } lisp [ database ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
database	(Optional) Show EID-prefixes configured for site
vrf	(Optional) Display information for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show ip lisp data-cache

```
show ip lisp data-cache [ <eid> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
lisp	LISP show commands
data-cache	Display EID-to-RLOC data cache mapping in this ITR
<i>eid</i>	(Optional) Display mapping for IP destination EID
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show ip lisp locator-hash

```
{ { show ip lisp locator-hash { <eid-prefix> | { <source-eid> <dest-eid> } } [ vrf { <vrf-name> |
<vrf-known-name> } ] } | { show ipv6 lisp locator-hash { <eid-prefix6> | { <source-eid6> <dest-eid6> } } [
vrf { <vrf-name> | <vrf-known-name> } ] } }
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
locator-hash	Display source and dest locators for EID pair
<i>source-eid</i>	Source IPv4 endpoint identifier (EID)
<i>dest-eid</i>	Destination IPv4 endpoint identifier (EID)
<i>eid-prefix</i>	Display exact match for IP EID-prefix entry
vrf	(Optional) Display information for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show ip lisp map-cache

```
{ { show ip lisp map-cache [ <eid> | <eid-prefix> | detail ] [ vrf { <vrf-name> | <vrf-known-name> } ] } | {  
show ipv6 lisp map-cache [ <eid6> | <eid-prefix6> | detail ] [ vrf { <vrf-name> | <vrf-known-name> } ] } }
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
map-cache	Display EID-to-RLOC cache mapping in this ITR
vrf	(Optional) Display information for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>eid</i>	(Optional) Display mapping for IP destination EID
<i>eid-prefix</i>	(Optional) Display exact match for IP EID-prefix entry
detail	(Optional) Display entire map-cache in long format

Command Mode

- /exec

show ip lisp statistics

```
show { ip | ipv6 } lisp statistics [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
statistics	Display global LISP statistics
vrf	(Optional) Display statistics information for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show ip lisp translate-cache

{ show ip lisp translate-cache [<nrEID>] } | { show ipv6 lisp translate-cache [<nrEID6>] }

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
translate-cache	Display configured translation cache
<i>nrEID</i>	(Optional) IPv4 address of inside non-routable EID
<i>nrEID6</i>	(Optional) IPv6 address of inside non-routable EID

Command Mode

- /exec

show ip lisp version-hash

show { ip | ipv6 } lisp version-hash { <eid-prefix> | <eid-prefix6> }

Syntax Description

show	Show running system information
ip	Display IP information
ipv6	Display IPv6 information
lisp	LISP show commands
version-hash	Display version-hash for EID-record
<i>eid-prefix</i>	Local IP EID-prefix from database-mapping command

Command Mode

- /exec

show ip load-sharing

```
show ip load-sharing [ __readonly__ { <univer-id-ran-seed> [ <l3-msg-load> ] [ <l34-msg-load> ] [
<dest-addr-load> ] [ <src-dst-ip-gre> ] [ <bad-load> ] [ <gre-outer-hash> ] [ <concatenation> ] [ <rotate> ] [
<src-dst-ip-gtpu> ] } ]
```

Syntax Description

show	Show running system information
ip	Configure IP features
load-sharing	Display global loadbalance info
__readonly__	(Optional)
<i>univer-id-ran-seed</i>	(Optional)
<i>l3-msg-load</i>	(Optional)
<i>l34-msg-load</i>	(Optional)
<i>dest-addr-load</i>	(Optional)
<i>src-dst-ip-gre</i>	(Optional)
<i>bad-load</i>	(Optional)
<i>gre-outer-hash</i>	(Optional)
<i>concatenation</i>	(Optional)
<i>rotate</i>	(Optional)
<i>src-dst-ip-gtpu</i>	(Optional)

Command Mode

- /exec

show ip local-pt

show ip local-pt [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

show	Show running system information
ip	Display IP information
local-pt	Display local ip address ptree
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

show ip local policy

```
show ip local policy [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_pbr [ <interface> ] [ <rmap> ] [ <status> ] [ <vrf_name> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
local	IP local options
policy	Policy routing
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_pbr	(Optional)
<i>interface</i>	(Optional)
<i>rmap</i>	(Optional)
<i>status</i>	(Optional)
<i>vrf_name</i>	(Optional)

Command Mode

- /exec

show ip logging

show ip logging [hash] [__readonly__]

Syntax Description

show	Show running system information
ip	Display IP information
logging	Display IP policy logging table
hash	(Optional) logging hash data
__readonly__	(Optional)

Command Mode

- /exec

show ip mbgp

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } { route-map { <rmap-name> | <rmap-name> } | filter-list { <fltrlist-name> | <test_pol_name> } | {
community-list { <commlist-name> | <test_pol_name> } | extcommunity-list { <extcommmlist-name> |
<test_pol_name> } } [ exact-match ] } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
route-map	Display routes matching the route-map
<i>rmap-name</i>	Route-map name
<i>rmap-name</i>	Known route-map name
filter-list	Display routes matching the filter-list
<i>fltrlist-name</i>	Name of filter-list
community-list	Display routes matching the community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>commlist-name</i>	Name of community-list
<i>extcommmlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families
exact-match	(Optional) Exact match of the communities

Command Mode

- /exec

show ip mbgp

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast | mdt } |
all } ] } ] [ <ip-addr> [ <ip-mask> [ longer-prefixes ] ] | <ip-prefix> [ longer-prefixes ] ] [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ] }
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ip-addr</i>	(Optional) Display one particular network from the BRIB in detail
<i>ip-mask</i>	(Optional) Mask for one particular prefix in the BRIB
<i>ip-prefix</i>	(Optional) Display one particular prefix from the BRIB in detail
longer-prefixes	(Optional) Display route and more specific routes
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
mdt	(Optional) Display BGP information for multicast distribution tree
all	(Optional) Display BGP information for all address families

Command Mode

- /exec

show ip mbgp community

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } community { <regex-str> | { { <comm-id> | <wellknown-id> } + [ exact-match ] } } [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display BGP information for all address families
community	Display routes matching the BGP communities
<i>regex-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities

Command Mode

- /exec

show ip mbgp dampening

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { ipv4 { unicast | multicast } | all }
] } } dampening { dampened-paths [ regexp <regexp-str> ] | flap-statistics | parameters | history-paths [ regexp
<regexp-str> ] } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
dampened-paths	Display all dampened paths
flap-statistics	Display flap statistics for routes
parameters	Display dampening parameters
history-paths	Display all history paths
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths

Command Mode

- /exec

show ip mbgp extcommunity

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { ipv4 { unicast | multicast } | all }
] } } extcommunity { <regexp-str> | { { 4byteas-generic { transitive <ext-comm-gen-trans> | non-transitive
<ext-comm-gen-nontrans> } } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] }
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display BGP information for all address families
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>regexp-str</i>	Regular expression to match the extcommunities
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities

Command Mode

- /exec

show ip mbgp flap-statistics

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
<i>ip-prefix</i>	(Optional) Display flap statistics for one prefix
<i>ip-addr</i>	(Optional) Display flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families

Command Mode

- /exec

show ip mbgp neighbors

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } neighbors { [ { <neighbor-id> | <ipv6-neighbor-id> } [ routes [ advertised | received | dampened ] |
advertised-routes | received-routes | paths | flap-statistics ] ] | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id>
} [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] }
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	Display details for a prefix peering
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families
routes	(Optional) Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer
advertised-routes	(Optional) Display all the routes advertised to this peer
received-routes	(Optional) Display all the routes received from this peer
flap-statistics	(Optional) Display flap statistics for routes received from this peer
paths	(Optional) Display AS paths learned from this peer

Command Mode

- /exec

show ip mbgp nexthop-database

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } nexthop-database [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop-database	Display nexthop database
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families

Command Mode

- /exec

show ip mbgp nexthop

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | bgp [ vrf {  
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ ipv4 { unicast | multicast } ] } nexthop  
<ipnexthop> [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop	Display routes matching the nexthop
<i>ipnexthop</i>	Nexthop address
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family

Command Mode

- /exec

show ip mbgp prefix-list

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ ipv4 { unicast | multicast } ] } }
prefix-list { <prfxlist-name> | <test_pol_name> } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
<i>test_pol_name</i>	An existing test-list policy
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family

Command Mode

- /exec

show ip mbgp received-paths

```
show ip { mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] | { bgp [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ipv4 { unicast | multicast } | all }
] } } received-paths [ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
ipv4	(Optional) Display BGP information for IPv4 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
all	(Optional) Display BGP information for all address families
private	(Optional) private

Command Mode

- /exec

show ip msdp count

```
show ip msdp count [ <asn> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <out-vrf>
<total-cnt> [ TABLE_asn <out-asn> <src-cnt> <grp-cnt> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
count	Display SA cache counters
<i>asn</i>	(Optional) AS number
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>__readonly__</i>	(Optional)
<i>out-vrf</i>	(Optional)
<i>total-cnt</i>	(Optional)
TABLE_asn	(Optional)
<i>out-asn</i>	(Optional)
<i>src-cnt</i>	(Optional)
<i>grp-cnt</i>	(Optional)

Command Mode

- /exec

show ip msdp event-history

show ip msdp [<asn>] [internal] event-history { errors | msgs | <msdp-event-hist-buf-name> | statistics }

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
<i>asn</i>	(Optional) AS number
internal	(Optional) Commands for internal use
event-history	Show various event logs of MSDP
errors	Error logs of MSDP
msgs	Message logs of MSDP
<i>msdp-event-hist-buf-name</i>	Buffer
statistics	Buffer state

Command Mode

- /exec

show ip msdp mesh-group

```
show ip msdp mesh-group [ <mesh-group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
<out-vrf> [ TABLE_meshgroup [ <meshgroup-name> ] [ TABLE_peer [ <peer-ipaddr> ] [ <peer-asn> ] [
<peer-description> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
mesh-group	Display members of mesh-group
<i>mesh-group</i>	(Optional) Display single mesh-group
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-vrf</i>	(Optional)
TABLE_meshgroup	(Optional)
<i>meshgroup-name</i>	(Optional)
TABLE_peer	(Optional)
<i>peer-ipaddr</i>	(Optional)
<i>peer-asn</i>	(Optional)
<i>peer-description</i>	(Optional)

Command Mode

- /exec

show ip msdp peer

```
show ip msdp peer [ <peer-address> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [
TABLE_peer [ <peer-ipaddr> ] [ <out-vrf> ] [ <peer-asn> ] [ <local-ipaddr> ] [ <local-iface> ] [
<fully-configured> ] [ <peer-description> ] [ <connection-status> ] [ <peer-listening> ] [ <state-duration> ]
[ <peer-uptime> ] [ <peer-rr> ] [ <peer-password> ] [ <peer-ki> ] [ <peer-kt> ] [ <peer-ri> ] [ <sa-in-policy>
] [ <sa-out-policy> ] [ <sa-limit> ] [ <mesh-name> ] [ <last-rcvd> ] [ <sa-rcvd> ] [ <sa-sent> ] [ <sa-req-rcvd>
] [ <sa-req-sent> ] [ <sa-resp-rcvd> ] [ <sa-resp-sent> ] [ <in-ctrl-msgs> ] [ <out-ctrl-msgs> ] [ <in-data-msgs>
] [ <out-data-msgs> ] [ <sa-ka-rcvd> ] [ <sa-ka-sent> ] [ <sa-notif-rcvd> ] [ <sa-notif-sent> ] [ <rem-port> ]
[ <local-port> ] [ <rpf-failures> ] [ <cache-lifetime> ] [ <estb-transitions> ] [ <conn-attempts> ] [ <discont-time>
] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
peer	Display MSDP peer information
<i>peer-address</i>	(Optional) IP address of MSDP peer
__readonly__	(Optional)
TABLE_peer	(Optional)
<i>peer-ipaddr</i>	(Optional)
<i>out-vrf</i>	(Optional)
<i>peer-asn</i>	(Optional)
<i>local-ipaddr</i>	(Optional)
<i>local-iface</i>	(Optional)
<i>fully-configured</i>	(Optional)
<i>peer-description</i>	(Optional)
<i>connection-status</i>	(Optional)
<i>state-duration</i>	(Optional)
<i>peer-listening</i>	(Optional)

<i>peer-uptime</i>	(Optional)
<i>peer-password</i>	(Optional)
<i>peer-ki</i>	(Optional)
<i>peer-kt</i>	(Optional)
<i>peer-ri</i>	(Optional)
<i>peer-rr</i>	(Optional)
<i>sa-in-policy</i>	(Optional)
<i>sa-out-policy</i>	(Optional)
<i>sa-limit</i>	(Optional)
<i>mesh-name</i>	(Optional)
<i>last-rcvd</i>	(Optional)
<i>sa-rcvd</i>	(Optional)
<i>sa-sent</i>	(Optional)
<i>sa-req-rcvd</i>	(Optional)
<i>sa-req-sent</i>	(Optional)
<i>sa-resp-rcvd</i>	(Optional)
<i>sa-resp-sent</i>	(Optional)
<i>out-ctrl-msgs</i>	(Optional)
<i>in-ctrl-msgs</i>	(Optional)
<i>out-data-msgs</i>	(Optional)
<i>in-data-msgs</i>	(Optional)
<i>sa-ka-rcvd</i>	(Optional)
<i>sa-ka-sent</i>	(Optional)
<i>sa-notif-rcvd</i>	(Optional)
<i>sa-notif-sent</i>	(Optional)
<i>rem-port</i>	(Optional)
<i>local-port</i>	(Optional)
<i>rpf-failures</i>	(Optional)
<i>cache-lifetime</i>	(Optional)

<i>estb-transitions</i>	(Optional)
<i>conn-attempts</i>	(Optional)
<i>discont-time</i>	(Optional)

Command Mode

- /exec

show ip msdp policy statistics sa-policy in

```
show ip msdp policy statistics sa-policy <peer-address> { in | out } [ vrf { <vrf-name> | <vrf-known-name>
} ] [ __readonly__ [ TABLE_routemap [ <name> ] [ <seq_num> ] [ <action> ] [ [ TABLE_cmd [ <command>
] [ <match_count> ] [ <compare_count> ] ] ] ] [ <total_accept_count> ] [ <total_reject_count> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	MSDP global configuration commands
policy	Policy information
statistics	Policy statistics
sa-policy	Configured SA policy for MSDP peer
<i>peer-address</i>	IP address of MSDP peer for SA policy
in	Input policy
out	Output policy
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_routemap	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seq_num</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>compare_count</i>	(Optional)
<i>match_count</i>	(Optional)
<i>total_accept_count</i>	(Optional)
<i>total_reject_count</i>	(Optional)

Command Mode

- /exec

show ip msdp rpf

```
show ip msdp rpf <rp-address> [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <out-rp-address>
<out-vrf> [ TABLE_mesh [ <peer-addr> ] [ <mesh-name> ] ] [ <is-peer-cnt-one> ] [ <is-rp-peer> ] [
<is-bgp-alive> ] [ <bgp-peer-addr> ] [ <peer-asn> ] [ <origin-asn> ] [ <is-mbgp> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
rpf	Display RPF-peer for RP address
<i>rp-address</i>	IP address of RP
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-rp-address</i>	(Optional)
<i>out-vrf</i>	(Optional)
TABLE_mesh	(Optional)
<i>peer-addr</i>	(Optional)
<i>mesh-name</i>	(Optional)
<i>is-peer-cnt-one</i>	(Optional)
<i>is-rp-peer</i>	(Optional)
<i>is-bgp-alive</i>	(Optional)
<i>bgp-peer-addr</i>	(Optional)
<i>peer-asn</i>	(Optional)
<i>origin-asn</i>	(Optional)
<i>is-mbgp</i>	(Optional)

Command Mode

- /exec

show ip msdp sa

```
show ip msdp { sa-cache | route } [ { <source> [ <group> ] } | { <group> [ <source> ] } ] [ <asn> ] [ peer
<peer> ] [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ <out-vrf> ] [
<total-sa-count> ] [ TABLE_sa [ <src-addr> ] [ <grp-addr> ] [ <rp-addr> ] [ <out-asn> ] [ <peer-addr> ] [
<uptime> ] [ <expire> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
route	Display MSDP SA route cache
sa-cache	Display MSDP SA route cache
<i>source</i>	(Optional) Display group/source address for SA
<i>group</i>	(Optional) Display group/source address for SA
<i>asn</i>	(Optional) AS number
detail	(Optional) Display detailed information
peer	(Optional) Display MSDP SA received from single peer
<i>peer</i>	(Optional) IP address of peer for SA
__readonly__	(Optional)
<i>out-vrf</i>	(Optional)
<i>total-sa-count</i>	(Optional)
TABLE_sa	(Optional)
<i>src-addr</i>	(Optional)
<i>grp-addr</i>	(Optional)
<i>rp-addr</i>	(Optional)
<i>peer-addr</i>	(Optional)

<i>out-asn</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expire</i>	(Optional)

Command Mode

- /exec

show ip msdp sources

```
show ip msdp sources [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ <out-vrf> ] [
TABLE_source [ <source-addr> ] [ <is-count-ge-limit> ] [ <count> ] [ <is-limit-valid> ] [ <limit> ] [
<source-prefix> ] [ <violates> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
sources	Display learned sources with their group counts and limits
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-vrf</i>	(Optional)
TABLE_source	(Optional)
<i>source-addr</i>	(Optional)
<i>is-count-ge-limit</i>	(Optional)
<i>count</i>	(Optional)
<i>is-limit-valid</i>	(Optional)
<i>limit</i>	(Optional)
<i>source-prefix</i>	(Optional)
<i>violates</i>	(Optional)

Command Mode

- /exec

show ip msdp statistics

```
show ip msdp statistics [ <peer-address> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
<out-vrf> <select-err> <recv-sel-err> { TABLE_peer <peer-address> <buffer-full> <recv-buf-full> <fatal-err>
<recv-fat-err> <would-block> <recv-would-block> <sock-exp> <invalid-type> <invalid-len> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
statistics	Display internal statistics
<i>peer-address</i>	(Optional) IP address of MSDP peer
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-vrf</i>	(Optional)
<i>select-err</i>	(Optional)
<i>recv-sel-err</i>	(Optional)
TABLE_peer	(Optional)
<i>peer-address</i>	(Optional)
<i>buffer-full</i>	(Optional)
<i>recv-buf-full</i>	(Optional)
<i>fatal-err</i>	(Optional)
<i>recv-fat-err</i>	(Optional)
<i>would-block</i>	(Optional)
<i>recv-would-block</i>	(Optional)
<i>sock-exp</i>	(Optional)
<i>invalid-type</i>	(Optional)
<i>invalid-len</i>	(Optional)

Command Mode

- /exec

show ip msdp summary

```
show ip msdp summary [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ <out-vrf> ] [
<local-asn> ] [ <originator-id> ] [ <config-peer-count> ] [ <estb-peer-count> ] [ <shut-peer-count> ] [
TABLE_peer [ <peer-address> ] [ <peer-asn> ] [ <peer-state> ] [ <peer-uptime> ] [ <peer-last-msg> ] [
<peer-sa-rcvd> ] [ <peer-sa-limit> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
msdp	Display MSDP status and configuration
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
summary	Display MSDP peer summary
__readonly__	(Optional)
<i>out-vrf</i>	(Optional)
<i>local-asn</i>	(Optional)
<i>originator-id</i>	(Optional)
<i>config-peer-count</i>	(Optional)
<i>estb-peer-count</i>	(Optional)
<i>shut-peer-count</i>	(Optional)
TABLE_peer	(Optional)
<i>peer-address</i>	(Optional)
<i>peer-asn</i>	(Optional)
<i>peer-state</i>	(Optional)
<i>peer-uptime</i>	(Optional)
<i>peer-last-msg</i>	(Optional)
<i>peer-sa-rcvd</i>	(Optional)
<i>peer-sa-limit</i>	(Optional)

Command Mode

- /exec

show ip nat-alias

show ip nat-alias

Syntax Description

show	Show running system information
ip	Display IP information
nat-alias	Display aliases registered by NAT module

Command Mode

- /exec

show ip nat max

```
show ip nat max [ __readonly__ <max_dyn_translations> <max_all_host> <static_translations>  
<dynamic_translations> <icmp_translations> ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
nat	IP NAT information
max	IP NAT max values
__readonly__	(Optional)
<i>max_dyn_translations</i>	(Optional) Max Dynamic Translations
<i>max_all_host</i>	(Optional) Max All Hosts
<i>static_translations</i>	(Optional) No. Static Translations
<i>dynamic_translations</i>	(Optional) No. Dynamic Translations
<i>icmp_translations</i>	(Optional) No. ICMP Translations

Command Mode

- /exec

show ip nat statistics

show ip nat statistics

Syntax Description

show	Show running system information
ip	Show the IP features of the system
nat	IP NAT information
statistics	Translation statistics

Command Mode

- /exec

Example

```
switch# show show ip nat statistics
Pro Inside global Inside local Outside local Outside global
uIP NAT Statistics
=====
Total active translations: 2
No.Static: 2
No.Dyn: 0
No.ICMP: 0
-----
Total expired Translations: 0
SYN timer expired:0
FIN-RST timer expired:0
Inactive timer expired: 0
-----
Total Hits: 0Total Misses: 3
In-Out Hits: 0In-Out Misses: 0
Out-In Hits: 0Out-In Misses: 3
-----
Total SW Translated Packets: 0
In-Out SW Translated: 0
Out-In SW Translated: 0
-----
Total SW Dropped Packets: 0
In-Out SW Dropped: 0
Out-In SW Dropped: 0
Address alloc. failure drop: 0
Port alloc. failure drop: 0
Dyn. Translation max limit drop: 0
ICMP max limit drop: 0
Allhost max limit drop: 0
-----
NAT Inside Interfaces: 1
Ethernet1/1
NAT Outside Interfaces: 1
Ethernet1/3
-----
Inside source list:
+++++++
Access list: ACL1
```

```
RefCount: 0
Pool: pool1 Overload
Total addresses: 200
Allocated: 0 percentage: 0%
Missed: 0
```

show ip nat timeout

```
show ip nat timeout [ __readonly__ <tcp_timeout> <udp_timeout> <dynamic_timeout> [ <sampling_timeout> ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
nat	IP NAT information
timeout	IP NAT timeout values
<i>__readonly__</i>	(Optional)
<i>tcp_timeout</i>	(Optional) TCP Timeout
<i>udp_timeout</i>	(Optional) UDP Timeout
<i>dynamic_timeout</i>	(Optional) Dynamic Timeout
<i>sampling_timeout</i>	(Optional) Sampling Timeout

Command Mode

- /exec

show ip nat translations

```
show ip nat translations [ vrf { <vrf-name> | <vrf-known-name> } ] [ verbose ] [ __readonly__ {
TABLE_nat_translation [ <Protocol> ] [ <Inside_global_IP_V4_Address> ] [ <Inside_global_port> ] [
<Inside_local_IP_V4_Address> ] [ <Inside_local_port> ] [ <Outside_local_IP_V4_Address> ] [
<Outside_local_port> ] [ <Outside_global_IP_V4_Address> ] [ <Outside_global_port> ] [ <Flags> ] [
<In_stats_count> ] [ <Out_stats_count> ] [ <Entry_id> ] [ <State> ] [ <Group_id> ] [ <VRF> ] [ <Time_left>
] [ <Syn> ] [ <Fin_rst> } } ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
nat	IP NAT information
translations	Translation entries
verbose	(Optional) Show extra information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Readonly
TABLE_nat_translation	(Optional) NAT Translation Table
<i>Protocol</i>	(Optional) Protocol
<i>Inside_global_IP_V4_Address</i>	(Optional) Inside global address
<i>Inside_global_port</i>	(Optional) Inside global port
<i>Inside_local_IP_V4_Address</i>	(Optional) Inside local address
<i>Inside_local_port</i>	(Optional) Inside local port
<i>Outside_local_IP_V4_Address</i>	(Optional) Outside local address
<i>Outside_local_port</i>	(Optional) Outside local port
<i>Outside_global_IP_V4_Address</i>	(Optional) Outside global address
<i>Outside_global_port</i>	(Optional) Outside global port
<i>Flags</i>	(Optional) Flags
<i>In_stats_count</i>	(Optional) In stats count
<i>Out_stats_count</i>	(Optional) Out stats count

<i>Entry_id</i>	(Optional) Entry ID
<i>State</i>	(Optional) State
<i>Group_id</i>	(Optional) Group ID
<i>VRF</i>	(Optional) VRF
<i>Time_left</i>	(Optional) Time Left (HH:MM:SS)
<i>Syn</i>	(Optional) Syn
<i>Fin_rst</i>	(Optional) FIN RESET

Command Mode

- /exec

show ip ospf

```
show ip ospf [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag>
<instance_number> <cname> <rid> [ <domain_tag> ] [ <dn_bit_ignore> ] <stateful_ha> <gr_ha> [
<gr_planned_only> ] [ <gr_notify_period> ] [ <gr_grace_period> ] [ <gr_state> ] [ <gr_last_status> ] [
<gr_helper_mode> ] <support_tos0_only> <support_opaque_lsa> [ <low_mem_cond> ] <is_abr> <is_asbr>
[ <max_lsa_non_self_number> ] [ <max_lsa_state> ] [ <max_lsa_warning_only> ] [
<max_lsa_current_non_self_lsa_number> ] [ <max_lsa_threshold_pct> ] [ <max_lsa_ignore_time> ] [
<max_lsa_reset_time> ] [ <max_lsa_ignore_count> ] [ <max_lsa_current_ignore_count> ] [
<max_lsa_ignore_time_left> ] [ <max_lsa_reset_time_left> ] [ <max_lsa_permanent_ignore> ] [ {
TABLE_redist <proto> [ <max_lsas> ] [ <warning> ] [ <threshold> ] [ <current_count> ] } ] <admin_dist>
<ref_bw> <spf_start_time> <spf_hold_time> <spf_max_time> <lsa_start_time> <lsa_hold_time>
<lsa_max_time> <min_lsa_arr_time> <lsa_aging_pace> <spf_max_paths> <max_metric_adver> [ [
<max_metric_time_left> ] [ <max_metric_wait_bgp> ] [ <max_metric_timeout> ] [ <max_metric_always>
] [ <max_metric_sum_lsa> ] [ <max_metric_ext_lsa> ] ] <asext_lsa_cnt> <asext_lsa_crc> <asopaque_lsa_cnt>
<asopaque_lsa_crc> <area_total> <area_normal> <area_stub> <area_nssa> <act_area_total> <act_area_normal>
<act_area_stub> <act_area_nssa> <no_discard_rt_ext> <no_discard_rt_int> [ <bfd_enabled> ] [ <passive_dflt>
] [ <name_lookup> ] [ { TABLE_area <aname> [ <backbone_active> ] [ <active> ] <age> <total_intf>
<act_intf> <passive_intf> <loopback_intf> [ <gr_nbr_cnt> ] <stub> [ <stub_def_cost> ] <nssa> [ <no_redist>
] [ <nssa_trans> ] <no_summary> <auth_type> <spf_runs> <last_spf_run_time> [ <rtr_lsa_throt> ] [
TABLE_range <addr> <masklen> <state> <nets> <advertise> [ <cost> ] ] [ <filter_in> ] [ <filter_out> ]
<lsa_cnt> <lsa_crc> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
instance_number	(Optional)
cname	(Optional)
rid	(Optional)

<i>domain_tag</i>	(Optional)
<i>dn_bit_ignore</i>	(Optional)
<i>stateful_ha</i>	(Optional)
<i>gr_ha</i>	(Optional)
<i>gr_planned_only</i>	(Optional)
<i>gr_notify_period</i>	(Optional)
<i>gr_grace_period</i>	(Optional)
<i>gr_state</i>	(Optional)
<i>gr_last_status</i>	(Optional)
<i>gr_helper_mode</i>	(Optional)
<i>support_tos0_only</i>	(Optional)
<i>support_opaque_lsa</i>	(Optional)
<i>low_mem_cond</i>	(Optional)
<i>is_abr</i>	(Optional)
<i>is_asbr</i>	(Optional)
<i>max_lsa_non_self_number</i>	(Optional)
<i>max_lsa_state</i>	(Optional)
<i>max_lsa_warning_only</i>	(Optional)
<i>max_lsa_current_non_self_lsa_number</i>	(Optional)
<i>max_lsa_threshold_pct</i>	(Optional)
<i>max_lsa_ignore_time</i>	(Optional)
<i>max_lsa_reset_time</i>	(Optional)
<i>max_lsa_ignore_count</i>	(Optional)
<i>max_lsa_current_ignore_count</i>	(Optional)
<i>max_lsa_ignore_time_left</i>	(Optional)
<i>max_lsa_reset_time_left</i>	(Optional)
<i>max_lsa_permanent_ignore</i>	(Optional)
TABLE_redist	(Optional)
<i>proto</i>	(Optional)

<i>max_lsas</i>	(Optional)
<i>warning</i>	(Optional)
<i>threshold</i>	(Optional)
<i>current_count</i>	(Optional)
<i>admin_dist</i>	(Optional)
<i>ref_bw</i>	(Optional)
<i>spf_start_time</i>	(Optional)
<i>spf_hold_time</i>	(Optional)
<i>spf_max_time</i>	(Optional)
<i>lsa_start_time</i>	(Optional)
<i>lsa_hold_time</i>	(Optional)
<i>lsa_max_time</i>	(Optional)
<i>min_lsa_arr_time</i>	(Optional)
<i>lsa_aging_pace</i>	(Optional)
<i>spf_max_paths</i>	(Optional)
<i>max_metric_adver</i>	(Optional)
<i>max_metric_time_left</i>	(Optional)
<i>max_metric_wait_bgp</i>	(Optional)
<i>max_metric_timeout</i>	(Optional)
<i>max_metric_always</i>	(Optional)
<i>max_metric_sum_lsa</i>	(Optional)
<i>max_metric_ext_lsa</i>	(Optional)
<i>asext_lsa_cnt</i>	(Optional)
<i>asext_lsa_crc</i>	(Optional)
<i>asopaque_lsa_cnt</i>	(Optional)
<i>asopaque_lsa_crc</i>	(Optional)
<i>area_total</i>	(Optional)
<i>area_normal</i>	(Optional)
<i>area_stub</i>	(Optional)

<i>area_nssa</i>	(Optional)
<i>act_area_total</i>	(Optional)
<i>act_area_normal</i>	(Optional)
<i>act_area_stub</i>	(Optional)
<i>act_area_nssa</i>	(Optional)
<i>bfd_enabled</i>	(Optional)
<i>name_lookup</i>	(Optional)
<i>passive_dflt</i>	(Optional)
<i>no_discard_rt_ext</i>	(Optional)
<i>no_discard_rt_int</i>	(Optional)
TABLE_area	(Optional)
<i>aname</i>	(Optional)
<i>backbone_active</i>	(Optional)
<i>active</i>	(Optional)
<i>age</i>	(Optional)
<i>total_intf</i>	(Optional)
<i>act_intf</i>	(Optional)
<i>passive_intf</i>	(Optional)
<i>loopback_intf</i>	(Optional)
<i>gr_nbr_cnt</i>	(Optional)
<i>stub</i>	(Optional)
<i>stub_def_cost</i>	(Optional)
<i>nssa</i>	(Optional)
<i>no_redist</i>	(Optional)
<i>nssa_trans</i>	(Optional)
<i>no_summary</i>	(Optional)
<i>auth_type</i>	(Optional)
<i>spf_runs</i>	(Optional)
<i>last_spf_run_time</i>	(Optional)

<i>rtr_lsa_throt</i>	(Optional)
<i>TABLE_range</i>	(Optional)
<i>addr</i>	(Optional)
<i>masklen</i>	(Optional)
<i>state</i>	(Optional)
<i>nets</i>	(Optional)
<i>advertise</i>	(Optional)
<i>cost</i>	(Optional)
<i>filter_in</i>	(Optional)
<i>filter_out</i>	(Optional)
<i>lsa_cnt</i>	(Optional)
<i>lsa_crc</i>	(Optional)

Command Mode

- /exec

show ip ospf border-routers

```
show ip ospf [ <tag> ] border-routers [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_ctx <ptag> <cname> [ TABLE_br <type> <addr> <cost> <asbr> <abr> <area> <spf_inst> [
<vlink_unresolved> ] [ TABLE_br_ubest_nh [ <ubest_nh_addr> ] [ <ubest_nh_intf> ] ] [ TABLE_br_mbset_nh
[ <mbest_nh_addr> ] [ <mbest_nh_intf> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
border-routers	Border routers
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_br	(Optional)
<i>type</i>	(Optional)
<i>addr</i>	(Optional)
<i>cost</i>	(Optional)
<i>asbr</i>	(Optional)
<i>abr</i>	(Optional)
<i>area</i>	(Optional)
<i>spf_inst</i>	(Optional)
<i>vlink_unresolved</i>	(Optional)
TABLE_br_ubest_nh	(Optional)

<i>ubest_nh_addr</i>	(Optional)
<i>ubest_nh_intf</i>	(Optional)
TABLE_br_mbest_nh	(Optional)
<i>mbest_nh_addr</i>	(Optional)
<i>mbest_nh_intf</i>	(Optional)

Command Mode

- /exec

show ip ospf database

```
show ip ospf [ <tag> ] database [ [ [ network | asbr-summary | summary | router | opaque-link | opaque-area
| nssa-external ] [ area <area-id-ip> ] ] | external [ ext_tag <tag_val> ] | opaque-as ] [ <lsid> ] [ self-originated
| adv-router <adv-id> | adv-router-name <adv-name> ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ TABLE_ctx <rid> <ptag> <cname> [ TABLE_db2_lsa <name> [ <area> ] <id> <advtr> <age>
<seqno> <cksum> [ <opaque_id> ] [ <corrupt> ] [ <rtr_num_links> ] [ <tag> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
network	(Optional) Display network LSAs
asbr-summary	(Optional) Display type 4 (asbr-summary) LSAs
external	(Optional) Display type 5 (external) LSAs
router	(Optional) Display router LSAs
nssa-external	(Optional) Display type 7 (NSSA external) LSAs
opaque-link	(Optional) Display Opaque Link-Local LSAs
opaque-area	(Optional) Display Opaque Area LSAs
opaque-as	(Optional) Display Opaque AS LSAs
summary	(Optional) Display type 3 (network-summary) LSAs
self-originated	(Optional) Display only self-originated LSAs
<i>lsid</i>	(Optional) Restrict display by link state ID
adv-router	(Optional) Restrict display by Advertising router
<i>adv-id</i>	(Optional) Advertising router ID
adv-router-name	(Optional) Restrict display by Advertising router name

<i>adv-name</i>	(Optional) DNS Name of the Advertising router
<i>area</i>	(Optional) Display only LSA's in this area
<i>area-id-ip</i>	(Optional) Area Id as an integer or ip address
<i>ext_tag</i>	(Optional) Restrict display by tag
<i>tag_val</i>	(Optional) 32-bit tag value
<i>tag</i>	(Optional)
<i>__readonly__</i>	(Optional)
<i>TABLE_ctx</i>	(Optional)
<i>rid</i>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>TABLE_db2_lsa</i>	(Optional)
<i>name</i>	(Optional)
<i>area</i>	(Optional)
<i>id</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>age</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>opaque_id</i>	(Optional)
<i>corrupt</i>	(Optional)
<i>rtr_num_links</i>	(Optional)

Command Mode

- /exec

show ip ospf database database-summary

```
show ip ospf [ <tag> ] database database-summary [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ TABLE_ctx <rid> <ptag> <cname> [ TABLE_dbsum [ TABLE_dbsum_area <area> [
TABLE_dbsum_area_lsa <area_lsa_name> <area_lsa_count> ] <area_lsa_total> ] [ TABLE_dbsum_all [
TABLE_dbsum_lsa_all <lsa_name> <lsa_count> ] <non_self_lsa_total> <lsa_total> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
database-summary	Summary of database
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>rid</i>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_dbsum	(Optional)
TABLE_dbsum_area	(Optional)
<i>area</i>	(Optional)
TABLE_dbsum_area_lsa	(Optional)
<i>area_lsa_name</i>	(Optional)
<i>area_lsa_count</i>	(Optional)
<i>area_lsa_total</i>	(Optional)
TABLE_dbsum_all	(Optional)

TABLE_dbsum_lsa_all	(Optional)
<i>lsa_name</i>	(Optional)
<i>lsa_count</i>	(Optional)
<i>non_self_lsa_total</i>	(Optional)
<i>lsa_total</i>	(Optional)

Command Mode

- /exec

show ip ospf database detail

```
show ip ospf [ <tag> ] database [ [ network | asbr-summary | summary | router | opaque-link | opaque-area |
nssa-external ] [ area <area-id-ip> ] ] | external [ ext_tag <tag_val> ] | opaque-as [ <lsid> ] [ self-originated
| adv-router <adv-id> | adv-router-name <adv-name> ] detail [ vrf { <vrf-name> | <vrf-known-name> | all } ]
[ __readonly__ TABLE_ctx <rid> <ptag> <cname> [ TABLE_db2_lsa <name> [ <area> ] [ <rtr_max_metric>
] [ TABLE_lsdb <age> <maxage> <options> <options_str> <wrapping> <dummy> <flush_pending> <type>
<id> <id_str> [ <opaque_type> ] [ <opaque_id> ] <advrtr> <seqno> <cksum> <len> [ <corrupt> ] [ <rtr_abr>
] [ <rtr_asbr> ] [ <rtr_translate> ] [ <rtr_vlink_end> ] [ <rtr_num_links> ] [ <rtr_links_mismatch> ] [
TABLE_rlsa [ <rtr_link_type> ] [ <rtr_link_id_str> ] [ <rtr_link_id> ] [ <rtr_link_data_str> ] [ <rtr_link_data>
] [ <rtr_link_num_tos> ] [ <rtr_link_metric> ] [ TABLE_rlinktos [ <rtr_link_tos_id> ] [ <rtr_link_tos_metric>
] ] ] [ <net_mask> ] [ TABLE_netlsa [ <net_rtr> ] ] [ <sum_mask> ] [ <sum_metric> ] [ TABLE_sumlsa [
<sum_tos_id> ] [ <sum_tos_metric> ] ] [ <nssa_mask> ] [ <nssa_metric_type2> ] [ <nssa_metric> ] [
<nssa_fwd_addr> ] [ <nssa_tag> ] [ TABLE_nssa [ <nssa_tos_metric_type2> ] [ <nssa_tos_id> ] [
<nssa_tos_metric> ] [ <nssa_tos_fwd_addr> ] [ <nssa_tos_tag> ] ] [ <asext_mask> ] [ <asext_metric_type2>
] [ <asext_metric> ] [ <asext_fwd_addr> ] [ <asext_tag> ] [ TABLE_asext [ <asext_tos_metric_type2> ] [
<asext_tos_id> <asext_tos_metric> ] [ <asext_tos_fwd_addr> ] [ <asext_tos_tag> ] ] [ <opaque_link_intf>
] [ <opaque_unknown> ] [ <opaque_data_len> ] [ <opaque_data> ] [ <opaque_corrupt> ] [ <tlv_type> ] [
<tlv_len> ] [ <tlv_data> ] [ <tlv_unknown> ] [ <gr_interval> ] [ <gr_reason> ] [ <gr_addr> ] [ <te_frag_id>
] [ <te_rtr_id> ] [ <te_link_type> ] [ <te_link_id> ] [ <te_link_metric> ] [ <te_link_max_bw> ] [
<te_link_rsv_bw> ] [ <te_link_unrsv_bw> ] [ <te_link_admin> ] [ <te_num_links> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
network	(Optional) Display network LSAs
asbr-summary	(Optional) Display type 4 (asbr-summary) LSAs
external	(Optional) Display type 5 (external) LSAs
router	(Optional) Display router LSAs
nssa-external	(Optional) Display type 7 (NSSA external) LSAs
opaque-link	(Optional) Display Opaque Link-Local LSAs

opaque-area	(Optional) Display Opaque Area LSAs
opaque-as	(Optional) Display Opaque AS LSAs
summary	(Optional) Display type 3 (network-summary) LSAs
self-originated	(Optional) Display only self-originated LSAs
<i>lsid</i>	(Optional) Restrict display by link state ID
adv-router	(Optional) Restrict display by Advertising router
<i>advid</i>	(Optional) Advertising router ID
adv-router-name	(Optional) Restrict display by Advertising router name
<i>adv-name</i>	(Optional) DNS Name of the Advertising router
area	(Optional) Display only LSA's in this area
<i>area-id-ip</i>	(Optional) Area Id as an integer or ip address
ext_tag	(Optional) Restrict display by tag
<i>tag_val</i>	(Optional) 32-bit tag value
detail	Display LSA in detail
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>rid</i>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_db2_lsa	(Optional)
<i>name</i>	(Optional)
<i>area</i>	(Optional)
<i>rtr_max_metric</i>	(Optional)
TABLE_lsdb	(Optional)
<i>age</i>	(Optional)
<i>maxage</i>	(Optional)
<i>options</i>	(Optional)
<i>options_str</i>	(Optional)
<i>wrapping</i>	(Optional)

<i>dummy</i>	(Optional)
<i>flush_pending</i>	(Optional)
<i>type</i>	(Optional)
<i>id</i>	(Optional)
<i>id_str</i>	(Optional)
<i>opaque_type</i>	(Optional)
<i>opaque_id</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>len</i>	(Optional)
<i>corrupt</i>	(Optional)
<i>rtr_abr</i>	(Optional)
<i>rtr_asbr</i>	(Optional)
<i>rtr_translate</i>	(Optional)
<i>rtr_vlink_end</i>	(Optional)
<i>rtr_num_links</i>	(Optional)
<i>rtr_links_mismatch</i>	(Optional)
TABLE_rlsa	(Optional)
<i>rtr_link_type</i>	(Optional)
<i>rtr_link_id_str</i>	(Optional)
<i>rtr_link_id</i>	(Optional)
<i>rtr_link_data_str</i>	(Optional)
<i>rtr_link_data</i>	(Optional)
<i>rtr_link_num_tos</i>	(Optional)
<i>rtr_link_metric</i>	(Optional)
TABLE_rlinktos	(Optional)
<i>rtr_link_tos_id</i>	(Optional)
<i>rtr_link_tos_metric</i>	(Optional)

<i>net_mask</i>	(Optional)
TABLE_netlsa	(Optional)
<i>net_rtr</i>	(Optional)
<i>sum_mask</i>	(Optional)
<i>sum_metric</i>	(Optional)
TABLE_sumlsa	(Optional)
<i>sum_tos_id</i>	(Optional)
<i>sum_tos_metric</i>	(Optional)
<i>nssa_mask</i>	(Optional)
<i>nssa_metric_type2</i>	(Optional)
<i>nssa_metric</i>	(Optional)
<i>nssa_fwd_addr</i>	(Optional)
<i>nssa_tag</i>	(Optional)
TABLE_nssa	(Optional)
<i>nssa_tos_metric_type2</i>	(Optional)
<i>nssa_tos_id</i>	(Optional)
<i>nssa_tos_metric</i>	(Optional)
<i>nssa_tos_fwd_addr</i>	(Optional)
<i>nssa_tos_tag</i>	(Optional)
<i>asext_mask</i>	(Optional)
<i>asext_metric_type2</i>	(Optional)
<i>asext_metric</i>	(Optional)
<i>asext_fwd_addr</i>	(Optional)
<i>asext_tag</i>	(Optional)
TABLE_asext	(Optional)
<i>asext_tos_metric_type2</i>	(Optional)
<i>asext_tos_id</i>	(Optional)
<i>asext_tos_metric</i>	(Optional)
<i>asext_tos_fwd_addr</i>	(Optional)

<i>asext_tos_tag</i>	(Optional)
<i>opaque_link_intf</i>	(Optional)
<i>opaque_unknown</i>	(Optional)
<i>opaque_data_len</i>	(Optional)
<i>opaque_data</i>	(Optional)
<i>opaque_corrupt</i>	(Optional)
<i>tlv_type</i>	(Optional)
<i>tlv_len</i>	(Optional)
<i>tlv_data</i>	(Optional)
<i>tlv_unknown</i>	(Optional)
<i>gr_interval</i>	(Optional)
<i>gr_reason</i>	(Optional)
<i>gr_addr</i>	(Optional)
<i>te_frag_id</i>	(Optional)
<i>te_rtr_id</i>	(Optional)
<i>te_link_type</i>	(Optional)
<i>te_link_id</i>	(Optional)
<i>te_link_metric</i>	(Optional)
<i>te_link_max_bw</i>	(Optional)
<i>te_link_rsv_bw</i>	(Optional)
<i>te_link_unrsv_bw</i>	(Optional)
<i>te_link_admin</i>	(Optional)
<i>te_num_links</i>	(Optional)

Command Mode

- /exec

show ip ospf event-history

show ip ospf [<tag>] [internal] event-history { errors | msgs | statistics | adjacency | event | ha | flooding | lsa | spf | redistribution | ldp | te | rib | hello | spf-trigger | cli | objstore }

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
internal	(Optional) Commands for internal use
event-history	Show various event logs of OSPF
errors	Error logs
msgs	IPC logs
statistics	Show the state and size of the buffers
adjacency	Adjacency formation logs
event	Internal event logs
ha	HA and GR logs
flooding	LSA flooding logs
lsa	LSA generation and database logs
spf	SPF calculation logs
redistribution	Redistribution logs
ldp	LDP related logs
te	MPLS TE related logs
rib	RIB related logs
hello	Hello related logs
cli	Cli logs
spf-trigger	SPF TRIGGER related logs
objstore	DME OBJSTORE related logs

Command Mode

 show ip ospf event-history

- /exec

show ip ospf event-history detail

show ip ospf [<tag>] [internal] event-history detail [statistics]

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
internal	(Optional) Commands for internal use
event-history	Show event history of OSPF
detail	Show detailed event history information
statistics	(Optional) Show the state and size of the verbose history buffer

Command Mode

- /exec

show ip ospf ha

```
show ip ospf [ <tag> ] ha [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag>
<cname> <stateful> <pss_restored> <pss_state> <gr_enabled> <gr_grace_period> <gr_state> <gr_last_status>
<gr_helper_mode> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ha	High Availability status
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>stateful</i>	(Optional)
<i>pss_restored</i>	(Optional)
<i>pss_state</i>	(Optional)
<i>gr_enabled</i>	(Optional)
<i>gr_grace_period</i>	(Optional)
<i>gr_state</i>	(Optional)
<i>gr_last_status</i>	(Optional)
<i>gr_helper_mode</i>	(Optional)

Command Mode

- /exec

show ip ospf interface

```
show ip ospf [ <tag> ] interface [ <interface> | vrf { <vrf-name> | <vrf-known-name> | all } ] [ private ] [
__readonly__ TABLE_ctx <ptag> <cname> [ TABLE_intf <ifname> <admin_status> <proto_status> [
<unnumbered> ] <addr> [ <masklen> ] [ <parent_intf> ] <area> [ <if_cfg> ] <state_str> <type_str> <cost>
[ <bfd_enabled> ] [ <ldp_sync> ] <index> [ <passive> ] [ <mpls> ] [ <transmit_delay> ] [ <if_priority> ] [
<dr_rid> ] [ <dr_addr> ] [ <bdr_rid> ] [ <bdr_addr> ] [ <nbr_total> ] [ <nbr_flood> ] [ <nbr_adjs> ] [ <gr_nbr>
] [ <hello_interval> ] [ <dead_interval> ] [ <wait_interval> ] [ <rxmt_interval> ] [ <hello_timer> ] [
<wait_timer> ] [ <pacing_timer> ] [ <lsu_timer> ] [ <lsack_timer> ] [ <netlsa_throt_timer> ] [ <auth_type>
] [ <keychain_name> ] [ <keychain_ready> ] [ <auth_md5_keyid> ] [ <auth_keyid> ] [ <auth_algo> ] [
<link_lsa_cnt> ] [ <link_lsa_crc> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
interface	OSPF enabled interface
<i>interface</i>	(Optional) OSPF enabled interface
private	(Optional) Developer-only statistics
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_intf	(Optional)
<i>ifname</i>	(Optional)
<i>admin_status</i>	(Optional)
<i>proto_status</i>	(Optional)
<i>unnumbered</i>	(Optional)
<i>addr</i>	(Optional)

<i>masklen</i>	(Optional)
<i>parent_intf</i>	(Optional)
<i>area</i>	(Optional)
<i>if_cfg</i>	(Optional)
<i>state_str</i>	(Optional)
<i>type_str</i>	(Optional)
<i>cost</i>	(Optional)
<i>bfd_enabled</i>	(Optional)
<i>ldp_sync</i>	(Optional)
<i>index</i>	(Optional)
<i>passive</i>	(Optional)
<i>mpls</i>	(Optional)
<i>transmit_delay</i>	(Optional)
<i>if_priority</i>	(Optional)
<i>dr_rid</i>	(Optional)
<i>dr_addr</i>	(Optional)
<i>bdr_rid</i>	(Optional)
<i>bdr_addr</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>nbr_flood</i>	(Optional)
<i>nbr_adjs</i>	(Optional)
<i>gr_nbr</i>	(Optional)
<i>hello_interval</i>	(Optional)
<i>dead_interval</i>	(Optional)
<i>wait_interval</i>	(Optional)
<i>rxmt_interval</i>	(Optional)
<i>hello_timer</i>	(Optional)
<i>wait_timer</i>	(Optional)
<i>pacing_timer</i>	(Optional)

<i>lsu_timer</i>	(Optional)
<i>lsack_timer</i>	(Optional)
<i>netlsa_throt_timer</i>	(Optional)
<i>auth_type</i>	(Optional)
<i>keychain_name</i>	(Optional)
<i>keychain_ready</i>	(Optional)
<i>auth_md5_keyid</i>	(Optional)
<i>auth_keyid</i>	(Optional)
<i>auth_algo</i>	(Optional)
<i>link_lsa_cnt</i>	(Optional)
<i>link_lsa_crc</i>	(Optional)

Command Mode

- /exec

show ip ospf interface brief

```
show ip ospf [ <tag> ] interface brief [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_ctx <ptag> <cname> <intf_count> TABLE_intf <ifname> <index> <area> <cost> <state_str>
<nbr_total> <admin_status> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
interface	OSPF enabled interface
brief	Display summary of OSPF interfaces
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>intf_count</i>	(Optional)
TABLE_intf	(Optional)
<i>ifname</i>	(Optional)
<i>index</i>	(Optional)
<i>area</i>	(Optional)
<i>cost</i>	(Optional)
<i>state_str</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>admin_status</i>	(Optional)

Command Mode

- /exec

show ip ospf lsa-content-changed-list

```
show ip ospf [ <tag> ] lsa-content-changed-list { <ip-addr> | <neighbor-name> } <interface> [ __readonly__
[ TABLE_ctx <ptag> <cname> [ TABLE_lschg <nbr_rid> <intf> <nbr_addr> [ TABLE_lsa [ <type> ] [
<lsid> ] [ <advrtr> ] [ <seqno> ] [ <cksum> ] [ <age> ] ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
lsa-content-changed-list	LSAs that changed contents
<i>interface</i>	OSPF enabled interface
<i>ip-addr</i>	Neighbor router ID
<i>neighbor-name</i>	DNS Name of the neighbor
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_lschg	(Optional)
<i>nbr_rid</i>	(Optional)
<i>intf</i>	(Optional)
<i>nbr_addr</i>	(Optional)
TABLE_lsa	(Optional)
<i>type</i>	(Optional)
<i>lsid</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>age</i>	(Optional)

Command Mode

- /exec

show ip ospf memory

```
show ip ospf [ <tag> ] memory [ __readonly__ TABLE_mem <ptag> <byte_total> <byte_consumed>
<byte_overhead> <byte_allocated> <alloc_current> <alloc_created> <alloc_failed> <alloc_free> <bf_current>
<bf_created> <bf_failed> <bf_free> <bf_byte_consumed> <bf_32_current> <bf_32_created> <bf_32_failed>
<bf_32_free> <bf_32_byte_consumed> <slab_current> <slab_created> <slab_failed> <slab_free>
<slab_byte_consumed> <if_index_alloc_failed> <nbr_index_alloc_failed> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
memory	Memory usage statistics
<i>__readonly__</i>	(Optional)
TABLE_mem	(Optional)
<i>ptag</i>	(Optional)
<i>byte_total</i>	(Optional)
<i>byte_consumed</i>	(Optional)
<i>byte_overhead</i>	(Optional)
<i>byte_allocated</i>	(Optional)
<i>alloc_current</i>	(Optional)
<i>alloc_created</i>	(Optional)
<i>alloc_failed</i>	(Optional)
<i>alloc_free</i>	(Optional)
<i>bf_current</i>	(Optional)
<i>bf_created</i>	(Optional)
<i>bf_failed</i>	(Optional)
<i>bf_free</i>	(Optional)
<i>bf_byte_consumed</i>	(Optional)
<i>bf_32_current</i>	(Optional)
<i>bf_32_created</i>	(Optional)

<i>bf_32_failed</i>	(Optional)
<i>bf_32_free</i>	(Optional)
<i>bf_32_byte_consumed</i>	(Optional)
<i>slab_current</i>	(Optional)
<i>slab_created</i>	(Optional)
<i>slab_failed</i>	(Optional)
<i>slab_free</i>	(Optional)
<i>slab_byte_consumed</i>	(Optional)
<i>if_index_alloc_failed</i>	(Optional)
<i>nbr_index_alloc_failed</i>	(Optional)

Command Mode

- /exec

show ip ospf neighbors

```
show ip ospf [ <tag> ] neighbors [ { { <interface> [ <neighbor> | <neighbor-name> ] } | { [ <neighbor> |
<neighbor-name> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] } } ] [ __readonly__ TABLE_ctx <ptag>
<cname> <nbrcount> [ TABLE_nbr <rid> <priority> <state> <drstate> <uptime> <addr> <intf> [ <multiarea>
] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
<i>interface</i>	(Optional) OSPF enabled interface
<i>neighbor</i>	(Optional) Router ID of neighbor
<i>neighbor-name</i>	(Optional) DNS Name of the neighbor
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>nbrcount</i>	(Optional)
TABLE_nbr	(Optional)
<i>rid</i>	(Optional)
<i>priority</i>	(Optional)
<i>state</i>	(Optional)
<i>drstate</i>	(Optional)
<i>uptime</i>	(Optional)

<i>addr</i>	(Optional)
<i>intf</i>	(Optional)
<i>multiarea</i>	(Optional)

Command Mode

- /exec

show ip ospf neighbors detail

```
show ip ospf [ <tag> ] neighbors [ <interface> ] [ <neighbor> | <neighbor-name> ] detail [ vrf { <vrf-name>
| <vrf-known-name> | all } ] [ private ] [ __readonly__ TABLE_ctx <ptag> <cname> [ TABLE_nbr <rid>
<addr> <area> <intf> <state> <transition> <lastchange> [ <bfd_state> ] [ <priority> ] [ <ifid> ] [ <dr> ] [
<dc> ] [ <bdr> ] [ <master> ] [ <seqno> ] [ <dbdallsentacked> ] [ <dbdallsent> ] [ <dbdallacked> ] [
<lsaonreqlist> ] [ <lsafromlastreq> ] [ <lsreqrxmts> ] <hellooptions> <dbdoptions> <lastnonhello> [ <deadtimer>
] [ <pacingtimer> ] [ <dbdrxmtimer> ] [ <reqrxmtimer> ] [ <lsutimer> ] [ <rerxmtimer> ] [ <fastrerxmtimer>
] [ <lsacktimer> ] [ <grtimer> ] [ <helpermode> ] [ <helpercand> ] [ <helperterm> ] [ <senddbd> ] [ <sendlsreq>
] [ <sendlsu> ] [ <sendlsurxmt> ] [ <sendlsack> ] [ <sendlsreqreply> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
interface	(Optional) OSPF enabled interface
neighbor	(Optional) Router ID of neighbor
neighbor-name	(Optional) DNS Name of the neighbor
detail	Show detailed neighbor display
private	(Optional) Developer-only statistics
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_nbr	(Optional)
rid	(Optional)
addr	(Optional)

<i>area</i>	(Optional)
<i>intf</i>	(Optional)
<i>state</i>	(Optional)
<i>transition</i>	(Optional)
<i>lastchange</i>	(Optional)
<i>bfd_state</i>	(Optional)
<i>priority</i>	(Optional)
<i>ifid</i>	(Optional)
<i>dr</i>	(Optional)
<i>bdr</i>	(Optional)
<i>master</i>	(Optional)
<i>seqno</i>	(Optional)
<i>dbdallsentacked</i>	(Optional)
<i>dbdallsent</i>	(Optional)
<i>dbdallacked</i>	(Optional)
<i>lsaonreqlist</i>	(Optional)
<i>lsafromlastreq</i>	(Optional)
<i>lsregrxmts</i>	(Optional)
<i>helloptions</i>	(Optional)
<i>dbdoptions</i>	(Optional)
<i>lastnonhello</i>	(Optional)
<i>deadtimer</i>	(Optional)
<i>pacingtimer</i>	(Optional)
<i>dbdrxmtimer</i>	(Optional)
<i>regrxmtimer</i>	(Optional)
<i>lsutimer</i>	(Optional)
<i>rerxmtimer</i>	(Optional)
<i>fastrerxmtimer</i>	(Optional)
<i>lsacktimer</i>	(Optional)

<i>grtimer</i>	(Optional)
<i>helpermode</i>	(Optional)
<i>helpercand</i>	(Optional)
<i>helperterm</i>	(Optional)
<i>senddbd</i>	(Optional)
<i>sendlsreq</i>	(Optional)
<i>sendlsu</i>	(Optional)
<i>sendlsurxmt</i>	(Optional)
<i>sendlsack</i>	(Optional)
<i>sendlsreqreply</i>	(Optional)
<i>dc</i>	(Optional)

Command Mode

- /exec

show ip ospf neighbors summary

```
show ip ospf [ <tag> ] neighbors [ <interface> ] summary [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ TABLE_ctx <ptag> <cname> TABLE_intf { <ifname> | <total> } <down> <attempt> <init>
<twoway> <exstart> <exchange> <loading> <full> <if_total> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
<i>interface</i>	(Optional) OSPF enabled interface
summary	Summary of neighbors
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_intf	(Optional)
<i>ifname</i>	(Optional)
<i>total</i>	(Optional)
<i>down</i>	(Optional)
<i>attempt</i>	(Optional)
<i>init</i>	(Optional)
<i>twoway</i>	(Optional)
<i>exstart</i>	(Optional)
<i>exchange</i>	(Optional)

<i>loading</i>	(Optional)
<i>full</i>	(Optional)
<i>if_total</i>	(Optional)

Command Mode

- /exec

show ip ospf policy statistics

```
show ip ospf [ <inst> ] policy statistics { { redistribute { { bgp | eigrp } <as> | { isis | ospf | rip } <tag> | static
| direct | amt } } | { area <area-id-ip> filter-list { in | out } } } [ vrf { <vrf-name> | <vrf-known-name> | all }
] [ __readonly__ <ptag> TABLE_ctx <cname> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>inst</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
policy	Display Policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	ISO Intermediate-to-Intermediate (IS-IS)
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
ospf	Open Shortest Path First (OSPFv2)
eigrp	Enhanced Interior Gateway Protocol (EIGRP)
rip	Routing Information Protocol (RIP)
static	Static
direct	Directly connected
amt	AMT anycast prefix
<i>tag</i>	Source protocol tag
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
filter-list	Filter prefixes between OSPF areas

in	Filter networks sent to this area
out	Filter networks sent from this area
__readonly__	(Optional)
<i>ptag</i>	(Optional)
TABLE_ctx	(Optional)
<i>cname</i>	(Optional)

Command Mode

- /exec

show ip ospf request-list

```
show ip ospf [ <tag> ] request-list { <ip-addr> | <neighbor-name> } <interface> [ __readonly__ [ TABLE_ctx
<ptag> <cname> [ TABLE_lsreq <nbr_rid> <intf> <nbr_addr> <total> [ TABLE_lsa [ <type> ] [ <lsid> ] [
<advtr> ] [ <seqno> ] [ <cksum> ] [ <age> ] ] ] ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>ip</code>	Display IP information
<code>ospf</code>	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
<code>request-list</code>	Link state request list
<i>interface</i>	OSPF enabled interface
<i>ip-addr</i>	Neighbor router ID
<i>neighbor-name</i>	DNS Name of the neighbor
<code>__readonly__</code>	(Optional)
<code>TABLE_ctx</code>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<code>TABLE_lsreq</code>	(Optional)
<i>nbr_rid</i>	(Optional)
<i>intf</i>	(Optional)
<i>nbr_addr</i>	(Optional)
<i>total</i>	(Optional)
<code>TABLE_lsa</code>	(Optional)
<i>type</i>	(Optional)
<i>lsid</i>	(Optional)
<i>advtr</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>age</i>	(Optional)

Command Mode

- /exec

show ip ospf retransmission-list

```
show ip ospf [ <tag> ] retransmission-list { <routerid> | <router-name> } <interface> [ __readonly__ [
TABLE_ctx <ptag> <cname> [ TABLE_rxmit <nbr_rid> <intf> <nbr_addr> [ <timer_running> ] [ <timer_due>
] [ TABLE_lsa [ <type> ] [ <lsid> ] [ <advrtr> ] [ <seqno> ] [ <cksum> ] [ <age> ] ] ] ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>ip</code>	Display IP information
<code>ospf</code>	Display OSPF status and configuration
<code>tag</code>	(Optional) Process tag
<code>retransmission-list</code>	Link state retransmission list
<code>routerid</code>	Neighbor router ID
<code>router-name</code>	DNS Name of the router
<code>interface</code>	OSPF enabled interface
<code>__readonly__</code>	(Optional)
<code>TABLE_ctx</code>	(Optional)
<code>ptag</code>	(Optional)
<code>cname</code>	(Optional)
<code>TABLE_rxmit</code>	(Optional)
<code>nbr_rid</code>	(Optional)
<code>intf</code>	(Optional)
<code>nbr_addr</code>	(Optional)
<code>timer_running</code>	(Optional)
<code>timer_due</code>	(Optional)
<code>TABLE_lsa</code>	(Optional)
<code>type</code>	(Optional)
<code>lsid</code>	(Optional)
<code>advrtr</code>	(Optional)
<code>seqno</code>	(Optional)
<code>cksum</code>	(Optional)

<i>age</i>	(Optional)
------------	------------

Command Mode

- /exec

show ip ospf route

```
show ip ospf [ <tag> ] route [ <ip-addr> | <ip-prefix> [ longer-prefixes ] ] [ all_routes ] [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag> <cname> [ <hdr_addr> ] [ <hdr_masklen> ]
[ TABLE_route <addr> <masklen> <type> <in_rib> <direct> [ <area> ] [ <tag> ] [ <vlink_unresolved> ] [
TABLE_route_ubest_nh [ <ubest_nh_addr> ] [ <ubest_nh_intf> ] [ <ubest_cost> ] [ <distance> ] [
<ubest_nh_direct> ] [ <ubest_nh_in_rib> ] ] [ TABLE_route_mbest_nh [ <mbest_nh_addr> ] [ <mbest_nh_intf>
] [ <mbest_cost> ] [ <mbest_nh_direct> ] [ <mbest_nh_in_rib> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
route	Internal OSPF routes
ip-addr	(Optional) Show single OSPF route
ip-prefix	(Optional) Show single exact match OSPF route
longer-prefixes	(Optional) Show exact match and more specific routes
all_routes	(Optional) Display all OSPF routes
tag	(Optional)
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
hdr_addr	(Optional)
hdr_masklen	(Optional)
TABLE_route	(Optional)
addr	(Optional)

<i>masklen</i>	(Optional)
<i>type</i>	(Optional)
<i>in_rib</i>	(Optional)
<i>direct</i>	(Optional)
<i>area</i>	(Optional)
<i>vlink_unresolved</i>	(Optional)
TABLE_route_ubest_nh	(Optional)
<i>ubest_nh_addr</i>	(Optional)
<i>ubest_nh_intf</i>	(Optional)
<i>ubest_cost</i>	(Optional)
<i>distance</i>	(Optional)
<i>ubest_nh_direct</i>	(Optional)
<i>ubest_nh_in_rib</i>	(Optional)
TABLE_route_mbest_nh	(Optional)
<i>mbest_nh_addr</i>	(Optional)
<i>mbest_nh_intf</i>	(Optional)
<i>mbest_cost</i>	(Optional)
<i>mbest_nh_direct</i>	(Optional)
<i>mbest_nh_in_rib</i>	(Optional)

Command Mode

- /exec

show ip ospf route summary

```
show ip ospf [ <tag> ] route [ <ip-prefix> [ longer-prefixes ] ] summary [ vrf { <vrf-name> | <vrf-known-name>
| all } ] [ __readonly__ TABLE_ctx <ptag> <cname> [ TABLE_route <total_routes> <total_paths> [
TABLE_route_type <path_type> <path_routes> <path_paths> ] [ TABLE_route_masklen <masklen>
<masklen_routes> <masklen_paths> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
route	Internal OSPF routes
<i>ip-prefix</i>	(Optional) Show single exact match OSPF route
longer-prefixes	(Optional) Show exact match and more specific routes
summary	Show route counts
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_route	(Optional)
<i>total_routes</i>	(Optional)
<i>total_paths</i>	(Optional)
TABLE_route_type	(Optional)
<i>path_type</i>	(Optional)
<i>path_routes</i>	(Optional)
<i>path_paths</i>	(Optional)

TABLE_route_masklen	(Optional)
<i>masklen</i>	(Optional)
<i>masklen_routes</i>	(Optional)
<i>masklen_paths</i>	(Optional)

Command Mode

- /exec

show ip ospf sham-links

```
show ip ospf [ <tag> ] sham-links [ brief ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_ctx <ptag> <cname> [ TABLE_slink <name> [ <nbr_rid> ] <if_state> <transit_area> <nh_intf>
<nbr_addr> [ <transit_area_stub> ] [ <transit_area_nssa> ] <addr> [ <masklen> ] <area> [ <if_cfg> ] <state_str>
<type_str> <cost> [ <bfd_enabled> ] <index> [ <passive> ] [ <mpls> ] [ <transmit_delay> ] [ <if_priority>
] [ <dr_rid> ] [ <dr_addr> ] [ <bdr_rid> ] [ <bdr_addr> ] [ <nbr_total> ] [ <nbr_flood> ] [ <nbr_adj> ] [
<gr_nbr> ] [ <hello_interval> ] [ <dead_interval> ] [ <wait_interval> ] [ <rxmt_interval> ] [ <sum_total> ] [
<hello_timer> ] [ <wait_timer> ] [ < pacing_timer> ] [ <lsu_timer> ] [ <lsack_timer> ] [ <netlsa_throt_timer>
] [ <auth_type> ] [ <keychain_name> ] [ <keychain_ready> ] [ <auth_md5_keyid> ] [ <link_lsa_cnt> ] [
<link_lsa_crc> ] [ <dc_enabled> ] [ <dest_ip> ] [ <src_ip> ] [ <ifnum> ] [ <state> ] [ <transition> ] [
<lastchange> ] [ <priority> ] [ <ifid> ] [ <dr> ] [ <bdr> ] [ <master> ] [ <seqno> ] [ <dbdallsentacked> ] [
<dbdallsent> ] [ <dbdallacked> ] [ <lsaonreqlist> ] [ <lsafromlastreq> ] [ <lsreqrxmts> ] [ <helloptions> ] [
<dbdoptions> ] [ <lastnonhello> ] [ <deadtimer> ] [ <pacingtimer> ] [ <dbdrxmtimer> ] [ <reqrxmtimer> ] [
<lsutimer> ] [ <rerxmtimer> ] [ <fastrerxmtimer> ] [ <lsacktimer> ] [ <grtimer> ] [ <helpermode> ] [
<helpercand> ] [ <helperterm> ] [ <senddbd> ] [ <sendlsreq> ] [ <sendlsu> ] [ <sendlsurxmt> ] [ <sendlsack>
] [ <sendlsreqreply> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
sham-links	Sham link information
brief	(Optional) Display summary of OSPF sham links
__readonly__	(Optional)
ptag	(Optional)
TABLE_ctx	(Optional)
cname	(Optional)
TABLE_slink	(Optional)
name	(Optional)
nbr_rid	(Optional)

<i>if_state</i>	(Optional)
<i>transit_area</i>	(Optional)
<i>nh_intf</i>	(Optional)
<i>dc_enabled</i>	(Optional)
<i>nbr_addr</i>	(Optional)
<i>sum_total</i>	(Optional)
<i>transit_area_stub</i>	(Optional)
<i>transit_area_nssa</i>	(Optional)
<i>addr</i>	(Optional)
<i>masklen</i>	(Optional)
<i>area</i>	(Optional)
<i>if_cfg</i>	(Optional)
<i>state_str</i>	(Optional)
<i>type_str</i>	(Optional)
<i>cost</i>	(Optional)
<i>bfd_enabled</i>	(Optional)
<i>index</i>	(Optional)
<i>passive</i>	(Optional)
<i>mpls</i>	(Optional)
<i>transmit_delay</i>	(Optional)
<i>if_priority</i>	(Optional)
<i>dr_rid</i>	(Optional)
<i>dr_addr</i>	(Optional)
<i>bdr_rid</i>	(Optional)
<i>bdr_addr</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>nbr_flood</i>	(Optional)
<i>nbr_adj</i>	(Optional)
<i>gr_nbr</i>	(Optional)

<i>hello_interval</i>	(Optional)
<i>dead_interval</i>	(Optional)
<i>wait_interval</i>	(Optional)
<i>rxmt_interval</i>	(Optional)
<i>hello_timer</i>	(Optional)
<i>wait_timer</i>	(Optional)
<i>pacing_timer</i>	(Optional)
<i>lsu_timer</i>	(Optional)
<i>lsack_timer</i>	(Optional)
<i>netlsa_throt_timer</i>	(Optional)
<i>auth_type</i>	(Optional)
<i>keychain_name</i>	(Optional)
<i>keychain_ready</i>	(Optional)
<i>auth_md5_keyid</i>	(Optional)
<i>link_lsa_cnt</i>	(Optional)
<i>link_lsa_crc</i>	(Optional)
<i>state</i>	(Optional)
<i>transition</i>	(Optional)
<i>lastchange</i>	(Optional)
<i>priority</i>	(Optional)
<i>ifid</i>	(Optional)
<i>dr</i>	(Optional)
<i>bdr</i>	(Optional)
<i>master</i>	(Optional)
<i>seqno</i>	(Optional)
<i>dbdallsentacked</i>	(Optional)
<i>dbdallsent</i>	(Optional)
<i>dbdallacked</i>	(Optional)
<i>lsaonreqlist</i>	(Optional)

<i>lsafromlastreq</i>	(Optional)
<i>lsreqrxmts</i>	(Optional)
<i>helloptions</i>	(Optional)
<i>dbdoptions</i>	(Optional)
<i>lastnonhello</i>	(Optional)
<i>deadtimer</i>	(Optional)
<i>pacingtimer</i>	(Optional)
<i>dbdrxmtimer</i>	(Optional)
<i>reqrxmtimer</i>	(Optional)
<i>lsutimer</i>	(Optional)
<i>rerxmtimer</i>	(Optional)
<i>fastrerxmtimer</i>	(Optional)
<i>lsacktimer</i>	(Optional)
<i>grtimer</i>	(Optional)
<i>helpermode</i>	(Optional)
<i>helpercand</i>	(Optional)
<i>helperterm</i>	(Optional)
<i>senddbd</i>	(Optional)
<i>sendlsreq</i>	(Optional)
<i>sendlsu</i>	(Optional)
<i>sendlsurxmt</i>	(Optional)
<i>sendlsack</i>	(Optional)
<i>sendlsreqreply</i>	(Optional)
<i>dest_ip</i>	(Optional)
<i>src_ip</i>	(Optional)
<i>ifnum</i>	(Optional)

Command Mode

- /exec

show ip ospf statistics

```
show ip ospf [ <tag> ] statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_stats
<ptag> <cname> <last_clear> <rid_change> <dr_elections> <older_lsa_rcv> <nbr_state_change>
<nbr_dead_postpone> <nbr_dead_expire> <nbr_bad_lsreq> <nbr_seqno_mismatch> <spf_full>
<spf_summary> <spf_external> <spf_extsummary> <rtr_generate> <rtr_refresh> <rtr_flush> <rtr_other_flush>
<net_generate> <net_refresh> <net_flush> <net_other_flush> <sum_generate> <sum_refresh> <sum_flush>
<sum_other_flush> <asbr_generate> <asbr_refresh> <asbr_flush> <asbr_other_flush> <asext_generate>
<asext_refresh> <asext_flush> <asext_other_flush> <opaque_link_generate> <opaque_link_refresh>
<opaque_link_flush> <opaque_link_other_flush> <opaque_area_generate> <opaque_area_refresh>
<opaque_area_flush> <opaque_area_other_flush> <opaque_as_generate> <opaque_as_refresh>
<opaque_as_flush> <opaque_as_other_flush> <limbo_lsa_count> <limbo_lsa_hwm> <limbo_lsa_deleted>
<limbo_lsa_revived> <limbo_runs> <limbo_lsa_last_time_hwm> [ <limbo_timer> ] <helloq_size>
<helloq_max_size> <helloq_hwm> <helloq_drops> <helloq_last_hwm_time> <floodq_size>
<floodq_max_size> <floodq_hwm> <floodq_drops> <floodq_last_hwm_time> <lsdb_add_fail> [
TABLE_buffer_detail [ <buf_size> ] [ <buf_size_huge> ] <buf_in_use> <buf_hwm> <buf_perm> <buf_alloc>
<buf_free> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Event counters
<i>__readonly__</i>	(Optional)
TABLE_stats	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>last_clear</i>	(Optional)
<i>rid_change</i>	(Optional)
<i>dr_elections</i>	(Optional)
<i>older_lsa_rcv</i>	(Optional)

<i>nbr_state_change</i>	(Optional)
<i>nbr_dead_postpone</i>	(Optional)
<i>nbr_dead_expire</i>	(Optional)
<i>nbr_bad_lsreq</i>	(Optional)
<i>nbr_seqno_mismatch</i>	(Optional)
<i>spf_full</i>	(Optional)
<i>spf_summary</i>	(Optional)
<i>spf_external</i>	(Optional)
<i>spf_extsummary</i>	(Optional)
<i>rtr_generate</i>	(Optional)
<i>rtr_refresh</i>	(Optional)
<i>rtr_flush</i>	(Optional)
<i>rtr_other_flush</i>	(Optional)
<i>net_generate</i>	(Optional)
<i>net_refresh</i>	(Optional)
<i>net_flush</i>	(Optional)
<i>net_other_flush</i>	(Optional)
<i>sum_generate</i>	(Optional)
<i>sum_refresh</i>	(Optional)
<i>sum_flush</i>	(Optional)
<i>sum_other_flush</i>	(Optional)
<i>asbr_generate</i>	(Optional)
<i>asbr_refresh</i>	(Optional)
<i>asbr_flush</i>	(Optional)
<i>asbr_other_flush</i>	(Optional)
<i>asext_generate</i>	(Optional)
<i>asext_refresh</i>	(Optional)
<i>asext_flush</i>	(Optional)
<i>asext_other_flush</i>	(Optional)

<i>opaque_link_generate</i>	(Optional)
<i>opaque_link_refresh</i>	(Optional)
<i>opaque_link_flush</i>	(Optional)
<i>opaque_link_other_flush</i>	(Optional)
<i>opaque_area_generate</i>	(Optional)
<i>opaque_area_refresh</i>	(Optional)
<i>opaque_area_flush</i>	(Optional)
<i>opaque_area_other_flush</i>	(Optional)
<i>opaque_as_generate</i>	(Optional)
<i>opaque_as_refresh</i>	(Optional)
<i>opaque_as_flush</i>	(Optional)
<i>opaque_as_other_flush</i>	(Optional)
<i>limbo_lsa_count</i>	(Optional)
<i>limbo_lsa_hwm</i>	(Optional)
<i>limbo_lsa_deleted</i>	(Optional)
<i>limbo_lsa_revived</i>	(Optional)
<i>limbo_runs</i>	(Optional)
<i>limbo_lsa_last_time_hwm</i>	(Optional)
<i>limbo_timer</i>	(Optional)
<i>helloq_size</i>	(Optional)
<i>helloq_max_size</i>	(Optional)
<i>helloq_hwm</i>	(Optional)
<i>helloq_drops</i>	(Optional)
<i>helloq_last_hwm_time</i>	(Optional)
<i>floodq_size</i>	(Optional)
<i>floodq_max_size</i>	(Optional)
<i>floodq_hwm</i>	(Optional)
<i>floodq_drops</i>	(Optional)
<i>floodq_last_hwm_time</i>	(Optional)

<i>lsdb_add_fail</i>	(Optional)
TABLE_buffer_detail	(Optional)
<i>buf_size</i>	(Optional)
<i>buf_size_huge</i>	(Optional)
<i>buf_in_use</i>	(Optional)
<i>buf_hwm</i>	(Optional)
<i>buf_perm</i>	(Optional)
<i>buf_alloc</i>	(Optional)
<i>buf_free</i>	(Optional)

Command Mode

- /exec

show ip ospf summary-address

```
show ip ospf [ <tag> ] summary-address [ private ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ [ TABLE_ctx <ptag> <cname> <rid> [ TABLE_sum <addr> <masklen> [ <metric> ] [ <tag>
] [ <pending> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
summary-address	Summary-address redistribution information
private	(Optional) Developer-only statistics
<i>tag</i>	(Optional)
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>rid</i>	(Optional)
TABLE_sum	(Optional)
<i>addr</i>	(Optional)
<i>masklen</i>	(Optional)
<i>metric</i>	(Optional)
<i>pending</i>	(Optional)

Command Mode

- /exec

show ip ospf traffic

```
show ip ospf [ <tag> ] traffic [ <interface> [ detail ] [ detail ] [ detail ] vrf { <vrf-name> | <vrf-known-name>
| all } ] [ __readonly__ TABLE_traf <ptag> <cname> <last_clear> [ <ifname> ] <pkt_in> <pkt_out>
<lsu_first_trans> <lsu_retrans> <lsu_for_lsreq> <lsu_nbr_trans> <throttle_out> <throttle_out_token>
<throttle_out_ip> <lsa_ignored> <lsa_dropped_spf> <lsa_dropped_gr> <pkt_drops_in> <pkt_drops_out>
<pkt_errors_in> <pkt_errors_out> <hello_errors_in> <dbds_errors_in> <lsreqs_errors_in> <lsus_errors_in>
<lsacks_errors_in> <pkt_unknown_in> <pkt_unknown_out> <pkt_no_ospf_intf> <bad_version> <bad_crc>
<dup_rtr_id> <dup_src_addr> <invalid_src_addr> <invalid_dst_addr> <non_existing_nbr> <pkt_passive_intf>
<wrong_area> <invalid_pkt_len> <nbr_changed_routerid_ipaddr> <nbr_changed_interfaceid> [ <bad_auth>
] [ <bad_reserved> ] [ <pkt_no_vrf> ] <hello_in> <dbds_in> <lsreqs_in> <lsus_in> <lsacks_in> <hello_out>
<dbds_out> <lsreqs_out> <lsus_out> <lsacks_out> [ <hello_in_hq> <dbds_in_hq> <lsreqs_in_flq>
<lsus_in_flq> <lsacks_in_flq> <lsas_in_dbds_in> <lsas_in_lsreqs_in> <lsas_in_lsus_in> <lsas_in_lsacks_in>
<lsas_in_dbds_out> <lsas_in_lsreqs_out> <lsas_in_lsus_out> <lsas_in_lsacks_out> <lsas_in_rxmt_lsus_out>
] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
<i>interface</i>	(Optional) OSPF enabled interface
detail	(Optional) Display detailed information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Packet counters
<i>__readonly__</i>	(Optional)
TABLE_traf	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>last_clear</i>	(Optional)
<i>ifname</i>	(Optional)
<i>pkt_in</i>	(Optional)

<i>pkt_out</i>	(Optional)
<i>lsu_first_trans</i>	(Optional)
<i>lsu_retrans</i>	(Optional)
<i>lsu_for_lsreq</i>	(Optional)
<i>lsu_nbr_trans</i>	(Optional)
<i>throttle_out</i>	(Optional)
<i>throttle_out_token</i>	(Optional)
<i>throttle_out_ip</i>	(Optional)
<i>lsa_ignored</i>	(Optional)
<i>lsa_dropped_spf</i>	(Optional)
<i>lsa_dropped_gr</i>	(Optional)
<i>pkt_drops_in</i>	(Optional)
<i>pkt_drops_out</i>	(Optional)
<i>pkt_errors_in</i>	(Optional)
<i>pkt_errors_out</i>	(Optional)
<i>hello_errors_in</i>	(Optional)
<i>dbds_errors_in</i>	(Optional)
<i>lsreqs_errors_in</i>	(Optional)
<i>lsus_errors_in</i>	(Optional)
<i>lsacks_errors_in</i>	(Optional)
<i>pkt_unknown_in</i>	(Optional)
<i>pkt_unknown_out</i>	(Optional)
<i>pkt_no_ospf_intf</i>	(Optional)
<i>bad_version</i>	(Optional)
<i>bad_crc</i>	(Optional)
<i>dup_rtr_id</i>	(Optional)
<i>dup_src_addr</i>	(Optional)
<i>invalid_src_addr</i>	(Optional)
<i>invalid_dst_addr</i>	(Optional)

<i>non_existing_nbr</i>	(Optional)
<i>pkt_passive_intf</i>	(Optional)
<i>wrong_area</i>	(Optional)
<i>invalid_pkt_len</i>	(Optional)
<i>nbr_changed_routerid_ipaddr</i>	(Optional)
<i>nbr_changed_interfaceid</i>	(Optional)
<i>bad_auth</i>	(Optional)
<i>bad_reserved</i>	(Optional)
<i>pkt_no_vrf</i>	(Optional)
<i>hellos_in</i>	(Optional)
<i>dbds_in</i>	(Optional)
<i>lsreqs_in</i>	(Optional)
<i>lsus_in</i>	(Optional)
<i>lsacks_in</i>	(Optional)
<i>hellos_out</i>	(Optional)
<i>dbds_out</i>	(Optional)
<i>lsreqs_out</i>	(Optional)
<i>lsus_out</i>	(Optional)
<i>lsacks_out</i>	(Optional)
<i>hellos_in_hq</i>	(Optional)
<i>dbds_in_hq</i>	(Optional)
<i>lsreqs_in_flq</i>	(Optional)
<i>lsus_in_flq</i>	(Optional)
<i>lsacks_in_flq</i>	(Optional)
<i>lsas_in_dbds_in</i>	(Optional)
<i>lsas_in_lsreqs_in</i>	(Optional)
<i>lsas_in_lsus_in</i>	(Optional)
<i>lsas_in_lsacks_in</i>	(Optional)
<i>lsas_in_dbds_out</i>	(Optional)

<i>lsas_in_lsreqs_out</i>	(Optional)
<i>lsas_in_lsus_out</i>	(Optional)
<i>lsas_in_lsacks_out</i>	(Optional)
<i>lsas_in_rxmt_lsus_out</i>	(Optional)

Command Mode

- /exec

show ip ospf traps-queue

show ip ospf [<tag>] traps-queue

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
traps-queue	Show all the priority traps queue parameters

Command Mode

- /exec

show ip ospf virtual-links

```
show ip ospf [ <tag> ] virtual-links [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx
<ptag> <cname> [ TABLE_vlink <name> <nbr_rid> <if_state> <transit_area> <nh_intf> <nbr_addr> [
<transit_area_stub> ] [ <transit_area_nssa> ] <addr> [ <masklen> ] <area> [ <if_cfg> ] <state_str> <type_str>
<cost> <index> [ <passive> ] [ <mpls> ] [ <transmit_delay> ] [ <if_priority> ] [ <dr_rid> ] [ <dr_addr> ] [
<bdr_rid> ] [ <bdr_addr> ] [ <nbr_total> ] [ <nbr_flood> ] [ <nbr_adj> ] [ <gr_nbr> ] [ <hello_interval> ] [
<dead_interval> ] [ <wait_interval> ] [ <rxmt_interval> ] [ <hello_timer> ] [ <wait_timer> ] [ <pacing_timer>
] [ <lsu_timer> ] [ <lsack_timer> ] [ <netlsa_throt_timer> ] [ <auth_type> ] [ <keychain_name> ] [
<keychain_ready> ] [ <auth_md5_keyid> ] [ <link_lsa_cnt> ] [ <link_lsa_crc> ] [ <dc_enabled> ] [ <state>
] [ <transition> ] [ <lastchange> ] [ <priority> ] [ <ifid> ] [ <dr> ] [ <bdr> ] [ <master> ] [ <seqno> ] [
<dbdallsentacked> ] [ <dbdallsent> ] [ <dbdallacked> ] [ <lsaonreqlist> ] [ <lsafromlastreq> ] [ <lsreqrxmts>
] [ <helloptions> ] [ <dbdoptions> ] [ <lastnonhello> ] [ <deadtimer> ] [ <pacingtimer> ] [ <dbdtxmtimer> ]
[ <reqrxmtimer> ] [ <lsutimer> ] [ <rerxmtimer> ] [ <fastrerxmtimer> ] [ <lsacktimer> ] [ <grtimer> ] [
<helpermode> ] [ <helpercand> ] [ <helperterm> ] [ <senddbd> ] [ <sendlsreq> ] [ <sendlsu> ] [ <sendlsurxmt>
] [ <sendlsack> ] [ <sendlsreqreply> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
virtual-links	Virtual link information
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_vlink	(Optional)
name	(Optional)
nbr_rid	(Optional)
if_state	(Optional)
transit_area	(Optional)

<i>nh_intf</i>	(Optional)
<i>dc_enabled</i>	(Optional)
<i>nbr_addr</i>	(Optional)
<i>transit_area_stub</i>	(Optional)
<i>transit_area_nssa</i>	(Optional)
<i>addr</i>	(Optional)
<i>masklen</i>	(Optional)
<i>area</i>	(Optional)
<i>if_cfg</i>	(Optional)
<i>state_str</i>	(Optional)
<i>type_str</i>	(Optional)
<i>cost</i>	(Optional)
<i>index</i>	(Optional)
<i>passive</i>	(Optional)
<i>mpls</i>	(Optional)
<i>transmit_delay</i>	(Optional)
<i>if_priority</i>	(Optional)
<i>dr_rid</i>	(Optional)
<i>dr_addr</i>	(Optional)
<i>bdr_rid</i>	(Optional)
<i>bdr_addr</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>nbr_flood</i>	(Optional)
<i>nbr_adj</i>	(Optional)
<i>gr_nbr</i>	(Optional)
<i>hello_interval</i>	(Optional)
<i>dead_interval</i>	(Optional)
<i>wait_interval</i>	(Optional)
<i>rxmt_interval</i>	(Optional)

<i>hello_timer</i>	(Optional)
<i>wait_timer</i>	(Optional)
<i>pacing_timer</i>	(Optional)
<i>lsu_timer</i>	(Optional)
<i>lsack_timer</i>	(Optional)
<i>netlsa_throt_timer</i>	(Optional)
<i>auth_type</i>	(Optional)
<i>keychain_name</i>	(Optional)
<i>keychain_ready</i>	(Optional)
<i>auth_md5_keyid</i>	(Optional)
<i>link_lsa_cnt</i>	(Optional)
<i>link_lsa_crc</i>	(Optional)
<i>state</i>	(Optional)
<i>transition</i>	(Optional)
<i>lastchange</i>	(Optional)
<i>priority</i>	(Optional)
<i>ifid</i>	(Optional)
<i>dr</i>	(Optional)
<i>bdr</i>	(Optional)
<i>master</i>	(Optional)
<i>seqno</i>	(Optional)
<i>dbdallsentacked</i>	(Optional)
<i>dbdallsent</i>	(Optional)
<i>dbdallacked</i>	(Optional)
<i>lsaonreqlist</i>	(Optional)
<i>lsafromlastreq</i>	(Optional)
<i>lsreqrxmts</i>	(Optional)
<i>helloptions</i>	(Optional)
<i>dbdoptions</i>	(Optional)

<i>lastnonhello</i>	(Optional)
<i>deadtimer</i>	(Optional)
<i>pacingtimer</i>	(Optional)
<i>dbdrxmtimer</i>	(Optional)
<i>reqrxmtimer</i>	(Optional)
<i>lsutimer</i>	(Optional)
<i>rerxmtimer</i>	(Optional)
<i>fastrerxmtimer</i>	(Optional)
<i>lsacktimer</i>	(Optional)
<i>grtimer</i>	(Optional)
<i>helpermode</i>	(Optional)
<i>helpercand</i>	(Optional)
<i>helperterm</i>	(Optional)
<i>senddbd</i>	(Optional)
<i>sendlsreq</i>	(Optional)
<i>sendlsu</i>	(Optional)
<i>sendlsurxmt</i>	(Optional)
<i>sendlsack</i>	(Optional)
<i>sendlsreqreply</i>	(Optional)

Command Mode

- /exec

show ip ospf virtual-links brief

```
show ip ospf [ <tag> ] virtual-links brief [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_ctx <ptag> <cname> <vlink_count> [ TABLE_vlink <nbr_rid> <vlink_num> <transit_area> <cost>
<if_state> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ospf	Display OSPF status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
virtual-links	Virtual link information
brief	Display summary of OSPF virtual links
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>vlink_count</i>	(Optional)
TABLE_vlink	(Optional)
<i>nbr_rid</i>	(Optional)
<i>vlink_num</i>	(Optional)
<i>transit_area</i>	(Optional)
<i>cost</i>	(Optional)
<i>if_state</i>	(Optional)

Command Mode

- /exec

show ip overlay-traffic

show ip overlay-traffic

Syntax Description

show	Show running system information
ip	Display IP information
overlay-traffic	Display IP overlay software processed traffic statistics

Command Mode

- /exec

show ip pim bitfield

show ip pim bitfield

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
bitfield	Display compressed bitfield details

Command Mode

- /exec

show ip pim config-sanity

```
show ip pim config-sanity [ __readonly__ [ TABLE_vrf <out-context> [ TABLE_RP <rp-addr> [ {
<rperr-count><rp-interface><rp-error> } ] ] [ TABLE_ANYCAST [ { <arperr-count> <anycastrp-addr> [
<arp-interface> ] <arp-error> [ <configure-as-RP> } ] ] [ TABLE_MEMBER [ { <memerr-count> [
<mem-interface> ] <mem-error> } ] ] <found> ] [ TABLE_BSR [ { <rp-cand-count> [ <rp-cand-interface>
] <rp-cand-error> } ] [ { <bsr-cand-count> [ <bsr-cand-interface> ] <bsr-cand-error> } ] ] [ TABLE_AUTORP
[ { <rp-cand-count> [ <rp-cand-interface> ] <rp-cand-error> } ] [ { <auto-cand-count> [ <auto-cand-interface>
] <auto-cand-error> } ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
config-sanity	Configuration Sanity check
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
TABLE_RP	(Optional)
<i>rp-addr</i>	(Optional)
TABLE_ANYCAST	(Optional)
<i>arperr-count</i>	(Optional)
<i>anycastrp-addr</i>	(Optional)
<i>arp-interface</i>	(Optional)
<i>arp-error</i>	(Optional)
<i>configure-as-RP</i>	(Optional)
TABLE_MEMBER	(Optional)
<i>memerr-count</i>	(Optional)
<i>mem-interface</i>	(Optional)
<i>mem-error</i>	(Optional)
<i>found</i>	(Optional)
TABLE_BSR	(Optional)
<i>rp-cand-count</i>	(Optional)

<i>rp-cand-interface</i>	(Optional)
<i>rp-cand-error</i>	(Optional)
<i>bsr-cand-count</i>	(Optional)
<i>bsr-cand-interface</i>	(Optional)
<i>bsr-cand-error</i>	(Optional)
TABLE_AUTORP	(Optional)
<i>rp-cand-count</i>	(Optional)
<i>rp-cand-interface</i>	(Optional)
<i>rp-cand-error</i>	(Optional)
<i>auto-cand-count</i>	(Optional)
<i>auto-cand-interface</i>	(Optional)
<i>auto-cand-error</i>	(Optional)

Command Mode

- /exec

show ip pim df

```
show ip pim df [ <rp-or-group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ internal ] [ __readonly__ ]
[ TABLE_ctx [ <out-context> ] [ TABLE_rp [ <rp-addr> ] [ <df-ordinal> ] [ <df-bits> ] [ <df-bits-count> ]
[ <metric-pref> ] [ <metric> ] [ TABLE_grange [ <grange-grp> ] [ <grange-masklen> ] ] [ TABLE_iod [
<if-name> ] [ <df-winner> ] [ <df-state> ] [ <winner-metric-pref> ] [ <winner-metric> ] [ <uptime> ] [ <is-rpf>
] ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
df	Display Bidir Designated Forwarders
<i>rp-or-group</i>	(Optional) Display for a single RP or group address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
internal	(Optional) Commands for internal use
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>out-context</i>	(Optional)
TABLE_rp	(Optional)
<i>rp-addr</i>	(Optional)
<i>df-ordinal</i>	(Optional)
<i>df-bits</i>	(Optional)
<i>df-bits-count</i>	(Optional)
<i>metric-pref</i>	(Optional)
<i>metric</i>	(Optional)
TABLE_grange	(Optional)
<i>grange-grp</i>	(Optional)
<i>grange-masklen</i>	(Optional)

TABLE_iod	(Optional)
<i>if-name</i>	(Optional)
<i>df-winner</i>	(Optional)
<i>df-state</i>	(Optional)
<i>winner-metric-pref</i>	(Optional)
<i>winner-metric</i>	(Optional)
<i>uptime</i>	(Optional)
<i>is-rpf</i>	(Optional)

Command Mode

- /exec

show ip pim event-history

show ip pim [internal] event-history { errors | msgs | <pim-event-hist-buf-name> | statistics }

Syntax Description

show	Show running system information
ip	Display IP information
pim	PIM global configuration commands
internal	(Optional) Commands for internal use
event-history	Show various event logs of PIM
errors	Show error logs of PIM
msgs	Show various message logs of PIM
<i>pim-event-hist-buf-name</i>	Show event hist buffer name
statistics	Show the state and size of the buffer

Command Mode

- /exec

show ip pim fabric info

```
show ip pim fabric info [ __readonly__ <switch_role> <fabric_ctrl_addr> <peer_fabric_ctrl_infra>  
<vpc_domain_id> <peer_fabric_ctrl_addr> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
fabric	Fabric functionality
info	show the fabric info
<i>__readonly__</i>	(Optional)
<i>switch_role</i>	(Optional)
<i>fabric_ctrl_addr</i>	(Optional)
<i>peer_fabric_ctrl_infra</i>	(Optional)
<i>vpc_domain_id</i>	(Optional)
<i>peer_fabric_ctrl_addr</i>	(Optional)

Command Mode

- /exec

show ip pim fabric legacy-vlans

show ip pim fabric legacy-vlans [__readonly__ TABLE_legacy_vlan <vlan_id>]

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
fabric	Fabric functionality
legacy-vlans	Show legacy VLANs on this switch
__readonly__	(Optional)
TABLE_legacy_vlan	(Optional)
<i>vlan_id</i>	(Optional)

Command Mode

- /exec

show ip pim group-range

```
show ip pim group-range [ <group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [
TABLE_vrf <out-context> [ { TABLE_group <grp-addr> [ <invalid-grp> ] [ <action> ] [ <mode> ] [ <rp-addr>
] [ <sh-tree-only-range> ] [ <origin> ] } ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
group-range	Display the various group-ranges
<i>group</i>	(Optional) IP address of group to display
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
TABLE_group	(Optional)
<i>invalid-grp</i>	(Optional)
<i>grp-addr</i>	(Optional)
<i>mode</i>	(Optional)
<i>rp-addr</i>	(Optional)
<i>sh-tree-only-range</i>	(Optional)
<i>action</i>	(Optional)
<i>origin</i>	(Optional)

Command Mode

- /exec

show ip pim host-proxy

show ip pim host-proxy [__readonly__ TABLE_intf <intf-name>]

Syntax Description

show	Show running system information
ip	Display IP information
pim	PIM global configuration commands
host-proxy	host-proxy
__readonly__	(Optional)
TABLE_intf	(Optional)
<i>intf-name</i>	(Optional)

Command Mode

- /exec

show ip pim interface

```
show ip pim interface [ <interface> ] [ brief ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ internal ] [
__readonly__ ] [ <is-pim-enabled> ] [ TABLE_vrf [ <out-context> ] [ TABLE_brief [ <if-name> ] [ <if-addr>
] [ <if-dr> ] [ <if-nbr-count> ] [ <if-is-border> ] ] [ TABLE_iod [ <if-name> ] [ <if-status> ] [
<cached_if_status> ] [ <if-addr-summary> ] [ <pim-dr-address> ] [ <dr-priority> ] [ <no-dr-priority> ] [
<nbr-cnt> ] [ <hello-interval-sec> ] [ <hello-interval-msec> ] [ <hello-timer> ] [ <holdtime-msec> ] [
<holdtime-sec> ] [ <if-conf-dr-priority> ] [ <if-conf-delay> ] [ <is-border> ] [ <genid> ] [ <isauth-config> ]
[ <nbr-policy-name> ] [ <jp-in-policy-name> ] [ <jp-out-policy-name> ] [ <jp-interval> ] [ <jp-next-send> ]
[ <pim-bfd-enabled> ] [ <is-passive> ] [ <is-pim-vpc-svi> ] [ <is-auto-enabled> ] [ <vpc-peer-nbr> ] [
<last-cleared> ] [ <hello-sent> ] [ <hello-rcvd> ] [ <hello-early-sent> ] [ <jp-sent> ] [ <jp-rcvd> ] [ <assert-sent>
] [ <assert-rcvd> ] [ <graft-sent> ] [ <graft-rcvd> ] [ <graft-ack-sent> ] [ <graft-ack-rcvd> ] [ <df-offer-sent>
] [ <df-offer-rcvd> ] [ <df-winner-sent> ] [ <df-winner-rcvd> ] [ <df-backoff-sent> ] [ <df-backoff-rcvd> ] [
<pass-sent> ] [ <pass-rcvd> ] [ <cksum-errors> ] [ <invalid-errors> ] [ <invalid-df-errors> ] [ <auth-failed>
] [ <pak-len-errors> ] [ <ver-errors> ] [ <pkts-self> ] [ <pkts-non-nbr> ] [ <pkts-on-passive> ] [ <jp-rcvd-on-rpf>
] [ <jp-rcvd-no-rp> ] [ <jp-rcvd-wrong-rp> ] [ <jp-rcvd-for-ssm> ] [ <jp-rcvd-for-bidir> ] [ <jp-in-policy-filter>
] [ <jp-out-policy-filter> ] [ <ecmp-redirect-sent> ] [ <ecmp-redirect-rcv> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
interface	Display PIM interface related information
<i>interface</i>	(Optional) Interface name of single interface to display
brief	(Optional) Display one line status per interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
internal	(Optional) Commands for internal use
__readonly__	(Optional)
<i>is-pim-enabled</i>	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
TABLE_brief	(Optional)
<i>if-name</i>	(Optional)

<i>if-addr</i>	(Optional)
<i>if-dr</i>	(Optional)
<i>if-nbr-count</i>	(Optional)
<i>if-is-border</i>	(Optional)
TABLE_iod	(Optional)
<i>if-name</i>	(Optional)
<i>if-status</i>	(Optional)
<i>cached_if_status</i>	(Optional)
<i>if-addr-summary</i>	(Optional)
<i>pim-dr-address</i>	(Optional)
<i>dr-priority</i>	(Optional)
<i>no-dr-priority</i>	(Optional)
<i>nbr-cnt</i>	(Optional)
<i>hello-interval-sec</i>	(Optional)
<i>hello-interval-msec</i>	(Optional)
<i>hello-timer</i>	(Optional)
<i>holdtime-msec</i>	(Optional)
<i>holdtime-sec</i>	(Optional)
<i>if-conf-dr-priority</i>	(Optional)
<i>if-conf-delay</i>	(Optional)
<i>is-border</i>	(Optional)
<i>genid</i>	(Optional)
<i>isauth-config</i>	(Optional)
<i>nbr-policy-name</i>	(Optional)
<i>jp-in-policy-name</i>	(Optional)
<i>jp-out-policy-name</i>	(Optional)
<i>jp-interval</i>	(Optional)
<i>jp-next-send</i>	(Optional)
<i>pim-bfd-enabled</i>	(Optional)

<i>is-passive</i>	(Optional)
<i>is-pim-vpc-svi</i>	(Optional)
<i>is-auto-enabled</i>	(Optional)
<i>vpc-peer-nbr</i>	(Optional)
<i>last-cleared</i>	(Optional)
<i>hello-sent</i>	(Optional)
<i>hello-rcvd</i>	(Optional)
<i>hello-early-sent</i>	(Optional)
<i>jp-sent</i>	(Optional)
<i>jp-rcvd</i>	(Optional)
<i>assert-sent</i>	(Optional)
<i>assert-rcvd</i>	(Optional)
<i>graft-sent</i>	(Optional)
<i>graft-rcvd</i>	(Optional)
<i>graft-ack-sent</i>	(Optional)
<i>graft-ack-rcvd</i>	(Optional)
<i>df-offer-sent</i>	(Optional)
<i>df-offer-rcvd</i>	(Optional)
<i>df-winner-sent</i>	(Optional)
<i>df-winner-rcvd</i>	(Optional)
<i>df-backoff-sent</i>	(Optional)
<i>df-backoff-rcvd</i>	(Optional)
<i>pass-sent</i>	(Optional)
<i>pass-rcvd</i>	(Optional)
<i>cksum-errors</i>	(Optional)
<i>invalid-errors</i>	(Optional)
<i>invalid-df-errors</i>	(Optional)
<i>auth-failed</i>	(Optional)
<i>pak-len-errors</i>	(Optional)

<i>ver-errors</i>	(Optional)
<i>pkts-self</i>	(Optional)
<i>pkts-non-nbr</i>	(Optional)
<i>pkts-on-passive</i>	(Optional)
<i>jp-rcvd-on-rpf</i>	(Optional)
<i>jp-rcvd-no-rp</i>	(Optional)
<i>jp-rcvd-wrong-rp</i>	(Optional)
<i>jp-rcvd-for-ssm</i>	(Optional)
<i>jp-rcvd-for-bidir</i>	(Optional)
<i>jp-in-policy-filter</i>	(Optional)
<i>jp-out-policy-filter</i>	(Optional)
<i>ecmp-redirect-sent</i>	(Optional)
<i>ecmp-redirect-recv</i>	(Optional)

Command Mode

- /exec

show ip pim mdt

```
show ip pim mdt [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf <out_context>
<mti> <mti_status> <default_mdt_grp> <grp_mode> <asm_shared_tree> <mti_config_mtu> <mti_active_mtu>
<cfg_tunnel_src_if> <bgp_update_src_if> <hello_interval> <jp_interval> <data_mdt_join_interval>
<data_switchover_interval> <data_holddown_interval> <data_timeout_interval> <mdt_src> <mdt_src_if>
<bgp_rd> <bgp_rd_set> <send_join_count> <rcvd_join_count> { TABLE_data_mdt <grange_prefix>
<grange_mask_len> <threshold> [ <policy_name> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
mdt	Display MDT information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out_context</i>	(Optional)
<i>mti</i>	(Optional)
<i>mti_status</i>	(Optional)
<i>default_mdt_grp</i>	(Optional)
<i>grp_mode</i>	(Optional)
<i>asm_shared_tree</i>	(Optional)
<i>mti_config_mtu</i>	(Optional)
<i>mti_active_mtu</i>	(Optional)
<i>cfg_tunnel_src_if</i>	(Optional)
<i>bgp_update_src_if</i>	(Optional)
<i>hello_interval</i>	(Optional)
<i>jp_interval</i>	(Optional)

<i>data_mdt_join_interval</i>	(Optional)
<i>data_switchover_interval</i>	(Optional)
<i>data_holddown_interval</i>	(Optional)
<i>data_timeout_interval</i>	(Optional)
<i>mdt_src</i>	(Optional)
<i>mdt_src_if</i>	(Optional)
<i>bgp_rd</i>	(Optional)
<i>bgp_rd_set</i>	(Optional)
<i>send_join_count</i>	(Optional)
<i>rcvd_join_count</i>	(Optional)
TABLE_data_mdt	(Optional)
<i>grange_prefix</i>	(Optional)
<i>grange_mask_len</i>	(Optional)
<i>threshold</i>	(Optional)
<i>policy_name</i>	(Optional)

Command Mode

- /exec

show ip pim mdt bgp

```
show ip pim mdt bgp [ mdt-source <src-addr> ] [ __readonly__ { TABLE_entry <bgp_rd> <mdt_src>
<mdt_grp> <local> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
mdt	Display MDT information
bgp	Display BGP related information
mdt-source	(Optional) Source address of MVPN neighbor
<i>src-addr</i>	(Optional) Source Address
__readonly__	(Optional)
TABLE_entry	(Optional)
<i>bgp_rd</i>	(Optional)
<i>mdt_src</i>	(Optional)
<i>mdt_grp</i>	(Optional)
<i>local</i>	(Optional)

Command Mode

- /exec

show ip pim mdt history interval

```
show ip pim mdt history interval <min> [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_vrf <out_context> [ { TABLE_entry <csrc> <cgrp> <psrc> <pgrp> <uptime> <send_count> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
mdt	Display MDT information
history	Display MDT Data Join Send Histoy
interval	Display in specified interval
<i>min</i>	Minutes
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out_context</i>	(Optional)
TABLE_entry	(Optional)
<i>csrc</i>	(Optional)
<i>cgrp</i>	(Optional)
<i>psrc</i>	(Optional)
<i>pgrp</i>	(Optional)
<i>uptime</i>	(Optional)
<i>send_count</i>	(Optional)

Command Mode

- /exec

show ip pim mdt receive

```
show ip pim mdt receive [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf
<out_context> [ { TABLE_entry <csrc> <cgrp> <psrc> <pgrp> <uptime> [ <expires> ] [ <recv_count> ] }
]]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
mdt	Display MDT information
receive	Display Received Data Joins Information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
detail	(Optional) Display detailed information
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out_context</i>	(Optional)
TABLE_entry	(Optional)
<i>csrc</i>	(Optional)
<i>cgrp</i>	(Optional)
<i>psrc</i>	(Optional)
<i>pgrp</i>	(Optional)
<i>uptime</i>	(Optional)
<i>expires</i>	(Optional)
<i>recv_count</i>	(Optional)

Command Mode

- /exec

show ip pim mdt send

```
show ip pim mdt send [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf
<out_context> [ { TABLE_entry <csrc> <cgrp> <psrc> <pgrp> <uptime> <send_count> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
mdt	Display MDT information
send	Display MDT Data Join Send Information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
detail	(Optional) Display detailed information
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out_context</i>	(Optional)
TABLE_entry	(Optional)
<i>csrc</i>	(Optional)
<i>cgrp</i>	(Optional)
<i>psrc</i>	(Optional)
<i>pgrp</i>	(Optional)
<i>uptime</i>	(Optional)
<i>send_count</i>	(Optional)

Command Mode

- /exec

show ip pim neighbor

```
show ip pim neighbor { [ <interface> ] | [ <ipaddr> ] } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ detail
| internal ] [ __readonly__ [ TABLE_vrf <out-context> [ TABLE_neighbor
<nbr-addr><if-name><uptime><expires> [ <dr-priority> ] <bidir-capable><bfd-state> [
<longest-hello-intvl><non-hello-pkts> ] [ <ecmp-redirect-capable> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
neighbor	Display PIM neighbor related information
<i>interface</i>	(Optional) Display neighbors on single interface name
<i>ipaddr</i>	(Optional) IP address of single neighbor to display
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
detail	(Optional) Display detailed information
internal	(Optional) Commands for internal use
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
TABLE_neighbor	(Optional)
<i>dr-priority</i>	(Optional)
<i>ecmp-redirect-capable</i>	(Optional)

Command Mode

- /exec

show ip pim oif-list

```
show ip pim oif-list <group> [ <source> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_vrf <vrf-name> { TABLE_grp <mcast-addr> <incoming-intf> <rpf-nbr> <timeout-interval>
<oif-list-count> [ { TABLE_oiflist <oif-name> } ] <timeout-list-count> [ { TABLE_timeoutlist
<timeoutoif-name> } ] <immediate-list-count> [ { TABLE_immediatelist <immediateoif-name> } ]
<immediate-timeout-list-count> [ { TABLE_immediatetimetoutlist <immediatetimeoutoif-name> } ]
<sgr-prune-list-count> [ { TABLE_sgrprunelist <sgrprunelistoif-name> } ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
oif-list	Display interfaces for oif-list of PIM route
<i>source</i>	(Optional) Source address to display
<i>group</i>	Group address to display
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_grp	(Optional)
<i>mcast-addr</i>	(Optional)
<i>incoming-intf</i>	(Optional)
<i>rpf-nbr</i>	(Optional)
<i>timeout-interval</i>	(Optional)
<i>oif-list-count</i>	(Optional)
TABLE_oiflist	(Optional)
<i>oif-name</i>	(Optional)
<i>timeout-list-count</i>	(Optional)

TABLE_timeoutlist	(Optional)
<i>timeoutoif-name</i>	(Optional)
<i>immediate-list-count</i>	(Optional)
TABLE_immediatelist	(Optional)
<i>immediateoif-name</i>	(Optional)
<i>immediate-timeout-list-count</i>	(Optional)
TABLE_immediatetimeoutlist	(Optional)
<i>immediatetimeoutoif-name</i>	(Optional)
<i>sgr-prune-list-count</i>	(Optional)
TABLE_sgrprunelist	(Optional)
<i>sgrprunelistoif-name</i>	(Optional)

Command Mode

- /exec

show ip pim policy statistics

```
show ip pim policy statistics { register-policy | bsr { bsr-policy | rp-candidate-policy } | auto-rp {
rp-candidate-policy | mapping-agent-policy } } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
{ TABLE_routemap <name> <action> <seq_num> [ { TABLE_cmd <command> <match_count>
<compare_count> } ] } <total_accept_count> <total_reject_count> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	PIM global configuration commands
policy	Policy related information
statistics	Policy statistics
register-policy	Show statistics for register-policy
bsr	Bootstrap protocol RP-distribution policy
bsr-policy	Statistics for filtered BSR messages
rp-candidate-policy	Statistics for filtered RP candidate messages
auto-rp	Statistics for auto-rp messages
rp-candidate-policy	Statistics for filtered RP candidate messages
mapping-agent-policy	Statistics for filtered mapping agent messages
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_routemap	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seq_num</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)

<i>compare_count</i>	(Optional)
<i>match_count</i>	(Optional)
<i>total_accept_count</i>	(Optional)
<i>total_reject_count</i>	(Optional)

Command Mode

- /exec

show ip pim policy statistics jp

```
show ip pim policy statistics { jp-policy | neighbor-policy } <interface> [ __readonly__ { TABLE_routemap
<name> <action> <seq_num> [ { TABLE_cmd <command> <match_count> <compare_count> } ] }
<total_accept_count> <total_reject_count> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	PIM global configuration commands
policy	Policy related information
statistics	Policy statistics
jp-policy	Statistics for jp-policy
neighbor-policy	Statistics for neighbor-policy
<i>interface</i>	Interface to display policy statistics for
<i>__readonly__</i>	(Optional)
TABLE_routemap	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seq_num</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>compare_count</i>	(Optional)
<i>match_count</i>	(Optional)
<i>total_accept_count</i>	(Optional)
<i>total_reject_count</i>	(Optional)

Command Mode

- /exec

show ip pim route

```
show ip pim route [ [ <source> [ <group> ] ] | [ <group> [ <source> ] ] ] [ bitfield ] [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ [ TABLE_vrf [ <context-name> ] [ <route-count> ] [
TABLE_one_route [ <mcast-addr> ] [ <rp-addr> ] [ <rp-local> ] [ <bidir> ] [ <sgexpire> ] [ <sgexpire> ]
[ <timeleft> ] [ <rp-bit> ] [ <register> ] [ <intf-name> ] [ <rpf-nbr-1> ] [ <rpf-nbr-addr> ] [ <intf-name-2> ]
[ <rpf-nbr-2> ] [ <uptime> ] [ <is-attached> ] [ <is-static> ] [ <zero-nonpim-oifs> ] [ <is-external> ] [
<otv-decap> ] [ <otv-router-mode> ] [ <non-dr-oifs-only> ] [ <data-created> ] [ <mdt-encap> ] [ <mdt-decap>
] [ <vxlan-decap> ] [ <vxlan-encap> ] [ <sw-pkts> ] [ <sw-bytes> ] [ <hw-pkts> ] [ <hw-bytes> ] [ <rpf-src>
] [ <mrib-rpf-notify> ] [ <add-pending> ] [ <aged-route> ] [ <sg-expiry-cfg> ] [ <jp-holdtime> ] [
<route-metric-internal> ] [ <metric-pref-internal> ] [ <delay-register-stop> ] [ <register-stop-rcvd> ] [
<lisp-src-rloc> ] [ TABLE_lisp_encap [ <encap-src-rloc> ] [ <encap-dst-rloc> ] [ <timeout-count> ] [
<add-pending> ] [ <del-pending> ] ] [ <oif-count> ] [ <oif-bf-str> ] [ <timeout-count> ] [ <timeout-bf-str> ]
[ <immediate-count> ] [ <immediate-bf-str> ] [ <immediate-timeout-count> ] [ <immediate-timeout-bf-str>
] [ <sgr-prune-list-count> ] [ <sgr-prune-list-bf-str> ] [ <timeout-interval> ] [ <jp-holdtime-rndup> ] [
<mdt-encap-index> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
route	Display PIM specific route information
<i>group</i>	(Optional) Group address to display
<i>source</i>	(Optional) Source address to display
bitfield	(Optional) Display details of each bitfield for PIM route
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>context-name</i>	(Optional)
<i>route-count</i>	(Optional)
TABLE_one_route	(Optional)
<i>mcast-addr</i>	(Optional)
<i>rp-addr</i>	(Optional)

<i>rp-local</i>	(Optional)
<i>bidir</i>	(Optional)
<i>sgexpire</i>	(Optional)
<i>sgrexpire</i>	(Optional)
<i>timeleft</i>	(Optional)
<i>rp-bit</i>	(Optional)
<i>register</i>	(Optional)
<i>intf-name</i>	(Optional)
<i>rpf-nbr-1</i>	(Optional)
<i>rpf-nbr-addr</i>	(Optional)
<i>intf-name-2</i>	(Optional)
<i>rpf-nbr-2</i>	(Optional)
<i>uptime</i>	(Optional)
<i>is-attached</i>	(Optional)
<i>is-static</i>	(Optional)
<i>zero-nonpim-oifs</i>	(Optional)
<i>is-external</i>	(Optional)
<i>otv-decap</i>	(Optional)
<i>otv-router-mode</i>	(Optional)
<i>non-dr-oifs-only</i>	(Optional)
<i>data-created</i>	(Optional)
<i>mdt-encap</i>	(Optional)
<i>mdt-decap</i>	(Optional)
<i>vxlان-decap</i>	(Optional)
<i>vxlان-encap</i>	(Optional)
<i>sw-pkts</i>	(Optional)
<i>sw-bytes</i>	(Optional)
<i>hw-pkts</i>	(Optional)
<i>hw-bytes</i>	(Optional)

<i>rpf-src</i>	(Optional)
<i>mrrib-rpf-notify</i>	(Optional)
<i>add-pending</i>	(Optional)
<i>aged-route</i>	(Optional)
<i>sg-expiry-cfg</i>	(Optional)
<i>jp-holdtime</i>	(Optional)
<i>route-metric-internal</i>	(Optional)
<i>metric-pref-internal</i>	(Optional)
<i>delay-register-stop</i>	(Optional)
<i>register-stop-rcvd</i>	(Optional)
<i>lisp-src-rloc</i>	(Optional)
TABLE_lisp_encap	(Optional)
<i>encap-src-rloc</i>	(Optional)
<i>encap-dst-rloc</i>	(Optional)
<i>timeout-count</i>	(Optional)
<i>add-pending</i>	(Optional)
<i>del-pending</i>	(Optional)
<i>oif-count</i>	(Optional)
<i>oif-bf-str</i>	(Optional)
<i>timeout-count</i>	(Optional)
<i>timeout-bf-str</i>	(Optional)
<i>immediate-count</i>	(Optional)
<i>immediate-bf-str</i>	(Optional)
<i>immediate-timeout-count</i>	(Optional)
<i>immediate-timeout-bf-str</i>	(Optional)
<i>sgr-prune-list-count</i>	(Optional)
<i>sgr-prune-list-bf-str</i>	(Optional)
<i>timeout-interval</i>	(Optional)
<i>jp-holdtime-rndup</i>	(Optional)

<i>mdt-encap-index</i>	(Optional)
------------------------	------------

Command Mode

- /exec

show ip pim rp-hash

```
show ip pim rp-hash <group> [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <out-context>
[ <rp-found> ] [ <is-rp-bsr-learned> ] [ <out-group1> <rp-addr1> ] [ <out-group> <hash-length> <out-bsr> ]
[ { TABLE_rp <rp-addr> <hash> <isbest_hash> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
rp-hash	Display RP hash value for group
<i>group</i>	Group address for RP lookup
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-context</i>	(Optional)
<i>rp-found</i>	(Optional)
<i>is-rp-bsr-learned</i>	(Optional)
<i>out-group1</i>	(Optional)
<i>rp-addr1</i>	(Optional)
<i>out-group</i>	(Optional)
<i>hash-length</i>	(Optional)
<i>out-bsr</i>	(Optional)
TABLE_rp	(Optional)
<i>rp-addr</i>	(Optional)
<i>hash</i>	(Optional)
<i>isbest_hash</i>	(Optional)

Command Mode

- /exec

show ip pim rp

```
show ip pim rp [ <group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ internal ] [ __readonly__ [
TABLE_vrf <out-context> [ <is-bsr-enabled> ] [ <is-bsr-listen-only> ] [ <is-bsr-forward-only> ] [ <bsr-address>
] [ <is-bsr-local> ] [ <bs-timer> ] [ <bsr-uptime> ] [ <bsr-expires> ] [ <bsr-priority> ] [ <bsr-hash-masklen>
] [ <is-autorp-enabled> ] [ <is-autorp-listen-only> ] [ <is-autorp-forward-only> ] [ <auto-rp-addr> ] [
<is-autorp-local> ] [ <autorp-dis-timer> ] [ <autorp-cand-address> ] [ <autorp-up-time> ] [ <autorp-expire-time>
] [ <rp-cand-policy-name> ] [ <bsr-policy-name> ] [ <rp-announce-policy-name> ] [
<rp-discovery-policy-name> ] [ TABLE_anycast_rp <anycast-rp-addr> [ TABLE_arp_rp <arp-rp-addr>
<is-rpaddr-local> ] ] [ TABLE_rp [ <rp-addr> ] [ <is-rp-local> ] [ <df-ordinal> ] [ <rp-uptime> ] [ <rp-priority>
] [ <rp-source> ] [ <static-rp-group-map> ] [ TABLE_grange [ <grange-grp> ] [ <grange-masklen> ] [
<grange-is-deny> ] [ <is-bidir-grp> ] [ <autorp-expires> ] [ <bsr-rp-expires> ] [ <rp-owner-flags> ] ] [ [
<bidir-ordinal> ] [ <df-bits-recovered> ] [ <rpf-nbr-address> ] [ <metric> ] [ <metric-preference> ] ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
rp	Display PIM RP, Auto-RP, and BSR related information
<i>group</i>	(Optional) Display RP for group address
internal	(Optional) Commands for internal use
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
<i>is-bsr-enabled</i>	(Optional)
<i>is-bsr-listen-only</i>	(Optional)
<i>is-bsr-forward-only</i>	(Optional)
<i>bsr-address</i>	(Optional)
<i>is-bsr-local</i>	(Optional)
<i>bsr-priority</i>	(Optional)

<i>bsr-hash-masklen</i>	(Optional)
<i>bs-timer</i>	(Optional)
<i>bsr-uptime</i>	(Optional)
<i>bsr-expires</i>	(Optional)
<i>is-atorp-enabled</i>	(Optional)
<i>is-atorp-listen-only</i>	(Optional)
<i>is-atorp-forward-only</i>	(Optional)
<i>auto-rp-addr</i>	(Optional)
<i>atorp-cand-address</i>	(Optional)
<i>is-atorp-local</i>	(Optional)
<i>atorp-dis-timer</i>	(Optional)
<i>atorp-up-time</i>	(Optional)
<i>atorp-expire-time</i>	(Optional)
<i>rp-cand-policy-name</i>	(Optional)
<i>bsr-policy-name</i>	(Optional)
<i>rp-announce-policy-name</i>	(Optional)
<i>rp-discovery-policy-name</i>	(Optional)
TABLE_anycast_rp	(Optional)
<i>anycast-rp-addr</i>	(Optional)
TABLE_arp_rp	(Optional)
<i>arp-rp-addr</i>	(Optional)
<i>is-rpaddr-local</i>	(Optional)
TABLE_rp	(Optional)
<i>rp-addr</i>	(Optional)
<i>is-rp-local</i>	(Optional)
<i>df-ordinal</i>	(Optional)
<i>rp-uptime</i>	(Optional)
<i>rp-priority</i>	(Optional)
<i>rp-source</i>	(Optional)

<i>static-rp-group-map</i>	(Optional)
TABLE_grange	(Optional)
<i>grange-grp</i>	(Optional)
<i>grange-masklen</i>	(Optional)
<i>grange-is-deny</i>	(Optional)
<i>is-bidir-grp</i>	(Optional)
<i>autorp-expires</i>	(Optional)
<i>bsr-rp-expires</i>	(Optional)
<i>rp-owner-flags</i>	(Optional)
<i>bidir-ordinal</i>	(Optional)
<i>df-bits-recovered</i>	(Optional)
<i>rpf-nbr-address</i>	(Optional)
<i>metric</i>	(Optional)
<i>metric-preference</i>	(Optional)

Command Mode

- /exec

show ip pim statistics

```
show ip pim statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf <vrf-name>
[ <uptime> <reg-sent> <reg-rcvd> <null-reg-sent> <null-reg-rcvd> <reg-stop-sent> <reg-stop-rcvd>
<reg-rcvd-not-rp> <reg-rcvd-for-ssm> <reg-rcvd-for-bidir> <bootstrap-sent> <bootstrap-rcvd> <cand-rp-sent>
<cand-rp-rcvd> <bs-no-nbr> <bs-border-deny> <bs-len-errors> <bs-rpf-failed> <bs-no-listen>
<candrp-border-deny> <candrp-no-listen> <autorp-announce-sent> <autorp-announce-rcvd>
<autorp-discovery-sent> <autorp-discovery-rcvd> <autorp-rpf-failed> <autorp-border-deny>
<autorp-invalid-type> <autorp-ttl-expired> <autorp-no-listen> <ctrl-no-route> <data-no-route> <no-state>
<create-state> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
statistics	Packet counter statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
<i>uptime</i>	(Optional)
<i>reg-sent</i>	(Optional)
<i>reg-rcvd</i>	(Optional)
<i>null-reg-sent</i>	(Optional)
<i>null-reg-rcvd</i>	(Optional)
<i>reg-stop-sent</i>	(Optional)
<i>reg-stop-rcvd</i>	(Optional)
<i>reg-rcvd-not-rp</i>	(Optional)
<i>reg-rcvd-for-ssm</i>	(Optional)
<i>reg-rcvd-for-bidir</i>	(Optional)

<i>bootstrap-sent</i>	(Optional)
<i>bootstrap-rcvd</i>	(Optional)
<i>cand-rp-sent</i>	(Optional)
<i>cand-rp-rcvd</i>	(Optional)
<i>bs-no-nbr</i>	(Optional)
<i>bs-border-deny</i>	(Optional)
<i>bs-len-errors</i>	(Optional)
<i>bs-rpf-failed</i>	(Optional)
<i>bs-no-listen</i>	(Optional)
<i>candrp-border-deny</i>	(Optional)
<i>candrp-no-listen</i>	(Optional)
<i>autorp-announce-sent</i>	(Optional)
<i>autorp-announce-rcvd</i>	(Optional)
<i>autorp-discovery-sent</i>	(Optional)
<i>autorp-discovery-rcvd</i>	(Optional)
<i>autorp-rpf-failed</i>	(Optional)
<i>autorp-border-deny</i>	(Optional)
<i>autorp-invalid-type</i>	(Optional)
<i>autorp-ttl-expired</i>	(Optional)
<i>autorp-no-listen</i>	(Optional)
<i>ctrl-no-route</i>	(Optional)
<i>data-no-route</i>	(Optional)
<i>no-state</i>	(Optional)
<i>create-state</i>	(Optional)

Command Mode

- /exec

show ip pim vrf

```
show ip pim vrf [ { <vrf-name> | <vrf-known-name> | all } ] [ detail | internal ] [ __readonly__ {
TABLE_context <out-context> <context-id> <table-id> <count> <bfd> <mvpn> } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
pim	Display PIM status and configuration
vrf	Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display all VRFs PIM is configured for
detail	(Optional) Display detailed information
internal	(Optional) VRF related internal information
__readonly__	(Optional)
TABLE_context	(Optional)
<i>out-context</i>	(Optional)
<i>context-id</i>	(Optional)
<i>table-id</i>	(Optional)
<i>count</i>	(Optional)
<i>bfd</i>	(Optional)
<i>mvpn</i>	(Optional)

Command Mode

- /exec

show ip ping source-interface

```
show ip ping source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_ippingvrf  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ping	Display ping client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ippingvrf	(Optional) source interface of ping
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip ping source-interface vrf all

show ip ping source-interface vrf all [__readonly__ [{ TABLE_ipping <vrfname> <ifname> }]]

Syntax Description

show	Show running system information
ip	Display IP information
ping	Display ping client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ipping	(Optional) source interface of ping
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip policy

```
show ip policy [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ detail ] [ __readonly__ { TABLE_pbr [ <interface> ] [ <rmap> ] [ <status> ] [ <vrf_name> ] } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
policy	Policy routing
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
detail	(Optional) Detailed information
__readonly__	(Optional)
TABLE_pbr	(Optional)
<i>interface</i>	(Optional)
<i>rmap</i>	(Optional)
<i>status</i>	(Optional)
<i>vrf_name</i>	(Optional)

Command Mode

- /exec

show ip prefix-list

```
show ip prefix-list { { [ detail | summary ] [ <ipv4-pfl-name> | <ipv4-pfl-cfg-name> ] } | { { <ipv4-pfl-name> | <ipv4-pfl-cfg-name> } seq <seq-no> } | { { <ipv4-pfl-name> | <ipv4-pfl-cfg-name> } <prefix> [ first-match | longer ] } } [ __readonly__ TABLE_ip_pfl <name> <seq> <action> <rule> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
detail	(Optional) Show detailed information
summary	(Optional) Show summarized information
prefix-list	List IP prefix lists
<i>ipv4-pfl-name</i>	(Optional) Name of prefix-list
<i>ipv4-pfl-cfg-name</i>	(Optional) Known prefix-list name
seq	Sequence number
<i>seq-no</i>	Sequence number
<i>prefix</i>	IP prefix network/length, e.g., 35.0.0.0/8
first-match	(Optional) Find the first match
longer	(Optional) Find the more specific entries
__readonly__	(Optional)
TABLE_ip_pfl	(Optional)
<i>name</i>	(Optional)
<i>seq</i>	(Optional)
<i>action</i>	(Optional)
<i>rule</i>	(Optional)

Command Mode

- /exec

show ip process

```
show ip process [ api ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ TABLE_ip_pro_vrf
[ { <pro-cntxt-name> <pro-cntxt-id> <pro-base-tid> <pro-auto-disc> <pro-atuo-add> <pro-null-bcast>
<auto-punt-bcast> <static-disc> <static-def-route> <ip-unreach> } ] [ TABLE_pro_api [ <api-vrf>
<api-cntxt-id> <api-base-tid> <api-ip-addr> <api-rtr-id-iod> } ] [ TABLE_iod [ { <entry-iod> } ] ] [
TABLE_local_addr [ { <local-addr> } ] ] ] [ TABLE_ip_pro_all { <all-pro-cntxt-name> <all-pro-cntxt-id>
} ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
process	Display IP global information
api	(Optional) Show api values
vrf	(Optional) Display per-VRF information
all	(Optional) Display all VRFs
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ip_pro_vrf	(Optional)
<i>pro-cntxt-name</i>	(Optional)
<i>pro-cntxt-id</i>	(Optional)
<i>pro-base-tid</i>	(Optional)
<i>pro-auto-disc</i>	(Optional)
<i>pro-atuo-add</i>	(Optional)
<i>pro-null-bcast</i>	(Optional)
<i>auto-punt-bcast</i>	(Optional)
<i>static-disc</i>	(Optional)
<i>static-def-route</i>	(Optional)
<i>ip-unreach</i>	(Optional)
TABLE_pro_api	(Optional)
<i>api-vrf</i>	(Optional)

<i>api-cntxt-id</i>	(Optional)
<i>api-base-tid</i>	(Optional)
<i>api-ip-addr</i>	(Optional)
<i>api-rtr-id-iod</i>	(Optional)
TABLE_iod	(Optional)
<i>entry-iod</i>	(Optional)
TABLE_local_addr	(Optional)
<i>local-addr</i>	(Optional)
TABLE_ip_pro_all	(Optional)
<i>all-pro-cntxt-name</i>	(Optional)
<i>all-pro-cntxt-id</i>	(Optional)

Command Mode

- /exec

show ip rip policy statistics redistribute

```
show ip rip [ instance <inst> ] policy statistics redistribute { bgp <as> | { eigrp | isis | <src-rip> | ospf } <tag>
| direct | static } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_asn <asn> TABLE_vrf
<vrf> { TABLE_rmap <name> <action> <seq_num> [ { TABLE_cmd <command> <compare_count>
<match_count> } ] } <total_accept_count> <total_reject_count> ]
```

Syntax Description

show	Show running system information
ip	Display IP information
rip	Display RIP routing protocol status
instance	(Optional) Process ID
<i>inst</i>	(Optional) Process ID
policy	Policy related information
statistics	Policy statistics
redistribute	RIP redistribute routes from other routing protocol
bgp	Border Gateway Protocol (BGP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>as</i>	Autonomous system number
isis	Intermediate-to-intermediate (ISIS)
src-rip	Routing Information Protocol (RIP)
ospf	Open Shortest Path First (OSPFv2)
<i>tag</i>	Process tag
direct	Directly connected routes
static	Static routes
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_asn	(Optional) AS number table

<i>asn</i>	(Optional) AS number
<i>TABLE_vrf</i>	(Optional) VRF table
<i>vrf</i>	(Optional) VRF name
<i>TABLE_rmap</i>	(Optional) Routemap table
<i>name</i>	(Optional) Route-map Name
<i>action</i>	(Optional) Route-map action
<i>seq_num</i>	(Optional) Sequence number of the rule in route-map
<i>TABLE_cmd</i>	(Optional) Route-map command table
<i>command</i>	(Optional) Route-map command
<i>compare_count</i>	(Optional) Number of comparisons
<i>match_count</i>	(Optional) Number of matches
<i>total_accept_count</i>	(Optional) Total number of packets accepted by the policy
<i>total_reject_count</i>	(Optional) Total number of packets rejected by the policy

Command Mode

- /exec

show ip route

```
show ip route [ ip | ipv4 ] [ unicast ] [ topology <topology-name> ] [ l3vm-info ] [ rpf ] [ <ip-addr> | {
<ip-prefix> [ { longer-prefixes | shorter-prefixes } ] } ] [ { <protocol> [ all ] } | { next-hop <next-hop> |
next-hop-v6 <next-hop-v6> } | { interface <interface> } | { updated { [ since <stime> ] [ until <utime> ] } }
] + [ summary | detail ] [ vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } ] [ __readonly__ TABLE_vrf
<vrf-name-out> TABLE_addrf <addrf> [ TABLE_prefix <ipprefix> <ucast-nhops> <mcast-nhops> <attached>
TABLE_path [ <ipnexthop> ] [ <ifname> ] <uptime> <pref> <metric> <clientname> [ <type> ] [ <tag> ] [
<stale> ] [ <unres> ] [ <hidden> ] [ <stale-label> ] [ <ubest> ] [ <mbest> ] ] [ TABLE_summary <routes>
<paths> [ <multicast_paths> ] [ TABLE_unicast [ <clientnameuni> ] [ <best-paths> ] [ <backup-paths> ] ] [
TABLE_multicast [ <clientnamemulti> ] [ <best-paths> ] [ <backup-paths> ] ] [ TABLE_route_count [
<mask_len> ] [ <count> ] ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
route	Display routing information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
ipv4	(Optional) Display IP information
unicast	(Optional) Display unicast information
topology	(Optional) Display per-topology information
<i>topology-name</i>	(Optional) topology name
l3vm-info	(Optional) Display corresponding L3VM information
rpf	(Optional) Display RPF information for multicast source
<i>ip-addr</i>	(Optional) Display single route longest match lookup
<i>ip-prefix</i>	(Optional) Display single exact match route
longer-prefixes	(Optional) Display matching routes with mask-lengths >= prefix
shorter-prefixes	(Optional) Display matching routes with mask-lengths <= prefix
<i>protocol</i>	(Optional) Display routes for protocol (or route type)
all	(Optional) Display routes for protocol for backup next-hops too
next-hop	(Optional) Display routes with this next-hop only

<i>next-hop</i>	(Optional) Next hop address
next-hop-v6	(Optional) Display routes with this V6 next-hop only
interface	(Optional) Display routes with this output interface only
<i>interface</i>	(Optional) Interface Name
updated	(Optional) Display routes filtered by last updated time
since	(Optional) Display those routes updated since this time
<i>stime</i>	(Optional) Since this date/time [[CC]YY-][MM-DD-]HH:MM[:SS]
until	(Optional) Display those routes updated until this time
<i>utime</i>	(Optional) Until this date/time [[CC]YY-][MM-DD-]HH:MM[:SS]
summary	(Optional) Display route counts
detail	(Optional) Display routes in full detail
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_addrf	(Optional)
<i>addrf</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>ucast-nhops</i>	(Optional)
<i>mcast-nhops</i>	(Optional)
<i>attached</i>	(Optional)
TABLE_path	(Optional)
<i>ipnexthop</i>	(Optional)
<i>ifname</i>	(Optional)
<i>uptime</i>	(Optional)
<i>pref</i>	(Optional)
<i>metric</i>	(Optional)
<i>clientname</i>	(Optional)
<i>type</i>	(Optional)

<i>tag</i>	(Optional)
<i>stale</i>	(Optional)
<i>unres</i>	(Optional)
<i>hidden</i>	(Optional)
<i>stale-label</i>	(Optional)
<i>ubest</i>	(Optional)
<i>mbest</i>	(Optional)
TABLE_summary	(Optional)
<i>routes</i>	(Optional)
<i>paths</i>	(Optional)
<i>multicast_paths</i>	(Optional)
TABLE_unicast	(Optional)
<i>clientnameuni</i>	(Optional)
<i>best-paths</i>	(Optional)
<i>backup-paths</i>	(Optional)
TABLE_multicast	(Optional)
<i>clientnamemulti</i>	(Optional)
<i>best-paths</i>	(Optional)
<i>backup-paths</i>	(Optional)
TABLE_route_count	(Optional)
<i>mask_len</i>	(Optional)
<i>count</i>	(Optional)

Command Mode

- /exec

show ip router-id

show ip router-id [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

show	Show running system information
ip	Display IP information
router-id	Display IP router identification
vrf	(Optional) Display per-VRF information
all	(Optional) Display all VRFs
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show ip rsvp

```
show ip rsvp [ __readonly__ [ <sup-state> <start-type> <restart-type> <ha-ena> <gr-ena> <hst-ena>
<glb-router-id> <psr-ena> <local-epoch> ] [ TABLE_clients <clnt-name> <clnt-sap> <clnt-type>
<clnt-batch-time> [ <clnt-lxsb> ] ] [ <bundle-ena> <bundle-time> <bundle-maxsz> ] [ <refresh-intvl>
<refresh-miss> ] [ <refred-ena> <rr-init-rexmit-delay> <rr-rapid-rexmit-ena> <rr-ack-delay> ] [ <rate-limit-ena>
<rate-limit-cap> <rate-limit-pace-intvl> ] [ <gr-tmr> [ <gr-tmr-expiry> ] ] [ <auth-ena> [ <key-src> ] [ <digest>
] [ <seq-winsize> ] [ <challenge> ] [ <lifetime> ] ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
rsvp	Display RSVP status
__readonly__	(Optional)
<i>sup-state</i>	(Optional)
<i>start-type</i>	(Optional)
<i>restart-type</i>	(Optional)
<i>ha-ena</i>	(Optional)
<i>gr-ena</i>	(Optional)
<i>hst-ena</i>	(Optional)
<i>glb-router-id</i>	(Optional)
<i>psr-ena</i>	(Optional)
<i>local-epoch</i>	(Optional)
<i>bundle-ena</i>	(Optional)
<i>bundle-time</i>	(Optional)
<i>bundle-maxsz</i>	(Optional)
<i>refresh-intvl</i>	(Optional)
<i>refresh-miss</i>	(Optional)
<i>refred-ena</i>	(Optional)
<i>rr-rapid-rexmit-ena</i>	(Optional)
<i>rr-init-rexmit-delay</i>	(Optional)
<i>rr-ack-delay</i>	(Optional)

<i>rate-limit-ena</i>	(Optional)
<i>rate-limit-cap</i>	(Optional)
<i>rate-limit-pace-intvl</i>	(Optional)
<i>gr-tmr</i>	(Optional)
<i>gr-tmr-expiry</i>	(Optional)
<i>auth-ena</i>	(Optional)
<i>key-src</i>	(Optional)
<i>digest</i>	(Optional)
<i>seq-winsize</i>	(Optional)
<i>challenge</i>	(Optional)
<i>lifetime</i>	(Optional)
TABLE_clients	(Optional)
<i>clnt-name</i>	(Optional)
<i>clnt-sap</i>	(Optional)
<i>clnt-type</i>	(Optional)
<i>clnt-batch-time</i>	(Optional)
<i>clnt-lxsb</i>	(Optional)

Command Mode

- /exec

show ip sla application

```
show ip sla application [ __readonly__ <version> [ <line-length> ] <type-name> <feature-name>
<lowmemorymark> <max-entries> <probe-cap> <entries-config> <entries-active> <entries-pending>
<entries-inactive> <last-change-time> <rttMonApplReset> [ <rttMonApplTimeOfLastSet> ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
application	IP SLAs Application
__readonly__	(Optional)
version	(Optional)
line-length	(Optional)
type-name	(Optional)
feature-name	(Optional)
lowmemorymark	(Optional)
max-entries	(Optional)
probe-cap	(Optional)
entries-config	(Optional)
entries-active	(Optional)
entries-pending	(Optional)
entries-inactive	(Optional)
last-change-time	(Optional)
rttMonApplReset	(Optional) Appl Reset
rttMonApplTimeOfLastSet	(Optional)

Command Mode

- /exec

show ip sla configuration

```
show ip sla configuration [ <entry-num> ] [ __readonly__ { TABLE_configuration [ <index> ] [ <owner> ]
[ <tag> ] [ <timeout> ] [ <oper-type> ] [ <dest-ip> ] [ <source-int> ] [ <source-ip> ] [ <dest-port> ] [
<source-port> ] [ <dns-source-port> ] [ <traffic-class> ] [ <tos> ] [ <dns-name-server> ] [ <flow-label> ] [
<data-pattern> ] [ <switch-id> ] [ <profile-id> ] [ <interface> ] [ <packet-size> ] [ <packet-interval> ] [
<num-packets> ] [ <codec-type> ] [ <codec-num-packets> ] [ <codec-packet-size> ] [ <codec-packet-interval>
] [ <codec-adv-factor> ] [ <verify-data> ] [ <precision> ] [ <packet-priority> ] [ <ntp-sync-tolerance> ] [
<ntp-sync-toltype> ] [ <vrf-name> ] [ <control-enabled> ] [ <http-oper> ] [ <http-version> ] [ <url> ] [ <proxy>
] [ <raw-strings> ] [ <cache-control> ] [ <http-vrf-name> ] [ <http-owner> ] [ <http-tag> ] [ <http-timeout>
] [ <frequency> ] [ <secondary-freq-timeout> ] [ <secondary-freq-loss> ] [ <next-start-time> ] [
<group-scheduled> ] [ <randomly-scheduled> ] [ <low-frequency> ] [ <high-frequency> ] [ <life> ] [ <ageout>
] [ <recurring> ] [ <status-of-entry> ] [ <threshold> ] [ <hours> ] [ <buckets> ] [ <interval> ] [ <einterval> ]
[ <ebuckets> ] [ <lives> ] [ <hsbuckets> ] [ <filter> ] } ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
configuration	IP SLA configurtaion
<i>entry-num</i>	(Optional) Entry Number
<i>__readonly__</i>	(Optional)
TABLE_configuration	(Optional) show ip sla configuration information
<i>index</i>	(Optional)
<i>owner</i>	(Optional)
<i>tag</i>	(Optional)
<i>timeout</i>	(Optional)
<i>oper-type</i>	(Optional)
<i>dest-ip</i>	(Optional)
<i>source-int</i>	(Optional)
<i>source-ip</i>	(Optional)
<i>dest-port</i>	(Optional)
<i>source-port</i>	(Optional)
<i>dns-source-port</i>	(Optional)
<i>traffic-class</i>	(Optional)

<i>tos</i>	(Optional)
<i>dns-name-server</i>	(Optional)
<i>flow-label</i>	(Optional)
<i>data-pattern</i>	(Optional)
<i>profile-id</i>	(Optional)
<i>switch-id</i>	(Optional)
<i>interface</i>	(Optional)
<i>packet-size</i>	(Optional)
<i>packet-interval</i>	(Optional)
<i>num-packets</i>	(Optional)
<i>codec-type</i>	(Optional)
<i>codec-num-packets</i>	(Optional)
<i>codec-packet-size</i>	(Optional)
<i>codec-packet-interval</i>	(Optional)
<i>codec-adv-factor</i>	(Optional)
<i>verify-data</i>	(Optional)
<i>precision</i>	(Optional)
<i>packet-priority</i>	(Optional)
<i>ntp-sync-tolerance</i>	(Optional)
<i>ntp-sync-toltype</i>	(Optional)
<i>vrf-name</i>	(Optional)
<i>control-enabled</i>	(Optional)
<i>http-oper</i>	(Optional)
<i>http-version</i>	(Optional)
<i>url</i>	(Optional)
<i>proxy</i>	(Optional)
<i>raw-strings</i>	(Optional)
<i>cache-control</i>	(Optional)
<i>http-vrf-name</i>	(Optional)

<i>http-owner</i>	(Optional)
<i>http-tag</i>	(Optional)
<i>http-timeout</i>	(Optional)
<i>frequency</i>	(Optional)
<i>secondary-freq-timeout</i>	(Optional)
<i>secondary-freq-loss</i>	(Optional)
<i>next-start-time</i>	(Optional)
<i>group-scheduled</i>	(Optional)
<i>randomly-scheduled</i>	(Optional)
<i>low-frequency</i>	(Optional)
<i>high-frequency</i>	(Optional)
<i>life</i>	(Optional)
<i>ageout</i>	(Optional)
<i>recurring</i>	(Optional)
<i>status-of-entry</i>	(Optional)
<i>threshold</i>	(Optional)
<i>hours</i>	(Optional)
<i>buckets</i>	(Optional)
<i>interval</i>	(Optional)
<i>einterval</i>	(Optional)
<i>ebuckets</i>	(Optional)
<i>lives</i>	(Optional)
<i>hsbuckets</i>	(Optional)
<i>filter</i>	(Optional)

Command Mode

- /exec

show ip sla enhanced-history collection-statistics

```
show ip sla enhanced-history collection-statistics [ <operation-number> [ interval <interval-in-secs> ] ] [
__readonly__ [ { TABLE_generic [ <entry-num> ] [ <aggregate-interval> ] [ { TABLE_bkt [ <bkt-index> ]
[ <agg-sti> ] [ <tgt-addr> ] [ <oper-type> ] [ <nofod> ] [ <nofot> ] [ <nofob> ] [ <nofonc> ] [ <nofoie> ] [
<nofose> ] [ <nofove> ] [ <ntp-state> ] [ <icpif> ] [ <mos-score> ] [ <rtt-values> ] [ <num-rtt> ] [ <rtt-avg>
] [ <rtt-min> ] [ <rtt-max> ] [ <rtt-sum> ] [ <rtt-sum2> ] [ <num-out-sync-rtt> ] [ <plsd> ] [ <plds> ] [ <pos>
] [ <pl-mia> ] [ <pla> ] [ <int-err> ] [ <busies> ] [ <pkt-skipped> ] [ <jitter-value-precision> ] [ <min-pos-sd>
] [ <max-pos-sd> ] [ <num-pos-sd> ] [ <sum-pos-sd> ] [ <sum2-pos-sd> ] [ <min-neg-sd> ] [ <max-neg-sd>
] [ <num-neg-sd> ] [ <sum-neg-sd> ] [ <sum2-neg-sd> ] [ <min-pos-ds> ] [ <max-pos-ds> ] [ <num-pos-ds>
] [ <sum-pos-ds> ] [ <sum2-pos-ds> ] [ <min-neg-ds> ] [ <max-neg-ds> ] [ <num-neg-ds> ] [ <sum-neg-ds>
] [ <sum2-neg-ds> ] [ <jitter-avg> ] [ <jitter-sd-avg> ] [ <jitter-ds-avg> ] [ <inter-jit-out> ] [ <inter-jit-in> ]
[ <ow-precision> ] [ <num-ow> ] [ <ow-min-sd> ] [ <ow-max-sd> ] [ <ow-sum-sd> ] [ <ow-sum2-sd> ] [
<ow-min-ds> ] [ <ow-max-ds> ] [ <ow-sum-ds> ] [ <ow-sum2-ds> ] [ <avg-ow-sd> ] [ <avg-ow-ds> ] } ] [
<outstring> ] } ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
enhanced-history	IP SLAs Enhanced History
collection-statistics	IP SLAs Collection Statistics
<i>operation-number</i>	(Optional) Entry Number
interval	(Optional) Aggregation Interval
<i>interval-in-secs</i>	(Optional) Interval in seconds
__readonly__	(Optional)
TABLE_generic	(Optional) Show History Information
<i>entry-num</i>	(Optional)
<i>aggregate-interval</i>	(Optional)
TABLE_bkt	(Optional) Show bucket History Information
<i>bkt-index</i>	(Optional)
<i>agg-sti</i>	(Optional)
<i>tgt-addr</i>	(Optional)
<i>oper-type</i>	(Optional)
<i>nofod</i>	(Optional)

<i>nofot</i>	(Optional)
<i>nofob</i>	(Optional)
<i>nofonc</i>	(Optional)
<i>nofoie</i>	(Optional)
<i>nofose</i>	(Optional)
<i>nofove</i>	(Optional)
<i>ntp-state</i>	(Optional)
<i>icpif</i>	(Optional)
<i>mos-score</i>	(Optional)
<i>rtt-values</i>	(Optional)
<i>num-rtt</i>	(Optional)
<i>rtt-avg</i>	(Optional)
<i>rtt-min</i>	(Optional)
<i>rtt-max</i>	(Optional)
<i>rtt-sum</i>	(Optional)
<i>rtt-sum2</i>	(Optional)
<i>num-out-sync-rtt</i>	(Optional)
<i>plsd</i>	(Optional)
<i>plds</i>	(Optional)
<i>pos</i>	(Optional)
<i>pl-mia</i>	(Optional)
<i>pla</i>	(Optional)
<i>int-err</i>	(Optional)
<i>busies</i>	(Optional)
<i>pkt-skipped</i>	(Optional)
<i>jitter-value-precision</i>	(Optional)
<i>min-pos-sd</i>	(Optional)
<i>max-pos-sd</i>	(Optional)
<i>num-pos-sd</i>	(Optional)

<i>sum-pos-sd</i>	(Optional)
<i>sum2-pos-sd</i>	(Optional)
<i>min-neg-sd</i>	(Optional)
<i>max-neg-sd</i>	(Optional)
<i>num-neg-sd</i>	(Optional)
<i>sum-neg-sd</i>	(Optional)
<i>sum2-neg-sd</i>	(Optional)
<i>min-pos-ds</i>	(Optional)
<i>max-pos-ds</i>	(Optional)
<i>num-pos-ds</i>	(Optional)
<i>sum-pos-ds</i>	(Optional)
<i>sum2-pos-ds</i>	(Optional)
<i>min-neg-ds</i>	(Optional)
<i>max-neg-ds</i>	(Optional)
<i>num-neg-ds</i>	(Optional)
<i>sum-neg-ds</i>	(Optional)
<i>sum2-neg-ds</i>	(Optional)
<i>jitter-avg</i>	(Optional)
<i>jitter-sd-avg</i>	(Optional)
<i>jitter-ds-avg</i>	(Optional)
<i>inter-jit-out</i>	(Optional)
<i>inter-jit-in</i>	(Optional)
<i>ow-precision</i>	(Optional)
<i>num-ow</i>	(Optional)
<i>ow-min-sd</i>	(Optional)
<i>ow-max-sd</i>	(Optional)
<i>ow-sum-sd</i>	(Optional)
<i>ow-sum2-sd</i>	(Optional)
<i>ow-min-ds</i>	(Optional)

<i>ow-max-ds</i>	(Optional)
<i>ow-sum-ds</i>	(Optional)
<i>ow-sum2-ds</i>	(Optional)
<i>avg-ow-sd</i>	(Optional)
<i>avg-ow-ds</i>	(Optional)
<i>outstring</i>	(Optional)

Command Mode

- /exec

show ip sla enhanced-history distribution-statistics

```
show ip sla enhanced-history distribution-statistics [ <operation-number> [ interval <interval-in-secs> ] ] [
__readonly__ [ <hdr> ] [ { TABLE_generic [ <col1> ] [ <col2> ] [ <col3> ] } ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
enhanced-history	IP SLAs Enhanced History
distribution-statistics	IP SLAs Distribution Statistics
<i>operation-number</i>	(Optional) Entry Number
interval	(Optional) Aggregation Interval
<i>interval-in-secs</i>	(Optional) Interval in seconds
<i>__readonly__</i>	(Optional)
<i>hdr</i>	(Optional)
TABLE_generic	(Optional) Show History Information
<i>col1</i>	(Optional)
<i>col2</i>	(Optional)
<i>col3</i>	(Optional)

Command Mode

- /exec

show ip sla group schedule

```
show ip sla group schedule [ <group-operation-number> ] [ __readonly__ [ <entry-number> ] [ <probe-list>
] [ <num-probes> ] [ <sched-period> ] [ <mode> ] [ <low-freq> ] [ <high-freq> ] [ <freq> ] [ <snmp-status>
] [ <next-start-time> ] [ <life> ] [ <ageout> ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
group	IP SLAs Group Scheduling/Configuration
schedule	Group Scheduling
<i>group-operation-number</i>	(Optional) Group Schedule Entry Number
<i>__readonly__</i>	(Optional)
<i>entry-number</i>	(Optional)
<i>probe-list</i>	(Optional)
<i>num-probes</i>	(Optional)
<i>sched-period</i>	(Optional)
<i>mode</i>	(Optional)
<i>low-freq</i>	(Optional)
<i>high-freq</i>	(Optional)
<i>freq</i>	(Optional)
<i>snmp-status</i>	(Optional)
<i>next-start-time</i>	(Optional)
<i>life</i>	(Optional)
<i>ageout</i>	(Optional)

Command Mode

- /exec

show ip sla history

```
show ip sla history [ <operation-number> ] [ tabular | full | interval-statistics ] [ __readonly__ [ <outstring> ] ] [ { TABLE_generic [ <index> ] [ <life-index> ] [ <bucket-index> ] [ <col1> ] [ <addr> ] [ <dest-id> ] [ <nsr> ] [ <st> ] [ <latest-rtt> ] [ <latest-ret-code> ] [ <col2> ] } ] [ <error> ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
history	IP SLAs History
<i>operation-number</i>	(Optional) Entry Number
tabular	(Optional) Compact Output
full	(Optional) Listed Output
interval-statistics	(Optional) Interval statistics output
__readonly__	(Optional)
<i>outstring</i>	(Optional)
TABLE_generic	(Optional) Show History Information
<i>index</i>	(Optional)
<i>life-index</i>	(Optional)
<i>bucket-index</i>	(Optional)
<i>col1</i>	(Optional)
<i>addr</i>	(Optional)
<i>dest-id</i>	(Optional)
<i>nsr</i>	(Optional)
<i>st</i>	(Optional)
<i>latest-rtt</i>	(Optional)
<i>latest-ret-code</i>	(Optional)
<i>col2</i>	(Optional)
<i>error</i>	(Optional)

Command Mode

- /exec

show ip sla reaction-configuration

```
show ip sla reaction-configuration [ <entry-num> ] [ __readonly__ [ { TABLE_reaction <entry-number> [
<index> ] [ <reaction> ] [ <threshold-type> ] [ <rising-value> ] [ <falling-value> ] [ <threshold-countX> ] [
<threshold-countY> ] [ <action-type> ] [ <unconfigured> } } ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
reaction-configuration	IP SLAs Reaction Configuration
<i>entry-num</i>	(Optional) Entry Number
<i>__readonly__</i>	(Optional)
TABLE_reaction	(Optional)
<i>entry-number</i>	(Optional)
<i>index</i>	(Optional)
<i>reaction</i>	(Optional)
<i>threshold-type</i>	(Optional)
<i>rising-value</i>	(Optional)
<i>falling-value</i>	(Optional)
<i>threshold-countX</i>	(Optional)
<i>threshold-countY</i>	(Optional)
<i>action-type</i>	(Optional)
<i>unconfigured</i>	(Optional)

Command Mode

- /exec

show ip sla reaction-trigger

```
show ip sla reaction-trigger [ <entry-num> ] [ __readonly__ [ { TABLE_trigger <entry-number> [ <index> ] [ <target-entry> ] [ <snmp-status> ] [ <operational-state> ] [ <unconfigured> ] } ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
reaction-trigger	IP SLAs Reaction Trigger
<i>entry-num</i>	(Optional) Entry Number
<i>__readonly__</i>	(Optional)
<i>TABLE_trigger</i>	(Optional)
<i>entry-number</i>	(Optional)
<i>index</i>	(Optional)
<i>target-entry</i>	(Optional)
<i>snmp-status</i>	(Optional)
<i>operational-state</i>	(Optional)
<i>unconfigured</i>	(Optional)

Command Mode

- /exec

show ip sla responder

```
show ip sla responder [ __readonly__ <rttMonApplResponder> <gen-enabled> [ <ctrl-msg-count> ] [ <errors>
] [ { TABLE_recent [ <print-recent-hdr> ] [ <print-recent-err-hdr> ] [ <recent-addr> ] [ <recent-time> ] [
<recent-error> ] } ] <perm-enabled> [ { TABLE_permanent_udp [ <print-udp-hdr> ] [ <address> ] [ <port>
] } ] [ { TABLE_permanent_tcp [ <print-tcp-hdr> ] [ <address> ] [ <port> ] } ] ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
responder	IP SLAs Responder Information
__readonly__	(Optional)
<i>rttMonApplResponder</i>	(Optional) rttMonApplResponder
<i>gen-enabled</i>	(Optional)
<i>ctrl-msg-count</i>	(Optional)
<i>errors</i>	(Optional)
TABLE_recent	(Optional) Show recent control message information
<i>print-recent-hdr</i>	(Optional)
<i>print-recent-err-hdr</i>	(Optional)
<i>recent-addr</i>	(Optional)
<i>recent-time</i>	(Optional)
<i>recent-error</i>	(Optional)
<i>perm-enabled</i>	(Optional)
TABLE_permanent_udp	(Optional) Show UDP permanent port/address information
<i>print-udp-hdr</i>	(Optional)
<i>address</i>	(Optional)
<i>port</i>	(Optional)
TABLE_permanent_tcp	(Optional) Show TCP permanent port/address information
<i>print-tcp-hdr</i>	(Optional)
<i>address</i>	(Optional)

<i>port</i>	(Optional)
-------------	------------

Command Mode

- /exec

show ip sla statistics

```
show ip sla statistics [ aggregated ] [ <entry-num> ] [ details ] [ __readonly__ <print_type> ] [ { TABLE_stats
[ <index> ] [ <top> ] [ { TABLE_detail [ <sti> ] [ <operation-type> ] [ <MINICPIF> ] [ <MAXICPIF> ] [
<MINMOS> ] [ <MAXMOS> ] [ <update-count> ] [ <micro-accuracy> ] [ <nano-accuracy> ] [ <latest-RTT>
] [ <latest-return-code> ] [ <latest-start-time> ] [ <http-dns-rtt> ] [ <http-tcp-rtt> ] [ <http-ttfb> ] [ <http-rtt>
] [ <http-status> ] [ <http-recvlen> ] [ <http-bodysize> ] [ <http-dns-timeout> ] [ <http-tcp-timeout> ] [
<http-t-timeout> ] [ <http-dns-error> ] [ <http-tcp-error> ] [ <http-t-error> ] [ <ntp-sync-state> ] [ <rtt-count>
] [ <rtt-min> ] [ <rtt-avg> ] [ <rtt-max> ] [ <lat-ow-samples> ] [ <sd-lat-ow-min> ] [ <sd-lat-ow-avg> ] [
<sd-lat-ow-max> ] [ <ds-lat-ow-min> ] [ <ds-lat-ow-avg> ] [ <ds-lat-ow-max> ] [ <sd-lat-sum> ] [
<sd-lat-sum2> ] [ <ds-lat-sum> ] [ <ds-lat-sum2> ] [ <sd-jitter-count> ] [ <ds-jitter-count> ] [ <sd-jitter-min>
] [ <sd-jitter-avg> ] [ <sd-jitter-max> ] [ <ds-jitter-min> ] [ <ds-jitter-avg> ] [ <ds-jitter-max> ] [
<sd-pos-jitter-min> ] [ <sd-pos-jitter-avg> ] [ <sd-pos-jitter-max> ] [ <sd-pos-jitter-num> ] [ <sd-pos-jitter-sum>
] [ <sd-pos-jitter-sum2> ] [ <sd-neg-jitter-min> ] [ <sd-neg-jitter-avg> ] [ <sd-neg-jitter-max> ] [
<sd-neg-jitter-num> ] [ <sd-neg-jitter-sum> ] [ <sd-neg-jitter-sum2> ] [ <ds-pos-jitter-min> ] [
<ds-pos-jitter-avg> ] [ <ds-pos-jitter-max> ] [ <ds-pos-jitter-num> ] [ <ds-pos-jitter-sum> ] [
<ds-pos-jitter-sum2> ] [ <ds-neg-jitter-min> ] [ <ds-neg-jitter-avg> ] [ <ds-neg-jitter-max> ] [
<ds-neg-jitter-num> ] [ <ds-neg-jitter-sum> ] [ <ds-neg-jitter-sum2> ] [ <pkt-unprocessed> ] [ <pkt-loss> ]
[ <pkt-loss-per> ] [ <pkt-loss-min> ] [ <pkt-loss-max> ] [ <pkt-loss-inter-min> ] [ <pkt-loss-inter-max> ] [
<inter-jitter-out> ] [ <inter-jitter-in> ] [ <jitter-avg> ] [ <pkt-loss-sd> ] [ <pkt-loss-sd-per> ] [ <pkt-loss-sd-min>
] [ <pkt-loss-sd-max> ] [ <pkt-loss-sd-inter-min> ] [ <pkt-loss-sd-inter-max> ] [ <pkt-loss-ds> ] [
<pkt-loss-ds-per> ] [ <pkt-loss-ds-min> ] [ <pkt-loss-ds-max> ] [ <pkt-loss-ds-inter-min> ] [
<pkt-loss-ds-inter-max> ] [ <pkt-oos> ] [ <pkt-oos-sd> ] [ <pkt-oos-ds> ] [ <pkt-oos-both> ] [ <pkt-mia> ] [
<pkt-late> ] [ <pkt-skipped> ] [ <voice-icpif> ] [ <voice-mos> ] [ <dnobs> ] [ <dmam> ] [ <dtoo> ] [ <dmin>
] [ <dmax> ] [ <pnobs> ] [ <pmam> ] [ <ptoo> ] [ <pmin> ] [ <pmax> ] [ <nnobs> ] [ <nmam> ] [ <ntoo> ]
[ <nmin> ] [ <nmax> ] [ <outstring1> ] [ <outstring2> ] [ <nos> ] [ <nof> ] [ <noot> ] [ <nofo1> ] [ <nofo2>
] [ { TABLE_br [ <br> ] [ <avg-lat> ] [ <potc> ] [ <noc-by-lat> ] [ <sortthigh-by-low> ] [ <operot> ] } } ]
[ <life-left> ] [ <oper-state> ] [ <reset-time> ] [ <nob> ] [ <bbh> ] [ <bbv> ] } } ]
```

Syntax Description

show	
ip	
sla	Service Level Agreement (SLA)
statistics	IP SLAs Statistics
<i>entry-num</i>	(Optional) Entry Number
details	(Optional) Detailed Output
aggregated	(Optional) IP SLAs Statistics Aggregated
<i>__readonly__</i>	(Optional)
<i>print_type</i>	(Optional)
TABLE_stats	(Optional) Show ip sla statistics information
<i>index</i>	(Optional)

<i>top</i>	(Optional)
TABLE_detail	(Optional) Show ip sla statistics detail information
<i>sti</i>	(Optional)
<i>operation-type</i>	(Optional)
<i>MINICPIF</i>	(Optional)
<i>MAXICPIF</i>	(Optional)
<i>MINMOS</i>	(Optional)
<i>MAXMOS</i>	(Optional)
<i>update-count</i>	(Optional)
<i>micro-accuracy</i>	(Optional)
<i>nano-accuracy</i>	(Optional)
<i>latest-RTT</i>	(Optional)
<i>latest-return-code</i>	(Optional)
<i>latest-start-time</i>	(Optional)
<i>http-dns-rtt</i>	(Optional)
<i>http-tcp-rtt</i>	(Optional)
<i>http-ttfb</i>	(Optional)
<i>http-rtt</i>	(Optional)
<i>http-status</i>	(Optional)
<i>http-recvlen</i>	(Optional)
<i>http-bodysize</i>	(Optional)
<i>http-dns-timeout</i>	(Optional)
<i>http-tcp-timeout</i>	(Optional)
<i>http-t-timeout</i>	(Optional)
<i>http-dns-error</i>	(Optional)
<i>http-tcp-error</i>	(Optional)
<i>http-t-error</i>	(Optional)
<i>ntp-sync-state</i>	(Optional)
<i>rtt-count</i>	(Optional)

<i>rtt-min</i>	(Optional)
<i>rtt-avg</i>	(Optional)
<i>rtt-max</i>	(Optional)
<i>lat-ow-samples</i>	(Optional)
<i>sd-lat-ow-min</i>	(Optional)
<i>sd-lat-ow-avg</i>	(Optional)
<i>sd-lat-ow-max</i>	(Optional)
<i>ds-lat-ow-min</i>	(Optional)
<i>ds-lat-ow-avg</i>	(Optional)
<i>ds-lat-ow-max</i>	(Optional)
<i>sd-lat-sum</i>	(Optional)
<i>sd-lat-sum2</i>	(Optional)
<i>ds-lat-sum</i>	(Optional)
<i>ds-lat-sum2</i>	(Optional)
<i>sd-jitter-count</i>	(Optional)
<i>ds-jitter-count</i>	(Optional)
<i>sd-jitter-min</i>	(Optional)
<i>sd-jitter-avg</i>	(Optional)
<i>sd-jitter-max</i>	(Optional)
<i>ds-jitter-min</i>	(Optional)
<i>ds-jitter-avg</i>	(Optional)
<i>ds-jitter-max</i>	(Optional)
<i>sd-pos-jitter-min</i>	(Optional)
<i>sd-pos-jitter-avg</i>	(Optional)
<i>sd-pos-jitter-max</i>	(Optional)
<i>sd-pos-jitter-num</i>	(Optional)
<i>sd-pos-jitter-sum</i>	(Optional)
<i>sd-pos-jitter-sum2</i>	(Optional)
<i>sd-neg-jitter-min</i>	(Optional)

<i>sd-neg-jitter-avg</i>	(Optional)
<i>sd-neg-jitter-max</i>	(Optional)
<i>sd-neg-jitter-num</i>	(Optional)
<i>sd-neg-jitter-sum</i>	(Optional)
<i>sd-neg-jitter-sum2</i>	(Optional)
<i>ds-pos-jitter-min</i>	(Optional)
<i>ds-pos-jitter-avg</i>	(Optional)
<i>ds-pos-jitter-max</i>	(Optional)
<i>ds-pos-jitter-num</i>	(Optional)
<i>ds-pos-jitter-sum</i>	(Optional)
<i>ds-pos-jitter-sum2</i>	(Optional)
<i>ds-neg-jitter-min</i>	(Optional)
<i>ds-neg-jitter-avg</i>	(Optional)
<i>ds-neg-jitter-max</i>	(Optional)
<i>ds-neg-jitter-num</i>	(Optional)
<i>ds-neg-jitter-sum</i>	(Optional)
<i>ds-neg-jitter-sum2</i>	(Optional)
<i>pkt-unprocessed</i>	(Optional)
<i>pkt-loss</i>	(Optional)
<i>pkt-loss-per</i>	(Optional)
<i>pkt-loss-min</i>	(Optional)
<i>pkt-loss-max</i>	(Optional)
<i>pkt-loss-inter-min</i>	(Optional)
<i>pkt-loss-inter-max</i>	(Optional)
<i>inter-jitter-out</i>	(Optional)
<i>inter-jitter-in</i>	(Optional)
<i>jitter-avg</i>	(Optional)
<i>pkt-loss-sd</i>	(Optional)
<i>pkt-loss-sd-per</i>	(Optional)

<i>pkt-loss-sd-min</i>	(Optional)
<i>pkt-loss-sd-max</i>	(Optional)
<i>pkt-loss-sd-inter-min</i>	(Optional)
<i>pkt-loss-sd-inter-max</i>	(Optional)
<i>pkt-loss-ds</i>	(Optional)
<i>pkt-loss-ds-per</i>	(Optional)
<i>pkt-loss-ds-min</i>	(Optional)
<i>pkt-loss-ds-max</i>	(Optional)
<i>pkt-loss-ds-inter-min</i>	(Optional)
<i>pkt-loss-ds-inter-max</i>	(Optional)
<i>pkt-oos</i>	(Optional)
<i>pkt-oos-sd</i>	(Optional)
<i>pkt-oos-ds</i>	(Optional)
<i>pkt-oos-both</i>	(Optional)
<i>pkt-mia</i>	(Optional)
<i>pkt-late</i>	(Optional)
<i>pkt-skipped</i>	(Optional)
<i>voice-icpif</i>	(Optional)
<i>voice-mos</i>	(Optional)
<i>dnobs</i>	(Optional)
<i>dmam</i>	(Optional)
<i>dtoo</i>	(Optional)
<i>dmin</i>	(Optional)
<i>dmax</i>	(Optional)
<i>pnobs</i>	(Optional)
<i>pmam</i>	(Optional)
<i>ptoo</i>	(Optional)
<i>pmin</i>	(Optional)
<i>pmax</i>	(Optional)

<i>nnobs</i>	(Optional)
<i>nmam</i>	(Optional)
<i>ntoo</i>	(Optional)
<i>nmin</i>	(Optional)
<i>nmax</i>	(Optional)
<i>outstring1</i>	(Optional)
<i>outstring2</i>	(Optional)
<i>nos</i>	(Optional)
<i>nof</i>	(Optional)
<i>noot</i>	(Optional)
<i>nofo1</i>	(Optional)
<i>nofo2</i>	(Optional)
TABLE_br	(Optional) Bin range related info
<i>br</i>	(Optional)
<i>avg-lat</i>	(Optional)
<i>potc</i>	(Optional)
<i>noc-by-lat</i>	(Optional)
<i>sortthigh-by-low</i>	(Optional)
<i>operot</i>	(Optional)
<i>life-left</i>	(Optional)
<i>oper-state</i>	(Optional)
<i>reset-time</i>	(Optional)
<i>nob</i>	(Optional)
<i>bbh</i>	(Optional)
<i>bbv</i>	(Optional)

Command Mode

- /exec

show ip ssh source-interface

```
show ip ssh source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_ipsshvrf  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
ssh	Display SSH client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ipsshvrf	(Optional) source interface of ssh given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip ssh source-interface vrf all

show ip ssh source-interface vrf all [__readonly__ [{ TABLE_ipssh <vrfname> <ifname> }]]

Syntax Description

show	Show running system information
ip	Display IP information
ssh	Display SSH client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ipssh	(Optional) source interface of ssh
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip static-route

```
show ip static-route [ multicast ] [ internal ] [ track-table ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ [ <count> <unres-count> ] [ TABLE_vrf_all { <cntxt_name> <cntxt_id> [ TABLE_each_vrf
{ <prefix_addr_msk> <nhop_addr_msk> <nhop_vrf_info> <nhop_intr_info> <urib_stat> [ <seg_id> ] [
<tunnel_id> <urib_encap_type> ] <nhop_urib_stat> [ <track_obj_num> <track_obj_state> ] } ] } ] [
TABLE_multicast <multicast> ] [ TABLE_track-table ] [ TABLE_route <prefix> <masklen> <nhop>
<nhop-masklen> <intf> <real-nhop> <iod> <pref> <tag> <unres> ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
static-route	Display configured static routes
multicast	(Optional) Display only multicast routes
internal	(Optional) Display internal data structure info
track-table	(Optional) Display track object details associated with static routes
vrf	(Optional) Display per-VRF information
all	(Optional) Display all VRFs
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_vrf_all	(Optional)
<i>cntxt_name</i>	(Optional)
<i>cntxt_id</i>	(Optional)
TABLE_each_vrf	(Optional)
<i>prefix_addr_msk</i>	(Optional)
<i>nhop_addr_msk</i>	(Optional)
<i>nhop_vrf_info</i>	(Optional)
<i>nhop_intr_info</i>	(Optional)
<i>urib_stat</i>	(Optional)
<i>seg_id</i>	(Optional)
<i>tunnel_id</i>	(Optional)

<i>urib_encap_type</i>	(Optional)
<i>nhop_urib_stat</i>	(Optional)
<i>track_obj_num</i>	(Optional)
<i>track_obj_state</i>	(Optional)
TABLE_multicast	(Optional)
<i>multicast</i>	(Optional)
TABLE_track-table	(Optional)
TABLE_route	(Optional)
<i>prefix</i>	(Optional)
<i>masklen</i>	(Optional)
<i>nhop</i>	(Optional)
<i>nhop-masklen</i>	(Optional)
<i>intf</i>	(Optional)
<i>real-nhop</i>	(Optional)
<i>iod</i>	(Optional)
<i>pref</i>	(Optional)
<i>tag</i>	(Optional)
<i>unres</i>	(Optional)
<i>count</i>	(Optional)
<i>unres-count</i>	(Optional)

Command Mode

- /exec

show ip stats

show ip stats

Syntax Description

show	Show running system information
ip	Display IP information
stats	Display IP internal stats

Command Mode

- /exec

show ip telnet source-interface

```
show ip telnet source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ {  
TABLE_ip telnet vrf <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
telnet	Display telnet information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ip telnet vrf	(Optional) source interface of telnet given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip telnet source-interface vrf all

```
show ip telnet source-interface vrf all [ __readonly__ [ { TABLE_ip telnet <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
telnet	Display telnet information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ip telnet	(Optional) source interface of telnet
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip tftp source-interface

```
show ip tftp source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_ipftpvrf  
<vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
tftp	Display TFTP client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_ipftpvrf	(Optional) source interface of tftp given vrf
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip tftp source-interface vrf all

```
show ip tftp source-interface vrf all [ __readonly__ [ { TABLE_ip tftp <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
tftp	Display TFTP client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_ip tftp	(Optional) source interface of tftp
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip traceroute source-interface

```
show ip traceroute source-interface [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ {  
TABLE_iptraceroutevrf <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
traceroute	Display traceroute client information
source-interface	Display source interface information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional)
TABLE_iptraceroutevrf	(Optional) source interface of traceroute
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip traceroute source-interface vrf all

```
show ip traceroute source-interface vrf all [ __readonly__ [ { TABLE_iptraceroute <vrfname> <ifname> } ] ]
```

Syntax Description

show	Show running system information
ip	Display IP information
traceroute	Display traceroute client information
source-interface	Display source interface information
vrf	Display per-VRF information
all	Display entries for all vrfs
__readonly__	(Optional)
TABLE_iptraceroute	(Optional) source interface of traceroute
<i>vrfname</i>	(Optional) vrfname
<i>ifname</i>	(Optional) ifname

Command Mode

- /exec

show ip traffic

```
show ip traffic [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__ [ { TABLE_vrf [ <vrf-name-out>
] } ] [ { TABLE_ip_soft_processed_traffic [ { TABLE_trans_and_reception [ <rcvd> ] [ <sent> ] [ <consumed>
] [ <fwd-ucast> ] [ <fwd-mcast> ] [ <fwd-label> ] [ <ingress-mcecfwd> ] } ] [ { TABLE_opts [ <opts-end>
] [ <opts-nop> ] [ <opts-bsec> ] [ <opts-loosesrc-route> ] [ <opts-timestamp> ] [ <opts-esec> ] [
<opts-record-route> ] [ <opts-stid> ] [ <opts-strsrc-route> ] [ <opts-alert> ] [ <opts-cipso> ] [ <opts-ump> ]
[ <opts-other> ] } ] [ { TABLE_errors [ <bad-csum> ] [ <too-small> ] [ <bad-ver> ] [ <bad-hlen> ] [ <bad-len>
] [ <bad-dest> ] [ <bad-ttl> ] [ <cant-fwd> ] [ <out-drop> ] [ <bad-encap> ] [ <no-route> ] [ <no-proto> ] [
<bad-options> ] [ <vinci> ] [ <snoop> ] [ <svi> ] [ <restart-recovery> ] [ <mbuf-fail> ] [ <bad-context> ] [
<rpf-drops> ] [ <bad-gw-mac> ] [ <ing-ips-option-fail> ] [ <nat-in-drop> ] [ <nat-out-drop> ] [
<ing-option-proc-fail> ] [ <ing-mfwd-fail> ] [ <ing-lisp-drop> ] [ <ing-lisp-decap-drop> ] [
<ing-lisp-encap-drop> ] [ <ing-lisp-encap> ] [ <ing-mfwd-copy-drop> ] [ <ing-ra-reass-drop> ] [
<ing-icmp-redirect> ] [ <ing-drop-ifmgr-init> ] [ <ing-drop-invlld-filter> ] [ <ing-drop-invlld-l2-msg> ] [
<ingress> ] [ <egrees> ] [ <directed_bdcast> ] } ] [ { TABLE_fragment [ <frag> ] [ <fragmented> ] [ <out-frag>
] [ <frag-drop> ] [ <cant-frag> ] [ <reasm> ] [ <frag-to> ] } ] } ] [ { TABLE_icmp_software_proc_traffic [ {
TABLE_transmission [ <tx-redir> ] [ <tx-unreach> ] [ <tx-echo-req> ] [ <tx-echo-reply> ] [ <tx-mask-req>
] [ <tx-mask-rep> ] [ <tx-info-req> ] [ <tx-info-reply> ] [ <tx-param-prob> ] [ <tx-source-quench> ] [
<tx-tstamp-req> ] [ <tx-tstamp-reply> ] [ <tx-time-exceeded> ] [ <tx-router-solicit> ] [ <tx-router-advert> ]
[ <out-drop-badlen> ] [ <encap-fail> ] [ <xmit-fail> ] [ <icmp-originate> ] [ <redirect-originate-req> ] [
<originate-deny> ] [ <short-ip> ] [ <old-icmp> ] [ <error-drop> ] } ] [ { TABLE_reception [ <rx-redir> ] [
<rx-unreach> ] [ <rx-echo-req> ] [ <rx-echo-reply> ] [ <rx-mask-req> ] [ <rx-mask-rep> ] [ <rx-info-req> ]
[ <rx-info-reply> ] [ <rx-param-prob> ] [ <rx-source-quench> ] [ <rx-tstamp-req> ] [ <rx-tstamp-reply> ] [
<rx-time-exceeded> ] [ <rx-router-solicit> ] [ <rx-router-advert> ] [ <rx-format-errors> ] [ <rx-csum-errors>
] [ <lisp-processed> ] [ <lisp-noclient> ] [ <lisp-consumed> ] [ <icmp-replies> ] [ <icmp-reply-drop> ] [
<icmp-inactive-addr> ] } ] [ { TABLE_stat_last_never [ <stat-last-never> ] } ] } ] [ {
TABLE_rfc4293_ip_soft_proc_traffic [ { TABLE_rfc_reception [ <inrcv> ] [ <inocet> ] [ <inhdrerr> ] [
<innoroutes> ] [ <inaddrerr> ] [ <innoproto> ] [ <intruncated> ] [ <inforw> ] [ <reasmreqds> ] [ <reasmoks>
] [ <reasmfails> ] [ <indiscards> ] [ <indelivers> ] [ <inmcastpkts> ] [ <inmcastbytes> ] [ <inbastpkts> ] } ]
[ { TABLE_rfc_transmission [ <tr-pkt-sent> ] [ <tr-bytes-sent> ] [ <tr-out-req> ] [ <tr-outno-routes> ] [
<tr-out-frwdgrams> ] [ <tr-outdiscards> ] [ <tr-outfragreqds> ] [ <tr-outfragoks> ] [ <tr-outfragfails> ] [
<tr-outfragcreates> ] [ <tr-outtransmits> ] [ <tr-bytes-sent-end> ] [ <tr-outmcast-pkts> ] [ <tr-outmcast-bytes>
] [ <tr-outbcastpkts> ] [ <tr-outbcastbytes> ] } ] } ] }
```

Syntax Description

show	Show running system information
ip	Display IP information
traffic	Display IP software processed traffic statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
__readonly__	(Optional)
TABLE_vrf	(Optional)

<i>vrf-name-out</i>	(Optional)
TABLE_ip_soft_processed_traffic	(Optional)
TABLE_trans_and_reception	(Optional)
<i>rcvd</i>	(Optional)
<i>sent</i>	(Optional)
<i>consumed</i>	(Optional)
<i>fwd-ucast</i>	(Optional)
<i>fwd-mcast</i>	(Optional)
<i>fwd-label</i>	(Optional)
<i>ingress-mcecfwd</i>	(Optional)
TABLE_opts	(Optional)
<i>opts-end</i>	(Optional)
<i>opts-nop</i>	(Optional)
<i>opts-bsec</i>	(Optional)
<i>opts-loosesrc-route</i>	(Optional)
<i>opts-timestamp</i>	(Optional)
<i>opts-esec</i>	(Optional)
<i>opts-record-route</i>	(Optional)
<i>opts-ump</i>	(Optional)
<i>opts-stid</i>	(Optional)
<i>opts-strsrc-route</i>	(Optional)
<i>opts-alert</i>	(Optional)
<i>opts-cipso</i>	(Optional)
<i>opts-other</i>	(Optional)
TABLE_errors	(Optional)
<i>bad-csum</i>	(Optional)
<i>too-small</i>	(Optional)
<i>bad-ver</i>	(Optional)
<i>bad-hlen</i>	(Optional)

<i>bad-len</i>	(Optional)
<i>bad-dest</i>	(Optional)
<i>bad-ttl</i>	(Optional)
<i>cant-fwd</i>	(Optional)
<i>out-drop</i>	(Optional)
<i>bad-encap</i>	(Optional)
<i>no-route</i>	(Optional)
<i>no-proto</i>	(Optional)
<i>bad-options</i>	(Optional)
<i>vinci</i>	(Optional)
<i>snoop</i>	(Optional)
<i>svi</i>	(Optional)
<i>restart-recovery</i>	(Optional)
<i>mbuf-fail</i>	(Optional)
<i>bad-context</i>	(Optional)
<i>rpf-drops</i>	(Optional)
<i>bad-gw-mac</i>	(Optional)
<i>ing-ips-option-fail</i>	(Optional)
<i>nat-in-drop</i>	(Optional)
<i>nat-out-drop</i>	(Optional)
<i>ing-option-proc-fail</i>	(Optional)
<i>ing-mfwd-fail</i>	(Optional)
<i>ing-lisp-drop</i>	(Optional)
<i>ing-lisp-decap-drop</i>	(Optional)
<i>ing-lisp-encap-drop</i>	(Optional)
<i>ing-lisp-encap</i>	(Optional)
<i>ing-mfwd-copy-drop</i>	(Optional)
<i>ing-ra-reass-drop</i>	(Optional)
<i>ing-icmp-redirect</i>	(Optional)

<i>ing-drop-ifmgr-init</i>	(Optional)
<i>ing-drop-invld-filter</i>	(Optional)
<i>ing-drop-invld-l2-msg</i>	(Optional)
<i>ingress</i>	(Optional)
<i>egrees</i>	(Optional)
<i>directed_bdcast</i>	(Optional)
TABLE_fragment	(Optional)
<i>frag</i>	(Optional)
<i>fragmented</i>	(Optional)
<i>out-frag</i>	(Optional)
<i>frag-drop</i>	(Optional)
<i>cant-frag</i>	(Optional)
<i>reasm</i>	(Optional)
<i>frag-to</i>	(Optional)
TABLE_icmp_software_proc_traffic	(Optional)
TABLE_transmission	(Optional)
<i>tx-redir</i>	(Optional)
<i>tx-unreach</i>	(Optional)
<i>tx-echo-req</i>	(Optional)
<i>tx-echo-reply</i>	(Optional)
<i>tx-mask-req</i>	(Optional)
<i>tx-mask-reply</i>	(Optional)
<i>tx-info-req</i>	(Optional)
<i>tx-info-reply</i>	(Optional)
<i>tx-param-prob</i>	(Optional)
<i>tx-source-quench</i>	(Optional)
<i>tx-tstamp-req</i>	(Optional)
<i>tx-tstamp-reply</i>	(Optional)
<i>tx-time-exceeded</i>	(Optional)

<i>tx-router-solicit</i>	(Optional)
<i>tx-router-advert</i>	(Optional)
<i>out-drop-badlen</i>	(Optional)
<i>encap-fail</i>	(Optional)
<i>xmit-fail</i>	(Optional)
<i>icmp-originate</i>	(Optional)
<i>redirect-originate-req</i>	(Optional)
<i>orginate-deny</i>	(Optional)
<i>short-ip</i>	(Optional)
<i>old-icmp</i>	(Optional)
<i>error-drop</i>	(Optional)
TABLE_reception	(Optional)
<i>rx-redir</i>	(Optional)
<i>rx-unreach</i>	(Optional)
<i>rx-echo-req</i>	(Optional)
<i>rx-echo-reply</i>	(Optional)
<i>rx-mask-req</i>	(Optional)
<i>rx-mask-rep</i>	(Optional)
<i>rx-info-req</i>	(Optional)
<i>rx-info-reply</i>	(Optional)
<i>rx-param-prob</i>	(Optional)
<i>rx-source-quench</i>	(Optional)
<i>rx-tstamp-req</i>	(Optional)
<i>rx-tstamp-reply</i>	(Optional)
<i>rx-time-exceeded</i>	(Optional)
<i>rx-router-solicit</i>	(Optional)
<i>rx-router-advert</i>	(Optional)
<i>rx-format-errors</i>	(Optional)
<i>rx-csum-errors</i>	(Optional)

<i>lisp-processed</i>	(Optional)
<i>lisp-noclient</i>	(Optional)
<i>lisp-consumed</i>	(Optional)
<i>icmp-replies</i>	(Optional)
<i>icmp-reply-drop</i>	(Optional)
<i>icmp-inactive-addr</i>	(Optional)
TABLE_stat_last_never	(Optional)
<i>stat-last-never</i>	(Optional)
TABLE_rfc4293_ip_soft_proc_traffic	(Optional)
TABLE_rfc_reception	(Optional)
<i>inrcv</i>	(Optional)
<i>inoctet</i>	(Optional)
<i>inhdrrr</i>	(Optional)
<i>innoroutes</i>	(Optional)
<i>inaddrerr</i>	(Optional)
<i>innoproto</i>	(Optional)
<i>intruncated</i>	(Optional)
<i>inforw</i>	(Optional)
<i>reasmreqds</i>	(Optional)
<i>reasmoks</i>	(Optional)
<i>reasmfails</i>	(Optional)
<i>indiscards</i>	(Optional)
<i>indelivers</i>	(Optional)
<i>inmcastpkts</i>	(Optional)
<i>inmcastbytes</i>	(Optional)
<i>inbastpkts</i>	(Optional)
TABLE_rfc_transmission	(Optional)
<i>tr-pkt-sent</i>	(Optional)
<i>tr-bytes-sent</i>	(Optional)

<i>tr-out-req</i>	(Optional)
<i>tr-outno-routes</i>	(Optional)
<i>tr-out-frwdgrams</i>	(Optional)
<i>tr-outdiscards</i>	(Optional)
<i>tr-outfragreqds</i>	(Optional)
<i>tr-outfragoks</i>	(Optional)
<i>tr-outfragfails</i>	(Optional)
<i>tr-outfragcreates</i>	(Optional)
<i>tr-outtransmits</i>	(Optional)
<i>tr-bytes-sent-end</i>	(Optional)
<i>tr-outmcast-pkts</i>	(Optional)
<i>tr-outmcast-bytes</i>	(Optional)
<i>tr-outbcastpkts</i>	(Optional)
<i>tr-outbcastbytes</i>	(Optional)

Command Mode

- /exec

show ip txlist list

show ip txlist { list | member }

Syntax Description

show	Show running system information
ip	Display IP information
txlist	Display IP txlist information
list	Display IP txlist main linkage
member	Display IP txlist active member linkage

Command Mode

- /exec

show ip udp relay

```
show ip udp relay [ __readonly__ [ <udp_relay_service_enable> <udp_relay_hdr> TABLE_default_ports
<port_name> <udp_relay_port_enable> ] [ <udp_ports_hdr> TABLE_ports <udp_port_num> ] [ <udp_intf_hdr>
TABLE_intf <udp_intf_idx> <udp_sub_bcast> <udp_objgrp> ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
udp	Show items in UDP relay
relay	UDP relay
__readonly__	(Optional) Read only
<i>udp_relay_service_enable</i>	(Optional)
<i>udp_relay_hdr</i>	(Optional)
TABLE_default_ports	(Optional)
<i>port_name</i>	(Optional) UDP Port Name
<i>udp_relay_port_enable</i>	(Optional)
<i>udp_ports_hdr</i>	(Optional)
TABLE_ports	(Optional)
<i>udp_port_num</i>	(Optional)
<i>udp_intf_hdr</i>	(Optional)
TABLE_intf	(Optional)
<i>udp_intf_idx</i>	(Optional) UDP relay interfaces
<i>udp_sub_bcast</i>	(Optional)
<i>udp_objgrp</i>	(Optional) Object-group

Command Mode

- /exec

show ip udp relay interface

show ip udp relay interface [<intf_range>] [__readonly__ <udp_intf_hdr> [TABLE_intf <udp_intf_idx> <udp_sub_bcast> <udp_objgrp>]]

Syntax Description

show	Show running system information
ip	Show the IP features of the system
udp	Show items in UDP relay
relay	UDP relay
interface	Interface ID
<i>intf_range</i>	(Optional) interface
<i>__readonly__</i>	(Optional) Read only
<i>udp_intf_hdr</i>	(Optional)
TABLE_intf	(Optional)
<i>udp_intf_idx</i>	(Optional) UDP relay interfaces
<i>udp_sub_bcast</i>	(Optional)
<i>udp_objgrp</i>	(Optional) Object-group

Command Mode

- /exec

show ip udp relay object-group

```
show ip udp relay object-group [ <obj-grp-name> ] [ __readonly__ [ TABLE_objgrp_list [ <udp_objgrp> ]
[ TABLE_objgrp [ <host_addr> ] [ <net_addr> <net_mask> ] [ <prefix_addr> <prefix_len> ] ] <udp_intf_hdr>
[ TABLE_intf <udp_intf_idx> ] ] ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
udp	Show items in UDP relay
relay	UDP relay
object-group	Object-group
<i>obj-grp-name</i>	(Optional) object-group name
<i>__readonly__</i>	(Optional) Read only
TABLE_objgrp_list	(Optional)
<i>udp_objgrp</i>	(Optional) Object-group
TABLE_objgrp	(Optional)
<i>host_addr</i>	(Optional) Host Address
<i>net_addr</i>	(Optional) Network Address
<i>net_mask</i>	(Optional) Network Mask
<i>prefix_addr</i>	(Optional) Network Address
<i>prefix_len</i>	(Optional) IP Prefix Length
<i>udp_intf_hdr</i>	(Optional)
TABLE_intf	(Optional)
<i>udp_intf_idx</i>	(Optional) UDP relay interfaces

Command Mode

- /exec

show ip verify source

```
show ip verify source [ interface <intf6> ] [ __readonly__ [ <verify_intf_ipsg_val> | <verify_ipsg_enable_intf> ] ] [ <verify_hdr> ] [ TABLE_verify_entry <verify_intf> <verify_filter_mode> <verify_ip_addr> <verify_mac_addr> <verify_vlan> ] <verify_ipsg_exclude_vlans> ]
```

Syntax Description

show	Show running system information
ip	Show the IP features of the system
verify	Verify IPSG information
source	IPSG source
interface	(Optional) Interface
<i>intf6</i>	(Optional) interface
<i>__readonly__</i>	(Optional) Read only
<i>verify_intf_ipsg_val</i>	(Optional) IP source guard value (enabled or disable)
<i>verify_ipsg_enable_intf</i>	(Optional) IP source guard enabled interfaces names
TABLE_verify_entry	(Optional)
<i>verify_filter_mode</i>	(Optional)
<i>verify_intf</i>	(Optional)
<i>verify_hdr</i>	(Optional) IP source guard operational entries
<i>verify_ip_addr</i>	(Optional) verify ip address
<i>verify_mac_addr</i>	(Optional) verify mac address
<i>verify_vlan</i>	(Optional) vlan for interface
<i>verify_ipsg_exclude_vlans</i>	(Optional)

Command Mode

- /exec

show ipv6 amt tunnel

```
show ipv6 amt tunnel [ <address6> <port> ] [ detail ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ __readonly__
TABLE_vrf <vrf> <tc6> { TABLE_tunnel <gwa> <gwp> <ut> <ld> <lr> <rc> <exp> { TABLE_route
<source> <group> <rexp> } } ]
```

Syntax Description

show	Show running system information
amt	AMT show commands
ipv6	Display IPv6 information
tunnel	Display tunnel information
vrf	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>port</i>	(Optional) UDP port number of gateway
detail	(Optional) Display routes joined by tunnel endpoint
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf</i>	(Optional)
<i>tc6</i>	(Optional)
TABLE_tunnel	(Optional)
<i>gwa</i>	(Optional)
<i>gwp</i>	(Optional)
<i>ut</i>	(Optional)
<i>ld</i>	(Optional)
<i>lr</i>	(Optional)
<i>rc</i>	(Optional)
<i>exp</i>	(Optional)
TABLE_route	(Optional)
<i>source</i>	(Optional)
<i>group</i>	(Optional)

<i>rexp</i>	(Optional)
-------------	------------

Command Mode

- /exec

show ipv6 bgp

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] {  
rib-install | rib-uninstall | rib-pending } [ vrf { <vrf-name> | <vrf-known-name> |  
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv6	Display BGP information for IPv6 address family
rib-install	Routes installed in RIB
rib-uninstall	Routes not installed in RIB
rib-pending	Routes not acknowledged by RIB

Command Mode

- /exec

show ipv6 bgp

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ <ipv6-prefix> [ longer-prefixes ] ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ipv6	Display BGP information for IPv6 address family
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
longer-prefixes	(Optional) Display route and more specific routes

Command Mode

- /exec

show ipv6 bgp

```
show ipv6 { bgp | mbgp } { route-map { <rmap-name> | <rmap-name> } | prefix-list { <prfxlist-name> |
<test_pol_name> } | filter-list { <fltrlist-name> | <test_pol_name> } | community-list { <commlist-name> |
<test_pol_name> } | extcommunity-list { <extcommlist-name> | <test_pol_name> } [ exact-match ] }
```

Syntax Description

show	Show running system information
ipv6	Display BGP information for IPv6 address family
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
route-map	Display routes matching the route-map
<i>rmap-name</i>	Route-map name
<i>rmap-name</i>	Known route-map name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
filter-list	Display routes matching the filter-list
<i>fltrlist-name</i>	Name of filter-list
community-list	Display routes matching the community-list
<i>commlist-name</i>	Name of community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>extcommlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
exact-match	(Optional) Exact match of the communities

Command Mode

- /exec

show ipv6 bgp community

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
community { <regexp-str> | { { <comm-id> | <wellknown-id> } + [ exact-match ] } } [ vrf { <vrf-name> |  
<vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
ipv6	Display BGP information for IPv6 address family
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
community	Display routes matching the BGP communities
<i>regexp-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities

Command Mode

- /exec

show ipv6 bgp dampening

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
dampening { dampened-paths [ regexp <regexp-str> ] | history-paths [ regexp <regexp-str> ] | parameters |  
flap-statistics } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
parameters	Display dampening parameters
dampened-paths	Display all dampened paths
history-paths	Display all history paths
flap-statistics	Display flap statistics for routes
ipv6	Display BGP information for IPv6 address family
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths

Command Mode

- /exec

show ipv6 bgp extcommunity

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
extcommunity { <regexp-str> | { { 4byteas-generic { transitive <ext-comm-gen-trans> | non-transitive
<ext-comm-gen-nontrans> } } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ipv6	Display BGP information for IPv6 address family
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>regexp-str</i>	Regular expression to match the extcommunities
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities

Command Mode

- /exec

show ipv6 bgp flap-statistics

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
flap-statistics [ <ipv6-prefix> ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 }  
]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
ipv6	Display BGP information for IPv6 address family

Command Mode

- /exec

show ipv6 bgp neighbors

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
neighbors { [ { <neighbor-id> | <ipv6-neighbor-id> } [ routes [ advertised | received | dampened ] |
advertised-routes | paths | received-routes | flap-statistics ] ] | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id>
} [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
neighbors	Display all configured BGP neighbors
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	Display details for a prefix peering
ipv6	Display BGP information for IPv6 address family
routes	(Optional) Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer
advertised-routes	(Optional) Display all the routes advertised to this peer
received-routes	(Optional) Display all the routes received from this peer
flap-statistics	(Optional) Display flap statistics for routes received from this peer
paths	(Optional) Display AS paths learned from this peer

Command Mode

- /exec

show ipv6 bgp nexthop-database

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
nexthop-database [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop-database	Display nexthop database
ipv6	Display BGP information for IPv6 address family

Command Mode

- /exec

show ipv6 bgp nexthop

show ipv6 { bgp | mbgp } nexthop <ipv6nexthop>

Syntax Description

show	Show running system information
ipv6	Display BGP information for IPv6 address family
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
nexthop	Display routes matching the nexthop

Command Mode

- /exec

show ipv6 bgp received-paths

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
received-paths [ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ipv6	Display BGP information for IPv6 address family
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
private	(Optional) private

Command Mode

- /exec

show ipv6 bgp regexp

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] regexp  
<regexp-str> [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv6	Display BGP information for IPv6 address family
regexp	Display routes matching the AS path regular expression
<i>regexp-str</i>	Regular expression to match the AS paths

Command Mode

- /exec

show ipv6 bgp summary

```
show ipv6 { bgp | mbgp } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]  
summary [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
mbgp	Display MBGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
summary	Display summarized information of BGP state
ipv6	Display BGP information for IPv6 address family

Command Mode

- /exec

show ipv6 dhcp-ldra

```
show ipv6 dhcp-ldra [ __readonly__ <ldra_gbl_enable> [ <cli_fac_disable_hdr>
TABLE_intf_entry_cli_fac_disable <cli_fac_disable_intf> ] [ <cli_fac_trusted_hdr>
TABLE_intf_entry_cli_fac_trusted <cli_fac_trusted_intf> ] [ <cli_fac_untrusted_hdr>
TABLE_intf_entry_cli_fac_untrusted <cli_fac_untrusted_intf> ] [ <srv_fac_hdr> TABLE_intf_entry_srv_fac
<srv_fac_intf> ] ]
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
dhcp-ldra	Show DHCPv6 LDRA
<i>__readonly__</i>	(Optional) Read only
<i>ldra_gbl_enable</i>	(Optional) is DHCPv6 LDRA service enabled
<i>cli_fac_disable_hdr</i>	(Optional) DHCPv6 LDRA policy client-facing-disable
TABLE_intf_entry_cli_fac_disable	(Optional)
<i>cli_fac_disable_intf</i>	(Optional) DHCPv6 LDRA policy client-facing-disable interfaces
<i>cli_fac_trusted_hdr</i>	(Optional) DHCPv6 LDRA policy client-facing-trusted
TABLE_intf_entry_cli_fac_trusted	(Optional)
<i>cli_fac_trusted_intf</i>	(Optional) DHCPv6 LDRA policy client-facing-trusted interfaces
<i>cli_fac_untrusted_hdr</i>	(Optional) DHCPv6 LDRA policy client-facing-untrusted
TABLE_intf_entry_cli_fac_untrusted	(Optional)
<i>cli_fac_untrusted_intf</i>	(Optional) DHCPv6 LDRA policy client-facing-untrusted interfaces
<i>srv_fac_hdr</i>	(Optional) DHCPv6 LDRA policy server-facing
TABLE_intf_entry_srv_fac	(Optional)
<i>srv_fac_intf</i>	(Optional) DHCPv6 LDRA policy server-facing interfaces

Command Mode

- /exec

show ipv6 dhcp-ldra statistics

```
show ipv6 dhcp-ldra statistics [ __readonly__ { <cf_total_msg_received> <cf_total_msg_sent>
<cf_total_msg_drops> } [ <rx_msg_stats_hdr> TABLE_rx_entry <rx_msg_type_str> <rx_pkts> ] [
<tx_msg_stats_hdr> TABLE_tx_entry <tx_msg_type_str> <tx_pkts> ] [ <drop_msg_stats_hdr>
TABLE_drop_entry <msg_discard_reason_str> <drops> ] { <sf_total_msg_received> <sf_total_msg_sent>
<sf_total_msg_drops> } [ <sf_rx_msg_stats_hdr> TABLE_sf_rx_entry <sf_rx_msg_type_str> <sf_rx_pkts>
] [ <sf_tx_msg_stats_hdr> TABLE_sf_tx_entry <sf_tx_msg_type_str> <sf_tx_pkts> ] [
<sf_drop_msg_stats_hdr> TABLE_sf_drop_entry <sf_msg_discard_reason_str> <sf_drops> ] ]
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
dhcp-ldra	Show information about DHCPv6 LDRA
statistics	Statistics related to DHCPv6 LDRA
__readonly__	(Optional) Read only
<i>cf_total_msg_received</i>	(Optional) client facing statistics messages received
<i>cf_total_msg_sent</i>	(Optional) client facing statistics messages sent
<i>cf_total_msg_drops</i>	(Optional) client facing statistics message drops
<i>rx_msg_stats_hdr</i>	(Optional) received message statistics header
TABLE_rx_entry	(Optional)
<i>rx_msg_type_str</i>	(Optional) received dhcpv6 message type
<i>rx_pkts</i>	(Optional) received dhcpv6 packets
<i>tx_msg_stats_hdr</i>	(Optional) forwarded message statistics header
TABLE_tx_entry	(Optional)
<i>tx_msg_type_str</i>	(Optional) forwarded dhcpv6 message type
<i>tx_pkts</i>	(Optional) forwarded dhcpv6 packets
<i>drop_msg_stats_hdr</i>	(Optional) drops message statistics header
TABLE_drop_entry	(Optional)
<i>msg_discard_reason_str</i>	(Optional) message discarded reason
<i>drops</i>	(Optional) dhcpv6 packet drops
<i>sf_total_msg_received</i>	(Optional) server facing statistics messages received
<i>sf_total_msg_sent</i>	(Optional) server facing statistics messages sent

<i>sf_total_msg_drops</i>	(Optional) server facing statistics message drops
<i>sf_rx_msg_stats_hdr</i>	(Optional) received message statistics header
TABLE_sf_rx_entry	(Optional)
<i>sf_rx_msg_type_str</i>	(Optional) received dhcpv6 message type
<i>sf_rx_pkts</i>	(Optional) received dhcpv6 packets
<i>sf_tx_msg_stats_hdr</i>	(Optional) server forwarded message statistics header
TABLE_sf_tx_entry	(Optional)
<i>sf_tx_msg_type_str</i>	(Optional) server forwarded dhcpv6 message type
<i>sf_tx_pkts</i>	(Optional) server forwarded dhcpv6 packets
<i>sf_drop_msg_stats_hdr</i>	(Optional) server drops message statistics header
TABLE_sf_drop_entry	(Optional)
<i>sf_msg_discard_reason_str</i>	(Optional) server message discarded reason
<i>sf_drops</i>	(Optional) server dhcpv6 packet drops

Command Mode

- /exec

show ipv6 dhcp guard policy

```
show ipv6 dhcp guard policy [ <pname> ] [ __readonly__ { TABLE_dhcp_guard_policy <name> <role> [ <target> ] [ <max_pref> ] [ <min_pref> ] [ <match_src_list> ] [ <match_prefix_list> ] } ]
```

Syntax Description

<i>show</i>	Show running system information
<i>ipv6</i>	Show the IPv6 features of the system
<i>pname</i>	(Optional) Policy name for dhcp guard feature
<i>__readonly__</i>	(Optional)
<i>TABLE_dhcp_guard_policy</i>	(Optional) IPv6 DHCP guard policy
<i>name</i>	(Optional) Policy Name
<i>role</i>	(Optional) Role
<i>target</i>	(Optional) Target
<i>max_pref</i>	(Optional) Max preference
<i>min_pref</i>	(Optional) Min preference
<i>match_src_list</i>	(Optional) Source Address Match Access List
<i>match_prefix_list</i>	(Optional) Prefix List Match Prefix List

Command Mode

- /exec

show ipv6 dhcp relay

```
show ipv6 dhcp relay [ interface <intf-range> ] [ __readonly__ [ <relay_service_enable> [ <gbl_src_intf> ]
<relay_vpn_enable> <relay_cisco_option_enable> ] [ TABLE_intf <interface-name> [ <intf_src_intf> ]
<intf_header> [ TABLE_addr <relay_address> <dst_intf> <vrf_name> ] ] ]
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
dhcp	Show DHCPv6
relay	DHCPv6 relay address of the interface
interface	(Optional) DHCPv6 relay address of the interface
<i>intf-range</i>	(Optional) interface
<i>__readonly__</i>	(Optional) Read only
<i>relay_service_enable</i>	(Optional) is dhcpv6 relay service enabled
<i>gbl_src_intf</i>	(Optional) interface name
<i>relay_vpn_enable</i>	(Optional) is dhcpv6 relay insertion of vpn sub options enabled
<i>relay_cisco_option_enable</i>	(Optional) is dhcpv6 relay cisco option enabled
TABLE_intf	(Optional)
<i>interface-name</i>	(Optional) interface name
<i>intf_src_intf</i>	(Optional) interface name
<i>intf_header</i>	(Optional) interface header
TABLE_addr	(Optional)
<i>dst_intf</i>	(Optional) interface name
<i>vrf_name</i>	(Optional) VRF name

Command Mode

- /exec

show ipv6 dhcp relay statistics

```
show ipv6 dhcp relay statistics [ interface <intf> [ [ server-ip <ip-addr-val> [ use-vrf <vrf-name> ] [ interface
<dest-interface> ] ] [ server-ip <ip-addr-val> [ interface <dest-interface> ] [ use-vrf <vrf-name> ] ] ] [
__readonly__ [ <msg_stats_hdr> <msg_type_str> <rx_pkts> <tx_pkts> <drops> <msg_type_str_advertise>
<rx_pkts_advertise> <tx_pkts_advertise> <drops_advertise> <msg_type_str_request> <rx_pkts_request>
<tx_pkts_request> <drops_request> <msg_type_str_confirm> <rx_pkts_confirm> <tx_pkts_confirm>
<drops_confirm> <msg_type_str_renew> <rx_pkts_renew> <tx_pkts_renew> <drops_renew>
<msg_type_str_rebind> <rx_pkts_rebind> <tx_pkts_rebind> <drops_rebind> <msg_type_str_reply>
<rx_pkts_reply> <tx_pkts_reply> <drops_reply> <msg_type_str_release> <rx_pkts_release> <tx_pkts_release>
<drops_release> <msg_type_str_decline> <rx_pkts_decline> <tx_pkts_decline> <drops_decline>
<msg_type_str_reconfigure> <rx_pkts_reconfigure> <tx_pkts_reconfigure> <drops_reconfigure>
<msg_type_str_inforeq> <rx_pkts_inforeq> <tx_pkts_inforeq> <drops_inforeq> <msg_type_str_relay_fwd>
<rx_pkts_relay_fwd> <tx_pkts_relay_fwd> <drops_relay_fwd> <msg_type_str_relay_reply>
<rx_pkts_relay_reply> <tx_pkts_relay_reply> <drops_relay_reply> <msg_type_str_unknown>
<rx_pkts_unknown> <tx_pkts_unknown> <drops_unknown> <msg_type_str_total> ] [ <server_stats_hdr>
[ TABLE_server <server_helper_addr> <server_vrf> <server_intf> <server_requests> <server_responses>
] ] [ <drop_hdr> <drop_relay_disable> <drop_max_hops> <drop_validation_fails> <drop_unknown_op_intf>
<drop_bad_context> <drop_opt_insert_fail> <drop_server_direct_reply> <drop_no_ipv6_addr>
<drop_intf_error> <drop_vpn_disabled> <drop_ipv6_extn_hdrs_presence> <drop_mct_drop> ] ]
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
dhcp	Show information about DHCPv6
relay	DHCPv6 Relay
statistics	Statistics related to DHCPv6
interface	(Optional) input interface
<i>intf</i>	(Optional) interface
server-ip	(Optional) Server address
use-vrf	(Optional) server address VRF membership
<i>vrf-name</i>	(Optional) VRF name
interface	(Optional) Destination interface for the server address
<i>dest-interface</i>	(Optional) Destination interface
<i>__readonly__</i>	(Optional) Read only
<i>msg_stats_hdr</i>	(Optional) dhcpv6 message statistics header
<i>msg_type_str</i>	(Optional) dhcpv6 message type

<i>rx_pkts</i>	(Optional) dhcpv6 received packets
<i>tx_pkts</i>	(Optional) dhcpv6 forwarded packets
<i>drops</i>	(Optional) dhcpv6 packet drops
<i>msg_type_str_advertise</i>	(Optional)
<i>rx_pkts_advertise</i>	(Optional)
<i>tx_pkts_advertise</i>	(Optional)
<i>drops_advertise</i>	(Optional)
<i>msg_type_str_request</i>	(Optional)
<i>rx_pkts_request</i>	(Optional)
<i>tx_pkts_request</i>	(Optional)
<i>drops_request</i>	(Optional)
<i>msg_type_str_confirm</i>	(Optional)
<i>rx_pkts_confirm</i>	(Optional)
<i>tx_pkts_confirm</i>	(Optional)
<i>drops_confirm</i>	(Optional)
<i>msg_type_str_renew</i>	(Optional)
<i>rx_pkts_renew</i>	(Optional)
<i>tx_pkts_renew</i>	(Optional)
<i>drops_renew</i>	(Optional)
<i>msg_type_str_rebind</i>	(Optional)
<i>rx_pkts_rebind</i>	(Optional)
<i>tx_pkts_rebind</i>	(Optional)
<i>drops_rebind</i>	(Optional)
<i>msg_type_str_reply</i>	(Optional)
<i>rx_pkts_reply</i>	(Optional)
<i>tx_pkts_reply</i>	(Optional)
<i>drops_reply</i>	(Optional)
<i>msg_type_str_release</i>	(Optional)
<i>rx_pkts_release</i>	(Optional)

<i>tx_pkts_release</i>	(Optional)
<i>drops_release</i>	(Optional)
<i>msg_type_str_decline</i>	(Optional)
<i>rx_pkts_decline</i>	(Optional)
<i>tx_pkts_decline</i>	(Optional)
<i>drops_decline</i>	(Optional)
<i>msg_type_str_reconfigure</i>	(Optional)
<i>rx_pkts_reconfigure</i>	(Optional)
<i>tx_pkts_reconfigure</i>	(Optional)
<i>drops_reconfigure</i>	(Optional)
<i>msg_type_str_inforeq</i>	(Optional)
<i>rx_pkts_inforeq</i>	(Optional)
<i>tx_pkts_inforeq</i>	(Optional)
<i>drops_inforeq</i>	(Optional)
<i>msg_type_str_relay_fwd</i>	(Optional)
<i>rx_pkts_relay_fwd</i>	(Optional)
<i>tx_pkts_relay_fwd</i>	(Optional)
<i>drops_relay_fwd</i>	(Optional)
<i>msg_type_str_relay_reply</i>	(Optional)
<i>rx_pkts_relay_reply</i>	(Optional)
<i>tx_pkts_relay_reply</i>	(Optional)
<i>drops_relay_reply</i>	(Optional)
<i>msg_type_str_unknown</i>	(Optional)
<i>rx_pkts_unknown</i>	(Optional)
<i>tx_pkts_unknown</i>	(Optional)
<i>drops_unknown</i>	(Optional)
<i>msg_type_str_total</i>	(Optional) total of all dhcpv6 message types
<i>server_stats_hdr</i>	(Optional) per-server statistics header
TABLE_server	(Optional)

<i>server_vrf</i>	(Optional) dhcpv6 server vrf
<i>server_intf</i>	(Optional) interface name
<i>server_requests</i>	(Optional)
<i>server_responses</i>	(Optional)
<i>drop_hdr</i>	(Optional)
<i>drop_relay_disable</i>	(Optional)
<i>drop_max_hops</i>	(Optional)
<i>drop_validation_fails</i>	(Optional)
<i>drop_unknown_op_intf</i>	(Optional)
<i>drop_bad_context</i>	(Optional)
<i>drop_opt_insert_fail</i>	(Optional)
<i>drop_server_direct_reply</i>	(Optional)
<i>drop_no_ipv6_addr</i>	(Optional)
<i>drop_intf_error</i>	(Optional)
<i>drop_vpn_disabled</i>	(Optional)
<i>drop_ipv6_extn_hdrs_presence</i>	(Optional)
<i>drop_mct_drop</i>	(Optional) drops through mct

Command Mode

- /exec

show ipv6 local policy

```
show ipv6 local policy [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_pbr [ <interface> ] [ <rmap> ] [ <status> ] [ <vrf_name> ] } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
local	IPv6 local options
policy	Policy routing
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_pbr	(Optional)
<i>interface</i>	(Optional)
<i>rmap</i>	(Optional)
<i>status</i>	(Optional)
<i>vrf_name</i>	(Optional)

Command Mode

- /exec

show ipv6 nd raguard policy

```
show ipv6 nd raguard policy [ <name> ] [ __readonly__ { TABLE_raguard_policy <policy> [ <port_type>
] <device_role> [ <min_hop_limit> ] [ <max_hop_limit> ] [ <mgd_conf_flag> ] [ <other_conf_flag> ] [
<rtr_pref_max> ] [ <ra_prefix_list> ] [ <ipv6_acl> ] [ { TABLE_raguard_targets <target> <target_type>
<target_policy> <feature> <target_range> } } ]
```

Syntax Description

<i>name</i>	(Optional) Policy name for feature RA guard
<i>__readonly__</i>	(Optional)
<i>TABLE_raguard_policy</i>	(Optional) IPv6 RA guard policy
<i>policy</i>	(Optional) Policy Name
<i>port_type</i>	(Optional) Port type
<i>device_role</i>	(Optional) Device role
<i>min_hop_limit</i>	(Optional) Minimum hop limit
<i>max_hop_limit</i>	(Optional) Minimum hop limit
<i>mgd_conf_flag</i>	(Optional) Check managed config flag
<i>other_conf_flag</i>	(Optional) Check other config flag
<i>rtr_pref_max</i>	(Optional) Router-preference maximum
<i>ra_prefix_list</i>	(Optional) Match RA prefix list
<i>ipv6_acl</i>	(Optional) Match IPv6 access list
<i>TABLE_raguard_targets</i>	(Optional) RA Guard Targets table
<i>target</i>	(Optional) Target Name
<i>target_type</i>	(Optional) Target Type
<i>target_policy</i>	(Optional) Policy Name
<i>feature</i>	(Optional) Feature
<i>target_range</i>	(Optional) Target Range

Command Mode

- /exec

show ipv6 neighbor binding

```
show ipv6 neighbor binding [ { { vlan <vlanid> [ details ] } | { { address { <ipv6-addr> | all } } { interface  
<intfid> vlan <vlanid> [ details ] |
```

Syntax Description

<i>intfid</i>	(Optional) [details]
show	Show running system information
ipv6	Show the IPv6 features of the system
<i>vlanid</i>	(Optional) Vlan number

Command Mode

- /exec

show ipv6 neighbor binding mac

show ipv6 neighbor binding mac <macaddr> { interface <intfid> vlan <vlanid> [details] |

Syntax Description

<i>intfid</i>	[details]
show	Show running system information
ipv6	Show the IPv6 features of the system
<i>macaddr</i>	48-bit hardware address
<i>vlanid</i>	Vlan number

Command Mode

- /exec

show ipv6 pim bitfield

show ipv6 pim bitfield

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
bitfield	Display compressed bitfield details

Command Mode

- /exec

show ipv6 pim df

```
show ipv6 pim df [ <rp-or-group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
<out-context> { TABLE_rp <rp-addr> <df-ordinal> <df-bits> <df-bits-count> <metric-pref> <metric> {
TABLE_grange <grange-grp> <grange-masklen> } { TABLE_iod <if-name> <df-winner> <df-state>
<winner-metric-pref> <winner-metric> <uptime> <is-rpf> } } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
df	Display Bidir Designated Forwarders
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-context</i>	(Optional)
TABLE_rp	(Optional)
<i>df-ordinal</i>	(Optional)
<i>df-bits</i>	(Optional)
<i>df-bits-count</i>	(Optional)
<i>metric-pref</i>	(Optional)
<i>metric</i>	(Optional)
TABLE_grange	(Optional)
<i>grange-masklen</i>	(Optional)
TABLE_iod	(Optional)
<i>if-name</i>	(Optional)
<i>df-state</i>	(Optional)
<i>winner-metric-pref</i>	(Optional)
<i>winner-metric</i>	(Optional)

<i>uptime</i>	(Optional)
<i>is-rpf</i>	(Optional)

Command Mode

- /exec

show ipv6 pim embed-rp

show ipv6 pim embed-rp <group>

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
embed-rp	Display Embed-RP group address mapping

Command Mode

- /exec

show ipv6 pim event-history

```
show ipv6 pim [ internal ] event-history { errors | msgs | <pim6-event-hist-buf-name> | statistics }
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	PIM6 global configuration commands
internal	(Optional) Commands for internal use
event-history	Show various event logs of PIM6
errors	Show error logs of PIM6
msgs	Show various message logs of PIM6
<i>pim6-event-hist-buf-name</i>	Show logs of event-hist buffer
statistics	Show state and size of buffers

Command Mode

- /exec

show ipv6 pim fabric info

show ipv6 pim fabric info [__readonly__ <switch_role>]

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
fabric	Fabric functionality
info	show the fabric info
__readonly__	(Optional)
<i>switch_role</i>	(Optional)

Command Mode

- /exec

show ipv6 pim fabric legacy-vlans

show ipv6 pim fabric legacy-vlans [__readonly__ TABLE_legacy_vlan <vlan_id>]

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
fabric	Fabric functionality
legacy-vlans	Show legacy VLANs on this switch
__readonly__	(Optional)
TABLE_legacy_vlan	(Optional)
<i>vlan_id</i>	(Optional)

Command Mode

- /exec

show ipv6 pim group-range

```
show ipv6 pim group-range [ <group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__  
<out-context> { TABLE_group <grp-addr> <invalid-grp> <mode> <rp-addr> <sh-tree-only-range> } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
group-range	Display the various group ranges
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-context</i>	(Optional)
TABLE_group	(Optional)
<i>invalid-grp</i>	(Optional)
<i>mode</i>	(Optional)

Command Mode

- /exec

show ipv6 pim interface show ipv6 pim interface

```
show ipv6 pim interface <interface> | show ipv6 pim interface [ brief ] [ vrf { <vrf-name> | <vrf-known-name>
| all } ] [ __readonly__ <out-context> { TABLE_iod <if-name> <if-addr> <dr> <nbr-cnt> <is-border>
<is-iface-in-cib> <is-pim-enabled> <if-addr-summary> <if-status> <dr-priority> <no-dr-priority>
<hello-interval-sec> <hello-interval-msec> <hello-timer> <holdtime-sec> <holdtime-msec> <genid>
<isauth-config> <is-passive> <nbr-policy-name> <jp-in-policy-name> <jp-out-policy-name> <last-cleared>
<hello-sent> <hello-rcvd> <jp-sent> <jp-rcvd> <assert-sent> <assert-rcvd> <graft-sent> <graft-rcvd>
<graft-ack-sent> <graft-ack-rcvd> <df-offer-sent> <df-offer-rcvd> <df-winner-sent> <df-winner-rcvd>
<df-backoff-sent> <df-backoff-rcvd> <pass-sent> <pass-rcvd> <cksum-errors> <invalid-errors>
<invalid-df-errors> <auth-failed> <pak-len-errors> <ver-errors> <pkts-self> <pkts-non-nbr> <pkts-on-passive>
<jp-rcvd-on-rpf> <jp-rcvd-no-rp> <jp-rcvd-wrong-rp> <jp-rcvd-for-ssm> <jp-rcvd-for-bidir>
<jp-in-policy-filter> <jp-out-policy-filter> } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
interface	Display PIM6 interface related information
<i>interface</i>	Interface name of single interface to display
brief	(Optional) Display one line status per interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>__readonly__</i>	(Optional)
<i>out-context</i>	(Optional)
TABLE_iod	(Optional)
<i>if-name</i>	(Optional)
<i>nbr-cnt</i>	(Optional)
<i>is-iface-in-cib</i>	(Optional)
<i>is-pim-enabled</i>	(Optional)
<i>is-border</i>	(Optional)
<i>if-addr-summary</i>	(Optional)

<i>if-status</i>	(Optional)
<i>dr-priority</i>	(Optional)
<i>no-dr-priority</i>	(Optional)
<i>hello-interval-sec</i>	(Optional)
<i>hello-interval-msec</i>	(Optional)
<i>hello-timer</i>	(Optional)
<i>holdtime-sec</i>	(Optional)
<i>holdtime-msec</i>	(Optional)
<i>genid</i>	(Optional)
<i>isauth-config</i>	(Optional)
<i>is-passive</i>	(Optional)
<i>nbr-policy-name</i>	(Optional)
<i>jp-in-policy-name</i>	(Optional)
<i>jp-out-policy-name</i>	(Optional)
<i>last-cleared</i>	(Optional)
<i>hello-sent</i>	(Optional)
<i>hello-rcvd</i>	(Optional)
<i>jp-sent</i>	(Optional)
<i>jp-rcvd</i>	(Optional)
<i>assert-sent</i>	(Optional)
<i>assert-rcvd</i>	(Optional)
<i>graft-sent</i>	(Optional)
<i>graft-rcvd</i>	(Optional)
<i>graft-ack-sent</i>	(Optional)
<i>graft-ack-rcvd</i>	(Optional)
<i>df-offer-sent</i>	(Optional)
<i>df-offer-rcvd</i>	(Optional)
<i>df-winner-sent</i>	(Optional)
<i>df-winner-rcvd</i>	(Optional)

<i>df-backoff-sent</i>	(Optional)
<i>df-backoff-rcvd</i>	(Optional)
<i>pass-sent</i>	(Optional)
<i>pass-rcvd</i>	(Optional)
<i>cksum-errors</i>	(Optional)
<i>invalid-errors</i>	(Optional)
<i>invalid-df-errors</i>	(Optional)
<i>auth-failed</i>	(Optional)
<i>pak-len-errors</i>	(Optional)
<i>ver-errors</i>	(Optional)
<i>pkts-self</i>	(Optional)
<i>pkts-non-nbr</i>	(Optional)
<i>pkts-on-passive</i>	(Optional)
<i>jp-rcvd-on-rpf</i>	(Optional)
<i>jp-rcvd-no-rp</i>	(Optional)
<i>jp-rcvd-wrong-rp</i>	(Optional)
<i>jp-rcvd-for-ssm</i>	(Optional)
<i>jp-rcvd-for-bidir</i>	(Optional)
<i>jp-in-policy-filter</i>	(Optional)
<i>jp-out-policy-filter</i>	(Optional)

Command Mode

- /exec

show ipv6 pim neighbor

```
show ipv6 pim neighbor { [ <interface> ] | [ <ipv6addr> ] } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
[ __readonly__ [ TABLE_vrf <out-context> [ TABLE_neighbor <nbr-addr><if-name><uptime><expires>
[ <dr-priority> ] <bidir-capable> <bfd-state><name> [ TABLE_secondary <sec-addr> ] ] ] ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
neighbor	Display PIM6 neighbor related information
<i>interface</i>	(Optional) Display neighbors on single interface name
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>out-context</i>	(Optional)
TABLE_neighbor	(Optional)
<i>dr-priority</i>	(Optional)
<i>bidir-capable</i>	(Optional)
TABLE_secondary	(Optional)

Command Mode

- /exec

show ipv6 pim oif-list

```
show ipv6 pim oif-list <group> [ <source> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
TABLE_vrf <vrf-name> { TABLE_grp <mcast-addr> <incoming-intf> <rpf-nbr> <timeout-interval>
<oif-list-count> [ { TABLE_oiflist <oif-name> } ] <timeout-list-count> [ { TABLE_timeoutlist
<timeoutoif-name> } ] <immediate-list-count> [ { TABLE_immediatelist <immediateoif-name> } ]
<immediate-timeout-list-count> [ { TABLE_immediatetimetoutlist <immediatetimeoutoif-name> } ]
<sgr-prune-list-count> [ { TABLE_sgrprunelist <sgrprunelistoif-name> } ] } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
oif-list	Display interfaces for oif-list of PIM6 route
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_grp	(Optional)
<i>mcast-addr</i>	(Optional)
<i>incoming-intf</i>	(Optional)
<i>timeout-interval</i>	(Optional)
<i>oif-list-count</i>	(Optional)
TABLE_oiflist	(Optional)
<i>oif-name</i>	(Optional)
<i>timeout-list-count</i>	(Optional)
TABLE_timeoutlist	(Optional)
<i>timeoutoif-name</i>	(Optional)
<i>immediate-list-count</i>	(Optional)

TABLE_immediatelist	(Optional)
<i>immediateoif-name</i>	(Optional)
<i>immediate-timeout-list-count</i>	(Optional)
TABLE_immediatetimetoutlist	(Optional)
<i>immediatetimetoutoif-name</i>	(Optional)
<i>sgr-prune-list-count</i>	(Optional)
TABLE_sgrprunelist	(Optional)
<i>sgrprunelistoif-name</i>	(Optional)

Command Mode

- /exec

show ipv6 pim policy statistics jp

```
show ipv6 pim policy statistics { jp-policy | neighbor-policy } <interface> [ __readonly__ { TABLE_routemap
<name> <action> <seq_num> [ { TABLE_cmd <command> <match_count> <compare_count> } ] }
<total_accept_count> <total_reject_count> ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	PIM6 global configuration commands
policy	Policy related information
statistics	Policy statistics
jp-policy	Statistics for jp-policy
neighbor-policy	Statistics for neighbor-policy
<i>interface</i>	Interface to display policy statistics for
__readonly__	(Optional)
TABLE_routemap	(Optional)
<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seq_num</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>compare_count</i>	(Optional)
<i>match_count</i>	(Optional)
<i>total_accept_count</i>	(Optional)
<i>total_reject_count</i>	(Optional)

Command Mode

- /exec

show ipv6 pim route

```
show ipv6 pim route { [ bitfield ] | <source> <group> | <group> [ <source> ] [ bitfield ] } [ vrf { <vrf-name>
| <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf <context-name> <route-count> [ TABLE_one_route
<mcast-addrs> [ <rp-addr> <rp-local> ] <bidir> <sgexpire> <is-fabricowned> [ <sgexpire> ] [ <timeleft> ]
<rp-bit> [ <register> ] [ <assert-timeout> ] <intf-name> <rpf-nbr-1> <rpf-nbr-addr> <rpf-nbr-2> [ <metric-pref>
<route-metric> ] [ <oif-count> ] [ <oif-bf-str> ] [ <timeout-count> ] [ <timeout-bf-str> ] [ <immediate-count>
] [ <immediate-bf-str> ] [ <immediate-timeout-count> ] [ <immediate-timeout-bf-str> ] [ <sgr-prune-list-count>
] [ <sgr-prune-list-bf-str> ] [ <timeout-interval> <jp-holdtime-rndup> ] ] ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
route	Display PIM6 specific route information
bitfield	(Optional) Display details of each bitfield for PIM6 route
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>context-name</i>	(Optional)
<i>route-count</i>	(Optional)
TABLE_one_route	(Optional)
<i>mcast-addrs</i>	(Optional)
<i>rp-addr</i>	(Optional)
<i>rp-local</i>	(Optional)
<i>bidir</i>	(Optional)
<i>sgexpire</i>	(Optional)
<i>is-fabricowned</i>	(Optional)
<i>sgexpire</i>	(Optional)
<i>timeleft</i>	(Optional)

<i>rp-bit</i>	(Optional)
<i>register</i>	(Optional)
<i>assert-timeout</i>	(Optional)
<i>intf-name</i>	(Optional)
<i>rpf-nbr-1</i>	(Optional)
<i>rpf-nbr-addr</i>	(Optional)
<i>rpf-nbr-2</i>	(Optional)
<i>metric-pref</i>	(Optional)
<i>route-metric</i>	(Optional)
<i>oif-count</i>	(Optional)
<i>oif-bf-str</i>	(Optional)
<i>timeout-count</i>	(Optional)
<i>timeout-bf-str</i>	(Optional)
<i>immediate-count</i>	(Optional)
<i>immediate-bf-str</i>	(Optional)
<i>immediate-timeout-count</i>	(Optional)
<i>immediate-timeout-bf-str</i>	(Optional)
<i>sgr-prune-list-count</i>	(Optional)
<i>sgr-prune-list-bf-str</i>	(Optional)
<i>timeout-interval</i>	(Optional)
<i>jp-holdtime-rndup</i>	(Optional)

Command Mode

- /exec

show ipv6 pim rp-hash

```
show ipv6 pim rp-hash <group> [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <out-context>
<rp-found> <is-rp-bsr-learnt> <out-group> <hash-length> <out-bsr> { TABLE_rp <rp-addr> <hash>
<isbest_hash> } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
rp-hash	Display RP hash value for group
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-context</i>	(Optional)
<i>rp-found</i>	(Optional)
<i>is-rp-bsr-learnt</i>	(Optional)
<i>hash-length</i>	(Optional)
TABLE_rp	(Optional)
<i>hash</i>	(Optional)
<i>isbest_hash</i>	(Optional)

Command Mode

- /exec

show ipv6 pim rp

```
show ipv6 pim rp [ <group> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <out-context>
<is-bsr-enabled> <is-bsr-listen-only> <is-bsr-forward-only> <are-we-bsr> <bsr-address> <is-bsr-address>
<bsr-priority> <bsr-hash-masklen> <bs-timer> <bsr-uptime> <bsr-expires> <is-autorp-enabled>
<is-autorp-listen-only> <is-autorp-forward-only> <are-we-autorp> <autorp-address> <is-autorp-address>
<autorp-dis-timer> <autorp-up-time> <autorp-expire-time> <rp-cand-policy-name> <bsr-policy-name>
<rp-announce-policy-name> <rp-discovery-policy-name> { TABLE_anycast_rp <anycast-rp-addr> {
TABLE_arp_rp <arp-rp-addr> <is-rpaddr-local> } } { TABLE_rp <rp-addr> <is-rp-in-cib> <df-ordinal>
<rp-uptime> <rp-priority> <autorp-expires> <bsr-rp-expires> <autorp-info-src> <bsr-info-src> <is-rp-static>
<static-rp-group-map> { TABLE_grange <grange-grp> <grange-masklen> <is-bidir-grp> <is-autorp-rp-owner>
<is-bsr-rp-owner> <is-static-rp-owner> } } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
rp	Display PIM6 RP, Auto-RP, and BSR related information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>out-context</i>	(Optional)
<i>is-bsr-enabled</i>	(Optional)
<i>is-bsr-listen-only</i>	(Optional)
<i>is-bsr-forward-only</i>	(Optional)
<i>are-we-bsr</i>	(Optional)
<i>is-bsr-address</i>	(Optional)
<i>bsr-priority</i>	(Optional)
<i>bsr-hash-masklen</i>	(Optional)
<i>bs-timer</i>	(Optional)
<i>bsr-uptime</i>	(Optional)
<i>bsr-expires</i>	(Optional)

<i>is-atorp-enabled</i>	(Optional)
<i>is-atorp-listen-only</i>	(Optional)
<i>is-atorp-forward-only</i>	(Optional)
<i>are-we-atorp</i>	(Optional)
<i>is-atorp-address</i>	(Optional)
<i>atorp-dis-timer</i>	(Optional)
<i>atorp-up-time</i>	(Optional)
<i>atorp-expire-time</i>	(Optional)
<i>rp-cand-policy-name</i>	(Optional)
<i>bsr-policy-name</i>	(Optional)
<i>rp-announce-policy-name</i>	(Optional)
<i>rp-discovery-policy-name</i>	(Optional)
TABLE_anycast_rp	(Optional)
TABLE_arp_rp	(Optional)
<i>is-rpaddr-local</i>	(Optional)
TABLE_rp	(Optional)
<i>is-rp-in-cib</i>	(Optional)
<i>df-ordinal</i>	(Optional)
<i>rp-uptime</i>	(Optional)
<i>rp-priority</i>	(Optional)
<i>atorp-expires</i>	(Optional)
<i>bsr-rp-expires</i>	(Optional)
<i>is-rp-static</i>	(Optional)
<i>static-rp-group-map</i>	(Optional)
TABLE_grange	(Optional)
<i>grange-masklen</i>	(Optional)
<i>is-bidir-grp</i>	(Optional)
<i>is-atorp-rp-owner</i>	(Optional)
<i>is-bsr-rp-owner</i>	(Optional)

<i>is-static-rp-owner</i>	(Optional)
---------------------------	------------

Command Mode

- /exec

show ipv6 pim statistics

```
show ipv6 pim statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <uptime> <reg-sent>
<reg-rcvd> <null-reg-sent> <null-reg-rcvd> <reg-stop-sent> <reg-stop-rcvd> <reg-rcvd-not-rp>
<reg-rcvd-for-ssm> <reg-rcvd-for-bidir> <bootstrap-sent> <bootstrap-rcvd> <cand-rp-sent> <cand-rp-rcvd>
<bs-no-nbr> <bs-border-deny> <bs-len-errors> <bs-rpf-failed> <bs-no-listen> <candrp-border-deny>
<candrp-no-listen> <autorp-announce-sent> <autorp-announce-rcvd> <autorp-discovery-sent>
<autorp-discovery-rcvd> <autorp-rpf-failed> <autorp-border-deny> <autorp-invalid-type> <autorp-ttl-expired>
<autorp-no-listen> <ctrl-no-route> <data-no-route> <no-state> <create-state> ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
statistics	Packet counter statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
<i>uptime</i>	(Optional)
<i>reg-sent</i>	(Optional)
<i>reg-rcvd</i>	(Optional)
<i>null-reg-sent</i>	(Optional)
<i>null-reg-rcvd</i>	(Optional)
<i>reg-stop-sent</i>	(Optional)
<i>reg-stop-rcvd</i>	(Optional)
<i>reg-rcvd-not-rp</i>	(Optional)
<i>reg-rcvd-for-ssm</i>	(Optional)
<i>reg-rcvd-for-bidir</i>	(Optional)
<i>bootstrap-sent</i>	(Optional)
<i>bootstrap-rcvd</i>	(Optional)
<i>cand-rp-sent</i>	(Optional)

<i>cand-rp-rcvd</i>	(Optional)
<i>bs-no-nbr</i>	(Optional)
<i>bs-border-deny</i>	(Optional)
<i>bs-len-errors</i>	(Optional)
<i>bs-rpf-failed</i>	(Optional)
<i>bs-no-listen</i>	(Optional)
<i>candrp-border-deny</i>	(Optional)
<i>candrp-no-listen</i>	(Optional)
<i>autorp-announce-sent</i>	(Optional)
<i>autorp-announce-rcvd</i>	(Optional)
<i>autorp-discovery-sent</i>	(Optional)
<i>autorp-discovery-rcvd</i>	(Optional)
<i>autorp-rpf-failed</i>	(Optional)
<i>autorp-border-deny</i>	(Optional)
<i>autorp-invalid-type</i>	(Optional)
<i>autorp-ttl-expired</i>	(Optional)
<i>autorp-no-listen</i>	(Optional)
<i>ctrl-no-route</i>	(Optional)
<i>data-no-route</i>	(Optional)
<i>no-state</i>	(Optional)
<i>create-state</i>	(Optional)

Command Mode

- /exec

show ipv6 pim vrf

```
show ipv6 pim vrf [ { <vrf-name> | <vrf-known-name> | all } ] [ detail ] [ __readonly__ TABLE_context  
<out-context> <context-id> <table-id> <count> ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
pim	Display PIM6 status and configuration
vrf	Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display all VRFs PIM6 is configured for
detail	(Optional) Display detailed information
__readonly__	(Optional)
TABLE_context	(Optional)
<i>out-context</i>	(Optional)
<i>context-id</i>	(Optional)
<i>table-id</i>	(Optional)
<i>count</i>	(Optional)

Command Mode

- /exec

show ipv6 policy

```
show ipv6 policy [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_pbr [ <interface> ] [ <rmap> ] [ <status> ] [ <vrf_name> ] } ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
policy	Policy routing
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_pbr	(Optional)
<i>interface</i>	(Optional)
<i>rmap</i>	(Optional)
<i>status</i>	(Optional)
<i>vrf_name</i>	(Optional)

Command Mode

- /exec

show ipv6 prefix-list

```
show ipv6 prefix-list { { [ detail | summary ] [ <ipv6-pfl-name> | <ipv6-pfl-cfg-name> ] } | { { <ipv6-pfl-name> | <ipv6-pfl-cfg-name> } seq <seq-no> } | { { <ipv6-pfl-name> | <ipv6-pfl-cfg-name> } <prefix> [ first-match | longer ] } } [ __readonly__ TABLE_ipv6_pfl <name> <seq> <action> <rule> ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
detail	(Optional) Show detailed information
summary	(Optional) Show summarized information
prefix-list	List IPv6 prefix lists
<i>ipv6-pfl-name</i>	(Optional) Name of prefix-list
<i>ipv6-pfl-cfg-name</i>	(Optional) Known prefix-list name
seq	Sequence number
<i>seq-no</i>	Sequence number
first-match	(Optional) Find the first match
longer	(Optional) Find the more specific entries
__readonly__	(Optional)
TABLE_ipv6_pfl	(Optional)
<i>name</i>	(Optional)
<i>seq</i>	(Optional)
<i>action</i>	(Optional)
<i>rule</i>	(Optional)

Command Mode

- /exec

show ipv6 route

```
show ipv6 route [ unicast ] [ topology <topology-name> ] [ l3vm-info ] [ rpf ] [ <ipv6-addr> | { <ipv6-prefix>
[ { longer-prefixes | shorter-prefixes } ] } ] [ { <ipv6-protocol> [ all ] } | { next-hop <next-hop> } | { interface
<interface> } | { updated { [ since <stime> ] [ until <utime> ] } } ] + [ summary | { [ detail ] [ deleted ] } ] [
vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_addrf
<addrf> [ TABLE_prefix <ipprefix> <ucast-nhops> <mcast-nhops> <attached> TABLE_path [ <ubest> ] [
<mbest> ] [ <ipnexthop> ] [ <ifname> ] <uptime> <pref> <metric> <clientname> [ <type> ] [ <tag> ] [ <stale>
] [ <stalebl> ] [ <hidden> ] ] [ TABLE_summary <routes> <paths> [ <mcast_paths> ] [ TABLE_unicast
[ <clientnameuni> ] [ <best-paths> ] [ <backup-paths> ] ] [ TABLE_multicast [ <clientnamemulti> ] [
<best-paths> ] [ <backup-paths> ] ] [ TABLE_route_count [ <mask_len> ] [ <count> ] ] ] ]
```

Syntax Description

show	Show running system information
ipv6	Display IPv6 information
route	Display IPv6 routing table
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
unicast	(Optional) Display unicast information
topology	(Optional) Display per-topology information
<i>topology-name</i>	(Optional) topology name
l3vm-info	(Optional) Display corresponding L3VM information
rpf	(Optional) Display RPF information for multicast source
longer-prefixes	(Optional) Display matching routes with mask-lengths >= prefix
shorter-prefixes	(Optional) Display matching routes with mask-lengths <= prefix
<i>ipv6-protocol</i>	(Optional) Display routes for protocol (or route type)
all	(Optional) Display routes for protocol for backup next-hops too
next-hop	(Optional) Display routes with this next-hop only
interface	(Optional) Display routes with this output interface only
<i>interface</i>	(Optional) Interface Name
updated	(Optional) Display routes filtered by last updated time
since	(Optional) Display those routes updated since this time

<i>stime</i>	(Optional) Since this date/time [[CC]YY-][MM-DD-]HH:MM[:SS]
<i>until</i>	(Optional) Display those routes updated until this time
<i>utime</i>	(Optional) Until this date/time [[CC]YY-][MM-DD-]HH:MM[:SS]
<i>summary</i>	(Optional) Display route counts
<i>deleted</i>	(Optional) Display delete-pending routes also
<i>detail</i>	(Optional) Display routes in full detail
<i>__readonly__</i>	(Optional)
<i>TABLE_vrf</i>	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>TABLE_addrf</i>	(Optional)
<i>addrf</i>	(Optional)
<i>TABLE_prefix</i>	(Optional)
<i>ucast-nhops</i>	(Optional)
<i>mcast-nhops</i>	(Optional)
<i>attached</i>	(Optional)
<i>TABLE_path</i>	(Optional)
<i>ubest</i>	(Optional)
<i>mbest</i>	(Optional)
<i>ifname</i>	(Optional)
<i>pref</i>	(Optional)
<i>tag</i>	(Optional)
<i>metric</i>	(Optional)
<i>uptime</i>	(Optional)
<i>clientname</i>	(Optional)
<i>type</i>	(Optional)
<i>stale</i>	(Optional)
<i>stalelbl</i>	(Optional)
<i>hidden</i>	(Optional)
<i>TABLE_summary</i>	(Optional)

<i>routes</i>	(Optional)
<i>paths</i>	(Optional)
<i>multicast_paths</i>	(Optional)
TABLE_unicast	(Optional)
<i>clientnameuni</i>	(Optional)
<i>best-paths</i>	(Optional)
<i>backup-paths</i>	(Optional)
TABLE_multicast	(Optional)
<i>clientnamemulti</i>	(Optional)
<i>best-paths</i>	(Optional)
<i>backup-paths</i>	(Optional)
TABLE_route_count	(Optional)
<i>mask_len</i>	(Optional)
<i>count</i>	(Optional)

Command Mode

- /exec

show ipv6 snooping capture-policy

show ipv6 snooping capture-policy [vlan <vlanid>] [interface <intf>] [__readonly__ <cmdout>]

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
<i>vlanid</i>	(Optional) VLAN ID
<i>intf</i>	(Optional) interface
__readonly__	(Optional)
<i>cmdout</i>	(Optional)

Command Mode

- /exec

show ipv6 snooping counters vlan

```
show ipv6 snooping counters { { vlan <vlanid> } | { interface <intf> } } [ __readonly__ [ {
TABLE_target_counters <target> [ { TABLE_protocol_msgs <protocol_name> [ { TABLE_sub_protocol_msgs
[ <subfield_name> ] [ <msg_count> ] } ] } ] [ { TABLE_bridged_msgs <protocol_name> [ {
TABLE_sub_protocol_msgs [ <subfield_name> ] [ <msg_count> ] } ] } ] [ { TABLE_dropped_msgs
<feature_name> <protocol_name> [ { TABLE_sub_protocol_msgs [ <subfield_name> ] [ <msg_count> ] [
<drop_reason> ] } ] } ] } ] }
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
<i>vlanid</i>	VLAN ID
<i>intf</i>	interface
__readonly__	(Optional)
TABLE_target_counters	(Optional) Policy counters per target
<i>target</i>	(Optional) Target Name
TABLE_protocol_msgs	(Optional) Protocol messages table
<i>protocol_name</i>	(Optional) Protocol name
TABLE_sub_protocol_msgs	(Optional) Protocol sub-messages table
<i>subfield_name</i>	(Optional) Sub-field name
<i>msg_count</i>	(Optional) Message count
TABLE_bridged_msgs	(Optional) Bridged messages table
<i>protocol_name</i>	(Optional) Protocol name
TABLE_sub_protocol_msgs	(Optional) Protocol sub-messages table
<i>subfield_name</i>	(Optional) Sub-field name
<i>msg_count</i>	(Optional) Message count
TABLE_dropped_msgs	(Optional) Bridged messages table
<i>feature_name</i>	(Optional) Feature name
<i>protocol_name</i>	(Optional) Protocol name
TABLE_sub_protocol_msgs	(Optional) Protocol sub-messages table
<i>subfield_name</i>	(Optional) Sub-field name

<i>msg_count</i>	(Optional) Message count
<i>drop_reason</i>	(Optional) Drop reason

Command Mode

- /exec

show ipv6 snooping events

show ipv6 snooping events [__readonly__ <cmdout>]

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
__readonly__	(Optional)
<i>cmdout</i>	(Optional)

Command Mode

- /exec

show ipv6 snooping features

show ipv6 snooping features [__readonly__ { TABLE_features <name> <priority> <state> }]

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
__readonly__	(Optional)
TABLE_features	(Optional) IPv6 Snooping Features
<i>name</i>	(Optional) Name
<i>priority</i>	(Optional) Priority
<i>state</i>	(Optional) State

Command Mode

- /exec

show ipv6 snooping messages

show ipv6 snooping messages [detailed <count>] [__readonly__ <cmdout>]

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
<i>count</i>	(Optional) Number of messages to display
<i>__readonly__</i>	(Optional)
<i>cmdout</i>	(Optional)

Command Mode

- /exec

show ipv6 snooping policies

```
show ipv6 snooping policies { [ vlan <vlanid> ] | [ interface <intf> ] } [ __readonly__ { TABLE_policies  
<target> <target_type> <policy> <feature> <target_range> } ]
```

Syntax Description

<code>show</code>	Show running system information
<code>ipv6</code>	Show the IPv6 features of the system
<code>vlanid</code>	(Optional) VLAN ID
<code>intf</code>	(Optional) interface
<code>__readonly__</code>	(Optional)
<code>TABLE_policies</code>	(Optional) IPv6 Snooping Policies
<code>target</code>	(Optional) Target Name
<code>target_type</code>	(Optional) Target Type
<code>policy</code>	(Optional) Policy Name
<code>feature</code>	(Optional) Feature
<code>target_range</code>	(Optional) Target Range

Command Mode

- /exec

show ipv6 snooping policy

```
show ipv6 snooping policy [ <policy_name> ] [ __readonly__ { [ TABLE_glean_policy <policy> [ <port_type>
] <sec_lvl> <device_role> [ <data_glean> ] [ <dest_glean> ] [ <glean_type> ] [ <reachable_lifetime> ] [
<stale_lifetime> ] { [ TABLE_non_glean_protocols | TABLE_glean_protocols # 394
../feature/sisf/core/nxos/src/sisf_glean_dme.cmd <protocol> [ <prefix_list> ] } ] [ <limit_address_cnt> ] [
<limit_address_cnt_v4_per_mac> ] [ <limit_address_cnt_v4_per_target> ] [ <tracking> ] { [ TABLE_targets
<target> <target_type> <target_policy> <feature> <target_range> ] } ] }
```

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
<i>policy_name</i>	(Optional) Policy name for feature snooping
<i>__readonly__</i>	(Optional)
TABLE_glean_policy	(Optional) IPv6 DHCP guard policy
<i>policy</i>	(Optional) Policy Name
<i>port_type</i>	(Optional) Port type
<i>sec_lvl</i>	(Optional) Security level
<i>device_role</i>	(Optional) Device role
<i>data_glean</i>	(Optional) Data glean
<i>dest_glean</i>	(Optional) Destination glean
<i>glean_type</i>	(Optional) Glean type
<i>reachable_lifetime</i>	(Optional) Reachable lifetime
<i>stale_lifetime</i>	(Optional) Stale lifetime
TABLE_non_glean_protocols	(Optional) Non Glean protocols
<i>protocol</i>	(Optional) Protocol
TABLE_glean_protocols	(Optional) Glean protocols
<i>prefix_list</i>	(Optional) Prefix list
<i>limit_address_cnt</i>	(Optional) Limit address count
<i>limit_address_cnt_v4_per_mac</i>	(Optional) Limit address count v4 per mac
<i>limit_address_cnt_v4_per_target</i>	(Optional) Limit address count v4 per target
<i>tracking</i>	(Optional) Tracking

TABLE_targets	(Optional) Targets table
<i>target</i>	(Optional) Target Name
<i>target_type</i>	(Optional) Target Type
<i>target_policy</i>	(Optional) Policy Name
<i>feature</i>	(Optional) Feature
<i>target_range</i>	(Optional) Target Range

Command Mode

- /exec

show ipv6 snooping pss database

show ipv6 snooping pss database [__readonly__ <cmdout>]

Syntax Description

show	Show running system information
ipv6	Show the IPv6 features of the system
__readonly__	(Optional)
<i>cmdout</i>	(Optional)

Command Mode

- /exec

show isis

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ process | protocol ] [ vrf { <vrf-name>
| <vrf-known-name> | all } ] [ __readonly__ TABLE_process_tag <process-tag-out> <instance_num> <uuid>
<process-id> <vrf-name-out> <system-id-out> <is-type-out> <sap-out> <qh-out> <mtu-out> [ <gr-status-out>
] [ <gr-state-active-out> ] [ <gr-state-inactive-out> ] [ <last-gr-status-fail-out> ] [ <last-gr-status-success-out>
] [ <last-gr-status-none-out> ] [ <gr-status-disable-out> ] [ TABLE_afi_safi <af-ix> <af-bfd-config>
<af-pib-tag> ] <metric-style> <accept-metric> [ <net-set-none> ] [ TABLE_area_addr <area-addr-nsap> ] [
<proc-state-not-config> ] [ <proc-state-admin-down> ] [ <proc-state-l3vm-down> ] [
<proc-state-unknown-down> ] [ <proc-state-not-specified> ] [ <proc-state-no-net> ] [ <proc-state-no-vrf-id>
] [ <proc-state-out-memory> ] [ <proc-state-restart> ] [ <proc-state-running> ] <vrf-id-out> [ TABLE_te
<te-lvl-out> <te-lvl-active> ] [ <te-ted-out> ] [ <mpls-te-out> ] [ TABLE_mpls_te [ <mpls-te-lvl-out> ] [
<mpls-te-rtrid-intf-out> ] [ <mpls-te-fa-lvl-out> ] [ TABLE_te_fa <te-fa-sysid-out> <te-fa-intf-out> ] [
<te-stat-sys-id-out> ] [ <te-stat-rtr-id-out> ] [ TABLE_te_stat_lvl <te-stat-lvl-out> <te-stat-up-out>
<te-stat-down-out> ] [ TABLE_segment_routing <af-out> <ptag-out> <cfg-out> <enable-out> [ <exp-null-cfg>
] ] [ TABLE_iib_list_yeild <intf-name-out> ] [ TABLE_auth <auth-lvl-out> [ <auth-type-no-type> ] [
<auth-type-clear-text> ] [ <auth-type-md5> ] [ <auth-type-key-chain> ] [ <auth-type-none> ] [ <auth-check>
] [ <auth-no-check> ] ] [ TABLE_spf <spf-lvl-out> [ <spf-timer> ] ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
process	(Optional) Display IS-IS process information
protocol	(Optional) Display IS-IS process information
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>instance_num</i>	(Optional)
<i>uuid</i>	(Optional)
<i>process-id</i>	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>system-id-out</i>	(Optional)

<i>is-type-out</i>	(Optional)
<i>sap-out</i>	(Optional)
<i>qh-out</i>	(Optional)
<i>mtu-out</i>	(Optional)
<i>gr-status-out</i>	(Optional)
<i>gr-state-active-out</i>	(Optional)
<i>gr-state-inactive-out</i>	(Optional)
<i>last-gr-status-fail-out</i>	(Optional)
<i>last-gr-status-success-out</i>	(Optional)
<i>last-gr-status-none-out</i>	(Optional)
<i>gr-status-disable-out</i>	(Optional)
TABLE_afi_safi	(Optional)
<i>af-ix</i>	(Optional)
<i>af-bfd-config</i>	(Optional)
<i>af-pib-tag</i>	(Optional)
<i>metric-style</i>	(Optional)
<i>accept-metric</i>	(Optional)
<i>net-set-none</i>	(Optional)
TABLE_area_addr	(Optional)
<i>area-addr-nsap</i>	(Optional)
<i>proc-state-not-config</i>	(Optional)
<i>proc-state-admin-down</i>	(Optional)
<i>proc-state-l3vm-down</i>	(Optional)
<i>proc-state-unknown-down</i>	(Optional)
<i>proc-state-not-specified</i>	(Optional)
<i>proc-state-no-net</i>	(Optional)
<i>proc-state-no-vrf-id</i>	(Optional)
<i>proc-state-out-memory</i>	(Optional)
<i>proc-state-restart</i>	(Optional)

<i>proc-state-running</i>	(Optional)
<i>vrf-id-out</i>	(Optional)
TABLE_te	(Optional)
<i>te-lvl-out</i>	(Optional)
<i>te-lvl-active</i>	(Optional)
<i>te-ted-out</i>	(Optional)
<i>mpls-te-out</i>	(Optional)
TABLE_mpls_te	(Optional)
<i>mpls-te-lvl-out</i>	(Optional)
<i>mpls-te-rtrid-intf-out</i>	(Optional)
<i>mpls-te-fa-lvl-out</i>	(Optional)
TABLE_te_fa	(Optional)
<i>te-fa-sysid-out</i>	(Optional)
<i>te-fa-intf-out</i>	(Optional)
<i>te-stat-sys-id-out</i>	(Optional)
<i>te-stat-rtr-id-out</i>	(Optional)
TABLE_te_stat_lvl	(Optional)
<i>te-stat-lvl-out</i>	(Optional)
<i>te-stat-up-out</i>	(Optional)
<i>te-stat-down-out</i>	(Optional)
TABLE_segment_routing	(Optional)
<i>af-out</i>	(Optional)
<i>ptag-out</i>	(Optional)
<i>cfg-out</i>	(Optional)
<i>enable-out</i>	(Optional)
<i>exp-null-cfg</i>	(Optional)
TABLE_iib_list_yeild	(Optional)
<i>intf-name-out</i>	(Optional)
TABLE_auth	(Optional)

<i>auth-lvl-out</i>	(Optional)
<i>auth-type-no-type</i>	(Optional)
<i>auth-type-cleartext</i>	(Optional)
<i>auth-type-md5</i>	(Optional)
<i>auth-type-key-chain</i>	(Optional)
<i>auth-type-none</i>	(Optional)
<i>auth-check</i>	(Optional)
<i>auth-no-check</i>	(Optional)
TABLE_spf	(Optional)
<i>spf-lvl-out</i>	(Optional)
<i>spf-timer</i>	(Optional)

Command Mode

- /exec

show isis adjacency

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] adjacency [ <interface> [ p2p-level-1-2 ] ] [ { system-id <sid> } | [ detail ] | [ summary ] } ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> { TABLE_vrf <vrf-name-out> <adj-summary-out> <adj-interface-out> [ <adj-interface-name-out> ] [ { TABLE_process_adj <adj-sys-name-out> <adj-sys-id-out> [ <adj-usage-out> ] [ <adj-level-out> ] <adj-state-out> <adj-hold-time-out> <adj-intf-name-out> <adj-detail-set-out> [ { <adj-transitions-out> <adj-flap-out> [ <adj-flap-time-out> ] <adj-ckt-type-out> <adj-ipv4-addr-out> <adj-ipv6-addr-out> <adj-bcast-out> [ { <adj-ckt-id-out> <adj-lan-prio-out> } ] <adj-bfd-ipv4-establish-out> <adj-bfd-ipv6-establish-out> <adj-resurrect-out> [ { <adj-resurrect-count-out> <adj-resurrect-hwm-out> } ] <adj-restart-capable-out> <adj-restart-ack-out> [ { <adj-restart-mode-out> <adj-restart-adj-seen-ra-out> <adj-restart-adj-seen-csnp-out> <adj-restart-adj-seen-l1-csnp-out> <adj-restart-adj-seen-l2-csnp-out> <adj-restart-suppress-adj-out> } ] [ { TABLE_adj_sid <adj-sid-value> <adj-sid-f-flag> <adj-sid-b-flag> <adj-sid-v-flag> <adj-sid-l-flag> <adj-sid-s-flag> <adj-sid-p-flag> <adj-sid-weight> } ] } ] } ] [ { TABLE_p2p_adj_sum <adj-summ-p2p-level-out> <adj-summ-p2p-state-out> <adj-summ-p2p-count-out> } ] [ { TABLE_lan_adj_sum <adj-summ-lan-level-out> <adj-summ-lan-state-out> <adj-summ-lan-count-out> } ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
adjacency	Display IS-IS adjacency information
<i>interface</i>	(Optional) IS-IS interface
system-id	(Optional) Hostname or System ID
<i>sid</i>	(Optional) Hostname or System ID (in the form of XXXX.XXXX.XXXX)
detail	(Optional) Display IS-IS adjacency detail information
p2p-level-1-2	(Optional) Display IS-IS point-to-point information at level-1-2
summary	(Optional) Display IS-IS adjacency summary information
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)

TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>adj-summary-out</i>	(Optional)
<i>adj-interface-out</i>	(Optional)
<i>adj-interface-name-out</i>	(Optional)
TABLE_process_adj	(Optional)
<i>adj-sys-name-out</i>	(Optional)
<i>adj-sys-id-out</i>	(Optional)
<i>adj-usage-out</i>	(Optional)
<i>adj-level-out</i>	(Optional)
<i>adj-state-out</i>	(Optional)
<i>adj-hold-time-out</i>	(Optional)
<i>adj-intf-name-out</i>	(Optional)
<i>adj-detail-set-out</i>	(Optional)
<i>adj-transitions-out</i>	(Optional)
<i>adj-flap-out</i>	(Optional)
<i>adj-flap-time-out</i>	(Optional)
<i>adj-ckt-type-out</i>	(Optional)
<i>adj-ipv4-addr-out</i>	(Optional)
<i>adj-ipv6-addr-out</i>	(Optional)
<i>adj-bcast-out</i>	(Optional)
<i>adj-ckt-id-out</i>	(Optional)
<i>adj-lan-prio-out</i>	(Optional)
<i>adj-bfd-ipv4-establish-out</i>	(Optional)
<i>adj-bfd-ipv6-establish-out</i>	(Optional)
<i>adj-resurrect-out</i>	(Optional)
<i>adj-resurrect-count-out</i>	(Optional)
<i>adj-resurrect-hwm-out</i>	(Optional)
<i>adj-restart-capable-out</i>	(Optional)

<i>adj-restart-ack-out</i>	(Optional)
<i>adj-restart-mode-out</i>	(Optional)
<i>adj-restart-adj-seen-ra-out</i>	(Optional)
<i>adj-restart-adj-seen-csnp-out</i>	(Optional)
<i>adj-restart-adj-seen-l1-csnp-out</i>	(Optional)
<i>adj-restart-adj-seen-l2-csnp-out</i>	(Optional)
<i>adj-restart-suppress-adj-out</i>	(Optional)
TABLE_adj_sid	(Optional)
<i>adj-sid-value</i>	(Optional)
<i>adj-sid-f-flag</i>	(Optional)
<i>adj-sid-b-flag</i>	(Optional)
<i>adj-sid-v-flag</i>	(Optional)
<i>adj-sid-l-flag</i>	(Optional)
<i>adj-sid-s-flag</i>	(Optional)
<i>adj-sid-p-flag</i>	(Optional)
<i>adj-sid-weight</i>	(Optional)
TABLE_p2p_adj_sum	(Optional)
<i>adj-summ-p2p-level-out</i>	(Optional)
<i>adj-summ-p2p-state-out</i>	(Optional)
<i>adj-summ-p2p-count-out</i>	(Optional)
TABLE_lan_adj_sum	(Optional)
<i>adj-summ-lan-level-out</i>	(Optional)
<i>adj-summ-lan-state-out</i>	(Optional)
<i>adj-summ-lan-count-out</i>	(Optional)

Command Mode

- /exec

show isis csnp

```
show isis [ <isis-tag> ] csnp [ detail ] [ __readonly__ TABLE_process_tag <process-tag-out> [ {
TABLE_CSNPLEVEL <csnp-level> <csnp-cache-valid> <csnp-cache-hit> <cscnp-cache-miss> <csnp-hit-rate>
[ { TABLE_CSNPLSPS <csnp-start-lsp-id> <csnp-end-lsp-id> <csnp-entry-valid> <csnp-pdu-length> [ {
TABLE_CSNPONELSP <csnp-lsp-id> <csnp-lsp-seq-num> <csnp-lsp-chk-sum> <csnp-lsp-life-time> } ] }
} ] ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
csnp	Display IS-IS CSNP cache contents
detail	(Optional) Display detailed IS-IS information
<i>__readonly__</i>	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_CSNPLEVEL	(Optional)
<i>csnp-level</i>	(Optional)
<i>csnp-cache-valid</i>	(Optional)
<i>csnp-cache-hit</i>	(Optional)
<i>cscnp-cache-miss</i>	(Optional)
<i>csnp-hit-rate</i>	(Optional)
TABLE_CSNPLSPS	(Optional)
<i>csnp-start-lsp-id</i>	(Optional)
<i>csnp-end-lsp-id</i>	(Optional)
<i>csnp-entry-valid</i>	(Optional)
<i>csnp-pdu-length</i>	(Optional)
TABLE_CSNPONELSP	(Optional)
<i>csnp-lsp-id</i>	(Optional)
<i>csnp-lsp-seq-num</i>	(Optional)
<i>csnp-lsp-chk-sum</i>	(Optional)

<i>csnp-lsp-life-time</i>	(Optional)
---------------------------	------------

Command Mode

- /exec

show isis database

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] database [ <level> ] [ detail | advertise
| summary ] [ <lid> ] { [ zero-sequence ] | [ ip prefix <ip-prefix> ] | [ ipv6 prefix <ipv6-prefix> ] | [ router-id
<rid> ] | [ adjacency <adj-id> ] } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ {
TABLE_process_tag <process-tag-out> { TABLE_vrf <vrf-name-out> [ <dbase-hname-absent-out> ] [ {
TABLE_process_lvl <dbase-level-out> [ { TABLE_process_lsp <dbase-lsp-name-out> <dbase-lsp-status-out>
<dbase-lsp-absent-out> [ { <dbase-lsp-seqnum-out> <dbase-lsp-cksum-out> [ <dbase-lsp-lifetime-str-out> ]
[ <dbase-lsp-lifetime-out> ] <dbase-att-out> <dbase-partition-out> <dbase-overload-out> <dbase-istype-out>
} ] [ { <dbase-lsp-instance-out> [ { TABLE_process_tlv <dbase-lsp-tlv-name-out> [ <dbase-lsp-area-addr-out>
] [ <dbase-lsp-is-nbr-name-out> ] [ <dbase-lsp-is-nbr-metric-out> ] [ <dbase-lsp-is-nbr-ext-metric-out> ] [
<dbase-lsp-es-nbr-name-out> ] [ <dbase-lsp-es-nbr-metric-out> ] [ <dbase-lsp-es-nbr-ext-metric-out> ] [
<dbase-lsp-auth-type-out> ] [ <dbase-lsp-auth-len-out> ] [ <dbase-lsp-ext-is-name-out> ] [
<dbase-lsp-ext-is-metric-out> ] [ <dbase-lsp-ip-ri-addr-out> ] [ <dbase-lsp-ip-ri-mask-out> ] [
<dbase-lsp-ip-ri-metric-out> ] [ <dbase-lsp-ip-ri-ext-metric-out> ] [ <dbase-lsp-ip-ri-up-down-out> ] [
<dbase-lsp-cap-rtrid> ] [ <dbase-lsp-cap-flags> ] [ { TABLE_process_nlpid <dbase-lsp-prot-support-out> }
] [ <dbase-lsp-ip-addr-out> ] [ <dbase-lsp-ipv6-addr-out> ] [ { TABLE_process_extip
<dbase-lsp-extip-addr-out> <dbase-lsp-extip-prefix-len-out> <dbase-lsp-extip-metric-out>
<dbase-lsp-extip-up-down-out> [ <dbase-lsp-extip-pfxsid> ] [ <dbase-lsp-extip-pfxsid-flags> ] [
<dbase-lsp-extip-unknown-out> } ] [ <dbase-lsp-hname-out> ] [ <dbase-lsp-hname-len-out> ] [ {
TABLE_process_extipv6 <dbase-lsp-extipv6-addr-out> <dbase-lsp-extipv6-prefix-len-out>
<dbase-lsp-extipv6-metric-out> <dbase-lsp-extipv6-up-down-out> <dbase-lsp-extipv6-ext-origin-out> [
<dbase-lsp-extipv6-pfxsid> ] [ <dbase-lsp-extipv6-pfxsid-flags> ] [ <dbase-lsp-extipv6-unknown-out> } ] ]
[ { TABLE_process_subtlv <dbase-lsp-subtlv-name-out> [ <dbase-lsp-extis-admin-group-out> ] [
<dbase-lsp-subtlv-ip-addr-out> ] [ <dbase-lsp-extis-bw-out> ] [ <dbase-lsp-extis-pri1-out> ] [
<dbase-lsp-extis-pri1-val-out> ] [ <dbase-lsp-extis-pri2-out> ] [ <dbase-lsp-extis-pri2-val-out> ] [
<dbase-lsp-extis-te-metric-out> ] [ <dbase-lsp-extis-p2p-adjsid-out> ] [ <dbase-lsp-extis-p2p-adjsid-flags> ]
[ <dbase-lsp-extis-p2p-adjsid-weight> ] [ <dbase-lsp-extis-lan-adjsid-out> ] [ <dbase-lsp-extis-lan-adjsid-sysid>
] [ <dbase-lsp-extis-lan-adjsid-flags> ] [ <dbase-lsp-extis-lan-adjsid-weight> ] [
<dbase-lsp-cap-subtlv-sr-start-sid> ] [ <dbase-lsp-cap-subtlv-sr-end-sid> ] [ <dbase-lsp-cap-subtlv-sr-range>
] [ <dbase-lsp-cap-subtlv-sr-flags> ] [ <dbase-lsp-subtlv-len-out> ] [ <dbase-lsp-subtlv-unknown-out> } ] ]
[ <dbase-lsp-tlv-len-out> ] [ <dbase-lsp-tlv-unknown-out> ] } ] <dbase-lsp-digest-out> } } ] [ {
<dbase-lsp-total-out> [ { <dbase-lsp-empty-out> <dbase-lsp-zeroseq-out> } } ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Display IS-IS database information

<i>level</i>	(Optional) IS-IS level
<i>lid</i>	(Optional) LSP ID in the form of XXXX.XXXX.XXXX.XX-XX
detail	(Optional) Display detailed IS-IS information
advertise	(Optional) Display advertise tlv lsp-memory information
summary	(Optional) Display summary IS-IS information
zero-sequence	(Optional) LSP with zero sequence number
ip	(Optional) IP attribute filter
ipv6	(Optional) IPv6 attribute filter
prefix	(Optional) Prefix filter
<i>ip-prefix</i>	(Optional) Single exact match IP prefix filter
adjacency	(Optional) Adjacency filter
<i>adj-id</i>	(Optional) Single exact match adjacency filter
router-id	(Optional) Router-id filter
<i>rid</i>	(Optional) single exact match router-id filter
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>dbase-hname-absent-out</i>	(Optional)
TABLE_process_lvl	(Optional)
<i>dbase-level-out</i>	(Optional)
TABLE_process_lsp	(Optional)
<i>dbase-lsp-name-out</i>	(Optional)
<i>dbase-lsp-status-out</i>	(Optional)
<i>dbase-lsp-absent-out</i>	(Optional)
<i>dbase-lsp-seqnum-out</i>	(Optional)
<i>dbase-lsp-cksum-out</i>	(Optional)
<i>dbase-lsp-lifetime-str-out</i>	(Optional)

<i>dbase-lsp-lifetime-out</i>	(Optional)
<i>dbase-att-out</i>	(Optional)
<i>dbase-partition-out</i>	(Optional)
<i>dbase-overload-out</i>	(Optional)
<i>dbase-istype-out</i>	(Optional)
<i>dbase-lsp-instance-out</i>	(Optional)
TABLE_process_tlv	(Optional)
<i>dbase-lsp-tlv-name-out</i>	(Optional)
<i>dbase-lsp-area-addr-out</i>	(Optional)
<i>dbase-lsp-is-nbr-name-out</i>	(Optional)
<i>dbase-lsp-is-nbr-metric-out</i>	(Optional)
<i>dbase-lsp-is-nbr-ext-metric-out</i>	(Optional)
<i>dbase-lsp-es-nbr-name-out</i>	(Optional)
<i>dbase-lsp-es-nbr-metric-out</i>	(Optional)
<i>dbase-lsp-es-nbr-ext-metric-out</i>	(Optional)
<i>dbase-lsp-auth-type-out</i>	(Optional)
<i>dbase-lsp-auth-len-out</i>	(Optional)
<i>dbase-lsp-ext-is-name-out</i>	(Optional)
<i>dbase-lsp-ext-is-metric-out</i>	(Optional)
<i>dbase-lsp-ip-ri-addr-out</i>	(Optional)
<i>dbase-lsp-ip-ri-mask-out</i>	(Optional)
<i>dbase-lsp-ip-ri-metric-out</i>	(Optional)
<i>dbase-lsp-ip-ri-ext-metric-out</i>	(Optional)
<i>dbase-lsp-ip-ri-up-down-out</i>	(Optional)
TABLE_process_nlpid	(Optional)
<i>dbase-lsp-prot-support-out</i>	(Optional)
<i>dbase-lsp-ip-addr-out</i>	(Optional)
<i>dbase-lsp-ipv6-addr-out</i>	(Optional)
TABLE_process_extip	(Optional)

<i>dbase-lsp-extip-addr-out</i>	(Optional)
<i>dbase-lsp-extip-prefix-len-out</i>	(Optional)
<i>dbase-lsp-extip-metric-out</i>	(Optional)
<i>dbase-lsp-extip-up-down-out</i>	(Optional)
<i>dbase-lsp-extip-pfxsid</i>	(Optional)
<i>dbase-lsp-extip-pfxsid-flags</i>	(Optional)
<i>dbase-lsp-extip-unknown-out</i>	(Optional)
<i>dbase-lsp-hname-out</i>	(Optional)
<i>dbase-lsp-hname-len-out</i>	(Optional)
TABLE_process_extipv6	(Optional)
<i>dbase-lsp-extipv6-addr-out</i>	(Optional)
<i>dbase-lsp-extipv6-prefix-len-out</i>	(Optional)
<i>dbase-lsp-extipv6-metric-out</i>	(Optional)
<i>dbase-lsp-extipv6-up-down-out</i>	(Optional)
<i>dbase-lsp-extipv6-ext-origin-out</i>	(Optional)
<i>dbase-lsp-extipv6-pfxsid</i>	(Optional)
<i>dbase-lsp-extipv6-pfxsid-flags</i>	(Optional)
<i>dbase-lsp-extipv6-unknown-out</i>	(Optional)
<i>dbase-lsp-tlv-len-out</i>	(Optional)
<i>dbase-lsp-tlv-unknown-out</i>	(Optional)
TABLE_process_subtlv	(Optional)
<i>dbase-lsp-subtlv-name-out</i>	(Optional)
<i>dbase-lsp-extis-admin-group-out</i>	(Optional)
<i>dbase-lsp-subtlv-ip-addr-out</i>	(Optional)
<i>dbase-lsp-extis-bw-out</i>	(Optional)
<i>dbase-lsp-extis-pri1-out</i>	(Optional)
<i>dbase-lsp-extis-pri1-val-out</i>	(Optional)
<i>dbase-lsp-extis-pri2-out</i>	(Optional)
<i>dbase-lsp-extis-pri2-val-out</i>	(Optional)

<i>dbase-lsp-extis-te-metric-out</i>	(Optional)
<i>dbase-lsp-extis-p2p-adjsid-out</i>	(Optional)
<i>dbase-lsp-extis-p2p-adjsid-flags</i>	(Optional)
<i>dbase-lsp-extis-p2p-adjsid-weight</i>	(Optional)
<i>dbase-lsp-extis-lan-adjsid-out</i>	(Optional)
<i>dbase-lsp-extis-lan-adjsid-sysid</i>	(Optional)
<i>dbase-lsp-extis-lan-adjsid-flags</i>	(Optional)
<i>dbase-lsp-extis-lan-adjsid-weight</i>	(Optional)
<i>dbase-lsp-subtlv-len-out</i>	(Optional)
<i>dbase-lsp-subtlv-unknown-out</i>	(Optional)
<i>dbase-lsp-digest-out</i>	(Optional)
<i>dbase-lsp-total-out</i>	(Optional)
<i>dbase-lsp-empty-out</i>	(Optional)
<i>dbase-lsp-zeroseq-out</i>	(Optional)
<i>dbase-lsp-cap-rtrid</i>	(Optional)
<i>dbase-lsp-cap-flags</i>	(Optional)
<i>dbase-lsp-cap-subtlv-sr-start-sid</i>	(Optional)
<i>dbase-lsp-cap-subtlv-sr-end-sid</i>	(Optional)
<i>dbase-lsp-cap-subtlv-sr-range</i>	(Optional)
<i>dbase-lsp-cap-subtlv-sr-flags</i>	(Optional)

Command Mode

- /exec

show isis distribute-ls

```
show isis [ <isis-tag> ] distribute-ls { [ system-id <sid> ] [ lsp-id <lid> ] } [ brief ] [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> <vrf-name-out>
<vrf-id-out> <lslib-connection-out> <client-type-out> <protocol-instance-out> <nxos-instance-out>
<ha-recovery-out> [ <queue-all-out> ] <update-timer-sec-out> <update-timer-msec-out>
<update-timer-running-out> [ <update-timer-due-in> ] [ { TABLE_process_lvl <level-out>
<level-distributing-out> [ { TABLE_ls_node <node-id-out> <node-name-out> [ { TABLE_ls_lsp <lsp-id-out>
<lsp-name-out> <lsp-purged-out> <node-grpid-out> <prefix-grpid-out> <link-grpid-out>
<node-attr-bitfield-out> <node-flags-out> [ <attached-bit-out> ] [ <overloaded-bit-out> ] [ <area-id-out> ] [
<area-length-out> ] [ <name-out> ] [ <ipv4-id-out> ] [ { TABLE_srgb <number-out> <start-out> <size-out>
} ] [ <sr-algo-count-out> ] [ { TABLE_sr_algo <algo-out> } ] [ { TABLE_ls_link <nbr-node-out>
<local-ip-out> <remote-ip-out> <link-attr-bitfield-out> [ <metric-out> ] <local-ip-attr-out> <remote-ip-attr-out>
[ <max-link-bw-out> ] [ <max-resv-bw-out> ] [ { TABLE_unresv_bw <number-out> <bw-out> } ] [
<metric-te-out> ] [ { TABLE_adj-sid <asid-out> <flag-out> <weight-out> } ] ] [ { TABLE_ls_prefix
<prefix-out> <prefix-len-out> <prefix-attr-bitfield-out> [ <metric-out> ] [ { TABLE-sid <sid-out> <algo-out>
<flags-out> } ] } ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
distribute-ls	Link-state distribution database
system-id	(Optional) Hostname or System ID
<i>sid</i>	(Optional) Hostname or System ID (in the form of XXXX.XXXX.XXXX)
lsp-id	(Optional) LSP ID in the form of XXXX.XXXX.XXXX.XX-XX
<i>lid</i>	(Optional) LSP ID in the form of XXXX.XXXX.XXXX.XX-XX
brief	(Optional) Short output
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>vrf-name-out</i>	(Optional)

<i>vrf-id-out</i>	(Optional)
<i>lslib-connection-out</i>	(Optional)
<i>client-type-out</i>	(Optional)
<i>protocol-instance-out</i>	(Optional)
<i>nxos-instance-out</i>	(Optional)
<i>ha-recovery-out</i>	(Optional)
<i>queue-all-out</i>	(Optional)
<i>update-timer-sec-out</i>	(Optional)
<i>update-timer-msec-out</i>	(Optional)
<i>update-timer-running-out</i>	(Optional)
<i>update-timer-due-in</i>	(Optional)
TABLE_process_lvl	(Optional)
<i>level-out</i>	(Optional)
<i>level-distributing-out</i>	(Optional)
TABLE_ls_node	(Optional)
<i>node-id-out</i>	(Optional)
<i>node-name-out</i>	(Optional)
TABLE_ls_lsp	(Optional)
<i>lsp-id-out</i>	(Optional)
<i>lsp-name-out</i>	(Optional)
<i>lsp-purged-out</i>	(Optional)
<i>node-grpid-out</i>	(Optional)
<i>prefix-grpid-out</i>	(Optional)
<i>link-grpid-out</i>	(Optional)
<i>node-attr-bitfield-out</i>	(Optional)
<i>node-flags-out</i>	(Optional)
<i>attached-bit-out</i>	(Optional)
<i>overloaded-bit-out</i>	(Optional)
<i>area-id-out</i>	(Optional)

<i>area-length-out</i>	(Optional)
<i>name-out</i>	(Optional)
<i>ipv4-id-out</i>	(Optional)
TABLE_srgb	(Optional)
<i>number-out</i>	(Optional)
<i>start-out</i>	(Optional)
<i>size-out</i>	(Optional)
<i>sr-algo-count-out</i>	(Optional)
TABLE_sr_algo	(Optional)
<i>algo-out</i>	(Optional)
TABLE_ls_link	(Optional)
<i>nbr-node-out</i>	(Optional)
<i>local-ip-out</i>	(Optional)
<i>remote-ip-out</i>	(Optional)
<i>link-attr-bitfield-out</i>	(Optional)
<i>metric-out</i>	(Optional)
<i>local-ip-attr-out</i>	(Optional)
<i>remote-ip-attr-out</i>	(Optional)
<i>max-link-bw-out</i>	(Optional)
<i>max-resv-bw-out</i>	(Optional)
TABLE_unresv_bw	(Optional)
<i>number-out</i>	(Optional)
<i>bw-out</i>	(Optional)
<i>metric-te-out</i>	(Optional)
TABLE-adj-sid	(Optional)
<i>asid-out</i>	(Optional)
<i>flag-out</i>	(Optional)
<i>weight-out</i>	(Optional)
TABLE_ls_prefix	(Optional)

<i>prefix-out</i>	(Optional)
<i>prefix-len-out</i>	(Optional)
<i>prefix-attr-bitfield-out</i>	(Optional)
<i>metric-out</i>	(Optional)
TABLE-sid	(Optional)
<i>sid-out</i>	(Optional)
<i>algo-out</i>	(Optional)
<i>flags-out</i>	(Optional)

Command Mode

- /exec

show isis event-history

```
show isis [ <isis-tag> ] [ internal ] event-history { errors | msgs | <isis-event-hist-buf-name> | statistics }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
internal	(Optional) Commands for internal use
event-history	Display IS-IS event history
errors	Error history
msgs	Message history
<i>isis-event-hist-buf-name</i>	Event history buffer
statistics	Show the state and size of the buffer

Command Mode

- /exec

show isis hostname

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] { hostname | hostname-table } [ detail
] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_vrf <vrf-name-out> <tag-out>
<hname-enabled-out> <hname-detail-out> [ TABLE_hostname <hname-id-out> <hname-level-out>
<hname-id-mine-out> <hname-name-out> ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
hostname	Display IS-IS hostname table information
hostname-table	Display IS-IS hostname table information
detail	(Optional) Display detailed IS-IS information
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>tag-out</i>	(Optional)
<i>hname-enabled-out</i>	(Optional)
<i>hname-detail-out</i>	(Optional)
TABLE_hostname	(Optional)
<i>hname-id-out</i>	(Optional)
<i>hname-level-out</i>	(Optional)
<i>hname-id-mine-out</i>	(Optional)
<i>hname-name-out</i>	(Optional)

Command Mode

- /exec

show isis interface

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] interface [ brief | <interface> ] [ level-1
| level-2 ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag
<process-tag-out> { TABLE_vrf <vrf-name-out> [ { TABLE_interface [ { <intfb-name-out> <intfb-type-out>
<intfb-ix-out> <intfb-state-out> <intfb-ready-state-out> <intfb-cid-out> <intfb-ckt-type-out> <intfb-mtu-out>
[ { <intf-p2p-metric-lvl-1-out> <intf-p2p-metric-lvl-2-out> <intf-p2p-prio-lvl-1-out> <intf-p2p-prio-lvl-2-out>
<intf-p2p-adj-count-lvl-1-out> <intf-p2p-adj-up-count-lvl-1-out> <intf-p2p-adj-count-lvl-2-out>
<intf-p2p-adj-up-count-lvl-2-out> } ] [ { <intf-loopback-metric-lvl-1-out> <intf-loopback-metric-lvl-2-out>
<intf-loopback-prio-lvl-1-out> <intf-loopback-prio-lvl-2-out> <intf-loopback-adj-count-lvl-1-out>
<intf-loopback-adj-up-count-lvl-1-out> <intf-loopback-adj-count-lvl-2-out>
<intf-loopback-adj-up-count-lvl-2-out> } ] [ { <intf-bcast-metric-lvl-1-out> <intf-bcast-metric-lvl-2-out>
<intf-bcast-prio-lvl-1-out> <intf-bcast-prio-lvl-2-out> <intf-bcast-adj-count-lvl-1-out>
<intf-bcast-adj-up-count-lvl-1-out> <intf-bcast-adj-count-lvl-2-out> <intf-bcast-adj-up-count-lvl-2-out> } ]
} ] [ { <intf-name-out> <intf-status-out> } ] [ { <intf-state-out> <intf-internal-state-out> [
<intf-cib-disabled-out> ] [ <intf-cid-invalid-out> } ] ] [ { TABLE_auth [ { <intf-auth-info-out> [
<intf-auth-kchain-out> ] <intf-auth-chk-info-out> } ] } ] [ { <intf-ix-out> <intf-cid-out> <intf-ckt-type-out>
} ] ] [ { TABLE_bfd [ <intf-bfd-ipv4-state-out> ] [ <intf-bfd-ipv6-state-out> } ] ] [ <intf-passive-mask-out> ]
[ <intf-passive-mask-lvl-out> ] [ <intf-mgrp-set-out> ] [ <intf-mgrp-state-out> ] [ <intf-mgrp-id-out> ] [
<intf-p2p-type-out> ] [ { <intf-p2p-ext-local-cid-out> <intf-p2p-cid-out> <intf-retx-intv-out>
<intf-retx-throttle-out> } ] [ <intf-loopback-type-out> ] [ { <intf-lsp-intv-out> <intf-mtu-out> [
<intf-hpad-state-out> } ] ] [ { <intf-p2p-pad-ts-out> ] <intf-p2p-adj-count-out> <intf-p2p-adj-up-count-out>
<intf-p2p-prio-out> <intf-p2p-hello-intv-out> <intf-p2p-hello-multi-out> <intf-p2p-hello-next-out> [ {
TABLE_p2p <intf-p2p-lvl-out> <intf-p2p-adj-lvl-out> <intf-p2p-adj-up-lvl-out> <intf-p2p-metric-lvl-out>
<intf-p2p-csnp-lvl-out> <intf-p2p-csnp-nxt-lvl-out> <intf-p2p-lspid-last-lvl-out> } ] ] [ { <intf-bcast-type-out>
[ { TABLE_bcast_pad [ { <intf-bcast-lvl-out> <intf-bcast-pad-ts-out> } ] } ] [ { TABLE_bcast_dis [ {
<intf-bcast-lvl-dis-out> <intf-bcast-dis-ts-out> } ] } ] [ { TABLE_bcast_pkt <intf-bcast-lvl-info-out>
<intf-bcast-lvl-metric-0-out> <intf-bcast-lvl-metric-2-out> <intf-bcast-lvl-csnp-intv-out>
<intf-bcast-lvl-csnp-next-out> <intf-bcast-lvl-iih-intv-out> <intf-bcast-lvl-iih-multi-out>
<intf-bcast-lvl-iih-next-out> } ] ] [ { TABLE_bcast_adj <intf-bcast-lvl-value-out> <intf-bcast-lvl-adj-out>
<intf-bcast-lvl-adj-up-out> <intf-bcast-lvl-prio-out> <intf-bcast-lvl-ctid-out> <intf-bcast-lvl-ctid-ts-out>
} ] } ] [ { TABLE_loopback <intf-loopback-lvl-out> <intf-loopback-lvl-metric-out> } ] [ <intf-unknown-out>
} ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
brief	(Optional) Brief display of IS-IS interfaces

interface	Display IS-IS interface information
level-1	(Optional) Display Level-1 interfaces
level-2	(Optional) Display level-2 interfaces
<i>interface</i>	(Optional) IS-IS interface
<i>__readonly__</i>	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_interface	(Optional)
<i>intf-status-out</i>	(Optional)
<i>intf-name-out</i>	(Optional)
<i>intf-ix-out</i>	(Optional)
<i>intf-state-out</i>	(Optional)
<i>intf-cid-out</i>	(Optional)
<i>intf-ckt-type-out</i>	(Optional)
<i>intfb-name-out</i>	(Optional)
<i>intfb-type-out</i>	(Optional)
<i>intfb-ix-out</i>	(Optional)
<i>intfb-state-out</i>	(Optional)
<i>intfb-ready-state-out</i>	(Optional)
<i>intfb-cid-out</i>	(Optional)
<i>intfb-ckt-type-out</i>	(Optional)
<i>intf-p2p-metric-lvl-1-out</i>	(Optional)
<i>intf-p2p-metric-lvl-2-out</i>	(Optional)
<i>intf-p2p-prio-lvl-1-out</i>	(Optional)
<i>intf-p2p-prio-lvl-2-out</i>	(Optional)
<i>intf-p2p-adj-count-lvl-1-out</i>	(Optional)
<i>intf-p2p-adj-count-lvl-2-out</i>	(Optional)

<i>intf-p2p-adj-up-count-lvl-1-out</i>	(Optional)
<i>intf-p2p-adj-up-count-lvl-2-out</i>	(Optional)
<i>intf-loopback-metric-lvl-1-out</i>	(Optional)
<i>intf-loopback-metric-lvl-2-out</i>	(Optional)
<i>intf-loopback-prio-lvl-1-out</i>	(Optional)
<i>intf-loopback-prio-lvl-2-out</i>	(Optional)
<i>intf-loopback-adj-count-lvl-1-out</i>	(Optional)
<i>intf-loopback-adj-count-lvl-2-out</i>	(Optional)
<i>intf-loopback-adj-up-count-lvl-1-out</i>	(Optional)
<i>intf-loopback-adj-up-count-lvl-2-out</i>	(Optional)
<i>intf-bcast-metric-lvl-1-out</i>	(Optional)
<i>intf-bcast-metric-lvl-2-out</i>	(Optional)
<i>intf-bcast-prio-lvl-1-out</i>	(Optional)
<i>intf-bcast-prio-lvl-2-out</i>	(Optional)
<i>intf-bcast-adj-count-lvl-1-out</i>	(Optional)
<i>intf-bcast-adj-count-lvl-2-out</i>	(Optional)
<i>intf-bcast-adj-up-count-lvl-1-out</i>	(Optional)
<i>intf-bcast-adj-up-count-lvl-2-out</i>	(Optional)
<i>intf-internal-state-out</i>	(Optional)
<i>intf-cib-disabled-out</i>	(Optional)
<i>intf-cid-invalid-out</i>	(Optional)
TABLE_auth	(Optional)
<i>intf-auth-info-out</i>	(Optional)
<i>intf-auth-kchain-out</i>	(Optional)
<i>intf-auth-chk-info-out</i>	(Optional)
TABLE_bfd	(Optional)
<i>intf-bfd-ipv4-state-out</i>	(Optional)
<i>intf-bfd-ipv6-state-out</i>	(Optional)
<i>intf-passive-mask-out</i>	(Optional)

<i>intf-passive-mask-lvl-out</i>	(Optional)
<i>intf-mgrp-set-out</i>	(Optional)
<i>intf-mgrp-state-out</i>	(Optional)
<i>intf-mgrp-id-out</i>	(Optional)
<i>intf-p2p-type-out</i>	(Optional)
<i>intf-p2p-ext-local-cid-out</i>	(Optional)
<i>intf-p2p-cid-out</i>	(Optional)
<i>intf-retx-intv-out</i>	(Optional)
<i>intf-retx-throttle-out</i>	(Optional)
<i>intf-loopback-type-out</i>	(Optional)
<i>intf-lsp-intv-out</i>	(Optional)
<i>intf-mtu-out</i>	(Optional)
<i>intfb-mtu-out</i>	(Optional)
<i>intf-hpad-state-out</i>	(Optional)
<i>intf-p2p-pad-ts-out</i>	(Optional)
<i>intf-p2p-adj-count-out</i>	(Optional)
<i>intf-p2p-adj-up-count-out</i>	(Optional)
<i>intf-p2p-prio-out</i>	(Optional)
<i>intf-p2p-hello-intv-out</i>	(Optional)
<i>intf-p2p-hello-multi-out</i>	(Optional)
<i>intf-p2p-hello-next-out</i>	(Optional)
TABLE_p2p	(Optional)
<i>intf-p2p-lvl-out</i>	(Optional)
<i>intf-p2p-adj-lvl-out</i>	(Optional)
<i>intf-p2p-adj-up-lvl-out</i>	(Optional)
<i>intf-p2p-metric-lvl-out</i>	(Optional)
<i>intf-p2p-csnp-lvl-out</i>	(Optional)
<i>intf-p2p-csnp-nxt-lvl-out</i>	(Optional)
<i>intf-p2p-lspid-last-lvl-out</i>	(Optional)

<i>intf-bcast-type-out</i>	(Optional)
TABLE_bcast_pad	(Optional)
<i>intf-bcast-lvl-out</i>	(Optional)
<i>intf-bcast-pad-ts-out</i>	(Optional)
TABLE_bcast_dis	(Optional)
<i>intf-bcast-lvl-dis-out</i>	(Optional)
<i>intf-bcast-dis-ts-out</i>	(Optional)
TABLE_bcast_pkt	(Optional)
<i>intf-bcast-lvl-info-out</i>	(Optional)
<i>intf-bcast-lvl-metric-0-out</i>	(Optional)
<i>intf-bcast-lvl-metric-2-out</i>	(Optional)
<i>intf-bcast-lvl-csnp-intv-out</i>	(Optional)
<i>intf-bcast-lvl-csnp-next-out</i>	(Optional)
<i>intf-bcast-lvl-iih-intv-out</i>	(Optional)
<i>intf-bcast-lvl-iih-multi-out</i>	(Optional)
<i>intf-bcast-lvl-iih-next-out</i>	(Optional)
TABLE_bcast_adj	(Optional)
<i>intf-bcast-lvl-value-out</i>	(Optional)
<i>intf-bcast-lvl-adj-out</i>	(Optional)
<i>intf-bcast-lvl-adj-up-out</i>	(Optional)
<i>intf-bcast-lvl-prio-out</i>	(Optional)
<i>intf-bcast-lvl-ctid-out</i>	(Optional)
<i>intf-bcast-lvl-ctid-ts-out</i>	(Optional)
TABLE_loopback	(Optional)
<i>intf-loopback-lvl-out</i>	(Optional)
<i>intf-loopback-lvl-metric-out</i>	(Optional)
<i>intf-unknown-out</i>	(Optional)

Command Mode

- /exec

show isis ipv6 redistribute route

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ipv6 redistribute route [ summary |
<ipv6-addr> | <ipv6-prefix> [ longer-prefixes [ summary ] ] ] [ direct-mask ] [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ TABLE_process_tag <process-tag-out> <redist-route-ipv6-vrf>
[ <redist-route-ipv6-af-ix> ] [ { TABLE_one_route <redist-route-ipv6-prefix> [ <redist-route-ipv6-mask-len>
] [ <redist-route-ipv6-pib-name> ] [ <redist-route-ipv6-direct-mask> ] [ <redist-route-ipv6-route-type> ] [ {
TABLE_redist <redist-route-ipv6-status> <redist-route-ipv6-level> [ <redist-route-ipv6-metric> ] [
<redist-route-ipv6-sum-addr-prefix> ] [ <redist-route-ipv6-sum-addr-mask-len> } } ] [
<redist-route-ipv6-summary-addr-prefix> ] [ <redist-route-ipv6-summary-addr-mask-len> ] [
<redist-route-ipv6-summary-route-total> ] [ { TABLE_protocol <redist-route-ipv6-summary-pib-name> [
<redist-route-ipv6-summary-prot-route-total> ] } ] [ <redist-route-ipv6-summary-pending-total> ] [ {
TABLE_mask_len <redist-route-ipv6-summary-mask-len-ix> [ <redist-route-ipv6-summary-mask-len> ] }
] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
redistribute	Display IS-IS redistribute information
route	Display ISIS redistribute route
ipv6	Display IS-IS IPv6 information
longer-prefixes	(Optional) Display exact match and more specific routes
summary	(Optional) Display route counts
direct-mask	(Optional) Display routes with direct-mask set
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>redist-route-ipv6-vrf</i>	(Optional)
<i>redist-route-ipv6-af-ix</i>	(Optional)
TABLE_one_route	(Optional)

<i>redist-route-ipv6-prefix</i>	(Optional)
<i>redist-route-ipv6-mask-len</i>	(Optional)
<i>redist-route-ipv6-pib-name</i>	(Optional)
<i>redist-route-ipv6-direct-mask</i>	(Optional)
<i>redist-route-ipv6-route-type</i>	(Optional)
TABLE_redist	(Optional)
<i>redist-route-ipv6-status</i>	(Optional)
<i>redist-route-ipv6-level</i>	(Optional)
<i>redist-route-ipv6-metric</i>	(Optional)
<i>redist-route-ipv6-sum-addr-prefix</i>	(Optional)
<i>redist-route-ipv6-sum-addr-mask-len</i>	(Optional)
<i>redist-route-ipv6-summary-addr-prefix</i>	(Optional)
<i>redist-route-ipv6-summary-addr-mask-len</i>	(Optional)
<i>redist-route-ipv6-summary-route-total</i>	(Optional)
TABLE_protocol	(Optional)
<i>redist-route-ipv6-summary-pib-name</i>	(Optional)
<i>redist-route-ipv6-summary-prot-route-total</i>	(Optional)
<i>redist-route-ipv6-summary-pending-total</i>	(Optional)
TABLE_mask_len	(Optional)
<i>redist-route-ipv6-summary-mask-len-ix</i>	(Optional)
<i>redist-route-ipv6-summary-mask-len</i>	(Optional)

Command Mode

- /exec

show isis ipv6 route-map statistics

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ipv6 route-map statistics { { redistribute
{ static | direct | amt | bgp <as> | { <src-isis> | eigrp | ospfv3 | rip } <tag> } } | { distribute <src-level> into
<dst-level> } } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_process_tag [
<process-tag-out> ] [ <route-map-stat-vrf> ] [ { TABLE_process_route_map [ <name> ] [ <action> ] [ <seq>
] [ { TABLE_cmd [ <str> ] [ <compare-count> ] [ <match-count> ] } ] <accept-count> <reject-count> } ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ipv6	Display IS-IS IPv6 information
route-map	Display IS-IS route-map information
statistics	Display IS-IS route-map statistics
redistribute	Redistribute information from another routing protocol
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
eigrp	Enhanced Interior Gateway Protocol
src-isis	IS-IS Routing for IPv6
ospfv3	Open Shortest Path First (OSPF) V3
rip	RIP for IPv6 (RIPNG)
<i>tag</i>	Process tag
distribute	Distribute routes between ISIS levels
into	from level-n into level-m

<i>src-level</i>	Route-distribution between levels
<i>dst-level</i>	Route-distribution between levels
<i>__readonly__</i>	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>route-map-stat-vrf</i>	(Optional)
TABLE_process_route_map	(Optional) Routemap table
<i>name</i>	(Optional) Route-map Name
<i>action</i>	(Optional) Route-map action
<i>seq</i>	(Optional) Sequence number of the rule in route-map
TABLE_cmd	(Optional) Route-map command table
<i>str</i>	(Optional) Route-map command
<i>compare-count</i>	(Optional) Number of comparisons
<i>match-count</i>	(Optional) Number of matches
<i>accept-count</i>	(Optional) Total number of packets accepted by the policy
<i>reject-count</i>	(Optional) Total number of pakcets rejected by the policy

Command Mode

- /exec

show isis ipv6 route

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ipv6 route [ topology { [ base ] |
mt-ipv6 } ] [ summary | detail | private | <ipv6-addr> [ detail | private ] | <ipv6-prefix> [ detail | private |
longer-prefixes [ summary | detail | private ] ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__
{ TABLE_process_tag <process-tag-out> { TABLE_vrf <vrf-name-out> <afi-safi-out> [ TABLE_prefix [
<route-prefix-out> <route-mask-len-out> <route-level-out> ] [ <route-summ-discard-addr-out>
<route-summ-discard-mask-len-out> ] [ <route-discard-addr-out> <route-discard-mask-len-out> ] [
<route-addr-print-out> <route-mask-len-print-out> <route-direct-print-out> ] [ TABLE_direct_path [
<route-direct-out> <route-direct-via-out> <route-direct-if-name-out> <route-direct-metric-out>
<route-direct-level-out> ] [ <route-direct-instance-out> ] ] [ TABLE_best_path [ <route-no-def-prefix-out>
] [ <route-def-prefix-out> ] <route-addr-valid-out> <route-marker-out> <route-ifname-out> <route-metric-out>
<route-pref-out> [ <route-instance-out> ] ] [ <route-discard-mask-out> ] [ [ <route-sum-prefix-out>
<route-sum-prefix-len-out> ] <route-total-out> <route-paths-total-out> <route-paths-best-out>
<route-paths-backup-out> [ TABLE_sum_best_route <route-sum-lvl-out> <route-sum-total-out> [
<route-sum-direct-out> ] [ <route-sum-normal-out> ] [ <route-sum-missing-out> ] ] [
<route-best-pend-num-out> ] <route-bestpaths-out> [ TABLE_sum_best_path <route-path-sum-lvl-out>
<route-path-sum-total-out> [ <route-path-sum-direct-out> ] [ <route-path-sum-normal-out> ] ]
<route-backuppaths-out> [ TABLE_sum_backup_path <backup-path-sum-lvl-out> <backup-path-sum-total-out>
[ <backup-path-sum-direct-out> ] [ <backup-path-sum-normal-out> ] ] <route-bestroutes-per-mask-out> [
TABLE_best_mask <route-best-mask-val-out> <route-best-mask-count-out> ] [ <route-pend-q-count-out> ]
] ] ] ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ipv6	Display IS-IS IPv6 information
route	Display IS-IS route information
topology	(Optional) Display routes for a topology
base	(Optional) Display routes for BASE topology
mt-ipv6	(Optional) Display routes for MT-IPV6-UNICAST topology
longer-prefixes	(Optional) Display exact match and more specific routes
summary	(Optional) Display route counts

detail	(Optional) Display detail route information
private	(Optional) Show detail and internal information
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>afi-safi-out</i>	(Optional)
TABLE_prefix	(Optional)
<i>route-prefix-out</i>	(Optional)
<i>route-mask-len-out</i>	(Optional)
<i>route-level-out</i>	(Optional)
<i>route-summ-discard-addr-out</i>	(Optional)
<i>route-summ-discard-mask-len-out</i>	(Optional)
<i>route-discard-addr-out</i>	(Optional)
<i>route-discard-mask-len-out</i>	(Optional)
<i>route-addr-print-out</i>	(Optional)
<i>route-mask-len-print-out</i>	(Optional)
<i>route-direct-print-out</i>	(Optional)
TABLE_direct_path	(Optional)
<i>route-direct-out</i>	(Optional)
<i>route-direct-via-out</i>	(Optional)
<i>route-direct-if-name-out</i>	(Optional)
<i>route-direct-metric-out</i>	(Optional)
<i>route-direct-level-out</i>	(Optional)
<i>route-direct-instance-out</i>	(Optional)
TABLE_best_path	(Optional)
<i>route-no-def-prefix-out</i>	(Optional)
<i>route-def-prefix-out</i>	(Optional)

<i>route-addr-valid-out</i>	(Optional)
<i>route-marker-out</i>	(Optional)
<i>route-ifname-out</i>	(Optional)
<i>route-metric-out</i>	(Optional)
<i>route-pref-out</i>	(Optional)
<i>route-instance-out</i>	(Optional)
<i>route-discard-mask-out</i>	(Optional)
<i>route-sum-prefix-out</i>	(Optional)
<i>route-sum-prefix-len-out</i>	(Optional)
<i>route-total-out</i>	(Optional)
<i>route-paths-total-out</i>	(Optional)
<i>route-paths-best-out</i>	(Optional)
<i>route-paths-backup-out</i>	(Optional)
TABLE_sum_best_route	(Optional)
<i>route-sum-lvl-out</i>	(Optional)
<i>route-sum-total-out</i>	(Optional)
<i>route-sum-direct-out</i>	(Optional)
<i>route-sum-normal-out</i>	(Optional)
<i>route-sum-missing-out</i>	(Optional)
<i>route-best-pend-num-out</i>	(Optional)
<i>route-bestpaths-out</i>	(Optional)
TABLE_sum_best_path	(Optional)
<i>route-path-sum-lvl-out</i>	(Optional)
<i>route-path-sum-total-out</i>	(Optional)
<i>route-path-sum-direct-out</i>	(Optional)
<i>route-path-sum-normal-out</i>	(Optional)
<i>route-backuppaths-out</i>	(Optional)
TABLE_sum_backup_path	(Optional)
<i>backup-path-sum-lvl-out</i>	(Optional)

<i>backup-path-sum-total-out</i>	(Optional)
<i>backup-path-sum-direct-out</i>	(Optional)
<i>backup-path-sum-normal-out</i>	(Optional)
<i>route-bestroutes-per-mask-out</i>	(Optional)
TABLE_best_mask	(Optional)
<i>route-best-mask-val-out</i>	(Optional)
<i>route-best-mask-count-out</i>	(Optional)
<i>route-pend-q-count-out</i>	(Optional)

Command Mode

- /exec

show isis lslib

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] lslib [ cache [ nodes | links | prefixes
| node <s0> | link <s1> | prefix <s2> | links-of-node <s3> | prefixes-of-node <s4> ] [ detail ] ] [ vrf { <vrf-name>
| <vrf-known-name> | all } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
lslib	LSLIB client information
cache	(Optional) Link-state cache in LSLIB
nodes	(Optional) All Node objects
links	(Optional) All Link objects
prefixes	(Optional) All Prefix objects
node	(Optional) One node object information
<i>s0</i>	(Optional) Node information
link	(Optional) One link object information
<i>s1</i>	(Optional) Link information
prefix	(Optional) One prefix object information
<i>s2</i>	(Optional) Prefix information
links-of-node	(Optional) All links information of a node
<i>s3</i>	(Optional) Node information
prefixes-of-node	(Optional) All prefixes information of a node
<i>s4</i>	(Optional) Node information
detail	(Optional) Detailed info
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

show isis lsp free-list

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] { non-pseudonode | pseudonode {
<interface> | orphan } } lsp free-list [ summary ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
non-pseudonode	Display IS-IS non-pseudo-node information
pseudonode	Display IS-IS pseudo-node information
<i>interface</i>	IS-IS interface
orphan	Display orphan LSP information
lsp	Display IS-IS LSP information
free-list	Display free-list information
summary	(Optional) Display LSP count per free-list

Command Mode

- /exec

show isis mesh-group

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] mesh-group [ <mesh-id> ] [ vrf {
<vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <tag-out> TABLE_vrf <vrf-name-out>
<mesh-id-set-out> <mesh-id-out> <mesh-set-id-out> <mesh-id-intf-name-out> <mesh-id-none-out> ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
mesh-group	Display IS-IS mesh-groups
<i>mesh-id</i>	(Optional) Display a single mesh-group
__readonly__	(Optional)
<i>tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>mesh-id-set-out</i>	(Optional)
<i>mesh-id-out</i>	(Optional)
<i>mesh-set-id-out</i>	(Optional)
<i>mesh-id-intf-name-out</i>	(Optional)
<i>mesh-id-none-out</i>	(Optional)

Command Mode

- /exec

show isis non tlv overflow-list

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] { non-pseudonode | pseudonode  
<interface> } tlv overflow-list [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
non-pseudonode	Display IS-IS non-pseudo-node information
pseudonode	Display IS-IS pseudo-node information
<i>interface</i>	IS-IS interface
tlv	Display IS-IS TLV information
overflow-list	Display ISIS TLV overflow-list information

Command Mode

- /exec

show isis redistribute route

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ ip ] redistribute route [ summary |
<ip-addr> | <ip-prefix> [ longer-prefixes [ summary ] ] [ direct-mask ] [ vrf { <vrf-name> | <vrf-known-name>
| all } ] [ __readonly__ TABLE_process_tag <process-tag-out> <redist-route-vrf> [ <redist-route-af-ix> ] [
{ TABLE_one_route <redist-route-prefix> [ <redist-route-mask-len> ] [ <redist-route-pib-name> ] [
<redist-route-direct-mask> ] [ <redist-route-route-type> ] [ { TABLE_redist <redist-route-status>
<redist-route-level> [ <redist-route-metric> ] [ <redist-route-sum-addr-prefix> ] [
<redist-route-sum-addr-mask-len> ] } ] [ <redist-route-summary-addr-prefix> ] [
<redist-route-summary-addr-mask-len> ] [ <redist-route-summary-route-total> ] [ { TABLE_protocol
<redist-route-summary-pib-name> [ <redist-route-summary-prot-route-total> ] } ] [
<redist-route-summary-pending-total> ] [ { TABLE_mask_len <redist-route-summary-mask-len-ix> [
<redist-route-summary-mask-len> ] } ] ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
redistribute	Display IS-IS redistribute information
route	Display ISIS redistribute route
ip	(Optional) Display IS-IS IPv4 information
<i>ip-addr</i>	(Optional) Display single IP redistribute route
<i>ip-prefix</i>	(Optional) Display single exact match IP redistribute route
longer-prefixes	(Optional) Display exact match and more specific routes
summary	(Optional) Display route counts
direct-mask	(Optional) Display routes with direct-mask set
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>redist-route-vrf</i>	(Optional)

<i>redist-route-af-ix</i>	(Optional)
TABLE_one_route	(Optional)
<i>redist-route-prefix</i>	(Optional)
<i>redist-route-mask-len</i>	(Optional)
<i>redist-route-pib-name</i>	(Optional)
<i>redist-route-direct-mask</i>	(Optional)
<i>redist-route-route-type</i>	(Optional)
TABLE_redist	(Optional)
<i>redist-route-status</i>	(Optional)
<i>redist-route-level</i>	(Optional)
<i>redist-route-metric</i>	(Optional)
<i>redist-route-sum-addr-prefix</i>	(Optional)
<i>redist-route-sum-addr-mask-len</i>	(Optional)
<i>redist-route-summary-addr-prefix</i>	(Optional)
<i>redist-route-summary-addr-mask-len</i>	(Optional)
<i>redist-route-summary-route-total</i>	(Optional)
TABLE_protocol	(Optional)
<i>redist-route-summary-pib-name</i>	(Optional)
<i>redist-route-summary-prot-route-total</i>	(Optional)
<i>redist-route-summary-pending-total</i>	(Optional)
TABLE_mask_len	(Optional)
<i>redist-route-summary-mask-len-ix</i>	(Optional)
<i>redist-route-summary-mask-len</i>	(Optional)

Command Mode

- /exec

show isis route-map statistics

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ ip ] route-map statistics { { redistribute
{ static | direct | amt | bgp <as> | { <src-isis> | eigrp | ospf | rip } <tag> } } | { distribute <src-level> into
<dst-level> } } [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag
<process-tag-out> { TABLE_vrf <route-map-stat-vrf> [ { TABLE_process_route_map [ <name> ] [ <action>
] [ <seq> ] [ { TABLE_cmd [ <str> ] [ <compare-count> ] [ <match-count> ] } ] <accept-count> <reject-count>
} } } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ip	(Optional) Display IS-IS IPv4 information
route-map	Display IS-IS route-map information
statistics	Display IS-IS route-map statistics
redistribute	Redistribute information from another routing protocol
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
eigrp	Enhanced Interior Gateway Protocol
src-isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
rip	RIP for IPv4
<i>tag</i>	Process tag
distribute	Distribute routes between ISIS levels

<i>into</i>	from level-n into level-m
<i>src-level</i>	Route-distribution between levels
<i>dst-level</i>	Route-distribution between levels
<i>__readonly__</i>	(Optional)
<i>TABLE_process_tag</i>	(Optional)
<i>process-tag-out</i>	(Optional)
<i>TABLE_vrf</i>	(Optional)
<i>route-map-stat-vrf</i>	(Optional)
<i>TABLE_process_route_map</i>	(Optional) Routemap table
<i>name</i>	(Optional) Route-map Name
<i>action</i>	(Optional) Route-map action
<i>seq</i>	(Optional) Sequence number of the rule in route-map
<i>TABLE_cmd</i>	(Optional) Route-map command table
<i>str</i>	(Optional) Route-map command
<i>compare-count</i>	(Optional) Number of comparisons
<i>match-count</i>	(Optional) Number of matches
<i>accept-count</i>	(Optional) Total number of packets accepted by the policy
<i>reject-count</i>	(Optional) Total number of packets rejected by the policy

Command Mode

- /exec

show isis route

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ ip ] route [ summary | detail | private
| <ip-addr> [ detail | private ] | <ip-prefix> [ detail | private | longer-prefixes [ summary | detail | private ] ] ]
[ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> {
TABLE_vrf <vrf-name-out> <afi-safi-out> [ TABLE_prefix [ <route-prefix-out> <route-mask-len-out>
<route-level-out> ] [ <route-summ-discard-addr-out> <route-summ-discard-mask-len-out> ] [
<route-discard-addr-out> <route-discard-mask-len-out> ] [ <route-addr-print-out> <route-mask-len-print-out>
<route-direct-print-out> ] [ TABLE_direct_path [ <route-direct-out> <route-direct-via-out>
<route-direct-if-name-out> <route-direct-metric-out> <route-direct-level-out> ] [ <route-direct-instance-out>
] ] [ TABLE_best_path [ <route-no-def-prefix-out> ] [ <route-def-prefix-out> ] <route-addr-valid-out>
<route-marker-out> <route-ifname-out> <route-metric-out> <route-pref-out> [ <route-instance-out> ] ] [
<route-discard-mask-out> ] [ [ <route-sum-prefix-out> <route-sum-prefix-len-out> ] <route-total-out>
<route-paths-total-out> <route-paths-best-out> <route-paths-backup-out> [ TABLE_sum_best_route
<route-sum-lvl-out> <route-sum-total-out> [ <route-sum-direct-out> ] [ <route-sum-normal-out> ] [
<route-sum-missing-out> ] ] [ <route-best-pend-num-out> ] <route-bestpaths-out> [ TABLE_sum_best_path
<route-path-sum-lvl-out> <route-path-sum-total-out> [ <route-path-sum-direct-out> ] [
<route-path-sum-normal-out> ] ] <route-backuppaths-out> [ TABLE_sum_backup_path
<backup-path-sum-lvl-out> <backup-path-sum-total-out> [ <backup-path-sum-direct-out> ] [
<backup-path-sum-normal-out> ] ] <route-bestroutes-per-mask-out> [ TABLE_best_mask
<route-best-mask-val-out> <route-best-mask-count-out> ] [ <route-pend-q-count-out> ] ] ] } }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ip	(Optional) Display IS-IS IPv4 information
route	Display IS-IS route information
<i>ip-addr</i>	(Optional) Display single IP route
<i>ip-prefix</i>	(Optional) Display single exact match IP route
longer-prefixes	(Optional) Display exact match and more specific routes
summary	(Optional) Display route counts
detail	(Optional) Display detail route information
private	(Optional) Show detail and internal information

<code>__readonly__</code>	(Optional)
<code>TABLE_process_tag</code>	(Optional)
<code>process-tag-out</code>	(Optional)
<code>TABLE_vrf</code>	(Optional)
<code>vrf-name-out</code>	(Optional)
<code>afi-safi-out</code>	(Optional)
<code>TABLE_prefix</code>	(Optional)
<code>route-prefix-out</code>	(Optional)
<code>route-mask-len-out</code>	(Optional)
<code>route-level-out</code>	(Optional)
<code>route-summ-discard-addr-out</code>	(Optional)
<code>route-summ-discard-mask-len-out</code>	(Optional)
<code>route-discard-addr-out</code>	(Optional)
<code>route-discard-mask-len-out</code>	(Optional)
<code>route-addr-print-out</code>	(Optional)
<code>route-mask-len-print-out</code>	(Optional)
<code>route-direct-print-out</code>	(Optional)
<code>TABLE_direct_path</code>	(Optional)
<code>route-direct-out</code>	(Optional)
<code>route-direct-via-out</code>	(Optional)
<code>route-direct-if-name-out</code>	(Optional)
<code>route-direct-metric-out</code>	(Optional)
<code>route-direct-level-out</code>	(Optional)
<code>route-direct-instance-out</code>	(Optional)
<code>TABLE_best_path</code>	(Optional)
<code>route-no-def-prefix-out</code>	(Optional)
<code>route-def-prefix-out</code>	(Optional)
<code>route-addr-valid-out</code>	(Optional)
<code>route-marker-out</code>	(Optional)

<i>route-ifname-out</i>	(Optional)
<i>route-metric-out</i>	(Optional)
<i>route-pref-out</i>	(Optional)
<i>route-instance-out</i>	(Optional)
<i>route-discard-mask-out</i>	(Optional)
<i>route-sum-prefix-out</i>	(Optional)
<i>route-sum-prefix-len-out</i>	(Optional)
<i>route-total-out</i>	(Optional)
<i>route-paths-total-out</i>	(Optional)
<i>route-paths-best-out</i>	(Optional)
<i>route-paths-backup-out</i>	(Optional)
TABLE_sum_best_route	(Optional)
<i>route-sum-lvl-out</i>	(Optional)
<i>route-sum-total-out</i>	(Optional)
<i>route-sum-direct-out</i>	(Optional)
<i>route-sum-normal-out</i>	(Optional)
<i>route-sum-missing-out</i>	(Optional)
<i>route-best-pend-num-out</i>	(Optional)
<i>route-bestpaths-out</i>	(Optional)
TABLE_sum_best_path	(Optional)
<i>route-path-sum-lvl-out</i>	(Optional)
<i>route-path-sum-total-out</i>	(Optional)
<i>route-path-sum-direct-out</i>	(Optional)
<i>route-path-sum-normal-out</i>	(Optional)
<i>route-backuppaths-out</i>	(Optional)
TABLE_sum_backup_path	(Optional)
<i>backup-path-sum-lvl-out</i>	(Optional)
<i>backup-path-sum-total-out</i>	(Optional)
<i>backup-path-sum-direct-out</i>	(Optional)

<i>backup-path-sum-normal-out</i>	(Optional)
<i>route-bestroutes-per-mask-out</i>	(Optional)
TABLE_best_mask	(Optional)
<i>route-best-mask-val-out</i>	(Optional)
<i>route-best-mask-count-out</i>	(Optional)
<i>route-pend-q-count-out</i>	(Optional)

Command Mode

- /exec

show isis route is

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] route is [ topology { [ base ] | mt-ipv6 } ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
route	Display IS-IS route information
is	Display IS route
topology	(Optional) Display routes for a topology
base	(Optional) Display routes for BASE topology
mt-ipv6	(Optional) Display routes for MT-IPV6-UNICAST topology

Command Mode

- /exec

show isis rrm

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] rrm <interface> [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> <rrm-if-name> [ {
TABLE_rrm <rrm-level> <rrm-retx-interval> <rrm-retx-throttle-interval> <rrm-retx-queue-length>
<rrm-next-retx> <rrm-retx-queue-hwm> <rrm-retx-queue-exceed> <rrm-dbase-hdr> [ <rrm-timestamp> ] [
<rrm-lsp-retx-instance> ] [ <rrm-lsp-db-instance> ] [ <rrm-rrm-set> ] [ <rrm-srm-set> } } ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
rrm	Display IS-IS Retransmit-Routing-Message information
<i>interface</i>	IS-IS interface
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>rrm-if-name</i>	(Optional)
TABLE_rrm	(Optional)
<i>rrm-level</i>	(Optional)
<i>rrm-retx-interval</i>	(Optional)
<i>rrm-retx-throttle-interval</i>	(Optional)
<i>rrm-retx-queue-length</i>	(Optional)
<i>rrm-next-retx</i>	(Optional)
<i>rrm-retx-queue-hwm</i>	(Optional)
<i>rrm-retx-queue-exceed</i>	(Optional)
<i>rrm-dbase-hdr</i>	(Optional)
<i>rrm-timestamp</i>	(Optional)

<i>rrm-lsp-retx-instance</i>	(Optional)
<i>rrm-lsp-db-instance</i>	(Optional)
<i>rrm-rrm-set</i>	(Optional)
<i>rrm-srm-set</i>	(Optional)

Command Mode

- /exec

show isis segment-routing local-mapcache

show isis [<isis-tag>] segment-routing local-mapcache [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
segment-routing	show segment-routing information
local-mapcache	local prefix-sid mappings
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

show isis segment-routing mapcache

```
show isis [ <isis-tag> ] segment-routing mapcache [ level-1 | level-2 ] [ <ipv4-prefix> ] [ sid <sr-sid> ] [ vrf
{ <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> {
TABLE_vrf <vrf-name-out> <srmap-v4-state> <srmap-v6-state> [ { TABLE_srmap_level <srmap-level> [
{ TABLE_srmap_pfxsid <srmap-pfxsid> <srmap-lsp-id> <srmap-pfxsid-valid> <srmap-pfxsid-flags>
<srmap-prefix> } ] } } } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
segment-routing	show segment-routing information
mapcache	prefix-sid mappings
level-1	(Optional) show information for level 1 only
level-2	(Optional) show information for level 2 only
<i>ipv4-prefix</i>	(Optional) Display single exact match IP route
sid	(Optional) show information for this SR SID value
<i>sr-sid</i>	(Optional) SR SID value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>srmap-v4-state</i>	(Optional)
<i>srmap-v6-state</i>	(Optional)
TABLE_srmap_level	(Optional)
<i>srmap-level</i>	(Optional)

TABLE_srmap_pfxsid	(Optional)
<i>srmap-pfxsid</i>	(Optional)
<i>srmap-lsp-id</i>	(Optional)
<i>srmap-pfxsid-valid</i>	(Optional)
<i>srmap-pfxsid-flags</i>	(Optional)
<i>srmap-prefix</i>	(Optional)

Command Mode

- /exec

show isis segment-routing remote-srgb

```
show isis [ <isis-tag> ] segment-routing remote-srgb [ vrf { <vrf-name> | <vrf-known-name> | all } ] [
__readonly__ { TABLE_process_tag <process-tag-out> { TABLE_vrf <vrf-name-out> <sr-v4-state>
<sr-v6-state> [ { TABLE_srgb_lsp <srgb-level> <srgb-lspid> <srgb-num-entries> <srgb-flags> [ {
TABLE_srgb_label <srgb-start-label> <srgb-range> } ] } ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
segment-routing	show segment-routing information
remote-srgb	remote SR ranges
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>sr-v4-state</i>	(Optional)
<i>sr-v6-state</i>	(Optional)
TABLE_srgb_lsp	(Optional)
<i>srgb-level</i>	(Optional)
<i>srgb-lspid</i>	(Optional)
<i>srgb-num-entries</i>	(Optional)
<i>srgb-flags</i>	(Optional)
TABLE_srgb_label	(Optional)
<i>srgb-start-label</i>	(Optional)

<i>srgb-range</i>	(Optional)
-------------------	------------

Command Mode

- /exec

show isis segment-routing sids

show isis [<isis-tag>] segment-routing sids [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
segment-routing	show segment-routing information
sids	sid database
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

show isis spf-adjacency

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] spf-adjacency [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ TABLE_process_tag <process-tag-out> <spf-adjacency-vrf> [
<spf-adjacency-system-name> ] [ <spf-adjacency-refcount> ] [ <spf-adjacency-if-name> ] [
<spf-adjacency-rib-addr> ] [ <spf-adjacency-rib-addr-valid> ] [ <spf-adjacency-rib-ipv6-addr> ] [
<spf-adjacency-rib-ipv6-addr-valid> ] [ <spf-adjacency-spf-addr> ] [ <spf-adjacency-spf-ipv6-addr> ] [ {
TABLE_SPFADJLEVEL <spf-adjacency-level> } ] ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
spf-adjacency	Display IS-IS SPF adjacency information
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>spf-adjacency-vrf</i>	(Optional)
<i>spf-adjacency-system-name</i>	(Optional)
<i>spf-adjacency-refcount</i>	(Optional)
<i>spf-adjacency-if-name</i>	(Optional)
<i>spf-adjacency-rib-addr</i>	(Optional)
<i>spf-adjacency-rib-addr-valid</i>	(Optional)
<i>spf-adjacency-rib-ipv6-addr</i>	(Optional)
<i>spf-adjacency-rib-ipv6-addr-valid</i>	(Optional)
<i>spf-adjacency-spf-addr</i>	(Optional)
<i>spf-adjacency-spf-ipv6-addr</i>	(Optional)
TABLE_SPFADJLEVEL	(Optional)

<i>spf-adjacency-level</i>	(Optional)
----------------------------	------------

Command Mode

- /exec

show isis spf-log

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] spf-log [ detail ] [ vrf { <vrf-name>
| <vrf-known-name> | all } ] [ __readonly__ <tag-out> TABLE_vrf <vrf-name-out> <spflog-calc-out>
<spflog-size-out> <spflog-maxsize-out> <spflog-ago-time-out> <spflog-lvl-out> <spflog-reason-out>
<spflog-count-out> <spflog-elapsed-ts-out> <spflog-log-num-out> <spflog-ts-detail-out>
<spflog-date-detail-out> <spflog-lvl-detail-out> <spflog-instance-detail-out> <spflog-init-ts-detail-out>
<spflog-spf-ts-detail-out> <spflog-detail-ts-is-out> <spflog-detail-ts-urib-out> <spflog-detail-ts-elapsed-out>
<spflog-detail-lvl-out> <spflog-detail-spf-cnt-out> <spflog-detail-sync-cnt-out> <spflog-detail-spf-reason-out>
]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
spf-log	Display IS-IS SPF information
detail	(Optional) Display detail ISIS SPF information
__readonly__	(Optional)
<i>tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>spflog-calc-out</i>	(Optional)
<i>spflog-size-out</i>	(Optional)
<i>spflog-maxsize-out</i>	(Optional)
<i>spflog-ago-time-out</i>	(Optional)
<i>spflog-lvl-out</i>	(Optional)
<i>spflog-reason-out</i>	(Optional)
<i>spflog-count-out</i>	(Optional)
<i>spflog-elapsed-ts-out</i>	(Optional)

<i>spflog-log-num-out</i>	(Optional)
<i>spflog-ts-detail-out</i>	(Optional)
<i>spflog-date-detail-out</i>	(Optional)
<i>spflog-lvl-detail-out</i>	(Optional)
<i>spflog-instance-detail-out</i>	(Optional)
<i>spflog-init-ts-detail-out</i>	(Optional)
<i>spflog-spf-ts-detail-out</i>	(Optional)
<i>spflog-detail-ts-is-out</i>	(Optional)
<i>spflog-detail-ts-urib-out</i>	(Optional)
<i>spflog-detail-ts-elapsed-out</i>	(Optional)
<i>spflog-detail-lvl-out</i>	(Optional)
<i>spflog-detail-spf-cnt-out</i>	(Optional)
<i>spflog-detail-sync-cnt-out</i>	(Optional)
<i>spflog-detail-spf-reason-out</i>	(Optional)

Command Mode

- /exec

show isis srm

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] srm <interface> [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> <srm-if-name> [ {
TABLE_srm <srm-level> <srm-if-eligible> <srm-if-not-on-srm-list> <srm-lsp-interval> <srm-next-lsp>
<srm-dbase-hdr> } ] } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
srm	Display IS-IS Send-Routing-Message information
<i>interface</i>	IS-IS interface
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>srm-if-name</i>	(Optional)
TABLE_srm	(Optional)
<i>srm-level</i>	(Optional)
<i>srm-if-eligible</i>	(Optional)
<i>srm-if-not-on-srm-list</i>	(Optional)
<i>srm-lsp-interval</i>	(Optional)
<i>srm-next-lsp</i>	(Optional)
<i>srm-dbase-hdr</i>	(Optional)

Command Mode

- /exec

show isis ssn

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ssn <interface> [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out> <snn-if-name> [ { TABLE_ssn <snn-level> <snn-psnp-eligible> <snn-next-psnp> <snn-dbase_hdr> } ] } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ssn	Display IS-IS Send-Sequence-Number information
<i>interface</i>	IS-IS interface
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>snn-if-name</i>	(Optional)
TABLE_ssn	(Optional)
<i>snn-level</i>	(Optional)
<i>snn-psnp-eligible</i>	(Optional)
<i>snn-next-psnp</i>	(Optional)
<i>snn-dbase_hdr</i>	(Optional)

Command Mode

- /exec

show isis statistics

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] statistics [ <interface> ] [ vrf {
<vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <tag-out> TABLE_vrf <vrf-name-out> <stat-if-out>
<stat-if-name-out> <stat-spf-calc-out> <stat-lsp-sourced-out> <stat-lsp-refresh-out> <stat-lsp-purge-out>
<stat-dis-elections-out> ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Display IS-IS protocol statistics
<i>interface</i>	(Optional) IS-IS interface
__readonly__	(Optional)
<i>tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>stat-if-out</i>	(Optional)
<i>stat-if-name-out</i>	(Optional)
<i>stat-spf-calc-out</i>	(Optional)
<i>stat-lsp-sourced-out</i>	(Optional)
<i>stat-lsp-refresh-out</i>	(Optional)
<i>stat-lsp-purge-out</i>	(Optional)
<i>stat-dis-elections-out</i>	(Optional)

Command Mode

- exec

show isis summary-address show isis ipv6 summary-address

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ ip ] summary-address [ <ip-addr> |
<ip-prefix> [ longer-prefixes ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] | show isis [ <isis-tag> ] [
vrf { <vrf-name> | <vrf-known-name> | all } ] ipv6 summary-address [ <ipv6-addr> | <ipv6-prefix> [
longer-prefixes ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ <tag-out> TABLE_vrf
<vrf-name-out> <afi-safi-out> <addr-absent-out> <addr-prefix-out> <addr-mask-len-out> <addr-level-out>
<addr-num-out> <addr-lvl-out> <addr-metric-absent-out> <addr-metric-out> <addr-route-count-out> ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ip	(Optional) Display IS-IS IPv4 information
ipv6	Display IS-IS IPv6 information
summary-address	Display IS-IS summary address
<i>ip-addr</i>	(Optional) Display single IP summary address
<i>ip-prefix</i>	(Optional) Display single exact match IP summary address
longer-prefixes	(Optional) Display exact match and more specific summary address
<i>isis-tag</i>	(Optional)
<i>__readonly__</i>	(Optional)
<i>tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>afi-safi-out</i>	(Optional)
<i>addr-absent-out</i>	(Optional)
<i>addr-prefix-out</i>	(Optional)
<i>addr-mask-len-out</i>	(Optional)

<i>addr-level-out</i>	(Optional)
<i>addr-num-out</i>	(Optional)
<i>addr-lvl-out</i>	(Optional)
<i>addr-metric-absent-out</i>	(Optional)
<i>addr-metric-out</i>	(Optional)
<i>addr-route-count-out</i>	(Optional)

Command Mode

- /exec

show isis topology

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] topology [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ TABLE_process_tag <process-tag-out> <topology-vrf> [ {
TABLE_LEVEL <topology-level> [ { TABLE_ONE_ROUTE <topology-one-route-node-name> [
<topology-one-route-spf-instance> ] [ <topology-one-route-on-path> ] [ <topology-one-route-mt-id> ] [ {
TABLE_ONE_ROUTE_NH <topology-one-route-nh-system-name> [ <topology-one-route-nh-if-name> ] [
<topology-one-route-nh-metric> } ] ] [ { TABLE_ONE_ROUTE_MBEST
<topology-one-route-mbest-system-name> [ <topology-one-route-mbest-if-name> ] [
<topology-one-route-mbest-metric> } ] } ] [ <topology-default-spf-instance> ] [ { TABLE_NH
<topology-nh-system-name> [ <topology-nh-if-name> ] [ <topology-nh-metric> } ] ] [ { TABLE_MBEST
<topology-mbest-system-name> [ <topology-mbest-if-name> ] [ <topology-mbest-metric> } ] } ] }
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
topology	Display IS-IS Topology information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>topology-vrf</i>	(Optional)
TABLE_LEVEL	(Optional)
<i>topology-level</i>	(Optional)
TABLE_ONE_ROUTE	(Optional)
<i>topology-one-route-node-name</i>	(Optional)
<i>topology-one-route-spf-instance</i>	(Optional)
<i>topology-one-route-on-path</i>	(Optional)
<i>topology-one-route-mt-id</i>	(Optional)
TABLE_ONE_ROUTE_NH	(Optional)

<i>topology-one-route-nh-system-name</i>	(Optional)
<i>topology-one-route-nh-if-name</i>	(Optional)
<i>topology-one-route-nh-metric</i>	(Optional)
TABLE_ONE_ROUTE_MBEST	(Optional)
<i>topology-one-route-mbest-system-name</i>	(Optional)
<i>topology-one-route-mbest-if-name</i>	(Optional)
<i>topology-one-route-mbest-metric</i>	(Optional)
<i>topology-default-spf-instance</i>	(Optional)
TABLE_NH	(Optional)
<i>topology-nh-system-name</i>	(Optional)
<i>topology-nh-if-name</i>	(Optional)
<i>topology-nh-metric</i>	(Optional)
TABLE_MBEST	(Optional)
<i>topology-mbest-system-name</i>	(Optional)
<i>topology-mbest-if-name</i>	(Optional)
<i>topology-mbest-metric</i>	(Optional)

Command Mode

- /exec

show isis traffic

```
show isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] traffic [ <interface> ] [ mbuf-priority
] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ { TABLE_process_tag <process-tag-out>
{ TABLE_vrf <vrf-name-out> <traffic-if-out> [ <traffic-if-name-out> ] <traffic-lan-iih-out>
<traffic-lan-iih-rcv-out> <traffic-lan-iih-xmit-out> <traffic-lan-iih-rcv-auth-err-out> <traffic-lan-iih-rcv-err-out>
<traffic-p2p-iih-out> <traffic-p2p-iih-rcv-out> <traffic-p2p-iih-xmit-out> <traffic-p2p-iih-rcv-auth-err-out>
<traffic-p2p-iih-rcv-err-out> <traffic-csnp-out> <traffic-csnp-rcv-out> <traffic-csnp-xmit-out>
<traffic-csnp-rcv-auth-err-out> <traffic-csnp-rcv-err-out> <traffic-psnp-out> <traffic-psnp-rcv-out>
<traffic-psnp-xmit-out> <traffic-psnp-rcv-auth-err-out> <traffic-psnp-rcv-err-out> <traffic-lsp-out>
<traffic-lsp-rcv-out> <traffic-lsp-flood-out> <traffic-lsp-rcv-auth-err-out> <traffic-lsp-rcv-err-out>
<traffic-lsp-rexmit-out> [ <traffic-xmit-err-out> ] [ <traffic-unknown-pdu-rcv-out> ] } } ]
```

Syntax Description

show	Show running system information
isis	Display IS-IS status and configuration
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Display IS-IS traffic information
<i>interface</i>	(Optional) IS-IS interface
mbuf-priority	(Optional) Display mbuf priorities for received PDUs
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>traffic-if-out</i>	(Optional)
<i>traffic-if-name-out</i>	(Optional)
<i>traffic-lan-iih-out</i>	(Optional)
<i>traffic-lan-iih-rcv-out</i>	(Optional)
<i>traffic-lan-iih-xmit-out</i>	(Optional)

<i>traffic-lan-iih-rcv-auth-err-out</i>	(Optional)
<i>traffic-lan-iih-rcv-err-out</i>	(Optional)
<i>traffic-p2p-iih-out</i>	(Optional)
<i>traffic-p2p-iih-rcv-out</i>	(Optional)
<i>traffic-p2p-iih-xmit-out</i>	(Optional)
<i>traffic-p2p-iih-rcv-auth-err-out</i>	(Optional)
<i>traffic-p2p-iih-rcv-err-out</i>	(Optional)
<i>traffic-csnp-out</i>	(Optional)
<i>traffic-csnp-rcv-out</i>	(Optional)
<i>traffic-csnp-xmit-out</i>	(Optional)
<i>traffic-csnp-rcv-auth-err-out</i>	(Optional)
<i>traffic-csnp-rcv-err-out</i>	(Optional)
<i>traffic-psnp-out</i>	(Optional)
<i>traffic-psnp-rcv-out</i>	(Optional)
<i>traffic-psnp-xmit-out</i>	(Optional)
<i>traffic-psnp-rcv-auth-err-out</i>	(Optional)
<i>traffic-psnp-rcv-err-out</i>	(Optional)
<i>traffic-lsp-out</i>	(Optional)
<i>traffic-lsp-rcv-out</i>	(Optional)
<i>traffic-lsp-flood-out</i>	(Optional)
<i>traffic-lsp-rcv-auth-err-out</i>	(Optional)
<i>traffic-lsp-rcv-err-out</i>	(Optional)
<i>traffic-lsp-rexmit-out</i>	(Optional)
<i>traffic-xmit-err-out</i>	(Optional)
<i>traffic-unknown-pdu-rcv-out</i>	(Optional)

Command Mode

- /exec

show itd

```
show itd [ brief ] [ __readonly__ <is_firstentry> <is_detail> <is_active> <is_firstentry_routemap>
<is_firstentry_standby> <is_firstentry_acl> <is_lastentry> [ TABLE_summary <service_name> <probe>
<lb_scheme> [ <interface> ] <state> <buckets> [ <reason> ] <vrf_name> <userACL> <peer_status> [
TABLE_device <device_grp> <dg_probe> <dg_probe_port> ] [ TABLE_route_map [ <route_map> ] [
<interface> ] [ <r_status> ] [ <int_track_id> ] ] [ TABLE_vip [ <vip_ip> ] [ <vip_probe> ] [ <vip_port> ] [
<vip_dgname> ] [ TABLE_vip_node [ <vip_node> ] [ <vip_nodev6> ] <vip_config> <vip_weight>
<vip_node_probe> <vip_node_probe_port> <vip_node_probe_ip> <vip_status> <vip_track_id>
<vip_ip_sla_id> [ TABLE_vip_standby [ <vip_standby_ip> ] [ <vip_standby_ipv6> ] <vip_standby_config>
<vip_standby_weight> <vip_standby_probe> <vip_standby_probe_port> <vip_standby_probe_ip>
<vip_standby_status> <vip_standby_track_id> <vip_standby_sla_id> ] [ TABLE_vip_acl [ <vip_access_list>
] ] ] [ TABLE_node [ <node> ] [ <nodev6> ] <config> <weight> <node_probe> <node_probe_port>
<node_probe_ip> <status> <track_id> <ip_sla_id> [ TABLE_standby [ <standby_ip> ] [ <standby_ipv6> ]
<standby_config> <standby_weight> <standby_probe> <standby_probe_port> <standby_probe_ip>
<standby_status> <standby_track_id> <standby_sla_id> ] [ TABLE_acl [ <access_list> ] ] ] ] ]
```

Syntax Description

show	Show running system information
itd	ITD service
brief	(Optional) brief
__readonly__	(Optional) Read Only
is_firstentry	(Optional)
is_detail	(Optional)
is_active	(Optional)
is_firstentry_routemap	(Optional)
is_firstentry_acl	(Optional)
is_lastentry	(Optional)
is_firstentry_standby	(Optional)
TABLE_summary	(Optional)
service_name	(Optional) service_name
probe	(Optional) probe
lb_scheme	(Optional) lb scheme
interface	(Optional) interface
state	(Optional) state
buckets	(Optional) buckets

<i>reason</i>	(Optional) inactive reason
<i>vrf_name</i>	(Optional) VRF-Name
<i>userACL</i>	(Optional) user access-list
<i>peer_status</i>	(Optional) peer status
TABLE_device	(Optional)
<i>device_grp</i>	(Optional) service device group
<i>dg_probe</i>	(Optional) device-group probe type
<i>dg_probe_port</i>	(Optional) device-group probe port
TABLE_route_map	(Optional)
<i>route_map</i>	(Optional) service route map
<i>interface</i>	(Optional) interface
<i>r_status</i>	(Optional) route map status
<i>int_track_id</i>	(Optional) interface track id
TABLE_vip	(Optional)
<i>vip_ip</i>	(Optional) vip ip
<i>vip_probe</i>	(Optional) vip protocol
<i>vip_port</i>	(Optional) vip port
<i>vip_dgname</i>	(Optional) vip device group
TABLE_vip_node	(Optional)
<i>vip_node</i>	(Optional) service node ip
<i>vip_nodev6</i>	(Optional) service node IPv6
<i>vip_config</i>	(Optional) node config
<i>vip_weight</i>	(Optional) node weight
<i>vip_status</i>	(Optional) node status
<i>vip_node_probe</i>	(Optional) node probe type
<i>vip_node_probe_port</i>	(Optional) node probe port
<i>vip_node_probe_ip</i>	(Optional) node probe ip
<i>vip_track_id</i>	(Optional) node track id
<i>vip_ip_sla_id</i>	(Optional) node ip sla id

TABLE_vip_standby	(Optional)
<i>vip_standby_ip</i>	(Optional) standby node ip
<i>vip_standby_ipv6</i>	(Optional) standby node ipv6
<i>vip_standby_config</i>	(Optional) standby node config
<i>vip_standby_weight</i>	(Optional) standby node weight
<i>vip_standby_status</i>	(Optional) standby node status
<i>vip_standby_probe</i>	(Optional) standby node probe type
<i>vip_standby_probe_port</i>	(Optional) standby node probe port
<i>vip_standby_probe_ip</i>	(Optional) standby node probe ip
<i>vip_standby_track_id</i>	(Optional) standby node track id
<i>vip_standby_sla_id</i>	(Optional) standby node sla id
TABLE_vip_acl	(Optional)
<i>vip_access_list</i>	(Optional) access list
TABLE_node	(Optional)
<i>node</i>	(Optional) service node ip
<i>nodev6</i>	(Optional) service node IPv6
<i>config</i>	(Optional) node config
<i>weight</i>	(Optional) node weight
<i>status</i>	(Optional) node status
<i>node_probe</i>	(Optional) node probe type
<i>node_probe_port</i>	(Optional) node probe port
<i>node_probe_ip</i>	(Optional) node probe ip
<i>track_id</i>	(Optional) node track id
<i>ip_sla_id</i>	(Optional) node ip sla id
TABLE_standby	(Optional)
<i>standby_ip</i>	(Optional) standby node ip
<i>standby_ipv6</i>	(Optional) standby node ipv6
<i>standby_config</i>	(Optional) standby node config
<i>standby_weight</i>	(Optional) standby node weight

<i>standby_status</i>	(Optional) standby node status
<i>standby_probe</i>	(Optional) standby node probe type
<i>standby_probe_port</i>	(Optional) standby node probe port
<i>standby_probe_ip</i>	(Optional) standby node probe ip
<i>standby_track_id</i>	(Optional) standby node track id
<i>standby_sla_id</i>	(Optional) standby node sla id
TABLE_acl	(Optional)
<i>access_list</i>	(Optional) access list

Command Mode

- /exec

show itd

```
show itd <svc-name> [ brief ] [ __readonly__ <is_firstentry> <is_detail> <is_active> <is_firstentry_routemap>
<is_firstentry_standby> <is_firstentry_acl> <is_lastentry> [ TABLE_summary <service_name> <probe>
<lb_scheme> [ <interface> ] <state> <buckets> [ <reason> ] <vrf_name> <userACL> <peer_status> [
TABLE_device <device_grp> <dg_probe> <dg_probe_port> ] [ TABLE_route_map [ <route_map> ] [
<interface> ] [ <r_status> ] [ <int_track_id> ] ] [ TABLE_vip [ <vip_ip> ] [ <vip_probe> ] [ <vip_port> ] [
<vip_dgname> ] [ <ace_name> ] [ <ace_seq> ] [ <ace_ip> ] [ <ace_protocol> ] [ <ace_port> ] [
TABLE_vip_node [ <vip_node> ] [ <vip_nodev6> ] <vip_config> <vip_weight> <vip_node_probe>
<vip_node_probe_port> <vip_node_probe_ip> <vip_status> <vip_track_id> <vip_ip_sla_id> [
TABLE_vip_standby [ <vip_standby_ip> ] [ <vip_standby_ipv6> ] <vip_standby_config>
<vip_standby_weight> <vip_standby_probe> <vip_standby_probe_port> <vip_standby_probe_ip>
<vip_standby_status> <vip_standby_track_id> <vip_standby_sla_id> ] [ TABLE_vip_acl [ <vip_access_list>
] ] ] [ TABLE_node [ <node> ] [ <nodev6> ] <config> <weight> <node_probe> <node_probe_port>
<node_probe_ip> <status> <track_id> <ip_sla_id> [ TABLE_standby [ <standby_ip> ] [ <standby_ipv6> ]
<standby_config> <standby_weight> <standby_probe> <standby_probe_port> <standby_probe_ip>
<standby_status> <standby_track_id> <standby_sla_id> ] [ TABLE_acl [ <access_list> ] ] ] ] ]
```

Syntax Description

show	Show running system information
itd	ITD service
<i>svc-name</i>	ITD service name
brief	(Optional) brief
<i>__readonly__</i>	(Optional) Read Only
<i>is_firstentry</i>	(Optional)
<i>is_detail</i>	(Optional)
<i>is_active</i>	(Optional)
<i>is_firstentry_routemap</i>	(Optional)
<i>is_firstentry_acl</i>	(Optional)
<i>is_lastentry</i>	(Optional)
<i>is_firstentry_standby</i>	(Optional)
TABLE_summary	(Optional)
<i>service_name</i>	(Optional) service_name
<i>probe</i>	(Optional) probe
<i>lb_scheme</i>	(Optional) lb scheme
<i>interface</i>	(Optional) interface

<i>state</i>	(Optional) state
<i>buckets</i>	(Optional) buckets
<i>reason</i>	(Optional) inactive reason
<i>vrf_name</i>	(Optional) VRF-Name
<i>userACL</i>	(Optional) user access-list
<i>peer_status</i>	(Optional) peer status
TABLE_device	(Optional)
<i>device_grp</i>	(Optional) service device group
<i>dg_probe</i>	(Optional) probe type
<i>dg_probe_port</i>	(Optional) probe port
TABLE_route_map	(Optional)
<i>route_map</i>	(Optional) service route map
<i>interface</i>	(Optional) interface
<i>r_status</i>	(Optional) route map status
<i>int_track_id</i>	(Optional) interface track id
TABLE_vip	(Optional)
<i>vip_ip</i>	(Optional) vip ip
<i>vip_probe</i>	(Optional) vip protocol
<i>vip_port</i>	(Optional) vip port
<i>vip_dgname</i>	(Optional) vip device group
<i>ace_name</i>	(Optional) ace information
<i>ace_seq</i>	(Optional) ace information
<i>ace_ip</i>	(Optional) ace information
<i>ace_protocol</i>	(Optional) ace information
<i>ace_port</i>	(Optional) ace information
TABLE_vip_node	(Optional)
<i>vip_node</i>	(Optional) service node ip
<i>vip_nodev6</i>	(Optional) service node IPv6
<i>vip_config</i>	(Optional) node config

<i>vip_weight</i>	(Optional) node weight
<i>vip_status</i>	(Optional) node status
<i>vip_node_probe</i>	(Optional) node probe type
<i>vip_node_probe_port</i>	(Optional) node probe port
<i>vip_node_probe_ip</i>	(Optional) node probe ip
<i>vip_track_id</i>	(Optional) node track id
<i>vip_ip_sla_id</i>	(Optional) node ip sla id
TABLE_vip_standby	(Optional)
<i>vip_standby_ip</i>	(Optional) standby node ip
<i>vip_standby_ipv6</i>	(Optional) standby node ipv6
<i>vip_standby_config</i>	(Optional) standby node config
<i>vip_standby_weight</i>	(Optional) standby node weight
<i>vip_standby_status</i>	(Optional) standby node status
<i>vip_standby_probe</i>	(Optional) standby node probe type
<i>vip_standby_probe_port</i>	(Optional) standby node probe port
<i>vip_standby_probe_ip</i>	(Optional) standby node probe ip
<i>vip_standby_track_id</i>	(Optional) standby node track id
<i>vip_standby_sla_id</i>	(Optional) standby node sla id
TABLE_vip_acl	(Optional)
<i>vip_access_list</i>	(Optional) access list
TABLE_node	(Optional)
<i>node</i>	(Optional) service node ip
<i>nodev6</i>	(Optional) service node IPv6
<i>config</i>	(Optional) node config
<i>weight</i>	(Optional) node weight
<i>status</i>	(Optional) node status
<i>node_probe</i>	(Optional) node probe type
<i>node_probe_port</i>	(Optional) node probe port
<i>node_probe_ip</i>	(Optional) node probe ip

<i>track_id</i>	(Optional) node track id
<i>ip_sla_id</i>	(Optional) node ip sla id
TABLE_standby	(Optional)
<i>standby_ip</i>	(Optional) standby node ip
<i>standby_ipv6</i>	(Optional) standby node ipv6
<i>standby_config</i>	(Optional) standby node config
<i>standby_weight</i>	(Optional) standby node weight
<i>standby_status</i>	(Optional) standby node status
<i>standby_probe</i>	(Optional) standby node probe type
<i>standby_probe_port</i>	(Optional) standby node probe port
<i>standby_probe_ip</i>	(Optional) standby node probe ip
<i>standby_track_id</i>	(Optional) standby node track id
<i>standby_sla_id</i>	(Optional) standby node sla id
TABLE_acl	(Optional)
<i>access_list</i>	(Optional) access list

Command Mode

- /exec

show itd session device-group

```
show itd session device-group [ <name> ] [ __readonly__ <first_entry> [ TABLE_svc <node> ] ]
```

Syntax Description

show	Show running system information
itd	ITD service
session	ITD service session
device-group	ITD service session device-group
<i>name</i>	(Optional) ITD Service session name
<i>__readonly__</i>	(Optional) Read Only
<i>first_entry</i>	(Optional)
TABLE_svc	(Optional)
<i>node</i>	(Optional) node

Command Mode

- /exec

show itd statistics

```
show itd { <service_name> | all } [ src { <src-ip> | <src-IPv6> } | dst { <dst-ip> | <dst-IPv6> } ] statistics [
brief ] [ __readonly__ <is_firstentry_node> <is_firstentry_acl> <is_for_ace> [ TABLE_nice <service_name>
[ <vip> ] [ <ace_seq> ] [ <ace_ip> ] [ <vip_pkt> ] <dev_grp> <node> <node_pkt> [ <acl> ] [ <acl_pkt> ]
<mode> <percentage> ] ]
```

Syntax Description

show	Show running system information
itd	ITD service
statistics	ITD statistics
brief	(Optional) brief
__readonly__	(Optional) Read Only
<i>is_firstentry_node</i>	(Optional)
<i>is_firstentry_acl</i>	(Optional)
<i>is_for_ace</i>	(Optional)
TABLE_nice	(Optional)
<i>service_name</i>	service_name
all	All ITD services
src	(Optional) Statistics for src ip
<i>src-ip</i>	(Optional) Provide statistics for src ip
dst	(Optional) Statistics for dst ip
<i>dst-ip</i>	(Optional) Provide statistics for dst ip
<i>vip</i>	(Optional) service virtual ip
<i>ace_seq</i>	(Optional) service ACE name and sequence number
<i>ace_ip</i>	(Optional) service ACE ip/mask/prefix
<i>vip_pkt</i>	(Optional) virtual ip pkt_count
<i>dev_grp</i>	(Optional) device group
<i>node</i>	(Optional) service node ip
<i>node_pkt</i>	(Optional) node pkt count
<i>acl</i>	(Optional) access list

<i>acl_pkt</i>	(Optional) acl pkt count
<i>mode</i>	(Optional) Redirect mode
<i>percentage</i>	(Optional) Packet percentage

Command Mode

- /exec

show itd vrf

```
show itd vrf [ <name> ] [ __readonly__ <first_entry> [ TABLE_svc <service_name> <vrf_name> <vrf_id> ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>itd</code>	ITD service
<code>vrf</code>	ITD service vrf
<i>name</i>	(Optional) ITD Service VRF name
<code>__readonly__</code>	(Optional) Read Only
<i>first_entry</i>	(Optional)
<code>TABLE_svc</code>	(Optional)
<i>service_name</i>	(Optional) itd service name
<i>vrf_name</i>	(Optional) vrf name
<i>vrf_id</i>	(Optional) vrf id

Command Mode

- /exec

show itd vrf