



## P Show Commands

---

- [show param-list](#), on page 3
- [show password secure-mode](#), on page 4
- [show password strength-check](#), on page 5
- [show pending](#), on page 6
- [show plb](#), on page 7
- [show plb analytics](#), on page 11
- [show plb session device-group](#), on page 13
- [show plb vrf](#), on page 14
- [show pmap-int-br interface br](#), on page 15
- [show pmap-int](#), on page 16
- [show policy-map](#), on page 17
- [show policy-map interface control-plane](#), on page 21
- [show policy-map interface type psp](#), on page 24
- [show policy-map system](#), on page 26
- [show policy-map type control-plane](#), on page 30
- [show policy-map type network-qos](#), on page 33
- [show policy-map type psp](#), on page 35
- [show port-channel load-balance](#), on page 37
- [show port-profile](#), on page 38
- [show port-profile brief](#), on page 40
- [show port-profile expand-interface](#), on page 41
- [show port-profile sync-status](#), on page 42
- [show port-profile usage](#), on page 43
- [show port-security](#), on page 44
- [show port-security address](#), on page 45
- [show port-security address blocked](#), on page 46
- [show port-security address interface](#), on page 47
- [show port-security address nvram](#), on page 48
- [show port-security detail interface](#), on page 49
- [show port-security interface](#), on page 50
- [show port-security multivlan address](#), on page 51
- [show port-security secure address](#), on page 52
- [show port-security state](#), on page 53

- [show port-security traps enable](#), on page 54
- [show power inline](#), on page 55
- [show power inline](#), on page 56
- [show power inline police](#), on page 57
- [show power inline priority](#), on page 58
- [show privilege](#), on page 59
- [show processes](#), on page 60
- [show processes cpu](#), on page 61
- [show processes cpu history](#), on page 62
- [show processes cpu history data](#), on page 63
- [show processes log](#), on page 64
- [show processes log details](#), on page 65
- [show processes log pid](#), on page 66
- [show processes log vdc-all](#), on page 67
- [show processes memory](#), on page 68
- [show processes memory clis](#), on page 69
- [show processes memory physical](#), on page 70
- [show processes memory shared](#), on page 71
- [show processes vdc](#), on page 74
- [show processes vdc cpu](#), on page 75
- [show processes vdc log](#), on page 76
- [show processes vdc log details](#), on page 77
- [show processes vdc log pid](#), on page 78
- [show processes vdc memory](#), on page 79
- [show processes version](#), on page 80
- [show pss debug](#), on page 81
- [show ptp brief](#), on page 82
- [show ptp clock](#), on page 83
- [show ptp clock foreign-masters record](#), on page 84
- [show ptp corrections](#), on page 85
- [show ptp cost](#), on page 86
- [show ptp counters interface](#), on page 87
- [show ptp domain data](#), on page 88
- [show ptp interface domain](#), on page 89
- [show ptp packet-trace](#), on page 90
- [show ptp parent](#), on page 91
- [show ptp port interface](#), on page 92
- [show ptp time-property](#), on page 93

# show param-list

```
show param-list [ param-list-name <plistname> ] [ show-instance ] [ __readonly__ <param_list_header_flag>
<param_list_name> <param_list_var> <param_list_type> <param_instance_header_flag>
<param_instance_name> <param_instance_var> <param_instance_val> ]
```

## Syntax Description

show	Show running system information
param-list	Show param-list
param-list-name	(Optional) param list name
<i>plistname</i>	(Optional) Enter the name of the param-list
show-instance	(Optional) show instances for the param list
<i>__readonly__</i>	(Optional)
<i>param_list_header_flag</i>	(Optional)
<i>param_list_name</i>	(Optional)
<i>param_list_var</i>	(Optional)
<i>param_list_type</i>	(Optional)
<i>param_instance_header_flag</i>	(Optional)
<i>param_instance_name</i>	(Optional)
<i>param_instance_var</i>	(Optional)
<i>param_instance_val</i>	(Optional)

## Command Mode

- /exec

# show password secure-mode

```
show password secure-mode [ __readonly__ { secure_mode <secure_mode_status> } ]
```

## Syntax Description

show	Show running system information
password	Password for the user
secure-mode	secure mode for changing passwords
__readonly__	(Optional)
secure_mode	(Optional) run time status about xml
<i>secure_mode_status</i>	(Optional) Run time status about secure mode

## Command Mode

- /exec

# show password strength-check

```
show password strength-check [ __readonly__ { operation_status <o_status> } ]
```

## Syntax Description

show	Show running system information
password	Password for the user
strength-check	Strength check of password
__readonly__	(Optional)
operation_status	(Optional) run-time information about password strength-check
<i>o_status</i>	(Optional) operational status of password strength check

## Command Mode

- /exec

# show pending

show [ pending ]

## Syntax Description

show	Display region configurations
pending	(Optional) Display the new mst configuration to be applied

## Command Mode

- /exec/configure/spanning-tree/mst/configuration

# show plb

```
show plb [ service <service-name> ] [ brief ] [ __readonly__ <is_firstentry> <is_detail> <is_active>
<is_firstentry_routemap> <is_firstentry_standby> <is_firstentry_acl> <is_lastentry> [ TABLE_summary
<service_name> <state> [ <reason> ] <lb_scheme> [ <interface> ] <buckets> [ <vrf_name> ] [ <excl_acl> ]
[ <src_interface> ] [ TABLE_device <device_grp> <dg_probe> <dg_probe_port> ] [ TABLE_route_map [
<route_map> ] <interface> <r_status> ] [ TABLE_vip [ <vip_ip> ] [ <vip_probe> ] [ <vip_port> ] [
<vip_dgname> ] [ <ace_name> ] [ <ace_seq> ] [ <ace_ip> ] [ <ace_protocol> ] [ <ace_port> ] [
TABLE_vip_node [ <vip_node> ] [ <vip_nodev6> ] <vip_config> <vip_weight> <vip_node_probe>
<vip_node_probe_port> <vip_node_probe_ip> <vip_status> <vip_track_id> <vip_ip_sla_id> [
TABLE_vip_standby [ <vip_standby_ip> ] [ <vip_standby_ipv6> ] <vip_standby_config>
<vip_standby_weight> <vip_standby_probe> <vip_standby_probe_port> <vip_standby_probe_ip>
<vip_standby_status> <vip_standby_track_id> <vip_standby_sla_id> ] [ TABLE_vip_acl [ <vip_access_list>
] ] ] [ TABLE_node [ <node> ] [ <nodev6> ] <config> <weight> <node_probe> <node_probe_port>
<node_probe_ip> <status> <track_id> <ip_sla_id> [ TABLE_standby [ <standby_ip> ] [ <standby_ipv6> ]
<standby_config> <standby_weight> <standby_probe> <standby_probe_port> <standby_probe_ip>
<standby_status> <standby_track_id> <standby_sla_id> ] [ TABLE_acl [ <access_list> ] ] ] ] ]
```

## Syntax Description

show	Show running system information
plb	Display PLB service details
service	(Optional) PLB details for specific service
<i>service-name</i>	(Optional) Specify PLB service name
brief	(Optional) Display PLB service in brief
<u>__readonly__</u>	(Optional) Read Only
<i>is_firstentry</i>	(Optional)
<i>is_detail</i>	(Optional)
<i>is_active</i>	(Optional)
<i>is_firstentry_routemap</i>	(Optional)
<i>is_firstentry_acl</i>	(Optional)
<i>is_lastentry</i>	(Optional)
<i>is_firstentry_standby</i>	(Optional)
TABLE_summary	(Optional)
<i>service_name</i>	(Optional) PLB service name
<i>lb_scheme</i>	(Optional) lb scheme
<i>interface</i>	(Optional) interface

<i>src_interface</i>	(Optional) source interface for probe
<i>state</i>	(Optional) state
<i>buckets</i>	(Optional) buckets
<i>reason</i>	(Optional) inactive reason
<i>vrf_name</i>	(Optional) VRF-Name
<i>excl_acl</i>	(Optional) exclude access-list
TABLE_device	(Optional)
<i>device_grp</i>	(Optional) service device group
<i>dg_probe</i>	(Optional) probe type
<i>dg_probe_port</i>	(Optional) probe port
TABLE_route_map	(Optional)
<i>route_map</i>	(Optional) service route map
<i>interface</i>	(Optional) interface
<i>r_status</i>	(Optional) route map status
TABLE_vip	(Optional)
<i>vip_ip</i>	(Optional) vip ip
<i>vip_probe</i>	(Optional) vip protocol
<i>vip_port</i>	(Optional) vip port
<i>vip_dgname</i>	(Optional) vip device group
<i>ace_name</i>	(Optional) ace information
<i>ace_seq</i>	(Optional) ace information
<i>ace_ip</i>	(Optional) ace information
<i>ace_protocol</i>	(Optional) ace information
<i>ace_port</i>	(Optional) ace information
TABLE_vip_node	(Optional)
<i>vip_node</i>	(Optional) service node ip
<i>vip_nodev6</i>	(Optional) service node IPv6
<i>vip_config</i>	(Optional) node config
<i>vip_weight</i>	(Optional) node weight



<i>vip_status</i>	(Optional) node status
<i>vip_node_probe</i>	(Optional) node probe type
<i>vip_node_probe_port</i>	(Optional) node probe port
<i>vip_node_probe_ip</i>	(Optional) node probe ip
<i>vip_track_id</i>	(Optional) node track id
<i>vip_ip_sla_id</i>	(Optional) node ip sla id
TABLE_vip_standby	(Optional)
<i>vip_standby_ip</i>	(Optional) standby node ip
<i>vip_standby_ipv6</i>	(Optional) standby node ipv6
<i>vip_standby_config</i>	(Optional) standby node config
<i>vip_standby_weight</i>	(Optional) standby node weight
<i>vip_standby_status</i>	(Optional) standby node status
<i>vip_standby_probe</i>	(Optional) standby node probe type
<i>vip_standby_probe_port</i>	(Optional) standby node probe port
<i>vip_standby_probe_ip</i>	(Optional) standby node probe ip
<i>vip_standby_track_id</i>	(Optional) standby node track id
<i>vip_standby_sla_id</i>	(Optional) standby node sla id
TABLE_vip_acl	(Optional)
<i>vip_access_list</i>	(Optional) access list
TABLE_node	(Optional)
<i>node</i>	(Optional) service node ip
<i>nodev6</i>	(Optional) service node IPv6
<i>config</i>	(Optional) node config
<i>weight</i>	(Optional) node weight
<i>status</i>	(Optional) node status
<i>node_probe</i>	(Optional) node probe type
<i>node_probe_port</i>	(Optional) node probe port
<i>node_probe_ip</i>	(Optional) node probe ip
<i>track_id</i>	(Optional) node track id

<i>ip_sla_id</i>	(Optional) node ip sla id
TABLE_standby	(Optional)
<i>standby_ip</i>	(Optional) standby node ip
<i>standby_ipv6</i>	(Optional) standby node ipv6
<i>standby_config</i>	(Optional) standby node config
<i>standby_weight</i>	(Optional) standby node weight
<i>standby_status</i>	(Optional) standby node status
<i>standby_probe</i>	(Optional) standby node probe type
<i>standby_probe_port</i>	(Optional) standby node probe port
<i>standby_probe_ip</i>	(Optional) standby node probe ip
<i>standby_track_id</i>	(Optional) standby node track id
<i>standby_sla_id</i>	(Optional) standby node sla id
TABLE_acl	(Optional)
<i>access_list</i>	(Optional) access list

**Command Mode**

- /exec

## show plb analytics

```
show plb analytics [ service <service-name> ] [ src { <sip> | <sipv6> } | node { <nip> | <nipv6> } | vip {
<vip> | <vipv6> } | device-group <group-name> ] [ brief ] [ __readonly__ <plbshowinfo-stats-svc-hdr> [
TABLE_stats_svc <plbshowinfo-stats-service_name> <plbshowinfo-stats-dev-grp> <plbshowinfo-stats-vip>
<plbshowinfo-stats-vip-pkts> <plbshowinfo-stats-vip-pkts-percentage> [ <plbshowinfo-stats-ace-seq> ] [
<plbshowinfo-stats-ace-ip> ] <plbshowinfo-stats-bkt-hdr> [ TABLE_stats_bkt <plbshowinfo-stats-acl> [
<plbshowinfo-stats-oper-node> ] <plbshowinfo-stats-node-mode> <plbshowinfo-stats-orig-node>
<plbshowinfo-stats-node-pkts> <plbshowinfo-stats-node-pkts-percentage> [ <plbshowinfo-stats-acl-pkts> ]
[ <plbshowinfo-for-ace> ] ] ] <plb-show-end> [ <plb-true-end> ] ]
```

### Syntax Description

show	Show running system information
plb	PLB service
analytics	PLB analytics information
service	(Optional) PLB analytics for specific service
<i>service-name</i>	(Optional) Specify plb service name
src	(Optional) Analytics information for source (bucket) ip
node	(Optional) Analytics information for destination device group node/server ip
vip	(Optional) Analytics information for virtual ip
device-group	(Optional) Analytics information of specified device group
<i>group-name</i>	(Optional) Specify device group name
<i>sip</i>	(Optional) Specify source ipv4 address
<i>nip</i>	(Optional) Specify destination ipv4 address
<i>vip</i>	(Optional) Specify virtual ipv4 address
brief	(Optional) Brief analytics information
<i>__readonly__</i>	(Optional) Read Only
<i>plbshowinfo-stats-svc-hdr</i>	(Optional) PLB analytics service header
TABLE_stats_svc	(Optional) plb stats service
<i>plbshowinfo-stats-service_name</i>	(Optional) PLB analytics service name
<i>plbshowinfo-stats-dev-grp</i>	(Optional) PLB analytics device group
<i>plbshowinfo-stats-vip</i>	(Optional) PLB analytics VIP IP
<i>plbshowinfo-stats-vip-pkts</i>	(Optional) PLB analytics virtual ip pkt_count

<i>plbshowinfo-stats-vip-pkts-percentage</i>	(Optional) PLB analytics virtual ip pkts percentage
<i>plbshowinfo-stats-ace-seq</i>	(Optional) PLB analytics ACE name and sequence number
<i>plbshowinfo-stats-ace-ip</i>	(Optional) PLB analytics ACE ip/mask/prefix
<i>plbshowinfo-stats-bkt-hdr</i>	(Optional) PLB analytics bucket header
TABLE_stats_bkt	(Optional) plb stats bucket
<i>plbshowinfo-stats-acl</i>	(Optional) PLB analytics bucket/acl name
<i>plbshowinfo-stats-oper-node</i>	(Optional) PLB analytics Operational node ip
<i>plbshowinfo-stats-node-mode</i>	(Optional) PLB analytics node mode
<i>plbshowinfo-stats-orig-node</i>	(Optional) PLB analytics Original node ip
<i>plbshowinfo-stats-node-pkts</i>	(Optional) PLB analytics node pkts count
<i>plbshowinfo-stats-node-pkts-percentage</i>	(Optional) PLB analytics node pkts percentage
<i>plbshowinfo-stats-acl-pkts</i>	(Optional) PLB analytics acl pkts
<i>plbshowinfo-for-ace</i>	(Optional) PLB analytics for ACE
<i>plb-show-end</i>	(Optional) Show plb end marker
<i>plb-true-end</i>	(Optional) show plb true end marker

**Command Mode**

- /exec

# show plb session device-group

```
show plb session device-group [ <group-name> ] [ __readonly__ <first_entry> [ TABLE_svc <node> ] ]
```

## Syntax Description

show	Show running system information
plb	Display PLB service details
session	PLB service session
device-group	Session device-group
<i>group-name</i>	(Optional) Device-group name
<i>__readonly__</i>	(Optional) Read Only
<i>first_entry</i>	(Optional)
TABLE_svc	(Optional)
<i>node</i>	(Optional) node

## Command Mode

- /exec

# show plb vrf

```
show plb vrf [ <vrf-name> ] [ __readonly__ <plbshowinfo-vrf-hdr> { TABLE_svc
<plbshowinfo-vrf-service_name> <plbshowinfo-vrf-name> <plbshowinfo-vrf-id> } <plb-show-end> [
<plb-true-end> ] ]
```

## Syntax Description

show	Show running system information
plb	PLB service
vrf	PLB service vrf
<i>vrf-name</i>	(Optional) VRF name
<i>__readonly__</i>	(Optional) Read Only
<i>plbshowinfo-vrf-hdr</i>	(Optional) PLB info vrf header
TABLE_svc	(Optional) PLB Service VRF details
<i>plbshowinfo-vrf-service_name</i>	(Optional) PLB service name
<i>plbshowinfo-vrf-name</i>	(Optional) PLB vrf name
<i>plbshowinfo-vrf-id</i>	(Optional) PLB vrf id
<i>plb-show-end</i>	(Optional) Show plb end marker
<i>plb-true-end</i>	(Optional) show plb true end marker

## Command Mode

- /exec

## show pmap-int-br interface br

```
show pmap-int-br interface br [ __readonly__ { [ TABLE_ifvlanstr <if-vlan-str> <if-status> [ <in-pmap-qos>
] [ <out-pmap-qos> ] [ <in-pmap-que> ] [ <out-pmap-que> ] ] } ]
```

### Syntax Description

show	Show running system information
pmap-int-br	Show policy maps
interface	Show service policy on interface
br	Brief report of all policies attached to interfaces
TABLE_ifvlanstr	(Optional) all interfaces xml sessions
<i>if-vlan-str</i>	(Optional) ifindex or vlan id: xml key
<i>__readonly__</i>	(Optional)
<i>if-status</i>	(Optional) Interface/vlan status [active/inactive]: xml key
<i>in-pmap-qos</i>	(Optional) Input QoS Policy-map name: xml key
<i>out-pmap-qos</i>	(Optional) output QoS Policy-map name: xml key
<i>in-pmap-que</i>	(Optional) Input Que Policy-map name: xml key
<i>out-pmap-que</i>	(Optional) Output Que Policy-map name: xml key

### Command Mode

- /exec

# show pmap-int

show pmap-int { interface [ <iface-list> ] [ input | output ] [ type <qos-or-q> ] [ detail ] |

## Syntax Description

show	Show running system information
pmap-int	Show policy maps
interface	Show service policy on interface
<i>iface-list</i>	(Optional) List of Interface
input	(Optional) Input Service policy
output	(Optional) Output Service policy
type	(Optional) Type of policy
<i>qos-or-q</i>	(Optional)
detail	(Optional) Detailed QoS or Queuing statistics

## Command Mode

- /exec



# show policy-map

```
show policy-map [ { [ type qos ] [ <pmap-name-qos> ] } | { type queuing [ <pmap-name-que> ] } ] [
__readonly__ { [ <display-all> ] [ TABLE_pmap <pmap-key> [ <type-spec> ] [ <yqos-or-q> ] [ <options>
] <pmap-name-out> [ <desc> ] [ TABLE_cmap <cmap-key> [ <type-cmap-spec> ] [ <xqos-or-q> ] [
<cmap-name> ] [ TABLE_action <action-key> [ <serv-pol-type> ] [ <serv-pol-name> ] [ <inner> ] [
<dlb-disable> ] [ <cos> ] [ <exp-val-imposition> ] [ <exp-val-topmost> ] [ <dscp-enum> ] [ <dscp> ] [
<prec-enum> ] [ <prec> ] [ <disc-class> ] [ <qos-group> ] [ <tmap-from> ] [ <tmap-to> ] [ <tmap-name> ] [
<avg-rate-type> ] [ <rate-units> ] [ <shape-rate> ] [ <min-rate-type> ] [ <min-rate-units> ] [ <shape-min-rate>
] [ <max-rate-type> ] [ <max-rate-units> ] [ <shape-max-rate> ] [ <rise-threshold-units> ] [
<fall-threshold-units> ] [ <prio-level> ] [ <qlim-param-type> ] [ <qlim-param-val> ] [ <ooo> ] [ <size-units>
] [ <qlim-size> ] [ <qlim-enum-spec> ] [ <rdet-agg> ] [ <rdet-mode> ] [ TABLE_rdet <rdet-key> [ <rdet-values>
] [ <rdet-min-thresh> ] [ <rdet-size-units> ] [ <rdet-max-thresh> ] [ <rdet-drop-prob> ] [ <rdet-weight> ] [
<rdet-cap-average> ] [ <rdet-ecn> ] [ <rdet-burst-opt> ] [ <rdet-mesh-opt> ] ] [ <rdet-nonecn-mode> ] [
TABLE_rdet_nonecn <rdet-nonecn-key> [ <rdet-nonecn-min-thresh> ] [ <rdet-nonecn-size-units> ] [
<rdet-nonecn-max-thresh> ] [ <rdet-nonecn-drop-prob> ] ] [ <afd-mode> ] [ TABLE_afd <afd-key> [
<afd-values> ] [ <afd-queue-desired> ] [ <afd-size-units> ] [ <afd-ecn> ] ] [ <pause> <size-in-bytes>
<xoff-bytes> <xon-bytes> ] [ <priority-group-number> ] [ <bw-units> ] [ <bw-rate> ] [ <rem-bw-units> ] [
<rem-bw-rate> ] [ <agg-policer-name> ] [ <cir-spec> ] [ <bc-spec> ] [ <be-spec> ] [ <cir-rate-units> ] [ <cir>
] [ <bc-size-units> ] [ <bc> ] [ <pir-rate-units> ] [ <pir> ] [ <be-size-units> ] [ <be> ] [ <cnf-col-cmap> ] [
<exc-col-cmap> ] [ TABLE_police <police-key> [ <cnf-act> ] [ <exc-act> ] [ <vio-act> ] [ <set-type> ] [
<enum-spec> ] [ <set-val> ] [ <ptmap-from> ] [ <ptmap-to> ] [ <ptmap-name> ] ] [ <burst-detect-enable>
] ] ] ] }
```

## Syntax Description

show	Show running system information
policy-map	Show policy maps
type	(Optional) Type of the policy-map
qos	(Optional) type qos
queuing	(Optional) type queuing
<i>pmap-name-qos</i>	(Optional) policy map name (type qos)
<i>pmap-name-que</i>	(Optional) policy map name (type queuing)
<i>__readonly__</i>	(Optional)
<i>display-all</i>	(Optional) Display all kinds of class-maps
TABLE_pmap	(Optional) all pmap xml sessions
<i>pmap-key</i>	(Optional) Policy-map name: xml key
TABLE_rdet	(Optional) all WRED sessions
TABLE_rdet_nonecn	(Optional) all WRED non ECN sessions
TABLE_afd	(Optional) all AFD sessions

TABLE_police	(Optional) all police actions
<i>police-key</i>	(Optional) police actions count: xml key
TABLE_cmap	(Optional) all cmap xml sessions
<i>cmap-key</i>	(Optional) Class-map name: xml key
TABLE_action	(Optional) all actions
<i>action-key</i>	(Optional) Actions count: xml key
<i>yqos-or-q</i>	(Optional)
<i>options</i>	(Optional) match-first option
<i>pmap-name-out</i>	(Optional) Policy-map name
<i>desc</i>	(Optional) Description string
<i>cmap-name</i>	(Optional) Class-map name
<i>xqos-or-q</i>	(Optional)
<i>serv-pol-type</i>	(Optional) Type of service policy referred to
<i>serv-pol-name</i>	(Optional) Name of policy-map referred to within this policy-map
<i>type-spec</i>	(Optional) Type of policy-map specified or not
<i>type-cmap-spec</i>	(Optional) Type of class-map specified or not
<i>inner</i>	(Optional) Specifies if tunnel or inner keywords are mentioned
<i>dlb-disable</i>	(Optional) Disable Dynamic Load Balancing
<i>cos</i>	(Optional) IEEE 802.1Q Class of Service value
<i>exp-val-imposition</i>	(Optional) MPLS EXP value of type imposition
<i>exp-val-topmost</i>	(Optional) MPLS EXP value of type topmost
<i>dscp</i>	(Optional) DSCP in IP(v4) and IPv6 packets
<i>dscp-enum</i>	(Optional)
<i>prec</i>	(Optional) Precedence in IP(v4) and IPv6 packets
<i>prec-enum</i>	(Optional)
<i>disc-class</i>	(Optional) Discard class
<i>qos-group</i>	(Optional) Qos-group
<i>tmap-from</i>	(Optional)
<i>tmap-to</i>	(Optional)

<i>tmap-name</i>	(Optional) Table map name
<i>ptmap-from</i>	(Optional)
<i>ptmap-to</i>	(Optional)
<i>ptmap-name</i>	(Optional) Table map name
<i>avg-rate-type</i>	(Optional) Specifies if average shape rate is specified
<i>rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>min-rate-type</i>	(Optional) Specifies if minimum shape rate is specified
<i>min-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>max-rate-type</i>	(Optional) Specifies if maximum shape rate is specified
<i>max-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>cir-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us, pps
<i>pir-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us, pps
<i>prio-level</i>	(Optional) Priority if specified
<i>qlim-param-type</i>	(Optional) Type of parameter for qlim - cos/prec/dscp/disc class/qosgrp
<i>qlim-param-val</i>	(Optional) Parameter value for qlimit
<i>qlim-size</i>	(Optional) Queue size for qlimit
<i>size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>rdet-size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>rdet-nonecn-size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>afd-size-units</i>	(Optional) Units of queue size - bytes/kbytes/mbytes
<i>bc-size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>be-size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>qlim-enum-spec</i>	(Optional) Whether qlimit parameter is specified in enum or not
<i>rdet-mode</i>	(Optional) Random-detect mode
<i>rdet-nonecn-mode</i>	(Optional) Random-detect non-ecn mode
<i>rdet-agg</i>	(Optional) Are the params for aggregate flow
<i>rdet-values</i>	(Optional) List of class-of-service values for random-detect
<i>rdet-drop-prob</i>	(Optional) Random-detect drop probability
<i>rdet-weight</i>	(Optional) Random-detect queue length weight

<i>rdet-cap-average</i>	(Optional) Random-detect cap-average
<i>rdet-ecn</i>	(Optional) Random-detect ECN
<i>rdet-burst-opt</i>	(Optional) Random-detect burst optimized
<i>rdet-mesh-opt</i>	(Optional) Random-detect mesh optimized
<i>rdet-nonecn-drop-prob</i>	(Optional) Random-detect non-ecn drop probability
<i>afd-mode</i>	(Optional) AFD mode
<i>afd-values</i>	(Optional) List of class-of-service values for AFD
<i>afd-ecn</i>	(Optional) AFD ECN
<i>pause</i>	(Optional) Pause value
<i>priority-group-number</i>	(Optional) Priority group value
<i>bw-units</i>	(Optional) Bandwidth units
<i>rem-bw-units</i>	(Optional) Remaining bandwidth units
<i>rem-bw-rate</i>	(Optional) Remaining bandwidth rate
<i>agg-policer-name</i>	(Optional) Aggregate policer name
<i>cir-spec</i>	(Optional) Is CIR keyword specified
<i>bc-spec</i>	(Optional) Is Committed Burst keyword specified
<i>be-spec</i>	(Optional) Is Extended Burst keyword specified
<i>cnf-col-cmap</i>	(Optional) Conforming color class-map name
<i>exc-col-cmap</i>	(Optional) Exceeding color class-map name
<i>enum-spec</i>	(Optional) Is DSCP or PREC enum value specified
<i>cnf-act</i>	(Optional) Conform action (Police)
<i>exc-act</i>	(Optional) Exceed action (Police)
<i>vio-act</i>	(Optional) Violate action (Police)
<i>set-type</i>	(Optional) Type of set in police action
<i>set-val</i>	(Optional) Value of set type in police action
<i>ooo</i>	(Optional) Out-of-Order
<i>burst-detect-enable</i>	(Optional) Burst detect feature is enabled

### Command Mode

- /exec

# show policy-map interface control-plane

```
show policy-map interface control-plane { [ module <slot-no-in> [ class <cmmap-name> ] ] [ class <cmmap-name>
[ module <slot-no-in> ] ] } [ __readonly__ [ <scale-factor-cmd> ] <pmap-name> [ TABLE_cmap <cmmap-key>
<cmmap-name-out> <opt_any_or_all> [ TABLE_match <match-key> { [ access_grp <acc_grp_name> ] [
redirect <opt_match_redirect> ] [ exception <opt_match_except> ] [ protocol <opt_match_protocol> ] ] + ] [
<class-off-rate> <class-drop-rate> <class-pkts> <class-bytes> ] [ [ <set_vld_flg> ] { { cos [ inner ] <cos-val>
} | { dscp [ tunnel ] <dscp-val> } | { precedence [ tunnel1 ] <prec-val> } } ] [ <threshold> <level> ] [ [
<policer_show_flags> ] [ <cir> <opt_kbps_mbps_gbps_pps_cir> ] [ { percent <cir-perc> } ] [ <bc>
<opt_kbytes_mbytes_gbytes_be> ] [ <pir> <opt_kbps_mbps_gbps_pps_pir> ] [ { percent1 <pir-perc> } ] [
<be> <opt_kbytes_mbytes_gbytes_be> ] ] [ TABLE_slot { <slot-no-out> { [ [ <conform-pkts> ]
<conform-bytes> ] [ [ <opt_drop_transmit_conform> ] | { set-cos-transmit <set-cos-val> } | { set-dscp-transmit
<set-dscp-val> } | { set-prec-transmit <set-prec-val> } ] [ [ [ <exceed-pkts> ] <exceed-bytes> ] { {
<opt_drop_transmit_exceed> } | { set dscp1 dscp2 table cir-markdown-map } } } ] [ [ [ <violate-pkts> ]
<violate-bytes> ] { { <opt_drop_transmit_violate> } | { set1 dscp3 dscp4 table1 pir-markdown-map } } } }
} ] ] ]
```

### Syntax Description

show	Show running system information
policy-map	Show policy maps
interface	Show service policy on interface
control-plane	command is for copp policy
module	(Optional) module number for statistics
class	(Optional) class-name name
<i>cmmap-name</i>	(Optional) Name of the class-map
<i>pmap-name</i>	(Optional) Name of the Policy-map
<i>__readonly__</i>	(Optional)
<i>scale-factor-cmd</i>	(Optional) Scale factor command
TABLE_cmap	(Optional) all cmap xml sessions
<i>cmmap-key</i>	(Optional) Class-map key : XML output
<i>cmmap-name-out</i>	(Optional) Name of the output class-map
<i>opt_any_or_all</i>	(Optional) Enter match-any or match-all
TABLE_match	(Optional) all match xml sessions
<i>match-key</i>	(Optional) Match key : XML output
access_grp	(Optional)
<i>acc_grp_name</i>	(Optional)

redirect	(Optional)
<i>opt_match_redirect</i>	(Optional) Match criteria for redirected packets
exception	(Optional)
<i>opt_match_except</i>	(Optional) Match criteria for exception packets
protocol	(Optional)
<i>opt_match_protocol</i>	(Optional) Match criteria for protocol packets
<i>set_vld_flg</i>	(Optional) Set valid flag
cos	(Optional)
inner	(Optional)
<i>cos-val</i>	(Optional) Set cos val
dscp	(Optional)
tunnel	(Optional)
<i>dscp-val</i>	(Optional) Set dscp val
precedence	(Optional)
tunnel1	(Optional)
<i>prec-val</i>	(Optional) Set prec val
<i>policer_show_flags</i>	(Optional) Policer show flags
<i>level</i>	(Optional) syslog severity level
<i>opt_kbps_mbps_gbps_pps_cir</i>	(Optional) Units
percent	(Optional)
<i>opt_kbps_mbps_gbps_pps_pir</i>	(Optional) Units
percent1	(Optional)
<i>opt_kbytes_mbytes_gbytes_bc</i>	(Optional) Units
<i>opt_kbytes_mbytes_gbytes_be</i>	(Optional) Units
TABLE_slot	(Optional) all slot-num : XML output
<i>slot-no-in</i>	(Optional) input slot no
<i>slot-no-out</i>	(Optional) output slot no
<i>opt_drop_transmit_conform</i>	(Optional) Set the action
set-cos-transmit	(Optional)

<i>set-cos-val</i>	(Optional) Conform action cos val
set-dscp-transmit	(Optional)
<i>set-dscp-val</i>	(Optional) Conform action dscp val
set-prec-transmit	(Optional)
<i>set-prec-val</i>	(Optional) Conform action prec val
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional)
dscp1	(Optional)
dscp2	(Optional)
table	(Optional)
cir-markdown-map	(Optional)
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional)
dscp3	(Optional)
dscp4	(Optional)
table1	(Optional)
pir-markdown-map	(Optional)

**Command Mode**

- /exec

## show policy-map interface type psp

```
show policy-map interface { [ <ifnum> ] } type psp { [ <pmap-name> [ client <clienttype> <clientID> ] ] | [
handle <ppf_id> ] } { [ class-map-list { [ <cmap-name-plc> + ] | [ class-map-handle <ppf_id1> + ] } ] } [
__readonly__ { [ <number-of-classes> ] [ <display-all> ] [ TABLE_pmap <pmap-key> <id> <pmap-name-out>
[ <desc> ] [ TABLE_cmap <cmap-key> [ <cmap-name-out> ] [ TABLE_interface <interface> <byte-count>
] ] ] }
```

### Syntax Description

show	Show running system information
policy-map	Show policy maps
interface	Show stats for interface
<i>ifnum</i>	(Optional) Interface type and number
type	Type of the policy-map
psp	type psp
<i>pmap-name</i>	(Optional) Policy-map name
client	(Optional) set client type
<i>clienttype</i>	(Optional) cli/onep
<i>clientID</i>	(Optional) client appID
handle	(Optional) Handle
<i>ppf_id</i>	(Optional) PPF ID
class-map-list	(Optional) Class-map list
<i>cmap-name-plc</i>	(Optional) Class-map name
class-map-handle	(Optional) Class-map Handle/s
<i>ppf_id1</i>	(Optional) PPF ID
__readonly__	(Optional)
<i>display-all</i>	(Optional) Display all kinds of policymaps
<i>number-of-classes</i>	(Optional) Total number of classes for which stats are returned
TABLE_pmap	(Optional) all pmap xml sessions
<i>id</i>	(Optional) Policy-map ID
<i>pmap-key</i>	(Optional) Policy-map name: xml key
<i>pmap-name-out</i>	(Optional) Policy-map name



<i>desc</i>	(Optional) Description string
TABLE_cmap	(Optional) all cmap xml sessions
<i>cmap-key</i>	(Optional) Class-map name: xml key
<i>cmap-name-out</i>	(Optional) Class-map name
TABLE_interface	(Optional) all interface xml sessions
<i>interface</i>	(Optional) Interface type and number
<i>byte-count</i>	(Optional) Byte Count Statistic

**Command Mode**

- /exec

## show policy-map system

```
show policy-map system [ type { network-qos | qos [ input2 ] | queuing [ input | output ] } ] [ __readonly__
{ [ <display-all> ] [ <desc> ] [ <xpmap-name> ] [ <xcmap-name> ] [ <cos-list> ] [ <qos-group-list> ] [
<protocol> ] [ <timeout> ] [ <pause> <size-in-bytes> <xoff-bytes> <xon-bytes> ] [ <pfc-cos-list>
<pfc_rx_only> ] [ <cc> ] [ <thresh-units> ] [ <min-thresh> ] [ <max-thresh> ] [ <drop-prob> ] [ <iod> ] [
<mtu> ] [ <set-cos> ] [ <dpp> ] [ <dctcp-threshold> ] [ <queue-limit> ] [ <stat-en-dis-enum> ] [ TABLE_pmap
<pmap-key> <pmap-inner-outer> <in-or-out> <yqos-or-q> [ <options> ] <pmap-name> [ <stat-status-enum>
] [ TABLE_cmap <cmap-key> [ <xqos-or-q> ] <match-opts> <cmap-name> [ TABLE_match <match-key>
[ <not> ] [ <inner> ] [ <cos-list> ] [ <match-cmap-xqos-or-q> ] [ <match-cmap-opts> ] [ <match-cmap-name>
] ] [ TABLE_action <action-key> [ <set-inner> ] [ <cos> ] [ <serv-pol-type> ] [ <serv-pol-name> ] [
<serv-pol-return-inout> ] [ <rate-units> ] [ <shape-rate> ] [ <min-rate-type> ] [ <min-rate-units> ] [
<shape-min-rate> ] [ <max-rate-type> ] [ <max-rate-units> ] [ <shape-max-rate> ] [ <prio-level> ] [
<qlim-param-type> ] [ <qlim-param-val> ] [ <size-units> ] [ <qlim-size> ] [ <qlim-enum-spec> ] [ <bw-units>
] [ <bw-rate> ] [ <rem-bw-units> ] [ <rem-bw-rate> ] [ <rise-threshold-units> ] [ <fall-threshold-units> ] [
TABLE_rdet <rdet-key> [ <rdet-values> ] [ <rdet-min-thresh> ] [ <rdet-size-units> ] [ <rdet-max-thresh> ]
[ <rdet-drop-prob> ] [ <rdet-weight> ] [ <rdet-ecn> ] [ <rdet-cap-average> ] [ <rdet-burst-opt> ] [
<rdet-mesh-opt> ] ] [ TABLE_afd <afd-key> [ <afd-values> ] [ <afd-queue-desired> ] [ <afd-size-units> ] [
<afd-ecn> ] ] [ <pause> <size-in-bytes> <xoff-bytes> <xon-bytes> ] ] ] ] }
```

### Syntax Description

show	Show running system information
policy-map	Show policy maps
type	(Optional) Type of the policy-map
system	Active policy in the system
network-qos	(Optional) type network-qos
qos	(Optional) type qos
input2	(Optional) input policy
queuing	(Optional) type queuing
input	(Optional) input policy
output	(Optional) output policy
__readonly__	(Optional)
<i>display-all</i>	(Optional) Display all network-qos policy-maps
<i>xpmap-name</i>	(Optional) Policy-map name
<i>desc</i>	(Optional) Description string
<i>xcmap-name</i>	(Optional) Class-map name
<i>thresh-units</i>	(Optional) Units of threshold - pkts/bytes/kbytes/mbytes/ms/us/perc

<i>drop-prob</i>	(Optional) Drop Probability at Maximum Threshold value
<i>pause</i>	(Optional) Pause value
<i>pfc-cos-list</i>	(Optional) List of class-of-service values
<i>pfc_rx_only</i>	(Optional) Pause receive only mode enabled
<i>timeout</i>	(Optional) timeout value
<i>cc</i>	(Optional) congestion control protocol
<i>iod</i>	(Optional) IOD value
<i>mtu</i>	(Optional) MTU value
<i>set-cos</i>	(Optional) Set CoS value
<i>dpp</i>	(Optional) Dynamic Packet Prioritization Class
<i>queue-limit</i>	(Optional) Queue size for the class
<i>protocol</i>	(Optional) protocol
<i>dctcp-threshold</i>	(Optional) DCTCP threshold in bytes
<i>cos-list</i>	(Optional) List of class-of-service values
<i>qos-group-list</i>	(Optional) List of qos-group values
TABLE_pmap	(Optional) all pmap xml sessions
<i>pmap-key</i>	(Optional) Policy-map name: xml key
TABLE_cmap	(Optional) all cmap xml sessions
<i>cmap-key</i>	(Optional) Class-map name: xml key
TABLE_action	(Optional) all actions
<i>action-key</i>	(Optional) Actions count: xml key
TABLE_match	(Optional) all match xml sessions
<i>match-key</i>	(Optional) match count: xml key
TABLE_rdet	(Optional) all WRED sessions
TABLE_afd	(Optional) all AFD sessions
<i>stat-en-dis-enum</i>	(Optional)
<i>in-or-out</i>	(Optional)
<i>yqos-or-q</i>	(Optional)
<i>stat-status-enum</i>	(Optional)

<i>options</i>	(Optional) match-first option
<i>pmap-name</i>	(Optional) Policy-map name
<i>pmap-inner-outer</i>	(Optional) Inner or Outer policy-map
<i>serv-pol-return-inout</i>	(Optional) Inner or Outer policy-map
<i>cmap-name</i>	(Optional) Class-map name
<i>xqos-or-q</i>	(Optional)
<i>match-opts</i>	(Optional) Type of match in class-map
<i>match-cmap-xqos-or-q</i>	(Optional)
<i>match-cmap-opts</i>	(Optional) Type of match in class-map
<i>not</i>	(Optional) Negate this match result
<i>inner</i>	(Optional) Specifies if tunnel or inner keywords are mentioned
<i>cos-list</i>	(Optional) List of class-of-service values
<i>match-cmap-name</i>	(Optional) class-map name
<i>serv-pol-type</i>	(Optional) Type of service policy referred to
<i>serv-pol-name</i>	(Optional) Name of policy-map referred to within this policy-map
<i>set-inner</i>	(Optional) Specifies if tunnel or inner keywords are mentioned
<i>cos</i>	(Optional) IEEE 802.1Q Class of Service value
<i>rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>min-rate-type</i>	(Optional) Specifies if minimum shape rate is specified
<i>min-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>max-rate-type</i>	(Optional) Specifies if maximum shape rate is specified
<i>max-rate-units</i>	(Optional) Units of rate - bps, kbps, mbps, gbps, ms, us
<i>prio-level</i>	(Optional) Priority if specified
<i>qlim-param-type</i>	(Optional) Type of parameter for qlim - cos/prec/dscp/disc class/qosgrp
<i>qlim-param-val</i>	(Optional) Parameter value for qlimit
<i>qlim-size</i>	(Optional) Queue size for qlimit
<i>size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>qlim-enum-spec</i>	(Optional) Whether qlimit parameter is specified in enum or not
<i>rdet-size-units</i>	(Optional) Units of queue size - pkts/bytes/kbytes/mbytes/ms/us/perc

<i>afd-size-units</i>	(Optional) Units of queue size - bytes/kbytes/mbytes
<i>bw-units</i>	(Optional) Bandwidth units
<i>rem-bw-units</i>	(Optional) Remaining bandwidth units
<i>rem-bw-rate</i>	(Optional) Remaining bandwidth rate
<i>rdet-values</i>	(Optional) List of class-of-service values for random-detect
<i>rdet-drop-prob</i>	(Optional) Random-detect drop probability
<i>rdet-weight</i>	(Optional) Random-detect queue length weight
<i>rdet-cap-average</i>	(Optional) Random-detect cap-average
<i>rdet-ecn</i>	(Optional) Random-detect ECN
<i>rdet-burst-opt</i>	(Optional) Random-detect burst optimized
<i>rdet-mesh-opt</i>	(Optional) Random-detect mesh optimized
<i>afd-values</i>	(Optional) List of class-of-service values for afd
<i>afd-ecn</i>	(Optional) AFD ECN
<i>pause</i>	(Optional) Pause value

**Command Mode**

- /exec



exception	(Optional)
<i>opt_match_except</i>	(Optional) Match criteria for exception packets
protocol	(Optional)
<i>opt_match_protocol</i>	(Optional) Match criteria for protocol packets
TABLE_set_action	(Optional) Table of set action
<i>set_vld_flg</i>	(Optional) Set valid flag
<i>level</i>	(Optional) syslog severity level
<i>opt_kbps_mbps_gbps_pps_cir</i>	(Optional) Units
percent	(Optional)
<i>opt_kbps_mbps_gbps_pps_pir</i>	(Optional) Units
percent1	(Optional)
<i>opt_kbytes_mbytes_gbytes_bc</i>	(Optional) Units
<i>opt_kbytes_mbytes_gbytes_be</i>	(Optional) Units
<i>opt_drop_transmit_conform</i>	(Optional) Set the action
set-cos-transmit	(Optional)
<i>set-cos-val</i>	(Optional) Conform action cos val
set-dscp-transmit	(Optional)
<i>set-dscp-val</i>	(Optional) Conform action dscp val
set-prec-transmit	(Optional)
<i>set-prec-val</i>	(Optional) Conform action prec val
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional)
dscp1	(Optional)
dscp2	(Optional)
table	(Optional)
cir-markdown-map	(Optional)
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional)
dscp3	(Optional)

dscp4	(Optional)
table1	(Optional)
pir-markdown-map	(Optional)
cos	(Optional)
inner	(Optional)
<i>cos-val</i>	(Optional) Set cos val
dscp	(Optional)
tunnel	(Optional)
<i>dscp-val</i>	(Optional) Set dscp val
precedence	(Optional)
tunnel1	(Optional)
<i>prec-val</i>	(Optional) Set prec val
<i>policer_show_flags</i>	(Optional) Policer show flags

**Command Mode**

- /exec



## show policy-map type network-qos

```
show policy-map type network-qos [ <pmap-name-nq> ] [ __readonly__ { [ <display-all> ] [ TABLE_pmap
<xpmap-name> [ <desc> ] [ TABLE_class_type <xcmap-name> [ <pause> ] [ <timeout> ] [ <size-in-bytes>
] [ <xoff-bytes> ] [ <xon-bytes> ] [ <pfc-cos-list> ] [ <cc> ] [ <thresh-units> ] [ <min-thresh> ] [ <max-thresh>
] [ <drop-prob> ] [ <iod> ] [ <mtu> ] [ <set-cos> ] [ <dpp> ] [ <dctcp-threshold> ] [ <queue-limit> ] [
<pfc_rx_only> ] ] ] } ]
```

### Syntax Description

show	Show running system information
policy-map	Show policy maps
type	Type of the policy-map
<i>pmap-name-nq</i>	(Optional) Policy-map name
network-qos	type network-qos
<i>__readonly__</i>	(Optional)
<i>display-all</i>	(Optional) Display all network-qos policy-maps
TABLE_pmap	(Optional) table for policy maps
TABLE_class_type	(Optional) table for class type
<i>xpmap-name</i>	(Optional) Policy-map name
<i>desc</i>	(Optional) Description string
<i>xcmap-name</i>	(Optional) Class-map name
<i>pause</i>	(Optional) Pause value
<i>timeout</i>	(Optional) timeout value
<i>pfc-cos-list</i>	(Optional) List of class-of-service values
<i>cc</i>	(Optional) congestion control protocol
<i>thresh-units</i>	(Optional) Units of threshold - pkts/bytes/kbytes/mbytes/ms/us/perc
<i>drop-prob</i>	(Optional) Drop Probability at Maximum Threshold value
<i>iod</i>	(Optional) IOD value
<i>mtu</i>	(Optional) MTU value
<i>set-cos</i>	(Optional) Set CoS value
<i>dpp</i>	(Optional) Dynamic Packet Prioritization Class
<i>dctcp-threshold</i>	(Optional) DCTCP threshold in bytes

<i>queue-limit</i>	(Optional) Queue size for the class
<i>pfc_rx_only</i>	(Optional) Pause receive only mode is enabled

**Command Mode**

- /exec

## show policy-map type psp

```
show policy-map type psp { [ <pmap-name> [ client <clienttype> <clientID> ] [ cfg-mode <cfgmode> ] ] [
handle <ppf_id> ] } [ __readonly__ { [ <display-all> ] [ TABLE_pmap <pmap-key> <id> <pmap-name-out>
[ <desc> ] [ TABLE_cmap <cmap-key> <if-else-id> <cmap-id> [ class-default ] [ <cmap-name-out> ] [
TABLE_action <action-key> [ <cos-val> ] [ <src-mac-addr> ] [ <dest-mac-addr> ] [ <vlan-number> ] [
<ip-tos-value> ] [ <interface-name> ] [ action-strip-vlan ] [ action-drop-pkt ] [ divert-action ] [ copy-action ]
[ forward-normal ] [ <goto-pmap-handle> ] [ action-decrement-ttl ] ] ] ] }
```

### Syntax Description

show	Show running system information
policy-map	Show policy maps
type	Type of the policy-map
psp	type psp
<i>pmap-name</i>	(Optional) Policy-map name
client	(Optional) set client type
<i>clienttype</i>	(Optional) cli/onep
<i>clientID</i>	(Optional) client appID
cfg-mode	(Optional) cfg-mode
<i>cfgmode</i>	(Optional) persistent/transient
handle	(Optional) Handle
<i>ppf_id</i>	(Optional) PPF ID
<i>__readonly__</i>	(Optional)
<i>display-all</i>	(Optional) Display all kinds of policymaps
TABLE_pmap	(Optional) all pmap xml sessions
<i>id</i>	(Optional) Policy-map ID
<i>pmap-key</i>	(Optional) Policy-map name: xml key
<i>pmap-name-out</i>	(Optional) Policy-map name
<i>desc</i>	(Optional) Description string
TABLE_cmap	(Optional) all cmap xml sessions
<i>cmap-key</i>	(Optional) Class-map name: xml key
<i>if-else-id</i>	(Optional) If-Else ID

<i>cmap-id</i>	(Optional) Class-map ID
<i>class-default</i>	(Optional)
<i>cmap-name-out</i>	(Optional) Class-map name
TABLE_action	(Optional) all action xml sessions
<i>action-key</i>	(Optional) action count: xml key
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
<i>src-mac-addr</i>	(Optional) Layer 2 MAC Address
<i>dest-mac-addr</i>	(Optional) Layer 2 MAC Address
<i>vlan-number</i>	(Optional) VLAN NUMBER
<i>ip-tos-value</i>	(Optional) IPv4 TOS Value
<i>interface-name</i>	(Optional) Physical Interface Name and Number
<i>action-strip-vlan</i>	(Optional) Perform the action STRIP-VLAN-ID
<i>action-drop-pkt</i>	(Optional) Perform the action Drop the Packet
<i>divert-action</i>	(Optional) Divert the packets to Controller
<i>copy-action</i>	(Optional) Copy the packets to Controller
<i>forward-normal</i>	(Optional) Forward the packets normally
<i>goto-pmap-handle</i>	(Optional) Pmap handle
<i>action-decrement-ttl</i>	(Optional) Decrement TTL on the Packet

**Command Mode**

- /exec

# show port-channel load-balance

```
show port-channel load-balance { [ module <module> ] | { fex { all } } } [ __readonly__ [ <sys-cfg> ] [ {
<module-cfg> } ] + <non-ip-val> <non-ip-sel> <ipv4-val> <ipv4-sel> [ <ipv6-val> ] { TABLE_mod_configs
[ <mod-number> ] <mod-non-ip-val> <mod-non-ip-sel> <mod-ipv4-val> <mod-ipv4-sel> } ]
```

## Syntax Description

show	Show running system information
port-channel	Show port-channel information
load-balance	Show port-channel load balance
module	(Optional) slot
<i>module</i>	(Optional) Specify a module number
fex	FEX devices
all	Display all configured FEX port-channel LB
<i>__readonly__</i>	(Optional)
<i>sys-cfg</i>	(Optional) system wide load balance configuraton
<i>module-cfg</i>	(Optional) per module load balance configuraton
<i>non-ip-val</i>	(Optional) load balance setting for non-ip traffic
<i>non-ip-sel</i>	(Optional) non ip select
<i>ipv4-val</i>	(Optional) load balance setting for ipv4 traffic
<i>ipv4-sel</i>	(Optional) ip select
<i>ipv6-val</i>	(Optional) load balance setting for ipv6 traffic
TABLE_mod_configs	(Optional) module configurations
<i>mod-number</i>	(Optional) module number
<i>mod-non-ip-val</i>	(Optional) load balance setting for non-ip traffic
<i>mod-non-ip-sel</i>	(Optional) non ip select
<i>mod-ipv4-val</i>	(Optional) load balance setting for ipv4 traffic
<i>mod-ipv4-sel</i>	(Optional) ip select

## Command Mode

- /exec

# show port-profile

```
show port-profile [ name <all_profile_name> ] [ __readonly__ <profile_name> <profile_id> <type> <desc>
<status> <max_ports> <min_ports> <inherit> <profile_cfg> <cmd_depth> <cmd_key> <parent_seqno>
<cmd_seqno> <cmd_attr> <form_type> <cmd_mask> <shadow_cmd> <cmd_flags> <eval_cfg> <intf>
<cap_l3> <cap_iscsi> <ctrl_sgid> <pkt_sgid> <sys_vlans> <portgrp> <pprole> <port_binding> ]
```

## Syntax Description

show	Show running system information
port-profile	Show port-profile
name	(Optional) port-profile name
<i>all_profile_name</i>	(Optional) Enter the name of the profile
<i>__readonly__</i>	(Optional)
<i>profile_name</i>	(Optional)
<i>profile_id</i>	(Optional)
<i>type</i>	(Optional)
<i>desc</i>	(Optional)
<i>status</i>	(Optional)
<i>max_ports</i>	(Optional)
<i>min_ports</i>	(Optional)
<i>inherit</i>	(Optional)
<i>profile_cfg</i>	(Optional)
<i>cmd_depth</i>	(Optional)
<i>cmd_key</i>	(Optional)
<i>parent_seqno</i>	(Optional)
<i>cmd_seqno</i>	(Optional)
<i>cmd_attr</i>	(Optional)
<i>form_type</i>	(Optional)
<i>cmd_mask</i>	(Optional)
<i>shadow_cmd</i>	(Optional)
<i>cmd_flags</i>	(Optional)

<i>eval_cfg</i>	(Optional)
<i>intf</i>	(Optional)
<i>cap_l3</i>	(Optional) L3 Profile
<i>cap_iscsi</i>	(Optional) iSCSI cap
<i>ctrl_sgid</i>	(Optional) Control Vlan Pinned Sgid
<i>pkt_sgid</i>	(Optional) Packet Vlan Pinned Sgid
<i>sys_vlans</i>	(Optional) System Vlans
<i>portgrp</i>	(Optional) VMware Portgroup
<i>pprole</i>	(Optional) Port-profile Role
<i>port_binding</i>	(Optional) Port-binding

**Command Mode**

- /exec

# show port-profile brief

```
show port-profile brief [ __readonly__ { TABLE_port_profile <profile_name> <type> <status>
<profile_cfg_cnt> <eval_cfg_cnt> <intf_cnt> <inherit_cnt> <header_flag> } { TABLE_intf_count <intf_type>
<intf_count> <tot_header_flag> } ]
```

## Syntax Description

show	Show running system information
port-profile	Show port-profile
brief	Brief info about profiles
<i>__readonly__</i>	(Optional)
<i>profile_name</i>	(Optional)
TABLE_port_profile	(Optional)
<i>type</i>	(Optional)
<i>status</i>	(Optional)
<i>profile_cfg_cnt</i>	(Optional)
<i>eval_cfg_cnt</i>	(Optional)
<i>intf_cnt</i>	(Optional)
<i>inherit_cnt</i>	(Optional)
<i>header_flag</i>	(Optional)
TABLE_intf_count	(Optional)
<i>intf_type</i>	(Optional)
<i>intf_count</i>	(Optional)
<i>tot_header_flag</i>	(Optional)

## Command Mode

- /exec



## show port-profile expand-interface

```
show port-profile expand-interface [ name <all_profile_name> ] [ __readonly__ <profile_name> <intf>
<intf_cfg> ]
```

### Syntax Description

show	Show running system information
port-profile	Show port-profile
expand-interface	Active profile config applied in a interface
name	(Optional) port-profile name
<i>all_profile_name</i>	(Optional) Enter the name of the profile
<i>__readonly__</i>	(Optional)
<i>profile_name</i>	(Optional)
<i>intf</i>	(Optional)
<i>intf_cfg</i>	(Optional)

### Command Mode

- /exec

# show port-profile sync-status

```
show port-profile sync-status [ interface <intfname> ] [ __readonly__ <intf> <status> <inherit> <sync_status>
<cached_cmds> <errors> <recovery> ]
```

## Syntax Description

show	Show running system information
port-profile	Show port-profile
sync-status	Interfaces out-of-sync with port-profiles
interface	(Optional) Interface name
<i>intfname</i>	(Optional) Name of interface
<i>__readonly__</i>	(Optional)
<i>intf</i>	(Optional)
<i>status</i>	(Optional)
<i>inherit</i>	(Optional)
<i>sync_status</i>	(Optional)
<i>cached_cmds</i>	(Optional)
<i>errors</i>	(Optional)
<i>recovery</i>	(Optional)

## Command Mode

- /exec

## show port-profile usage

```
show port-profile usage [ name <all_profile_name> ] [ __readonly__ TABLE_port_profile <profile_name>
{ TABLE_interface <interface> } ]
```

### Syntax Description

show	Show running system information
port-profile	Show port-profile
usage	List of interfaces inherited a profile
name	(Optional) port-profile name
<i>all_profile_name</i>	(Optional) Enter the name of the profile
<i>__readonly__</i>	(Optional)
TABLE_port_profile	(Optional)
TABLE_interface	(Optional)
<i>profile_name</i>	(Optional)
<i>interface</i>	(Optional)

### Command Mode

- /exec

# show port-security

```
show port-security [ __readonly__ { TABLE_eth_port_sec_interfaces <secure_port> <max_secure_addr>
<current_addr> <security_violation> <security_action> <num_val> <num_elems> <cmdid_show_index>
<port_state> } <total_addr> <max_sys_limit> ]
```

## Syntax Description

port-security	Show secure port information
<i>__readonly__</i>	(Optional)
TABLE_eth_port_sec_interfaces	(Optional) Displays the secured interfaces
<i>secure_port</i>	(Optional) Interface Index
<i>max_secure_addr</i>	(Optional) Maximum number of secured MAC addresses
<i>current_addr</i>	(Optional) Number of secured MAC addresses
<i>security_violation</i>	(Optional) Number of security violations
<i>security_action</i>	(Optional) Security Action Shutdown/Restrict/Protect
<i>num_val</i>	(Optional) Number of Values
<i>num_elems</i>	(Optional) Number of Elements
<i>cmdid_show_index</i>	(Optional) Index for the Interfaces
<i>port_state</i>	(Optional) Port security enabled or disabled
<i>total_addr</i>	(Optional) Total number of secured MAC addresses
<i>max_sys_limit</i>	(Optional) Maximum allowed MACs excluding one per port

## Command Mode

- /exec

## show port-security address

```
show port-security address [ __readonly__ { TABLE_eth_port_sec_mac_addrs <vlan_id> <mac_addr> <type>
<if_index> <remain_age> <remote_learnt> <remote_aged> <num_elems> <cmd_addr_index> } <total_addr>
<max_sys_limit> ]
```

### Syntax Description

port-security	Show secure port information
address	Show secure address
<i>__readonly__</i>	(Optional)
TABLE_eth_port_sec_mac_addrs	(Optional) Displays the secured MAC addresses
<i>if_index</i>	(Optional) Interface index
<i>vlan_id</i>	(Optional) vlan id
<i>mac_addr</i>	(Optional) mac address
<i>type</i>	(Optional) static/sticky/dyanmic MAC address
<i>remain_age</i>	(Optional) Remaining age
<i>remote_learnt</i>	(Optional) Remotely learnt
<i>remote_aged</i>	(Optional) Remotely Aged Out
<i>num_elems</i>	(Optional) Number of Elements
<i>cmd_addr_index</i>	(Optional) Index for the interface address
<i>total_addr</i>	(Optional) Total number of secured MAC addresses
<i>max_sys_limit</i>	(Optional) Maximum allowed MACs excluding one per port

### Command Mode

- /exec

# show port-security address blocked

```
show port-security address blocked [ __readonly__ { TABLE_eth_port_sec_mac_addrs <vlan_id> <mac_addr>
<type> <if_index> <remain_age> <num_elems> <cmd_addr_index> } <total_addr> <max_sys_limit> ]
```

## Syntax Description

port-security	Show secure port information
address	Show secure address
blocked	Port Security Blocked macs
<i>__readonly__</i>	(Optional)
TABLE_eth_port_sec_mac_addrs	(Optional) Displays the secured MAC addresses
<i>if_index</i>	(Optional) Interface index
<i>vlan_id</i>	(Optional) vlan id
<i>mac_addr</i>	(Optional) mac address
<i>type</i>	(Optional) static/sticky/dyanmic MAC address
<i>remain_age</i>	(Optional) Remaining age
<i>num_elems</i>	(Optional) Number of Elements
<i>cmd_addr_index</i>	(Optional) Index for the interface address
<i>total_addr</i>	(Optional) Total number of secured MAC addresses
<i>max_sys_limit</i>	(Optional) Maximum allowed MACs excluding one per port

## Command Mode

- /exec

## show port-security address interface

```
show port-security address interface <interface-id> [ __readonly__ { TABLE_eth_port_sec_mac_addrs
<vlan_id> <mac_addr> <type> <if_index> <remain_age> <remote_learnt> <remote_aged> <num_elems>
} <total_addr> <max_sys_limit> <first> ]
```

### Syntax Description

port-security	Show secure port information
address	Show secure address
interface	Show secure interface
<i>interface-id</i>	ethernet
<i>__readonly__</i>	(Optional)
TABLE_eth_port_sec_mac_addrs	(Optional) Displays the secured MAC addresses
<i>if_index</i>	(Optional) Interface index
<i>vlan_id</i>	(Optional) vlan id
<i>mac_addr</i>	(Optional) mac address
<i>type</i>	(Optional) static/sticky/dyanmic MAC address
<i>remain_age</i>	(Optional) Remaining age
<i>remote_learnt</i>	(Optional) Remotely learnt
<i>remote_aged</i>	(Optional) Remotely Aged Out
<i>num_elems</i>	(Optional) Number of Elements
<i>total_addr</i>	(Optional) Total number of secured MAC addresses
<i>max_sys_limit</i>	(Optional) Maximum allowed MACs excluding one per port
<i>first</i>	(Optional) To identify the first entry

### Command Mode

- /exec

## show port-security address nvr

```
show port-security address nvr [ __readonly__ { TABLE_eth_port_sec_mac_addrs <vlan_id> <mac_addr>
<type> <if_index> <remain_age> <remote_learnt> <remote_aged> <num_elems> <cmd_addr_index> }
<total_addr> <max_sys_limit> ]
```

### Syntax Description

port-security	Show secure port information
address	Show secure address
nvr	Port Security NVRAM
<i>__readonly__</i>	(Optional)
<i>TABLE_eth_port_sec_mac_addrs</i>	(Optional) Displays the secured MAC addresses
<i>if_index</i>	(Optional) Interface index
<i>vlan_id</i>	(Optional) vlan id
<i>mac_addr</i>	(Optional) mac address
<i>type</i>	(Optional) static/sticky/dyanmic MAC address
<i>remain_age</i>	(Optional) Remaining age
<i>remote_learnt</i>	(Optional) Remotely learnt
<i>remote_aged</i>	(Optional) Remotely Aged Out
<i>num_elems</i>	(Optional) Number of Elements
<i>cmd_addr_index</i>	(Optional) Index for the interface address
<i>total_addr</i>	(Optional) Total number of secured MAC addresses
<i>max_sys_limit</i>	(Optional) Maximum allowed MACs excluding one per port

### Command Mode

- /exec



## show port-security detail interface

```
show port-security detail interface [ __readonly__ { TABLE_eth_port_sec_intf_detail <if_index>
<port_security> <port_status> <violation_mode> <aging_time> <aging_type> <max_mac_addr>
<total_sec_addrs> <trap_count> <addr_aging_enable> <secure_last_mac_addr> <sticky_enable>
<secure_last_mac_addr_vlan_id> } ]
```

### Syntax Description

port-security	Show secure port information
detail	Show detailed information about secure interface
interface	Show secure interface
TABLE_eth_port_sec_intf_detail	(Optional) Displays the secured interface details
__readonly__	(Optional)
<i>if_index</i>	(Optional) Interface index
<i>port_security</i>	(Optional) Port Security is Enabled/Disabled
<i>port_status</i>	(Optional) Secure Up/Down
<i>violation_mode</i>	(Optional) Shutdown/Restrict/Protect
<i>aging_time</i>	(Optional) Aging time in minutes
<i>aging_type</i>	(Optional) Absolute/Inactivity
<i>max_mac_addr</i>	(Optional) Maximum number of MAC addresses that can be secured
<i>total_sec_addrs</i>	(Optional) Total number of secured MAC addresses
<i>trap_count</i>	(Optional) Trap Count
<i>addr_aging_enable</i>	(Optional) Specifies whether address aging is enabled
<i>secure_last_mac_addr</i>	(Optional) Secured last mac address
<i>sticky_enable</i>	(Optional) Specifies sticky feature is enabled on the port
<i>secure_last_mac_addr_vlan_id</i>	(Optional) Indicates the VLAN where the last MAC address seen on this interface

### Command Mode

- /exec

# show port-security interface

```
show port-security interface <interface-id> [ __readonly__ <config_port_security> <oper_port_security>
<port_status> <violation_mode> <aging_time> <aging_type> <max_mac_addr> <total_sec_addrs>
<conf_num_addrs> <num_sticky_addrs> <trap_count> ]
```

## Syntax Description

port-security	Show secure port information
interface	Show secure interface
<i>interface-id</i>	ethernet
<i>__readonly__</i>	(Optional)
<i>config_port_security</i>	(Optional) Port Security configuration is Enabled/Disabled
<i>oper_port_security</i>	(Optional) Port Security is Operationally Enabled/Disabled
<i>port_status</i>	(Optional) Secure Up/Down
<i>violation_mode</i>	(Optional) Shutdown/Restrict/Protect
<i>aging_time</i>	(Optional) Aging time in minutes
<i>aging_type</i>	(Optional) Absolute/Inactivity
<i>max_mac_addr</i>	(Optional) Configured Maximum
<i>total_sec_addrs</i>	(Optional) Total number of secured MAC addresses
<i>conf_num_addrs</i>	(Optional) Number of configured MAC addresses
<i>num_sticky_addrs</i>	(Optional) Number of sticky MAC addresses
<i>trap_count</i>	(Optional) Trap Count

## Command Mode

- /exec

## show port-security multivlan address

```
show port-security multivlan address [ __readonly__ { TABLE_eth_port_sec_multi_vlan <if_index> <vlan_id>
<max_sec_mac_addr_count> <cur_sec_mac_addr_count> } ]
```

### Syntax Description

port-security	Show secure port information
address	Show secure address
multivlan	Show port security information for a particular vlan in a multivlan port
__readonly__	(Optional)
TABLE_eth_port_sec_multi_vlan	(Optional) Displays the secured MAC addresses
<i>if_index</i>	(Optional) Interface index
<i>vlan_id</i>	(Optional) vlan id
<i>max_sec_mac_addr_count</i>	(Optional) The maximum number of MAC addresses to be secured in the vlan
<i>cur_sec_mac_addr_count</i>	(Optional) Current number of MAC addresses secured in the VLAN

### Command Mode

- /exec

## show port-security secure address

```
show port-security secure address [ __readonly__ { TABLE_eth_port_sec_if_vlan_secure_mac_addr <if_index>
<mac_addr> <vlan_id> <mac_addr_type> <remain_age> } ]
```

### Syntax Description

<code>port-security</code>	Show secure port information
<code>secure</code>	Show detail information about secure address
<code>address</code>	Show secure address
<code>__readonly__</code>	(Optional)
<code>TABLE_eth_port_sec_if_vlan_secure_mac_addr</code>	(Optional) Displays the secured MAC addresses
<code>if_index</code>	(Optional) Interface index
<code>mac_addr</code>	(Optional) mac address
<code>vlan_id</code>	(Optional) vlan id
<code>mac_addr_type</code>	(Optional) static/sticky/ MAC address
<code>remain_age</code>	(Optional) Remaining age

### Command Mode

- /exec

# show port-security state

show port-security state [ \_\_readonly\_\_ <status> ]

## Syntax Description

port-security	Port security related command
state	port security state
__readonly__	(Optional)
<i>status</i>	(Optional) show port-security

## Command Mode

- /exec

# show port-security traps enable

```
show port-security traps enable [ __readonly__ { <snmp_traps_enable> } ]
```

## Syntax Description

port-security	Show secure port information
traps	Enable SNMP traps
enable	enable
__readonly__	(Optional)
<i>snmp_traps_enable</i>	(Optional) SNMP traps enable/disable

## Command Mode

- /exec

# show power inline

```
show power inline <if0> [ __readonly__ { TABLE_intf_info <intf_name> <admin> <oper> <supp_pwr>
<del_pwr> <device> <class> <max> } ]
```

## Syntax Description

show	Show running system information
power	Power over Ethernet
<i>if0</i>	
<i>__readonly__</i>	(Optional)
TABLE_intf_info	(Optional) Interface information
<i>intf_name</i>	(Optional) Interface name
<i>admin</i>	(Optional) Port mode
<i>oper</i>	(Optional) Oper mode
<i>supp_pwr</i>	(Optional) Supplied power
<i>del_pwr</i>	(Optional) delivered power
<i>device</i>	(Optional) Device information
<i>class</i>	(Optional) POE Class
<i>max</i>	(Optional) Max power

## Command Mode

- /exec

# show power inline

```
show power inline [ __readonly__ { TABLE_fex_info <module_id> <avail_pwr> <used_pwr> <rem_pwr>
} { TABLE_intf_info <intf_name> <admin> <oper> <supp_pwr> <del_pwr> <device> <class> <max> } ]
```

## Syntax Description

show	Show running system information
power	Power over Ethernet
__readonly__	(Optional)
TABLE_fex_info	(Optional) FEX information
<i>module_id</i>	(Optional) FEX id
<i>avail_pwr</i>	(Optional) Available power
<i>used_pwr</i>	(Optional) Used power
<i>rem_pwr</i>	(Optional) Free power
TABLE_intf_info	(Optional) Interface information
<i>intf_name</i>	(Optional) Interface name
<i>admin</i>	(Optional) Port mode
<i>oper</i>	(Optional) Oper mode
<i>supp_pwr</i>	(Optional) Supplied power
<i>del_pwr</i>	(Optional) delivered power
<i>device</i>	(Optional) Device information
<i>class</i>	(Optional) POE Class
<i>max</i>	(Optional) Max power

## Command Mode

- /exec



# show power inline police

```
show power inline police [ __readonly__ { TABLE_police <intf_name> <admin> <oper> <admin_police>
<oper_police> <cutoff_pwr> <oper_pwr> } ]
```

## Syntax Description

show	Show running system information
power	Power over Ethernet
police	Show per-port policing
<i>__readonly__</i>	(Optional)
<i>TABLE_police</i>	(Optional) Police information
<i>intf_name</i>	(Optional) Interface name
<i>admin</i>	(Optional) Port mode
<i>oper</i>	(Optional) Oper mode
<i>admin_police</i>	(Optional) Configured admin police
<i>oper_police</i>	(Optional) Current police
<i>cutoff_pwr</i>	(Optional) Cutoff power
<i>oper_pwr</i>	(Optional) Oper power

## Command Mode

- /exec

# show power inline priority

show power inline priority [ *\_\_readonly\_\_* { *TABLE\_priority* <intf\_name> <admin> <oper> <priority> } ]

## Syntax Description

<i>show</i>	Show running system information
<i>power</i>	Power over Ethernet
<i>priority</i>	Show per-port priority
<i>__readonly__</i>	(Optional)
<i>TABLE_priority</i>	(Optional) Port priority information
<i>intf_name</i>	(Optional) Interface name
<i>admin</i>	(Optional) Port mode
<i>oper</i>	(Optional) Oper mode
<i>priority</i>	(Optional) port priority

## Command Mode

- /exec

# show privilege

show privilege

## Syntax Description

show	Show running system information
privilege	Display privilege information

## Command Mode

- /exec

# show processes

```
show processes [ __readonly__ { [ TABLE_processes <pid> <state> <pc> <start_cnt> <tty> <p_type>
<process> ] } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
__readonly__	(Optional)
TABLE_processes	(Optional) all process information
<i>pid</i>	(Optional) process id
<i>state</i>	(Optional) process state
<i>pc</i>	(Optional) pc register
<i>start_cnt</i>	(Optional) TBD
<i>tty</i>	(Optional) TBD
<i>p_type</i>	(Optional) process type
<i>process</i>	(Optional) process name

## Command Mode

- /exec

## show processes cpu

```
show processes cpu [ sort ] [ __readonly__ { [ TABLE_process_cpu <pid> <runtime> <invoked> <usecs>
<onsec> <process> ] [ <user_percent> ] [ <kernel_percent> ] [ <idle_percent> ] } ]
```

### Syntax Description

show	Show running system information
processes	Show processes
cpu	Show processes CPU Info
sort	(Optional) Show processes CPU Info (Sorted by Cpu Util with time base)
__readonly__	(Optional)
TABLE_process_cpu	(Optional) all process memory
<i>pid</i>	(Optional) process id
<i>runtime</i>	(Optional) Runtime
<i>invoked</i>	(Optional) Invoked
<i>usecs</i>	(Optional) usecs
<i>onsec</i>	(Optional) fivesec
<i>process</i>	(Optional) name of the process
<i>user_percent</i>	(Optional) user
<i>kernel_percent</i>	(Optional) kernel
<i>idle_percent</i>	(Optional) idle

### Command Mode

- /exec

# show processes cpu history

show processes cpu history

## Syntax Description

show	Show running system information
processes	Show processes
cpu	Show processes CPU Info
history	Show processes CPU Util History

## Command Mode

- /exec

## show processes cpu history data

```
show processes cpu history data [ __readonly__ { [ TABLE_processes_cpu_history <cpu_avg_sec> ] } ]
```

### Syntax Description

show	Show running system information
processes	Show processes
cpu	Show processes CPU Info
history	Show processes CPU Util History
data	Display the CPU util as data, instead of graph
<i>__readonly__</i>	(Optional)
<i>TABLE_processes_cpu_history</i>	(Optional) 60 sec cpu history
<i>cpu_avg_sec</i>	(Optional) cpu avg for a sec

### Command Mode

- /exec

# show processes log

```
show processes log [ __readonly__ { [ TABLE_processes_log <vdc> <process> <pid> <normal_exit> <stack>
<core> <create_time> ] } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
log	Show information about process logs
<i>__readonly__</i>	(Optional)
TABLE_processes_log	(Optional) all processes log
<i>vdc</i>	(Optional) vdc
<i>process</i>	(Optional) vdc process name
<i>pid</i>	(Optional) pid
<i>normal_exit</i>	(Optional) process exit
<i>stack</i>	(Optional) stack
<i>core</i>	(Optional) core
<i>create_time</i>	(Optional) log create time

## Command Mode

- /exec



# show processes log details

show processes log details [ \_\_readonly\_\_ { line\_in\_log\_detail <line\_in\_file> } ]

## Syntax Description

show	Show running system information
processes	Show processes
log	Show information about process logs
details	Show detail of all logs with stack
__readonly__	(Optional)
line_in_log_detail	(Optional)
<i>line_in_file</i>	(Optional) each line

## Command Mode

- /exec

# show processes log pid

```
show processes log pid <i0> [ __readonly__ { TABLE_line_in_log_pid <line_in_file> } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
log	Show information about process logs
pid	Show detail log info about a specific process
<i>i0</i>	pid of the process
<code>__readonly__</code>	(Optional)
TABLE_line_in_log_pid	(Optional)
<i>line_in_file</i>	(Optional) each line

## Command Mode

- /exec

# show processes log vdc-all

```
show processes log vdc-all [ __readonly__ { [ TABLE_processes_log_vdc_all <vdc> <process> <pid>
<normal_exit> <stack> <core> <create_time> ] } ]
```

## Syntax Description

TABLE_processes_log_vdc_all	(Optional) all processes log vdc all
show	Show running system information
processes	Show processes
log	Show information about process logs
vdc-all	Show information about process logs in all vdc's
__readonly__	(Optional)
vdc	(Optional) vdc process name
process	(Optional) vdc process name
pid	(Optional) process id
normal_exit	(Optional) process exit
stack	(Optional) stack
core	(Optional) core
create_time	(Optional) log create time

## Command Mode

- /exec

# show processes memory

```
show processes memory [ __readonly__ { TABLE_process_memory <mem_pid> <mem_alloc> <mem_limit>
<mem_used> <stack_base_ptr> <process> } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
memory	Show processes Memory Info
<i>__readonly__</i>	(Optional)
TABLE_process_memory	(Optional) all process memory
<i>mem_pid</i>	(Optional) process id
<i>mem_alloc</i>	(Optional) allocated memory
<i>mem_limit</i>	(Optional) memory limit
<i>mem_used</i>	(Optional) memory used
<i>stack_base_ptr</i>	(Optional) stack and base pointer
<i>process</i>	(Optional) name of the process

## Command Mode

- /exec

# show processes memory clis

show processes memory clis [ shared | private ]

## Syntax Description

show	Show running system information
processes	Display process information
memory	Display memory information
clis	
shared	(Optional) Display CLIS shared memory information
private	(Optional) Display CLIS private memory information

## Command Mode

- /exec

# show processes memory physical

```
show processes memory physical [ __readonly__ { TABLE_process_physical_memory <processid> <virtual>
<physical> <rss> <processname> } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
memory	Show processes Memory Info
physical	Show processes physical Memory
__readonly__	(Optional)
TABLE_process_physical_memory	(Optional) all process physical memory
<i>processid</i>	(Optional) process id
<i>virtual</i>	(Optional) virtual allocated memory
<i>physical</i>	(Optional) physical memory used
<i>rss</i>	(Optional) rss memory
<i>processname</i>	(Optional) name of the process

## Command Mode

- /exec

# show processes memory shared

```
show processes memory shared [ detail | dynamic ] [ __readonly__ TABLE_process_tag [ <process-tag-out>
] [ <process-memory-share-dynamic-component-str> ] [ <process-memory-share-dynamic-shared-memory-str>
] [ <process-memory-share-dynamic-current-size-str> ] [ <process-memory-share-dynamic-max-size-str> ] [
<process-memory-share-dynamic-used-str> ] [ <process-memory-share-component-str> ] [
<process-memory-share-shared-memory-str> ] [ <process-memory-share-size-str> ] [
<process-memory-share-used-str> ] [ <process-memory-share-available-str> ] [ <process-memory-share-ref-str>
] [ <process-memory-share-byte-set-address-str> ] [ <process-memory-share-byte-set-count-str> ] [
<process-memory-share-address-str> ] [ <process-memory-share-kbytes-1-str> ] [
<process-memory-share-kbytes-2-str> ] [ <process-memory-share-kbytes-3-str> ] [
<process-memory-share-count-str> ] [ { TABLE_SMMITEM <process-memory-share-smr-name> } ] [ {
TABLE_SHOWPROC <process-memory-share-table-showproc-key> [ { TABLE_SHOWONEDYNAMIC
[ <process-memory-share-component> ] [ <process-memory-share-shared-memory> ] [
<process-memory-share-current-size> ] [ <process-memory-share-max-size> ] [ <process-memory-share-used>
] } ] [ { TABLE_ONEITEM [ <process-memory-share-proc-smr-name> ] [ <process-memory-share-smr-addr>
] [ <process-memory-share-smr-size> ] [ <process-memory-share-smr-star-char> ] [
<process-memory-share-smr-empty-char> ] [ <process-memory-share-smr-used> ] [
<process-memory-share-smr-avail> ] [ <process-memory-share-smr-ref-count> ] [
<process-memory-share-dynamic-smr-name> } ] } ] [ { TABLE_ONEITEMDYNAMIC [
<process-memory-share-dynamic-smr-addr> ] [ <process-memory-share-dynamic-smr-size> ] [
<process-memory-share-dynamic-plus-char> ] [ <process-memory-share-max-mem-size-str> ] [
<process-memory-share-dynamic-smr-used> ] [ <process-memory-share-dynamic-smr-avail> ] [
<process-memory-share-dynamic-smr-ref-count> ] [ <process-memory-share-region-smr-name> } ] } ] [
<process-memory-share-total-shm-size> ] [ <process-memory-share-total-shm-used> ] [
<process-memory-share-total-shm-avail> ] ] ]
```

## Syntax Description

show	Show running system information
processes	Display process information
memory	Display memory information
shared	Display shared memory info
detail	(Optional) Display shared memory in bytes instead of default kbytes
dynamic	(Optional) Display details of dynamic shared memory segments
__readonly__	(Optional)
TABLE_process_tag	(Optional)
<i>process-tag-out</i>	(Optional)
<i>process-memory-share-dynamic-component-str</i>	(Optional)
<i>process-memory-share-dynamic-shared-memory-str</i>	(Optional)
<i>process-memory-share-dynamic-current-size-str</i>	(Optional)

<i>process-memory-share-dynamic-max-size-str</i>	(Optional)
<i>process-memory-share-dynamic-used-str</i>	(Optional)
<i>process-memory-share-component-str</i>	(Optional)
<i>process-memory-share-shared-memory-str</i>	(Optional)
<i>process-memory-share-size-str</i>	(Optional)
<i>process-memory-share-used-str</i>	(Optional)
<i>process-memory-share-available-str</i>	(Optional)
<i>process-memory-share-ref-str</i>	(Optional)
<i>process-memory-share-byte-set-address-str</i>	(Optional)
<i>process-memory-share-byte-set-count-str</i>	(Optional)
<i>process-memory-share-address-str</i>	(Optional)
<i>process-memory-share-kbytes-1-str</i>	(Optional)
<i>process-memory-share-kbytes-2-str</i>	(Optional)
<i>process-memory-share-kbytes-3-str</i>	(Optional)
<i>process-memory-share-count-str</i>	(Optional)
TABLE_SMMITEM	(Optional)
<i>process-memory-share-smr-name</i>	(Optional)
TABLE_SHOWPROC	(Optional)
<i>process-memory-share-table-showproc-key</i>	(Optional)
TABLE_SHOWONEDYNAMIC	(Optional)
<i>process-memory-share-component</i>	(Optional)
<i>process-memory-share-shared-memory</i>	(Optional)
<i>process-memory-share-current-size</i>	(Optional)
<i>process-memory-share-max-size</i>	(Optional)
<i>process-memory-share-used</i>	(Optional)
TABLE_ONEITEM	(Optional)
<i>process-memory-share-proc-smr-name</i>	(Optional)
<i>process-memory-share-smr-addr</i>	(Optional)
<i>process-memory-share-smr-size</i>	(Optional)



<i>process-memory-share-smr-star-char</i>	(Optional)
<i>process-memory-share-smr-empty-char</i>	(Optional)
<i>process-memory-share-smr-used</i>	(Optional)
<i>process-memory-share-smr-avail</i>	(Optional)
<i>process-memory-share-smr-ref-count</i>	(Optional)
TABLE_ONEITEMDYNAMIC	(Optional)
<i>process-memory-share-dynamic-smr-name</i>	(Optional)
<i>process-memory-share-dynamic-smr-addr</i>	(Optional)
<i>process-memory-share-dynamic-smr-size</i>	(Optional)
<i>process-memory-share-dynamic-plus-char</i>	(Optional)
<i>process-memory-share-max-mem-size-str</i>	(Optional)
<i>process-memory-share-dynamic-smr-used</i>	(Optional)
<i>process-memory-share-dynamic-smr-avail</i>	(Optional)
<i>process-memory-share-dynamic-smr-ref-count</i>	(Optional)
<i>process-memory-share-region-smr-name</i>	(Optional)
<i>process-memory-share-total-shm-size</i>	(Optional)
<i>process-memory-share-total-shm-used</i>	(Optional)
<i>process-memory-share-total-shm-avail</i>	(Optional)

**Command Mode**

- /exec

# show processes vdc

```
show processes vdc <e-vdc2> [ __readonly__ { TABLE_processes_vdc <pid> <state> <pc> <start_cnt> <tty>
<p_type> <process> } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
<i>__readonly__</i>	(Optional) Read only
<i>TABLE_processes_vdc</i>	(Optional) All process information
<i>pid</i>	(Optional) PID of process
<i>state</i>	(Optional) State of process
<i>pc</i>	(Optional) PC in which process exists
<i>start_cnt</i>	(Optional) TBD
<i>tty</i>	(Optional) TBD
<i>p_type</i>	(Optional) Type of Process
<i>process</i>	(Optional) Process Name

## Command Mode

- /exec

## show processes vdc cpu

```
show processes vdc <e-vdc2> cpu [ __readonly__ { [ TABLE_process_vdc_cpu <pid> <runtime> <invoked>
<usecs> <onesecc> <process> ] } ]
```

### Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
cpu	Show processes CPU Info
<i>__readonly__</i>	(Optional) Readonly table for cpu log
TABLE_process_vdc_cpu	(Optional) All cpu process logs of vdc
<i>pid</i>	(Optional) PID of process
<i>runtime</i>	(Optional) Runtime
<i>invoked</i>	(Optional) Invoked
<i>usecs</i>	(Optional) uSecs
<i>onesecc</i>	(Optional) fivesec
<i>process</i>	(Optional) Name of process

### Command Mode

- /exec

# show processes vdc log

```
show processes vdc <e-vdc2> log [ __readonly__ { [ TABLE_processes_vdc_log <vdc> <process> <pid>
<normal_exit> <stack> <core> <create_time> ] } ]
```

## Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
log	Show information about process logs
<i>__readonly__</i>	(Optional) Read only table
<i>TABLE_processes_vdc_log</i>	(Optional) Table for log of all VDC Processes
<i>pid</i>	(Optional) PID of process
<i>vdc</i>	(Optional) VDC Number
<i>process</i>	(Optional) Process name
<i>normal_exit</i>	(Optional) Normal Exit status
<i>stack</i>	(Optional) Stack
<i>core</i>	(Optional) Core
<i>create_time</i>	(Optional) Time stamp of log

## Command Mode

- /exec

# show processes vdc log details

show processes vdc <e-vdc2> log details

## Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
log	Show information about process logs
details	Show detail of all logs with stack

## Command Mode

- /exec

# show processes vdc log pid

show processes vdc <e-vdc2> log pid <i1>

## Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
log	Show information about process logs
pid	Show detail log info about a specific process
<i>i1</i>	pid of the process

## Command Mode

- /exec

## show processes vdc memory

```
show processes vdc <e-vdc2> memory [ __readonly__ { [ TABLE_process_memory <mem_pid> <mem_alloc>
<mem_limit> <mem_used> <stack_base_ptr> <process> ] [ <sum_mem_mallosed> ] } ]
```

### Syntax Description

show	Show running system information
processes	Show processes
vdc	Show processes in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
memory	Show processes Memory Info
<i>__readonly__</i>	(Optional)
TABLE_process_memory	(Optional) all process memory
<i>mem_pid</i>	(Optional) process id
<i>mem_alloc</i>	(Optional) allocated memory
<i>mem_limit</i>	(Optional) memory limit
<i>mem_used</i>	(Optional) memory used
<i>stack_base_ptr</i>	(Optional) stack and base pointer
<i>process</i>	(Optional) name of the process

### Command Mode

- /exec

# show processes version

```
show processes { version | threads } [ <comp-string> ] [ __readonly__ TABLE_component <component-name>
<version> <buildinfo> <sourceversion> ]
```

## Syntax Description

show	Show running system information
processes	Display process information
version	Display system release information
threads	Threads Info
<i>comp-string</i>	(Optional) Component name for detailed information
<i>__readonly__</i>	(Optional)
TABLE_component	(Optional)
<i>component-name</i>	(Optional)
<i>version</i>	(Optional)
<i>buildinfo</i>	(Optional)
<i>sourceversion</i>	(Optional)

## Command Mode

- /exec



# show pss debug

show pss debug

## Syntax Description

show	Show running system information
pss	display pss information
debug	display pss debug configuration

## Command Mode

- /exec

# show ptp brief

```
show ptp brief [ __readonly__ [ TABLE_ptp <ptp-ifindex> <state> ] <ptp-end> ]
```

## Syntax Description

<code>ptp</code>	Precision Time Protocol (IEEE 1588) Subsystem
<code>brief</code>	port states in brief
<code>__readonly__</code>	(Optional) Read Only
<code>TABLE_ptp</code>	(Optional) ptp table
<code>ptp-ifindex</code>	(Optional) ptp ifindex
<code>state</code>	(Optional) BMC state
<code>ptp-end</code>	(Optional) End of table

## Command Mode

- /exec

# show ptp clock

```
show ptp clock [ __readonly__ <clock-id> <domain-id> <num-ports> <priority1> <priority2> <class>
<accuracy> <scaled-log-variance> <offset-from-master> <mean-path-delay-to-master> <steps-removed>
<correction-threshold> <bs-status> ]
```

## Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
clock	Set local clock attributes
<i>__readonly__</i>	(Optional) Read only
<i>domain-id</i>	(Optional) Domain Id
<i>clock-id</i>	(Optional) Clock Id
<i>priority1</i>	(Optional) Priority 1
<i>priority2</i>	(Optional) Priority 2
<i>num-ports</i>	(Optional) Number of PTP ports
<i>class</i>	(Optional) Class
<i>accuracy</i>	(Optional) Clock accuracy
<i>scaled-log-variance</i>	(Optional) scaled log variance
<i>offset-from-master</i>	(Optional) Offset from master
<i>mean-path-delay-to-master</i>	(Optional) mean path delay to master
<i>steps-removed</i>	(Optional) Steps removed
<i>correction-threshold</i>	(Optional) correction-threshold
<i>bs-status</i>	(Optional) Broadsync status enable/disable

## Command Mode

- /exec

# show ptp clock foreign-masters record

```
show ptp clock foreign-masters record [ interface <if0> ] [ __readonly__ { TABLE_ptp <interface-name>
<clock-id> <priority1> <priority2> <class> <accuracy> <scaled-log-variance> <steps-removed> <is-gm> }
<ptp-end> ]
```

## Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
clock	Set local clock attributes
foreign-masters	foreign-masters
record	record
<i>if0</i>	(Optional)
<i>__readonly__</i>	(Optional) Read only
<i>TABLE_ptp</i>	(Optional) ptp table
<i>interface-name</i>	(Optional) interface name
<i>clock-id</i>	(Optional) Clock Id
<i>priority1</i>	(Optional) Priority 1
<i>priority2</i>	(Optional) Priority 2
<i>class</i>	(Optional) Class
<i>accuracy</i>	(Optional) Clock accuracy
<i>scaled-log-variance</i>	(Optional) scaled log variance
<i>steps-removed</i>	(Optional) Steps removed
<i>is-gm</i>	(Optional) Is Grandmaster
<i>ptp-end</i>	(Optional) End of table

## Command Mode

- /exec

# show ptp corrections

```
show ptp corrections [ __readonly__ [ TABLE_ptp <intf-name> <sup-time> <correction-val>
<mean-path-delay> ] <ptp-end> ]
```

## Syntax Description

<code>ptp</code>	Precision Time Protocol (IEEE 1588) Subsystem
<code>__readonly__</code>	(Optional) Read Only
<code>corrections</code>	Display last few corrections
<code>TABLE_ptp</code>	(Optional) ptp table
<code>intf-name</code>	(Optional) interface name
<code>sup-time</code>	(Optional) sup time
<code>correction-val</code>	(Optional) correction value
<code>ptp-end</code>	(Optional) End of table

## Command Mode

- /exec

# show ptp cost

```
show ptp cost [ interface <if0> ] [ __readonly__ { TABLE_ptp <ptp-ifindex> <cost> } <ptp-end> ]
```

## Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
cost	port costs
<i>if0</i>	(Optional)
__readonly__	(Optional) Read Only
TABLE_ptp	(Optional) ptp table
<i>ptp-ifindex</i>	(Optional) ptp ifindex
<i>cost</i>	(Optional) cost
<i>ptp-end</i>	(Optional) End of table

## Command Mode

- /exec

## show ptp counters interface

```
show ptp counters { interface <if0> | all } [ { detail | ipv4 <ip> } ] [ __readonly__ [ TABLE_ptp
<interface_name> [ <accepted-ip> ] <tx-announce-pkts> <rx-announce-pkts> <tx-sync-pkts> <rx-sync-pkts>
<tx-follow-up-pkts> <rx-follow-up-pkts> <tx-delay-req-pkts> <rx-delay-req-pkts> <tx-delay-resp-pkts>
<rx-delay-resp-pkts> <tx-pdelay-req-pkts> <rx-pdelay-req-pkts> <tx-pdelay-resp-pkts> <rx-pdelay-resp-pkts>
<tx-pdelay-follow-up-pkts> <rx-pdelay-follow-up-pkts> <tx-mgmt-pkts> <rx-mgmt-pkts> ] <ptp-end> ]
```

### Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
__readonly__	(Optional) Read Only
counters	Display PTP packet counters
interface	Enter the port interface
all	Displays all information
<i>if0</i>	
detail	(Optional) Show detail
ipv4	(Optional) IP address for the stat info
<i>ip</i>	(Optional) IPv4 address (A.B.C.D)
TABLE_ptp	(Optional) ptp table
<i>interface_name</i>	(Optional) interface name
<i>accepted-ip</i>	(Optional) Accepted IP in unicast mode
<i>ptp-end</i>	(Optional) End of table

### Command Mode

- /exec

## show ptp domain data

```
show ptp domain data [ __readonly__ [ TABLE_ptp <multidom_cap> <gm_cap> <gm_convergence_time>
<def_dom> <transition_priority1> <transition_priority2> { TABLE_ptp_domain <domain_number>
<domain_priority> <ptp_clock_class_threshold> <ptp_clock_accuracy_threshold> <ptp-ifindex> } ] <ptp-end>
]
```

### Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp domain number
data	ptp domain data
__readonly__	(Optional) Read Only
TABLE_ptp	(Optional) ptp table
<i>multidom_cap</i>	(Optional) Multidomain state ENABLED/DISABLED
<i>gm_cap</i>	(Optional) GM state ENABLE/DISABLED
<i>gm_convergence_time</i>	(Optional) ptp grandmaster convergence time
<i>def_dom</i>	(Optional) ptp default domain
<i>transition_priority1</i>	(Optional) ptp multi-domain transition priority1
<i>transition_priority2</i>	(Optional) ptp multi-domain transition priority2
TABLE_ptp_domain	(Optional)
<i>domain_number</i>	(Optional) ptp domain number
<i>domain_priority</i>	(Optional) ptp domain priority
<i>ptp_clock_class_threshold</i>	(Optional) ptp domain class
<i>ptp_clock_accuracy_threshold</i>	(Optional) ptp domain accuracy
<i>ptp-ifindex</i>	(Optional) ptp ifindex
<i>ptp-end</i>	(Optional) End of table

### Command Mode

- /exec



## show ptp interface domain

show ptp interface domain [ *\_\_readonly\_\_* { *TABLE\_ptp* <ptp-ifindex> <interface-domain> } <ptp-end> ]

### Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
interface	port
domain	ptp port domain
<i>__readonly__</i>	(Optional) Read Only
<i>TABLE_ptp</i>	(Optional) ptp table
<i>ptp-ifindex</i>	(Optional) ptp ifindex
<i>interface-domain</i>	(Optional) ptp port domain
<i>ptp-end</i>	(Optional) End of table

### Command Mode

- /exec

# show ptp packet-trace

```
show ptp packet-trace [ __readonly__ [ TABLE_ptp <intf-name> <sup-time> <pkt_dir> <pkt_type> <pkt_info>
] <ptp-header> <ptp-end> ]
```

## Syntax Description

<code>ptp</code>	Precision Time Protocol (IEEE 1588) Subsystem
<code>__readonly__</code>	(Optional) Read Only
<code>packet-trace</code>	Display last few pkt traces
<code>TABLE_ptp</code>	(Optional) ptp table
<code>intf-name</code>	(Optional) interface name
<code>sup-time</code>	(Optional) sup time
<code>pkt_dir</code>	(Optional) pkt_dir
<code>pkt_type</code>	(Optional) pkt_type
<code>pkt_info</code>	(Optional) pkt_info
<code>ptp-header</code>	(Optional) Start of table
<code>ptp-end</code>	(Optional) End of table

## Command Mode

- /exec

# show ptp parent

```
show ptp parent [ __readonly__ <clock-id> <port-num> <obs-parent-offset> <obs-parent-clk-phase-chg> [
<parent-ip> ] <gm-id> <gm-class> <gm-accuracy> <gm-scaled-log-variance> <gm-priority1> <gm-priority2>
]
```

## Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
parent	parent clock
__readonly__	(Optional) Read only
<i>clock-id</i>	(Optional) Clock Id
<i>port-num</i>	(Optional) Port ID: port number
<i>obs-parent-offset</i>	(Optional) observed parent offset
<i>obs-parent-clk-phase-chg</i>	(Optional) observed parent clock phase change
<i>parent-ip</i>	(Optional) Parent clock IP
<i>gm-id</i>	(Optional) Grandmaster Id
<i>gm-class</i>	(Optional) Class
<i>gm-accuracy</i>	(Optional) Clock accuracy
<i>gm-scaled-log-variance</i>	(Optional) scaled log variance
<i>gm-priority1</i>	(Optional) GM Priority 1
<i>gm-priority2</i>	(Optional) GM Priority 2

## Command Mode

- /exec

# show ptp port interface

```
show ptp port interface <if0> [ __readonly__ <intf-name> <clock-id> <port-num> <version> <transport-mode>
<accepted-ip> <state> <vlan> <delay-req-intv> <ann-rx-tout> <peer-mean-path-delay> <ann-intv> <sync-intv>
<delay-mechanism> <peer-delay-req-intv> ]
```

## Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
port	port
interface	Enter the port interface
<i>if0</i>	
<i>__readonly__</i>	(Optional) Read only
<i>intf-name</i>	(Optional) interface name
<i>clock-id</i>	(Optional) Port ID: Clock Id
<i>port-num</i>	(Optional) Port ID: port number
<i>version</i>	(Optional) version
<i>transport-mode</i>	(Optional) Transport mode
<i>accepted-ip</i>	(Optional) Accepted IPs
<i>state</i>	(Optional) BMC state
<i>vlan</i>	(Optional) Vlan
<i>delay-req-intv</i>	(Optional) log mean delay req interval
<i>ann-rx-tout</i>	(Optional) announce receipt timeout
<i>peer-mean-path-delay</i>	(Optional) peer mean path delay
<i>ann-intv</i>	(Optional) announce interval
<i>sync-intv</i>	(Optional) sync interval
<i>delay-mechanism</i>	(Optional) delay mechanism
<i>peer-delay-req-intv</i>	(Optional) peer delay req interval

## Command Mode

- /exec

## show ptp time-property

```
show ptp time-property [ __readonly__ <current-utc-offset-valid> <current-utc-offset> <leap-59> <leap-61>
<time-traceable> <freq-traceable> <ptp-timescale> <time-source> ]
```

### Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
time-property	time property
<i>__readonly__</i>	(Optional) Read only
<i>current-utc-offset-valid</i>	(Optional) current_utc_offset_valid
<i>current-utc-offset</i>	(Optional) current_utc_offset
<i>leap-59</i>	(Optional) leap-59
<i>leap-61</i>	(Optional) leap-61
<i>time-traceable</i>	(Optional) time-traceable
<i>freq-traceable</i>	(Optional) freq-traceable
<i>ptp-timescale</i>	(Optional) ptp-timescale
<i>time-source</i>	(Optional) time-source

### Command Mode

- /exec

show ptp time-property