

## **New and Changed Information**

This chapter provides release-specific information for each new and changed feature in the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide, Release 6.x. The latest version of this document is available at the following Cisco website:

http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-installation-and-configuration-guides-list.html

To check for additional information, see the Cisco Nexus 3548 Switch NX-OS Release Notes, Release 6.x available at the following Cisco website:

http://www.cisco.com/c/en/us/support/switches/nexus-3000-series-switches/products-release-notes-list.html

• New and Changed Information, page 1

## **New and Changed Information**

Table below summarizes the new and changed features for the Cisco Nexus 3548 Switch NX-OS Unicast Routing Configuration Guide, Release 6.x, and tells you where they are documented.

Table 1: New and Changed Feature Information

Feature	Description	Changed in Release	Where Documented
Policy based routing	Added support for policy based routing.	6.0(2)A7(1)	Configuring Policy-Based Routing
Multiprotocol BGP	Added support for Multiprotocol BGP.	6.0(2)A7(1)	Multiprotocol BGP
BFD over OSPF	Added support for BFD over OSPFv2.	6.0(2)A6(4)	Configuring Bidirectional Forwarding Detection
BFD	Added information about support for BGP and PIM.	6.0(2)A4(1)	Configuring Bidirectional Forwarding Detection

Feature	Description	Changed in Release	Where Documented
BGP Additional Paths	Added information on how to configure BGP Additional Paths.	6.0(2)A1(1)	Configuring BGP Additional Paths
VRF Route Leaking	Added information on VRF-lite support for VRF route leaking. Included guidelines, limitations, and sample configurations.	6.0(2)A1(1)	Configuring Layer 3 Virtualization