

Send comments to nexus5k-docfeedback@cisco.com



T Commands

This chapter describes the Cisco NX-OS unicast Routing Information Base (RIB) and the Forwarding Information Base (FIB) commands that begin with T.

Send comments to nexus5k-docfeedback@cisco.com

test forwarding distribution perf

To test the forwarding distribution performance of the Forwarding Information Base (FIB), use the **test forwarding distribution perf** command.

test forwarding distribution perf

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes

Release	Modification
5.0(3)N1(1)	This command was introduced.

Examples This example shows how to test the forwarding distribution performance:

```
switch# test forwarding distribution perf
```

Related Commands	Command	Description
	show forwarding distribution	Displays information about the FIB.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

test forwarding inconsistency

To trigger the Layer 3 inconsistency checker for the Forwarding Information Base (FIB), use the **test forwarding inconsistency** command.

```
test forwarding inconsistency [ip | ipv4] [unicast] [vrf vrf-name] [module {slot | all}] [stop]
```

Syntax Description		
ip	(Optional)	Specifies the inconsistency check for IPv4 routes.
ipv4	(Optional)	Specifies the inconsistency check for IPv4 routes.
unicast	(Optional)	Specifies the inconsistency check for unicast routes.
vrf vrf-name	(Optional)	Specifies the virtual routing and forwarding (VRF) context name. The name can be any case-sensitive, alphanumeric string up to 32 characters.
module	(Optional)	Specifies the inconsistency check for one or more modules.
<i>slot</i>		Module number. The range depends on the platform.
all	(Optional)	Specifies the inconsistency check for all modules.
stop	(Optional)	Stops the inconsistency check.

Command Default None

Command Modes

Release	Modification
5.0(3)N1(1)	This command was introduced.

Examples

This example shows how to trigger the Layer 3 inconsistency checker for all modules:

```
switch# test forwarding inconsistency module all
```

This example shows how to stop the Layer 3 inconsistency checker for all modules:

```
switch# test forwarding inconsistency module all stop
```

Related Commands

Command	Description
clear forwarding inconsistency	Clears the FIB inconsistencies.
show forwarding inconsistency	Displays information about the FIB inconsistencies.

Send comments to nexus5k-docfeedback@cisco.com