



Show Commands

This chapter describes the Cisco NX-OS Fibre Channel, virtual Fibre Channel, and Fibre Channel over Ethernet (FCoE) **show** commands.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show cfs

To display Cisco Fabric Services (CFS) information, use the **show cfs** command.

```
show cfs { application [name app-name] | lock [name app-name [vsan vsan-id]] | merge status
          [name app-name [vsan vsan-id]] | peers [name app-name [vsan vsan-id]] | regions | status }
```

Syntax Description

application	Displays locally registered applications.
name <i>app-name</i>	(Optional) Specifies a local application information by name. The name can be a maximum of 64 characters.
lock	Displays the state of application logical or physical locks.
vsan <i>vsan-id</i>	(Optional) Specifies the VSAN ID. The range is from 1 to 4093.
merge status	Displays CFS merge information.
peers	Displays logical or physical CFS peers.
regions	Displays the CFS regions.
status	Displays if CFS distribution is enabled or disabled. Enabled is the default configuration.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Usage Guidelines

The **show cfs application** command displays only those applications that are registered with CFS. Conditional services that use CFS do not appear in the output unless those services are running.

Examples

This example shows how to display the CFS physical peer information for all applications:

```
switch# show cfs peers
```

This example shows how to display the CFS information for all applications on the switch:

```
switch# show cfs application
```

This example shows how to display the status of the CFS distribution:

```
switch# show cfs status
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command

Description

cfs

Configures Cisco Fabric Services (CFS) information.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show debug npv

To display the N Port Virtualization (NPV) debug commands configured on the switch, use the **show debug npv** command.

```
show debug npv
```

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The **show debug npv** command is available only when the switch is in NPV mode.

Examples This example shows how to display all the NPV debug commands available on the switch:

```
switch# show debug npv
```

Related Commands	Command	Description
	debug npv	Enables the debugging of NPV configurations.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show device-alias

To display the device name information, use the **show device-alias** command.

```
show device-alias { database | merge status | name device-name [pending] | pending |
pending-diff | pwwn pwwn-id [pending] | session status | statistics | status }
```

Syntax Description		
database		Displays the entire device name database.
merge status		Displays the device merge status.
name <i>device-name</i>		Displays device name database information for a specific device name.
pending		(Optional) Displays the pending device name database information.
pending-diff		Displays pending differences in the device name database information.
pwwn <i>pwwn-id</i>		Displays device name database information for a specific pWWN. The format is <i>hh:hh:hh:hh:hh:hh:hh:hh</i> , where <i>h</i> is a hexadecimal digit.
session status		Displays the device name session status.
statistics		Displays device name database statistics.
status		Displays the device name database status.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines To use fcalias as device names instead of using the cryptic device name, add only one member per fcalias.

Examples This example shows how to display the contents of the device alias database:

```
switch# show device-alias database
```

This example shows how to display all global fcalias and all Virtual SAN (VSAN) dependent fcalias:

```
switch# show device-alias name efg
```

This example shows how to display all global fcalias and all VSAN dependent fcalias:

```
switch# show device-alias statistics
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands	Command	Description
	device-alias name	Configures device alias names.
	device-alias database	Configures device alias information.
	device-alias distribute	Enables device alias CFS distribution.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fabric-binding

To display configured fabric binding information, use the **show fabric-binding** command.

```
show fabric-binding { database [active] [vsan vsan-id] | efmd statistics [vsan vsan-id] | statistics [vsan vsan-id] | status [vsan vsan-id] | violations [last number] }
```

Syntax Description		
database		Displays configured database information.
active		(Optional) Displays the active database configuration information.
vsan <i>vsan-id</i>		(Optional) Specifies the FICON-enabled Virtual SAN (VSAN) ID. The range is from 1 to 4093.
efmd statistics		Displays Exchange Fabric Membership Data (EFMD) statistics.
statistics		Displays fabric binding statistics.
status		Displays fabric binding status.
violations		Displays violations in the fabric binding configuration.
last number		(Optional) Specifies recent violations. The range is from 1 to 100.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the configured fabric binding database information:

```
switch# show fabric-binding database
```

This example shows how to display the active fabric binding information:

```
switch# show fabric-binding database active
```

This example shows how to display the active VSAN-specific fabric binding information:

```
switch# show fabric-binding database active vsan 61
```

This example shows how to display the configured VSAN-specific fabric binding information:

```
switch# show fabric-binding database vsan 4
```

This example shows how to display the fabric binding statistics:

```
switch# show fabric-binding statistics
```

This example shows how to display the fabric binding status for each VSAN:

```
switch# show fabric-binding status
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the EFMD statistics:

```
switch# show fabric-binding efmd statistics
```

This example shows how to display the EFMD statistics for a specified VSAN:

```
switch# show fabric-binding efmd statistics vsan 4
```

This example shows how to display the fabric binding violations:

```
switch# show fabric-binding violations
```

Related Commands

Command	Description
fabric-binding	Configures fabric binding in a VSAN.

Send comments to nexus5k-docfeedback@cisco.com

show fc2

To display FC2 information, use the **show fc2** command.

```
show fc2 { bind | classf | exchange | exchresp | flogi | nport | plogi | plogi_pwwn | port [brief] |
socket | sockexch | socknotify | socknport | vsan }
```

Syntax Description

bind	Displays FC2 socket bindings.
classf	Displays FC2 classf sessions.
exchange	Displays FC2 active exchanges.
exchresp	Displays FC2 active responder exchanges.
flogi	Displays FC2 FLOGI table.
nport	Displays FC2 local N ports.
plogi	Displays FC2 PLOGI sessions.
plogi_pwwn	Displays FC2 PLOGI pWWN entries.
port	Displays FC2 physical port table.
brief	(Optional) Displays FC2 physical port table in a brief format.
socket	Displays FC2 active sockets.
sockexch	Displays FC2 active exchanges for each socket.
socknotify	Displays FC2 local N port PLOGI/LOGO notifications for each socket.
socknport	Displays FC2 local nports per each socket.
vsan	Displays the FC2 VSAN table.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the FC2 active socket information:

```
switch# show fc2 socket
```

This example shows how to display the FC2 socket binding information:

```
switch# show fc2 bind
```

This example shows how to display the FC2 local N port information:

```
switch# show fc2 nport
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the FC2 PLOGI session information:

```
switch# show fc2 plogi
```

This example shows how to display the FC2 physical port information:

```
switch# show fc2 port
```

This example shows how to display the FC2 local N port PLOGI notifications for each socket:

```
switch# show fc2 socknotify
```

This example shows how to display the FC2 local N ports for each socket:

```
switch# show fc2 socknport
```

This example shows how to display the FC2 VSAN table:

```
switch# show fc2 vsan
```

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fc-port-security

To display configured port security feature information, use the **show fc-port-security** command.

```
show fc-port-security { database [active [vsan vsan-id]] | fwwn fwwn-id vsan vsan-id | interface
  { fc slot/port | san-port-channel port } vsan vsan-id | vsan vsan-id | pending [vsan vsan-id] |
  pending-diff [vsan vsan-id] | session status [vsan vsan-id] | statistics [vsan vsan-id] | status
  [vsan vsan-id] | violations [last count | vsan vsan-id] }
```

Syntax Description		
database		Displays database-related port security information.
active		(Optional) Displays the activated database information.
vsan <i>vsan-id</i>		(Optional) Displays information for the specified database.
fwwn <i>fwwn-id</i>		Displays information for the specified fabric WWN.
interface		Displays information for an interface.
fc <i>slot/port</i>		Displays information for the specified Fibre Channel interface.
san-port-channel <i>port</i>		Displays information for the specified SAN port channel interface. The range is from 1 to 128.
pending		Displays the server address pending configuration.
pending-diff		Displays the server address pending configuration differences with the active configuration.
session status		Displays the port security session status on a per VSAN basis.
statistics		Displays port security statistics.
status		Displays the port security status on a per VSAN basis.
violations		Displays violations in the port security database.
last <i>count</i>		(Optional) Displays the last number of lines in the database. The range is from 1 to 100.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The access information for each port can be individually displayed. If you specify the fabric world wide name (fWWN) or interface options, all devices that are paired in the active database (at that point) with the given fWWN or the interface are displayed.

When you enter the **show fc-port-security** command with the **last** *number* option, only the specified number of entries that appear first are displayed.

Send comments to nexus5k-docfeedback@cisco.com

Examples

This example shows how to display the contents of the port security database:

```
switch# show fc-port-security database
```

This example shows how to display the output of the active port security database in VSAN 1:

```
switch# show fc-port-security database vsan 1
```

This example shows how to display the active database:

```
switch# show fc-port-security database active
```

This example shows how to display the wildcard fWWN port security in VSAN 1:

```
switch# show fc-port-security database fwwn 20:85:00:44:22:00:4a:9e vsan 1
```

This example shows how to display the configured fWWN port security in VSAN 1:

```
switch# show fc-port-security database fwwn 20:01:00:05:30:00:95:de vsan 1
```

This example shows how to display the interface port information in VSAN 2:

```
switch# show fc-port-security database interface fc 2/1 vsan 2
```

This example shows how to display the port security statistics:

```
switch# show fc-port-security statistics
```

This example shows how to display the status of the active database and the autolearn configuration:

```
switch# show fc-port-security status
```

This example shows how to display the previous 100 violations:

```
switch# show fc-port-security violations
```

Related Commands

Command	Description
fc-port-security	Configures port security parameters.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcalias

To display the member name information in a Fibre Channel alias (fcalias), use the **show fcalias** command.

```
show fcalias [name fcalias-name] [pending] [vsan vsan-id]
```

Syntax Description

name <i>fcalias-name</i>	(Optional) Displays fcalias information for a specific name. The maximum length is 64.
pending	(Optional) Displays pending fcalias information.
vsan <i>vsan-id</i>	(Optional) Displays fcalias information for a VSAN. The range is from 1 to 4093.

Command Default

Displays a list of all global fcaliases and all VSAN-dependent fcaliases.

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Usage Guidelines

To make use of fcaliases as device names instead of using the cryptic device name, add only one member per fcalias.

Examples

This example shows how to display the fcalias configuration information:

```
switch# show fcalias vsan 1
```

Related Commands

Command	Description
fcalias name	Configures fcalias names.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcdomain

To display the Fibre Channel domain (fcdomain) information, use the **show fcdomain** command.

```
show fcdomain [address-allocation [cache] | allowed | domain-list | fcid persistent [unused] |
pending [vsan vsan-id] | pending-diff [vsan vsan-id] | session-status [vsan vsan-id] | statistics
[interface { fc slot/port [vsan vsan-id] } | san-port-channel port [vsan vsan-id]] | status | vsan
vsan-id]
```

Syntax	Description
address-allocation	(Optional) Displays statistics for the FC ID allocation.
cache	(Optional) Reassigns the FC IDs for a device (disk or host) that exited and reentered the fabric for the principal switch. In the cache content, Virtual SAN (VSAN) refers to the VSAN that contains the device, WWN refers to the device that owned the FC IDs, and mask refers to a single or entire area of FC IDs.
allowed	(Optional) Displays a list of allowed domain IDs.
domain-list	(Optional) Displays a list of domain IDs provided by the principal switch.
fcid persistent	(Optional) Displays persistent FC IDs (across reboot).
unused	(Optional) Displays unused persistent FCIDs (across reboot).
pending	(Optional) Displays the pending configuration.
vsan vsan-id	(Optional) Specifies a VSAN ID. The range is from 1 to 4093.
pending-diff	(Optional) Displays the difference between the running configuration and the pending configuration.
session-status	(Optional) Displays the last action performed by an FC domain.
statistics	(Optional) Displays the statistics of an FC domain.
interface	(Optional) Specifies an interface.
fc slot/port	(Optional) Specifies a Fibre Channel interface.
san-port-channel port	(Optional) Specifies a SAN port channel interface. The range is from 1 to 128.
status	(Optional) Displays all VSAN-independent information in an FC domain.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines When you enter the **show fcdomain** with no arguments, all VSANs appear. The VSANs should be active or you will get an error.

Send comments to nexus5k-docfeedback@cisco.com

Examples

This example shows how to display the fcdomain information for VSAN 1:

```
switch# show fcdomain vsan 1
```

This example shows how to display the fcdomain domain-list information for VSAN 76:

```
switch# show fcdomain domain-list vsan 76
```

```
Number of domains: 3
Domain ID          WWN
-----
0xc8(200)         20:01:00:05:30:00:47:df [Principal]
0x63(99)          20:01:00:0d:ec:08:60:c1 [Local]
0x61(97)          50:00:53:0f:ff:f0:10:06 [Virtual (IVR)]
```

Table 1 describes the significant fields shown in the **show fcdomain domain-list** command output.

Table 1 *show fcdomain Field Descriptions*

Field	Description
Domain ID	Lists the domain IDs corresponding to the WWN.
WWN	Indicates the WWN of the switch (physical or virtual) that requested the corresponding domain ID.
Principal	Indicates which row of the display lists the WWN and domain ID of the principal switch in the VSAN.
Local	Indicates which row of the display lists the WWN and domain ID of the local switch (the switch where you entered the show fcdomain domain-list command).
Virtual (IVR)	Indicates which row of the display lists the WWN of the virtual switch used by the Inter-VSAN Routing (IVR) manager to obtain the domain ID.

This example shows how to display the allowed domain ID lists:

```
switch# show fcdomain allowed vsan 1
```

This example shows how to display the status of the CFS distribution for allowed domain ID lists:

```
switch# show fcdomain status
```

This example shows how to display the pending configuration changes:

```
switch# show fcdomain pending vsan 10
```

This example shows how to display the differences between the pending configuration and the current configuration:

```
switch# show fcdomain pending-diff vsan 10
```

This example shows how to display the status of the distribution session:

```
switch# show fcdomain session-status vsan 1
```

Related Commands

Command	Description
fcdomain	Configures the Fibre Channel domain feature.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcdroplateny

To display the configured Fibre Channel latency parameters, use the **show fcdroplateny** command.

```
show fcdroplateny [network | switch]
```

Syntax Description	network	(Optional) Displays the network latency in milliseconds.
	switch	(Optional) Displays the switch latency in milliseconds.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the configured Fibre Channel latency parameters:

```
switch# show fcdroplateny
```

Related Commands	Command	Description
	fcdroplateny	Configures the network and switch Fibre Channel drop latency time.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcflow stats

To display the configured Fibre Channel flow (fcflow) information, use the **show fcflow stats** command.

```
show fcflow stats [aggregated | usage] [index flow-index]
```

Syntax Description	aggregated	(Optional) Displays aggregated fcflow statistics.
	usage	(Optional) Displays flow index usage.
	index <i>flow-index</i>	(Optional) Specifies an fcflow index.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the aggregated fcflow details:

```
switch# show fcflow stats aggregated
```

This example shows how to display the fcflow details:

```
switch# show fcflow stats
```

This example shows how to display the fcflow index usage:

```
switch# show fcflow stats usage
```

Related Commands	Command	Description
	fcflow stats	Configures fcflow statistics.

Send comments to nexus5k-docfeedback@cisco.com

show fcid-allocation

To display the Fibre Channel area list of company IDs, use the **show fcid allocation** command.

```
show fcid-allocation area | company-id-from-wwn wwn [company-id]
```

Syntax Description	area	Displays the auto area list of company IDs.
	company-id-from-wwn <i>wwn</i>	Displays the company ID from the specified world wide name (WWN).
	<i>company-id</i>	(Optional) Company ID (also know as Organizational Unit Identifier, or OUI) to display.

Command Default	None
-----------------	------

Command Modes	EXEC mode
---------------	-----------

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the Fibre Channel area company list of company IDs:

```
switch# show fcid-allocation area
Fcid area allocation company id info:
```

```
00:50:2E
00:50:8B
00:60:B0
00:A0:B8
00:E0:69
00:E0:8B
00:32:23 +
```

```
Total company ids: 7
+ - Additional user configured company ids.
* - Explicitly deleted company ids from default list.
```

[Table 2](#) describes the significant fields shown in the display.

Table 2 *show fcid-allocation area company Field Descriptions*

Field	Description
+	Indicates a company ID added to the default list.
-	Indicates a company ID deleted from the default list.

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
fcid-allocation	Adds a FCID to the default area company ID list.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcns database

To display the results of the discovery, or to display the name server database for a specified Virtual SAN (VSAN) or for all VSANs, use the **show fcns database** command.

```
show fcns database { detail [vsan vsan-id] | domain domain-id [detail] [vsan vsan-range] | fcid
fcid-id [detail] vsan vsan-range | local [detail] [vsan vsan-range] | vsan vsan-id }
```

Syntax Description

detail	Displays all objects in each entry.
vsan <i>vsan-id</i>	(Optional) Displays entries for a specified VSAN ID. The range is from 1 to 4093.
domain <i>domain-id</i>	Displays entries in a domain.
detail	(Optional) Displays detailed entries for the domain.
fcid <i>fcid-id</i>	Displays entry for the given port.
local	Displays local entries.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Usage Guidelines

The discovery can take several minutes to complete, especially if the fabric is large or if several devices are slow to respond.

Virtual enclosure ports can be viewed using the **show fcns database** command.

Examples

This example shows how to display the contents of the FCNS database:

```
switch# show fcns database
```

This example shows how to display the detailed contents of the FCNS database:

```
switch# show fcns database detail
```

This example shows how to display the management VSAN (VSAN 2):

```
switch# show fcns database vsan 2
```

This example shows how to display the database for all configured VSANs:

```
switch# show fcns database
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands	Command	Description
	fcns	Specifies the configuration mode command for name server configuration.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcns statistics

To display the statistical information for a specified Virtual SAN (VSAN) or for all VSANs, use the **show fcns statistics** command.

```
show fcns statistics [detail] [vsan vsan-id]
```

Syntax Description	detail	(Optional) Displays detailed statistics.
	vsan vsan-id	(Optional) Displays statistics for the specified VSAN ID. The range is from 1 to 4093.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the statistical information for a specified VSAN:

```
switch# show fcns statistics
```

Related Commands	Command	Description
	fcns	Specifies the configuration mode command for name server configuration.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcoe

To display the status of Fibre Channel over Ethernet (FCoE) parameters on the switch, use the **show fcoe** command.

show fcoe

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the FCoE status:

```
switch# show fcoe
Global FCF details
  FCF-MAC is 00:0d:ec:a3:9d:80
  FCF-MAP is 0e:fc:00
  FCF Priority is 128
  FKA Advertisement period for FCF is 8 seconds
switch#
```

Related Commands	Command	Description
	fcoe fcf-priority	Configures the FCoE Initialization Protocol (FIP) priority value.
	fcoe fcmapi	Configures the FCoE MAC Address Prefix (FC MAP) used to associate the FCoE node (ENode).
	fcoe fka-adv-period	Configures the time interval at which FIP keep alive (FKA) messages are transmitted to the MAC address of the ENode.
	show fcoe database	Displays the FCoE database information.

Send comments to nexus5k-docfeedback@cisco.com

show fcoe-npv issu-impact

To display the configuration issues caused by the Fibre Channel over Ethernet (FCoE) N-Port Virtualizer (NPV) during a nondisruptive in-service software upgrade (ISSU), use the **show fcoe-npv issu-impact** command.

show fcoe-npv issu-impact

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines Before you use this command, make sure that you enable Fibre Channel over Ethernet (FCoE) N-Port Virtualizer (NPV) on the switch by using the **feature fcoe-npv** command.

This command requires the FCoE NPV license.

Examples This example shows how to display the configuration issues caused by the FCoE NPV feature:

```
switch# show fcoe-npv issu-impact
show fcoe-npv issu-impact
-----
```

```
Please make sure to enable "disable-fka" on all logged in VFCs
Please increase the FKA duration to 60 seconds on FCF
```

```
Active VNP ports with no disable-fka set
-----
```

```
ISSU downgrade not supported as feature fcoe-npv is enabled
switch#
```

Related Commands	Command	Description
	feature fcoe-npv	Enables FCoE NPV on the switch.

Send comments to nexus5k-docfeedback@cisco.com

Command	Description
show running-config fcoe_mgr	Displays the FCoE running configuration information.
show tech-support fcoe	Displays troubleshooting information about FCoE.

Send comments to nexus5k-docfeedback@cisco.com

show fcoe database

To display information about the Fibre Channel over Ethernet (FCoE) database, use the **show fcoe database** command.

show fcoe database

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the FCoE database:

```
switch# show fcoe database
```

```
-----
INTERFACE          FCID          PORT NAME      MAC ADDRESS
-----
vfc1                0x580016     10:00:00:00:07:f8:0e:45 00:00:00:13:05:01
vfc1                0x580017     10:00:00:00:07:f8:21:bf 00:00:00:13:05:01
vfc2                0x580020     10:00:00:00:07:f8:0e:46 00:00:00:13:05:02
vfc2                0x580033     10:00:00:00:07:f8:21:c0 00:00:00:13:05:02
vfc4                0x58001e     10:00:00:00:07:f8:0e:48 00:00:00:13:05:04
vfc4                0x580031     10:00:00:00:07:f8:21:c2 00:00:00:13:05:04
vfc5                0x58001d     10:00:00:00:07:f8:0e:49 00:00:00:13:05:05
vfc5                0x580030     10:00:00:00:07:f8:21:c3 00:00:00:13:05:05
vfc6                0x58001c     10:00:00:00:07:f8:0e:4a 00:00:00:13:05:06
vfc6                0x58002f     10:00:00:00:07:f8:21:c4 00:00:00:13:05:06
vfc7                0x58001b     10:00:00:00:07:f8:0e:4b 00:00:00:13:05:07
vfc7                0x58002e     10:00:00:00:07:f8:21:c5 00:00:00:13:05:07
vfc8                0x58001a     10:00:00:00:07:f8:0e:4c 00:00:00:13:05:08
vfc8                0x58002d     10:00:00:00:07:f8:21:c6 00:00:00:13:05:08
vfc9                0x580019     10:00:00:00:07:f8:0e:4d 00:00:00:13:05:09
vfc9                0x58002c     10:00:00:00:07:f8:21:c7 00:00:00:13:05:09
vfc10               0x580018     10:00:00:00:07:f8:0e:4e 00:00:00:13:05:0a
vfc10               0x58002a     10:00:00:00:07:f8:21:c8 00:00:00:13:05:0a
vfc11               0x580023     10:00:00:00:07:f8:0e:4f 00:00:00:13:05:0b
vfc11               0x580036     10:00:00:00:07:f8:21:c9 00:00:00:13:05:0b
vfc12               0x580022     10:00:00:00:07:f8:0e:50 00:00:00:13:05:0c
vfc12               0x580035     10:00:00:00:07:f8:21:ca 00:00:00:13:05:0c
vfc13               0x580021     10:00:00:00:07:f8:0e:51 00:00:00:13:05:0d
vfc13               0x580034     10:00:00:00:07:f8:21:cb 00:00:00:13:05:0d
vfc14               0x58002b     10:00:00:00:07:f8:0e:52 00:00:00:13:05:0e
vfc14               0x58003d     10:00:00:00:07:f8:21:cc 00:00:00:13:05:0e
vfc15               0x580029     10:00:00:00:07:f8:0e:53 00:00:00:13:05:0f
vfc15               0x58003c     10:00:00:00:07:f8:21:cd 00:00:00:13:05:0f
-----
```

Send comments to nexus5k-docfeedback@cisco.com

```

vfc16          0x580028          10:00:00:00:07:f8:0e:54 00:00:00:13:05:10
vfc16          0x58003b          10:00:00:00:07:f8:21:ce 00:00:00:13:05:10
vfc17          0x580027          10:00:00:00:07:f8:0e:55 00:00:00:13:05:11
vfc17          0x580039          10:00:00:00:07:f8:21:cf 00:00:00:13:05:11
vfc18          0x580026          10:00:00:00:07:f8:0e:56 00:00:00:13:05:12
vfc18          0x58003a          10:00:00:00:07:f8:21:d0 00:00:00:13:05:12
vfc19          0x580025          10:00:00:00:07:f8:0e:57 00:00:00:13:05:13
vfc19          0x580038          10:00:00:00:07:f8:21:d1 00:00:00:13:05:13
vfc20          0x580024          10:00:00:00:07:f8:0e:58 00:00:00:13:05:14
switch#

```

Related Commands

Command	Description
fcoe fcf-priority	Configures the FCoE Initialization Protocol (FIP) priority value.
fcoe fcmap	Configures the FCoE MAC Address Prefix (FC MAP) used to associate the FCoE node (ENode).
fcoe fka-adv-period	Configures the time interval at which FIP keep alive (FKA) messages are transmitted to the MAC address of the ENode.
show fcoe	Displays the status of the FCoE parameters.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcroute

To view specific information about existing Fibre Channel and Fabric Shortest Path First (FSPF) configurations, use the **show fcroute** command.

```
show fcroute {distance | label [label] vsan vsan-id | multicast [fc-id vsan vsan-id | vsan vsan-id]
| summary [vsan vsan-id] | unicast [[host] fc-id fc-mask vsan vsan-id | vsan vsan-id] }
```

Syntax Description	Parameter	Description
	distance	Displays the FC route preference.
	label	Displays label routes.
	<i>label</i>	(Optional) Label routes for the specified label.
	vsan <i>vsan-id</i>	(Optional) Specifies the ID of the VSAN (from 1 to 4093).
	multicast	Displays FC multicast routes.
	<i>fc-id</i>	(Optional) Fibre Channel ID.
	summary	Displays the FC routes summary.
	unicast	Displays FC unicast routes.
	<i>host</i>	Unicast routes for the specified host.
	<i>fc-mask</i>	Unicast routes for hosts that match the range of FCIDs that are specified by the mask.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines When the number of routes are displayed in the command output, both visible and hidden routes are included in the total number of routes.

Examples This example shows how to display the administrative distance:

```
switch# show fcroute distance
```

This example shows how to display the multicast routing information:

```
switch# show fcroute multicast
```

This example shows how to display the FCID information for a specified VSAN:

```
switch# show fcroute multicast vsan 3
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the FCID and interface information for a specified VSAN:

```
switch# show fcroute multicast 0xffffffff vsan 2
```

This example shows how to display the unicast routing information:

```
switch# show fcroute unicast
```

This example shows how to display the unicast routing information for a specified VSAN:

```
switch# show fcroute unicast vsan 4
```

This example shows how to display the unicast routing information for a specified FCID:

```
switch# show fcroute unicast 0x040101 0xffffffff vsan 4
```

This example shows how to display the route database information:

```
switch# show fcroute summary
```

This example shows how to display the route database information for a specified VSAN:

```
switch# show fcroute summary vsan 4
```

Related Commands

Command	Description
<code>fcroute</code>	Configures Fibre Channel routes and activates policy routing.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcs

To display the status of the fabric configuration, use the **show fcs** commands.

```
show fcs { database [vsan vsan-id] | ie [nwwn wwn | vsan vsan-id] | platform { name string | vsan
vsan-id } | port { pwwn wwn | vsan vsan-id } | statistics vsan vsan-id | vsan }
```

Syntax Description

database	Displays local database of frame check sequence (FCS).
vsan <i>vsan-id</i>	(Optional) Specifies a Virtual SAN (VSAN) ID. The range is from 1 to 4093.
ie	Displays interconnect element objects information.
nwwn <i>wwn</i>	(Optional) Specifies a node WWN ID. The format is <i>hh:hh:hh:hh:hh:hh:hh:hh</i> .
platform	Displays platform objects information.
name <i>string</i>	(Optional) Specifies a platform name. The name can be a maximum of 255 characters.
port	Displays port objects information.
pwwn <i>wwn</i>	Specifies a port WWN ID. The format is <i>hh:hh:hh:hh:hh:hh:hh:hh</i> .
statistics	Displays statistics for FCS packets.
vsan	Displays list of all the VSANs.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the FCS database information:

```
switch# show fcs database
```

This example shows how to display the interconnect element object information for a specific VSAN:

```
switch# show fcs ie vsan 1
```

This example shows how to display the interconnect element object information for a specific WWN:

```
switch# show fcs ie nwwn 20:01:00:05:30:00:16:df vsan 1
```

This example shows how to display the platform information:

```
switch# show fcs platform name SamplePlatform vsan 1
```

This example shows how display to the platform information within a specified VSAN:

```
switch# show fcs platform vsan 1
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the FCS port information within a specified VSAN:

```
switch# show fcs port vsan 24
```

This example shows how to display the ports within a specified WWN:

```
switch# show fcs port pwwn 20:51:00:05:30:00:16:de vsan 24
```

This example shows how to display the FCS statistics:

```
switch# show fcs statistics
```

Related Commands

Command	Description
<code>fcs</code>	Configures FCS platform attributes.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fcsp

To display the status of the Fibre Channel Security Protocol (FC-SP) configuration, use the **show fcsp** commands.

```
show fcsp [asciiwn ascii-wwn | dhchap [database] | interface {fc slot/port | vfc vfc-id} [statistics
| wwn]]
```

Syntax Description

asciiwn <i>ascii-wwn</i>	(Optional) Displays the ASCII representation of the WWN used with authentication, authorization, and accounting (AAA) server.
dhchap	(Optional) Displays the DHCHAP hash algorithm status.
database	(Optional) Displays the contents of the local DHCHAP database.
interface	(Optional) Displays the FC-SP settings for a Fibre Channel or Fibre Channel interface.
fc <i>slot/port</i>	Specifies a Fibre Channel interface.
vfc <i>vfc-id</i>	(Optional) Specifies a virtual Fibre Channel interface.
statistics	(Optional) Displays the statistics for the specified interface.
wwn	(Optional) Displays the FC-SP identity of the other device.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the DHCHAP configurations in FC interfaces:

```
switch# show fcsp interface fc2/3
```

This example shows how to display the DHCHAP statistics for an FC interface:

```
switch# show fcsp interface fc2/3 statistics
```

This example shows how to display the FC-SP WWN of the device connected through a specified interface:

```
switch# show fcsp interface fc 2/1 wwn
```

This example shows how to display the hash algorithm and DHCHAP groups configured for the local switch:

```
switch# show fcsp dhchap
```

This example shows how to display the DHCHAP local password database:

```
switch# show fcsp dhchap database
```


Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the ASCII representation of the device WWN:

```
switch# show fcsp asciiwwn 30:11:bb:cc:dd:33:11:22
```

Related Commands

Command	Description
fcsp enable	Enables the FC-SP feature for this switch.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fctimer

To display the Fibre Channel timers (fctimer), use the **show fctimer** command.

```
show fctimer [d_s_tov [vsan vsan-id] | e_d_tov [vsan vsan-id] | f_s_tov [vsan vsan-id] | r_a_tov
[vsan vsan-id] | last action status | pending | pending-diff | session status | status | vsan
vsan-id]
```

Syntax Description		
d_s_tov	(Optional) Displays the distributed services time out value (D_S_TOV) in milliseconds.	
vsan vsan-id	(Optional) Displays information for a Virtual SAN (VSAN). The range is from 1 to 4093.	
e_d_tov	(Optional) Displays the error detection timeout value (E_D_TOV) in milliseconds.	
f_s_tov	(Optional) Displays the fabric stability timeout value (F_S_TOV) in milliseconds.	
r_a_tov	(Optional) Displays the resource allocation time out value (R_A_TOV) in milliseconds.	
last action status	(Optional) Displays the status of the last Cisco Fabric Services (CFS) commit or discard operation.	
pending	(Optional) Displays the status of pending fctimer commands.	
pending-diff	(Optional) Displays the difference between the pending database and running configuration.	
session status	(Optional) Displays the state of the fctimer CFS session.	
status	(Optional) Displays the Fibre Channel timer status.	

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the configured global TOVs:

```
switch# show fctimer
```

This example shows how to display the configured TOVs for a specified VSAN:

```
switch# show fctimer vsan 10
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
fctimer	Configures fctimer parameters.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fDMI

To display the Fabric-Device Management Interface (FDMI) database information, use the **show fDMI** command.

```
show fDMI database [detail [hba-id {hba-id vsan vsan-id} | vsan vsan-id] | vsan vsan-id] |
suppress-updates
```

Syntax	Description
database	Displays the FDMI database contents.
detail	(Optional) Specifies detailed FDMI information.
hba-id <i>hba-id</i>	(Optional) Displays detailed information for the specified host bus adapter (HBA) entry.
vsan <i>vsan-id</i>	(Optional) Specifies FDMI information for the specified Virtual SAN (VSAN). The range is from 1 to 4093.
suppress-updates	Displays the VSANs that are configured to suppress updates.

Command Default	None
-----------------	------

Command Modes	EXEC mode
---------------	-----------

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display all HBA management servers:

```
switch# show fDMI database
```

This example shows how to display the VSAN1-specific FDMI information:

```
switch# show fDMI database detail vsan 1
```

This example shows how to display the details for the specified HBA entry:

```
switch# show fDMI database detail Hba-id 21:01:00:e0:8b:2a:f6:54 vsan 1
```

Related Commands	Command	Description
	fDMI suppress-updates	Suppresses FDMI updates.

Send comments to nexus5k-docfeedback@cisco.com

show fex

To display information about a specific Fabric Extender or all attached chassis, use the **show fex** command.

```
show fex [chassis_ID [detail]]
```

Syntax Description	
<i>chassis_ID</i>	(Optional) Fabric Extender chassis ID. The chassis ID range is from 100 to 199.
detail	(Optional) Displays a detailed listing.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display information about all attached Fabric Extender chassis:

```
switch# show fex
FEX          FEX          FEX          FEX
Number      Description    State         Model         Serial
-----
100         FEX0100       Online        N5K-C5110T-BF-1GE  JAF1237ABSE
101         FEX0101       Online        N2K-C2248TP-1GE   JAF11223333
102         FEX0102       Online        N5K-C5110T-BF-1GE  JAF1241BLHQ
105         FEX0105       Online        N2K-C2232P-10GE   JAF1331AKBM
switch#
```

This example shows how to display information about a specific Fabric Extender chassis:

Need new output

```
switch# show fex 101
FEX: 101 Description: FEX0101 state: Online
  FEX version: 4.2(1)N1(1) [Switch version: 4.2(1)N1(1)]
  Extender Model: N2K-C2248TP-1GE, Extender Serial: JAF11223333
  Part No: 73-12748-01
  pinning-mode: static Max-links: 1
  Fabric port for control traffic: Eth3/5
  Fabric interface state:
    Po5 - Interface Up. State: Active
    Eth3/5 - Interface Up. State: Active
    Eth3/6 - Interface Up. State: Active
switch#
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands	Command	Description
	fex	Creates a Fabric Extender and enters fabric extender configuration mode.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show flogi

To list all the fabric login (FLOGI) sessions through all interfaces across all Virtual SAN (VSANs), use the **show flogi** command.

```
show flogi {auto-area-list} | database {fcid fcid-id | interface {fc slot/port | vfc vfc-id} | vsan
vsan-id}
```

Syntax Description		
auto-area-list		Displays the list of Organizational Unit Identifiers (OUIs) that are allocated areas.
database		Displays information about FLOGI sessions.
fcid <i>fcid-id</i>		Displays FLOGI database entries based on the FCID allocated. The format is <i>0xhhhhhh</i> .
interface		Displays FLOGI database entries based on the logged in interface.
fc <i>slot/port</i>		Specifies the Fibre Channel or virtual Fibre Channel interface by slot and port number.
vfc <i>vfc-id</i>		Specifies a virtual Fibre Channel interface.
vsan <i>vsan-id</i>		Displays FLOGI database entries based on the VSAN ID. The range is from 1 to 4093.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The output of this command is sorted by interface numbers and then by VSAN IDs.

In a Fibre Channel fabric, each host or disk requires an FCID. Use the **show flogi database** command to verify if a storage device is displayed in the fabric login (FLOGI) table as in the examples below. If the required device is displayed in the FLOGI table, the fabric login is successful. Examine the FLOGI database on a switch that is directly connected to the host HBA and connected ports.

Examples This example shows how to display the details on the FLOGI database:

```
switch# show flogi database
```

This example shows how to display the FLOGI interface:

```
switch# show flogi database interface fc 2/3
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the FLOGI VSAN:

```
switch# show flogi database vsan 1
```

This example shows how to display the FLOGI for a specific FCID:

```
switch# show flogi database fcid 0xef02e2
```

Related Commands

Command	Description
show fcns database	Displays all the local and remote name server entries.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show fspf

To display global Fibre Shortest Path First (FSPF) routing information, use the **show fspf** command.

```
show fspf [database [vsan vsan-id] [detail | domain domain-id detail] | interface | vsan vsan-id
interface {fc slot/port | san-port-channel port-channel}]
```

Syntax Description		
database	(Optional)	Displays the FSPF link state database.
vsan <i>vsan-id</i>	(Optional)	Specifies the Virtual SAN (VSAN) ID. The range is from 1 to 4093.
detail	(Optional)	Displays detailed FSPF information.
domain <i>domain-id</i>	(Optional)	Specifies the domain of the database. The range is from 0 to 255.
interface	(Optional)	Specifies the FSPF interface.
fc <i>slot/port</i>		Specifies the Fibre Channel interface to configure.
san-port-channel <i>port-channel</i>		Specifies the port channel interface. The range is from 1 to 256.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines If you enter the command without parameters, all the entries in the database are displayed.

Examples This example shows how to display the FSPF interface information:

```
switch# show fspf vsan 1 fc2/1
```

This example shows how to display the FSPF database information:

```
switch# show fspf database vsan 1
```

```
FSPF Link State Database for VSAN 1 Domain 0xc6(198)
```

```
LSR Type = 1
Advertising domain ID = 0xc6(198)
LSR Age = 1050
LSR Incarnation number = 0x800007c5
LSR Checksum = 0x35d2
Number of links = 0
```

```
  NbrDomainId      IfIndex  NbrIfIndex  Link Type      Cost
```

```
-----
switch#
```

Send comments to nexus5k-docfeedback@cisco.com

This command shows how to display the FSPF information for a specified VSAN:

```
switch# show fspf vsan 1
FSPF routing for VSAN 1
FSPF routing administration status is enabled
FSPF routing operational status is UP
It is an intra-domain router
Autonomous region is 0
SPF hold time is 0 msec
MinLsArrival = 1000 msec , MinLsInterval = 2000 msec
Local Domain is 0xc6(198)
Number of LSRs = 1, Total Checksum = 0x000035d2

Protocol constants :
  LS_REFRESH_TIME = 30 minutes (1800 sec)
  MAX_AGE          = 60 minutes (3600 sec)

Statistics counters :
  Number of LSR that reached MaxAge = 0
  Number of SPF computations         = 0
  Number of Checksum Errors          = 0
  Number of Transmitted packets :   LSU 0 LSA 0 Hello 0 Retranmsitted LSU 0
  Number of received packets :     LSU 0 LSA 0 Hello 0 Error packets 0

switch#
```

This command shows how to display the FSPF information for all interfaces:

```
switch# show fspf interface
FSPF interface vfc5 in VSAN 1
FSPF routing administrative state is active
Interface cost is 2100
Timer intervals configured, Hello 20 s, Dead 80 s, Retransmit 5 s
FSPF State is DOWN

switch#
```

Related Commands

Command	Description
fspf	Configures FSPF.

Send comments to nexus5k-docfeedback@cisco.com

show in-order-guarantee

To display the present configured state of the in-order delivery feature, use the **show in-order-guarantee** command.

show in-order-guarantee

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the present configuration status of the in-order delivery feature:

```
switch# show in-order-guarantee
```

Related Commands	Command	Description
	in-order-guarantee	Enables in-order delivery.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show interface fcoe

To display information about the Fibre Channel over Ethernet (FCoE) for an interface, use the **show interface fcoe** command.

show interface [*interface number*] **fcoe**

Syntax Description	<i>interface</i>	(Optional) Interface, either Ethernet or EtherChannel.
	<i>number</i>	Interface number. The number can be one of the following: <ul style="list-style-type: none"> The Ethernet interface slot and the port number within the slot. The slot number range is from 1 to 255, and the port number range is from 1/255. The EtherChannel number. The range is from 1 to 4096.
Command Default	None	
Command Modes	EXEC mode	
Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the FCoE information for Ethernet interfaces:

```
switch# show interface fcoe
Ethernet1/1 is FCoE UP
Ethernet1/2 is FCoE UP
Ethernet1/3 is FCoE UP
Ethernet1/4 is FCoE UP
Ethernet1/5 is FCoE UP
Ethernet1/6 is FCoE UP
Ethernet1/7 is FCoE UP
Ethernet1/8 is FCoE UP
Ethernet1/9 is FCoE UP
Ethernet1/10 is FCoE UP
Ethernet1/11 is FCoE down
Ethernet1/12 is FCoE down
Ethernet1/13 is FCoE UP
Ethernet1/14 is FCoE UP
Ethernet1/15 is FCoE down
Ethernet1/16 is FCoE down
Ethernet1/17 is FCoE UP
Ethernet1/18 is FCoE down
Ethernet1/19 is FCoE UP
Ethernet1/20 is FCoE UP
Ethernet1/21 is FCoE UP
Ethernet1/22 is FCoE UP
Ethernet1/23 is FCoE UP
Ethernet1/24 is FCoE UP
```

Send comments to nexus5k-docfeedback@cisco.com

```

Ethernet1/25 is FCoE UP
Ethernet1/26 is FCoE UP
Ethernet1/27 is FCoE UP
Ethernet1/28 is FCoE UP
Ethernet1/29 is FCoE UP
Ethernet1/30 is FCoE UP
Ethernet1/31 is FCoE UP
Ethernet1/32 is FCoE UP
Ethernet1/33 is FCoE UP
  vfc1 is Up
    FCID is 0x580016
    PWWN is 10:00:00:00:07:f8:0e:45
    MAC addr is 00:00:00:13:05:01
    FCID is 0x580017
    PWWN is 10:00:00:00:07:f8:21:bf
    MAC addr is 00:00:00:13:05:01
  vfc2 is Up
    FCID is 0x580020
    PWWN is 10:00:00:00:07:f8:0e:46
    MAC addr is 00:00:00:13:05:02
    FCID is 0x580033
    PWWN is 10:00:00:00:07:f8:21:c0
    MAC addr is 00:00:00:13:05:02
  vfc4 is Up
    FCID is 0x58001e
    PWWN is 10:00:00:00:07:f8:0e:48
    MAC addr is 00:00:00:13:05:04
    FCID is 0x580031
    PWWN is 10:00:00:00:07:f8:21:c2
    MAC addr is 00:00:00:13:05:04
  vfc5 is Up
    FCID is 0x58001d
    PWWN is 10:00:00:00:07:f8:0e:49
    MAC addr is 00:00:00:13:05:05
    FCID is 0x580030
    PWWN is 10:00:00:00:07:f8:21:c3
    MAC addr is 00:00:00:13:05:05
  vfc6 is Up
    FCID is 0x58001c
    PWWN is 10:00:00:00:07:f8:0e:4a
    MAC addr is 00:00:00:13:05:06
    FCID is 0x58002f
    PWWN is 10:00:00:00:07:f8:21:c4
    MAC addr is 00:00:00:13:05:06
Ethernet1/34 is FCoE down
Ethernet1/35 is FCoE UP
<--Output truncated-->
switch#

```

This example shows how to display the FCoE information for a specific Ethernet interface:

```

switch# show interface ethernet 1/21 fcoe
Ethernet1/21 is FCoE UP
switch#

```

This example shows how to display the FCoE information for a specific EtherChannel interface:

```

switch# show interface port-channel 3 fcoe
port-channel3 is FCoE UP
switch#

```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
show fcoe	Displays the status of the FCoE parameters.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show interface san-port-channel

To display the configuration information of SAN port channel interfaces, use the **show interface san-port-channel** command.

```
show interface san-port-channel port-num [brief | counters [brief] | trunk vsan [vsan-range]]
```

Syntax Description	
<i>port-num</i>	SAN port channel interface ID. The range is from 1 to 256.
brief	(Optional) Displays brief information about the SAN port channel interfaces.
counters	(Optional) Displays the SAN port channel interface counters.
trunk	(Optional) Displays the SAN port channel interface trunk information.
vsan	(Optional) Displays the per VSAN information for the SAN port channel interface trunk.
<i>vsan-range</i>	(Optional) VSAN range. The range is from 1 to 4093.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the configuration information for a specified SAN port channel interface:

```
switch# show interface san-port-channel 101
san-port-channel 101 is down (No operational members)
  Hardware is Fibre Channel
  Port WWN is 24:65:00:05:9b:74:a6:c0
  Admin port mode is NP, trunk mode is off
  snmp link state traps are enabled
  Port vsan is 1
  1 minute input rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
  1 minute output rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
  0 frames input, 0 bytes
    0 discards, 0 errors
    0 CRC, 0 unknown class
    0 too long, 0 too short
  0 frames output, 0 bytes
    0 discards, 0 errors
  0 input OLS, 0 LRR, 0 NOS, 0 loop inits
  0 output OLS, 0 LRR, 0 NOS, 0 loop inits
  last clearing of "show interface" counters never
  No members

switch#
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the summary information of the counters of a specified SAN port channel interface:

```
switch# show interface san-port-channel 101 counters brief
```

```
-----
Interface                Input (rate is 1 min avg)  Output (rate is 1 min avg)
-----
                          Rate      Total          Rate      Total
                          MB/s     Frames         MB/s     Frames
-----
san-port-channel 101     0         0              0         0
-----

switch#
```

Related Commands

Command	Description
interface san-port-channel	Configures a SAN port channel interface.
show interface	Displays an interface configuration for a specified interface.
show running-config interface san-port-channel	Displays the running configuration information for SAN port channels.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show interface vfc

To display the configuration information of virtual Fibre Channel interfaces, use the **show interface vfc** command.

```
show interface vfc vfc-id [brief] [counters]
```

Syntax Description	
<i>vfc-id</i>	Virtual Fibre Channel interface ID. The range is from 1 to 8192.
brief	(Optional) Displays brief information about the virtual Fibre Channel interfaces.
counters	(Optional) Displays the virtual Fibre Channel interface counters.

Command Default	
None	

Command Modes	
EXEC mode	

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the configuration information for a specified virtual Fibre Channel interface:

```
switch# show interface vfc 1
vfc1 is down (Administratively down)
  Bound MAC is 00:50:3e:8d:64:00
  Hardware is Virtual Fibre Channel
  Port WWN is 20:00:00:05:9b:23:40:7f
  Admin port mode is F, trunk mode is on
  snmp link state traps are enabled
  Port vsan is 1
  1 minute input rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
  1 minute output rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
    0 frames input, 0 bytes
      0 discards, 0 errors
    0 frames output, 0 bytes
      0 discards, 0 errors
  last clearing of "show interface" counters never
```

```
switch#
```

This example shows how to display a brief information for a specified virtual Fibre Channel interface:

```
switch# show interface vfc 5 brief
```

```
-----
Interface Vsan   Admin  Admin  Status          SFP   Oper  Oper  Port
              Mode   Trunk  Mode
                              Mode   Speed Channel
                              (Gbps)
-----
```

Send comments to nexus5k-docfeedback@cisco.com

```
vfc5      1      E      on      down      --      --      --
switch#
```

This example shows how to display the counters for a specified virtual Fibre Channel interface:

```
switch# show interface vfc 5 counters
vfc5
  5 minute input rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
  5 minute output rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
  0 frames input, 0 bytes
    0 discards, 0 errors, 0 CRC
    0 too long, 0 too short
  0 frames output, 0 bytes
    0 discards, 0 errors
  0 input OLS, 0 LRR, 0 NOS, 0 loop inits
  0 output OLS, 0 LRR, 0 NOS, 0 loop inits
  0 link failures, 0 sync losses, 0 signal losses
  0 BB credit transitions from zero

switch#
```

Related Commands

Command	Description
interface vfc	Configures a virtual Fibre Channel interface.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show lldp

To display information about the Link Layer Discovery Protocol (LLDP) configuration on the switch, use the **show lldp** command.

```
show lldp {interface {ethernet slot/port | mgmt intf-no} | neighbors [detail | interface |
system-detail] | timers | traffic [interface {ethernet slot/port | mgmt intf-no}]}
```

Syntax Description		
interface		Displays LLDP interface information, or LLDP neighbor information on an interface.
ethernet slot/port		Displays the configuration information of the Ethernet IEEE 802.3z interface. The slot number is from 1 to 255, and the port number is from 1 to 128.
mgmt intf-no		Displays the configuration information of the management interface. The management interface number is 0.
neighbors		Displays information about LLDP neighbors.
detail		(Optional) Displays the detailed information about LLDP neighbors.
timers		Displays information about LLDP timers.
traffic		Displays the LLDP counters configured on the switch.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display LLDP interface information:

```
switch# show lldp traffic interface ethernet 1/1
LLDP interface traffic statistics:

Total frames transmitted: 7490
Total entries aged: 0
Total frames received: 7458
Total frames received in error: 0
Total frames discarded: 0
Total unrecognized TLVs: 0
switch#
```

This example shows how to display LLDP management interface information:

```
switch# show lldp traffic interface mgmt 0
LLDP interface traffic statistics:

Total frames transmitted: 0
Total entries aged: 0
```

Send comments to nexus5k-docfeedback@cisco.com

```

Total frames received: 0
Total frames received in error: 0
Total frames discarded: 0
Total unrecognized TLVs: 0
switch#

```

This example shows how to display LLDP timers configured on the switch:

```

switch# show lldp timers
LLDP Timers:

    Holdtime in seconds: 120
    Reinit-time in seconds: 2
    Transmit interval in seconds: 30
switch#

```

This example shows how to display LLDP neighbor information:

```

switch# show lldp neighbors
Capability codes:
  (R) Router, (B) Bridge, (T) Telephone, (C) DOCSIS Cable Device
  (W) WLAN Access Point, (P) Repeater, (S) Station, (O) Other
Local Intf  Chassis ID      Port ID      Hold-time  Capability
Eth1/1      000d.eca3.6080    Eth1/1      120        B
Eth1/2      000d.eca3.6080    Eth1/2      120        B
Eth1/3      000d.eca3.6080    Eth1/3      120        B
Eth1/4      000d.eca3.6080    Eth1/4      120        B
Eth1/7      000d.ecf2.0880    Eth1/7      120        B
Eth1/8      000d.ecf2.0880    Eth1/8      120        B
Eth1/9      000d.ecf2.0b40    Eth1/9      120        B
Eth1/10     000d.ecf2.0b40    Eth1/10     120        B
switch#

```

This example shows how to display LLDP neighbor information with system detail:

```

switch# sh lldp neighbors system-detail
Capability codes:
  (R) Router, (B) Bridge, (T) Telephone, (C) DOCSIS Cable Device
  (W) WLAN Access Point, (P) Repeater, (S) Station, (O) Other
Device ID   Local Intf  Chassis ID      Port ID      Hold-time  Capability
switch-2   Eth1/1     0005.73b7.37ce  Eth1/1      120        B
switch-3   Eth1/2     0005.73b7.37d0  Eth1/2      120        B
switch-4   Eth1/3     0005.73b7.37d1  Eth1/3      120        B
Total entries displayed: 3

```

This example shows how to display LLDP information for a specified interface:

```

switch# show lldp interface ethernet 1/1
Interface Information:
  Enable (tx/rx/dcbx): Y/Y/Y      Port Mac address: 00:0d:ec:b2:30:c8

Peer's LLDP TLVs:
Type Length Value
-----
001 007 04000dec a36080
002 007 05457468 312f31
003 002 0078
004 009 4e354b2d 506f7274 00
005 013 45756765 6e652d4e 354b2d32 00
006 010 4e354b2d 53776974 6368
007 004 00040004
008 012 05010ac1 8303021a 00000000
128 055 001b2102 020a0000 00000001 00000001 06060000 80000808 080a0000
      80008906 001b2108 04110000 80000001 00003232 00000000 000002

```

Send comments to nexus5k-docfeedback@cisco.com

```
128 005 00014201 01
128 006 0080c201 0001
000 000
switch#
```

This example shows how to display LLDP traffic information:

```
switch# show lldp traffic
LLDP traffic statistics:

    Total frames transmitted: 89743
    Total entries aged: 0
    Total frames received: 59300
    Total frames received in error: 0
    Total frames discarded: 0
    Total unrecognized TLVs: 0
switch#
```

Related Commands

Command	Description
lldp	Configures the global LLDP options on the switch.
lldp (Interface)	Configures the LLDP feature on an interface.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show loadbalancing

To display load balancing status for specific unicast flows, use the **show loadbalancing** command.

```
show loadbalancing vsan vsan-id source-fcid dest-fcid [exchange-id]
```

Syntax Description	vsan vsan-id	Displays Fabric login (FLOGI) database entries based on the FCID allocated. The format is 0xhhhhhh.
	source-fcid	Displays the load balancing status for the specified source FCID. The format is 0xhhhhhh.
	dest-fcid	Displays the load balancing status for the specified destination FCID. The format is 0xhhhhhh.
	exchange-id	(Optional) Displays the load balancing status for the specified exchange. The format is 0xhhhhhh.

Command Default	None
-----------------	------

Command Modes	EXEC mode
---------------	-----------

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the load-balancing information for the specified source and destination in VSAN 3:

```
switch# show loadbalancing vsan 3 0x3345 0x2546
```

Related Commands	Command	Description
	vsan	Configures VSAN information or membership.

Send comments to nexus5k-docfeedback@cisco.com

show npv flogi-table

To display the information about N port virtualization (NPV) Fabric login (FLOGI) session, use the **show npv flogi-table** command.

show npv flogi-table

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The **show npv flogi-table** command is available only when the switch is in NPV mode.

Examples This example shows how to display the information on NPV FLOGI session:
switch# **show npv flogi-table**

Related Commands	Command	Description
	show npv status	Displays the NPV current status.

Send comments to nexus5k-docfeedback@cisco.com

show npv status

To display the N port virtualization (NPV) current status, use the **show npv status** command.

```
show npv status
```

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The **show npv status** command is available only when the switch is in NPV mode.

Examples This example shows how to display the current status of NPV:

```
switch# show npv status
```

Related Commands	Command	Description
	show npv flogi-table	Displays the information about NPV FLOGI session.

Send comments to nexus5k-docfeedback@cisco.com

show npv traffic-map

To display N port virtualization (NPV) traffic maps, use the **show npv traffic-map** command.

```
show npv traffic-map
```

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines The **show npv traffic-map** command is available only when the switch is in NPV mode.

Examples This example shows how to display the current status of NPV:

```
switch# show npv traffic-map
```

Related Commands	Command	Description
	show npv flogi-table	Displays the information about an NPV FLOGI session.

Send comments to nexus5k-docfeedback@cisco.com

show port index-allocation

To display port index allocation information, use the **show port index-allocation** command.

```
show port index-allocation [startup]
```

Syntax Description	startup (Optional) Displays port index allocation information at startup.				
Command Default	None				
Command Modes	EXEC mode				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>6.0(2)N1(1)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	6.0(2)N1(1)	This command was introduced.
Release	Modification				
6.0(2)N1(1)	This command was introduced.				

Usage Guidelines On a switch where the maximum number of port indexes is 256, any module that exceeds that limit does not power up. There is no startup module index distribution for the Cisco Nexus 6000 Series switch.

Examples This example shows how to display port index allocation information:

```
switch# show port index-allocation
```

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show rlir

To display Registered Link Incident Report (RLIR) information, use the **show rlir** command.

```
show rlir {erl [vsan vsan-id] | history | recent {interface fc slot/port | portnumber port} |
statistics [vsan vsan-id]}
```

Syntax Description

erl	Displays the Established Registration List.
vsan <i>vsan-id</i>	(Optional) Specifies a VSAN ID. The range is from 1 to 4093.
history	Displays the link incident history.
recent	Displays recent link incidents.
interface fc <i>slot/port</i>	Specifies a Fibre Channel interface.
portnumber <i>port</i>	Displays RLIR information for the specified port number.
statistics	Displays RLIR statistics for all VSANs or the specified VSAN.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the RLIR information for VSAN 1:

```
switch# show rlir erl vsan 1
```

This example shows how to display the RLIR statistics:

```
switch# show rlir statistics vsan 1
```

Related Commands

Command	Description
rlir preferred-cond fcid	Specifies a preferred host to receive RLIR frames.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show rscn

To display Registered State Change Notification (RSCN) information, use the **show rscn** command.

```
show rscn {event-tov vsan vsan-id | pending vsan vsan-id | pending-diff vsan vsan-id | scr-table
[vsan vsan-id] | session status vsan vsan-id | statistics [vsan vsan-id]}
```

Syntax Description

event-tov	Displays the event timeout value.
vsan vsan-id	Specifies a VSAN ID. The range is from 1 to 4093.
pending	Displays the pending configuration.
pending-diff	Displays the difference between the active and the pending configuration.
scr-table	Displays the State Change Registration (SCR) table.
session status	Displays the RSCN session status.
statistics	Displays RSCN statistics.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Usage Guidelines

The SCR table cannot be configured. It is only populated if one or more N ports send SCR frames to register for RSCN information. If the **show rscn scr-table** command does not return any entries, no N port is interested in receiving RSCN information.

Examples

This example shows how to display the RSCN information:

```
switch# show rscn scr-table vsan 1
```

This example shows how to display the RSCN statistics:

```
switch# show rscn statistics vsan 1
```

This example shows how to display the RSCN event timeout value configured on VSAN 1:

```
switch# show rscn event-tov vsan 1
```

This example shows how to display the difference between the active RSCN configuration and the pending RSCN configuration on VSAN 1:

```
switch# show rscn pending-diff vsan 1
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
rscn	Configures a registered state change notification (RSCN).

Send comments to nexus5k-docfeedback@cisco.com

show running-config fcoe_mgr

To display the running configuration information about Fibre Channel over Ethernet (FCoE), use the **show running-config fcoe_mgr** command.

show running-config fcoe_mgr [all]

Syntax Description	all	(Optional) Displays the full operating information including default settings.
Command Default	None	
Command Modes	EXEC mode	
Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the FCoE running configuration information:

Need new output¹

```
switch# show running-config fcoe_mgr

!Command: show running-config fcoe_mgr
!Time: Fri Jan  2 06:33:11 2009

version 5.0(3)N2(1)

interface vfc1
  bind mac-address 00:50:3e:8d:64:00
  fcoe fka-adv-period 60
  fcoe veloopback

switch#
```

This example shows how to display detailed information on the running configuration:

```
switch# show running-config fcoe_mgr all

!Command: show running-config fcoe_mgr all
!Time: Fri Jan  2 05:36:52 2009

version 5.0(3)N2(1)
logging level fcoe_mgr 3

interface vfc1
  bind mac-address 00:50:3e:8d:64:00
  fcoe fka-adv-period 60
```

1.

Send comments to nexus5k-docfeedback@cisco.com

```
fcoe vloopback
```

```
switch#
```

Related Commands

Command	Description
copy running-config startup-config	Copies the running configuration information to the startup configuration file.
show tech-support fcoe	Displays troubleshooting information about FCoE.

Send comments to nexus5k-docfeedback@cisco.com

show running-config interface san-port-channel

To display the running system configuration information of SAN port channel interfaces, use the **show running-config interface san-port-channel** command.

```
show running-config interface san-port-channel port-num [all | expand-port-profile]
```

Syntax Description	
all	(Optional) Displays configured and default information.
expand-port-profile	(Optional) Displays the configuration information of port profiles.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the running configuration information for a specified SAN port channel interface:

Need new output

```
switch# show running-config interface san-port-channel 101

!Command: show running-config interface san-port-channel 101
!Time: Mon Apr 11 09:14:20 2005

version 5.1(3)N1(1)

interface san-port-channel 101
  channel mode active
  switchport mode NP

switch#
```

Related Commands	Command	Description
	interface san-port-channel	Configures a SAN port channel interface.
	copy running-config startup-config	Copies the running configuration information to the startup configuration file.

Send comments to nexus5k-docfeedback@cisco.com

show san-port-channel

To view information about existing SAN port channel configurations, use the **show san-port-channel** command.

```
show san-port-channel { compatibility-parameters | consistency [detail] | database [interface
san-port-channel port] | summary | usage }
```

Syntax Description	
compatibility-parameters	Displays compatibility parameters.
consistency	Displays the database consistency information of all modules.
detail	(Optional) Displays detailed database consistency information.
database	Displays SAN port channel database information.
interface san-port-channel port	(Optional) Specifies the SAN port channel number. The range is from 1 to 256.
summary	Displays the SAN port channel summary.
usage	Displays the SAN port channel number usage.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the SAN port channel summary:

```
switch# show san-port-channel summary
```

This example shows how to display the SAN port channel compatibility parameters:

```
switch# show san-port-channel compatibility-parameters
```

This example shows how to display the SAN port channel database:

```
switch# show san-port-channel database
```

This example shows how to display the consistency status of the SAN port channel database:

```
switch# show san-port-channel consistency
```

This example shows how to display detailed information about the consistency status of the SAN port channel database:

```
switch# show san-port-channel consistency detail
```

This example shows how to display details of the used and unused SAN port channel numbers:

```
switch# show san-port-channel usage
```

■ show san-port-channel

Send comments to nexus5k-docfeedback@cisco.com

Related Commands	Command	Description
	san-port-channel persistent	Converts an autogenerated SAN port channel to a persistent SAN port channel.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show scsi-target

To display information about existing SCSI target configurations, use the **show scsi-target** command.

```
show scsi-target { auto-poll | custom-list | devices [vsan vsan-id] [fcid fcid-id] | disk [vsan
vsan-id] [fcid fcid-id] | lun [vsan vsan-id] [fcid fcid-id] [os [aix | all | hpux | linux | solaris |
windows] | pwwn | status | tape [vsan vsan-id] [fcid fcid-id] | vsan vsan-id }
```

Syntax Description		
auto-poll		Displays SCSI target auto polling information.
custom-list		Displays customized discovered targets.
devices		Displays discovered SCSI target devices information.
vsan <i>vsan-id</i>		(Optional) Specifies the Virtual SAN (VSAN) ID. The range is from 1 to 4093.
fcid <i>fcid-id</i>		(Optional) Specifies the FCID of the SCSI target to display.
disk		Displays discovered disk information.
lun		Displays discovered SCSI target logical unit number (LUN) information.
os		(Optional) Discovers the specified operating system.
aix		(Optional) Specifies the AIX operating system.
all		(Optional) Specifies all operating systems.
hpux		(Optional) Specifies the HPUX operating system.
linux		(Optional) Specifies the Linux operating system.
solaris		(Optional) Specifies the Solaris operating system.
windows		(Optional) Specifies the Windows operating system.
pwwn		Displays discovered pWWN information for each operating system.
status		Displays the SCSI target discovery status.
tape		Displays discovered tape information.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Usage Guidelines Use the **show scsi-target auto-poll** command to verify automatic discovery of online SCSI targets.

Examples This example shows how to display the status of a SCSI discovery:

```
switch# show scsi-target status
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the customized discovered targets:

```
switch# show scsi-target custom-list
```

This example shows how to display the discovered disk information:

```
switch# show scsi-target disk
```

This example shows how to display the discovered LUNs for all operating systems:

```
switch# show scsi-target lun os all
```

This example shows how to display the discovered LUNs for the Solaris operating system:

```
switch# show scsi-target lun os solaris
```

This example shows how to display the auto-polling information:

```
switch# show scsi-target auto-poll
```

This example shows how to display the port WWN that is assigned to each operating system (Windows, AIX, Solaris, Linux, or HPUX):

```
switch# show scsi-target pwwn
```

Related Commands

Command	Description
scsi-target	Configures SCSI target discovery.

Send comments to nexus5k-docfeedback@cisco.com

show startup-config fcoe_mgr

To display the startup configuration information about Fibre Channel over Ethernet (FCoE), use the `show startup-config fcoe_mgr` command.

`show startup-config fcoe_mgr`

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the FCoE startup configuration information:

Need new output

```
switch# show startup-config fcoe_mgr

!Command: show startup-config fcoe_mgr
!Time: Fri Jan  2 05:41:38 2009
!Startup config saved at: Thu Jan  1 00:04:46 2009

version 5.0(3)N2(1)
logging level fcoe_mgr 3

interface vfc1
  bind mac-address 00:50:3e:8d:64:00
  fcoe fka-adv-period 60
  fcoe veloopback

switch#
```

Related Commands	Command	Description
	<code>copy running-config startup-config</code>	Copies the running configuration information to the startup configuration file.
	<code>show tech-support fcoe</code>	Displays troubleshooting information about FCoE.

Send comments to nexus5k-docfeedback@cisco.com

show tech-support fcoe

To display troubleshooting information about Fibre Channel over Ethernet (FCoE), use the **show tech-support fcoe** command.

show tech-support fcoe

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display Cisco technical support information for FCoE interfaces:

```
switch# show tech-support fcoe
***** FCOE MGR tech-support start *****
`show platform software fcoe_mgr event-history errors`
1) Event:E_DEBUG, length:71, at 269945 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_demux(535): (Warning) unexpected mts msg (opcode - 7972)

2) Event:E_DEBUG, length:64, at 269136 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5428): fka-adv-period: 60

3) Event:E_DEBUG, length:64, at 269107 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5427): fcf-priority  : 128

4) Event:E_DEBUG, length:68, at 269076 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5426): fcmap          : 0xefc00

5) Event:E_DEBUG, length:100, at 269036 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5425): fcoe_mgr_pss_add_global_cfg_da
   ta: Exiting, ret_val = 0

6) Event:E_DEBUG, length:88, at 268788 usecs after Fri Jan  2 06:35:17 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5400): fcoe_mgr_pss_add_global_cfg_data:
   Entering

7) Event:E_DEBUG, length:63, at 567997 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5428): fka-adv-period: 8

8) Event:E_DEBUG, length:64, at 567965 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5427): fcf-priority  : 128
```

Send comments to nexus5k-docfeedback@cisco.com

```
9) Event:E_DEBUG, length:68, at 567932 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5426): fcmmap          : 0xefc00

10) Event:E_DEBUG, length:100, at 567891 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5425): fcoe_mgr_pss_add_global_cfg_da
   ta: Exiting, ret_val = 0

11) Event:E_DEBUG, length:88, at 567732 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_pss_add_global_cfg_data(5400): fcoe_mgr_pss_add_global_cfg_da
   ta: Entering

12) Event:E_DEBUG, length:88, at 567667 usecs after Fri Jan  2 06:30:27 2009
   [102] fcoe_mgr_cli_set_ve_loopback(1562): Enabling VE loopback (will disable
   VFID check)

13) Event:E_DEBUG, length:129, at 177534 usecs after Fri Jan  2 06:25:17 2009
   [102] fcoe_mgr_mts_vfc_bind_check_resp_handler(2488): Bind Check Resp: if_in
   dex: 0x0, status: (null): success (err_id 0x00000000)

14) Event:E_DEBUG, length:71, at 176687 usecs after Fri Jan  2 06:25:17 2009
   [102] fcoe_mgr_demux(535): (Warning) unexpected mts msg (opcode - 7972)

15) Event:E_DEBUG, length:71, at 392038 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_mac_pool_bmp_to_tlv(143): mac_pool->mac_usage_bmp = NULL

16) Event:E_DEBUG, length:63, at 89603 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/31

17) Event:E_DEBUG, length:63, at 89509 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/29

18) Event:E_DEBUG, length:63, at 89405 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/18

19) Event:E_DEBUG, length:63, at 89310 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/17

20) Event:E_DEBUG, length:63, at 89212 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/15

21) Event:E_DEBUG, length:62, at 89101 usecs after Fri Jan  2 06:16:00 2009
   [102] fcoe_mgr_get_eth_fcoe_info(58): sending lls down Eth1/8

<--Output truncated-->
switch#
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands	Command	Description
	show running-config fcoe_mgr	Displays the running configuration information about FCoE.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show topology

To display topology information for connected SAN switches, use the **show topology** command.

```
show topology [vsan vsan-id]
```

Syntax Description	vsan vsan-id (Optional) Displays information for a VSAN. The range is from 1 to 4093.
---------------------------	--

Command Default	None
------------------------	------

Command Modes	EXEC mode
----------------------	-----------

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples	This example shows how to display topology information:
-----------------	---

```
switch# show topology
```

Related Commands	Command	Description
	cfs ipv4 mcast-address	Configures an IPv4 multicast address for Cisco Fabric Services (CFS) distribution over IPv4.
	cfs ipv6 distribute	Enables CFS distribution over IPv6 for applications using CFS.
	cfs ipv6 mcast-address	Configures an IPv6 multicast address for CFS distribution over IPv6.

Send comments to nexus5k-docfeedback@cisco.com

show trunk protocol

To display the trunk protocol status, use the **show trunk protocol** command.

```
show trunk protocol
```

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the trunk protocol status:

```
switch# show trunk protocol
switch#
```

Related Commands	Command	Description
	trunk protocol enable	Configures the trunking protocol for Fibre Channel interfaces.

Send comments to nexus5k-docfeedback@cisco.com

show vlan fcoe

To display information about the Fibre Channel over Ethernet (FCOE) VLAN to Virtual SAN (VSAN) mappings, use the **show vlan fcoe** command.

show vlan fcoe

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the FCoE VLAN to VSAN mappings on the switch:

```
switch# show vlan fcoe
VLAN      VSAN      Status
-----
331       331       Operational
332       332       Operational
333       333       Operational
334       334       Operational
335       335       Non-operational
336       336       Operational
337       337       Operational
switch#
```

Related Commands	Command	Description
	fcoe vsan	Maps a FCoE VLAN to a VSAN.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show vsan

To display information about a configured Virtual SAN (VSAN), use the **show vsan** command.

```
show vsan [vsan-id [membership] | membership [interface {fc slot/port | san-port-channel port
| vfc vfc-id}] | usage]
```

Syntax Description

<i>vsan-id</i>	(Optional) Information for the specified VSAN ID. The range is from 1 to 4094.
membership	(Optional) Displays membership information.
interface	(Optional) Specifies the interface type.
fc slot/port	Specifies a Fibre Channel interface.
san-port-channel port	Specifies a SAN port channel interface specified by the port channel number.
vfc vfc-id	Specifies a virtual Fibre Channel interface.
usage	(Optional) Displays VSAN usage in the system.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Usage Guidelines

When you enter the **show vsan membership interface** command, interface information appears for interfaces that are configured in this VSAN.

The interface range must be in ascending order and nonoverlapping. You can specify a range using a hyphen and several interfaces using commas:

- The interface range format for a Fibre Channel interface range is

fcslot/port - port, fcslot/port, fcslot/port:

For example, **show int fc2/1 - 3 , fc2/4 , fc3/2**

Examples

This example shows how to display the configured VSAN information:

```
switch# show vsan 1
vsan 1 information
  name:VSAN0001 state:active
  interoperability mode:default
  loadbalancing:src-id/dst-id/oxid
  operational state:up

switch#
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the membership information for all VSANs:

```
switch # show vsan membership
vsan 1 interfaces:

vsan 331 interfaces:
    fc2/3          fc2/4          san-port-channel 14 vfc1
    vfc2           vfc3           vfc4            vfc5
    vfc6           vfc7           vfc8            vfc9
    vfc10          vfc11          vfc12           vfc13
    vfc14          vfc15          vfc16           vfc17
    vfc18          vfc19          vfc20

vsan 332 interfaces:
    fc2/5          fc2/6          fc2/7           fc2/8
    san-port-channel 8 san-port-channel 9 vfc21           vfc22
    vfc23          vfc24          vfc25           vfc26
    vfc27          vfc28          vfc29           vfc30
    vfc31          vfc32          vfc33           vfc34
    vfc35          vfc36          vfc37           vfc38
    vfc39          vfc40

vsan 333 interfaces:
    fc2/1          fc2/2          san-port-channel 13

vsan 334 interfaces:

vsan 336 interfaces:

vsan 337 interfaces:

vsan 4079(evfp_isolated_vsan) interfaces:

vsan 4094(isolated_vsan) interfaces:

switch#
```

This example shows how to display the membership information for a specified interface:

```
switch# show vsan membership interface fc2/1
fc2/1
    vsan:333
    allowed list:1-4078,4080-4093
switch#
```

Related Commands

Command	Description
vsan	Configures a VSAN.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show wwn

To display the status of the WWN configuration, use the **show wwn** command.

```
show wwn {status [block-id number] | switch | vsan-wwn}
```

Syntax Description	Parameter	Description
	status	Displays a summary of the WWN usage and alarm status.
	block-id <i>number</i>	(Optional) Displays the WWN usage and alarm status for a block ID. The range is from 34 to 1793.
	switch	Displays the switch WWN.
	vsan-wwn	Displays all user-configured VSAN WWNs.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the WWN of the switch:

```
switch# show wwn switch
```

This example shows how to display a user-configured VSAN WWN:

```
switch# show wwn vsan-wwn
```

Related Commands	Command	Description
	wwn vsan	Configures a WWN for a suspended VSAN that has interop mode 4 enabled.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show zone

To display zone information, use the **show zone** command.

```
show zone [active [vsan vsan-id] | analysis { active vsan vsan-id | vsan vsan-id | zoneset
zoneset-name } | ess [vsan vsan-id] | member { fcalias alias-name | fcid fc-id [active | lun lun-id
| vsan vsan-id] | pwwn wwn [active | lun lun-id | vsan vsan-id] } | name string [active]
[pending] [vsan vsan-id] | pending [active] [vsan vsan-id] | pending-diff [vsan vsan-id] |
policy [pending] [vsan vsan-id] | statistics [vsan vsan-id] | status [vsan vsan-id]
```

Syntax Description

active	(Optional) Displays zones that are part of active zone set.
vsan <i>vsan-id</i>	(Optional) Displays zones belonging to the specified VSAN ID. The range is from 1 to 4093.
analysis	(Optional) Displays the analysis of the zone database.
active	Displays the analysis of the active zone database.
vsan	Displays the analysis of the zone database for the specified VSAN.
zoneset <i>zoneset-name</i>	Displays the analysis of the specified zone set.
ess	(Optional) Displays the exchange switch support (ESS) information.
member	(Optional) Displays all zones in which the given member is part of.
fcalias <i>alias-name</i>	Displays member information for a specific fcalias.
fc-id <i>fc-id</i>	Displays member information for a specific Fibre Channel ID.
lun <i>lun-id</i>	Displays the logical unit ID.
pwwn <i>wwwn</i>	Displays device name information for a specific pWWN. The format is <i>hh:hh:hh:hh:hh:hh:hh:hh</i> , where <i>h</i> is a hexadecimal number.
name <i>string</i>	Displays members of a specified zone.
pending	Displays members of a specified zone in the current session.
pending-diff	Displays pending changes to the zone database.
statistics	Displays zone server statistics.
status	Displays the zone server current status.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the configured zone information:

```
switch# show zone
```

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the zone information for a specific VSAN:

```
switch# show zone vsan 1
```

This example shows how to display the members of a specific zone:

```
switch# show zone name Zone1
```

This example shows how to display all zones to which a member belongs using the FCID:

```
switch# show zone member pwwn 21:00:00:20:37:9c:48:e5
```

This example shows how to display the number of control frames exchanged with other switches:

```
switch# show zone statistics
```

This example shows how to display the status of the configured zones:

```
switch# show zone status
```

This example checks the status of the **zoneset distribute vsan** command and displays the default zone attributes of a specific VSAN or all active VSANs:

```
switch# show zone status vsan 1
VSAN:1 default-zone:deny distribute:active only Interop:default
      mode:basic merge-control:allow session:none
      hard-zoning:enabled
Default zone:
      qos:low broadcast:disabled ronly:disabled
Full Zoning Database :
      Zonesets:0 Zones:0 Aliases:0
Active Zoning Database :
      Database Not Available
Status:
```

[Table 3](#) describes the significant fields shown in the **show zone status vsan** display.

Table 3 *show zone status Field Descriptions*

Field	Description
VSAN:	VSAN number displayed.
default-zone:	Default-zone policy, either permit or deny.
Default zone:	Field that displays the attributes for the specified VSAN. The attributes include Qos level, broadcast zoning enabled/disabled, and read-only zoning enabled/disabled.
distribute:	Distribute full-zone set (full) or active-zone set (active only).
Interop:	Interop mode. 100 = default, 1 = standard, 2 and 3 = Non-Cisco vendors.
mode:	Zoning mode, either basic or enhanced.
merge control:	Merge policy, either allow or restrict.
Hard zoning is enabled	If hardware resources (TCAM) becomes full, hard zoning is automatically disabled.
Full Zoning Database:	Values of zone database.
Active Zoning Database:	Values of active zone database.
Status:	Status of last zone distribution.

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
zone	Configures zone information.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show zone analysis

To display detailed analysis and statistical information about the zoning database, use the **show zone analysis** command.

```
show zone analysis {active vsan vsan-id | vsan vsan-id | zoneset name vsan vsan-id}
```

Syntax Description	active	Displays analysis information for the active zone set.
	vsan vsan-id	Displays analysis information for the specified VSAN ID. The range is from 1 to 4093.
	zoneset name	Displays zone set analysis information for the specified zone set.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples

This example shows how to display the detailed statistics and analysis of the active zoning database:

```
switch# show zone analysis active vsan 1
```

This example shows how to display the detailed statistics and analysis of the full zoning database:

```
switch# sh zone analysis vsan 1
Zoning database analysis vsan 1
  Full zoning database
    Last updated at: 14:36:56 UTC Oct 04 2005
    Last updated by: Local [CLI / SNMP / GS / CIM / INTERNAL] or
                    Merge [interface] or
                    Remote [Domain, IP-Address]
                    [Switch name]

    Num zonesets: 1
    Num zones: 1
    Num aliases: 0
    Num attribute groups: 0
    Formatted database size: < 1 Kb / 2000 kb ( < 1% usage)

Unassigned zones:
  zone name z1 vsan 1
```

Send comments to nexus5k-docfeedback@cisco.com

Table 4 describes the fields displayed in the output of a **show zone analysis** command for the full zoning database.

Table 4 *show zone analysis Field Descriptions for the Full Zoning Database*

Field	Description
Last updated at	Time stamp that shows when the full zoning database was last updated.
Last Updated by	<p>Agent that most recently modified the full zoning database. The agent can be one of the following three types:</p> <ul style="list-style-type: none"> • Local—Indicates that the full database was last modified locally through a configuration change from one of the following applications: <ul style="list-style-type: none"> – CLI—The full zoning database was modified by the user from the command line interface. – SNMP—The full zoning database was modified by the user through the Simple Network Management Protocol (SNMP). – GS—The full zoning database was modified from the Generic Services (GS) client. – CIM—The full zoning database was modified by the applications using the Common Information Model (CIM). – INTERNAL—The full zoning database was modified as a result of an internal activation either from Inter-VSAN Routing (IVR) or from the IP storage services manager. • Merge—Indicates that the full database was last modified by the Merge protocol. In this case, the interface on which the merge occurred is also displayed. • Remote—Indicates that the full database was last modified by the Change protocol, initiated by a remote switch, when the full zone set distribution was enabled. The domain, IP address, and switch name of the switch initiating the change are also displayed. <p>Note The switch name is displayed on the next line, aligned with the domain, only if the switch name is set. The default switch name <i>switch</i> and the <i>ip-address</i> are not displayed.</p>
Num zonesets	Total number of zone sets in the database.
Num zones	Total number of zones in the database, including unassigned zones.
Num aliases	Total number of aliases in the database, including unassigned FC aliases.
Num attribute groups	Total number of attribute groups in the database. This field applies only when enhanced zoning is used.

Send comments to nexus5k-docfeedback@cisco.com

Table 4 *show zone analysis Field Descriptions for the Full Zoning Database (continued)*

Field	Description
Formatted database size	Total size of the full database when formatted to be sent over the wire. The formatted database size is displayed in kilobytes in this format: < X KB / Y KB, as in the following example: Formatted database size: < 1 KB/2000 KB In this example, the formatted database size is less than 1 KB out of the maximum size of 2000 KB.
Unassigned zones	All the unassigned zones in the VSAN. Only the names of the zones are displayed. The details about the members of the zone are not displayed in this section.

This example shows how to display the zone set analysis information:

```
switch# show zone analysis zoneset zs1 vsan 1
```

Related Commands

Command	Description
zone compact database	Compacts a zone database in a VSAN.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show zoneset

To display the configured zone sets, use the **show zoneset** command.

```
show zoneset [active [vsan vsan-id] | brief [active [vsan vsan-id] | vsan vsan-id] | name
zoneset-name [active [vsan vsan-id] | brief [active [vsan vsan-id] | vsan vsan-id] | vsan
vsan-id] | pending [active [vsan vsan-id] | brief [active [vsan vsan-id] | vsan vsan-id] | vsan
vsan-id] | vsan vsan-id
```

Syntax Description		
active	(Optional)	Displays only active zone sets.
vsan <i>vsan-id</i>	(Optional)	Displays the VSAN. The range is from 1 to 4093.
brief	(Optional)	Displays zone set members in a brief list.
name <i>zoneset-name</i>	(Optional)	Displays members of a specified zone set.
pending	(Optional)	Displays zone sets members that are in session.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

Examples This example shows how to display the configured zone set information:

```
switch# show zoneset vsan 1
```

This example shows how to display the configured zone set information for a specific VSAN:

```
switch# show zoneset vsan 2-3
```

Related Commands	Command	Description
	zoneset (Global configuration mode)	Groups zones under one zone set.
	zoneset (EXEC mode)	Merges zone set databases.

Send comments to nexus5k-docfeedback@cisco.com