



New and Changed Information

This chapter provides release-specific information for each new and changed feature in the *Cisco Nexus 7000 Series NX-OS Overlay Transport Virtualization Command Reference*. The latest version of this document is available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-7000-series-switches/products-command-reference-list.html>

To check for additional information about this Cisco NX-OS Release, see the Cisco NX-OS Release Notes available at the following Cisco website:

<http://www.cisco.com/c/en/us/support/switches/nexus-7000-series-switches/products-release-notes-list.html>

Table 1 summarizes the new and changed features for the *Cisco Nexus 7000 Series NX-OS Overlay Transport Virtualization Command Reference*.

Table 1 *New and Changed Features*

Feature	Description	Changed in Release
otv depolarization disable	Added support for the F3 Series module.	6.2(8)
otv broadcast-group	This command was introduced	6.2(2)
otv flood mac	This command was introduced	6.2(2)
otv isis bfd	This command was introduced	6.2(2)
otv vlan mapping	This command was introduced	6.2(2)
show bfd neighbors	This command was introduced	6.2(2)
show otv vlan-mapping	This command was introduced	6.2(2)
show otv mroute vlan	This command was introduced	6.2(2)
show otv vlan	Changed the command output to show the time remaining for the VLANs to become active after the overlay interface is unshut.	6.2(2)
show otv-isis track-adjacency-nexthop track-adjacency-nexthop	These commands were introduced	6.2(2)

Table 1 *New and Changed Features*

Feature	Description	Changed in Release
otv arp-nd timeout	Added the otv arp-nd timeout command	6.1(1)
otv use-adjacency-server unicast-only	Added support for unicast cores using an adjacency server	5.2(1)
show otv vlan-mapping	Added the overlay and vpn keywords	
otv extend-vlan	Added the add and remove keywords	