



## X Commands

---

- [xml](#), on page 2
- [xml](#), on page 3
- [xml server max-session](#), on page 4
- [xml server terminate session](#), on page 5
- [xml server timeout](#), on page 6
- [xml server validate](#), on page 7
- [xml server xml-debug](#), on page 8
- [xmlin](#), on page 9
- [xmlin](#), on page 10
- [xmlin](#), on page 11
- [xmlin](#), on page 12
- [xmlout](#), on page 13

# xml

| xml

## Syntax Description

---

### Syntax Description

| Pipe command output to filter

---

**xi** output in xml format (according to .xsd definitions)

---

## Command Mode

- /output

# xml

| xml

## Syntax Description

---

### Syntax Description

| Pipe command output to filter

---

**xml** output in xml format (according to .xsd definitions)

---

## Command Mode

- /output

# xml server max-session

[no] xml server max-session <number>

## Syntax Description

Syntax Description		
no	(Optional)	Negate a command or set its defaults
xml	xml agent	
server	xml agent server	
max-session	configure	maximum number of xml sessions allowed
<i>number</i>	number of the sessions	

## Command Mode

- /exec/configure

# xml server terminate session

xml server terminate session <session\_id>

## Syntax Description

<b>Syntax Description</b>	xml	xml agent
	server	xml agent server
	terminate	command to terminate an XML session
	session	terminate an XML session
	<i>session_id</i>	sessions number

## Command Mode

- /exec

# xml server timeout

[no] xml server timeout <value> [ <session\_id> ]

## Syntax Description

Syntax Description		
no	(Optional)	Negate a command or set its defaults
xml		xml agent
server		xml agent server
timeout		configure xml agent session timeout
<i>value</i>		timeout in seconds
<i>session_id</i>	(Optional)	xml agent session id

## Command Mode

- /exec/configure

# xml server validate

[no] xml server validate { all | <session\_id> }

## Syntax Description

Syntax Description	
no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml agent server
validate	command to validate an XML session
all	all sessions
<i>session_id</i>	session number

## Command Mode

- /exec/configure

# xml server xml-debug

[no] xml server xml-debug

## Syntax Description

Syntax Description	
no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml server
xml-debug	xml server xml-debug

## Command Mode

- /exec/configure



# xmlin

xmlin

## Syntax Description

---

### Syntax Description

---

xmlin Convert CLI commands to their XML formats

---

## Command Mode

- /exec

# xmlin

| xmlin

## Syntax Description

---

### Syntax Description

| Pipe command output to filter

---

**xmlin** Convert CLI show commands to their XML formats

---

## Command Mode

- /output

# xmlin

xmlin

## Syntax Description

---

### Syntax Description

---

xmlin Convert CLI commands to their XML formats

---

## Command Mode

- /exec

# xmlin

| xmlin

## Syntax Description

---

### Syntax Description

| Pipe command output to filter

---

**xmlin** Convert CLI show commands to their XML formats

---

## Command Mode

- /output

# xmlout

| xmlout

## Syntax Description

---

### Syntax Description

| Pipe command output to filter

---

xmlout output in xml format (according to the latest .xsd version)

---

## Command Mode

- /output

