



B Commands

- [show background](#), on page 3
- [show banner motd](#), on page 4
- [show bash-shell](#), on page 5
- [show bfd-app session status](#), on page 6
- [show bfd addrmap](#), on page 7
- [show bfd clients](#), on page 8
- [show bfd discrmap](#), on page 9
- [show bfd intfipmap](#), on page 10
- [show bfd neighbors](#), on page 11
- [show bfd scalar](#), on page 15
- [show bfd session](#), on page 16
- [show bgp](#), on page 19
- [show bgp](#), on page 22
- [show bgp](#), on page 29
- [show bgp](#), on page 35
- [show bgp](#), on page 36
- [show bgp](#), on page 42
- [show bgp](#), on page 45
- [show bgp community](#), on page 47
- [show bgp convergence](#), on page 53
- [show bgp convergence private](#), on page 55
- [show bgp dampening dampened](#), on page 56
- [show bgp dampening flap-statistics](#), on page 62
- [show bgp dampening parameters](#), on page 65
- [show bgp default-info](#), on page 68
- [show bgp event-history](#), on page 69
- [show bgp extcommunity](#), on page 70
- [show bgp l3vpn](#), on page 76
- [show bgp neighbors](#), on page 78
- [show bgp neighbors](#), on page 86
- [show bgp neighbors commands](#), on page 91
- [show bgp neighbors flap-statistics](#), on page 93
- [show bgp neighbors paths](#), on page 95

- [show bgp paths](#), on page 97
- [show bgp peer-template](#), on page 98
- [show bgp peer](#), on page 102
- [show bgp prefix-list](#), on page 104
- [show bgp private](#), on page 109
- [show bgp private attr](#), on page 110
- [show bgp private damp](#), on page 111
- [show bgp process](#), on page 112
- [show bgp received-paths](#), on page 116
- [show bgp regexp](#), on page 122
- [show bgp self-originated](#), on page 127
- [show bgp sessions](#), on page 132
- [show bgp statistics](#), on page 134
- [show bgp summary](#), on page 138
- [show bgp summary](#), on page 142
- [show boot](#), on page 146
- [show boot auto-copy](#), on page 147
- [show boot auto-copy list](#), on page 148
- [show boot current](#), on page 149
- [show boot module](#), on page 150
- [show boot order](#), on page 151
- [show boot sup-1](#), on page 152
- [show boot sup-2](#), on page 153
- [show boot timings](#), on page 154
- [show boot variables](#), on page 155
- [show bootmode](#), on page 156
- [show buffers ip](#), on page 157

show background

show background

Syntax Description

show	Show running system information
background	show background processes (started with 'source background <file>' command)

Command Mode

- /exec

show banner motd

```
show banner motd [ __readonly__ { banner_msg <b_msg> } ]
```

Syntax Description

show	Show running system information
banner	Show current motd banner message
motd	Show current motd banner message
__readonly__	(Optional)
banner_msg	(Optional) The banner message
<i>b_msg</i>	(Optional) The banner message

Command Mode

- /exec

show bash-shell

```
show bash-shell [ __readonly__ { operation_status <o_status> } ]
```

Syntax Description

show	Show running system information
bash-shell	Show bash shell status
<i>__readonly__</i>	(Optional)
<i>operation_status</i>	(Optional) Bash shell status
<i>o_status</i>	(Optional) operational status of bash shell

Command Mode

- /exec

show bfd-app session status

```
show bfd-app session status { src-ip { <src_ip> dest-ip <dest_ip> | <src_ipv6> dest-ip <dest_ipv6> } { iod
<iod_id> | intf <intf_id> } | <all> }
```

Syntax Description

show	Show running system information
bfd-app	BFD application commands
session	session operation
src-ip	Source ip
<i>src_ip</i>	Source ip value
dest-ip	Destination ip
<i>dest_ip</i>	Destination ip value
iod	interface iod
<i>iod_id</i>	Interface iod in hex
intf	interface
<i>intf_id</i>	Interface Id
status	status of sessions
<i>all</i>	All sessions

Command Mode

- /exec

show bfd addrmap

```
show bfd addrmap [ application <appid> discriminator <discr> address-type <addrtype> address <addr> ] [
__readonly__ TABLE_bfdSessMapTable <ciscoBfdSessApplicationId> <ciscoBfdSessDiscriminator>
<ciscoBfdSessAddrType> <ciscoBfdSessAddr> <ciscoBfdSessMapBfdIndex> ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
addrmap	Session
application	(Optional)
discriminator	(Optional)
address-type	(Optional)
address	(Optional)
<i>appid</i>	(Optional)
<i>discr</i>	(Optional)
<i>addrtype</i>	(Optional)
<i>addr</i>	(Optional)
<i>__readonly__</i>	(Optional)
TABLE_bfdSessMapTable	(Optional) Address Map table
<i>ciscoBfdSessApplicationId</i>	(Optional)
<i>ciscoBfdSessDiscriminator</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessMapBfdIndex</i>	(Optional)

Command Mode

- /exec

show bfd clients

show bfd clients [*__readonly__* <header> TABLE-bfdClients <client_name> <num_sess>]

Syntax Description

show	Show running system information
bfd	BFD commands
clients	bfd client list
<i>__readonly__</i>	(Optional)
<i>header</i>	(Optional) print header
TABLE-bfdClients	(Optional) BFD Client table
<i>client_name</i>	(Optional) client name
<i>num_sess</i>	(Optional) Number of sessions

Command Mode

- /exec

show bfd discrmap

```
show bfd discrmap [ <discr> ] [ __readonly__ TABLE_bfdDiscMapTable <ciscoBfdSessDiscMapIndex> ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
discrmap	Session
<i>discr</i>	(Optional)
<i>__readonly__</i>	(Optional)
<i>TABLE_bfdDiscMapTable</i>	(Optional) Discriminator map table
<i>ciscoBfdSessDiscMapIndex</i>	(Optional)

Command Mode

- /exec

show bfd intfipmap

```
show bfd intfipmap [ interface <intf> address-type <addrtype> address <addr> ] [ __readonly__
TABLE_ipMapTable <ciscoBfdSessInterface> <ciscoBfdSessAddrType> <ciscoBfdSessAddr>
<ciscoBfdSessIpMapIndex> ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
intfipmap	Session
interface	(Optional)
address-type	(Optional)
address	(Optional)
<i>intf</i>	(Optional)
<i>addrtype</i>	(Optional)
<i>addr</i>	(Optional)
<i>__readonly__</i>	(Optional)
TABLE_ipMapTable	(Optional) ip map table
<i>ciscoBfdSessInterface</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessIpMapIndex</i>	(Optional)

Command Mode

- /exec

show bfd neighbors

```
show bfd { [ vrf { <vrf-name> | <vrf-known-name> | all } ] } { [ <ip_type> ] } neighbors { [ module
<module_no> ] [ interface <intf_id> ] [ application <bfd_cli_client_names> ] [ { src-ip <src_ip> | src-ipv6
<src_ipv6> } ] [ { dest-ip <dest_ip> | dest-ipv6 <dest_ipv6> } ] [ vrf { <vrf-name> | <vrf-known-name> |
all } ] } + [ details ] [ __readonly__ TABLE_bfdNeighbor <local_disc> [ <header> ] [ <vrf_name> ] [
<src_ip_addr> ] [ <src_ipv6_addr> ] [ <dest_ip_addr> ] [ <dest_ipv6_addr> ] [ <remote_disc> ] [ <local_state>
] [ <remote_state> ] [ <holddown> ] [ <cur_detect_mult> ] [ <intf> ] [ <echo> ] [ <echo_tx> ] [ <local_diag>
] [ <demand> ] [ <poll> ] [ <min_tx> ] [ <min_rx> ] [ <local_multi> ] [ <dectect_timer> ] [ <down_count>
] [ <tx_interval> ] [ <rx_count> ] [ <rx_avg> ] [ <rx_min> ] [ <rx_max> ] [ <last_rx> ] [ <tx_count> ] [
<tx_avg> ] [ <tx_min> ] [ <tx_max> ] [ <last_tx> ] [ <app> ] [ <up_time> ] [ <version> ] [ <diag> ] [
<state_bit> ] [ <demand_bit> ] [ <poll_bit> ] [ <final_bit> ] [ <multiplier> ] [ <length> ] [ <my_disc> ] [
<your_disc> ] [ <min_tx_interval> ] [ <req_min_rx> ] [ <min_echo_interval> ] [ <out_str> ] [ <host_lc> ] [
<down_reason> ] [ <no_host_reason> ] [ <parent> ] [ <per_link_str> ] [ <auth> ] [ <auth_bit> ] [ <print_details>
] ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
<i>ip_type</i>	(Optional) ipv4 or ipv6
neighbors	neighbors
module	(Optional) module
<i>module_no</i>	(Optional) module number
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>bfd_cli_client_names</i>	(Optional) __nil__ Clients need to register with bfd for this list
src-ip	(Optional) Source ip
src-ipv6	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
dest-ipv6	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name

<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
details	(Optional) details
<i>__readonly__</i>	(Optional)
TABLE_bfdNeighbor	(Optional) BFD Neighbor table
<i>header</i>	(Optional) Header
<i>vrf_name</i>	(Optional) vrf name
<i>src_ip_addr</i>	(Optional) Source IPV4 address
<i>dest_ip_addr</i>	(Optional) Destination IPV4 address
<i>local_disc</i>	(Optional) Local Discriminator
<i>remote_disc</i>	(Optional) Remote Discriminator
<i>local_state</i>	(Optional) Local State
<i>remote_state</i>	(Optional) Remote State
<i>holddown</i>	(Optional) Hold Down Time
<i>cur_detect_mult</i>	(Optional) Current Detection Multiplier
<i>intf</i>	(Optional) Interface
<i>echo</i>	(Optional) Echo enabled
<i>echo_tx</i>	(Optional) Echo Tx Interval
<i>local_diag</i>	(Optional) Local Diag
<i>demand</i>	(Optional) Demand Mode
<i>poll</i>	(Optional) Poll Bit
<i>min_tx</i>	(Optional) Local Min Tx Interval
<i>min_rx</i>	(Optional) Local Min Rx Interval
<i>local_multi</i>	(Optional) Local Detection Multiplier
<i>dectect_timer</i>	(Optional) Current Detection Timer
<i>down_count</i>	(Optional) Session Down Count
<i>tx_interval</i>	(Optional) Tx Interval
<i>rx_count</i>	(Optional) Tx Count
<i>rx_avg</i>	(Optional) Rx Interval Avg

<i>rx_min</i>	(Optional) Rx Interval Min
<i>rx_max</i>	(Optional) Rx Interval Max
<i>last_rx</i>	(Optional) Last Rx time
<i>tx_count</i>	(Optional) Tx Count
<i>tx_avg</i>	(Optional) Tx Interval Avg
<i>tx_min</i>	(Optional) Tx Interval Min
<i>tx_max</i>	(Optional) Tx Interval Max
<i>last_tx</i>	(Optional) Last Tx time
<i>app</i>	(Optional) App name
<i>up_time</i>	(Optional) Up time
<i>version</i>	(Optional) Version in Last Packet
<i>diag</i>	(Optional) diag in Last Packet
<i>state_bit</i>	(Optional) State Bit in Last Packet
<i>demand_bit</i>	(Optional) Demand Bit in Last Packet
<i>poll_bit</i>	(Optional) Poll Bit in Last Packet
<i>final_bit</i>	(Optional) Final Bit in Last Packet
<i>multiplier</i>	(Optional) Detection Multiplier in Last Packet
<i>length</i>	(Optional) Length in Last Packet
<i>my_disc</i>	(Optional) My Discriminator in Last Packet
<i>your_disc</i>	(Optional) Your Discriminator in Last Packet
<i>min_tx_interval</i>	(Optional) Min Tx Interval in Last Packet
<i>req_min_rx</i>	(Optional) Required Rx Interval in Last Packet
<i>min_echo_interval</i>	(Optional) Min Echo Interval in Last Packet
<i>out_str</i>	(Optional) No Host LC string
<i>parent</i>	(Optional) Parent Session
<i>per_link_str</i>	(Optional) Per Link string
<i>host_lc</i>	(Optional) Host LC
<i>down_reason</i>	(Optional) Session Down Reason
<i>no_host_reason</i>	(Optional) Not Hosted Reason

<i>auth</i>	(Optional) Authentication Mode
<i>auth_bit</i>	(Optional) Auth Bit in Last Packet
<i>print_details</i>	(Optional) print details

Command Mode

- /exec

show bfd scalar

show bfd scalar [__readonly__ <adminStatus> <version> <notifEnable>]

Syntax Description

show	Show running system information
bfd	BFD commands
scalar	bfd mib scalars
__readonly__	(Optional)
<i>adminStatus</i>	(Optional) bfd admin status
<i>version</i>	(Optional) bfd version number
<i>notifEnable</i>	(Optional) Enable bfd traps

Command Mode

- /exec

show bfd session

```
show bfd session { [ discriminator <sessionIndex> ] | [ interface <intf_id> ] | [ application <app_name> ] | [ src-ip <src_ip> ] | [ dest-ip <dest_ip> ] | [ vrf { <vrf-name> | <vrf-known-name> | all } ] } + [ __readonly__ <vrf_name_header> TABLE_bfdSessTable <ciscoBfdSessIndex> <isMember> <ciscoBfdSessApplicationId> <ciscoBfdSessDiscriminator> <ciscoBfdSessRemoteDiscr> <ciscoBfdSessUdpPort> <ciscoBfdSessState> <remoteBfdSessState> <ciscoBfdSessRemoteHeardFlag> <ciscoBfdSessDiag> <remoteBfdSessDiag> <ciscoBfdSessOperMode> <ciscoBfdSessDemandModeDesiredFlag> <ciscoBfdSessEchoFuncModeDesiredFlag> <ciscoBfdSessControlPlanIndepFlag> <ciscoBfdSessAddrType> <ciscoBfdSessAddr> <localBfdSessAddr> <ciscoBfdSessDesiredMinTxInterval> <ciscoBfdSessReqMinRxInterval> <ciscoBfdSessReqMinEchoRxInterval> <ciscoBfdSessDetectMult> <remoteBfdSessDesiredMinTxInterval> <remoteBfdSessReqMinRxInterval> <remoteBfdSessReqMinEchoRxInterval> <remoteBfdSessDetectMult> <ciscoBfdSessStorType> <ciscoBfdSessRowStatus> <ciscoBfdSessAuthPresFlag> <ciscoBfdSessAuthenticationType> <ciscoBfdSessVersionNumber> <ciscoBfdSessType> <ciscoBfdSessInterface> <ciscoBfdSessPerfPktIn> <ciscoBfdSessPerfPktOut> <ciscoBfdSessUpTime> <ciscoBfdSessPerfLastSessDownTime> <ciscoBfdSessPerfLastCommLostDiag> <ciscoBfdSessPerfSessUpCount> <ciscoBfdSessPerfDiscTime> <ciscoBfdSessPerfPktInHC> <ciscoBfdSessPerfPktOutHC> <effasyncdt> <effechothd> ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
session	Session
discriminator	(Optional) Session local discriminator
<i>sessionIndex</i>	(Optional)
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>app_name</i>	(Optional) show bfd session based on application name
src-ip	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

<i>__readonly__</i>	(Optional)
<i>vrf_name_header</i>	(Optional)
TABLE_bfdSessTable	(Optional) BFD Session table
<i>ciscoBfdSessIndex</i>	(Optional)
<i>isMember</i>	(Optional)
<i>ciscoBfdSessApplicationId</i>	(Optional)
<i>ciscoBfdSessDiscriminator</i>	(Optional)
<i>ciscoBfdSessRemoteDiscr</i>	(Optional)
<i>ciscoBfdSessUdpPort</i>	(Optional)
<i>ciscoBfdSessState</i>	(Optional) Session state
<i>remoteBfdSessState</i>	(Optional) Session state
<i>ciscoBfdSessRemoteHeardFlag</i>	(Optional)
<i>ciscoBfdSessDiag</i>	(Optional) Session diagnostic code
<i>remoteBfdSessDiag</i>	(Optional) Session diagnostic code
<i>ciscoBfdSessOperMode</i>	(Optional) ciscoBfdSessOperMode
<i>ciscoBfdSessDemandModeDesiredFlag</i>	(Optional)
<i>ciscoBfdSessEchoFuncModeDesiredFlag</i>	(Optional)
<i>ciscoBfdSessControlPlanIndepFlag</i>	(Optional)
<i>ciscoBfdSessAddrType</i>	(Optional) ciscoBfdSessAddrType
<i>localBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessAddr</i>	(Optional)
<i>ciscoBfdSessDesiredMinTxInterval</i>	(Optional)
<i>ciscoBfdSessReqMinRxInterval</i>	(Optional)
<i>ciscoBfdSessReqMinEchoRxInterval</i>	(Optional)
<i>ciscoBfdSessDetectMult</i>	(Optional)
<i>remoteBfdSessDesiredMinTxInterval</i>	(Optional)
<i>remoteBfdSessReqMinRxInterval</i>	(Optional)
<i>remoteBfdSessReqMinEchoRxInterval</i>	(Optional)
<i>remoteBfdSessDetectMult</i>	(Optional)

<i>ciscoBfdSessStorType</i>	(Optional) ciscoBfdSessStorType
<i>ciscoBfdSessRowStatus</i>	(Optional)
<i>ciscoBfdSessAuthPresFlag</i>	(Optional)
<i>ciscoBfdSessAuthenticationType</i>	(Optional) ciscoBfdSessAuthenticationType
<i>ciscoBfdSessVersionNumber</i>	(Optional)
<i>ciscoBfdSessType</i>	(Optional) ciscoBfdSessType
<i>ciscoBfdSessInterface</i>	(Optional)
<i>ciscoBfdSessPerfPktIn</i>	(Optional)
<i>ciscoBfdSessPerfPktOut</i>	(Optional)
<i>ciscoBfdSessUpTime</i>	(Optional)
<i>ciscoBfdSessPerfLastSessDownTime</i>	(Optional)
<i>ciscoBfdSessPerfLastCommLostDiag</i>	(Optional)
<i>ciscoBfdSessPerfSessUpCount</i>	(Optional)
<i>ciscoBfdSessPerfDiscTime</i>	(Optional)
<i>ciscoBfdSessPerfPktInHC</i>	(Optional)
<i>ciscoBfdSessPerfPktOutHC</i>	(Optional)
<i>effasyncdt</i>	(Optional)
<i>effechodt</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } policy statistics { { redistribute [ { { eigrp | isis | ospf | rip } <tag> } | static | direct | amt
| lisp | hmm ] } | { neighbor <neighbor-id> [ default-originate | { route-map | filter-list | prefix-list } { in | out
} ] } | { dampening } | { network { <ip-addr> mask <ip-mask> | <ip-prefix> } } | { aggregate-address {
<ip-addr> <ip-mask> | <ip-prefix> } { suppress-map | advertise-map } } } | vpnv4 unicast policy statistics {
neighbor <neighbor-id> [ { route-map | filter-list | prefix-list } { in | out } ] } | ipv6 { unicast | multicast }
policy statistics { { redistribute [ { { eigrp | isis | ospfv3 | rip } <tag> } | static | direct | amt | lisp | hmm ] } |
{ neighbor { <neighbor-id> | <ipv6-neighbor-id> } [ default-originate | { route-map | filter-list | prefix-list }
{ in | out } ] } | { dampening } | { network <ipv6-prefix> } | { aggregate-address <ipv6-prefix> { suppress-map
| advertise-map } } } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-polstats> [ <rpm-handle-count> ] [ { TABLE_rmap <name> <action>
<seqnum> [ { TABLE_cmd <command> <comparecount> <matchcount> } ] } ] [ <totalacceptcount> ] [
<totalrejectcount> ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
policy	Display policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	(Optional) ISO IS-IS
ospf	(Optional) Open Shortest Path First
ospfv3	(Optional) Open Shortest Path First v3
rip	(Optional) Routing Information Protocol

eigrp	(Optional) Enhanced Interior Gateway Protocol
static	(Optional) Static routes
direct	(Optional) Directly connected
amt	(Optional) AMT anycast prefix
lisp	(Optional) LISP EID-prefixes in the non-default VRF
hmm	(Optional) HMM prefix
<i>tag</i>	(Optional) Source protocol tag
neighbor	Show neighbor specific counters
<i>neighbor-id</i>	Neighbor IPv4 address
route-map	(Optional) Neighbor route-map
prefix-list	(Optional) Neighbor prefix-list
filter-list	(Optional) Neighbor filter-list
out	(Optional) Outbound policy
in	(Optional) Inbound policy
default-originate	(Optional) Default-originate policy
dampening	Show dampening info
network	Configured IP prefix to advertise
mask	Configured mask of the IP prefix advertised
aggregate-address	Configured BGP aggregate prefixes
suppress-map	Statistics of suppress policy
advertise-map	Statistics of advertise policy
<i>ip-addr</i>	IP network advertised
<i>ip-mask</i>	Dotted 4-octet mask
<i>ip-prefix</i>	IP prefix in CIDR format
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-polstats</i>	(Optional)
<i>rpm-handle-count</i>	(Optional)
TABLE_rmap	(Optional)

<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seqnum</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>comparecount</i>	(Optional)
<i>matchcount</i>	(Optional)
<i>totalacceptcount</i>	(Optional)
<i>totalrejectcount</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4
labeled-unicast [ <ip-addr> [ <ip-mask> [ longer-prefixes ] ] | <ip-prefix> [ longer-prefixes ] | labels |
exported | imported ] | { ipv6 { unicast | multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast } [ <ipv6-prefix> [ longer-prefixes ] | labels | exported |
imported ] | { ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] [ <ip-addr> [ <ip-mask>
] | <ip-prefix> | labels | mdt-group <mdt-group> ] | { ipv4 | ipv6 } unicast [ injected-routes ] | link-state [
route-type <rt-type> | <ipv4-rt> | <ipv6-rt> ] | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2>
} ] [ { <ip-addr> [ <ip-mask> ] | <ip-prefix> } ] { ve-id <ve-id> block-offset <ve-bs> } ] | ipv4 mvpn [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v4src-addr> <v4grp-addr> <src-asn> | rp
<v4src-addr> <grp-v4prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v4prefix> ] ] | ipv6
mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v6src-addr> <v6grp-addr> <src-asn>
| rp <v6src-addr> <grp-v6prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v6prefix> ] ] |
l2vpn evpn [ route-type <rtype> | rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ route-type <rtype>
| <ipv4-rt> | <ipv6-rt> | <mac-address> ] | vni-id <vni-id> [ route-type <rtype> ] | <ipv4-rt> | <ipv6-rt> |
<mac-address> ] | all } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version>
<router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> { <ipnexthop> | <ipv6nexthop> } } {
<inlabel> <outlabel> <vpn> <hold_down> } | { <metric> <localpref> <weight> <aspath> <origin> } } } | {
[ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabeledrn> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop>
] <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> ] [ <inlabel> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappentalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid_flag> ] [ <psid_origsrgrb_len>
<psid_origsrgrb_flag> <psid_origsrgrb_base> <psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto
<advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ip-addr</i>	(Optional) Display one particular network from the BRIB in detail
<i>ip-mask</i>	(Optional) Mask for one particular prefix in the BRIB

<i>ip-prefix</i>	(Optional) Display one particular prefix from the BRIB in detail
longer-prefixes	(Optional) Display route and more specific routes
labels	(Optional) Display BGP labels for prefixes
exported	(Optional) Display only exported prefixes
imported	(Optional) Display only imported prefixes
injected-routes	(Optional) Display only injected prefixes
mdt-group	(Optional) Display prefixes with MDT group address
<i>mdt-group</i>	(Optional) MDT group address
rd	(Optional) Display information for a route distinguisher
ve-id	(Optional) VPLS VE ID
<i>ve-id</i>	(Optional) VPLS VE ID
route-type	(Optional) EVPN Route Type number
<i>rtype</i>	(Optional) EVPN route type number
vni-id	(Optional) EVPN VNI ID number
<i>vni_id</i>	(Optional) EVPN VNI ID number
<i>rt-type</i>	(Optional) Link-State route-type
<i>ipv4-rt</i>	(Optional) EVPN IPv4 address
<i>mac-address</i>	(Optional) MAC address
block-offset	(Optional) VPLS VE Block offset
<i>ve-bs</i>	(Optional) VPLS VE Block offset
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ip	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family

mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
join	(Optional) Display Multicast Join route
sa	(Optional) Display Multicast Source Active AD route
rp	(Optional) Display Multicast Group to RP route
<i>v4src-addr</i>	(Optional) Source IP Address
<i>src-asn</i>	(Optional) Source ASN
<i>v4grp-addr</i>	(Optional) Group IP Address
<i>grp-v4prefix</i>	(Optional) Group IP prefix
<i>pe-addr</i>	(Optional) PE IP Address
<i>rp-flags</i>	(Optional) Flags
<i>rp-priority</i>	(Optional) RP Priority
<i>hashlen</i>	(Optional) Hash mask length
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)

<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)

<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappentalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)

<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)

<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

community-list	Display routes matching the community-list
<i>commlist-name</i>	Name of community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>extcommlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
exact-match	(Optional) Exact match of the communities
<u>__readonly__</u>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)

<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)

<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)

<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)

<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } { rib-install | rib-uninstall | rib-pending } [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
rib-install	Routes installed in RIB
rib-uninstall	Routes not installed in RIB
rib-pending	Routes not acknowledged by RIB

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { { ip | ipv4 } {
unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpv4 unicast [
rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4>
| <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4
mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast } nexthop <ipnexthop>
| { ipv6 { unicast | multicast } | vpv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] |
ipv6 labeled-unicast | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } nexthop
<ipv6nexthop> } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> { <ipnexthop> | <ipv6nexthop> } { {
<inlabel> <outlabel> <vpn> <hold_down> } | { <metric> <localpref> <weight> <aspath> <origin> } } } } {
[ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabeledrn> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop>
] <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> ] [ <inlabel> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid_flag> ] [ <psid_origsrGB_len>
<psid_origsrGB_flag> <psid_origsrGB_base> <psid_origsrGB_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto
<advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop	Display routes matching the nexthop
<i>ipnexthop</i>	Nexthop address
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family

ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)

<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_ <i>advertisedto</i>	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_ <i>scheduledto</i>	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_ <i>path</i>	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)

<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)

<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { { { ip | ipv4 } {
unicast | multicast } | vpv4 unicast | ipv4 mdt | link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn }
nextthop-database [ <ipnextthop> ] } } { ipv6 { unicast | multicast } | vpv6 unicast | ipv6 mvpn }
nextthop-database [ <ipv6nextthop> ] } } { all nextthop-database } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_nhvrfr <nhvrfr-name-out> TABLE_nhafi <nhafi>
TABLE_nhsafi <nhsafi> <af-name> <nhcriticaldelay> <nhnoncriticaldelay> [ { TABLE_nextthop {
<ipnextthop-out> | <ipv6nextthop-out> } <refcount> <igpmetric> <igptype> <igppref> [ { TABLE_attachedhops
{ <attachedhop> | <ipv6attachedhop> } <interface> [ { TABLE_labels <index> <label> } ] } ] <attached>
<local> <reachable> <labeled> <filtered> <resolvetime> { <ribroute> | <ipv6ribroute> } } { <pendingupdate>
| <pendingtime> } } <nextadvertise> <rnhepoch> [ <pendingrnhepoch> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
nextthop-database	Display nextthop database
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
mdt	Display BGP information for multicast distribution tree
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family

all	Display BGP information for all address families
<i>ipnexthop</i>	(Optional) Nexthop address
<i>__readonly__</i>	(Optional)
TABLE_nhvr	(Optional)
<i>nhvr-name-out</i>	(Optional)
TABLE_nhafi	(Optional)
<i>nhafi</i>	(Optional)
TABLE_nhsafi	(Optional)
<i>nhsafi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>nhcriticaldelay</i>	(Optional)
<i>nhnoncriticaldelay</i>	(Optional)
TABLE_nexthop	(Optional)
<i>ipnexthop-out</i>	(Optional)
<i>refcount</i>	(Optional)
<i>igpmetric</i>	(Optional)
<i>igptype</i>	(Optional)
<i>igppref</i>	(Optional)
TABLE_attachedhops	(Optional)
<i>attachedhop</i>	(Optional)
<i>interface</i>	(Optional)
TABLE_labels	(Optional)
<i>index</i>	(Optional)
<i>label</i>	(Optional)
<i>attached</i>	(Optional)
<i>local</i>	(Optional)
<i>reachable</i>	(Optional)
<i>labeled</i>	(Optional)
<i>filtered</i>	(Optional)

<i>resolvetime</i>	(Optional)
<i>pendingupdate</i>	(Optional)
<i>pendingtime</i>	(Optional)
<i>ribroute</i>	(Optional)
<i>nextadvertise</i>	(Optional)
<i>rnhepoch</i>	(Optional)
<i>pendingrnhepoch</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] | ipv6 { unicast | multicast }
flap-statistics [ <ipv6-prefix> ] | all flap-statistics } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ TABLE_rd [ <rd_val> ] [ <rd_vrf> [ <rd_vniid> ] ] [ <dampeningenabled> <historypaths>
<dampenedpaths> ] ] [ { TABLE_prefix [ <ipprefix> | <ipv6prefix> ] [ <status> ] [ <pathtype> ] [ <peer> |
<ipv6peer> ] [ <flapcount> ] [ <duration> ] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [
<best> ] } ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
<i>ip-prefix</i>	(Optional) Display flap statistics for one prefix
<i>ip-addr</i>	(Optional) Display flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)

<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>dampeningenabled</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6
unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn
vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } community {
<regexp-str> | { <comm-id> | <wellknown-id> } + [ exact-match ] } [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths>
<bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> { <ipnexthop> | <ipv6nexthop> } { <inlabel> <outlabel> <vpn> <hold_down> } | { <metric>
<localpref> <weight> <aspath> <origin> } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <existpath> ] [
<aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> }
<neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> ] [ <inlabel> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalf-life> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len>
<psid_v6sid_flag> ] [ <psid_origrsgb_len> <psid_origrsgb_flag> <psid_origrsgb_base> <psid_origrsgb_end>
] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] }
} ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family

vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
community	Display routes matching the BGP communities
<i>regexp-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)

<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)

<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)

<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)

<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp convergence

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] convergence [ detail
] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ <starttime>
<configdonetime> <juststarted> [ <initwaittime> ] [ <ldpconverged> ] [ <ulibconvergencesent> ] TABLE_vrf
<vrf-name-out> <bestpathtimeout> <configuredtimeout> <updatedelay> [ <firstpeerup> ] <timerrunning> [
<timerexpires> ] TABLE_afi <afi> TABLE_safi <safi> <af-name> <total_configured_peers>
<total_capable_peers> <firstbestpathsignalled> [ <firstbestpathsignalledtime> ] <firstbestpathdone> [
<firstbestpathdonetime> [ <lastbestpathsignalledtime> <lastbestpathdonetime> ] ] [ <riblicconvergencesent>
] [ <importtimerrunning> ] [ <importtimerexpires> ] [ { TABLE_rcvdpeers [ <peer> ] [ <ipv6peer> ] [
<signalledtimepeer> ] } ] [ { TABLE_notrcvdpeers [ <notpeer> ] [ <notipv6peer> ] [ <nokeepalive> ] [
<notsignalledtime> ] } ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
convergence	Display information about convergence
detail	(Optional) Display detailed information about convergence
<i>__readonly__</i>	(Optional)
<i>starttime</i>	(Optional)
<i>configdonetime</i>	(Optional)
<i>juststarted</i>	(Optional)
<i>initwaittime</i>	(Optional)
<i>ldpconverged</i>	(Optional)
<i>ulibconvergencesent</i>	(Optional)
TABLE_vrf	(Optional)
<i>total_configured_peers</i>	(Optional)
<i>total_capable_peers</i>	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>bestpathtimeout</i>	(Optional)
<i>updatedelay</i>	(Optional)

<i>firstpeerup</i>	(Optional)
<i>configuredtimeout</i>	(Optional)
<i>timerrunning</i>	(Optional)
<i>timerexpires</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>firstbestpathsignalled</i>	(Optional)
<i>firstbestpathsignalledtime</i>	(Optional)
<i>firstbestpathdone</i>	(Optional)
<i>firstbestpathdonetime</i>	(Optional)
<i>lastbestpathsignalledtime</i>	(Optional)
<i>lastbestpathdonetime</i>	(Optional)
<i>ribbibconvergencesent</i>	(Optional)
<i>importtimerrunning</i>	(Optional)
<i>importtimerexpires</i>	(Optional)
TABLE_rcvdpeers	(Optional)
<i>peer</i>	(Optional)
<i>signalledtimepeer</i>	(Optional)
TABLE_notrcvdpeers	(Optional)
<i>notpeer</i>	(Optional)
<i>nokeepalive</i>	(Optional)
<i>notsignalledtime</i>	(Optional)

Command Mode

- /exec

show bgp convergence private

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] convergence private  
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
convergence	Display information about convergence
private	Display private information about convergence

Command Mode

- /exec

ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)

<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)

<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregators</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)

<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)

<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp dampening flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6
unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn
vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening
flap-statistics [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> ] [
<rd_vrf> [ <rd_vniid> ] ] [ <dampeningenabled> <historypaths> <dampenedpaths> ] ] [ { TABLE_prefix [
<ipprefix> | <ipv6prefix> ] [ <status> ] [ <pathtype> ] [ <peer> | <ipv6peer> ] [ <flapcount> ] [ <duration>
] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [ <best> ] } ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
flap-statistics	Display flap statistics for routes
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family

link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional)
TABLE_afi	(Optional)
afi	(Optional)
TABLE_safi	(Optional)
safi	(Optional)
af-name	(Optional)
TABLE_rd	(Optional)
rd_val	(Optional)
rd_vrf	(Optional)
rd_vniid	(Optional)
dampeningenabled	(Optional)
historypaths	(Optional)
dampenedpaths	(Optional)
TABLE_prefix	(Optional)
ipprefix	(Optional)
status	(Optional)
best	(Optional)
pathtype	(Optional)
peer	(Optional)
flapcount	(Optional)

<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp dampening parameters

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6
unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn
vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening
parameters [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> ] [
<rd_vrf> ] [ <rd_vniid> ] [ <rpmname> ] [ TABLE_rpm <rpmindex> <rpmdamphalflife> <rpm dampsuppress>
<rpm dampreuse> <rpm dampsuppressesstime> <rpm dampmaxpenalty> ] [ <dampconfigured> <damp halflife>
<damp suppress> <damp reuse> <damp suppressesstime> <damp maxpenalty> ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
parameters	Display dampening parameters
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family

link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional) VRF RD
<i>rd_vniid</i>	(Optional)
TABLE_rpm	(Optional)
<i>rpmname</i>	(Optional)
<i>rpmindex</i>	(Optional)
<i>rpmdamphalflife</i>	(Optional)
<i>rpmdampsuppress</i>	(Optional)
<i>rpmdampreuse</i>	(Optional)
<i>rpmdampsuppresstime</i>	(Optional)
<i>rpmdampmaxpenalty</i>	(Optional)
<i>dampconfigured</i>	(Optional)
<i>damphalflife</i>	(Optional)

<i>dampsuppress</i>	(Optional)
<i>dampreuse</i>	(Optional)
<i>dampsuppresstime</i>	(Optional)
<i>dampmaxpenalty</i>	(Optional)

Command Mode

- /exec

show bgp default-info

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } default-info [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
ip	Display IP information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
default-info	Display information about default routes
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families

Command Mode

- /exec

show bgp event-history

```
show bgp [ internal ] event-history { <bgp-event-hist> | errors | msgs | detail } [ statistics ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
internal	(Optional) Commands for internal use
event-history	Show various event logs of BGP
<i>bgp-event-hist</i>	Show BGP event log
detail	Show detailed event logs
errors	Show error logs of BGP
msgs	Show various message logs of BGP
statistics	(Optional) Event history buffer statistics

Command Mode

- /exec

vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
<i>regexp-str</i>	Regular expression to match the extcommunities
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)

<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregadoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)

<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)

<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp l3vpn

```
show bgp l3vpn [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-rd> ] [ <vrf-state> ] [ <vrf-state-rsn> ] [
<vrf-pending-rd> ] [ { TABLE_af <af-id> [ <af-name> ] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [
<af-num-peers> ] [ <af-num-active-peers> ] [ <af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ]
[ <af-peer-aggregates> ] [ <af-export-rmap> ] [ <af-import-rmap> ] [ <af-retain-rt> ] [ TABLE_export_rt
<export-rt> ] [ TABLE_import_rt <import-rt> ] [ TABLE_evpn_export_rt <evpn-export-rt> ] [
TABLE_evpn_import_rt <evpn-import-rt> ] [ <af-label-mode> ] [ <af-aggregate-label> ] } ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
l3vpn	BGP l3vpn information
vrf	(Optional) Virtual Router Context
detail	(Optional) Detailed information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers

<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label

Command Mode

- /exec

show bgp neighbors

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast
| link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn | ipv6 mvpn | ipv4 labeled-unicast } neighbors [ { <neighbor-id>
| <ipv6-neighbor-id> | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id> } ] [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_neighbor { <neighbor> |
<ipv6neighbor> | <templatepeer> } [ <remoteas> ] [ <localas> ] <link> [ <index> ] [ <configpeer> ] [
<inherit-template> ] [ <inherit-session-template> ] [ { <prefix-parent> | <ipv6prefix-parent> } ] [ <description>
] [ <version> <remote-id> <state> <up> <elapsedtime> [ <restarttime> ] ] [ <sourceif> ] [ <connectedif> ] [
<connectedcheck> ] [ <lowmemexempt> ] [ <bfd> ] [ <ttlsecurity> ] [ <ttllimit> ] [ <password> ] [
<passiveonly> ] [ <localas-inactive> ] <remove-privateas> { { <lastread> <holdtime> <keepalivetime>
<lastwrite> [ <keepalive> ] <msgrecvd> <notificationsrcvd> <rcvbufbytes> <msgsent> <notificationssent>
<sentbytesoutstanding> <connsestablished> <connsdropped> [ <connattempts> ] } { <peerresettime>
<peerresetreason> <resettime> <resetreason> } | { <resettime> <resetreason> <peerresettime>
<peerresetreason> } } [ <capsnegotiated> <capmpadvertised> <caprefreshadvertised>
<capgrdynamicadvertised> [ <capmprecvd> <caprefreshrecvd> <capgrdynamicrecvd> ]
<capolddynamicadvertised> <capolddynamicrecvd> <caprradvertised> <caprrrecvd> <capolddrradvertised>
<capolddrrrecvd> <capas4advertised> <capas4recvd> [ { TABLE_af <af-afi> TABLE_saf <af-safi>
<af-advertised> <af-recvd> <af-name> } ] [ <capgradvertised> <capgrrecvd> ] [ { TABLE_graf <gr-afi>
TABLE_grsaf <gr-safi> <gr-af-name> <gr-adv> <gr-recv> <gr-fwd> } ] [ <grrestarttime> <grstaletime> ] [
<grrecvrestarttime> ] [ [ { TABLE_addpathscapaf <addpathscap-afi> TABLE_addpathscapsaf
<addpathscap-safi> <addpathscap-af-name> <addpathssendcap-adv> <addpathsrecvcap-adv>
<addpathssendcap-recv> <addpathsrecvcap-recv> } ] [ <capaddpathsadvertised> <capaddpathsrecvd> ] ]
<capextendednhadvertised> <capextendednhrecvd> [ { TABLE_capextendednhaf <capextendednh-afi>
TABLE_capextendednhsaf <capextendednh-safi> <capextendednh-af-name> } ] ] } [ <configholdtime>
<configkeepalivetime> ] } ] [ <grstate> <grexpiry> ] [ <firstkeepalive> ] [ <openssent> <opensrecvd>
<updatesent> <updatesrecvd> <keepalivesent> <keepaliverecvd> <rtrefreshsent> <rtrefreshrecvd>
<capabilitiesent> <capabilitiesrecvd> <bytessent> <bytesrecvd> ] [ [ { TABLE_peraf <per-afi> TABLE_persaf
<per-safi> <per-af-name> [ <tableversion> ] [ <neighborstableversion> ] [ <pfxrecvd> ] [ <pfxbytes> ] [
<pfxsent> ] [ <conditionmap> <advertisemap> <advertisemapstatus> ] <insoftreconfigallowed> [
<insoftreconfigallowedalways> ] [ <sendcommunity> ] [ <sendextcommunity> ] [ { <localnexthop> |
<ipv6localnexthop> } ] [ <thirdpartynexthop> ] [ <maxpfx> ] [ <maxpfx_threshold> ] [ <soo> ] [ <weight>
] [ <allowasin> ] <asoverride> <peerascheckdisabled> [ <vplssignalingprotocol> ] [ { TABLE_inpolicy
<inpolicynr> <inpolicytype> <inpolicyname> [ <inpolicyhandle> } ] ] [ { TABLE_outpolicy <outpolicynr>
<outpolicytype> <outpolicyname> [ <outpolicyhandle> } ] ] [ <rrconfigured> ] [ <defaultoriginate> ] [
<defaultoriginatormap> ] [ <defaultsent> ] [ <grpathssaved> ] [ <grEoRrecvd> ] [ <grEoRtime> ] [
<unsuppress-map> ] [ { TABLE_policy_template <preference> <inherit-policy-template> } ] [ TABLE_vrf
[ <vrf-name> ] [ TABLE_peer_template <inheritingpeer> ] ] ] ] [ <threadid> ] [ <passivethreadid>
<passivefd> ] [ { <localaddr> | <ipv6localaddr> } <localport> { <remoteaddr> | <ipv6remoteaddr> }
<remoteport> <fd> ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name

<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	(Optional) Display details for a prefix peering
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
<i>__readonly__</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor</i>	(Optional)
<i>templatepeer</i>	(Optional)
<i>remotear</i>	(Optional)
<i>localas</i>	(Optional)
<i>link</i>	(Optional)
<i>index</i>	(Optional)
<i>configpeer</i>	(Optional)
<i>inherit-template</i>	(Optional)

<i>inherit-session-template</i>	(Optional)
<i>prefix-parent</i>	(Optional)
<i>description</i>	(Optional)
<i>version</i>	(Optional)
<i>remote-id</i>	(Optional)
<i>state</i>	(Optional)
<i>up</i>	(Optional)
<i>elapsedtime</i>	(Optional)
<i>restarttime</i>	(Optional)
<i>sourceif</i>	(Optional)
<i>connectedif</i>	(Optional)
<i>connectedcheck</i>	(Optional)
<i>lowmemexempt</i>	(Optional)
<i>bfd</i>	(Optional)
<i>ttlsecurity</i>	(Optional)
<i>tllimit</i>	(Optional)
<i>localas-inactive</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>password</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>lastread</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalivetime</i>	(Optional)
<i>lastwrite</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>notificationsrcvd</i>	(Optional)
<i>rcvbufbytes</i>	(Optional)
<i>msgsent</i>	(Optional)

<i>notificationssent</i>	(Optional)
<i>sentbytesoutstanding</i>	(Optional)
<i>connsestablished</i>	(Optional)
<i>connsdropped</i>	(Optional)
<i>connattempts</i>	(Optional)
<i>peerresetime</i>	(Optional)
<i>peerresetreason</i>	(Optional)
<i>resetime</i>	(Optional)
<i>resetreason</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
<i>grstate</i>	(Optional)
<i>gexpiry</i>	(Optional)
<i>firstkeepalive</i>	(Optional)
<i>openssent</i>	(Optional)
<i>opensrcvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updatesrcvd</i>	(Optional)
<i>keepalivesent</i>	(Optional)
<i>keepaliverecvd</i>	(Optional)
<i>rtrefreshsent</i>	(Optional)
<i>rtrefreshrcvd</i>	(Optional)
<i>capabilitiesent</i>	(Optional)
<i>capabilitiesrcvd</i>	(Optional)
<i>bytessent</i>	(Optional)
<i>bytesrcvd</i>	(Optional)
<i>threadid</i>	(Optional)
<i>fd</i>	(Optional)
<i>passivethreadid</i>	(Optional)

<i>passivefd</i>	(Optional)
<i>localaddr</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteaddr</i>	(Optional)
<i>remoteport</i>	(Optional)
<i>capsnegotiated</i>	(Optional)
<i>capmpadvertised</i>	(Optional)
<i>capgrdynamicadvertised</i>	(Optional)
<i>capaddpathsadvertised</i>	(Optional)
<i>caprefreshadvertised</i>	(Optional)
<i>capmprecvd</i>	(Optional)
<i>capgrdynamicrecvd</i>	(Optional)
<i>capaddpathsrecvd</i>	(Optional)
<i>caprefreshrecvd</i>	(Optional)
<i>capolddynamicadvertised</i>	(Optional)
<i>capolddynamicrecvd</i>	(Optional)
<i>caprradvertised</i>	(Optional)
<i>caprrrecvd</i>	(Optional)
<i>capoldrradvertised</i>	(Optional)
<i>capoldrrrecvd</i>	(Optional)
<i>capas4advertised</i>	(Optional)
<i>capas4recvd</i>	(Optional)
TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-advertised</i>	(Optional)
<i>af-recvd</i>	(Optional)
<i>af-name</i>	(Optional)

<i>capgradvertised</i>	(Optional)
<i>capgrrecvd</i>	(Optional)
TABLE_graf	(Optional)
<i>gr-afi</i>	(Optional)
TABLE_grsaf	(Optional)
<i>gr-safi</i>	(Optional)
<i>gr-af-name</i>	(Optional)
<i>gr-adv</i>	(Optional)
<i>gr-recv</i>	(Optional)
<i>gr-fwd</i>	(Optional)
<i>grrestarttime</i>	(Optional)
<i>grstaletime</i>	(Optional)
<i>grrecvdrestarttime</i>	(Optional)
TABLE_addpathscapaf	(Optional)
<i>addpathscap-afi</i>	(Optional)
TABLE_addpathscapsaf	(Optional)
<i>addpathscap-safi</i>	(Optional)
<i>addpathscap-af-name</i>	(Optional)
<i>addpathsendcap-adv</i>	(Optional)
<i>addpathsrecvcap-adv</i>	(Optional)
<i>addpathsendcap-recv</i>	(Optional)
<i>addpathsrecvcap-recv</i>	(Optional)
<i>capextendednhadvertised</i>	(Optional)
<i>capextendednhrecvd</i>	(Optional)
TABLE_capextendednhaf	(Optional)
<i>capextendednh-afi</i>	(Optional)
TABLE_capextendednhsaf	(Optional)
<i>capextendednh-safi</i>	(Optional)
<i>capextendednh-af-name</i>	(Optional)

TABLE_peraf	(Optional)
<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)
<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pxrecvd</i>	(Optional)
<i>pxbytes</i>	(Optional)
<i>pxsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)
<i>maxpx</i>	(Optional)
<i>maxpx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
<i>inpolicy</i>	(Optional)
<i>inpolicytype</i>	(Optional)
<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
<i>outpolicy</i>	(Optional)
<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)

<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatemap</i>	(Optional)
<i>defaultsent</i>	(Optional)
<i>grpathsaved</i>	(Optional)
<i>grEoRrecvd</i>	(Optional)
<i>grEoRtime</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)
<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vplssignalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)
TABLE_inpolicy	(Optional)
TABLE_outpolicy	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_peer_template	(Optional)
<i>inheritingpeer</i>	(Optional)

Command Mode

- /exec

show bgp neighbors

```
show bgp { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ ip | ipv4 ] {
unicast | multicast } | ipv6 { unicast | multicast } | all } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast
| l2vpn evpn | ipv4 labeled-unicast } neighbors { <neighbor-id> | <ipv6-neighbor-id> } { routes [ advertised
| received | dampened ] | advertised-routes | received-routes } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [
<on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhdwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> { <ipnexthop> | <ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } } { <metric>
<localpref> <weight> <aspath> <origin> } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabelednrh> ] [ <existpath> ] [
<aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nextthopmetric> { <neighbor> | <ipv6neighbor> }
<neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> ] [ <inlabel> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalflife> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len>
<psid_v6sid_flag> ] [ <psid_origrsrb_len> <psid_origrsrb_flag> <psid_origrsrb_base> <psid_origrsrb_end>
] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] }
} ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
labeled-unicast	Display BGP information for labeled-unicast address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family

multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
routes	Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
advertised-routes	Display all the routes advertised to this peer
received-routes	Display all the routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)

<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)

<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenaity</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)

<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp neighbors commands

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ip | ipv4 } { unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } commands [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ { TABLE_sesscmd <sessioncmd> <sessioncmdstatus> [ <sessioncmdtemplate> ] } ] [ TABLE_af <af-afi> TABLE_saf <af-safi> <af-name> [ { TABLE_polecmd <policycmd> <policycmdstatus> [ <policycmdtemplate> ] } ] ] ] ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>neighbor-id</i>	Display one particular BGP neighbor
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
neighbors	Display all configured BGP neighbors
commands	Display details on commands
__readonly__	(Optional)
TABLE_sesscmd	(Optional)
<i>sessioncmd</i>	(Optional)
<i>sessioncmdstatus</i>	(Optional)

<i>sessioncmdtemplate</i>	(Optional)
TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_polcmd	(Optional)
<i>polycmd</i>	(Optional)
<i>polycmdstatus</i>	(Optional)
<i>polycmdtemplate</i>	(Optional)

Command Mode

- /exec

show bgp neighbors flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } neighbors { <neighbor-id> | <ipv6-neighbor-id> }
flap-statistics [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> ] [
<rd_vrf> [ <rd_vniid> ] ] [ <dampeningenabled> <historypaths> <dampenedpaths> ] ] [ { TABLE_prefix [
<ipprefix> | <ipv6prefix> ] [ <status> ] [ <pathtype> ] [ <peer> | <ipv6peer> ] [ <flapcount> ] [ <duration>
] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [ <best> } } ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
flap-statistics	Display flap statistics for routes received from this peer
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>dampeningenabled</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp neighbors paths

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast
| l2vpn evpn | ipv4 labeled-unicast } neighbors { <neighbor-id> | <ipv6-neighbor-id> } paths [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_id <id> <hashvalue> <refcount> <metric>
<aspath> ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
paths	Display AS paths learned from this peer
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)

TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)

Command Mode

- /exec

show bgp paths

```
show [ ip ] bgp paths [ __readonly__ TABLE_id <id> <hashvalue> <refcount> <metric> <aspath> <origin> ]
```

Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
paths	Display Path information
__readonly__	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)

Command Mode

- /exec

<i>ttlsecurity</i>	(Optional)
<i>tllimit</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>password</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
TABLE_peraf	(Optional)
<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)
<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pxrecvd</i>	(Optional)
<i>pxbytes</i>	(Optional)
<i>pxsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)
<i>maxpx</i>	(Optional)
<i>maxpx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
<i>inpolicynr</i>	(Optional)
<i>inpolicytype</i>	(Optional)

<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
<i>outpolicynr</i>	(Optional)
<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)
<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatermap</i>	(Optional)
<i>defaultsent</i>	(Optional)
<i>grpathssaved</i>	(Optional)
<i>grEoRrecvd</i>	(Optional)
<i>grEoRtime</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)
<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vplssignalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)
TABLE_inpolicy	(Optional)
TABLE_outpolicy	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_peer_template	(Optional)

<i>inheritingpeer</i>	(Optional)
-----------------------	------------

Command Mode

- /exec

show bgp peer

```
show [ ip ] bgp { peer-session [ <session-template-name> ] | peer-policy [ <policy-template-name> ] } [
__readonly__ TABLE_template <template> <present> [ { TABLE_command <command> [ <polarity> ] [
<updatesource> ] [ <description> ] [ <multihop> ] [ <holdtime> ] [ <keepalive> ] [ <routemapin> ] [
<routemapout> ] [ <filterlistin> ] [ <filterlistout> ] [ <prefixlistin> ] [ <prefixlistout> ] [ <maxprefixlimit> ]
[ <defaultorigin> ] } ] [ { TABLE_vrf <vrf-name> { TABLE_peer <inheritingpeer> } } ] ] ]
```

Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-session	Display information about a peer-session
peer-policy	Display information about a peer-policy
<i>session-template-name</i>	(Optional) Peer-session name
<i>policy-template-name</i>	(Optional) Peer-policy name
<i>__readonly__</i>	(Optional)
TABLE_template	(Optional)
<i>template</i>	(Optional)
<i>present</i>	(Optional)
TABLE_command	(Optional)
<i>command</i>	(Optional)
<i>polarity</i>	(Optional)
<i>updatesource</i>	(Optional)
<i>description</i>	(Optional)
<i>multihop</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>routemapin</i>	(Optional)
<i>routemapout</i>	(Optional)
<i>filterlistin</i>	(Optional)
<i>filterlistout</i>	(Optional)

<i>prefixlistin</i>	(Optional)
<i>prefixlistout</i>	(Optional)
<i>maxprefixlimit</i>	(Optional)
<i>defaultorigin</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_peer	(Optional)
<i>inheritingpeer</i>	(Optional)

Command Mode

- /exec

show bgp prefix-list

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } } prefix-list { <prfxlist-name> | <test_pol_name> } [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf
<vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd
[ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [
<prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync>
<locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] {
TABLE_path <pathnr> { { <status> <best> <type> { <ipnexthop> | <ipv6nexthop> } } { <inlabel> <outlabel>
<vpn> <hold_down> } | { <metric> <localpref> <weight> <aspath> <origin> } } } | [ <policyincomplete>
<pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath>
<pathnolabeledrn> ] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric>
{ <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator>
<aggregatoras> ] [ <inlabel> ] [ { TABLE_community <community> } ] [ { TABLE_extcommunity
<extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime>
<flaps> <flaptime> <flapflags> <flapindex> <flaphalfife> <flapreuse> <flapsuppress> <flapmax> ] [
<con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx>
] [ <psid_v6sid_len> <psid_v6sid_flag> ] [ <psid_origrsgb_len> <psid_origrsgb_flag> <psid_origrsgb_base>
<psid_origrsgb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <mdt_grp_addr> ] ] } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ]
]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
<i>test_pol_name</i>	An existing test-list policy
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
__readonly__	(Optional)

TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)

<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)

<i>aggregator</i>	(Optional)
<i>aggregadoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)

<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp private

```
show bgp private [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { all_private
| session | ipc | rnh | lists | rpm-info [ route-map <rpm-name> { <ip-prefix> | <ipv6-prefix> } ] | attr [ {
<ip-prefix> } ] | rpm-attribute-cache | rpm-comm-attr-cache | virtual [ summary ] } [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
all_private	Show all info
session	Show session info
lists	Show BGP internal lists
route-map	(Optional) Show information for route-map
rpm-info	Show BGP policy outbound info
<i>ip-prefix</i>	(Optional) Show attribute for a prefix
<i>rpm-name</i>	(Optional) Route-map name
attr	Show attribute information
ipc	Show ipc information
rnh	Show recursive next hops
rpm-attribute-cache	Show rpm attribute cache statistics
rpm-comm-attr-cache	Show rpm community attribute cache statistics
summary	(Optional) Summary only
virtual	Virtualization related
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

show bgp private attr

```
show bgp private attr [ remote-nh ] [ [ [ ipv4 { unicast | multicast } <ip-prefix> ] ] [ ipv6 { unicast | multicast } <ipv6-prefix> ] ] [ detail ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
attr	Show BGP attributes
remote-nh	(Optional) Show Remote NH Attr
ipv4	(Optional) Display BGP information for IPv4 address family
ipv6	(Optional) Display BGP information for IPv6 address family
unicast	(Optional) Display BGP information for unicast address family
multicast	(Optional) Display BGP information for multicast address family
detail	(Optional) Show detailed info
<i>ip-prefix</i>	(Optional) Show attribute for a prefix

Command Mode

- /exec

show bgp private damp

```
show bgp private [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4
} { unicast | multicast } | ipv6 { unicast | multicast } | all } damp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
damp	Show dampening info

Command Mode

- /exec

show bgp process

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] process [ detail ] [
vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ <processid>
<protocolstartedreason> <protocoltag> <protocolstate> [ <isolatemode> ] <mmode> <memorystate> [
<malloccmemorystate> ] [ <platformmemorystate> ] [ <lowmemorytimer> ] [ <issu> ] <forwardingstatesaved>
<asformat> [ <fabricsoo> ] [ <srgbmin> <srgbmax> ] [ <epeconfiguredpeers> <epeactivepeers> ]
<attributeentries> <hwmattributeentries> <bytesused> <entriespendingdelete> <hwmentriespendingdelete>
<pathsperattribute> <aspathentries> <aspathbytes> ] TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-state>
] [ <vrf-state-rsn> ] [ <vrf-delete-pending> ] [ <vrf-vni-id> ] [ <vrf-vni-id-valid> ] [ <vrf-encap-type> ] [
<vrf-vtep-ip> ] [ <vrf-vtep-virtual-ip> ] [ <vrf-router-mac> ] [ <vrf-router-id> ] [ <vrf-cfgd-id> ] [ <vrf-local-as>
] [ <vrf-confed-id> ] [ <vrf-cluster-id> ] [ <vrf-reconnect-interval> ] [ <vrf-peers> ] [ <vrf-pending-peers> ]
[ <vrf-est-peers> ] [ <vrf-cfgd-max-as-limit> ] [ <vrf-max-as-limit> ] [ <vrf-rd> ] [ <vrf-pending-rd> ] {
TABLE_af <af-id> [ <af-name> ] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [ <af-num-peers> ] [
<af-num-active-peers> ] [ <af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ] [ <af-peer-aggregates>
] [ <af-export-rmap> ] [ <af-import-rmap> ] [ <af-retain-rt> ] [ { TABLE_redist <protocol> <route-map> }
] [ { TABLE_add_paths_selection <route-map> } ] [ TABLE_export_rt <export-rt> ] [ TABLE_import_rt
<import-rt> ] [ TABLE_evpn_export_rt <evpn-export-rt> ] [ TABLE_evpn_import_rt <evpn-import-rt> ] [
<af-label-mode> ] [ <af-aggregate-label> ] [ <importdefault_prefixlimit> <importdefault_prefixcount>
<importdefault_map> ] [ <exportdefault_prefixlimit> <exportdefault_prefixcount> <exportdefault_map> ] [
<af-rr> ] } ] }
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
process	BGP global information
detail	(Optional) Detailed information
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only
<i>processid</i>	(Optional)
<i>protocolstartedreason</i>	(Optional)
<i>protocoltag</i>	(Optional)
<i>protocolstate</i>	(Optional)
<i>isolatemode</i>	(Optional)
<i>mmode</i>	(Optional)
<i>memorystate</i>	(Optional)

<i>mallocmemorystate</i>	(Optional)
<i>platformmemorystate</i>	(Optional)
<i>lowmemorytimer</i>	(Optional)
<i>issu</i>	(Optional)
<i>forwardingstatesaved</i>	(Optional)
<i>asformat</i>	(Optional)
<i>attributeentries</i>	(Optional)
<i>fabricsoo</i>	(Optional)
<i>srgbmin</i>	(Optional)
<i>srgbmax</i>	(Optional)
<i>epeconfiguredpeers</i>	(Optional)
<i>epeactivepeers</i>	(Optional)
<i>hwmattributeentries</i>	(Optional)
<i>bytesused</i>	(Optional)
<i>entriespendingdelete</i>	(Optional)
<i>hwmentriespendingdelete</i>	(Optional)
<i>pathsperattribute</i>	(Optional)
<i>aspathentries</i>	(Optional)
<i>aspathbytes</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP

<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map

<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_redist	(Optional)
<i>protocol</i>	(Optional) Protocol
<i>route-map</i>	(Optional) Route Map
TABLE_add_paths_selection	(Optional)
<i>route-map</i>	(Optional) Route Map
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label
<i>importdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>importdefault_prefixcount</i>	(Optional) Current number of prefixes
<i>importdefault_map</i>	(Optional) Configured route-map
<i>exportdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>exportdefault_prefixcount</i>	(Optional) Current number of prefixes
<i>exportdefault_map</i>	(Optional) Configured route-map
<i>af-rr</i>	(Optional) Is a Route-reflector

Command Mode

- /exec

show bgp received-paths

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6
unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn
vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } received-paths
[ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ]
[ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> { <ipnexthop> | <ipv6nexthop> } } {
<inlabel> <outlabel> <vpn> <hold_down> } | { <metric> <localpref> <weight> <aspath> <origin> } } } | {
[ <policyincomplete> <pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit>
<pathmultipath> <pathnolabeledrn> ] [ <existpath> ] [ <aspath> <source> ] [ <ipnexthop> | <ipv6nexthop>
] <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight>
[ <aggregator> <aggregators> ] [ <inlabel> ] [ { TABLE_community <community> } ] [ {
TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappensity> <dampenedtime> <flaps> <flaptime> <flapflaps> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_v6sid_flag> ] [ <psid_origsrcb_len>
<psid_origsrcb_flag> <psid_origsrcb_base> <psid_origsrcb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] } } ] [ TABLE_advertisedto
<advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family

vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
private	(Optional) private
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)

<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)

<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)

<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp regexp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } regexp <regexp-str> [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion>
<totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [
<export-on-newlist> <export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path
<pathnr> { { <status> <best> <type> { <ipnexthop> | <ipv6nexthop> } } { <inlabel> <outlabel> <vpn>
<hold_down> } | { <metric> <localpref> <weight> <aspath> <origin> } } } | { [ <policyincomplete>
<pathvalid> <pathbest> <pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath>
<pathnolabeledrn> ] [ <existpath> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric>
{ <neighbor> | <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator>
<aggregatoras> ] [ <inlabel> ] [ { TABLE_community <community> } ] [ { TABLE_extcommunity
<extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime>
<flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse> <flapsuppress> <flapmax> ] [
<con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx>
] [ <psid_v6sid_len> <psid_v6sid_flag> ] [ <psid_origrsgb_len> <psid_origrsgb_flag> <psid_origrsgb_base>
<psid_origrsgb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <mdt_grp_addr> ] ] } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ]
] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
regexp	Display routes matching the AS path regular expression
<i>regexp-str</i>	Regular expression to match the AS paths
__readonly__	(Optional)

TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)

<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)

<i>aggregator</i>	(Optional)
<i>aggregadoras</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)

<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp self-originated

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ip | ipv4 } {
unicast | multicast } | ipv6 { unicast | multicast } | all } self-originated [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths>
<bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync> <locked> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> { <ipnexthop> | <ipv6nexthop> } { { <inlabel> <outlabel> <vpn> <hold_down> } | { <metric>
<localpref> <weight> <aspath> <origin> } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> ] [ <existpath> ] [
<aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> }
<neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> ] [ <inlabel> ] [ {
TABLE_community <community> } ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> {
TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags>
<flapindex> <flaphalflife> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd>
<con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len>
<psid_v6sid_flag> ] [ <psid_origrsgb_len> <psid_origrsgb_flag> <psid_origrsgb_base> <psid_origrsgb_end>
] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <mdt_grp_addr> ] ]
} } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
self-originated	Self originated routes
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)

TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)

<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>existpath</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)

<i>inlabel</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)

<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_v6sid_flag</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)

Command Mode

- /exec

show bgp sessions

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] sessions [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ <totalpeers>
<totalestablishedpeers> <localas> TABLE_vrf <vrf-name-out> <local-as> <vrfpeers> <vrfestablishedpeers>
<router-id> TABLE_neighbor <neighbor-id> <remotetas> <connectionsdropped> <lastflap> <lastread>
<lastwrite> <state> <localport> <remoteport> <notificationssent> <notificationsreceived> ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
sessions	Display session information for all peers
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>local-as</i>	(Optional)
<i>totalpeers</i>	(Optional)
<i>totalestablishedpeers</i>	(Optional)
<i>router-id</i>	(Optional)
<i>localas</i>	(Optional)
<i>vrfpeers</i>	(Optional)
<i>vrfestablishedpeers</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor-id</i>	(Optional)
<i>remotetas</i>	(Optional)
<i>connectionsdropped</i>	(Optional)
<i>lastflap</i>	(Optional)
<i>lastread</i>	(Optional)
<i>lastwrite</i>	(Optional)

<i>state</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteport</i>	(Optional)
<i>notificationssent</i>	(Optional)
<i>notificationsreceived</i>	(Optional)

Command Mode

- /exec

show bgp statistics

```
show bgp statistics [ __readonly__ <msgsent> <msgrcvd> <bytesent> <bytercvd> <opensent> <openrcvd>
<updatesent> <updaterecvd> <kasent> <karecvd> <notifsent> <notifrcvd> <rrefreshsent> <rrefreshrcvd>
<capsent> <caprcvd> <active_open_attempts> <passive_open_attempts> <bgp_io_open_loops>
<bgp_io_open_calls> <bgp_io_open_rcv_calls> <bgp_io_send_calls> <bgp_io_partial_send>
<bgp_send_bytes_min> <bgp_send_bytes_max> <bgp_send_min_fd_set_from_write_select>
<bgp_send_max_fd_set_from_write_select> <bgp_send_urgent_qsize_min> <bgp_send_urgent_qsize_max>
<bgp_send_urgent_qsize_enq> <bgp_send_normal_qsize_min> <bgp_send_normal_qsize_max>
<bgp_send_normal_qsize_enq> { TABLE_sosend_thread_load { <peers> <bytes> <max_send_time> } }
<bgp_sosend_thread_spurious_wakeup> <bgp_send_past_due_max_time> <bgp_send_past_due_max_count>
<bgp_io_rcv_calls> <bgp_io_write_calls> <bgp_select_call_errors> <bgp_io_write_loops>
<bgp_io_write_loop_yields> <bgp_io_read_calls> <bgp_io_read_loops> <bgp_io_read_loop_yields>
<bgp_io_process_nlri_yields> <bgp_io_process_withdraw_yields> <bgp_min_prefix_in_update_gen>
<bgp_max_prefix_in_update_gen> <bgp_update_send_pending> <bgp_update_buffer_not_avail>
<bgp_update_walk_suspend> <bgp_yield_in_updates> <bgp_yield_in_packing> <bgp_yield_to_fsm>
<bgp_yield_to_fsm_no_work> <bgp_yield_due_to_update_len> <bgp_no_sendbuf_for_peer>
<bgp_no_withdraw_buf_for_peer> <bgp_yield_while_update_peer> <bgp_yield_between_update_peer>
<bgp_yield_in_update_event> <signal_update_event> <work_queue_empty> <no_data_to_write>
<msg_queue_rcv_error> <socket_create> <socket_accept> <socket_close> <socket_create_retry>
<socket_create_failure> <socket_fd_close_session> <socket_fd_close_setup> <socket_fd_close_runs>
<socket_fd_close_total> <socket_fd_close_max> <socket_fd_close_curr> ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
statistics	BGP global statistics
<i>__readonly__</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>msgrcvd</i>	(Optional)
<i>bytesent</i>	(Optional)
<i>bytercvd</i>	(Optional)
<i>opensent</i>	(Optional)
<i>openrcvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updaterecvd</i>	(Optional)
<i>kasent</i>	(Optional)
<i>karecvd</i>	(Optional)

<i>notifsent</i>	(Optional)
<i>notifrecvd</i>	(Optional)
<i>rrefreshsent</i>	(Optional)
<i>rrefreshrecvd</i>	(Optional)
<i>capsent</i>	(Optional)
<i>caprecvd</i>	(Optional)
<i>active_open_attempts</i>	(Optional)
<i>passive_open_attempts</i>	(Optional)
<i>bgp_io_open_loops</i>	(Optional)
<i>bgp_io_open_calls</i>	(Optional)
<i>bgp_io_open_rcv_calls</i>	(Optional)
<i>bgp_io_send_calls</i>	(Optional)
<i>bgp_io_partial_send</i>	(Optional)
<i>bgp_send_bytes_min</i>	(Optional)
<i>bgp_send_bytes_max</i>	(Optional)
<i>bgp_send_min_fd_set_from_write_select</i>	(Optional)
<i>bgp_send_max_fd_set_from_write_select</i>	(Optional)
<i>bgp_send_urgent_qsize_min</i>	(Optional)
<i>bgp_send_urgent_qsize_max</i>	(Optional)
<i>bgp_send_urgent_qsize_enq</i>	(Optional)
<i>bgp_send_normal_qsize_min</i>	(Optional)
<i>bgp_send_normal_qsize_max</i>	(Optional)
<i>bgp_send_normal_qsize_enq</i>	(Optional)
TABLE_sosend_thread_load	(Optional)
<i>peers</i>	(Optional)
<i>bytes</i>	(Optional)
<i>max_send_time</i>	(Optional)
<i>bgp_sosend_thread_spurious_wakeup</i>	(Optional)
<i>bgp_send_past_due_max_time</i>	(Optional)

<i>bgp_send_past_due_max_count</i>	(Optional)
<i>bgp_io_rcv_calls</i>	(Optional)
<i>bgp_io_write_calls</i>	(Optional)
<i>bgp_select_call_errors</i>	(Optional)
<i>bgp_io_write_loops</i>	(Optional)
<i>bgp_io_write_loop_yields</i>	(Optional)
<i>bgp_io_read_calls</i>	(Optional)
<i>bgp_io_read_loops</i>	(Optional)
<i>bgp_io_read_loop_yields</i>	(Optional)
<i>bgp_io_process_nlri_yields</i>	(Optional)
<i>bgp_io_process_withdraw_yields</i>	(Optional)
<i>bgp_min_prefix_in_update_gen</i>	(Optional)
<i>bgp_max_prefix_in_update_gen</i>	(Optional)
<i>bgp_update_send_pending</i>	(Optional)
<i>bgp_update_buffer_not_avail</i>	(Optional)
<i>bgp_update_walk_suspend</i>	(Optional)
<i>bgp_yield_in_updates</i>	(Optional)
<i>bgp_yield_in_packing</i>	(Optional)
<i>bgp_yield_to_fsm</i>	(Optional)
<i>bgp_yield_to_fsm_no_work</i>	(Optional)
<i>bgp_yield_due_to_update_len</i>	(Optional)
<i>bgp_no_sendbuf_for_peer</i>	(Optional)
<i>bgp_no_withdraw_buf_for_peer</i>	(Optional)
<i>bgp_yield_while_update_peer</i>	(Optional)
<i>bgp_yield_between_update_peer</i>	(Optional)
<i>bgp_yield_in_update_event</i>	(Optional)
<i>signal_update_event</i>	(Optional)
<i>work_queue_empty</i>	(Optional)
<i>no_data_to_write</i>	(Optional)

<i>msg_queue_rcv_error</i>	(Optional)
<i>socket_create</i>	(Optional)
<i>socket_accept</i>	(Optional)
<i>socket_close</i>	(Optional)
<i>socket_create_retry</i>	(Optional)
<i>socket_create_failure</i>	(Optional)
<i>socket_fd_close_session</i>	(Optional)
<i>socket_fd_close_setup</i>	(Optional)
<i>socket_fd_close_runs</i>	(Optional)
<i>socket_fd_close_total</i>	(Optional)
<i>socket_fd_close_max</i>	(Optional)
<i>socket_fd_close_curr</i>	(Optional)

Command Mode

- /exec

<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers

<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)
<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)

<i>softreconfigcombopaths</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighbors</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)

Command Mode

- /exec

show bgp summary

```
show bgp { { ip | ipv4 } { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt | vpnv4 unicast | vpnv6
unicast | ipv6 labeled-unicast | link-state | l2vpn vpls | ipv4 mvpn | ipv6 mvpn | l2vpn evpn | ipv4 labeled-unicast
| all } summary [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-state> ] [ <vrf-state-rsn> ] [ <vrf-delete-pending> ] [
<vrf-vni-id> ] [ <vrf-vni-id-valid> ] [ <vrf-encap-type> ] [ <vrf-vtep-ip> ] [ <vrf-vtep-virtual-ip> ] [
<vrf-router-mac> ] [ <vrf-router-id> ] [ <vrf-cfgd-id> ] [ <vrf-local-as> ] [ <vrf-confed-id> ] [ <vrf-cluster-id>
] [ <vrf-reconnect-interval> ] [ <vrf-peers> ] [ <vrf-pending-peers> ] [ <vrf-est-peers> ] [
<vrf-cfgd-max-as-limit> ] [ <vrf-max-as-limit> ] [ <vrf-rd> ] [ <vrf-pending-rd> ] [ TABLE_af <af-id> [
<af-name> ] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [ <af-num-peers> ] [ <af-num-active-peers> ] [
<af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ] [ <af-peer-aggregates> ] [ <af-export-rmap> ]
[ <af-import-rmap> ] [ <af-retain-rt> ] TABLE_saf <safi> [ <af-name> ] [ <tableversion> ] [ <configuredpeers>
] [ <capablepeers> ] [ <totalnetworks> ] [ <totalpaths> ] [ <memoryused> ] [ <numberattrs> ] [ <bytesattrs>
] [ <numberpaths> ] [ <bytespaths> ] [ <numbercommunities> ] [ <bytescommunities> ] [ <numberclusterlist>
] [ <bytesclusterlist> ] [ <dampening> ] [ <historypaths> ] [ <dampenedpaths> ] [ <softreconfigrecvdpaths>
] [ <softreconfigidenticalpaths> ] [ <softreconfigcombopaths> ] [ <softreconfigfilteredrecvd> ] [
<softreconfigbytes> ] [ TABLE_neighbor <neighborid> [ <neighborversion> ] [ <neighboras> ] [ <msgrecvd>
] [ <msgsent> ] [ <neighbortableversion> ] [ <inq> ] [ <outq> ] [ <time> ] [ <state> ] [ <prefixreceived> ] ]
] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
summary	Display summarized information of BGP state
ip	Display BGP information for IPv4 address family
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
mdt	Display BGP information for multicast distribution tree

link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers

<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)

<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)
<i>softreconfigcombopath</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighboras</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)

Command Mode

- /exec

show boot

```
show boot [ __readonly__ { [ TABLE_bootvar_show <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_show	(Optional) Bootvar table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot auto-copy

```
show boot auto-copy [ __readonly__ { [ TABLE_auto_copy <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autcopy is turned on
__readonly__	(Optional)
TABLE_auto_copy	(Optional) Auto copy table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot auto-copy list

show boot auto-copy list [__readonly__ { [TABLE_auto_copy_list <Str1>] }]

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autcopy is turned on
list	Show the list of files to be auto-copied
__readonly__	(Optional)
TABLE_auto_copy_list	(Optional) Auto copy table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot current

```
show boot current [ __readonly__ { [ TABLE_bootvar_current <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
current	Show Current Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_current	(Optional) Bootvar current table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot module

```
show boot module [ [ <module> ] [ <s0> ] [ __readonly__ { [ TABLE_show_mod <Str1> ] } ] ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
module	Enter module to show config of all modules
<i>module</i>	(Optional) Enter module number to show config
<i>s0</i>	(Optional) Enter module keyword to show config
<code>__readonly__</code>	(Optional)
TABLE_show_mod	(Optional) Show Module table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot order

```
show boot order [ __readonly__ { [ TABLE_bootvar_order <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
order	Show Boot Order
__readonly__	(Optional)
TABLE_bootvar_order	(Optional) Boot order table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot sup-1

```
show boot sup-1 [ __readonly__ { [ TABLE_show_sup1 <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
sup-1	Enter sup-1 to show the 1st sup config
__readonly__	(Optional)
TABLE_show_sup1	(Optional) Show Sup-1 bootvar table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot sup-2

```
show boot sup-2 [ __readonly__ { [ TABLE_show_sup2 <Str1> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
sup-2	Enter sup-2 to show the 2nd sup config
__readonly__	(Optional)
TABLE_show_sup2	(Optional) Show Sup-22 bootvar table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show boot timings

show boot timings

Syntax Description

show	Show running system information
boot	show boot information
timings	show boot timings

Command Mode

- /exec

show boot variables

show boot variables [__readonly__ { [TABLE_boot_vars <Str1>] }]

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
variables	Display the list of boot variables
__readonly__	(Optional)
TABLE_boot_vars	(Optional) Show boot variables table
<i>Str1</i>	(Optional)

Command Mode

- /exec

show bootmode

```
show bootmode [ module <module> ] [ __readonly__ { TABLE_bootmode_info <mod_num> <bootmode>
} ]
```

Syntax Description

show	Show running system information
bootmode	show bootmode of the all linecard modules
module	(Optional) show bootmode of a specific linecard module
<i>module</i>	(Optional) please enter module number
<i>__readonly__</i>	(Optional)
TABLE_bootmode_info	(Optional)
<i>mod_num</i>	(Optional)
<i>bootmode</i>	(Optional)

Command Mode

- /exec

show buffers ip

```
show buffers ip [ { [ all <count> ] [ free <count> ] } ]
```

Syntax Description

show	Show running system information
buffers	Display detailed buffer statistics
ip	Display IP buffer information
all	(Optional) Dump buffers from ALL list
free	(Optional) Dump buffers from FREE list
<i>count</i>	(Optional) Number of buffers to dump

Command Mode

- /exec

show buffers ip