



X Show Commands

- [show xml server internal exec-info, on page 2](#)
- [show xml server internal history, on page 3](#)
- [show xml server logging configuration, on page 4](#)
- [show xml server status, on page 5](#)

show xml server internal exec-info

show xml server internal exec-info

```
show xml server internal exec-info { all | <session_id> } [ __readonly__ { <shmem_size><shmem_slot_size><nb_of_slots><free_slots> } [ { TABLE_session_slots <offset><session_id><start_time><ip_addr><state> } ] ]
```

Syntax Description

Syntax Description	
show	Show running system information
xml	xml agent
server	xml agent server
internal	Commands for internal use
exec-info	Information about xml sessions execution
all	all sessions
__readonly__	(Optional)
shmem_size	(Optional) shared memory size
shmem_slot_size	(Optional) shared memory slot size
nb_of_slots	(Optional) number of slots
free_slots	(Optional) number of free slots
TABLE_session_slots	(Optional) all xml sessions
offset	(Optional) offset on the shared memory segment
session_id	session number
start_time	(Optional) the xml session start time
ip_addr	(Optional) ip address of the session
state	(Optional) slot state

Command Mode

- /exec

show xml server internal history

```
show xml server internal history { commands | errors | all_history } [ session <session_id> ] [ __readonly__ { TABLE_history <session_id> <ip_addr> [ { TABLE_commands <cmdtime> <cmd> } ] [ { TABLE_errors <errtime> <err> } ] } ]
```

Syntax Description

Syntax Description	
show	Show running system information
xml	xml agent
server	xml agent server
internal	Commands for internal use
history	XML History
commands	XML commands processed
errors	Errors returned by XML commands
all_history	All history elements
session	(Optional) xml agent session
<i>session_id</i>	(Optional) xml agent session id
__readonly__	(Optional)
TABLE_history	(Optional) xml commands history
<i>ip_addr</i>	(Optional) ip address of the session
<i>session_id</i>	(Optional) xml agent session id
TABLE_commands	(Optional) all xml commands
<i>cmdtime</i>	(Optional) Time when command was issued
<i>cmd</i>	(Optional) CLI equivalent of an XML instance
TABLE_errors	(Optional) errors returned by xml commands
<i>errtime</i>	(Optional) Time when error was encountered
<i>err</i>	(Optional) CLI equivalent of an XML instance

Command Mode

- /exec

show xml server logging configuration

show xml server logging configuration

show xml server logging configuration

Syntax Description

Syntax Description		
show	Show running system information	
xml	Show xmagent logging configuration	
server	xml agent server	
logging	Show logging configuration and contents of logfile	
configuration	Show facility logging configuration	

Command Mode

- /exec

show xml server status

```
show xml server status [ __readonly__ { operational_status <o_status> } { maximum_sessions_configured <max_session> } [ { TABLE_sessions <session_id> <user_name> <start_time> <sap_id> <timeout> <time_remaining_to_timeout> <ip_addr> } ] ]
```

Syntax Description

Syntax Description	
show	to display xml agent information
xml	xml agent
server	xml agent server
status	display xml agent information
<u>__readonly__</u>	(Optional)
operational_status	(Optional) run-time info about xml
<i>o_status</i>	(Optional) operational status of the xml
maximum_sessions_configured	(Optional) the max session configured
<i>max_session</i>	(Optional) max sessions number
TABLE_sessions	(Optional) all xml sessions
<i>session_id</i>	(Optional) one xml session id
<i>user_name</i>	(Optional) the xml session user name
<i>start_time</i>	(Optional) the xml session start time
<i>sap_id</i>	(Optional) the mts sap id
<i>timeout</i>	(Optional) inactivity timeout value
<i>time_remaining_to_timeout</i>	(Optional) time remaining to timeout
<i>ip_addr</i>	(Optional) ip address of the session

Command Mode

- /exec

show xml server status