



## X Commands

---

- [xconnect, on page 2](#)
- [xml, on page 3](#)
- [xml, on page 4](#)
- [xml server max-session, on page 5](#)
- [xml server terminate session, on page 6](#)
- [xml server timeout, on page 7](#)
- [xml server validate, on page 8](#)
- [xmlin, on page 9](#)
- [xmlin, on page 10](#)
- [xmlin, on page 11](#)
- [xmlin, on page 12](#)
- [xmlout, on page 13](#)

# xconnect

xconnect | no xconnect

## Syntax Description

|          |                                      |
|----------|--------------------------------------|
| no       | Negate a command or set its defaults |
| xconnect | Enable cross connect on this VLAN    |

## Command Mode

- /exec/configure/vlan

# xml

| xml

## Syntax Description

|     |  |
|-----|--|
|     | Pipe command output to filter                        |
| xml | output in xml format (according to .xsd definitions) |

## Command Mode

- /output

# xml

| xml

## Syntax Description

|     |  |
|-----|--|
|     | Pipe command output to filter                        |
| xml | output in xml format (according to .xsd definitions) |

## Command Mode

- /output

# xml server max-session

[no] xml server max-session <number>

## Syntax Description

|               |  |
|---------------|--|
| no            | (Optional) Negate a command or set its defaults  |
| xml           | xml agent  |
| server        | xml agent server                                 |
| max-session   | configure maximum number of xml sessions allowed |
| <i>number</i> | number of the sessions                           |

## Command Mode

- /exec/configure

# xml server terminate session

xml server terminate session <session\_id>

## Syntax Description

|                   |                                     |
|-------------------|-------------------------------------|
| xml               | xml agent                           |
| server            | xml agent server                    |
| terminate         | command to terminate an XML session |
| session           | terminate an XML session            |
| <i>session_id</i> | sessions number                     |

## Command Mode

- /exec

# xml server timeout

[no] xml server timeout <value> [ <session\_id> ]

## Syntax Description

|                   |   |
|-------------------|---|
| no                | (Optional) Negate a command or set its defaults |
| xml               | xml agent                                       |
| server            | xml agent server                                |
| timeout           | configure xml agent session timeout             |
| <i>value</i>      | timeout in seconds                              |
| <i>session_id</i> | (Optional) xml agent session id                 |

## Command Mode

- /exec/configure

# xml server validate

[no] xml server validate { all | <session\_id> }

## Syntax Description

|                   |   |
|-------------------|---|
| no                | (Optional) Negate a command or set its defaults |
| xml               | xml agent                                       |
| server            | xml agent server                                |
| validate          | command to validate an XML session              |
| all               | all sessions                                    |
| <i>session_id</i> | session number                                  |

## Command Mode

- /exec/configure

# xmlin

| xmlin

## Syntax Description

|       |  |
|-------|--|
|       | Pipe command output to filter                  |
| xmlin | Convert CLI show commands to their XML formats |

## Command Mode

- /output

# xmlin

xmlin

## Syntax Description

|       |   |
|-------|---|
| xmlin | Convert CLI commands to their XML formats |
|-------|---|

## Command Mode

- /exec

# xmlin

| xmlin

## Syntax Description

|       |  |
|-------|--|
|       | Pipe command output to filter                  |
| xmlin | Convert CLI show commands to their XML formats |

## Command Mode

- /output

# xmlin

xmlin

## Syntax Description

|       |   |
|-------|---|
| xmlin | Convert CLI commands to their XML formats |
|-------|---|

## Command Mode

- /exec

# xmlout

| xmlout

## Syntax Description

|        |   |
|--------|---|
|        | Pipe command output to filter                               |
| xmlout | output in xml format (according to the latest .xsd version) |

## Command Mode

- /output

