



## INDEX

---

### Numerics

82628

1HPr\_Head1Pref

Document Conventions [1-x](#)

---

### A

automatic synchronization

conditions [4-10](#)

---

### D

documentation

additional publications [1-xi](#)

related documents [1-x](#)

---

### H

HA policy

description [2-3](#)

maximum retries [2-3](#)

minimum lifetime [2-3](#)

high availability

displaying status [4-10](#)

supervisor module switchover mechanism [4-5](#)

switchover characteristics [4-5](#)

---

### I

internal switch states

description [4-11](#)

ISSU

steps [5-2](#)

---

### L

licenses

ISSU [5-2](#)

service-level HA [2-2](#)

Smart Call Home [4-2](#)

system-level HA [4-2](#)

VDC [4-2](#)

---

### M

maximum retries. See HA policy

message and transaction service. See MTS

minimum lifetime. See HA policy

MTS

description [2-3](#)

---

### P

persistent storage service. See PSS

policy. See HA policy

processes

restartability [2-3](#)

PSS

description [2-2](#)

global and local synchronization [2-3](#)

private and shared [2-3](#)

---

### R

redundancy states

***Send document comments to [nexus7k-docfeedback@cisco.com](mailto:nexus7k-docfeedback@cisco.com)***

value descriptions [4-10](#)

related documents [1-xi](#)

restart

stateful, description [2-4](#)

stateless, description [2-5](#)

within a VDC [2-6](#)

---

## S

services

restartability [2-3](#)

software upgrades

disruptive [5-2](#)

stateful restart

description [2-4](#)

stateless restart

description [2-5](#)

supervisor modules

active state [4-11](#)

manual switchovers [4-6](#)

replacing active supervisor [4-8](#)

replacing standby supervisor [4-9](#)

standby state [4-11](#)

state descriptions [4-11](#)

switchover mechanisms [4-5](#)

switchovers

characteristics [4-5](#)

failures [4-6](#)

guidelines [4-6](#)

manually initiating [4-6](#)

System Manager [2-2](#)

description [2-2](#)

---

## V

VDC

restart [2-6](#)

system-level HA [4-11](#)