



Uninstalling Cisco MDS NX-OS and DCNM-SAN

This chapter describes about installing Cisco DCNM-SAN components and contains the following section:

- [Uninstalling the Management Software, page 1-1](#)

Uninstalling the Management Software

To uninstall the Cisco DCNM-SAN applications on a Microsoft Windows PC, follow these steps:

Detailed Steps

Step 1 Close all running instances of Cisco DCNM-SAN and Device Manager.

Step 2 Select **Start > Programs > Cisco DCNM Server > Uninstall_DCNM**.

Alternatively, you can run the following executable file:

```
INSTALL_DIR\dcn\dcnm\Uninstall_DCNM\Uninstall_DCNM.exe
```

where the default *INSTALL_DIR* value is C:\Program Files\Cisco Systems.

Step 3 Click **Uninstall**.

Step 4 Click **Done**.



Note When you uninstall Cisco DCNM-SAN Server, only Cisco DCNM-SAN client is removed. Jboss and the database, either PostgreSQL or Oracle, are not removed because they might be shared with other applications such as Cisco DCNM-SAN.



Note If you have installed Cisco DCNM-SAN or Device Manager on Windows Vista, you may see the application shortcuts on your desktop even after uninstalling the application. To remove the shortcuts, you need to refresh the desktop.

Send document comments to dcnm-docfeedback@cisco.com



Note If the DCNM-SAN Client fails to uninstall with an error message, you may need to remove the DCNM-SAN Client from cache using Java Cache Viewer. To remove DCNM-SAN Client from cache, select Start > Run and enter javaws -viewer. Select DCNM-SAN Client in the java cache viewer and click delete.



Note For older installations, delete the .cisco_mds9000 folder. Manually delete all desktop icons and program menu items.

On a Windows PC, this folder is created under the Documents and Settings folder (for example, d:\Documents and Settings\Administrator\.cisco_mds9000 if you had installed it as user Administrator). On a UNIX machine, the default installation folder is /usr/bin.

To uninstall the DCNM-SAN applications on a UNIX machine, use the Uninstall_DCNM script, as follows:

```
sh Uninstall_DCNM
```

You can find this script in your home folder or the folder that you specified when setting up the link folder during your installation of Cisco DCNM-SAN.



Note For all releases starting with Release 2.x, run the shell script \$HOME/cisco_mds9000/Uninstall.sh or /usr/local/cisco_mds9000/uninstall.sh, depending on where DCNM-SAN was installed. You can find this script in your home folder or the folder that you specified when setting up the link folder during your installation of Cisco DCNM-SAN.



Note For all releases starting with Release 1.3(1), run the shell script \$HOME/.cisco_mds9000/Uninstall.sh or /usr/local/.cisco_mds9000/uninstall.sh, depending on where DCNM-SAN was installed.
For earlier installations, delete the \$HOME/.cisco_mds9000 folder.



Note To uninstall DCNM-SAN Federated Server, on a windows machine, run the batch file \$TOPDIR/Uninstall.bat on each server node.