



New and Changed Information

- [New and Changed Information](#), page 1

New and Changed Information

The table below summarizes the new and changed features for this document and shows the releases in which each feature is supported. Your software release might not support all the features in this document. For the latest caveats and feature information, see the Bug Search Tool at <https://tools.cisco.com/bugsearch/> and the release notes for your software release.

Table 1: New and Changed ITD Features

Feature	Description	Changed in Release
Include ACL	Introduced this feature.	7.3(0)D1(1)
Optimized Node Insertion/Removal	Introduced this feature.	7.3(0)D1(1)
Destination NAT	Introduced this feature.	7.2(1)D1(1)
Multiple Device-Groups Within an ITD Service	Introduced this feature.	7.2(1)D1(1)
Intelligent Traffic Director	Added the following enhancements: <ul style="list-style-type: none">• Per-node probe.• IPv4 control probe for IPv6 data nodes.• Exclude ACL to exclude traffic from redirection.	7.2(0)D1(1)

Feature	Description	Changed in Release
Intelligent Traffic Director	Added the following enhancements: <ul style="list-style-type: none">• Weighted load-balancing.• Node-level standby.• Layer 4 port load-balancing.• Sandwich mode node-state synchronization across two VDCs on the same device.• DNS probe.• Start/stop/clear ITD statistics collection.• VRF support for the ITD service and probes.	6.2(10)
Intelligent Traffic Director	Introduced this feature.	6.2(8)